



(L1)	<b>Plastic Laminite</b> Pattern: Wood grain Colour: Brown Oak
(L2)	<b>Plastic Laminite</b> Pattern: Small textured circle pattern Colour: Green/Beige
(L3)	<b>Plastic Laminite</b> Colour: Satin Brushed Aluminium
(L4)	<b>Plastic Laminite</b> Colour: Sculpted White
(L5)	<b>Plastic Laminite</b> Colour: Beige Granite
(F1)	<b>Window Film (Maple Leaf pattern)</b> Permanent Representative to provide EPS file for film design. Refer to 24/10/10 for design.
(F2)	<b>Window Film (Safety)</b> Note: Security film to be bonded to window frame. Indicates direction of "wood grain"

1. Contractor to ensure all surfaces above counter tops/work surface are sanded smooth to prevent harm to clothing.
2. Refer to Partition Plan on ID04 for plywood blocking location within partition cavity.
3. Countertops to be 19mm plywood, finished with plastic laminate, unless otherwise noted.
4. Cabinets to be 16mm high density particle board, finished with plastic laminate, unless otherwise noted.
5. Shelves to be 16mm high density particle board.
6. Interior surfaces of closed cabinets, drawers and adjustable shelves to be finished with standard white melamine.
7. It is the Contractor's responsibility to provide hardware connection to all equipment supplied/installed by Others, including any electrical and/or plumbing.
8. Refer to Mechanical Drawings for connection of plumbing fixtures and equipment.
9. Refer to Plan Details and Elevations for countertop material join/break locations.
10. Contractor to finish edge of tiles with brushed stainless steel square edge trim.  
Notes:
  - Thickness of trim to suit application
11. Open shelving to be finished with plastic laminate all exposed faces.
12. Additional blocking to be provided in partition cavity as required to support millwork.
13. Supply of equipment including: Refrigerators, Microwave Ovens, Coffee Machine, Photocopiers, Facsimile Machines and Printers, is by Departmental Representative.

P1	Paint - General (Vibhte) Colour: White Finish: Gloss level 3
P2	Paint - Accent (Light Gray) Colour: Gray Finish: Gloss level 3
P3	Paint - Accent (Blue) Colour: Blue Finish: Gloss level 3
P4	Paint - Doors (Dark Gray) Colour: Dark Gray Finish: Gloss level 6
P5	Paint - Ceiling (White) Colour: White Finish: Gloss level 1
P6	Paint - Corridor (Gray) Colour: Purple/Gray Finish: Gloss level 3
G1	Back Painted Glass (Corridor) Size: 12mm, low rise, tempered glass Colour: Back painted white
C1	Ceramic Tile Colour: Light Green Size: 254mm x 762mm Installation: Socked
C2	Ceramic Tile with Metal Finish Colour: Stainless steel Size: 13mm x 100mm Installation: Staggered
T4	Porcelain Tile (Corridor) Colour: Beige Size: 610mm x 610mm Installation: Staggered

1	Supply and install new water closet. Refer to Mechanical Drawings.
2	Supply and install new level faucet. Refer to Mechanical Drawings.
3	Supply and install new wall hung sink. Refer to Mechanical Drawings.
4	Supply and install new wall mounted toilet. Refer to Mechanical Drawings.
5	Supply and install new floor mounted urinal partition. Ambulatory stall door requirements as follows: Capable of being latched from the inside with a mechanism that is operable using a closed fist. - When the door is in an open position have a clear opening of at least 810mm for the ambulatory stall. - Provided with a spring type or gravity hinge in order for the door to close automatically. - Provided with a door pull on both sides of the door, near the latch side of the door, located at a height less than 900 mm and not more than 1100 mm A.F.F. - Curved ambulatory door width, grab bar reinforced panels. See dimension required.
6	Supply and install new stainless steel "L"-shaped grab bar. Length: 760mm long horizontal and vertical components Specification: Grab bar to be 35mm Min. - 40mm Max. dia. and have a fascia of 40mm clearance from partition. Finish: Slip resistant metal surface Provide reinforced partition to stall. Resistance load of at least 1.3KN applied vertically or horizontally.
7	Supply and install new stainless steel 600mm long grab bar. Length: 600mm Specification: Grab bar to be 35mm Min. - 40mm Max. dia. and have a fascia of 40mm clearance from partition. Finish: Slip resistant metal surface Provide reinforced partition to stall. Resistance load of at least 1.3KN applied vertically or horizontally.
8	Supply and install new toilet tissue dispenser. Mounting height: 600mm - 800mm A.F.F.
9	Supply and install new soap dispenser. Mounting height: 1100mm A.F.F.
10	Supply and install new surface mounted paper towel dispenser. Mounting height: 1200mm A.F.F.
11	Supply and install new surface mounted garbage disposal. Mounting height: 900mm A.F.F.
12	Supply and install surface mounted sanitary napkin disposal. Mounting height: 900mm A.F.F.
13	Supply and install new wall mounted coat hook. Colour: Brushed metal Mounting height: Mounted not more than at 1200mm A.F.F. on a side partition and projecting not more than 40mm from partition fascia.
14	Supply and install new mirror. Mounting height: 1000mm A.F.F.
15	Supply and install wall mounted shelf. Size: 200mm x 400mm Shelf to be located not more than 200mm above the top of the lavatory and not more than 100mm R.F. and project not more than 200mm from the wall.