



P1	Paint - General (White) Colour: White Finish: Gloss level 3
P2	Paint - Accent (Light Gray) Colour: Gray Finish: Gloss level 3
P3	Paint - Accent (Blue) Colour: Blue Finish: Gloss level 3
P4	Paint - Doors (Dark Gray) Colour: Dark Gray Finish: Gloss level 6
P5	Paint - Ceiling (White) Colour: White Finish: Gloss level 1
P6	Paint - Corridor (Gray) Colour: Purple/Gray Finish: Gloss level 3
G1	Back Painted Glass (Combo) Finish: 12mm, low iron, tempered glass Colour: Back painted white.
C1	Ceramic Tile Colour: Light Green Size: 254mm x 762mm Installation: Staggered
C2	Ceramic Tile with Mostle Finish Colour: Stainless steel Size: 15mm x 102mm Installation: Staggered
T4	Porcelain Tile (Corridor) Colour: Beige Size: 610mm x 610mm Installation: Staggered

L1	Plastic Laminate Pattern: Wood grain Colour: Brown Oak
L2	Plastic Laminate Pattern: Small textured circle pattern Colour: Green/Beige
L3	Plastic Laminate Colour: Satin Brushed Aluminium
L4	Plastic Laminate Colour: Scalloped White
L5	Plastic Laminate Colour: Beige Granite
F1	Window Film (Maple Leaf pattern) Environmental Representative to provide EPS file for film design. Refer to 24/10/10 for design.
F2	Window Film (<u>Safety</u>) Note: Security film to be bonded to window frame.

↖ Indicates direction of "wood grain"

1. Contractor to ensure all surfaces under plywood/work/face are sanded smooth to prevent harm to clothing.
2. Refer to Partition Plan on ID04 for plywood block location within partition cavity.
3. Countertops to be 19mm plywood, finished with plastic laminate, unless otherwise noted.
4. Cabinets to be 16mm high density particle board, finished with plastic laminate, unless otherwise noted.
5. Shelves to be 16mm high density particle board.
6. Interior surfaces of closed cabinets, drawers and adjustable shelves to be finished with standard white melamine.
7. It is the Contractor's responsibility to provide hardware connection to all equipment supplied/installed by Others, including any electrical and/or plumbing.
8. Refer to Mechanical Drawings for connection of plumbing fixtures and equipment.
9. Refer to Plan Details and Elevations for countertop material joint/seam locations.
10. Contractor to finish edge of tiles with brushed stainless steel square edge trim.
Notes:
 - Thickness of trim to suit application
11. Open shelving to be finished with plastic laminate all exposed faces.
12. Additional blocking to be provided in partition cavity as required to support millwork.
13. Supply of equipment including: Refrigerators, Microwave Ovens, Coffee Machines, Photocopiers, Facsimile Machines and Printers, is to be coordinated Representative.

- 1) Supply and install new lower cabinet. Refer to Mechanical Drawings.
- 2) Supply and install new lower closet. Refer to Mechanical Drawings.
- 3) Supply and install new wall hung sink. Refer to Mechanical Drawings.
- 4) Supply and install new wall mounted urinal. Refer to Mechanical Drawings.
- 5) Supply and install new floor mounted toilet partition.
 - Ambulatory stool door requirements as follows:
 - Capable of being latched from the inside with a mechanism that is operable using a closed fist.
 - When the door is in an open position have a clear opening of at least 810mm for the ambulatory stall.
 - Provided with a spring type or gravity hinge in order for the door to close automatically.
 - Provided with a door pull on both sides of the door, near the latch side of the door, located at a height not less than 900 mm and not more than 1100 mm A.F.F.
- 6) Custom: Ambulatory door with room grab bar reinforced panels.
 - Size dimension required.
- 7) Supply and install new stainless steel L-shaped grab bar.
 - Length: 760mm long horizontal and vertical components
 - Specification: Grab bar to be 35mm Min. - 40mm Max. dia. and have a fascia of 40mm clearance from partition.
 - Finish: Slip resistant metal surface
 - Provide reinforced partition to suit. Resistance load of at least 1.38kN applied vertically or horizontally.
- 8) Supply and install new stainless steel 600mm long grab bar.
 - Length: 600mm
 - Specification: Grab bar to be 35mm Min. - 40mm Max. dia. and have a fascia of 40mm clearance from partition.
 - Finish: Slip resistant metal surface
 - Provide reinforced partition to suit. Resistance load of at least 1.38kN applied vertically or horizontally.
- 9) Supply and install new toilet tissue dispenser. Mounting height: 600mm - 800mm A.F.F.
- 10) Supply and install new soap dispenser. Mounting height: 1100mm A.F.F.
- 11) Supply and install new surface mounted paper towel dispenser. Mounting height: 1200mm A.F.F.
- 12) Supply and install new surface mounted garbage disposal. Mounting height: 900mm A.F.F.
- 13) Supply and install surface mounted sanitary napkin dispenser. Mounting height: 900mm A.F.F.
- 14) Supply and install new wall mount coat hook.
 - Colour: Brushed metal
 - Mounting height: Mounted not more than at 1200mm A.F.F. on a side partition and projecting not more than 40mm from partition fascia.
- 15) Supply and install new mirror. Mounting height: 1000mm A.F.F.
- 16) Supply and install wall mounted shelf.
 - Size: 200mm x 400mm
 - Shelf to be located not more than 200mm above the top of the lavatory and not more than 1100mm A.F.F. and project not more than 200mm from the wall.