

# Addendum/Addenda

No./N° 2
-------------

Project Description / Description de projet  S77 laser Labs Chilled Water System Modifications		
Solicitation No./ N° de sollicitation  16-22099	Project No./N° de projet  4060	W.O. No./N° d'ordre de travail
Departmental Representative / représentant ministériel  Allan Smith	Date  2016 Nov 23	
<b>Notice:</b> This addendum shall form part of the tender documents and all conditions shall apply and be read in conjunction with the original plans and specifications.		<b>Nota:</b> Cet addenda fait partie intégrale des dossiers d'appel d'offres; toutes les conditions énoncées doivent être lues et appliquées en conjonction avec les plans et les devis originaux.

## BIDDER'S QUESTIONS

**Question:** No abatement report or specification issued for this tender, may we assume there is no abatement work included with this tender?

**Answer:** We do not expect abatement will be required for asbestos, or any other designated substances.

## GENERAL INFORMATION

1. Pages from a Designated Substance Survey by Oakhill Environmental, which pertain to the area of work, are attached to this addendum.
2. The mandatory site visit attendance sheets are attached to this addendum.

End / Fin

Page 1 of 1



NATIONAL RESEARCH COUNCIL CANADA  
100 SUSSEX DRIVE  
OTTAWA, ONTARIO  
K1A 0R6

---



**DESIGNATED SUBSTANCES SURVEY  
BUILDING S-77  
OTTAWA, ONTARIO**

Prepared by:



---

Distribution:

2 copies - National Research Council Canada

1 copy - Oakhill Environmental

August 2007

PR-06-039



**OAKHILL**  
ENVIRONMENTAL

**LEGEND**

- 1001 FUNCTIONAL SPACE #
- INACCESSIBLE AREA
- LIMITED ACCESS AREA
- ACM FLOOR TILE
- ACM DEBRIS
- ACM PIPE INSULATION: STEAM
- ACM PIPE INSULATION: CONDENSATE
- ACM PIPE INSULATION: HW HEATING
- ACM PIPE INSULATION: DOMESTIC CW
- ACM PIPE INSULATION: DOMESTIC HW
- ACM PIPE INSULATION: RIVER WATER
- ACM DUCT INSULATION
- ACM FITTING INSULATION: STEAM
- ACM FITTING INSULATION: CONDENSATE
- ACM FITTING INSULATION: HW HEATING
- ACM FITTING INSULATION: DOMESTIC CW
- ACM FITTING INSULATION: DOMESTIC HW
- ACM FITTING INSULATION: CHILLER
- ACM TRANSITE WALL PANEL
- ACM TRANSITE CEILING TILE

**NOTE:**  
ACM fitting insulation locations are shown only on systems where NON-ACM pipe insulation was found. ONLY ACM ELBOWS are shown. These systems may also have ACM on: t's, valves, ends, hangers, etc.

**CLIENT**

NATIONAL RESEARCH COUNCIL CANADA  
ADMINISTRATIVE SERVICES  
AND PROPERTY MANAGEMENT  
BUILDING M-19  
1200 MONTREAL RD.  
OTTAWA, ON, K1A 0R6

**PROJECT**

DESIGNATED SUBSTANCES SURVEY  
BUILDING S-77

**PROJECT NO.**

PR-06-39

**DATE**

AUGUST 2007

**SCALE**


NTS

**TITLE**

**SUB-BASEMENT  
ASBESTOS  
LOCATIONS**

**SHEET**

**SB-1**





Functional Space ID#	Location	Homo. Mat. No.	Material Description and Quantity	Response Measure
	& B161D B161L	26	Fireproofing on the ceiling. – 0.75 m <sup>2</sup>	3 Encap
SB27	Cafeteria Foyer & Hallway	05	9" x 9" Floor Tile on the floor. – 96 m <sup>2</sup>	O&M
SB28	Rm. B163	03	MagBlock Pipe Insulation on the steam system. – 11 LM	O&M
		02	Mud Joint Compound Fitting Insulation on the steam system. – 5 Units	O&M
		03	MagBlock Pipe Insulation on the condensate system. – 10 LM	O&M
		02	Mud Joint Compound Fitting Insulation on the condensate system. – 5 Units	O&M
		02	Mud Joint Compound Fitting Insulation on the condensate system. – 2 Units	2 Encap
		02	Mud Joint Compound Fitting Insulation on the condensate system. – 1 Unit	Removal
		02	Mud Joint Compound Fitting Insulation on the steam system. – 1 Unit	1 Encap
		03	MagBlock Pipe Insulation on the condensate system. – 0.2 LM	2 Encap
		03	MagBlock Pipe Insulation on the steam system. – 0.4 LM	3 Encap
		18	Mud Joint Compound Fitting Insulation on the domestic cold water system. – 7 Units	O&M
		17	Aircell Pipe Insulation on the hot water heating system. – 9 LM	O&M
		17	Aircell Pipe Insulation on the hot water heating system. – 1 LM	7 Encap
		17	ACM Debris (Aircell Pipe Insulation) on the duct system. – 0.25 m <sup>2</sup>	Clean-up
SB32	Rms. B121 & B121A including stairwell	10	Transite Panel on ceiling. – 31 m <sup>2</sup>	O&M
		10	Transite Panel on walls – 89 m <sup>2</sup>	O&M
		10	Transite Panel on wall. – 0.4 m <sup>2</sup>	4 Removals
		17	Aircell Pipe Insulation on the hot water heating system. – 4 LM	O&M
		02	Mud Joint Compound Fitting Insulation on the hot water heating system. – 1 Unit	O&M
		02	Mud Joint Compound Fitting Insulation on the hot water heating system. – 1 Unit	1 Encap
		18	Mud Joint Compound Fitting Insulation on the chiller system. – 5 Units	O&M
SB33	Rm. B40A	05	9" x 9" Floor Tile on the floor. – 14 m <sup>2</sup>	O&M
		18	Mud Joint Compound Fitting Insulation on the domestic cold water system. – 4 Units	O&M
SB34	Rm. B40B	05	9" x 9" Floor Tile on the floor. – 54 m <sup>2</sup>	O&M
SB36	Rm. B40H	05	9" x 9" Floor Tile on the floor. – 10 m <sup>2</sup>	O&M
SB37	Rm. B40J	05	9" x 9" Floor Tile on the floor. – 10 m <sup>2</sup>	O&M
SB38	Rm. B40K	05	9" x 9" Floor Tile on the floor. – 10 m <sup>2</sup>	O&M
		17	Aircell Pipe Insulation on the hot water heating system. – 5 LM	O&M
		02	Mud Joint Compound Fitting Insulation on the hot water heating system. – 2 Units	O&M
		17	Aircell Pipe Insulation on the hot water heating system. – 0.2 LM	2 Encap
SB39	Rm. B40M (Hallway)	05	9" x 9" Floor Tile on the floor. – 27 m <sup>2</sup>	O&M
		17	Aircell Pipe Insulation on the hot water heating system. – 1 LM	O&M
SB40	Rm. B40L	05	9" x 9" Floor Tile on the floor. – 20 m <sup>2</sup>	O&M
		17	Aircell Pipe Insulation on the hot water heating system. – 4 LM	O&M
		02	Mud Joint Compound Fitting Insulation on the hot water heating system. – 5 Units	O&M



<p><b>Building:</b> S-77</p> <p><b>Date:</b> May 9, 2007</p> <p><b>Job #:</b> PR-06-039</p>	<p><b>Notes:</b></p> <p>1) Samples S77-L1, S77-L2, S77-01A and S77-07 were collected in this area.</p> <p>2) All ACM's were observed to be in good condition.</p> <p>3) Mould was observed on the chiller pipe insulation in four locations.</p> <p>4) The only access above the solid ceiling was a damaged area (large hole in ceiling) in the south-east corner.</p> <p>Above the ceiling area, ACM's were observed in various locations on mechanical systems (piping). No assessment of these materials was conducted due to the limited access.</p>	<p><b>Functional Space (FS) #:</b> SB01</p> <p><b>FS Area:</b> Rms. B12, B24, B36 &amp; B38</p> <p><b>Inspector:</b> BM &amp; RT</p>
---	---	--

Building Materials				ACM Assessment										Report Reference		
Location	Homg. Material #	Material Description	System	ACM Y/N	Fri-able Y/N	ACM Type	Qty.	Condition			Access			Response / Comments	Dwg. #	Photo #
								G	F	P	A	B	C			
Floor	NA	Concrete	Floor	N	--	--	--	--	--	--	--	--	--	--	--	--
Walls	NA	Concrete	Wall	N	--	--	--	--	--	--	--	--	--	--	--	--
	NA	Brick	Wall	N	--	--	--	--	--	--	--	--	--	--	--	--
Ceiling	01	Plaster (cementitious)	Ceiling	N	--	--	--	--	--	--	--	--	--	--	--	--
Above ceiling	NA	Limited access	--	--	--	--	--	--	--	--	--	--	--	See notes	--	--
Other	03	MagBlock PI	HWH	Y	Y	25% Chrysotile 30% Amosite	3 LM	X	--	--	--	X	--	O & M	S-1	--
	NA	FG PI & FI	All	N	--	--	--	--	--	--	--	--	--	Newer Installations	--	--
	07	Thermal patch	Ceiling	N	--	--	--	--	--	--	--	--	--	--	--	--
	NA	Mould	Chiller	N	--	--	--	--	--	--	--	--	--	4 locations	S-3	M2, M5-M7

**Criteria for Access to an area containing ACM:**

A: All building occupants may have access to this area

B: Restricted to building staff only

C: Areas of the building behind walls or ceiling system

**Criteria for Condition of an ACM:**

G: ACM is in GOOD condition; No damage

F: ACM is in FAIR condition; Less than 2% damage

P: ACM is in POOR condition; Greater than 2% damage

MJC: Mud Joint Compound

PI: Pipe Insulation

FI: Fitting Insulation

FG: Fibreglass



<b>Building:</b> S-77  <b>Date:</b> May 29, 2007  <b>Job #:</b> PR-06-039	<b>Notes:</b>  1) No access above plaster ceiling. 2) All ACM's were observed to be in good condition below the plaster ceiling.	<b>Functional Space (FS) #:</b> SB33  <b>FS Area:</b> Rm. B40A  <b>Inspector:</b> BM & RT
---	---	---

Building Materials				ACM Assessment										Report Reference		
Location	Homg. Material #	Material Description	System	ACM Y/N	Fri-able Y/N	ACM Type	Qty.	Condition			Access			Response / Comments	Dwg. #	Photo #
								G	F	P	A	B	C			
Floor	NA	Terrazzo	Floor	N	--	--	--	--	--	--	--	--	--	--	--	--
	01	Plaster	Floor	N	--	--	--	--	--	--	--	--	--	--	--	--
	NA	Wood Panel	Floor	N	--	--	--	--	--	--	--	--	--	--	--	--
	05	9" x 9"FT	Floor	Y	N	2% Chrysotile	14 m <sup>2</sup>	X	--	--	--	X	--	O & M	S-1	--
Ceiling	01	Plaster	Ceiling	N	--	--	--	--	--	--	--	--	--	--	--	--
Above ceiling	NA	No access	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Other	18	MJC FI	DCW	Y	Y	40% Chrysotile	4 units	X	--	--	--	X	--	O & M	S-1	--
	NA	FG PI & FI	All	N	--	--	--	--	--	--	--	--	--	Newer Installation	--	--

**Criteria for Access to an area containing ACM:**  
*A:* All building occupants may have access to this area  
*B:* Restricted to building staff only  
*C:* Areas of the building behind walls or ceiling system

**Criteria for Condition of an ACM:**  
*G:* ACM is in GOOD condition; No damage  
*F:* ACM is in FAIR condition; Less than 2% damage  
*P:* ACM is in POOR condition; Greater than 2% damage

MJC: Mud Joint Compound  
 PI: Pipe Insulation  
 FI: Fitting Insulation  
 FG: Fibreglass



