



**RETURN BIDS TO:**  
**RETOURNER LES SOUMISSIONS À:**  
Public Works and Government Services / Travaux  
publics et services gouvernementaux  
Kingston Procurement  
Des Acquisitions Kingston  
86 Clarence Street, 2nd floor  
Kingston  
Ontario  
K7L 1X3  
Bid Fax: (613) 545-8067

**SOLICITATION AMENDMENT**  
**MODIFICATION DE L'INVITATION**

The referenced document is hereby revised; unless otherwise indicated, all other terms and conditions of the Solicitation remain the same.

Ce document est par la présente révisé; sauf indication contraire, les modalités de l'invitation demeurent les mêmes.

**Comments - Commentaires**

Address inquiries to the Contracting Authority at  
marta.porter@pwgsc-tpsgc.gc.ca

**Vendor/Firm Name and Address**

Raison sociale et adresse du  
fournisseur/de l'entrepreneur

**Issuing Office - Bureau de distribution**

Public Works and Government Services / Travaux  
publics et services gouvernementaux  
Kingston Procurement  
Des Acquisitions Kingston  
86 Clarence Street, 2nd floor  
Kingston  
Ontario  
K7L 1X3

<b>Title - Sujet</b> Vehicle Lift	
<b>Solicitation No. - N° de l'invitation</b> W3909-170001/A	<b>Amendment No. - N° modif.</b> 003
<b>Client Reference No. - N° de référence du client</b> W3909-170001	<b>Date</b> 2017-01-26
<b>GETS Reference No. - N° de référence de SEAG</b> PW-\$KIN-620-7086	
<b>File No. - N° de dossier</b> KIN-6-46161 (620)	<b>CCC No./N° CCC - FMS No./N° VME</b>
<b>Solicitation Closes - L'invitation prend fin</b> <b>at - à 02:00 PM</b> <b>on - le 2017-02-03</b>	
<b>Time Zone</b> Fuseau horaire Eastern Standard Time EST	
<b>F.O.B. - F.A.B.</b> Specified Herein - Précisé dans les présentes	
<b>Plant-Usine:</b> <input type="checkbox"/> <b>Destination:</b> <input type="checkbox"/> <b>Other-Autre:</b> <input checked="" type="checkbox"/>	
<b>Address Enquiries to: - Adresser toutes questions à:</b> Porter, Marta M.	<b>Buyer Id - Id de l'acheteur</b> kin620
<b>Telephone No. - N° de téléphone</b> (613) 483-6084 ( )	<b>FAX No. - N° de FAX</b> (613) 545-8067
<b>Destination - of Goods, Services, and Construction:</b> <b>Destination - des biens, services et construction:</b>	

Instructions: See Herein

Instructions: Voir aux présentes

<b>Delivery Required - Livraison exigée</b>	<b>Delivery Offered - Livraison proposée</b>
<b>Vendor/Firm Name and Address</b> Raison sociale et adresse du fournisseur/de l'entrepreneur	
<b>Telephone No. - N° de téléphone</b> <b>Facsimile No. - N° de télécopieur</b>	
<b>Name and title of person authorized to sign on behalf of Vendor/Firm</b> (type or print) <b>Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)</b>	
<b>Signature</b>	<b>Date</b>

**Amendment 003 – Vehicle Lift, is being raised for the following reason:**

- 1. Provide a response back from Public Works and Government Services Canada to questions received from bidders.**
- 

**Q1.** Under Annex “A” it states **4.3.1 Must be capable of lifting a minimum of 20,000lbs to a maximum of 30,000 lbs.** Our proposed alternative, has a capacity of 36,000 lbs, is this acceptable?

**A1.** Yes, 36,000 lbs is acceptable.

**Q2.** Under Annex “A” it states **4.4.1 Motors must be a minimum for 2HP, 1PH, 230V** Our proposed alternative, has a Motor rating: 4 HP or 3 kW (DC) per column lifting assembly and a Voltage rating: 110 VAC for Charging 12 VDC batteries , is this acceptable?

**A2.** Rechargeable batteries are acceptable.

**Q3.** Under Annex “A” it states **4.1.8 The runway must have an adjustable width between each ranging from 42 inches to 52 inches; and** Our lift has a non-adjustable distance of 45 inches, is this acceptable?

**A3.** 45” width runway is acceptable.

**Q4.** Our HDC36 Lift consists of four individual column style lifting assemblies connected to two runways/platforms. Lifting assemblies/columns shall be anchored to the ground and lift directly without the use of cables, chains, or mechanical screws. The hydraulic cylinders are not expose during movement to decrease the chances for damage. Is this an acceptable alternative?

**A4.** Yes, lift must be anchored to the ground & hydraulic cylinders for lift assemblies.

**Q5.** What is the heaviest vehicle to be used on the proposed lifts, please provide axle weights.

**A5.** Must be capable of supporting min 20,000 lbs overall. Axle weights of 10,000lbs each.

**Q6.** Is the runways a drive on – back off OR drive on - drive off design?

**A6.** Drive on - back off

**Refer: Annex “A” – Requirement, 4.0 Minimum Mandatory Technical Specifications**

**Delete: In its Entirety**

**Insert: Annex “A” – Requirement, 4.0 Minimum Mandatory Technical Specifications**

#### 4.1 DIMENSIONS

- 4.1.1 Overall length must be 350 inches to a maximum of 400 inches;
- 4.1.2 Overall width must be 144 inches to a maximum of 156 inches;
- 4.1.3 Length between posts must be 290 inches to a maximum of 320 inches;
- 4.1.4 Width between posts must be 130 inches to a maximum of 156 inches;
- 4.1.5 Height of posts including hydraulic cylinders must be 140 inches to a maximum of 180 inches;
- 4.1.6 Lift travel must be 66 inches to a maximum of 84 inches;
- 4.1.7 The runway dimensions must be a width of 24 inches to a maximum of 30 inches;
- 4.1.8 The runway must have a width between each runway of 47" +/- 5", and
- 4.1.9 The approach ramp length must be 40 inches to 60 inches.

#### 4.2 DESIGN

- 4.2.1 Must be a four corner post;
- 4.2.2 Must be installed above ground with one hydraulic cylinder per corner;
- 4.2.3 Must have an automatic locking system integrated into each column;
- 4.2.4 Must have a single point air release;
- 4.2.5 Air supply must be incorporated into runways;
- 4.2.6 Approach ramp must double as wheel stops during lift operations;
- 4.2.7 Must have hydraulic synchronising;
- 4.2.8 Must be equipped with level sensors; and
- 4.2.9 Must include two (2) minimum 10,000 lbs to a maximum of 20,000 lbs air/hydraulic rolling bridge jacks with safety locks in the raised position.

#### 4.3 CAPACITY

- 4.3.1 Must be capable of lifting a minimum of 20,000 lbs to a maximum of 36,000 lbs.

#### 4.4 ELECTRICAL POWER

- 4.4.1 Electric motors must be either 2HP, 1PH, 230V or 110V with a draw of less than 15AMP.

**ALL OTHER TERMS AND CONDITIONS OF THIS SOLICITATION REMAIN UNCHANGED.**

**If your tender has already been forwarded and you wish to revise same, this revision should be faxed and reach the bid receiving area before the closing date. The tender number and the closing date are to be shown on the first page of your fax.**