



RETURN BIDS TO:
RETOURNER LES SOUMISSIONS À:
Bid Receiving Public Works and Government
Services Canada/Réception des soumissions Travaux
publics et Services gouvernementaux Canada
Room 100,
167 Lombard Ave.
Winnipeg
Manitoba
R3B 0T6
Bid Fax: (204) 983-0338

SOLICITATION AMENDMENT

MODIFICATION DE L'INVITATION

The referenced document is hereby revised; unless otherwise indicated, all other terms and conditions of the Solicitation remain the same.

Ce document est par la présente révisé; sauf indication contraire, les modalités de l'invitation demeurent les mêmes.

Comments - Commentaires

Vendor/Firm Name and Address
Raison sociale et adresse du
fournisseur/de l'entrepreneur

Issuing Office - Bureau de distribution
Public Works and Government Services Canada -
Western Region
Room 100
167 Lombard Ave.
Winnipeg
Manitoba
R3B 0T6

Title - Sujet Commercial Kitchen Equipment	
Solicitation No. - N° de l'invitation A7100-163511/A	Amendment No. - N° modif. 003
Client Reference No. - N° de référence du client A7100-163511	Date 2017-02-21
GETS Reference No. - N° de référence de SEAG PW-\$WPG-016-10116	
File No. - N° de dossier WPG-6-39233 (016)	CCC No./N° CCC - FMS No./N° VME
Solicitation Closes - L'invitation prend fin at - à 02:00 PM on - le 2017-02-28	Time Zone Fuseau horaire Central Standard Time CST
F.O.B. - F.A.B. Plant-Usine: <input type="checkbox"/> Destination: <input checked="" type="checkbox"/> Other-Autre: <input type="checkbox"/>	
Address Enquiries to: - Adresser toutes questions à: Hall, Marlene	Buyer Id - Id de l'acheteur wpg016
Telephone No. - N° de téléphone (204) 230-0147 ()	FAX No. - N° de FAX (204) 983-7796
Destination - of Goods, Services, and Construction: Destination - des biens, services et construction: Wills Transfer Ltd. 3100 Swansea Crescent Ottawa, ON K1G 3W4 c/o Claudette Weedmark	

Instructions: See Herein

Instructions: Voir aux présentes

Delivery Required - Livraison exigée	Delivery Offered - Livraison proposée
Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur	
Telephone No. - N° de téléphone Facsimile No. - N° de télécopieur	
Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)	
Signature	Date

This **amendment # 003** is raised to modify **Solicitation # A7100-163511/A** as follows:

1) Closing date has been extended as follows:

**REVISED CLOSING DATE OF:
02:00 PM on February 28, 2017**

2) Compliance Matrix – MINIMUM MANDATORY PERFORMANCE SPECIFICATIONS

Delete: Delete in its entirety.
Insert: Replace with the following:

<p><u>Completion and submission of Mandatory Performance Specification is required to be considered responsive and for your offer to be given further consideration.</u></p> <p>a. Bidder must cross reference where in their technical offer, the performance specification is located.</p> <p>b. Provide the specification being offered which meets or exceeds <u>and cross-reference as to where the supporting documentation is found within your proposal</u>. If there is insufficient space in the table, assign SIR # (Supplementary Information Reference) and provide the appropriate details on a separate page in your offer. Where published supporting documentation is not available in the form of brochures, technical data sheets etc., prepare a written narrative complete with a detailed explanation of how its offer demonstrates compliance.</p>		
<p><u>All work and materials herein specified must meet and maintain minimum Canadian and Provincial certification(s) and approval(s) as applicable by Industry Standards.</u></p>		
Item	Specifications	Bidder Response: indicate how they meet the specifications addressed below/ cross-reference where this technical specification is indicated in their bid documentation
1	Platform cart	
1.1	Platform dimensions: 610 mm x 915 mm ± 25 mm (24" x 36" ± 1").	
1.2	Capacity: at least 725 kg (1600 lbs).	
1.3	Heavy duty aluminum platform truck with tread deck.	
1.4	One (1) handle at a height of 675 mm ± 25 mm (26.5" ± 1") from the base of the platform.	

1.5	Durable extruded corner sockets integrated with frame so handle fits tightly and securely.	
1.6	Full perimeter non-marking rubber bumper.	
1.7	Four (4) casters with brake option.	
2	Rack Dolly (Cart for basket)	
2.1	Dimensions: 595 mm W x 595 mm D x 310 mm H \pm 25 mm (23.38" x 23.38" x 12.13" \pm 1").	
2.2	Heavy-duty rack dolly for transporting tableware.	
2.3	Lightweight aluminum.	
2.4	Non marking corner bumpers.	
2.5	A tubular steel handle.	
2.6	Equipped with four (4) non marking, resilient thread, 125 mm \pm 13 mm (5" \pm 0.5") swivel casters	
2.7	Dollies are 330 mm \pm 25 mm (13" \pm 1") off the floor	
3	Utility Cart	
3.1	Dimensions: 595 mm W x 875 mm D x 900 mm H \pm 25 mm (23.5" x 34.38" x 35.5" \pm 1").	
3.2	Cart capacity: at least 180 kg (400 lbs).	
3.3	Three (3) antimicrobial shelves.	
3.4	Shelf dimensions: 510 mm W x 760 mm D \pm 25 mm (20" x 30" \pm 1").	
3.5	Chrome plated posts.	
3.6	Easy to grip handle.	
3.7	Corrosion proof, smooth surfaces.	
3.8	Unit conforms to NSF standards.	
4	Coffee Machine	
4.1	Dimensions: 245 mm W x 385 mm D x 400 mm H \pm 25 mm (9.7" x 15.2" x 15.8" \pm 1").	

4.2	Single serve automatic coffee machine.	
4.3	Use a pod system for coffee and tea.	
4.4	Plumbed water connection.	
4.5	Automatically dispose used pods after each brew, holding at least 20 in a bin.	
4.6	Brew servings of at least 473 ml \pm 30 ml (16 oz \pm 1 oz).	
4.7	Able to provide at least 295 ml \pm 30 ml (10 oz \pm 1 oz) of hot water.	
4.8	Electrical requirement 120 V	
5	Espresso Coffee Machine	
5.1	Dimensions: 420 mm W x 540 mm D x 640 mm H \pm 25 mm (16.5" x 20.5" x 25.2" \pm 1")	
5.2	Milk cooler with a capacity of at least 4000 ml \pm 60 ml (135 oz \pm 2 oz).	
5.3	Cup warmer for at least 65 cups.	
5.4	Programmable for at least 30 different products and a button panel with at least 12 buttons.	
5.5	Aerated coffee bean container.	
5.6	Powder dispenser for decaffeinated ground coffee.	
5.7	A chip card to store and load data and recipes.	
5.8	Brewing accelerator to improve efficiency.	
5.9	Under-counter disposal of coffee grounds.	
5.10	Electrical requirement 400 V	
6	Coffee Grinder	
6.1	Dimensions: 240 mm W x 455 mm D x 740 mm H \pm 25 mm (9.5" x 17.9" x 29.1" \pm 1")	

6.2	Two (2) front loading hoppers with a capacity of 2.75 kg ± 0.5 kg (6 lbs ± 1.1 lbs) each	
6.3	3 batch sizes per hopper.	
6.4	Removable hoppers to serve as storage containers when not in the grinder.	
6.5	Lid locks to prevent tampering.	
6.6	Electrical requirement 120 V	
7	Coffee Brewer	
7.1	Dimensions: 230 mm W x 470 mm D x 700 mm H ± 25 mm (9.0" x 18.5" x 27.6" ± 1")	
7.2	Capacity: minimum 100 cups per hour.	
7.3	Includes a hot water faucet (plumbed water connection).	
7.4	Pour over feature.	
7.5	Stainless steel internal components.	
7.6	Electrical requirement 120 V	
8	Double Coffee Thermos	
8.1	Dimensions: 730 mm H x 195 mm W x 430 mm D ± 25 mm (28.7" x 7.8" x 16.9" ± 1")	
8.2	Coffee thermos compatible with item 7 (Coffee Brewer).	
8.3	Two (2) 2.5 liter thermal servers each including base, glass and stainless steel lined. <ul style="list-style-type: none"> • Dimensions: 205 mm x 177 mm x 298 mm high. 	
8.4	Made of durable plastic.	
8.5	Drip trays to catch spills and keep serving areas clean.	
8.6	Double thermal server racks to hold the server.	
8.7	Two (2) thermal server boosters for the coffee brewer, item #7.	

9	Muffin Display	
9.1	Dimensions: 455 mm W x 405 mm D x 535 mm H \pm 25 mm (18" x 16" x 21" \pm 1").	
9.2	Black iron frame display with clear acrylic on each side and three (3) tiers.	
9.3	Curved front with three (3) hinged doors with black iron handle.	
9.4	To receive one 330 mm x 455 mm \pm 25 mm (13" x 18" \pm 1") clear acrylic tray per tier.	
9.5	Three (3) clear trays.	
10	Condiment Dispenser	
10.1	Dimensions: 100 mm W x 305 mm D x 265 mm H \pm 25 mm (4" x 12" x 10.5" \pm 1").	
10.2	Three (3) tier glass jar display.	
10.3	Black iron frame.	
10.4	Three (3) removable square clear glass jars.	
10.5	Jar dimensions: 100 mm W x 100 mm D \pm 13 mm (4" x 4" \pm 0.5").	
11	Cutlery Dispenser	
11.1	Dimensions: 180 mm W x 330 mm D x 330 mm H \pm 25 mm (7" x 13" x 13" \pm 1")	
11.2	Sloped black iron frame cylinder displays.	
11.3	Holds three (3) stainless steel perforated cylinders.	
11.4	Each cylinder is installed at three (3) different levels.	
12	Rotary Toaster	
12.1	Dimensions: 370 mm W x 580 mm D x 420 mm H \pm 25 mm (14.5" x 22.7" x 16.6" \pm 1").	

Solicitation No. - N° de l'invitation
A7100-163511/A
Client Ref. No. - N° de réf. du client
A7100-163511

Amd. No. - N° de la modif.
003
File No. - N° du dossier
WPG-6-39233

Buyer ID - Id de l'acheteur
wpg016
CCC No./N° CCC - FMS No./N° VME

12.2	Minimum 750 toasts per hour.	
12.3	Front or rear discharge.	
12.4	Stainless steel, vertical type.	
12.5	Conveyor type toaster with adjustable speeds.	
12.6	Two (2) heat zones each including two (2) heating elements.	
12.7	All controls on the front of the unit.	
12.8	Switch for toast or buns in a way to toast one (1) side of the product if wanted.	
12.9	A switch to run the elements and the conveyor.	
12.10	A thermostatic control to control the intensity of the heat.	
12.11	Removable stainless steel tray.	
12.12	80 mm \pm 13mm (3" \pm 0.5") opening height.	
12.13	Cool surface temperatures.	
12.14	Automatic power save mode.	
12.15	Electrical requirement 208 V	
13	Panini Grill	
13.1	Dimensions: 410 mm W x 380 mm D x 205 mm H \pm 25 mm (16.1" x 15" x 8" \pm 1").	
13.2	Single style Panini grill.	
13.3	Heavy duty ribbed cast iron plates.	
13.4	Stainless steel body.	
13.5	Pivot-action top plate to suit any food thickness.	
13.6	Thermostatically controlled up to at least 285 °C (545 °F).	

13.7	Electrical requirement 120 V	
14	Cutter-mixer	
14.1	Dimensions: 220 mm W x 310 mm D x 445 mm H \pm 25 mm (9" x 12" x 17.5" \pm 1")	
14.2	Direct drive, 1.5 H.P., single phase motor with magnetic safety system and motor brake for user safety.	
14.3	Control panel with push buttons for "on", "off" and "pulse".	
14.4	Including 4 mm (0.17") slicing disc and 2 mm (0.08") grating discs.	
14.5	Stainless steel "S" blade.	
14.6	4.25 L (4.5 qt) stainless steel cutter bowl with handle, see-thru lid with introduction port which allows user to add ingredients while processing.	
14.7	Attachments easily removed for easy cleaning and optimum sanitation.	
14.8	Electrical requirement 120 V	
15	Steam Table Adaptor Plate	
15.1	Dimensions: 525 mm x 325 mm \pm 25 mm (20.7" x 12.8" \pm 1")	
15.2	Stainless steel adaptor plate.	
15.3	To fit a standard steam table opening.	
15.4	Two (2) openings, one (1) of 265 mm (10.4") and one (1) of 215 mm (8.4").	
16	Garbage Can	
16.1	Dimensions: 380 mm x 285 mm x 510 mm \pm 25 mm (15.0" x 11.2" x 20.0" \pm 1")	
16.2	Volume: 38 L \pm 1 L (40 qt \pm 1 qt)	

Solicitation No. - N° de l'invitation
A7100-163511/A
Client Ref. No. - N° de réf. du client
A7100-163511

Amd. No. - N° de la modif.
003
File No. - N° du dossier
WPG-6-39233

Buyer ID - Id de l'acheteur
wpg016
CCC No./N° CCC - FMS No./N° VME

16.3	Fire resistant.	
16.4	Color: Beige.	
16.5	UL Rating.	
17	Recycling Bin	
17.1	Dimensions: 380 mm x 285 mm x 510 mm \pm 25 mm (15.0" x 11.2" x 20.0" \pm 1")	
17.2	Volume: 38 L \pm 1 L (40 qt \pm 1 qt)	
17.3	Fire resistant.	
17.4	Color: Beige.	
17.5	UL Rating.	
18	Compost Bin	
18.1	Dimensions: 300 mm x 220 mm x 215 mm \pm 25 mm (11.8" x 8.7" x 8.5" \pm 1")	
18.2	Volume: 7 L \pm 1 L	
18.3	Color: Beige with white cover	
19	Garbage Can	
19.1	Dimensions: 585 mm x 280 mm x 630 mm \pm 25 mm (23.1" x 11.0" x 24.9" \pm 1").	
19.2	Color: Light grey.	
19.3	Volume: 60 L \pm 5 L (63.4 qt \pm 4.4 qt)	
19.4	All plastic construction, will not rust, chip, or peel, and chock resistant.	
19.5	Reinforced rims to add strength and durability.	
19.6	Built-in handles for better handling.	
19.7	Stainless steel dolly with non-marking plastic casters. Resists chemicals and rust. For use in wet environments.	

Solicitation No. - N° de l'invitation
A7100-163511/A
Client Ref. No. - N° de réf. du client
A7100-163511

Amd. No. - N° de la modif.
003
File No. - N° du dossier
WPG-6-39233

Buyer ID - Id de l'acheteur
wpg016
CCC No./N° CCC - FMS No./N° VME

20	Garbage Can	
20.1	Dimensions: 490 mm diameter x 580 mm high \pm 25 mm (19.4" x 22.9" \pm 1").	
20.2	Color: Grey.	
20.3	Volume: 75.7 L \pm 5 L (66.6 qt \pm 4.4 qt)	
20.4	Reinforced rims to add strength and durability.	
20.5	Built-in handles for better handling.	
20.6	Double ribbed base increases stability and dragging capacity.	
20.7	"USDA Meat and Poultry" equipment group listed.	
20.8	Certified to NSF standards.	
20.9	Strong snap-on lids.	
20.10	Dolly with five (5) rugged non-marking casters, structural foam construction, twist lock.	
21	Garbage Can	
21.1	Dimensions: 400 mm diameter x 475 mm high \pm 25 mm (15.8" x 18.8" \pm 1").	
21.2	Capacity: 42 L \pm 5 L (37 qt \pm 4.4 qt)	
21.3	Color: Gray	
21.4	All around rim.	
21.5	All plastic, durable and crack resistant.	
22	Recycling Bin	
22.1	Dimensions: 400 mm diameter x 475 mm high \pm 25 mm (15.8" x 18.8" \pm 1").	
22.2	Capacity: 42 L \pm 5 L (37 qt \pm 4.4 qt)	
22.3	Color: Gray	

22.4	All around rim.	
22.5	All plastic, durable and crack resistant.	
23	Microwave Oven	
23.1	Dimensions: 510 mm x 400 mm x 305 mm \pm 25 mm (20.08" x 15.75" x 12" \pm 1").	
23.2	Cavity dimensions: 330 mm x 330 mm x 205 mm high \pm 25 mm (13" x 13" x 8" \pm 1").	
23.3	Stainless steel commercial microwave.	
23.4	Output power 1000 watts.	
23.5	Bottom Energy Feed	
23.6	6 Minute Dial Timer	
23.7	Interior oven light	
23.8	See-through oven door	
23.9	Electrical requirement 120 V	
24	Microwave Oven	
24.1	Dimensions: 510 mm x 380 mm x 305 mm \pm 25 mm (20.08" x 14.96" x 12" \pm 1").	
24.2	Cavity dimensions: 330 mm x 330 mm x 205 mm high \pm 25 mm (13" x 13" x 8" \pm 1").	
24.3	Stainless steel digital display commercial microwave.	
24.4	Ten (10) programmable memory pads.	
24.5	Six (6) power levels.	
24.6	2 and 3 stage cooking.	
24.7	Output power 1000 watts.	
24.8	Electrical requirement 120 V	

25	Under-counter Refrigerator	
25.1	Dimensions: 450 mm x 520 mm x 685 mm high ± 25 mm (17.63" x 20.5" x 26" ± 1 ").	
25.2	Capacity: 74L ± 5 L (2.6 cuft ± 0.18 cuft).	
2	One (1) door.	
5.3	Stainless steel front and top. Aluminum sides and finished back.	
25.4	Energy Star compliant.	
25.5	To be installed under a counter.	
25.6	Electrical requirement 115 V	
26	Refrigerated Display	
26.1	Dimensions: 425 mm x 405 mm x 980 mm ± 25 mm (16.75" x 16" x 38.5" ± 1 ").	
26.2	Four (4) sided clear glass cabinet.	
26.3	Interior LED lighting.	
26.4	Capacity: 85 L ± 5 L (3 cuft ± 0.18 cuft).	
26.5	Sturdy stainless steel wire shelving.	
26.6	Three (3) shelves.	
26.7	One (1) swing door	
26.8	Electrical requirement 115 V	
27	Mobile Refrigerator	
27.1	Dimensions: 815 mm x 675 mm x 1795 mm ± 25 mm (32" x 26.5" x 70.63" ± 1 ").	
27.2	One (1) door, full height.	

27.3	Stainless steel door finish.	
27.4	Grey cabinet finish.	
27.5	Capacity: 527 L ± 5 L (18.6 cuft ± 0.18 cuft).	
27.6	Electrical requirement 115 V	
28	Shelving Unit	
28.1	Two (2) 1220 mm x 455 mm x 1890 mm high ± 25 mm (48" x 18" x 74.4" ± 1").	
28.2	One (1) 1370 mm x 455 mm x 1890 mm high ± 25 mm (53.93" x 18" x 74.4" ± 1").	
28.3	Four post and five shelves per unit.	
28.4	Chrome plated wire shelving and posts.	
28.5	Shelf height adjustable by 25 mm increments (1") along the entire length of the post without tools.	
28.6	Capacity: maximum weight capacity of at least 270 kg (600 lb) per shelf.	
28.7	Total unit capacity: maximum unit capacity of at least 910 kg (2000 lbs)	
29	Mobile Shelving Units	
29.1	Two (2) 1370 mm x 455 mm x 1580 mm ± 25 mm (53.93" x 18" x 62.2" ± 1").	
29.2	Four (4) 915 mm x 455 mm x 1580 mm ± 25 mm (36" x 18" x 62.2" ± 1").	
29.3	Three (3) 1220 mm x 455 mm x 1580 mm ± 25 mm (48" x 18" x 62.2" ± 1").	
29.4	Four posts for stem casters and at least four shelves per unit.	
29.5	Epoxy coated steel frames and posts.	
29.6	Antibacterial polypropylene grid mat shelving.	
29.7	Shelves removable for cleaning.	

Solicitation No. - N° de l'invitation
A7100-163511/A
Client Ref. No. - N° de réf. du client
A7100-163511

Amd. No. - N° de la modif.
003
File No. - N° du dossier
WPG-6-39233

Buyer ID - Id de l'acheteur
wpg016
CCC No./N° CCC - FMS No./N° VME

29.8	Capacity: maximum weight capacity of at least 270 kg (600 lb) per shelf.	
29.9	Total unit capacity: maximum unit capacity of at least 405 kg (900 lbs)	
29.10	Shelf height adjustable by 25 mm increments (1") along the entire length of the post.	
29.11	Four (4) stem casters with bumpers to protect walls and furniture.	
30	Shelving Unit for Pots and Pans	
30.1	Dimensions: 1525 mm x 455 mm x 1875 mm \pm 25 mm (60" x 18" x 73.8" \pm 1").	
30.2	Four post and four shelves per unit.	
30.3	Stainless steel posts and shelves.	
30.4	Raised shelf edges so contain spills.	
30.5	Shelves louvered/embossed with epoxy coated cast corners address the majority of applications for solid, corrosion resistant shelves.	
30.6	Stainless steel stationary posts include stainless levelling bolts.	

ALL OTHER TERMS AND CONDITIONS REMAIN THE SAME