

PART 1 - GENERAL

- 1.1 REFERENCES
- .1 Canada Green Building Council (CaGBC)
 - .1 LEED Canada 2009 for Design and Construction Leadership in Energy and Environmental Design Green Building Rating System Reference Guide.
 - .2 CSA International
 - .1 CSA B111-1974(R2003), Wire Nails, Spikes and Staples.
 - .2 CSA O121-08, Douglas Fir Plywood.
 - .3 CSA O151-09, Canadian Softwood Plywood.
 - .4 CAN/CSA-Z809-08, Sustainable Forest Management.
 - .3 Environmental Choice Program (ECP)
 - .1 CCD-045-95, Sealants and Caulking Compounds.
 - .4 Forest Stewardship Council (FSC)
 - .1 FSC-STD-01-001-2004, FSC Principle and Criteria for Forest Stewardship.
 - .5 National Lumber Grading Authority (NLGA)
 - .1 NLGA Standard Grading Rules for Canadian Lumber 2010.
 - .6 Sustainable Forestry Initiative (SFI)
 - .1 SFI-2010-2014 Standard.
- 1.2 ACTION AND INFORMATIONAL SUBMITTALS
- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
 - .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for wood siding and include product characteristics, performance criteria, physical size, finish and limitations.
 - .2 Submit 2 copies of WHMIS MSDS in accordance with Section 01 35 29.06 - Health and Safety Requirements. Indicate VOC's for caulking materials during application and curing.
-

PART 2 - PRODUCTS

- 2.1 MATERIALS
- .1 Lumber siding: to NLGA Standard Grading Rules for Canadian Lumber.
 - .1 Rabetted Bevel siding: lodgepole pine, factory finished face.
 - .2 Board size: 22 mm x 150 mm nominal.
 - .3 FSC or SFI certified wood.
 - .2 Accessories: exposed soffit trim, closures, cap pieces and all related accessories manufacturer's standard, finish to match siding. Colour to be selected from manufacturer's full colour range.
 - .3 Fasteners: nails to CSA B111, type 316, stainless steel ring shank coloured nails, sized as required.
 - .4 Sealants: to Section 07 92 00.

PART 3 - EXECUTION

- 3.1 EXAMINATION
- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.
- 3.2 MANUFACTURER'S INSTRUCTIONS
- .1 Compliance: comply with manufacturer's written data, including product technical bulletins, product catalogue installation instructions, product carton installation instructions, and data sheets.

- 3.3 INSTALLATION .1 Install siding and accessories to manufacturers' written instructions.
- .2 Install sill flashings, wood starter strips, inside corner flashings, edgings and flashings over openings.
- .3 Fasten wood siding in straight, aligned lengths.
- 3.4 ATTACHMENT SURFACE .1 Provide flat surface for mounting of electrical and mechanical components, 150 mm longer all around than item being mounted from trim boards.
- 3.5 CLEANING .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
.1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal and Section 01 35 21 - LEED Requirements.
.1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.
- 3.6 PROTECTION .1 Protect installed products and components from damage during construction.
- .2 Repair damage to adjacent materials caused by wood siding installation.