

PART 1 - GENERAL

- | | | |
|--|----|---|
| <u>1.1 REFERENCES</u> | .1 | Canada Green Building Council (CaGBC)
.1 LEED Canada-NC-2009, LEED (Leadership in Energy and Environmental Design): Green Building Rating System Reference Package For New Construction and Major Renovations. |
| | .2 | Environment Canada (EC)
.1 Volatile Organic Compound (VOC) Concentration Limits for Architectural Coatings Regulations, SOR/2009-264. |
| | .3 | Health Canada/Workplace Hazardous Materials Information System (WHMIS)
.1 Material Safety Data Sheets (MSDS). |
| | .4 | Master Painters Institute (MPI)
.1 Architectural Painting Specification Manual - current edition.
.1 MPI #32 Traffic Markings Paint, Alkyd. |
| | .5 | South Coast Air Quality Management District (SCAQMD)
.1 SCAQMD Rule 1113-13, Architectural Coatings. |
| <u>1.2 ACTION AND INFORMATIONAL SUBMITTALS</u> | .1 | Submit in accordance with Section 01 33 00 - Submittal Procedures. |
| | .2 | Product Data:
.1 Submit manufacturer's printed product literature and data sheets for pavement markings and include product characteristics, performance criteria, physical size, finish and limitations.
.2 Submit 2 copies of WHMIS MSDS in accordance with Section 01 35 29.06 - Health and Safety Requirements. |
| | .3 | Samples: |
-

1.2 ACTION AND
INFORMATIONAL
SUBMITTALS
(Cont'd)

- .3 Samples: (Cont'd)
 - .1 Submit to Departmental Representative following material sample quantities at least 4 weeks prior to commencing work.
 - .1 Two 1 L samples of each type of paint.
 - .2 Sampling to MPI Painting Manual.
 - .2 Mark samples with name of project and its location, paint manufacturer's name and address, name of paint, MPI specification number and formulation number and batch number.
 - .4 Sustainable Design Submittals:
 - .1 LEED Canada submittals: in accordance with Section 01 35 21 - LEED Requirements.
 - .2 Construction Waste Management:
 - .1 Submit project Waste Management Plan highlighting recycling and salvage requirements.
 - .2 Submit calculations on end-of-project recycling rates, salvage rates, and landfill rates demonstrating that 75% of construction wastes were recycled or salvaged.
 - .3 Recycled Content:
 - .1 Submit listing of recycled content products used, including details of required percentages or recycled content materials and products, showing their costs and percentages of post-consumer and post-industrial content, and total cost of materials for project.
 - .4 Regional Materials: submit evidence that project incorporates required percentage 20% of regional materials and products, showing their cost, distance from project to furthest site of extraction or manufacture, and total cost of materials for project.
 - .5 Low-Emitting Materials: submit listing of paints and coatings to comply with VOC and chemical component limits or restrictions requirements.
-

- 1.3 CLOSEOUT SUBMITTALS
- .1 Submit in accordance with Section 01 78 00 - Closeout Submittals.
 - .2 Operations and Maintenance Data: submit information on materials relative to work of this Section for inclusion in operations and maintenance manual and as follows:
 - .1 Paint.
- 1.4 DELIVERY, STORAGE AND HANDLING
- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
 - .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
 - .3 Storage and Handling Requirements:
 - .1 Store materials and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect specified materials from nicks, scratches, and blemishes.
 - .3 Replace defective or damaged materials with new.
 - .4 Develop Construction Waste Management Plan related to Work of this Section and in accordance with Section 01 35 21 - LEED Requirements.
 - .5 Packaging Waste Management: remove for reuse or return of pallets, crates, padding, banding, and packaging materials as specified in Construction Waste Management Plan in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal and Section 01 35 21 - LEED Requirements.
- 1.5 SITE CONDITIONS
- .1 Sustainable Design Provisions:
-

1.5 SITE CONDITIONS .1
(Cont'd)

(Cont'd)

.1 Seasonal restriction for high VOC content traffic marking coatings.

.1 Traffic marking coating application between May 1st and October 15th is subject to seasonal use restriction and must not have a VOC concentration in excess of 150 g/L.

PART 2 - PRODUCTS

2.1 MATERIALS .1

Paint and Markings:

.1 To MPI #32, Alkyd zone/traffic marking.

.2 Traffic Marking Coatings: maximum VOC limit 450 g/L to SOR/2009-264 Schedule 1 and to GS-11 Standard and to SCAQMD Rule 1113.

.3 Paints: in accordance with MPI recommendation for surface conditions.

.4 Colour: to MPI listed, yellow and white.

.5 Upon request, Departmental Representative will supply qualified product list of paints applicable to work. Qualified paints may be used but Departmental Representative reserves right to perform further tests.

.2 Thinner: to MPI listed manufacturer.

PART 3 - EXECUTION

3.1 EXAMINATION .1

Verification of Conditions: verify conditions of substrates and surfaces to receive pavement markings previously installed under other Sections or Contracts are acceptable for product installation in accordance with MPI instructions prior to pavement markings installation.

.1 Visually inspect substrate in presence of Departmental Representative.

.2 Pavement surface: dry, free from water, frost, ice, dust, oil, grease and other deleterious materials.

- | | | |
|---------------------------------------|----|---|
| <u>3.1 EXAMINATION
(Cont'd)</u> | .3 | Proceed with Work only after unacceptable conditions have been rectified. |
| <u>3.2 EQUIPMENT
REQUIREMENTS</u> | .1 | Paint applicator: approved pressure type mobile with positive shut-off distributor capable of applying paint in single, double and dashed lines and capable of applying marking components uniformly, at rates specified, and to dimensions as indicated. |
| <u>3.3 APPLICATION</u> | .1 | Pavement markings: lay out pavement markings. |
| | .2 | Unless otherwise approved by Departmental Representative, apply paint only when air temperature is above 10 degrees C, wind speed is less than 60 km/h and no rain is forecast within next 4 hours. |
| | .3 | Apply traffic paint evenly at rate of 3m ² /L. |
| | .4 | Do not thin paint unless approved by Departmental Representative. |
| | .5 | Symbols and letters to dimensions indicated. |
| | .6 | Paint lines of uniform colour and density with sharp edges. |
| | .7 | Thoroughly clean distributor tank before refilling with paint of different colour. |
| <u>3.4 TOLERANCE</u> | .1 | Paint markings: within plus or minus 12 mm of dimensions indicated. |
| | .2 | Remove incorrect markings to approval of Departmental Representative. |
| <u>3.5 CLEANING</u> | .1 | Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
.1 Leave Work area clean at end of each day. |
-

3.5 CLEANING
(Cont'd)

- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
 - .1 Remove insulation material spilled during installation and leave work area ready for application of wall board.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal and Section 01 35 21 - LEED Requirements.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

3.6 PROTECTION

- .1 Protect pavement markings until dry.
- .2 Repair damage to adjacent materials caused by pavement marking application.