

PART 1 - GENERAL

1.1 REFERENCES

- .1 American Society of Heating, Refrigerating and Air-Conditioning Engineers (ASHRAE)
 - .2 ASTM International
 - .1 ASTM A 480/A 480M-12, Standard Specification for General Requirements for Flat-Rolled Stainless and Heat-Resisting Steel Plate, Sheet and Strip.
 - .2 ASTM A 635/A 635M-09b, Standard Specification for Steel, Sheet and Strip, Heavy-Thickness Coils, Hot-Rolled, Alloy, Carbon, Structural, High-Strength Low-Alloy, and High-Strength Low-Alloy with Improved Formability, General Requirements for.
 - .3 ASTM A 653/A 653M-11, Standard Specification for Steel Sheet, Zinc Coated (Galvanized) or Zinc-Iron Alloy Coated (Galvannealed) by the Hot-Dip Process.
 - .3 Canada Green Building Council (CaGBC)
 - .1 LEED Canada 2009 for Design and Construction, LEED Canada 2009 for Design and Construction Leadership in Energy and Environmental Design Green Building Rating System Reference Guide.
 - .4 Green Seal Environmental Standards (GS)
 - .1 GS-36-11, Standard for Adhesives for Commercial Use.
 - .5 National Fire Protection Association (NFPA)
 - .1 NFPA 90A-12, Standard for the Installation of Air-Conditioning and Ventilating Systems.
 - .2 NFPA 90B-12, Standard for the Installation of Warm Air Heating and Air-Conditioning Systems.
 - .6 Sheet Metal and Air Conditioning Contractors' National Association (SMACNA)
 - .1 SMACNA HVAC Duct Construction Standards - Metal and Flexible, 2005.
 - .2 SMACNA HVAC Air Duct Leakage Test Manual, 2012.
-

- | | | |
|---|----|--|
| 1.1 REFERENCES
(Cont'd) | .7 | South Coast Air Quality Management District (SCAQMD), California State, Regulation XI. Source Specific Standards
.1 SCAQMD Rule 1168-A2005, Adhesives and Sealants Applications. |
| 1.2 ACTION AND INFORMATIONAL SUBMITTALS | .1 | Submit in accordance with Section 01 33 00 - Submittal Procedures. |
| | .2 | Product Data:
.1 Submit manufacturer's instructions, printed product literature and data sheets for metal ducts and include product characteristics, performance criteria, physical size, finish and limitations. |
| | .3 | Shop Drawings:
.1 Submit drawings stamped and signed by professional engineer registered or licensed in the Province of Newfoundland and Labrador. |
| | .4 | Test and Evaluation Reports:
.1 Certification of Ratings:
.1 Catalogue or published ratings to be those obtained from tests carried out by manufacturer or independent testing agency signifying adherence to codes and standards. |
| | .5 | Sustainable Design Submittals:
.1 LEED Canada submittals: in accordance with Section 01 35 21 - LEED Requirements.
.2 Construction Waste Management:
.1 Submit project Waste Management Plan highlighting recycling and salvage requirements.
.2 Submit calculations on end-of-project recycling rates, salvage rates, and landfill rates demonstrating that 75% of construction wastes were recycled or salvaged. |
| | .3 | Recycled Content:
.1 Submit listing of recycled content products used, including details of required percentages or recycled content materials and products, showing their costs and percentages of post-consumer |
-

1.2 ACTION AND
INFORMATIONAL
SUBMITTALS
(Cont'd)

- .5 Sustainable Design Submittals:(Cont'd)
 - .3 Recycled Content:(Cont'd)
 - .1 (Cont'd)
 - and post-industrial content, and total cost of materials for project.
 - .4 Regional Materials: submit evidence that project incorporates required percentage 30% of regional materials and products, showing their cost, distance from project to furthest site of extraction or manufacture, and total cost of materials for project.
 - .5 Construction IAQ Management Plan:
 - .1 Submit Indoor Air Quality (IAQ) Plan for construction and pre-occupancy phases of building.

1.3 DELIVERY,
STORAGE AND
HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials indoors in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect metal ducts from nicks, scratches, and blemishes.
 - .3 Replace defective or damaged materials with new.
- .4 Develop Construction Waste Management Plan related to Work of this Section and in accordance with Section 01 35 21 - LEED Requirements.
- .5 Packaging Waste Management: remove for reuse or return of pallets, crates, padding, banding, and packaging materials as specified in Construction Waste Management Plan in accordance with Section 01 74 21 - Construction/Demolition Waste Management and

1.3 DELIVERY, STORAGE AND HANDLING (Cont'd)	.5 Packaging Waste Management: (Cont'd) Disposal and Section 01 35 21 - LEED Requirements.
--	--

PART 2 - PRODUCTS

2.1 SEAL CLASSIFICATION	.1 Classification as follows:
----------------------------	-------------------------------

Maximum Pressure Pa	SMACNA Seal Class
500	A
250	A
125	A

.2 Seal classification:
.1 Class A: Longitudinal seams, transverse joints, duct wall penetration and connections made air tight with sealant or tape.

2.2 SEALANT	.1 Sustainability Characteristics:
	.1 Adhesives and sealants: in accordance with Section 07 92 00 - Joint Sealants.
	.2 Adhesives and sealants: VOC limit 30 g/L maximum to SCAQMD Rule 1168.
	.2 Sealant: oil resistant, water borne, polymer type flame resistant duct sealant. Temperature range of minus 30 degrees C to plus 93 degrees C.

2.3 TAPE	.1 Tape: polyvinyl treated, open weave fiberglass tape, 50 mm wide.
----------	---

2.4 DUCT LEAKAGE	.1 In accordance with SMACNA HVAC Air Duct Leakage Test Manual.
------------------	---

2.5 FITTINGS

- .1 Fabrication: to SMACNA.
- .2 Radiused elbows:
 - .1 Rectangular: standard radius centreline radius: 1.5 times width of duct.
 - .2 Round: five piece, centreline radius: 1.5 times diameter.
- .3 Mitred elbows, rectangular:
 - .1 To 400 mm: with single thickness turning vanes.
 - .2 Over 400 mm: with double thickness turning vanes.
- .4 Branches:
 - .1 Rectangular main and branch: with radius on branch 1.5 times width of duct.
 - .2 Round main and branch: enter main duct at 45 degrees with conical connection.
 - .3 Provide volume control damper in branch duct near connection to main duct.
 - .4 Main duct branches: with splitter damper.
- .5 Transitions:
 - .1 Diverging: 20 degrees maximum included angle.
 - .2 Converging: 30 degrees maximum included angle.
- .6 Obstruction deflectors: maintain full cross-sectional area.
 - .1 Maximum included angles: as for transitions.

2.6 FIRE STOPPING

- .1 Retaining angles around duct, on both sides of fire separation in accordance with Section 07 84 00 - Fire Stopping.
 - .2 Fire stopping material and installation must not distort duct.
-

- 2.7 GALVANIZED STEEL
- .1 Lock forming quality: to ASTM A 653/A 653M, Z90 zinc coating.
 - .2 Thickness, fabrication and reinforcement: to SMACNA.
 - .3 Joints: to SMACNA.

- 2.8 HANGERS AND SUPPORTS
- .1 Hangers and Supports: in accordance with Section 23 05 29 - Hangers and Supports for HVAC Piping and Equipment.
 - .1 Strap hangers: of same material as duct but next sheet metal thickness heavier than duct.
 - .1 Maximum size duct supported by strap hanger: 500.
 - .2 Hanger configuration: to ASHRAE and SMACNA.
 - .3 Hangers: galvanized steel angle with galvanized steel rods to ASHRAE and SMACNA following table:

Duct Size	Angle Size	Rod Size
(mm)	(mm)	(mm)
up to 750	25 x 25 x 3	6
751 to 1050	40 x 40 x 3	6

- .4 Upper hanger attachments:
 - .1 For concrete: manufactured concrete inserts.
 - .2 For steel joist: manufactured joist clamp.
 - .3 For steel beams: manufactured beam clamps:
-

PART 3 - EXECUTION

- | | | |
|------------------------|----|---|
| <u>3.1 EXAMINATION</u> | .1 | Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for metal duct installation in accordance with manufacturer's written instructions.
.1 Visually inspect substrate in presence of Departmental Representative.
.2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
.3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative. |
| <u>3.2 GENERAL</u> | .1 | Do work in accordance with NFPA 90A, NFPA 90B, ASHRAE and SMACNA. |
| | .2 | Do not break continuity of insulation vapour barrier with hangers or rods.
.1 Insulate strap hangers 100 mm beyond insulated duct Ensure diffuser is fully seated. |
| | .3 | Support risers in accordance with SMACNA. |
| | .4 | Install breakaway joints in ductwork on sides of fire separation. |
| | .5 | Install proprietary manufactured flanged duct joints in accordance with manufacturer's instructions. |
| <u>3.3 HANGERS</u> | .1 | Strap hangers: install in accordance with SMACNA. |
| | .2 | Angle hangers: complete with locking nuts and washers. |
| | .3 | Hanger spacing: in accordance with ASHRAE and SMACNA as follows: |

3.3 HANGERS
(Cont'd)

.3 Hanger spacing: (Cont'd)

Duct Size	Spacing
(mm)	(mm)
to 1500	3000

3.4 WATERTIGHT DUCT

- .1 Provide watertight duct for:
- .1 Fresh air intake.
 - .2 Minimum 3000 mm from duct mounted humidifier in all directions.
 - .3 As indicated.
- .2 Form bottom of horizontal duct without longitudinal seams.
- .1 Solder joints of bottom and side sheets.
 - .2 Seal other joints with duct sealer.
- .3 Slope horizontal branch ductwork down towards hoods served.
- .1 Slope header ducts down toward risers.
- .4 Fit base of riser with 150 mm deep drain sump and 32 mm drain connected, with deep seal trap and valve and discharging to open funnel drain.

3.6 SEALING AND TAPING

- .1 Apply sealant in accordance with SMACNA and to manufacturer's recommendations.
- .2 Bed tape in sealant and recoat with minimum of 1 coat of sealant to manufacturers recommendations.

3.7 LEAKAGE TESTS

- .1 Refer to Section 23 05 94 - Pressure Testing of Ducted Air Systems.
- .2 In accordance with SMACNA HVAC Duct Leakage Test Manual.
- .3 Do leakage tests in sections.
- .4 Make trial leakage tests as instructed to demonstrate workmanship.
-

- 3.7 LEAKAGE TESTS (Cont'd)
- .5 Do not install additional ductwork until trial test has been passed.
 - .6 Test section minimum of 30 m long with not less than three branch takeoffs and two 90 degrees elbows.
 - .7 Complete test before performance insulation or concealment Work.
- 3.8 CLEANING
- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Leave Work area clean at end of each day.
 - .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
 - .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal and Section 01 35 21 - LEED Requirements.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.