



## RETURN BIDS TO:

## RETOURNER LES SOUMISSIONS À:

Bid Receiving Public Works and Government  
Services Canada/Réception des  
soumissions/Travaux publics et Services  
gouvernementaux Canada  
The Cambridge Building  
3 Queen Street/3, rue Queen  
Charlottetown  
Prince Edward Island  
C1A 4A2

## INVITATION TO TENDER

## APPEL D'OFFRES

**Tender To: Public Works and Government Services  
Canada**

We hereby offer to sell to Her Majesty the Queen in right of  
Canada, in accordance with the terms and conditions set  
out herein, referred to herein or attached hereto, the goods,  
services, and construction listed herein and on any attached  
sheets at the price(s) set out therefor.

### Soumission aux: Travaux Publics et Services Gouvernementaux Canada

Nous offrons par la présente de vendre à Sa Majesté la  
Reine du chef du Canada, aux conditions énoncées ou  
incluses par référence dans la présente et aux annexes  
ci-jointes, les biens, services et construction énumérés  
ici et sur toute feuille ci-annexée, au(x) prix indiqué(s).

### Comments - Commentaires

**Vendor/Firm Name and Address**  
**Raison sociale et adresse du**  
**fournisseur/de l'entrepreneur**

### Issuing Office - Bureau de distribution

Public Works and Government Services Canada  
The Cambridge Building  
3 Queen Street/3 rue, Queen  
PO Box 1268/CP 1268  
Charlottetown  
Prince Ed  
C1A 4A2

<b>Title - Sujet</b> Flooring Replacement, JAG Building	
<b>Solicitation No. - N° de l'invitation</b> ED001-180814/A	<b>Date</b> 2017-08-02
<b>Client Reference No. - N° de référence du client</b> ED001-180814	<b>GETS Ref. No. - N° de réf. de SEAG</b> PW-\$PWC-010-4164
<b>File No. - N° de dossier</b> PWC-7-40053 (010)	<b>CCC No./N° CCC - FMS No./N° VME</b>
<b>Solicitation Closes - L'invitation prend fin</b> <b>at - à 02:00 PM</b> <b>on - le 2017-08-22</b>	
<b>Time Zone</b> <b>Fuseau horaire</b> Atlantic Daylight Saving Time ADT	
<b>F.O.B. - F.A.B.</b> <b>Plant-Usine:</b> <input type="checkbox"/> <b>Destination:</b> <input checked="" type="checkbox"/> <b>Other-Autre:</b> <input type="checkbox"/>	
<b>Address Enquiries to: - Adresser toutes questions à:</b> MacDonald, Anne (PWC) D.	<b>Buyer Id - Id de l'acheteur</b> pwc010
<b>Telephone No. - N° de téléphone</b> (902) 626-4949 ( )	<b>FAX No. - N° de FAX</b> (902) 566-7514
<b>Destination - of Goods, Services, and Construction:</b> <b>Destination - des biens, services et construction:</b> DEPARTMENT OF PUBLIC WORKS AND GOVERNMENT SERVICES CANADA PO BOX 1268 3 QUEEN ST CHARLOTTETOWN Prince Edward Island C1A4A2 Canada	

**Instructions: See Herein**

**Instructions: Voir aux présentes**

<b>Delivery Required - Livraison exigée</b> See Herein	<b>Delivery Offered - Livraison proposée</b>
<b>Vendor/Firm Name and Address</b> <b>Raison sociale et adresse du fournisseur/de l'entrepreneur</b>	
<b>Telephone No. - N° de téléphone</b> <b>Facsimile No. - N° de télécopieur</b>	
<b>Name and title of person authorized to sign on behalf of Vendor/Firm</b> <b>(type or print)</b> <b>Nom et titre de la personne autorisée à signer au nom du fournisseur/</b> <b>de l'entrepreneur (taper ou écrire en caractères d'imprimerie)</b>	
<b>Signature</b>	<b>Date</b>

## INVITATION À SOUMISSIONNER

**Bâtiment Joseph A Ghiz,  
Remplacement du revêtement de sol  
275 chemin Pope  
Summerside (île-du-Prince-Édouard)**

### AVIS IMPORTANT AUX SOUMISSIONNAIRES

#### PAIEMENT SANS DÉLAI DANS L'INDUSTRIE DE LA CONSTRUCTION

##### Principes en matière de paiement sans délai

Services publics et Approvisionnement Canada est d'avis que ces trois principes devraient régir le versement des paiements faits au titre des contrats de construction :

- **Rapidité** : Le Ministère examinera et traitera les factures dans les meilleurs délais. En cas de différend, Services publics et Approvisionnement Canada paiera les éléments non contestés, tout en s'employant à résoudre la question du montant contesté de façon rapide et équitable
- **Transparence** : Le Ministère rendra publics les renseignements sur les paiements versés au titre des contrats de construction, comme les dates de versement de paiements, ainsi que le nom des entreprises, les numéros de contrat et de projet; de leur côté, les entrepreneurs devraient communiquer ces renseignements aux paliers inférieurs
- **Responsabilité partagée** : Les payeurs et les bénéficiaires sont tenus de respecter les conditions de leurs contrats, entre autres leurs obligations liées au versement et à la réception des paiements, ainsi que d'adopter les pratiques exemplaires de l'industrie

Pour plus de renseignements : <http://www.tpsgc-pwgsc.gc.ca/biens-property/divulcation-disclosure/psdic-ppci-fra.html>

#### APPUYER LE RECOURS AUX APPRENTIS

Le gouvernement du Canada propose de soutenir l'embauche d'apprentis dans le cadre des projets de construction et d'entretien du gouvernement fédéral. Vous référer à IP10

#### MISE À JOUR SUR L'UTILISATION DE L'AMIANTE DE TPSGC

En date du 1<sup>er</sup> avril 2016, tous les contrats de Travaux publics et services gouvernementaux Canada (TPSGC) qui portent sur des projets de nouvelle construction et des rénovations importantes interdiront l'utilisation des matériaux de construction contenant de l'amiante. Pour de plus amples informations veuillez consulter ce lien <http://www.tpsgc-pwgsc.gc.ca/comm/vedette-features/2016-04-19-00-fra.html>

#### AJOUT D'UNE CLAUSE ÉVALUATION DU RENDEMENT - CONTRAT

Prendre connaissance à la condition supplémentaire CS05 de l'ajout d'un paragraphe à la clause R2810D.

#### AJOUT DE TERMINOLOGIE

Prendre connaissance à la condition supplémentaire CS06 de l'ajout de terminologie à la clause R2810D.

## TABLE DES MATIÈRES

### INSTRUCTIONS PARTICULIÈRES AUX SOUMISSIONNAIRES (IP)

- IP01 Documents de soumission
- IP02 Demandes de renseignements pendant l'appel d'offres
- IP03 Visite des lieux
- IP04 Révision des soumissions
- IP05 Résultats de l'appel d'offres
- IP06 Fonds insuffisants
- IP07 Période de validité des soumissions
- IP08 Documents de construction
- IP09 Exigences relatives à la sécurité industrielle
- IP10 Initiative de Travaux publics et Services gouvernementaux Canada pour l'embauche d'apprentis
- IP11 Sites Web

### R2710T INSTRUCTIONS GÉNÉRALES - SERVICES DE CONSTRUCTION - EXIGENCES RELATIVES À LA GARANTIE DE SOUMISSION (IG) (2017-04-27)

Les articles suivants de la clause R2710T sont reproduits sur le site Web <https://achatsetventes.gc.ca/politiques-et-lignes-directrices/guide-des-clauses-et-conditions-uniformisees-d-achat/5/R>

- IG01 Dispositions relatives à l'intégrité - soumission
- IG02 La soumission
- IG03 Identité ou capacité civile du soumissionnaire
- IG04 Taxes applicables
- IG05 Frais d'immobilisation
- IG06 Immatriculation et évaluation préalable de l'outillage flottant
- IG07 Liste des sous-traitants et fournisseurs
- IG08 Exigences relatives à la garantie de soumission
- IG09 Livraison des soumissions
- IG10 Révision des soumissions
- IG11 Rejet de la soumission
- IG12 Coûts relatifs aux soumissions
- IG13 Numéro d'entreprise – approvisionnement
- IG14 Respect des lois applicables
- IG15 Approbation des matériaux de remplacement
- IG16 Évaluation du rendement
- IG17 Conflit d'intérêts / Avantage indus.
- IG18 Code de conduite pour l'approvisionnement-soumission

### CONDITIONS SUPPLÉMENTAIRES (CS)

- CS01 Exigences relatives à la sécurité industrielle, lieu de sauvegarde des documents
- CS02 Limitation de la responsabilité
- CS03 Condition d'assurance
- CS04 Ajustement du prix du bitume
- CS05 Évaluation du rendement – contrat
- CS06 Interprétation

Solicitation No. - N° de l'invitation  
ED001-180814/A  
Client Ref. No. - N° de réf. du client  
ED001-180814

Amd. No. - N° de la modif.  
File No. - N° du dossier

Buyer ID - Id de l'acheteur  
PWC010  
CCC No./N° CCC - FMS No/ N° VME

## **DOCUMENTS DU CONTRAT (DC)**

### **FORMULAIRE DE SOUMISSION ET D'ACCEPTATION (SA)**

SA01 Identification du projet  
SA02 Nom commercial et adresse du soumissionnaire  
SA03 Offre  
SA04 Période de validité des soumissions  
SA05 Acceptation et contrat  
SA06 Durée des travaux  
SA07 Garantie de soumission  
SA08 Signature

### **APPENDICE 1- DISPOSITION RELATIVES À L'INTÉGRITÉ**

### **APPENDICE 2 - LISTE DES SOUS-TRAITANTS**

### **APPENDICE 3 - ATTESTATION VOLONTAIRE À L'APPUI DU RECOURS AUX APPRENTIS**

### **ANNEXE A -ATTESTATION D'ASSURANCE**

### **ANNEXE B- RAPPORT VOLONTAIRE D'APPRENTIS EMPLOYÉS PENDANT LES CONTRATS**

### **ANNEXE C – SPÉCIFICATIONS**

## INSTRUCTIONS PARTICULIÈRES AUX SOUMISSIONNAIRES (IP)

### IP01 DOCUMENTS DE SOUMISSION

1. Les documents suivants constituent les documents de soumission:
  - a. Appel d'offres - Page 1;
  - b. Instructions particulières aux soumissionnaires
  - c. Instructions générales – services de construction – exigences relatives à la garantie de soumission R2710T (2017-04-27)
  - d. Clauses et conditions identifiées aux "Documents du contrat";
  - e. Dessins et devis;
  - f. Formulaire de soumission et d'acceptation et tout appendice s'y rattachant; et
  - g. Toute modification émise avant la clôture de l'invitation.

La présentation d'une soumission constitue une affirmation que le soumissionnaire a lu ces documents et accepte les modalités qui y sont énoncées.

2. Les Instructions générales - Services de construction - Exigences relatives à la garantie de soumission R2710T sont incorporées par renvoi et reproduites dans le Guide des clauses et conditions uniformisées d'achat (CCUA) publié par Travaux publics et Services gouvernementaux Canada (TPSGC). Le guide des CCUA est disponible sur le site Web de TPSGC: <https://achatsetventes.gc.ca/politiques-et-lignes-directrices/guide-des-clauses-et-conditions-uniformisees-d-achat/5/R>

### IP02 DEMANDES DE RENSEIGNEMENTS PENDANT L'APPEL D'OFFRES

1. Toute demande de renseignements sur l'appel d'offres doit être présentée par écrit à l'agent d'approvisionnement dont le nom figure à l'Appel d'offres - Page 1 à l'adresse courriel [anne.macdonald@tpsgc-pwgsc.gc.ca](mailto:anne.macdonald@tpsgc-pwgsc.gc.ca), et ce le plus tôt possible pendant la durée de l'invitation. À l'exception de l'approbation de matériaux de remplacement, comme cela est décrit à l'IG15 de la R2710T toutes les autres demandes de renseignements devraient être reçues au moins cinq (5) jours civils avant la date de clôture de l'invitation afin de laisser suffisamment de temps pour y répondre. Pour ce qui est des demandes de renseignements reçues après cette date, il est possible qu'on ne puisse y répondre.
2. Pour assurer la cohérence et la qualité de l'information fournie aux soumissionnaires, l'agent d'approvisionnement examinera le contenu de la demande de renseignements et décidera s'il convient ou non de publier une modification.
3. Toutes les demandes de renseignements et autres communications envoyées avant la clôture de l'appel d'offres doivent être adressées UNIQUEMENT à l'agent d'approvisionnement dont le nom figure à l'Appel d'offres - Page 1. Le défaut de se conformer à cette exigence pourrait avoir pour conséquence que la soumission soit déclarée non recevable.

### IP03 VISITE DES LIEUX

Il y aura une visite des lieux le **9 aoûtj 2017 à 14 :00 h**. Les soumissionnaires intéressés sont priés de se présenter à l'entrée principale de l'édifice Joseph A Ghiz, 275, chemin Pope, Summerside, Île-du-Prince-Édouard.

### IP04 RÉVISION DES SOUMISSIONS

Une soumission peut être révisée par télécopie conformément à l'IG10 de la R2710T Le numéro du télécopieur pour la réception de révisions est le (902-566-7514

## **IP05 RÉSULTATS DE L'APPEL D'OFFRES**

1. Un dépouillement public des soumissions aura lieu au bureau désigné sur la page frontispice «Appel d'offres» pour la réception des soumissions, peu de temps après l'heure indiquée pour la clôture des soumissions.
2. L'entrepreneur ayant fourni la soumission recevable la plus basse sera recommandée pour l'octroi du contrat.
3. Après la date de clôture pour la réception des soumissions, on peut demander les résultats de l'appel d'offres en communiquant au numéro de téléphone (902) 566-7520

## **IP06 FONDS INSUFFISANTS**

Si la soumission conforme la plus basse dépasse le montant des fonds alloués par le Canada pour les travaux, le Canada pourra

- a. annuler l'appel d'offres; ou
- b. obtenir des fonds supplémentaires et attribuer le contrat au soumissionnaire ayant présenté la soumission conforme la plus basse; et/ou
- c. négocier une réduction maximale de 15% du prix offert et/ou de la portée des travaux avec le soumissionnaire ayant présenté la soumission conforme la plus basse. Si le Canada n'arrive pas à une entente satisfaisante, il exercera l'option a) ou b).

## **IP07 PÉRIODE DE VALIDITÉ DES SOUMISSIONS**

1. Le Canada se réserve le droit de demander une prorogation de la période de validité des soumissions tel que précisé à la SA04 du Formulaire de soumission et d'acceptation. Dès réception d'un avis écrit du Canada, les soumissionnaires auront le choix d'accepter ou de refuser la prorogation proposée.
2. Si la prorogation mentionnée à l'alinéa 1. de l'IP07 est acceptée par écrit par tous les soumissionnaires qui ont présenté une soumission, le Canada poursuivra alors sans tarder l'évaluation des soumissions et les processus d'approbation.
3. Si la prorogation mentionnée à l'alinéa 1. de l'IP07 n'est pas acceptée par écrit par tous les soumissionnaires qui ont présenté une soumission, le Canada pourra alors, à sa seule discrétion,
  - a) poursuivre l'évaluation des soumissions de ceux qui auront accepté la prorogation proposée et obtenir les approbations nécessaires; ou
  - b) annuler l'appel d'offres.
4. Les conditions exprimées dans les présentes ne limitent d'aucune façon les droits du Canada définis dans la loi ou en vertu de l'IG11 de R2710T

## **IP08 DOCUMENTS DE CONSTRUCTION**

À l'attribution du contrat, une copie électronique des dessins signés et scellés, du devis et des modifications sera fournie à l'entrepreneur retenu. Des copies supplémentaires, jusqu'à concurrence de (Inscrire le montant), seront fournies sans frais à la demande de l'entrepreneur. Il incombera à l'entrepreneur d'obtenir les autres exemplaires dont il peut avoir besoin et, le cas échéant, d'en assurer les coûts.

## **IP09 EXIGENCES RELATIVES À LA SÉCURITÉ INDUSTRIELLE**

Non applicable

## IP10 INITIATIVE DE TRAVAUX PUBLICS ET SERVICES GOUVERNEMENTAUX CANADA POUR L'EMBAUCHE D'APPRENTIS

1. Pour les encourager à participer à la formation d'apprentis, on demande aux employeurs qui soumissionnent pour des contrats de construction ou d'entretien de Travaux publics et Services gouvernementaux Canada (TPSGC) de signer une attestation volontaire, attestation signalant leur engagement à embaucher et former des apprentis.
2. Le Canada doit composer avec des pénuries de main-d'œuvre dans divers secteurs et dans diverses régions, en particulier dans des métiers spécialisés. Faciliter l'acquisition de compétences et la formation chez les Canadiens est une responsabilité partagée. Le gouvernement du Canada a pris l'engagement de faciliter l'utilisation d'apprentis dans le cadre des contrats fédéraux de construction et d'entretien. Les soumissionnaires ont un rôle important à jouer au titre du soutien des apprentis, à savoir les embaucher et les former. On les encourage à attester qu'ils proposent des possibilités d'emploi à des apprentis dans le cadre de leurs relations d'affaires avec le gouvernement du Canada.
3. Le gouvernement du Canada encourage les Canadiens à faire l'apprentissage de métiers spécialisés et à y faire carrière. En outre, le gouvernement offre un crédit d'impôt aux employeurs afin de les encourager à embaucher des apprentis. Vous trouverez de l'information à propos de ces mesures fiscales administrées par l'Agence du revenu du Canada dans son site Web à : [www.cra-arc.gc.ca](http://www.cra-arc.gc.ca). Les employeurs sont aussi invités à se renseigner à propos de l'information et des mesures de soutien additionnelles dont ils pourraient tirer profit auprès de leur autorité provinciale ou territoriale en matière d'apprentissage.
4. Les attestations signées (APPENDICE 4) aideront à mieux comprendre comment les entrepreneurs utilisent des apprentis dans le cadre de contrats fédéraux de construction et d'entretien et pourraient éclairer l'élaboration, dans l'avenir, de nouvelles politiques et de nouveaux programmes.
5. L'entrepreneur atteste ce qui suit :

En vue de contribuer à la satisfaction de la demande en travailleurs qualifiés, l'entrepreneur convient de déployer et d'exiger de ses sous-traitants qu'ils déploient des efforts commerciaux raisonnables pour embaucher et former des apprentis inscrits, de s'efforcer d'utiliser pleinement les ratios compagnon/apprenti \* autorisés et de respecter toutes les exigences liées à l'embauche prescrites dans les lois provinciales et territoriales.

L'entrepreneur consent, par la présente, à ce que cette information soit recueillie et conservée par TPSGC et Emploi et Développement social Canada en vue d'appuyer la compilation de données sur l'embauche et la formation d'apprentis dans le cadre de contrats fédéraux de construction et d'entretien.

Pour appuyer cette initiative, une attestation volontaire signalant que le fournisseur s'engage à embaucher et former des apprentis est disponible à l'APPENDICE 4.

Si vous acceptez, veuillez compléter et apposer votre signature à l'APPENDICE 4.

*\* Le ratio compagnon/apprenti, c'est le nombre de compagnons qualifiés/agrérés qu'un employeur doit employer dans une profession ou un métier désigné afin d'être admissible à inscrire un apprenti conformément à la législation, aux règlements, aux directives d'orientation ou aux arrêtés provinciaux/territoriaux émis par les autorités ou les organismes responsables.*

Solicitation No. - N° de l'invitation  
ED001-180814/A  
Client Ref. No. - N° de réf. du client  
ED001-180814

Amd. No. - N° de la modif.  
File No. - N° du dossier

Buyer ID - Id de l'acheteur  
PWC010  
CCC No./N° CCC - FMS No/ N° VME

## IP11 SITES WEB

La connexion à certains des sites Web se trouvant aux documents d'appel d'offres est établie à partir d'hyperliens. La liste suivante énumère les adresses de ces sites Web.

Appendice L du Conseil du Trésor, Compagnies de cautionnement reconnues  
<http://www.tbs-sct.gc.ca/pol/doc-fra.aspx?id=14494&section=text#appL>

Achats et ventes <https://achatsetventes.gc.ca/>

Sanctions économiques canadiennes <http://www.international.gc.ca/sanctions/index.aspx?lang=fra>

Rapport d'évaluation du rendement de l'entrepreneur (Formulaire PWGSC-TPSGC 2913)  
<http://www.tpsgc-pwgsc.gc.ca/app-acq/forms/documents/2913.pdf>

Cautionnement de soumission (formulaire PWGSC-TPSGC 504)  
<http://www.tpsgc-pwgsc.gc.ca/app-acq/forms/documents/504.pdf>

Cautionnement d'exécution (formulaire PWGSC-TPSGC 505)  
<http://www.tpsgc-pwgsc.gc.ca/app-acq/forms/documents/505.pdf>

Cautionnement pour le paiement de la main-d'œuvre et des matériaux (formulaire PWGSC-TPSGC 506)  
<http://www.tpsgc-pwgsc.gc.ca/app-acq/forms/documents/506.pdf>

Guide des clauses et conditions uniformisées d'achats (CCUA) <https://achatsetventes.gc.ca/politiques-et-lignes-directrices/guide-des-clauses-et-conditions-uniformisees-d-achat/5/R>

Services de sécurité industrielle <http://ssi-iss.tpsgc-pwgsc.gc.ca/index-fra.html>

TPSGC, Code de conduite pour l'approvisionnement <http://www.tpsgc-pwgsc.gc.ca/app-acq/cndt-cndct/contexte-context-fra.html>

TPSGC, Formulaires relatifs à l'administration des contrats de construction et de services d'experts-conseils  
<http://www.tpsgc-pwgsc.gc.ca/app-acq/forms/formulaires-forms-fra.html>

Formulaire de déclaration  
<http://www.tpsgc-pwgsc.gc.ca/ci-if/formulaire-form-fra.html>



## CONDITIONS SUPPLÉMENTAIRES (CS)

### CS01 CONDITIONS D'ASSURANCE

- 1) Polices d'assurance
  - a) L'entrepreneur souscrit et maintient, à ses propres frais, les polices d'assurance conformément aux exigences de l'Attestation d'assurance. L'assurance doit être souscrite auprès d'un assureur autorisé à faire affaire au Canada.
  - b) Le respect des exigences en matière d'assurance ne dégage pas l'entrepreneur de sa responsabilité en vertu du contrat, ni ne la diminue. L'entrepreneur est responsable de décider si une assurance supplémentaire est nécessaire pour remplir ses obligations en vertu du contrat et pour se conformer aux lois applicables. Toute assurance supplémentaire souscrite est à la charge de l'entrepreneur ainsi que pour son bénéfice et sa protection.
- 2) Période d'assurance
  - a) Les polices exigées à l'Attestation d'assurance doivent prendre effet le jour de l'attribution du contrat et demeurer en vigueur pendant toute la durée du contrat.
  - b) Il incombe à l'entrepreneur de fournir et de maintenir la couverture pour produits/travaux complétés de sa police d'assurance responsabilité civile des entreprises et ce pour un délai minimum de (6) six ans suivant la date du Certificat d'achèvement substantiel.
- 3) Preuve d'assurance
  - a) Avant le début des travaux, et au plus tard trente (30) jours après l'acceptation de sa soumission, l'entrepreneur doit remettre au Canada une Attestation d'assurance sur le formulaire fournis.
  - b) À la demande du Canada, l'entrepreneur doit fournir les originaux ou les copies certifiées de tous les contrats d'assurance auxquels l'entrepreneur a souscrit conformément à l'Attestation d'assurance.
- 4) Indemnités d'assurance

En cas de sinistre, l'entrepreneur doit faire sans délai toutes choses et exécuter tous documents requis pour le paiement de l'indemnité d'assurance.
- 5) Franchise

L'entrepreneur doit assumer le paiement de toutes sommes d'argent en règlement d'un sinistre, jusqu'à concurrence de la franchise.

### CS04 AJUSTEMENT DU PRIX DU BITUME

Non applicable

## **CS05 ÉVALUATION DU RENDEMENT-CONTRAT**

La Condition générale CG1.22 est ajouté à la clause R2810D

### **CG1.22 Évaluation du rendement– contrat**

1. Les entrepreneurs doivent prendre note que le rendement de l'entrepreneur pendant et après la prestation des services sera évalué par le Canada. L'évaluation sera basée sur les critères suivants:
  - a. qualité des travaux exécutés.
  - b. délais d'exécution
  - c. gestion de projet
  - d. gestion du contrat
  - e. santé et sécurité
2. Un facteur de pondération de 20 points est attribué à chacun des cinq critères comme suit:
  - a. inacceptable: 0 à 5 points
  - b. non satisfaisant: 6 à 10 points
  - c. satisfaisant: 11 à 16 points
  - d. supérieur: 17 à 20 points
3. Les conséquences découlant de l'évaluation du rendement sont les suivantes :
  - a. Pour une cote globale de 85 p. 100 ou plus, une lettre de félicitation est envoyée à l'entrepreneur.
  - b. Pour une cote globale entre 51 p. 100 et 84 p. 100, une lettre type rencontre les attentes est envoyée à l'entrepreneur.
  - c. Pour une cote globale entre 30 p. 100 et 50 p. 100, une lettre d'avertissement est envoyée à l'entrepreneur indiquant que si, au cours des deux (2) prochaines années, sa cote de rendement est de 50 p. 100 ou moins sur une autre évaluation, la firme pourrait être suspendue de toute nouvelle invitation à soumissionner de TPSGC pour des services de construction, des services d'architecture et de génie ou des services d'entretien des installations, de projets immobiliers, pour une période d'un an.
  - d. Pour une cote globale de moins de 30 p. 100, une lettre de suspension est envoyée à l'entrepreneur indiquant que la firme est suspendue de toute nouvelle invitation à soumissionner de TPSGC pour des services de construction, des services d'architecture et de génie ou des services d'entretien des installations, de projets immobiliers, pour une période d'un an.
  - e. Pour une cote de 5 points ou moins pour un critère, une lettre de suspension est envoyée à l'entrepreneur indiquant que la firme est suspendue de toute nouvelle invitation à soumissionner de TPSGC pour des services de construction, des services d'architecture et de génie ou des services d'entretien des installations, de projets immobiliers, pour une période d'un an.

Le formulaire PWGSC-TPSGC 2913, Select - Formulaire du rapport d'évaluation du rendement de l'entrepreneur (FRERE), est utilisé pour évaluer le rendement.

## **CS06 INTERPRÉTATION**

La Condition générale CG1.1.2 de la clause R2810D est modifié pour inclure les nouvelles terminologies suivantes

- « Services d'architecture et de génie » :  
services pour fournir une gamme de rapports d'enquêtes et de recommandations, la planification, la conception, la préparation ou la supervision de travaux de construction, de réparation, de rénovation ou de restauration et inclut les services de gestion de contrats, de projets immobiliers.
- « Services de construction » :  
la construction, la réparation, la rénovation ou la restauration d'un ouvrage à l'exception d'un navire et qui comprend; la fourniture et l'érection d'une structure préfabriquée; le dragage; la démolition; les services environnementaux liés à un bien immobilier; ou, la location d'outillage destiné directement ou indirectement à l'exécution des services de construction mentionnés ci-dessus.
- « Services d'entretien d'installations » :  
services liés aux activités normalement associées à l'entretien d'une installation et le maintien des espaces, des structures et des infrastructures en bon état de fonctionnement, d'une manière routinière, prévue ou anticipée pour éviter la défaillance et / ou la dégradation, incluant des services d'inspections, d'essais, d'entretien, de classification quant à l'état de fonctionnement, de réparations, de reconstruction et de remise en état, ainsi que la fourniture de services d'entretien ménager, d'enlèvement des déchets, de déneigement, d'entretien des pelouses, de remplacement des revêtements de sol, d'appareils d'éclairage ou de plomberie, de peinture, et autres petits travaux.

## DOCUMENTS DU CONTRAT (DC)

1. Les documents suivants constituent le contrat:
  - a. Page « Contrat » une fois signée par le Canada;
  - b. Formulaire de soumission et d'acceptation et tout Appendice s'y rattachant rempli(s) en bonne et due forme;
  - c. Dessins et devis;
  - d. Conditions générales et clauses:

CG1	Dispositions générales – Services de construction	R2810D	(2016-04-04);
CG2	Administration du contrat	R2820D	(2016-01-28);
CG3	Exécution et contrôle des travaux	R2830D	(2015-02-25);
CG4	Mesures de protection	R2840D	(2008-05-12);
CG5	Modalités de paiement	R2850D	(2016-01-28);
CG6	Retards et modifications des travaux	R2860D	(2016-01-28);
CG7	Défaut, suspension ou résiliation du contrat	R2870D	(2008-05-12);
CG8	Règlement des différends	R2880D	(2016-01-28);
CG9	Garantie contractuelle	R2890D	(2014-06-26);
CG10	Assurances	R2900D	(2008-05-12);
	Coûts admissibles pour les modifications de contrat sous CG6.4.1	R2950D	(2015-02-25);
	Conditions supplémentaires		
  - e. Toute modification émise ou toute révision de soumission recevable, reçue avant l'heure et la date déterminée pour la clôture de l'invitation;
  - f. Toute modification incorporée d'un commun accord entre le Canada et l'entrepreneur avant l'acceptation de la soumission; et
  - g. Toute modification aux documents du contrat qui est apportée conformément aux conditions générales.
2. Les documents identifiés par titre, numéro et date ci-dessus sont intégrés par renvoi et sont reproduits dans le Guide des clauses et conditions uniformisées d'achat (CCUA) publié par Travaux publics et Services gouvernementaux Canada (TPSGC). Le guide des CCUA est disponible sur le site Web de TPSGC: <https://achatsetventes.gc.ca/politiques-et-lignes-directrices/guide-des-clauses-et-conditions-uniformisees-d-achat/5/R>
3. La langue des documents du contrat est celle du Formulaire de soumission et d'acceptation présenté.

Solicitation No. - N° de l'invitation  
ED001-180814/A  
Client Ref. No. - N° de réf. du client  
ED001-180814

Amd. No. - N° de la modif.  
File No. - N° du dossier

Buyer ID - Id de l'acheteur  
PWC010  
CCC No./N° CCC - FMS No/ N° VME

## FORMULAIRE DE SOUMISSION ET D'ACCEPTATION (SA)

### SA01 IDENTIFICATION DU PROJET

**Bâtiment Joseph A Ghiz,  
Remplacement du revêtement de sol  
275 chemin Pope  
Summerside (île-du-Prince-Édouard)**

### SA02 NOM COMMERCIAL ET ADRESSE DU SOUMISSIONNAIRE

Nom: \_\_\_\_\_

Adresse: \_\_\_\_\_

Téléphone: \_\_\_\_\_ Télécopieur: \_\_\_\_\_ NEA \_\_\_\_\_

Adresse courriel : \_\_\_\_\_

Le Numéro d'organisation du Programme de sécurité industrielle \_\_\_\_\_  
(si requis)

### SA03 OFFRE

Le soumissionnaire offre au Canada d'exécuter les travaux du projet mentionné ci-dessus, conformément aux documents de soumission pour le montant total de la soumission de

\_\_\_\_\_ \$ excluant les taxe(s) applicables.  
(exprimé en chiffres)

### SA04 PÉRIODE DE VALIDITÉ DES SOUMISSIONS

La soumission ne peut être retirée pour une période de trente (30) jours suivant la date de clôture de l'invitation.

### SA05 ACCEPTATION ET CONTRAT

À l'acceptation de l'offre de l'entrepreneur par le Canada, un contrat exécutoire est formé entre le Canada et l'entrepreneur. Les documents constituant le contrat sont ceux mentionnés aux Documents du contrat.

### SA06 DURÉE DES TRAVAUX

L'entrepreneur doit effectuer et achever les travaux pour le 1 décembre 2017.

### SA07 GARANTIE DE SOUMISSION

Le soumissionnaire joint à sa soumission une garantie de soumission conformément à l'IG08 - Exigences relatives à la garantie de soumission de la R2710T -Instructions générales - Services de construction - Exigences relatives à la garantie de soumission

### SA08 SIGNATURE

\_\_\_\_\_  
Nom et titre de la personne autorisée à signer au nom du soumissionnaire (Tapés ou lettres moulées)

\_\_\_\_\_  
Signature

\_\_\_\_\_  
Date



Solicitation No. - N° de l'invitation  
ED001-180814/A  
Client Ref. No. - N° de réf. du client  
ED001-180814

Amd. No. - N° de la modif.  
File No. - N° du dossier

Buyer ID - Id de l'acheteur  
PWC010  
CCC No./N° CCC - FMS No/ N° VME

## APPENDICE 2 - LISTE DES SOUS-TRAITANTS

- 1) Conformément à la clause IG07 – Liste des sous-traitants et fournisseurs des Instructions générales - Services de construction - Exigences relatives à la garantie de soumission R2710T, le soumissionnaire devrait accompagner sa soumission d'une liste de sous-traitants.
- 2) Le soumissionnaire devrait soumettre la liste des sous-traitants pour toute partie des travaux dont la valeur équivaut à au moins 20 % du prix soumissionné.

	Sous-traitant	Division	Valeur estimative des travaux
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			

Solicitation No. - N° de l'invitation  
ED001-180814/A  
Client Ref. No. - N° de réf. du client  
ED001-180814

Amd. No. - N° de la modif.  
File No. - N° du dossier

Buyer ID - Id de l'acheteur  
PWC010  
CCC No./N° CCC - FMS No/ N° VME

### APPENDICE 3 - ATTESTATION VOLONTAIRE À L'APPUI DU RECOURS AUX APPRENTIS

*Avis; L'entrepreneur sera appelé à compléter à tous les six mois ou à la fin des travaux un rapport tel qu'inclus à l'annexe C « Rapport volontaire d'apprentis employés pendant les contrats ».*

Nom: \_\_\_\_\_

Signature: \_\_\_\_\_

Nom de la compagnie: \_\_\_\_\_

Dénomination sociale: \_\_\_\_\_

Numéro de l'invitation à soumissionner: \_\_\_\_\_

Nombre d'employés de l'entreprise: \_\_\_\_\_

Nombre planifié d'apprentis qui travailleront sur ce contrat: \_\_\_\_\_

Métiers spécialisés de ces apprentis;

---

---

---

---

---

---

---

---



Solicitation No. - N° de l'invitation  
ED001-180814/A  
Client Ref. No. - N° de réf. du client  
ED001-180814

Amd. No. - N° de la modif.  
File No. - N° du dossier

Buyer ID - Id de l'acheteur  
PWC010  
CCC No./N° CCC - FMS No/ N° VME

## ANNEXE A - ATTESTATION D'ASSURANCE



Travaux publics et  
Services gouvernementaux  
Canada

Public Works and  
Government Services  
Canada

## ATTESTATION D'ASSURANCE

Page 1 de 2

Description et emplacement des travaux <b>Bâtiment Joseph A Ghiz, Remplacement du revêtement de sol, 275 chemin Pope, Summerside (île-du-Prince-Édouard)</b>	N° de contrat. ED001-180814
	N° de projet R.086476.001

Nom de l'assureur, du courtier ou de l'agent	Adresse (N°, rue)	Ville	Province	Code postal
Nom de l'assuré (Entrepreneur)	Adresse (N°, rue)	Ville	Province	Code Postal
Assuré additionnel <b>Sa majesté la Reine du chef du Canada représentée par le Ministre des Travaux publics et des Services gouvernementaux</b>				

Genre d'assurance	Compagnie et N° de la police	Date d'effet J / M / A	Date d'expiration J / M / A	Plafonds de garantie		
<b>Responsabilité civile des entreprises</b> <b>Responsabilité complémentaire/exc édentaire.</b>				Par sinistre	Global général annuel	Global - Risque après travaux
				\$	\$	\$
				\$	\$	\$

J'atteste que les polices ci-dessus ont été émises par des assureurs dans le cadre de leurs activités d'assurance au Canada et que ces polices sont présentement en vigueur, comprennent les garanties et dispositions applicables de la page 2 de l'Attestation d'assurance, incluant le préavis d'annulation ou de réduction de garantie.

Nom de la personne autorisée à signer au nom de(s) (l')assureur(s) (Cadre, agent, courtier)

Numéro de téléphone

Signature

Date J / M / A

Solicitation No. - N° de l'invitation  
ED001-180814/A  
Client Ref. No. - N° de réf. du client  
ED001-180814

Amd. No. - N° de la modif.  
File No. - N° du dossier

Buyer ID - Id de l'acheteur  
PWC010  
CCC No./N° CCC - FMS No/ N° VME

## ATTESTATION D'ASSURANCE Page 2 de 2

### Généralités

Les polices exigées à la page 1 de l'Attestation d'assurance doivent être en vigueur et doivent inclure les garanties énumérées sous le genre d'assurance correspondant de cette page-ci.

Les polices doivent assurer l'entrepreneur et doivent inclure, en tant qu'assuré additionnel, Sa majesté la Reine du chef du Canada représentée par le Ministre des Travaux publics et des Services gouvernementaux.

Les polices d'assurance doivent comprendre un avenant prévoyant la transmission au Canada d'un préavis écrit d'au moins trente (30) jours en cas d'annulation de l'assurance ou de toute réduction de la garantie d'assurance.

Sans augmenter la limite de responsabilité, la police doit couvrir toutes les parties assurées dans la pleine mesure de la couverture prévue.

De plus, la police doit s'appliquer à chaque assuré de la même manière et dans la même mesure que si une police distincte avait été émise à chacun d'eux.

### Responsabilité civile des entreprises

La garantie d'assurance fournie ne doit pas être substantiellement inférieure à la garantie fournie par la dernière publication du formulaire BAC 2100.

La police doit inclure ou avoir un avenant pour l'inclusion d'une garantie pour les risques et dangers suivants si les travaux y sont assujettis :

- a) Dynamitage.
- b) Battage de pieux et travaux de caisson.
- c) Reprise en sous-œuvre.
- d) Enlèvement ou affaiblissement d'un support soutenant toute structure ou terrain, que ce support soit naturel ou non, si le travail est exécuté par l'entrepreneur assuré.

La police doit comporter:

- a) un « Plafond par sinistre » d'au moins **5 000 000 \$**;
- b) un « Plafond global général » d'au moins **10 000 000 \$** par année d'assurance, si le contrat d'assurance est assujetti à une telle limite.
- c) un « Plafond pour risque produits/après travaux » d'au moins **5 000 000 \$**.

Une assurance responsabilité complémentaire ou excédentaire peut être utilisée pour atteindre les plafonds obligatoires.

Solicitation No. - N° de l'invitation  
ED001-180814/A  
Client Ref. No. - N° de réf. du client  
ED001-180814

Amd. No. - N° de la modif.  
File No. - N° du dossier

Buyer ID - Id de l'acheteur  
PWC010  
CCC No./N° CCC - FMS No/ N° VME

## **ANNEXE B - RAPPORT VOLONTAIRE D'APPRENTIS EMPLOYÉS PENDANT LES CONTRATS (exemple)**

*(Ce rapport volontaire n'est pas requis lors du dépôt de soumission)*

L'entrepreneur devrait compiler et tenir à jour des données sur le nombre d'apprentis ayant été embauchés pour travailler sur le contrat, ainsi que leur métier spécialisé.

L'entrepreneur devrait fournir ces données conformément au format ci-dessous. Si aucun apprenti n'a été embauché pendant la durée du contrat, l'entrepreneur devrait soumettre un rapport portant la mention « néant ».

Les données devraient être présentées à l'autorité contractante au plus tard six mois après l'octroi du contrat ou à la fin du contrat, selon la première éventualité.

<b>Nombre d'apprentis embauchés</b>	<b>Métier spécialisé</b>

(Ajouter des lignes au besoin)

Solicitation No. - N° de l'invitation  
ED001-180814/A  
Client Ref. No. - N° de réf. du client  
ED001-180814

Amd. No. - N° de la modif.  
File No. - N° du dossier

Buyer ID - Id de l'acheteur  
PWC010  
CCC No./N° CCC - FMS No/ N° VME

## **ANNEXE C – SPÉCIFICATIONS**

<u>Section Number</u>	<u>Section Name</u>	<u>Number of Pages</u>
01 14 10	Scheduling	7
01 33 00	Submittal Procedures	4
01 35 29	Health and Safety	9
01 35 43	Environmental Procedures	2
01 45 00	Testing	2
01 50 00	Temporary Facilities	4
01 61 00	Common Product Requirements	2
01 74 11	Cleaning	2
01 74 21	Waste Management	2
01 77 00	Closeout Procedures	1
01 78 00	Closeout Submittals	4
02 41 16	Demolition	3
09 30 13	Ceramic Tiling	6
09 65 99	Resilient Flooring	7

END OF SECTION

1.1. SUBMITTALS

- .1 Upon acceptance of bid and prior to commencement of work, submit to Departmental Representative the following work management documents:
  - .1 Work Schedule as specified herein.
  - .2 Security Requirements as specified herein.
  - .3 Shop Drawing Submittal Schedule specified in section 01 33 00.
  - .4 Health and Safety Plan specified in section 01 35 29.
  - .5 Environmental Plan specified in section 01 35 43.
  - .6 Temporary Facilities and Controls 01 50 00.
  - .7 Dust Control Plan specified in section 01 50 00.
  - .8 Waste Management Plan specified in section 01 74 21.

1.2. WORK SCHEDULE

- .1 Upon acceptance of bid submit:
  - .1 Work schedule within 14 calendar days of contract award.
- .2 Schedule to indicate all calendar dates from commencement to completion of all work within the time stated in the contract.
- .3 Provide sufficient details in schedule to clearly illustrate entire implementation plan, depicting efficient coordination of tasks and resources, to achieve completion of work on time and permit effective monitoring of work progress in relation to established milestones.
- .4 Preliminary work schedule content to include as a minimum the following:
  - .1 Bar (GANTT) Charts, indicating all work activities, tasks and other project elements, their anticipated durations, planned dates for achieving key activities and major project milestones supported with;
  - .2 Written narrative on key elements of work illustrated in bar chart, providing sufficient details to demonstrate a reasonable implementation plan for completion of project within time stated in contract.
  - .3 Bar Charts derived from commercially available computerized project management system are preferred but not mandatory.
- .5 Work schedule must take into consideration and reflect the required sequence of work, special conditions and operational restrictions as specified below and indicated on drawings.
- .6 Schedule work in cooperation with the Departmental Representative.
- .7 Completed schedule shall be approved by Departmental Representative. When approved, take necessary measures to complete work within scheduled time. Do not change schedule without Departmental Representative's approval.
- .8 Ensure that all subtrades and subcontractors are made aware of the work restraints and

operational restrictions specified in section 01 14 10.1.3.

- .9 Schedule Updates:
  - .1 Provide information and pertinent details explaining reasons for necessary changes to implementation plan.
  - .2 Identify problem areas, anticipated delays, impact on schedule and proposed corrective measures to be taken.
- .10 Departmental Representative will make interim reviews and evaluate progress of work based on approved schedule. Frequency of such reviews will be as decided by Departmental Representative. Address and take corrective measures on items identified by reviews and as directed by Departmental Representative. Update schedule accordingly.
- .11 In every instance, change or deviation from the Work Schedule, no matter how minimal the risk or impact on safety or inconvenience to tenant or public might appear, will be subject to prior review and approval by the Departmental Representative.

### 1.3. PROJECT PHASING

- .1 *Be aware that, other than portion of Dining Area identified in this Section, Facility must be kept operational for the full duration of work of this contract. Building services to areas under use by tenants must also be maintained at all times during the Facility's operational hours and as specifically defined in operational restrictions specified in this section.*
- .2 *Perform Work of this contract in two individual phases as indicated in the phasing drawings and in the following sequence of activities:*
  - .1 *Phase 1 Lobby (REF: Detail 2-A1):*
    - .1 *Relocate security desk temporarily to location shown on drawings for Phase 1 of flooring replacement.*
    - .2 *Provide hoarding and dust control in Lobby as indicated on drawings.*
    - .3 *Temporarily relocate existing furniture and equipment out of work area.*
    - .4 *Maintain access to Security Office for security personnel.*
    - .5 *Remove existing flooring, base and other items as indicated in drawings.*
    - .6 *Advise Departmental Representative of completion of Work to date in order to allow for potential installation of conduit for security/access system (N.I.C.). Work is NOT to recommence before written authorization from the Departmental Representative.*
    - .7 *Once written confirmation to continue is granted, complete surface preparation, installation of new materials and any necessary repairs.*
    - .8 *Reinstall millwork, furniture and equipment.*
  - .2 *Phase 2 Lobby (REF: Detail 3-A1):*
    - .1 *Relocate hoarding and dust control in lobby to access remaining floor area to be replaced.*
    - .2 *Re-install security desk in original location.*
    - .3 *Temporarily relocate existing furniture and equipment out of work area.*
    - .4 *Remove existing flooring, base and other items as indicated in drawings.*
    - .5 *Advise Departmental Representative of completion of Work to date in*

*order to allow for potential installation of conduit for security/access system (N.I.C.). Work is NOT to recommence before written authorization from the Departmental Representative.*

- .6 Once written confirmation to continue is granted, complete surface preparation, installation of new materials and any necessary repairs.*
- .7 Reinstall millwork, furniture and equipment.*
- .3 Coordinate all activities with Departmental Representative's to ensure minimum disruption to tenants.*
- .4 Work performed in the Dining Area can run concurrent with work in Lobby, but must adhere to all operational restrictions noted in the Specifications and Drawings. Dining area is permitted to be divided into sections with hoarding/dust control (and hoarding is permitted to remain in place during hours of operation) in order to perform Work, but must not be reduced in size more than 50% of its total area at any given time: at least 50% of the space must remain accessible to Building Occupants at all times.*

#### 1.4. OPERATIONAL RESTRICTIONS

- .1 The Contractor must recognize that building occupants will be affected by implementation of this Contract. The Contractor must perform the work with utmost regard to the safety and convenience of building occupants and users. All work activities must be planned and scheduled with this in mind. The Contractor will not be permitted to disturb any portion of the building during operational hours.
- .2 Contractor to meet with the Departmental Representative on a weekly basis to identify intended work areas, activities and scheduling for the coming week.
- .3 To assure that construction work may proceed productively without risk to safety of building occupants and the public, and due to the nature of the tenant's operation be aware that all work included in this contract must be carried out during "Off Hours".
- .4 Off Hours: means a period of time which is outside the daily operational hours of the tenants of the Facility. For the purposes of this contract, Off-Hours are defined as follows:
  - .1 Weeknight Off-Hours: between the hours of 12:00 am and 06:00 am for each weekday Monday to Thursday inclusive.
    - .1 Quiet, non-invasive or set-up work will be permitted to commence at 04:00 pm each evening with written approval from Departmental Representative. This work is subject to strict limitations regarding sound, dust, odours, and any other disturbance to tenants.
  - .2 Weekend Off-Hours: between the hours of 12:00 am Saturday Morning to 06:00 am Monday morning.
  - .3 Statutory holidays observed by the tenants: Work can be performed with prior written approval from Departmental Representative.
- .5 Work undertaken Off-Hours must be completed and returned to a clean, clear and usable state for any period of use by the tenants. Tenants must not be affected in any way by the ongoing work. All paths of travel must be free of flooring height changes and shall be



completed works. No temporary access materials to be used while tenants are at work.

- .6 The following work, to be performed during Off-Hours, includes but is not limited to:
  - .1 Erection and dismantling of dust barriers, hoarding or other protective devices to separate areas of Facility occupied and under use by public and tenants from work areas (this may be permitted after 4:00 pm with the approval of the Departmental Representative, as noted above);
  - .2 Demolition of any masonry or concrete inside building;
  - .3 All work involving saw cutting or boring of openings through masonry and concrete walls, floors, ceilings or roof;
  - .4 Work which requires the use of products controlled by WHMIS and for which MSDS sheets indicate toxic or hazardous materials requiring special handling and application procedures;
  - .5 Use of materials having high solvent content or other content emitting strong noxious fumes or odours;
  - .6 Painting or repainting;
  - .7 Removal of demolition debris from the building including cleaning of premises;
  - .8 Cleaning and preparing of occupied areas for daytime use by tenants immediately following an off-hour workshift;
  - .9 Work to be limited to construction areas.;
  - .10 Work which requires the temporary disconnection of power and communication services to occupied areas. All life safety systems shall be operational at all times;
  - .11 Delivery of materials and equipment from exterior to the interior of building when access routes are located in tenant occupied spaces.
  - .12 Work which creates excessive noise or vibration creating interference with tenant operations.
- .7 Ensure that all sub-contractors are aware of the "Off-Hour" requirements of this Contract and ensure that any extra costs incurred as a result is included in the Contractor's bid amount for the work. No extra cost will be paid due to failure by General Contractor or his sub-contractors to recognize the off-hour requirements and other restrictions specified herein and to include all necessary allowances within their bids.
- .8 Security Requirements:
  - .1 Special security requirements which must be observed in the course of work:
    - .1 Provision of security personnel and Commissionaire by Contractor.
    - .2 List of workers requiring security clearance and those to be placed on Site Security Control list to be coordinated with Departmental Representative.
- .9 Facility circulation maintained:
  - .1 Ensure that entrances, corridors, stairwells, fire exits and other circulation routes are maintained free and clear providing safe and uninterrupted passage for Facility users and public at all times during the entire work.
  - .2 Maintain those areas clean and free of construction materials and equipment. Provide temporary dust barriers and other suitable enclosures to ensure users and unaffected areas of the building are not exposed to construction activities and are protected from exposure to dust, noise and hazardous conditions.

- .3 Maintain fire escape routes accessible and fire fighting access open all times for the duration of the project.
- .4 Do not under any circumstances block fire exit doors. Do not leave construction materials or debris in corridors, stairwells building entrances and exits.
- .10 Safety Signage:
  - .1 Provide on site, and erect as required during progress of work, proper bilingual signage, mounted on self-supporting stands, warning the public and building occupants of construction activities in progress and alerting need to exercise caution near facility.
  - .2 Signage to be professionally printed and mounted on wooden backing, coloured and to express messages as directed by the Departmental Representative.
  - .3 Generally maximum size of sign should be in the order of 1.0 square meters. Number of signs required will be dependent on number of areas in facility under renovation at any one time.
  - .4 Include costs for the supply and installation of these signs in the bid amount.
- .11 Dust and Dirt Control:
  - .1 See section 01 50 00 and 01 74 11 for dust control and cleaning requirements.
  - .2 Effectively plan and implement dust control measures and cleaning activities as an integral part of all construction activities. Review all measures with the Departmental Representative before undertaking work, especially for major dust generating activities.
  - .3 Discuss and obtain Departmental Representative's approval beforehand on the type and extent of dust barriers, protective devices and measures needed.
  - .4 Provide temporary dust barriers around immediate work areas and place fabric drop sheets over workstations, equipment and other furnishings located immediately adjacent to such work.
  - .5 Be responsible for temporarily moving office furnishings, workstations, millwork, computer equipment and other objects as needed to gain access and conduct work. Reinstall all dislocated items as directed by drawings or Departmental Representative. Any damage during removal shall be reinstated at the cost of the contractor.
  - .6 Disconnect and reconnect any power and communications systems feeding workstations as required.
  - .7 Conduct work in such a way as to minimize the creation of dust and to avoid contaminating areas beyond the immediate location.
  - .8 Do not allow demolition debris and construction waste to accumulate on site and contribute to the propagation of dust.
  - .9 As work progresses, maintain construction areas in a tidy condition at all times. Remove gross dust accumulations by cleaning and vacuuming immediately following the completion of any major dust generating activity.
  - .10 Immediately remove all debris and dust from within occupied areas as generated by work therein during a given work shift.
  - .11 Provide mechanical means for evacuating airborne dust or fumes from contained site prior to removal of dust barriers.

- .12 Disconnect and seal-off ductwork of HVAC servicing the construction area to stop spread of dust or fumes into other areas of Facility.
  - .13 Avoid situations and practices which results in dust and dirt being brought from the construction areas inside the building into occupied areas used by tenants and the public.
  - .14 Inform workers and make them sensitive to the need for dust and dirt control. Stringently enforce rules and regulations, immediately address non-compliance.
  - .15 Keep access doors to work areas closed at all times. Use only designated doors for entry or egress.
  - .16 **Ensure that all dust, dirt, debris, construction waste, materials, tools and equipment are completely removed at the end of each "off-hour" workshift. Clean and reinstate area ready for daytime use by tenant.**
- .12 Cleaning of tenant occupied areas used by Contractor:
- .1 Clean lobbies, corridors, stairs and other circulation routes used by workers to gain access to work by conducting cleaning, vacuuming and washing of floors, walls and other soiled surfaces.
  - .2 Meager attempts at controlling dust and ineffective unprofessional cleaning procedures will not be tolerated.
  - .3 Failure to provide effective dust control, allowing construction dust and dirt to escape beyond construction areas and contaminate occupied areas and building circulation areas will result in Contractor being ordered to immediately provide professional cleaning services without delay to remedy the situation and conduct all cleaning to the extent as determined by Departmental Representative. Alternatively, Departmental Representative may, at certain times and at own discretion, obtain the services of an independent building cleaning agency when cleaning being provided by Contractor is ineffective or tardy in response. Costs of such services will be charged against Contractor in the form of financial penalties or holdback assessments against the Contract.
- .13 **Smoking is not permitted on the property at any time and will be cause for immediate dismissal.**
- .14 **Ensure that all sub-trades are made aware of and abide by the contents of this section and in particularly the work restrictions specified herein due to tenant operational requirements.**

1.5. PROJECT MEETINGS

- .1 Attend project meetings scheduled and administered by Departmental Representative, held on a minimum weekly basis, for entire duration of work and more often as deemed necessary due to progress of work or particular situation.
- .2 Communicate items to be included in agenda for meetings to Departmental Representative.
- .3 Participants will be notified in writing 4 days in advance of meeting date.
  - .1 Ensure attendance of all subcontractors.

- .4 Location of meetings will be coordinated by Departmental Representative.
- .5 Departmental Representative will arrange project meetings and assume responsibility for setting times and recording minutes. Minutes will:
  - .1 Include significant proceedings and decisions. Action items by parties.
  - .2 Be distributed to participants by email or by facsimile within 3 calendar days after each meeting.
  - .3 Be revised if necessary.

1.6. WORK COORDINATION

- .1 General Contractor is responsible for coordinating the work of the various trades and predetermining where the work of such trades interfaces with each other.
  - .1 Designate one person from own employ having overall responsibility to review contract documents and shop drawings, plan and manage such coordination.
- .2 General Contractor shall convene meetings between trades whose work interfaces and ensure that they are fully aware of the areas and the extent of where interfacing is required.
  - .1 Provide each trade with the plans and specs of the interfacing trade, as required, to assist them in planning and carrying out their respective work.
- .3 Submission of shop drawings and ordering of prefabricated equipment or prebuilt components shall only occur once coordination meeting for such items has taken place between trades and all conditions affecting the work of the interfacing trades has been made known and accounted for.
- .4 Work Cooperation:
  - .1 Ensure cooperation between trades in order to facilitate the general progress of the work and avoid situations of spatial interference.
  - .2 Ensure that each trade provides all other trades reasonable opportunity for the completion of the work and in such a way as to prevent unnecessary delays, cutting, patching and the need to remove and replace completed work.
- .5 No extra costs to the Contract will be considered by the Departmental Representative as a result of Contractor's failure to effectively coordinate all portions of the Work. Disputes between the various trades as a result of their not being informed of the areas and extent of interface work shall be the sole responsibility of the General Contractor to be resolved at own cost.

END OF SECTION

1.1. RELATED SECTIONS

- .1 Section 01 78 00: Closeout Submittals.

1.2. SUBMITTAL GENERAL REQUIREMENTS

- .1 Submit to Departmental Representative for review requested submittals specified in various sections of the specifications including shop drawings, samples, permits, compliance certificates, test reports, work management plans and other data required as part of the work.
- .2 Submit with reasonable promptness and in orderly sequence so as to allow for Departmental Representative's review and not cause delay in Work. Failure to submit in ample time will not be considered sufficient reason for an extension of Contract time and no claim for extension by reason of such default will be allowed.
- .3 Do not proceed with work until relevant submissions have been reviewed.
- .4 Present shop drawings, product data, and samples in SI Metric units.
- .5 Where items or information is not produced in SI Metric units, provide soft converted values.
- .6 Review submittals prior to submission. Ensure that necessary requirements have been determined and verified and that each submittal has been checked and co-ordinated with requirements of Work and Contract Documents.
  - .1 Submittals not stamped, signed, dated and identified as to specific project will be returned unexamined by Departmental Representative and considered rejected.
- .7 Verify field measurements and affected adjacent Work are coordinated.
- .8 Notify Departmental Representative, in writing at time of submission, identifying deviations from requirements of Contract Documents stating reasons for deviations.
- .9 Contractor's responsibility for errors, omissions or deviations in submission from requirements of Contract Documents is not relieved by Departmental Representative's review.
- .10 Submittal format:
  - .1 Submit paper originals, or alternatively clear and fully legible photocopies of originals. Facsimiles are not acceptable, except in special circumstances pre-approved by Departmental Representative. Poorly printed non-legible photocopies or facsimiles will not be accepted and be returned for resubmission.
  - .2 Submit in electronic format as pdf files. Forward pdf and in the native program format, MS Word, MS Excel, MS Project and Autocad dwg and photograph jpg files on USB compatible with PWGSC encryption requirements or through email or alternate electronic file sharing service such as ftp, as directed by Departmental Representative.

- .11 Make changes or revision to submissions which Departmental Representative may require, consistent with Contract Documents and resubmit as directed by Departmental Representative. When resubmitting, identify in writing of any revisions other than those requested.
- .12 Keep one reviewed copy of each submittal document on site for duration of Work.

1.3. SHOP DRAWINGS AND PRODUCT DATA

- .1 The term "shop drawings" means fabrication drawings, erection drawings, diagrams, illustrations, schedules, performance charts, technical product data, brochures, specifications, test reports installation instructions and other data which are to be provided by Contractor to illustrate compliance with specified materials and details of a portion of work.
- .2 Shop Drawing Quantities: submit sufficient copies required by the General Contractor and sub-contractors plus (3) copies which will be retained by Departmental Representative.
  - .1 Ensure sufficient copies are submitted to enable one complete set to be included in each of the maintenance manuals specified in 01 78 00.
- .3 Shop Drawings Format:
  - .1 Opaque white prints or photocopies of original drawings or standard drawings modified to clearly illustrate work specific to project requirements. Maximum sheet size to be 1000 x 707 mm.
  - .2 Product Data from manufacturer's standard catalogue sheets, brochures, literature, performance charts and diagrams, used to illustrate standard manufactured products, to be original full colour brochures, clearly marked indicating applicable data and deleting information not applicable to project.
  - .3 Non or poorly legible drawings, photocopies or facsimiles will not be accepted and returned not reviewed.
- .4 Shop Drawings Content:
  - .1 Indicate materials, methods of construction and attachment or anchorage, erection diagrams, connections, explanatory notes and other information necessary for completion of Work. Where items or equipment attach or connect to other items or equipment, confirm that all interrelated work have been coordinated, regardless of section or trade from which the adjacent work is being supplied and installed.
  - .2 Supplement manufacturer's standard drawings and literature with additional information to provide details applicable to project.
  - .3 Delete information not applicable to project on all submittals.
- .5 Allow (7) calendar days for Departmental Representative's review of each submission.

- .6 Adjustments or corrections made on shop drawings by Departmental Representative are not intended to change Contract Amount. If adjustments affect value of Work, advise Departmental Representative in writing prior to proceeding with Work.
- .7 If upon review by Departmental Representative, no errors or omissions are discovered or if only minor corrections and comments are made, fabrication and installation may proceed upon receipt of shop drawings. If shop drawings are rejected and noted to be Resubmitted, do not proceed with that portion of work until resubmission and review of corrected shop drawings, through same submission procedures indicated above.
- .8 Be advised that costs and expenses incurred by Departmental Representative to conduct more than one review of incorrectly prepared shop drawing submittal for a particular material, equipment or component of work may be assessed against the Contractor in the form of a financial holdback to the Contract.
- .9 Accompany each submission with transmittal letter, containing:
  - .1 Date.
  - .2 PWGSC Project title and project number.
  - .3 Contractor's name and address.
  - .4 Identification and quantity of each shop drawing, product data and sample.
  - .5 Other pertinent data.
- .10 Submissions shall include:
  - .1 Date and revision dates.
  - .2 PWGSC Project title and project number.
  - .3 Name and address of:
    - .1 Subcontractor.
    - .2 Supplier.
    - .3 Manufacturer.
  - .4 Contractor's stamp, signed by Contractor's authorized Representative certifying approval of submissions, verification of field measurements and compliance with Contract Documents.
  - .5 Cross references to particular details of contract drawings and specifications section number for which shop drawing submission addresses.
  - .6 Details of appropriate portions of Work as applicable:
    - .1 Fabrication.
    - .2 Layout, showing dimensions, including identified field dimensions, and clearances.
    - .3 Setting or erection details.
    - .4 Capacities.
    - .5 Performance characteristics.
    - .6 Standards.
    - .7 Operating weight.
    - .8 Wiring diagrams.
    - .9 Single line and schematic diagrams.
    - .10 Relationship to adjacent work.

- .11 After Departmental Representative's review, distribute copies.
- .12 The review of shop drawings by the Departmental Representative or by an authorized Consultant or designate is for sole purpose of ascertaining conformance with general concept. This review shall not mean that Canada approves the detail design inherent in the shop drawings, responsibility for which shall remain with Contractor submitting same, and such review shall not relieve Contractor of responsibility for errors or omissions in shop drawings or of responsibility for meeting all requirements of the construction and Contract Documents. Without restricting generality of foregoing, Contractor is responsible for dimensions to be confirmed and correlated at job site, for information that pertains solely to fabrication processes or to techniques of construction and installation and for co-ordination of Work of all sub-trades.

1.2. SAMPLES

- .1 Submit for review samples as specified in respective specification Sections. Label samples with origin and intended use.
- .2 Deliver samples to Departmental Representative's office or to other address as directed. Do not drop off samples at construction site except for pre-approved circumstances previously approved by Departmental Representative.
- .3 Notify Departmental Representative in writing, at time of submission of deviations in samples from requirements of Contract Documents.
- .4 Where colour, pattern or texture is criterion, submit full range of samples.
- .5 Adjustments made on samples by Departmental Representative are not intended to change Contract Amount. If adjustments will result in a cost increase to the Contract notify Departmental Representative in writing prior to proceeding with Work.
- .6 Make changes in samples which Departmental Representative may require, consistent with Contract Documents.
- .7 Reviewed and accepted samples will become standard of workmanship and material against which installed Work will be verified.

END OF SECTION



1.1. DEFINITIONS

- .1 COSH: Canada Occupational Health and Safety Regulations made under Part II of the Canada Labour Code.
- .2 Competent Person: means a person who is:
  - .1 Qualified by virtue of personal knowledge, training and experience to perform assigned work in a manner that will ensure the health and safety of persons in the workplace, and;
  - .2 Knowledgeable about the provisions of occupational health and safety statutes and regulations that apply to the Work and;
  - .3 Knowledgeable about potential or actual danger to health or safety associated with the Work.
- .3 Medical Aid Injury: any minor injury for which medical treatment was provided and the cost of which is covered by Workers' Compensation Board of the province in which the injury was incurred.
- .4 PPE: personal protective equipment.
- .5 Work Site: where used in this section shall mean areas, located at the premises where Work is undertaken, used by Contractor to perform all of the activities associated with the performance of the Work.

1.2. SUBMITTALS

- .1 Make submittals in accordance with Section 01 33 00.
- .2 Submit site-specific Health and Safety Plan prior to commencement of Work.
  - .1 Submit within (14) work days of notification of Bid Acceptance. Allow for 5-10 days for Department review and recommendations prior to the commencement of work. Provide (3) copies.
  - .2 Departmental Representative will review Health and Safety Plan and provide comments.
  - .3 Revise the Plan as appropriate and resubmit within (5) work days after receipt of comments.
  - .4 Departmental Representative's review and comments made of the Plan shall not be construed as an endorsement, approval or implied warranty of any kind by Canada and does not reduce Contractor's overall responsibility for Occupational Health and Safety of the Work.
  - .5 Submit revisions and updates made to the Plan during the course of Work.
- .3 Submit name of designated Health and Safety Site Representative and support documentation specified in the Safety Plan.
- .4 Submit building permit, compliance certificates and other permits obtained.
- .5 Submit copy of Letter in Good Standing from Provincial Workers Compensation or other

Department of Labour organization.

- .1 Submit update of Letter of Good Standing whenever expiration date occurs during the period of Work.
- .6 Submit copies of reports or directions issued by Federal, Provincial and Territorial health and safety inspectors.
- .7 Submit copies of incident reports.
- .8 Submit WHMIS MSDS - Material Safety Data Sheets.

### 1.3. COMPLIANCE REQUIREMENTS

- .1 Comply with Occupational Health and Safety Act for Province of Prince Edward Island, and Occupational Health and Safety Regulations made pursuant to the Act.
- .2 Comply with Canada Labour Code - Part II (entitled Occupational Health and Safety) and the Canada Occupational Health and Safety Regulations as well as any other regulations made pursuant to the Act.
  - .1 The Canada Labour Code can be viewed at: [www.http://laws-lois.justice.gc.ca/eng/acts/L-2\\_fulltext.html](http://laws-lois.justice.gc.ca/eng/acts/L-2_fulltext.html).
  - .2 Canadian Occupational Health and Safety Regulations can be viewed at: <http://laws-lois.justice.gc.ca/eng/regulations/SOR-86-304/index.html>.
  - .3 A copy may be obtained at: Canadian Government Publishing Public Works & Government Services Canada Ottawa, Ontario, K1A 0S9 Tel: 819-956-4800 or 1-800-635-7943 Publication No. L31-85/2000 (E or F).
- .3 Treasury Board of Canada Secretariat (TBS):
- .4 Treasury Board, Fire Protection Standard April 1, 2010 [www.tbs-sct.gc.ca/pol/doc-eng.aspx?id=17316&section=text](http://www.tbs-sct.gc.ca/pol/doc-eng.aspx?id=17316&section=text).
- .5 Canadian Standards Association (CSA):
  - .1 CSA S350-M1980(R2003), Code of Practice for Safety in Demolition of Structures.
- .6 Observe construction safety measures of:
  - .1 NBC 2010, Division B, Part 8.
  - .2 Municipal by-laws and ordinances.
- .7 In case of conflict or discrepancy between above specified requirements, the more stringent shall apply.
- .8 Maintain Workers Compensation Coverage in good standing for duration of Contract. Provide proof of clearance through submission of Letter in Good Standing.
- .9 Medical Surveillance: Where prescribed by legislation or regulation, obtain and maintain worker medical surveillance documentation.

1.4. RESPONSIBILITY

- .1 Be responsible for health and safety of persons on site, safety of property on site and for protection of persons and environment adjacent to the site to extent that they may be affected by conduct of Work.
- .2 Comply with and enforce compliance by all workers, sub-contractors and other persons granted access to Work Site with safety requirements of Contract Documents, applicable federal, provincial, and local by-laws, regulations, and ordinances, and with site-specific Health and Safety Plan.

1.5. SITE CONTROL AND ACCESS

- .1 Control the Work and entry points to Work Site. Approve and grant access only to workers and authorized persons. Immediately stop and remove non-authorized persons.
  - .1 Departmental Representative will provide names of those persons authorized by Departmental Representative to enter onto Work Site and will ensure that such authorized persons have the required knowledge and training on Health and Safety pertinent to their reason for being at the site, however, Contractor remains responsible for the health and safety of authorized persons while at the Work Site.
- .2 Isolate Work Site from other areas of the premises by use of appropriate means.
  - .1 Erect fences, hoarding, barricades and temporary lighting as required to effectively delineate the Work Site, stop non-authorized entry, and to protect tenants adjacent to the Work and create a safe environment. See Section 01 50 00 for minimum acceptable requirements.
  - .2 Post signage at entry points and other strategic locations indicating restricted access and conditions for access.
  - .3 Use professionally made signs with bilingual message in the 2 official languages or international known graphic symbols.
- .3 Provide safety orientation session to persons granted access to Work Site. Advise of hazards and safety rules to be observed while on site.
- .4 Ensure persons granted site access wear appropriate PPE. Supply PPE to inspection authorities who require access to conduct tests or perform inspections.
- .5 Secure Work Site against entry when inactive or unoccupied and to protect persons against harm. Provide security guard where adequate protection cannot be achieved by other means.

1.6. PROTECTION

- .1 Give precedence to safety and health of persons and protection of environment over cost and schedule considerations for Work.

- .2 Should unforeseen or peculiar safety related hazard or condition become evident during performance of Work, immediately take measures to rectify situation and prevent damage or harm. Advise Departmental Representative verbally and in writing.

1.7. FILING OF NOTICE

- .1 File Notice of Project with pertinent provincial health and safety authorities prior to beginning of Work.
  - .1 Departmental Representative will assist in locating address if needed.

1.8. PERMITS

- .1 Post permits, licenses and compliance certificates at Work Site.
- .2 Where a particular permit or compliance certificate cannot be obtained, notify Departmental Representative in writing and obtain approval to proceed before carrying out applicable portion of work.

1.9. HAZARD ASSESSMENTS

- .1 Perform site specific health and safety hazard assessment of the Work and its site.
- .2 Carryout initial assessment prior to commencement of Work with further assessments as needed during progress of work, including when new trades and subcontractors arrive on site.
- .3 Record results and address in Health and Safety Plan.
- .4 Keep documentation on site for entire duration of the Work.

1.10. PROJECT/SITE CONDITIONS

- .1 Following are potential health, environmental and safety hazards at the site for which Work may involve contact with:
  - .1 Air-borne dust particles.
  - .2 Hazardous products.
  - .3 Dropping hazards.
  - .4 Working during night hours.
  - .5 Hazardous odours.
- .2 Above items shall not be construed as being complete and inclusive of potential health and safety hazards encountered during Work.

- .3 Include above items in the hazard assessment of the Work, as well as contractor's own observed site specific hazards.
- .4 MSDS Data sheets of pertinent hazardous and controlled products stored on site can be obtained from Departmental Representative.

1.11. MEETINGS

- .1 Attend pre-construction health and safety meeting, convened and chaired by Departmental Representative, prior to commencement of Work, at time, date and location determined by Departmental Representative. Ensure attendance of:
  - .1 Superintendent of Work.
  - .2 Designated Health & Safety Site Representative.
  - .3 Subcontractors.
- .2 Conduct regularly scheduled tool box and safety meetings during the Work in conformance with Occupational Health and Safety regulations.
- .3 Keep documents on site.

1.12. HEALTH AND SAFETY PLAN

- .1 Prior to commencement of Work, develop written Health and Safety Plan specific to the Work. Implement, maintain, and enforce Plan for entire duration of Work and until final demobilization from site.
- .2 Health and Safety Plan shall include the following components:
  - .1 List of health risks and safety hazards identified by hazard assessment.
  - .2 Control measures used to mitigate risks and hazards identified.
  - .3 On-site Contingency and Emergency Response Plan as specified below.
  - .4 On-site Communication Plan as specified below.
  - .5 Name of Contractor's designated Health & Safety Site Representative and information showing proof of his/her competence and reporting relationship in Contractor's company.
  - .6 Names, competence and reporting relationship of other supervisory personnel used in the Work for occupational health and safety purposes.
- .3 On-site Contingency and Emergency Response Plan shall include:
  - .1 Operational procedures, evacuation measures and communication process to be implemented in the event of an emergency.
  - .2 Evacuation Plan: site and floor plan layouts showing escape routes, marshalling areas. Details on alarm notification methods, fire drills, location of firefighting equipment and other related data.
  - .3 Name, duties and responsibilities of persons designated as Emergency Warden(s)

- and deputies.
- .4 Emergency Contacts: name and telephone number of officials from:
  - .1 General Contractor and subcontractors.
  - .2 Pertinent Federal and Provincial Departments and Authorities having jurisdiction.
  - .3 Local emergency resource organizations.
- .5 Harmonize Plan with Facility's Emergency Response and Evacuation Plan. Departmental Representative will provide pertinent data including name of PWGSC and Facility Management contacts.
- .4 On-site Communication Plan:
  - .1 Procedures for sharing of work related safety information to workers and subcontractors, including emergency and evacuation measures.
  - .2 List of critical work activities to be communicated with Facility Manager which have a risk of endangering health and safety of Facility users.
- .5 Address all activities of the Work including those of subcontractors.
- .6 Review Health and Safety Plan regularly during the Work. Update as conditions warrant to address emerging risks and hazards, such as whenever new trade or subcontractor arrive at Work Site.
- .7 Departmental Representative will respond in writing, where deficiencies or concerns are noted and may request re-submission of the Plan with correction of deficiencies or concerns.
- .8 Post copy of the Plan, and updates, prominently on Work Site.

#### 1.13. SAFETY SUPERVISION

- .1 Employ Health & Safety Site Representative responsible for daily supervision of health and safety of the Work.
- .2 Health & Safety Site Representative may be the Superintendent of the Work or other person designated by Contractor and shall be assigned the responsibility and authority to:
  - .1 Implement, monitor and enforce daily compliance with health and safety requirements of the Work
  - .2 Monitor and enforce Contractor's site-specific Health and Safety Plan.
  - .3 Conduct site safety orientation session to persons granted access to Work Site.
  - .4 Ensure that persons allowed site access are knowledgeable and trained in health and safety pertinent to their activities at the site or are escorted by a competent person while on the Work Site.
  - .5 Stop the Work as deemed necessary for reasons of health and safety.
- .3 Health & Safety Site Representative must:

- .1 Be qualified and competent person in occupational health and safety.
- .2 Have site-related working experience specific to activities of the Work.
- .3 Be on Work Site at all times during execution of the Work.
- .4 All supervisory personnel assigned to the Work shall also be competent persons.
- .5 Inspections:
  - .1 Conduct regularly scheduled safety inspections of the Work on a minimum bi-weekly basis. Record deficiencies and remedial action taken.
  - .2 Follow-up and ensure corrective measures are taken.
- .6 Cooperate with Facility's Occupational Health and Safety representative should one be designated by Departmental Representative.
- .7 Keep inspection reports and supervision related documentation on site.

#### 1.14. TRAINING

- .1 Use only skilled workers on Work Site who are effectively trained in occupational health and safety procedures and practices pertinent to their assigned task.
- .2 Maintain employee records and evidence of training received. Make data available to Departmental Representative upon request.
- .3 When unforeseen or peculiar safety-related hazard, or condition occur during performance of Work, follow procedures in place for Employee's Right to Refuse Work in accordance with Acts and Regulations of Province having jurisdiction and advise Departmental Representative verbally and in writing.

#### 1.15. MINIMUM SITE SAFETY RULES

- .1 Notwithstanding requirement to abide by federal and provincial health and safety regulations; ensure the following minimum safety rules are obeyed by persons granted access to Work Site:
  - .1 Wear appropriate PPE pertinent to the Work or assigned task; minimum being hard hat, safety footwear, safety glasses and hearing protection.
  - .2 Immediately report unsafe condition at site, near-miss accident, injury and damage.
  - .3 Maintain site and storage areas in a tidy condition free of hazards causing injury.
  - .4 Obey warning signs and safety tags.
- .2 Brief persons of disciplinary protocols to be taken for noncompliance. [Post rules on site].

1.16. CORRECTION OF NON-COMPLIANCE

- .1 Immediately address health and safety non-compliance issues identified by authority having jurisdiction or by Departmental Representative.
- .2 Provide Departmental Representative with written report of action taken to correct non-compliance of health and safety issues identified.
- .3 Departmental Representative will stop Work if non-compliance of health and safety regulations is not corrected in a timely manner.

1.17. INCIDENT REPORTING

- .1 Investigate and report the following incidents to Departmental Representative:
  - .1 Incidents requiring notification to Provincial Department of Occupational Safety and Health, Workers Compensation Board or to another regulatory Agency.
  - .2 Medical aid injuries.
  - .3 Property damage in excess of \$10,000.00,
  - .4 Interruptions to Facility operations resulting in an operational lost to a Federal department in excess of \$5,000.00.
- .2 Submit report in writing.

1.18. HAZARDOUS PRODUCTS

- .1 Comply with requirements of Workplace Hazardous Materials Information System (WHMIS).
- .2 Keep MSDS data sheets for all products delivered to site.
  - .1 Post on site.
  - .2 Submit copy to Departmental Representative.
  - .3 For interior work in an occupied Facility, post additional copy in one or more publically accessible locations.

1.19. BLASTING

- .1 Blasting or other use of explosives is not permitted on site.

1.20. POWDER ACTUATED DEVICES

- .1 Use powder actuated fastening devices not permitted on site.



1.21. CONFINED SPACES

- .1 Abide by occupational health and safety regulations regarding work in confined spaces.

1.22. SITE RECORDS

- .1 Maintain on Work Site copy of safety related documentation and reports stipulated to be produced in compliance with Acts and Regulations of authorities having jurisdiction and of those documents specified herein.
- .2 Upon request, make available to Departmental Representative or authorized Safety Officer for inspection.

1.23. POSTING OF DOCUMENTS

- .1 Ensure applicable items, articles, notices and orders are posted in conspicuous location on Work Site in accordance with Acts and Regulations of Province having jurisdiction.
- .2 Post other documents as specified herein, including:
  - .1 Site specific Health and Safety Plan.
  - .2 WHMIS data sheets.

END OF SECTION

1.1. RELATED SECTIONS

- .1 Waste Management and Disposal: Section 01 74 21.

1.2. DEFINITIONS

- .1 Hazardous Material: Product, substance, or organism that is used for its original purpose; and that is either dangerous goods or a material that may cause adverse impact to the environment or adversely affect health of persons, animals, or plant life when released into the environment.
- .2 Environmental Pollution and Damage: presence of chemical, physical, biological elements or agents which adversely affect human health and welfare; unfavourably alter ecological balances of importance to human life; affect other species of importance to humans; or degrade environment aesthetically, culturally and/or historically.
- .3 Environmental Protection: prevention/control of pollution and habitat or environment disruption during construction.

1.3. FIRES

- .1 Fires and burning of rubbish on site not permitted.

1.4. HAZARDOUS MATERIAL HANDLING

- .1 Store and handle hazardous materials in accordance with applicable federal and provincial laws, regulations, codes and guidelines. Store in location that will prevent spillage into the environment
- .2 Label containers to WHMIS requirements and keep MSDS data sheets on site for all hazardous materials.
- .3 Maintain inventory of hazardous materials and hazardous waste stored on site. List items by product name, quantity and date when storage began.
- .4 Store and handle flammable and combustible materials in accordance with National Fire Code.
- .5 Transport hazardous materials in accordance with federal Transportation of Dangerous Goods Regulations and applicable Provincial regulations.

1.5. DISPOSAL OF WASTES

- .1 Do not bury rubbish and waste materials on site. Dispose in accordance with project waste

management requirements specified in section 01 74 21.

- .2 Do not dispose of hazardous waste or volatile materials, such as mineral spirits, paints, thinners, oil or fuel into waterways, storm or sanitary sewers or waste landfill sites.
- .3 Dispose of hazardous waste in accordance with applicable federal and provincial laws, regulations, codes and guidelines.

END OF SECTION

1.1. RELATED SECTIONS

- .1 Section 01 33 00 Submittal Procedures.
- .2 Section 01 78 00 Closeout Submittals.

1.2. INSPECTION

- .1 Give timely notice requesting inspection of Work designated for special tests, inspections or approvals by Departmental Representative or by inspection authorities having jurisdiction.
- .2 In accordance with the General Conditions, Departmental Representative may order any part of Work to be examined if Work is suspected to be not in accordance with Contract Documents.
- .3 If Contractor covers or permits to be covered Work designated for special tests, inspections or approvals before such is made, uncover Work until particular inspections or tests have been fully and satisfactorily completed and until such time as Departmental Representative gives permission to proceed.
- .4 Pay costs to uncover and make good work disturbed by inspections and tests.

1.3. TESTING

- .1 Tests on materials, equipment and building systems as specified in various sections of the Specifications is the responsibility of the Contractor except where stipulated otherwise.
  - .1 Provide all necessary instruments, equipment and qualified personnel to perform tests.
- .2 At completion of tests, turn over 2 sets of fully documented tests reports to the Departmental Representative. Submit in accordance with Section 01 33 00.
  - .1 Obtain additional copies for inclusion of a complete set in each of the maintenance manuals specified in Section 01 78 00.
- .3 Unspecified tests may also be made by Departmental Representative, at the discretion of the Departmental Representative. The costs of these tests will be paid for by the Departmental Representative.
- .4 Where tests or inspections reveal work not in accordance with contract requirements, Contractor shall pay costs for additional tests and inspections incurred by Departmental Representative as required to verify acceptability of corrected work.

1.4. REJECTED WORK

- .1 Remove and replace defective Work, whether result of poor workmanship, use of defective or damaged products and whether incorporated in Work or not, which has been identified by Departmental Representative as failing to conform to Contract Documents.
- .2 Make good damages to new and existing construction and finishes resulting from removal or replacement of defective work.

END OF SECTION

1.1. RELATED SECTIONS

- .1 Scheduling and Management of work: Section 01 14 10.

1.2. SITE ACCESS AND PARKING

- .1 The Departmental Representative will designate Contractor's access to project site as well as parking facilities for equipment and workers.

1.2. BUILDING ACCESS

- .1 Use only access doors, and circulation routes within building as designated by Departmental Representative to access interior work.

1.3. MATERIAL STORAGE

- .1 Material storage space on site does not exist. Coordinate delivery to minimize storage period on site before being needed for incorporation into work.

1.4. INTERIOR HOARDING

- .1 Erect hoarding inside building to isolate construction areas and protect tenants and public for duration of work.
- .2 Construct hoarding as follows:
  - .1 Height: to underside of floor or roof above.
  - .2 Framing type: 38mm x 89mm lightweight steel studs spaced at 24 oc.
  - .3 Covering: 12 mm thick plywood sheathing c/w airtight taped 6mil poly.
  - .4 Sealed to abutting surfaces and taped to be airtight.
  - .5 Access Doors: (1) quantity wood pedestrian door; dust tight, lockable, c/w closer.

1.5. INTERIOR DUST CONTROL AND DUST BARRIERS

- .1 Control creation and spread of dust and dirt to building interior and in particular to areas within premises still under use by occupants.
- .2 Develop and implement a dust control plan, addressing effective measures to carry out work with least amount of dust being created and propagated.
  - .1 Carefully evaluate the type of work to be undertaken and the physical layout of each work area on site.
  - .2 Provide specifically tailored strategy for each work area.
  - .3 Pre-determine location and placement of dust barriers to confine resulting dust

- to immediate work area.
- .4 Inform Departmental Representative of the proposed dust control measures to be followed at each work area and for each major dust generating activities. Obtain Departmental Representative's approval before proceeding with work.
- .3 Dust control plan to incorporate as a minimum the following dust protection and cleaning requirements, **as well as requirements listed in Section 01 14 10:**
  - .1 Erect dustproof partitions completely around work area to fully isolate construction from other parts of the building.
  - .2 Construct dust partitions as follows:
    - .1 Use 10 mm polyethylene installed and sealed tightly to abutting walls, ceilings and floor with continuous duct tape along all edges and seams. Support in position with 38 x 89 wood framing at 400 mm o.c. Locate seams only at framing members and overlap sheeting by minimum of 150 mm.
  - .3 Provide a "dust tight" and lockable access door(s) within dust partition or between rooms for worker entry into work area. This is of particular importance for situations where excessive dust will be generated.
  - .4 Provide additional dust barriers, placed tightly to underside of the floor/roof deck above, in locations where existing walls are used as part of the dust barrier system but simply terminate at the finished ceiling level resulting in an open space above, or other similar condition, permitting dust to migrate beyond the construction areas.
  - .5 Provide dust barriers at doorways in perimeter of work area.
  - .6 Make all dust barriers airtight, effectively blocking and stopping all dust migration.
  - .7 Inspect dust barriers at various intervals during each work shift. Immediately fix tears, unsealed edges and maintain barriers effectively sealed for the entire work duration.
  - .8 Shut down existing ventilation system feeding construction space, or disconnect and seal-off supply and return air ducts to stop dust from contaminating other areas.
  - .9 Immediately clean areas in use by occupants and public contaminated by work.
    - .1 Vacuum carpets, wash floors and walls. Remove accumulated dust from all surfaces. Clean and remove smears, scuffs and marks.
- .4 Meager attempts at controlling dust will not be tolerated. Failure to provide effective dust control during work and to perform satisfactory cleaning thereafter will result in Departmental Representative to proceed and obtain a separate cleaning service agency to perform cleaning to tenant's satisfaction with cost for such services being charged against this Contract in the form of financial holdbacks.
- .5 Obtain Departmental Representative's approval before erecting any dust partitions simply to underside of finish ceiling.

1.6. SANITARY FACILITIES

- .1 Contractor to provide own sanitary facilities. Place facilities where directed by Departmental Representative.

1.7. POWER

- .1 Power supply is available and will be provided for construction usage at no cost.
  - .1 Make arrangements for the use of such services through the Departmental Representative.
  - .2 Departmental Representative will designate and approve each location of existing power source to which connections can be made to obtain temporary power service.
  - .3 Connect to existing power supply in accordance with CSA C22.1-12, Canadian Electrical Code.

1.8. VENTILATING

- .1 Supply, install and pay for costs of temporary ventilation used during construction.
- .2 Provide temporary ventilation in enclosed areas as required to provide adequate ventilation to meet health regulations for safe working environment.
- .3 Ventilating:
  - .1 Prevent accumulations of dust, fumes, mists, vapours or gases in areas occupied during construction.
  - .2 Provide local exhaust ventilation to prevent harmful accumulation of hazardous substances into atmosphere of occupied areas.
  - .3 Dispose of exhaust materials in manner that will not result in harmful exposure to persons.
  - .4 Ventilate storage spaces containing hazardous or volatile materials.
  - .5 Ventilate temporary sanitary facilities.
  - .6 Continue operation of ventilation and exhaust system for time after cessation of work process to assure removal of harmful contaminants.
- .4 Maintain strict supervision of operation of temporary ventilating equipment to:
  - .1 Conform with applicable codes and standards.
  - .2 Enforce safe practices.
  - .3 Prevent abuse of services.
  - .4 Prevent damage to finishes.
- .5 Submit bid assuming existing equipment and systems will not be used for temporary ventilating.



1.9. CONSTRUCTION SIGN AND NOTICES

- .1 Upon request by Departmental Representative, erect a self supporting project sign in location indicated.
- .2 Install sign plumb and level in neat wood framework and securely anchor in ground by posts to withstand wind pressure of 160 km/h.
- .3 Contractor or subcontractor advertisement signboards are not permitted on site.
- .4 Safety and Instruction Signs and Notices:
  - .1 Signs and notices for safety and instruction shall be in both official languages or commonly understood graphic symbols conforming to CAN/CSA-Z321-96(R2006).
- .5 Maintenance and Disposal of Site Signs:
  - .1 Maintain approved signs and notices in good condition for duration of project and dispose of off site on completion of project or earlier if directed by Departmental Representative.

1.10. REMOVAL OF TEMPORARY FACILITIES

- .1 Remove temporary facilities from site when directed by Departmental Representative.

END OF SECTION

1.1. GENERAL

- .1 Use new material and equipment unless otherwise specified.
- .2 Within (7) days of written request by Departmental Representative, submit following information for any materials and products proposed for supply:
  - .1 Name and address of manufacturer.
  - .2 Trade name, model and catalogue number.
  - .3 Performance, descriptive and test data.
  - .4 Compliance to specified standards.
  - .5 Manufacturer's installation or application instructions.
  - .6 Evidence of arrangements to procure.
  - .7 Evidence of manufacturer delivery problems or unforeseen delays.
- .3 Provide material and equipment of specified design and quality, performing to published ratings and for which replacement parts are readily available.
- .4 Use products of one manufacturer for equipment or material of same type or classification unless otherwise specified.
- .5 Permanent labels, trademarks and nameplates on products are not acceptable in prominent locations, except where required for operating instructions, or when located in mechanical or electrical rooms.

1.2. PRODUCT QUALITY

- .1 Contractor shall be solely responsible for submitting relevant technical data and independent test reports to confirm whether a product or system proposed for use meets contract requirements and specified standards.
- .2 Final decision as to whether a product or system meets contract requirements rest solely with the Departmental Representative in accordance with the General Conditions of the Contract.

1.3. ACCEPTABLE MATERIALS AND ALTERNATIVES

- .1 Acceptable Materials: When materials specified include trade names or trade marks or manufacturer's or supplier's name as part of the material description, select and only use one of the names listed for incorporation into the Work.
- .2 Alternative Materials: Submission of alternative materials to trade names or manufacturer's names specified must be done during the bidding period following procedures indicated in the Instructions to Bidders.
- .3 Substitutions: After contract award, substitution of a specified material will be dealt with as a change to the Work in accordance with the General Conditions of the Contract.

1.4. MANUFACTURERS INSTRUCTIONS

- .1 Unless otherwise specified, comply with manufacturer's latest printed instructions for materials and installation methods to be used. Do not rely on labels or enclosure provided with products. Obtain written instructions directly from manufacturers.
- .2 Notify Departmental Representative in writing of any conflict between these specifications and manufacturers instructions, so that Departmental Representative will designate which document is to be followed.

1.5. AVAILABILITY

- .1 Immediately notify Departmental Representative in writing of unforeseen or unanticipated material delivery problems by manufacturer. Provide support documentation as per clause 1.1.2 above.

1.6. WORKMANSHIP

- .1 Ensure quality of work is of highest standard, executed by workers experienced and skilled in respective duties for which they are employed.
- .2 Remove unsuitable or incompetent workers from site as stipulated in the General Conditions of the Contract.
- .3 Ensure cooperation of workers in laying out work. Maintain efficient and continuous supervision on site at all times.
- .4 Coordinate work between trades and subcontractors. See section 01 14 10 in this regard.

1.7. STORAGE, HANDLING AND PROTECTION

- .1 Storage of materials on site is not permitted.
- .2 Deliver and handle materials in manner to prevent deterioration and soiling and in accordance with manufacturer's instructions when applicable.
- .3 Immediately remove damaged or rejected materials from site.
- .4 Touch-up damaged factory finished surfaces to Departmental Representative's satisfaction. Use touch-up materials to match original. Do not paint over name plates.

END OF SECTION

1.1. RELATED SECTIONS

- .1 Section 01 14 10: Scheduling and Management of Work.
- .2 Section 01 50 00: Temporary Facilities.

1.2. GENERAL

- .1 Conduct cleaning and disposal operations to comply with local ordinances and anti-pollution laws.
- .2 Store volatile waste in covered metal containers, and remove from premises at end of each working day.
- .3 Provide adequate ventilation during use of volatile or noxious substances. Use of building ventilation systems is not permitted for this purpose.

1.3. MATERIALS

- .1 Use only cleaning materials recommended by manufacturer of surface to be cleaned, and as recommended by cleaning material manufacturer.

1.4. CLEANING DURING CONSTRUCTION

- .1 Refer to section 01 14 10 for additional requirements.
- .2 Maintain work areas in a tidy condition, free from accumulations of waste material and debris. Clean areas on a daily basis.
- .3 Keep building entrances in a clean dust free condition at all times. Conduct thorough cleaning of these areas at end of each work shift when used by workers or affected by the Work.
- .4 Provide on-site containers for collection of waste materials and debris.
- .5 Use separate collection bins, clearly marked as to purpose, for source separation and recycling of waste and debris in accordance with waste management requirements specified.
- .6 Remove waste materials, and debris from site on a daily basis.
- .7 Schedule cleaning operations so that resulting dust, debris and other contaminants will not fall on wet, newly painted surfaces nor contaminate building systems.
- .8 Provide dust barriers, dividers, seals on doors and employ other dust control measures as required to ensure that dust and dirt, generated by work, are not transmitted to [other] [new] [existing] areas of building. Should dust migrate into [tenant occupied] [and public] areas of building, employ such means as may be necessary to immediately clean all contaminated surfaces to the satisfaction of the Departmental Representative.

- .1 See Section 01 50 00 for requirements on dust control and for erection of dust partitions.
- .9 Immediately clean all dust, dirt, smears, scuffs and soiled surfaces resulting from the Work.
  - .1 Perform cleaning, dusting and washing operations, carpet vaccuming (including shampooing if deemed required by Departmental Representative) and floor washing as necessary to thoroughly clean all soiled surfaces.
  - .2 All costs associated with cleaning will be considered incidental to the work.
- .10 Remove snow and ice from access doors used by workforce when applicable.

#### 1.5. FINAL CLEANING

- .1 In preparation for acceptance of the completed work perform final cleaning.
- .2 Remove grease, dust, dirt, stains, labels, fingerprints, marks and other foreign materials, from interior and exterior finished surfaces. Clean and polish surfaces including glass, mirrors, hardware, wall tile, stainless steel, chrome, baked enamel, plastic laminate, mechanical and electrical fixtures.
- .3 Replace items with broken pieces, scratches or disfigured.
- .4 Clean lighting reflectors, lenses, and other lighting surfaces.
- .5 Vacuum clean and dust building interiors, behind grilles, louvres and screens.
- .6 Wax, seal, shampoo or prepare floor finishes as recommended by manufacturer.
- .7 Inspect finishes, fitments and equipment. Ensure specified workmanship and operation.
- .8 Broom clean and wash exterior paved surfaces and walks; rake clean other surfaces of grounds.
- .9 Remove debris and surplus materials from crawl areas, roof areas and other accessible concealed spaces.
- .10 Clean equipment, washroom and kitchen fixtures to a sanitary condition. Replace filters of mechanical equipment.

END OF SECTION

1.1. DEFINITIONS

- .1 Hazardous Material: Product, substance, or organism that is used for its original purpose, and that is either dangerous goods or a material that may cause adverse impact to the environment or adversely affect health of persons, animals, or plant life when released into the environment.

1.2. WASTE MANAGEMENT

- .1 Incorporate environmental and sustainable practices in managing waste resulting from work.
- .2 Divert as much waste as possible from landfill.
- .3 Coordinate work of subtrades and subcontractors to ensure all possible waste reduction and recycling opportunities are taken. Follow waste management requirements specified in trade sections of the Specifications.
- .4 Reduce waste during installation of new materials. Undertake practices which will optimize full use of materials and minimize waste.
- .5 Develop innovative procedures to reduce quantity of waste generated by construction such as by delivering materials to site with minimal packaging etc.
- .6 Provide on-site facilities to collect, handle and store anticipated quantities of reusable, salvageable and recyclable materials.
- .7 During demolition and removal work separate materials and equipment at source, carefully dismantling, labelling and stockpiling alike items for the following purposes:
  - .1 Reinstallation into the work where indicated.
  - .2 Salvaging reusable items not needed in project which Contractor may sell to other parties.
  - .3 Sending as many items as possible to locally available recycling facility.
  - .4 Segregating remaining waste and debris into various individual waste categories for disposal in a "non-mixed state" as recommended by waste processing/landfill sites.
- .8 Isolate product packaging and delivery containers from general waste stream. Send to recycling facility or return to supplier/manufacturer.
- .9 Send leftover material resulting from installation work for recycling whenever possible.
- .10 Establish methods whereby hazardous and toxic materials, and their containers used on site are properly handled, stored and disposed in accordance with applicable federal, provincial and municipal laws and regulations.

1.3. DISPOSAL REQUIREMENTS

- .1 Burying or burning of rubbish and waste materials is prohibited.
- .2 Disposal of volatile materials, mineral spirits, oil, paint, and other hazardous materials into waterways, storm, or sanitary sewers is prohibited.
- .3 Dispose of waste only at approved waste processing facility or landfill sites approved by authority having jurisdiction.
- .4 Contact the authority having jurisdiction prior to commencement of work, to determine what, if any, demolition and construction waste materials have been banned from disposal in landfills and at transfer stations. Take appropriate action to isolate such banned materials at site of work and dispose in strict accordance with provincial and municipal regulations.
- .5 Transport and dispose of waste intended for waste processing plant or landfill facility in separated condition and to Operator's rules and recommendations in support of their effort to recycle, reduce and divert certain waste stream from general landfill.
- .6 Collect, bundle and transport salvaged materials to be recycled in separated categories and condition as directed by recycling facility. Ship materials only to approved recycling facilities.
- .7 Sale of salvaged items by Contractor to other parties not permitted on site.

END OF SECTION

1.1. SECTION INCLUDES

- .1 Administrative procedures preceding inspection and acceptance of Work by Departmental Representative.

1.2. RELATED SECTIONS

- .1 .1 Section 01 78 00: Closeout Submittals.

1.3. INSPECTION AND DECLARATION

- .1 Contractor's Inspection: Coordinate and perform, in concert with subcontractors, an inspection and check of all Work. Identify and correct deficiencies, defects, repairs and perform outstanding items as required to complete work in conformance with Contract Documents.
  - .1 Notify Departmental Representative in writing when deficiencies from Contractor's inspection have been rectified and that Work is deemed to be complete and ready for Departmental Representative's inspection of the completed work.
- .2 Departmental Representative's Inspection: Accompany Departmental Representative during all substantial and final inspections of the Work.
  - .1 Address defects, faults and outstanding items of work identified by such inspections.
  - .2 Advise Departmental Representative when all deficiencies identified have been rectified.
- .3 Note that Departmental Representative will not issue a Certificate of Substantial Performance of the work until such time that Contractor performs following work and turns over the specified documents:
  - .1 As Built drawings and Specifications;
  - .2 Final Maintenance manuals;
  - .3 Maintenance materials, parts and tools;
  - .4 Compliance certificates from applicable authorities;
  - .5 Reports resulting from designated tests;
  - .6 Manufacturer's Guarantee certificates.
- .4 Correct all discrepancies before Departmental Representative will issue the Certificate of Completion.

END OF SECTION



1.1. SECTION INCLUDES

- .1 Project Record Documents.
- .2 Operations and Maintenance data.

1.2. RELATED SECTIONS

- .1 Section 01 77 00: Closeout Procedures.

1.3. PROJECT RECORD DOCUMENTS

- .1 Departmental Representative will provide 2 white print sets of contract drawings and 2 copies of Specifications Manual specifically for "As-Built" purposes.
- .2 Maintain at site one set of the contract drawings and specifications to record actual As-Built site conditions.
- .3 Maintain up-to-date, real time as-built drawings and specifications in good condition and make available for inspection by the Departmental Representative upon request.
- .4 As-Built Drawings:
  - .1 Record changes in red ink on the prints. Mark only on one set of prints and at completion of work, neatly transfer notations to second set (also by use of red ink).
  - .2 Submit both sets to Departmental Representative prior to application for Certificate of Substantial Performance.
  - .3 Stamp all drawings with "As-Built". Label and place Contractor's signature and date.
  - .4 Show all modifications, substitutions and deviations from what is shown on the contract drawings.
- .5 As-Built Specifications: legibly mark in red each item to record actual construction, including:
  - .1 Manufacturer, trade name, and catalogue number of each product actually installed, particularly items substituted from that specified.
  - .2 Changes made by Addenda and Change Orders.
  - .3 Mark up both copies of specifications; stamp "As-Built", sign and date similarly to drawings as per above clause.
- .6 Maintain As-Built documents current as the contract progresses. Departmental Representative will conduct reviews and inspections of the documents on a regular basis. Failure to maintain as-builts current and complete to satisfaction of the Departmental Representative shall be subject to financial penalties in the form of progress payment reductions and holdback assessments.
- .7 Submit on paper and in electronic format as pdf files. Forward pdf and in the native

program format files on USB compatible with PWGSC encryption requirements or through email or alternate electronic file sharing service such as ftp, as directed by Departmental Representative.

1.4. REVIEWED SHOP DRAWINGS

- .1 Provide a complete set of all shop drawings reviewed for project to incorporate into each copy of the Operations and Maintenance Manuals.
- .2 Submit full sets at same time and as part of the contents of the Operation and Maintenance Manuals specified.

1.5. OPERATIONS & MAINTENANCE MANUAL

- .1 O&M Manual - Definition: an organized compilation of operating and maintenance data including detailed technical information, documents and records describing operation and maintenance of individual products or systems as specified in individual sections of the specifications.
- .2 Manual Language: final manuals to be in English.
- .3 Number of copies required:
  - .1 Submit (2) interim copies of the manual for review and inspection by Departmental Representative. Make revisions and additions as directed and resubmit.
  - .2 Upon review and acceptance by Departmental Representative, submit (2) final copies. Interim copies are not to be considered as part of the final copies unless they have been fully revised and are identical to the final approved version.
- .4 Submission Date: submit complete operation and maintenance manual to Departmental Representative (3 weeks) prior to application for Certificate of Substantial Performance of the work.
- .5 Binding:
  - .1 Assemble, coordinate, bind and index required data into Operation and Maintenance Manual.
  - .2 Use vinyl, hard covered, 3 "D" ring binders, loose leaf, sized for 215 x 280 mm paper, with spine pocket.
  - .3 Identify contents of binder on spine.
  - .4 Organize and divide data following same numerical system as the section numbers of the Specification Manual.
  - .5 Dividers: separate each section by use of cardboard dividers and labels. Provide tabbed fly leaf for each individual product and system and give description of product or component.
  - .6 Type lists and notes. Do not hand write.
  - .7 Drawings, diagrams and manufacturers' literature must be legible. Provide with reinforced, punched binder tab. Bind in with text; fold larger drawings to size of

text pages.

- .6 Manual Contents:
  - .1 Cover sheet containing:
    - .1 Date submitted.
    - .2 Project title, location and project number.
    - .3 Names and addresses of Contractor, and all Sub-Contractors.
  - .2 Table of Contents: provide full table of contents in each binder(s), clearly indicate which contents are in each binder.
  - .3 List of maintenance materials.
  - .4 List of spare parts.
  - .5 List of special tools.
  - .6 Original or certified copy of warranties and product guarantees.
  - .7 Copy of approval documents and certificates issued by Inspection Authorities.
  - .8 Copy of reports and test results performed by Contractor as specified.
  - .9 Product Information (PI Data) on materials, equipment and systems as specified in various sections of the specifications. Data to include:
    - .1 List of materials including manufacturer's name, supplier, local source of supplies and service. Provide full addresses and telephone numbers.
    - .2 Installation details.
    - .3 Maintenance instructions for finishes.
- .7 Shop drawings:
  - .1 Include complete set of reviewed shop drawings into each copy of the operations and maintenance manual.
  - .2 Fold and bind material professionally in a manner that corresponds with the specification section numbering system.
  - .3 When large quantity of data is submitted, place into separate binders of same size as O&M binders.
- .8 Materials and Finishes Maintenance Data:
  - .1 Building Products, Applied Materials, and Finishes: include product data, with catalogue number, size, composition, and colour and texture designations.
  - .2 Instructions for cleaning agents and methods, precautions against detrimental agents and methods, and recommended schedule for cleaning and maintenance.
  - .3 Moisture-protection and Weather-exposed Products: include manufacturer's recommendations for cleaning agents and methods, precautions against detrimental agents and methods, and recommended schedule for cleaning and maintenance.

1.6. SPARE PARTS, TOOLS AND MAINTENANCE MATERIALS

- .1 Provide spare parts, special tools and extra materials for maintenance purposes in

quantities specified in individual specification sections.

- .2 Tag all items with associated use.
- .3 Provide items of same manufacture and quality as items in Work.
- .4 Deliver to site in well packaged condition. Store in location as directed by Departmental Representative.
- .5 Clearly mark as to contents indicating:
  - .1 Product number.
  - .2 Manufacturer.
  - .3 Installation instructions or intended use as applicable.
  - .4 Name, address and telephone number of nearest supplier.
- .6 Prepare and submit complete inventory list of items supplied. Include list within Maintenance Manual.

**END OF SECTION**

PART 1 - GENERAL

1.1 RELATED REQUIREMENTS

- .1 Section 01 14 10 Scheduling.
- .2 Section 01 50 00 Temporary Facilities.
- .3 Section 01 74 21 Waste Management.

1.2 REFERENCES

- .1 Canadian Council of Ministers of the Environment (CCME)
- .2 Canadian Standards Association (CSA International):
  - .1 CSA S350-M1980(R2003), Code of Practice for Safety in Demolition of Structures.

1.3 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Prior to beginning of Work on site submit detailed Waste Reduction Workplan in accordance with Section 01 74 21 – Waste Management and indicate:
  - .1 Schedule of selective demolition.
  - .2 Number and location of dumpsters.
  - .3 Anticipated frequency of tippage.
  - .4 Name and address of haulers, waste facilities, waste receiving organizations.

1.4 DELIVERY, STORAGE AND HANDLING

- .1 Waste Management and Disposal:
- .2 Separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Waste Management.

1.5 SITE CONDITIONS

- .1 Review designated substance report and take precautions to protect environment.
- .2 Should material resembling spray or trowel-applied asbestos or other designated substance listed as hazardous be encountered, stop work, take preventative measures, and notify Departmental Representative immediately.

- .1 Do not proceed until written instructions have been received from Departmental Representative.

## PART 2 - PRODUCTS

### 2.1 EQUIPMENT

- .1 Leave equipment and machinery running only while in use.
- .2 Demonstrate that tools and machinery are being used in manner which allows for salvage of materials in best condition possible.

## PART 3 - EXECUTION

### 3.1 PREPARATION

- .1 Do Work in accordance with Section 01 35 29.06 - Health and Safety Requirements.
- .2 Protection:
  - .1 Prevent damage to adjacent structures, utilities, and parts of building to remain in place.
  - .2 Keep noise, dust, and inconvenience to occupants to minimum. Refer to Section 01 14 10 Scheduling.
  - .3 Protect building systems, services and equipment.
  - .4 Provide temporary dust screens, covers, railings, supports and other protection as required in Sections 01 14 10 Scheduling and 01 50 00 Temporary Facilities.
- .3 Disconnect and re-route electrical, telephone and communication service lines. Post warning signs on electrical lines and equipment which must remain energized to serve other products during period of demolition.

### 3.2 DEMOLITION SALVAGE AND DISPOSAL

- .1 Remove parts of existing building to permit new construction. Sort materials into appropriate piles for reuse and recycling.
- .2 Remove items to be reused, store as directed by Departmental Representative and re-install under appropriate section of specification.
- .3 Dispose of removed materials, to appropriate recycling facilities in accordance with authority having jurisdiction.

### 3.3 REMOVAL FROM SITE

- .1 Transport material designated for alternate disposal to organizations listed in waste reduction workplan and in accordance with applicable regulations.
- .2 Dispose of materials not designated for alternate disposal in accordance with applicable regulations. Disposal facilities must be approved of and listed in waste reduction workplan.

### 3.4 CLEANING AND RESTORATION

- .1 Keep site clean and organized throughout demolition procedure. Refer to Sections 01 14 10 Scheduling and 01 50 00 Temporary Facilities.

END OF SECTION

PART 1 - GENERAL

1.1 REFERENCES

- .1 American National Standards Institute (ANSI)/Ceramic Tile Institute (CTI)
  - .1 ANSI A108.1-99, Specification for the Installation of Ceramic Tile (Includes ANSI A108.1A-C, 108.4-.13, A118.1-.10, ANSI A136.1).
  - .2 CTI A118.3-92, Specification for Chemical Resistant, Water Cleanable Tile Setting and Grouting Epoxy and Water Cleanable Tile Setting Epoxy Adhesive (included in ANSI A108.1).
  - .3 CTI A118.4-92, Specification for Latex Cement Mortar (included in ANSI A108.1).
  - .4 CTI A118.5-92, Specification for Chemical Resistant Furan Resin Mortars and Grouts for Tile Installation (included in ANSI A108.1).
  - .5 CTI A118.6-92, Specification for Ceramic Tile Grouts (included in ANSI A108.1).
- .2 American Society for Testing and Materials International (ASTM)
  - .1 ASTM C 144-04, Specification for Aggregate for Masonry Mortar.
  - .2 ASTM C 207-06, Specification for Hydrated Lime for Masonry Purposes.
  - .3 ASTM C 979-05, Specification for Pigments for Integrally Coloured Concrete.
- .3 Canadian General Standards Board (CGSB)
  - .1 CGSB 71-GP-22M-78(AMEND.), Adhesive, Organic, for Installation of Ceramic Wall Tile.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Provide samples of tile, grout and decoupling membrane, movement joints.
- .3 Provide product data in accordance with Section 01 33 00 - Submittal Procedures.
  - .1 Include manufacturer's information on:
    - .1 Tile Base
    - .2 Mortar and grout.
    - .3 Divider strip.
    - .4 Elastomeric membrane and bond coat.
    - .5 Reinforcing tape.
    - .6 Organic adhesive.

1.3 QUALITY ASSURANCE

- .1 Quality Assurance Submittals:
  - .1 Manufacturer's Instructions: manufacturer's installation instructions.



#### 1.4 DELIVERY, STORAGE AND HANDLING

- .1 Packing, shipping, handling and unloading:
  - .1 Deliver, store and handle materials in accordance with manufacturer's instructions.
- .2 Waste Management and Disposal:
  - .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Waste Management.

#### 1.5 AMBIENT CONDITIONS

- .1 Maintain air temperature and structural base temperature at ceramic tile installation area above 12 degrees C for 48 hours before, during, and 48 hours after, installation.
- .2 Do not install tiles at temperatures less than 12 degrees C or above 38 degrees C.
- .3 Do not apply epoxy mortar and grouts at temperatures below 15 degrees C or above 25 degrees C.

#### 1.6 MAINTENANCE

- .1 Extra Materials:
  - .1 Provide 2% of total amount used, of each colour, pattern and type flooring material required for this project for maintenance use.
  - .2 Provide minimum 20 tiles of each type and colour of tile required for project for maintenance use. Store where directed.
  - .3 Maintenance material same production run as installed material.

### PART 2 - PRODUCTS

#### 2.1 FLOOR TILE

- .1 Porcelain Floor tile, resistant to acid, frost proof;
  - .1 Size: 301 x 605 mm
  - .2 Thickness: 9.5mm, or 10mm
  - .3 Texture/Pattern: stone
  - .4 Edges: Rectified
  - .5 Water Absorption: <0.5% ISO 10545-3
  - .6 Breaking Strength: 35N/mm<sup>2</sup> ISO 10545-4
  - .7 PEI: 4
  - .8 Resistance to Acid: GLA ISO 10545-13
  - .9 Stain Resistance: 4 ISO 10545-14

- .10 Frost Resistance: frost proof ISO 10545-12
- .11 Static Coefficient of Friction: DIN51097 A+B+C, DIN51130 R11, DCOFBOT3000 >0.42
- .12 Complete with 7x75mm purpose made base to match.
- .13 Colour: To be selected by Departmental Representative from manufacturer's standard colour range.

## 2.2 ACCESSORIES

- .1 Movement joints;
  - .1 Provide around perimeter of new tile installation, between floor tile and tile base.
  - .2 Stainless steel with trapezoid perforated leg secured in mortar bond coat and cove section that forms the visible surface with 10mm radius in 2348mm lengths, complete with purpose made inside and outside corners.
  - .3 Install as per manufacturers written instructions.
- .2 Polyethylene Uncoupling Membrane;
  - .1 Provide under all new floor tile installation.
  - .2 Sized to eliminate transition height differences at existing floors.
  - .3 10 year warranty.
- .3 Control joints:
  - .1 Of type recommended by uncoupling membrane manufacturer for specified installation. Submit sample to Departmental Representative for approval.
  - .2 Install over existing control joints or sawcuts in concrete slab.

## 2.3 MORTAR AND ADHESIVE MATERIALS

- .1 Cement: to CSA-A5, type 10.
- .2 Sand: to ASTM C 144, passing 16 mesh.
- .3 Hydrated lime: to ASTM C 207
- .4 Latex additive: formulated for use in cement mortar and thin set bond coat.
- .5 Water: potable and free of minerals and chemicals which are detrimental to mortar and grout mixes.
- .6 Adhesives:
  - .1 Maximum VOC limit 65 g/L to SCAQMD Rule 1168.

## 2.4 SELF-LEVELLING UNDERLAYMENT

- .1 Cement-based, quick setting, self levelling, self-drying underlayment for engineer approved floors,

very fluid once mixed, installation from featheredge 6mm to at least 138mm in a single application.

## 2.5 BOND COAT

- .1 Provide bond coat to suit application, as per manufacturer's specifications:
  - .1 Full coverage medium-bed mortars, latex-Portland cement mortar (minimum acceptable standard ANSI A 118.4), modified epoxy emulsion mortars or 100% solids epoxy mortar to minimum acceptable standard ANSI A 118.3
  - .2 Organic adhesive: to CGSB 71-GP-22M.
  - .3 Latex Cement mortar: to ANSI A108.1, two-component universal dry-set mortar.
  - .4 Epoxy bond coat: non-toxic, non-flammable, non-hazardous during storage, mixing, application, and when cured. To produce shock and chemical resistant mortars having the following physical characteristics:
    - .1 Compressive Strength: 246 kg/cm<sup>2</sup>.
    - .2 Bond Strength: 53 kg/cm<sup>2</sup>.
    - .3 Water Absorption: 4.0% Max.
    - .4 Ozone Resistance, 200 hours @ 200 ppm: no loss of strength.
    - .5 Smoke Contribution Factor: 0.
    - .6 Flame Contribution Factor: 0.
    - .7 Finished mortar and grout to be resistant to urine, dilute acid, dilute alkali, sugar, brine and food waste products, petroleum distillates, oil and aromatic solvents.
    - .8 Bond Coat: maximum VOC limit 65 g/L.
  - .5 Chemical-Resistant Bond Coat:
    - .1 Epoxy Resin Type: CTI A118.3.
    - .2 Furan Resin Type: CTI A118.5.
  - .6 Bond Coat: maximum VOC limit 65 g/L to SCAQMD Rule 1168.

## 2.6 GROUT

- .1 High-strength alumina cement based acrylic grout suitable for general interior, exterior and underwater applications and providing superior resistance against microorganisms and mould.
  - .1 4mm grout lines maximum.
  - .2 Efflorescence free.
  - .3 Abrasion resistance to CG 2 WA nach, DIN EN 13888.
  - .4 Chemical resistance:
    - .1 Formic acid ≤ 3%: conditionally resistant.
    - .2 Acetic acid ≤ 2%: resistant, ≤ 5% conditionally resistant.
    - .3 Lactic acid ≤ 5%: conditionally resistant.
    - .4 Hydrochloric acid ≤ 2%: conditionally resistant.
    - .5 Tartaric acid ≤ 5%: conditionally resistant.
    - .6 Citric acid ≤ 2%: resistant, ≤ 5% conditionally resistant.
    - .7 Phosphoric acid ≤ 2%: resistant, ≤ 5%: conditionally resistant, alkaline solution ≤ 10%:

- resistant.
- .8 Ammonia  $\leq$  25%: resistant.
- .9 Calcium hydroxide  $\leq$  10%: resistant.
- .10 Solvents: acetone, ethanol, isopropanol-xylol: resistant.
- .2 Colour: To be selected by Departmental Representative from manufacturer's standard colour range.
  - .1 Colouring Pigments:
    - .1 Pure mineral pigments, limeproof and nonfading, complying with ASTM C 979.
    - .2 Colouring pigments to be added to grout by manufacturer.
    - .3 Job coloured grout are not acceptable.
    - .4 Use in Commercial Cement Grout, Dry-Set Grout, and Latex Cement Grout.

## 2.7 CLEANING COMPOUNDS

- .1 Specifically designed for cleaning masonry and concrete and which will not prevent bond of subsequent tile setting materials including patching and leveling compounds and elastomeric waterproofing membrane and coat.
- .2 Materials containing acid or caustic material are not acceptable.

## PART 3- EXECUTION

### 3.1 MANUFACTURER'S INSTRUCTIONS

- .1 Compliance: comply with manufacturer's written recommendations or specifications, including product technical bulletins, handling, storage and installation instructions, and datasheets.

### 3.2 WORKMANSHIP

- .1 Do tile work in accordance with TTMAC Tile Installation Manual 2006/2007, "Ceramic Tile", 329 LFT-2016-2017 Large format tile on interior floors.
- .2 Apply tile or backing coats to clean and sound surfaces.
- .3 Fit tile around corners, fitments, fixtures, drains and other built-in objects. Maintain uniform joint appearance. Cut edges smooth and even. Do not split tiles.
- .4 Maximum surface tolerance 1:800.
- .5 Make joints between tile uniform and approximately 1.5 mm wide, plumb, straight, true, even and flush with adjacent tile. Align patterns.
- .6 Lay out tiles as indicated on drawings. With factory tile edge (not cut) to abut existing carpet tile

finish to remain.

- .7 Sound tiles after setting and replace hollow-sounding units to obtain full bond.
- .8 Allow minimum 24 hours after installation of tiles, before grouting.
- .9 Clean installed tile surfaces after installation and grouting cured.

### 3.3 FIELD QUALITY CONTROL

- .1 Manufacturer's Field Services:
  - .1 Provide manufacturer's field services consisting of product use recommendations and periodic site visits for inspection of product installation in accordance with manufacturer's instructions.

### 3.4 CLEANING

- .1 Proceed in accordance with Section 01 74 11 - Cleaning.

END OF SECTION

PART 1- GENERAL

1.1 REFERENCES

- .1 ASTM International
  - .1 ASTM D 2047-11, Standard Test Method for Static Coefficient of Friction of Polish-Coated Flooring Surfaces as Measured by the James Machine.
  - .2 ASTM E662-15a/NFPA258, Standard Test Method for Specific Optical Density of Smoke Generated by Solid Materials.
  - .3 ASTM E648-15e1, Test Method for Critical Radiant Flux of Floor-Covering Systems.
  - .4 ASTM D2047, Test Method for Static Coefficient of Friction.
  - .5 ASTM F970, Test Method for Static Load Limit.
- .2 BSI Group
  - .1 BS 7976, Pendulum test.
- .3 CAN/ULC
  - .1 CAN/ULCS102.2, Test of Surface Burning Characteristics
- .4 DIN Deutsches Institut Fur Normung E.V.
  - .1 DIN 51130, Anti-slip property, Ramp test.
- .5 Standards Australia
  - .1 ISO 140-8-2006, Acoustics, Sound Insulation, Reduction of transmitted impact noise by floor coverings.
- .6 South Coast Air Quality Management District (SCAQMD), California State, Regulation XI. Source Specific Standards
  - .1 SCAQMD Rule 1168-A2005, Adhesives and Sealants Applications.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
  - .1 Submit manufacturer's instructions, printed product literature and data sheets for flooring, adhesive, sealer, and include product characteristics, performance criteria, physical size, finish and limitations.
  - .2 Submit 2 copies of WHMIS MSDS in accordance with Section 01 35 29 - Health and Safety

Requirements.

- .3 Samples:
  - .1 Submit for review and acceptance of each unit.
  - .2 Samples will be returned for inclusion into work.
  - .3 Submit duplicate 300 x 300 mm sample pieces of sheet material.
  - .4 Submit 300 mm long base and weld strips.
- .4 Sustainable Design Submittals:
  - .1 Construction Waste Management:
    - .1 Submit project Waste Management Plan, and Waste Reduction Workplan highlighting recycling and salvage requirements in accordance with Section 01 74 21.
  - .2 Low-Emitting Materials:
    - .1 Submit listing of adhesives and coatings used in building, showing compliance with VOC and chemical component limits or restriction requirements.

#### 1.3 CLOSEOUT SUBMITTALS

- .1 Submit in accordance with Section 01 78 00 - Closeout Submittals.
- .2 Operation and Maintenance Data: submit operation and maintenance data for resilient flooring for incorporation into manual.

#### 1.4 MAINTENANCE MATERIAL SUBMITTALS

- .1 Extra Materials:
  - .1 Provide maintenance materials of resilient tile flooring, base and adhesive in accordance with Section 01 78 00 - Closeout Submittals.
  - .2 Provide 2% of total amount used, of each colour, pattern and type flooring material required for this project for maintenance use.
  - .3 Extra materials from same production run as installed materials.
  - .4 Identify each container of floor tile and each container of adhesive.
  - .5 Deliver to Departmental Representative, upon completion of the work of this section.
  - .6 Store where directed by Departmental Representative.

#### 1.5 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging,

labelled with manufacturer's name and address.

- .3 Storage and Handling Requirements:
  - .1 Store materials off ground, indoors, in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
  - .2 Store and protect resilient flooring from nicks, scratches, and blemishes.
  - .3 Replace defective or damaged materials with new.
- .4 Packaging Waste Management: remove for reuse and return by manufacturer of pallets, crates, padding, and packaging materials as specified in Construction Waste Management Plan in accordance with Section 01 74 21 - Waste Management.

#### 1.6 SITE CONDITIONS

- .1 Ensure high ventilation rate, with maximum outside air, during installation.
  - .1 Vent directly to outside.
  - .2 Do not let contaminated air recirculate through a district or whole building air distribution system. Refer to Section 01 14 10 Scheduling and Management of Work.
- .2 Ambient Conditions:
  - .1 Maintain air temperature and structural base temperature at flooring installation area above 20 degrees for 48 hours before, during and 48 hours after installation.

### PART 2 - PRODUCTS

#### 2.1 MATERIALS

- .1 (RS1, RS2) Commercial resilient vinyl sheet flooring for Heavy Traffic. Heterogeneous PVC with a glass fiber reinforcement scrim between wood grain print and integral acoustic backing.
  - .1 Pattern: wood look
  - .2 Surface texture: embossed
  - .3 Thickness: 3.7mm
  - .4 Width: 2m
  - .5 Length: 20m
  - .6 Wear Layer: .65mm min.
  - .7 Coating: protective urethane wear layer
  - .8 Colours: from standard range, to be selected by Departmental Representative.
  - .9 Warranty: 10 year commercial warranty.
  - .10 VOC emissions: Passes CA-01350
  - .11 Installation: Glue down
  - .12 Fire and Smoke: Tested to CAN/ULC-S102.2, ASTM E648 Class 1, ASTM E662 <450
  - .13 Slip Resistance: ASTM D2047 .83D/.97W, DIN 51130 R10, BS 7976 TRRL 36+



- .14 Sound Insulation: ISO 140-8 18dB
- .15 Static Load: ASTM F970 500psi
- .16 Seams: Heat Weld
- .17 Cleaning: factory treatment to increase ease of cleaning. No wax, no polish required.
- .18 Backing Recycled content: 100% recycled PUR foam with binder

## 2.2 ACCESSORIES

- .1 (RB) Resilient base: continuous, top set, complete with premoulded end stops and external corners:
  - .1 Type: rubber.
  - .2 Style: Cove with toe.
  - .3 Thickness: 3.2 mm.
  - .4 Height: 102 mm.
  - .5 Lengths: cut lengths minimum 2400 mm.
  - .6 Colour: from standard range to be selected by Departmental Representative.
- .2 Primers and adhesives: of types recommended by resilient flooring manufacturer for specific material on applicable substrate.
  - .1 Resilient floor adhesives:
    - .1 Adhesive: maximum VOC limit 60 g/L to SCAQMD Rule 1168.
  - .2 Rubber Base adhesives:
    - .1 Adhesive: maximum VOC limit 50 g/L to SCAQMD Rule 1168.
- .3 Sub-floor filler and leveller: white premix latex requiring water only to produce cementitious paste or as recommended by flooring manufacturer for use with their product.
- .4 External corner protectors: stainless steel, type recommended by flooring manufacturer.
- .5 Edging to floor penetrations: stainless steel, type recommended by flooring manufacturer

## PART 3- EXECUTION

### 3.1 EXAMINATION

- .1 Examine conditions, substrates and work to receive work of this Section.
- .2 Verification of Conditions: verify conditions of substrates previously installed under other Sections or Contracts are acceptable for product installation in accordance with manufacturer's written instructions.
  - .1 Visually inspect substrate in presence of Departmental Representative.

- .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
- .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

### 3.2 INSPECTION

- .1 Ensure concrete floors are clean and dry by using test methods recommended by flooring manufacturer.

### 3.3 PREPARATION

- .1 Prepare for installation in accordance with manufacturer's written recommendations.
- .2 Remove sub-floor ridges and bumps and fill low spots, cracks, joints, holes and other defects with sub-floor filler. Treat control joints as recommended by manufacturer's written instructions.
- .3 Ensure existing flooring is removed by trained personnel.
- .4 Remove or treat existing adhesives to prevent residual bleeding through to new flooring or interfering with bonding of new adhesives.
- .5 Seal concrete slab as recommended by resilient flooring manufacturer's written instructions.
- .6 Prepare subfloor so that finished floor height will match adjacent floor finishes.

### 3.4 APPLICATION: FLOORING

- .1 Flooring to be installed by a professional flooring installer with specialized training when recommended by manufacturer's written instructions.
- .2 Flooring to be installed to meet manufacturer's warranty requirements.
- .3 Apply adhesive uniformly using recommended trowel. Do not spread more adhesive that can be covered by flooring before initial set takes place.
- .4 Run sheets in direction as shown on drawings. Double cut sheet joints and heat weld according to manufacturer's printed instructions.
- .5 Cut flooring neatly around fixed objects.
- .6 Continue flooring over areas which will be under built-in furniture or millwork.
- .7 Terminate resilient flooring at centreline of door in openings where adjacent floor finish or colour

is dissimilar, or at edge of existing floor finish to remain.

- .8 Install factory edge (not cut) where floor abuts existing floor finish to remain, where possible.
- .9 Ensure that flooring runs under base to conceal cut edges where flooring meets vertical surfaces.

### 3.5 APPLICATION: BASE

- .1 Lay out base to keep number of joints at minimum.
- .2 Clean substrate and prime with one coat of adhesive.
- .3 Apply adhesive to back of base.
- .4 Set base against wall and floor surfaces tightly by using 3 kg hand roller.
- .5 Install straight and level to variation of 1:1000.
- .6 Scribe and fit to door frames and other obstructions. Use premoulded end pieces at flush door frames.
- .7 Cope internal corners using premoulded corner units for right angle external corners and formed straight base material for external corners of other angles.

### 3.6 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
  - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
  - .1 Remove excess adhesive from floor, base and wall surfaces without damage.
  - .2 Follow manufacturer's printed instructions for initial cleaning procedure.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section

01 74 21 - Waste Management.

### 3.7 PROTECTION

- .1 Protect installed products and components from damage during construction.
- .2 Protect new floors in accordance with manufacturer's printed instructions.
- .3 Prohibit traffic on floor after installation in accordance with manufacturer's printed instructions. Refer to Section 01 14 10 for operational restrictions; Dining Area must be accessible to tenants during operational hours.

### 3.8 SCHEDULES

- .1 Refer to drawings.

END OF SECTION



revision	date
REV 0	01/7/2017 FOR NOK REVIEW
REV 1	03/7/2017 FOR NOK REVIEW
REV 2	03/7/2017 FOR NOK REVIEW
REV 3	03/7/2017 ISSUED FOR TENDER

**JAG  
FLOORING REPLACEMENT**

## LOBBY AND CAFETERIA

[illegible]

1-800-441-0000 ext. 547915



