



RETURN BIDS TO:

RETOURNER LES SOUMISSIONS À:

Bid Receiving Public Works and Government
Services Canada/Réception des soumissions Travaux
publics et Services gouvernementaux Canada
800 Burrard Street, Room 219
800, rue Burrard, pièce 219
Vancouver, BC V6Z 0B9
Bid Fax: (604) 775-7526

SOLICITATION AMENDMENT MODIFICATION DE L'INVITATION

The referenced document is hereby revised; unless otherwise
indicated, all other terms and conditions of the Solicitation
remain the same.

Ce document est par la présente révisé; sauf indication contraire,
les modalités de l'invitation demeurent les mêmes.

Comments - Commentaires

Vendor/Firm Name and Address

Raison sociale et adresse du
fournisseur/de l'entrepreneur

Issuing Office - Bureau de distribution

Public Works and Government Services Canada - Pacific
Region
219 - 800 Burrard Street
800, rue Burrard, pièce 219
Vancouver, BC V6Z 0B9

Title - Sujet Herbicide Tractor	
Solicitation No. - N° de l'invitation 01550-180154/A	Amendment No. - N° modif. 002
Client Reference No. - N° de référence du client 01550-180154	Date 2017-09-05
GETS Reference No. - N° de référence de SEAG PW-\$VAN-585-8146	
File No. - N° de dossier VAN-7-40167 (585)	CCC No./N° CCC - FMS No./N° VME
Solicitation Closes - L'invitation prend fin at - à 02:00 PM on - le 2017-09-26	
Time Zone Fuseau horaire Pacific Daylight Saving Time PDT	
F.O.B. - F.A.B. Plant-Usine: <input type="checkbox"/> Destination: <input checked="" type="checkbox"/> Other-Autre: <input type="checkbox"/>	
Address Enquiries to: - Adresser toutes questions à: Nelson, Jodi	Buyer Id - Id de l'acheteur van585
Telephone No. - N° de téléphone (604) 364-9827 ()	FAX No. - N° de FAX () -
Destination - of Goods, Services, and Construction: Destination - des biens, services et construction:	

Instructions: See Herein

Instructions: Voir aux présentes

Delivery Required - Livraison exigée	Delivery Offered - Livraison proposée
Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur	
Telephone No. - N° de téléphone Facsimile No. - N° de télécopieur	
Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)	
Signature	Date

Solicitation No. - N° de l'invitation
01550-180154/A
Client Ref. No. - N° de réf. du client
01550-180154

Amd. No. - N° de la modif.
002
File No. - N° du dossier
VAN-7-40167

Buyer ID - Id de l'acheteur
van585
CCC No./N° CCC - FMS No/ N° VME

Amendment #2 – 01550-180154/A

The above referenced solicitation is amended as follows:

Page 11, Annex A: Requirement, 5. Engine, Item 5.1

Remove: "The tractor must have a minimum net engine power output of 70 horsepower"

Insert: "The tractor must have a minimum gross engine power output of 70 horsepower"

All other terms and conditions remain unchanged.

Item #	FORM B: Substantiation of Technical Compliance	Compliant		Supporting Documentation or Statement of Compliance (please indicate where this information can be found in your Bid)
		Yes	No	
1.0	Tractor must be four wheel drive.			
2.0	All standards and specifications referenced herein refer and must adhere to the current regulations laid out by the Society of Automotive Engineers (SAE). The specifications as laid out in SAE J1150 must apply.			
3.1.a	The tractor must be the manufacturer's latest model.			
3.1.b	The tractor must be a new built, standard commercial product.			
3.2	The tractor must be complete with all standard accessories as advertised to the public; all other required accessories will be specified herein.			
4.1	The tractor must be capable of operation in narrow field research plots, such as fruit tree plots and vineyards.			
4.2	The tractor must operate without failure of components when operated continuously at the specified RPM (revolution per minute) of 540.			
4.3	Overall width: The tractor must be a Minimum of 40 inches / Maximum of 55 inches.			
4.4	Height to the top of the Cab: The tractor height must be a Minimum of 80 inches / Maximum of 100 inches.			
4.5	Overall length: The tractor length must be a Minimum of 120 inches / Maximum of 160 inches.			
4.6	Operating speed: The tractor must have a minimum operating speed of 16km/h (10 mph) when operating in top gear.			
4.7	Operating weight of the unit: The tractor must have a Minimum weight of 4,900 lbs / Maximum weight of 6,000 lbs.			
5.1	The tractor must have a minimum gross engine power output of 70 horsepower, with a 4 cycle turbo diesel engine.			
5.2	The tractor must have a minimum power take off (PTO) of 60 horsepower with 540/540E option.			
5.3	The tractor must have a full flow type oil filter with a user-replaceable element.			
5.4	The tractor must have an oil pressure and temperature gauge and engine hour meter.			
5.5	The tractor must have a full flow fuel/water separator incorporating a replacement element.			
5.6	The tractor must have coolant protection to -35C; coolant must be included with delivery.			
5.7	The tractor must have a dry type air cleaner with a user-replaceable element.			

Item #	<u>FORM B: Substantiation of Technical Compliance</u>	Compliant		Supporting Documentation or Statement of Compliance (please indicate where this information can be found in your Bid)
		Yes	No	
6.1	The tractor must be minimum 12 X 12 standard shuttle transmission, with a minimum infinite speed range of 0-16 km/h (0-10 mph).			
7.1	The tractor must have brakes on both rear drive wheels, and a parking brake.			
8.1	The wheels and tires must comply with the axle manufacturer's rating for imposed loads and operating conditions.			
8.2	The rear tires must be agricultural tread pattern, liquid calcium filled tires.			
8.3	The front tires must be agricultural tread pattern tires.			
9.1	The exhaust system must be installed with an elbow or side mounted exhaust, and must have a muffler.			
10.1	The tractor must have a maintenance free battery with a minimum total of 400 cold cranking amps.			
10.2	The electrical system must be 12 volts, and must be equipped with a circuit able to support two electrical convenience outlets.			
10.3	The alternator must have a minimum output of 20 amps.			
11.1	The rear wheels must have fenders; if the fenders are removable they must be in place when meeting the tractor's general size specifications.			
11.2	The tractor must have a heavy duty removable radiator grill guard to prevent grass fouling, and an engine hood; if the tractor has side panels, the panels must be easily removable.			
11.3	The tractor must have guards or shields to ensure safety during servicing and operation.			
11.4	The tractor must have a Rollover Protective Structure (ROPS) guard.			
12.1	The tractor must have a full cab with two (2) doors; both doors must open and must be detachable.			
12.2	The cab must have windshield wipers front and rear.			
12.3	The cab must have a heater complete with window defrost system and air conditioning.			
12.4	The cab must have folding rear view mirrors.			
13.1.a	The hydraulic system must have a minimum ten gallon per minute oil capacity.			
13.1.b	The hydraulic system must have filtration (with replaceable filters).			

Item #	FORM B: Substantiation of Technical Compliance	Compliant		Supporting Documentation or Statement of Compliance (please indicate where this information can be found in your Bid)
		Yes	No	
13.1.c	The hydraulic system must have two (2) rear hydraulic remotes.			
13.2	Hydraulics for the attachments must be readily coupled to the system with industry standard quick-disconnect fittings.			
13.3	The system must have a minimum 5 GPM at 2000 PSI hydraulic capacity.			
14.1	The tractor must have the following minimum lights: <ul style="list-style-type: none"> - two (2) rear fender tail/ break/ turn lights; - cab dome light; - head lights; - front and rear hazard lights; and - front and rear upper cab lights. 			
15.1	The tractor must have a minimum 40 litre fuel tank.			
16.1	The tractor must have permanently installed ISO or English instructions, diagrams, and warning plates to ensure efficient and safe operation and servicing.			
17.1.a	Must include four (4) front end weights with mounting brackets configured to industry standard and include quick change capability.			
17.1.b	Must include a three point hitch system on rear, including top arm configured to industry standard and include quick change capability.			
17.1.c	Must include a removable draw bar configured to industry standard and include quick change capability.			
18.1	The Contractor must provide an English copy of both the operator's maintenance manual and the spare parts manual at the time of delivery. The manuals may be in hard copy or electronic form.			
19.1	The unit must include an onsite warranty on all components and repair labour for a minimum of 24 months or 2000 operational hours from the date the unit is introduced into service.			
20.1	The Contractor must list the repair depot responsible for performing any required warranty repairs.			
21.1	The pre-delivery service must be completed by the manufacturer's dealer located closest to the operating site.			List repair depot address and contact information.
21.2	The tractor must be lubricated and serviced with all associated products suitable for the climatic conditions in the region in which the tractor will operate.			
21.3	The tractor must be delivered to the final destination with a maximum of 20 operational hours on the unit.			
22.1	The Contractor must ensure that the tractor is tested and inspected prior to delivery.			