1.1 SECTION INCLUDES

.1 Barriers.

.2 Environmental Controls.

.3 Traffic Controls.

.4 Fire Routes.

1.2 RELATED SECTIONS

.1 Section 01 35 29 - Health and Safety Requirements.

.2 Section 01 50 00 - Temporary Facilities.

1.3 REFERENCES

.1 Canadian Standards Association (CSA International)
.1 CSA O80.02 Series-08, Wood Preservation
.2 CSA-O121-[M1978], Douglas Fir Plywood.

1.4 INSTALLATION AND REMOVAL

.1 Provide temporary controls in order to execute Work expeditiously.

.2 Remove from site all such work after use.

1.5 SITE ENCLOSURE

.1 Erect temporary site enclosure using new [1.2] m high snow fence wired to rolled steel "T" bar fence posts spaced at [2.4] m oc. Provide [one] lockable truck gate. Maintain fence in good repair.

1.6 GUARD RAILS AND BARRICADES

.1 Provide secure, rigid guard rails and barricades around deep excavations, open shafts, open stair wells, open edges of

floors and roofs.

1.7 DUST TIGHT SCREENS

.1 Provide dust tight screens or [insulated] partitions to localize dust generating activities, and for protection of workers, finished areas of Work and public.

.2 Maintain and relocate protection until such work is complete.

1.8 PUBLIC TRAFFIC FLOW

.1 Provide and maintain competent signal flag operators, traffic signals, barricades and flares, lights, or lanterns as required to perform Work and protect the public.

1.9 FIRE ROUTES

.1 Maintain access to property including overhead clearances for use by emergency response vehicles.

1.10 PROTECTION FOR OFF-SITE AND PUBLIC PROPERTY

.1 Protect surrounding private and public property from damage during performance of Work.

.2 Be responsible for damage incurred.

END OF SECTION