



RETURN BIDS TO:

RETOURNER LES SOUMISSIONS À:

Bid Receiving Public Works and Government
Services Canada/Réception des soumissions Travaux
publics et Services gouvernementaux Canada
Room 100,
167 Lombard Ave.
Winnipeg
Manitoba
R3B 0T6
Bid Fax: (204) 983-0338

SOLICITATION AMENDMENT MODIFICATION DE L'INVITATION

The referenced document is hereby revised; unless otherwise
indicated, all other terms and conditions of the Solicitation
remain the same.

Ce document est par la présente révisé; sauf indication contraire,
les modalités de l'invitation demeurent les mêmes.

Comments - Commentaires

Vendor/Firm Name and Address
Raison sociale et adresse du
fournisseur/de l'entrepreneur

Issuing Office - Bureau de distribution
Public Works and Government Services Canada -
Western Region
Room 100
167 Lombard Ave.
Winnipeg
Manitoba
R3B 0T6

Title - Sujet Compact Track Loader	
Solicitation No. - N° de l'invitation H3567-173030/A	Amendment No. - N° modif. 002
Client Reference No. - N° de référence du client H3567-173030	Date 2017-11-22
GETS Reference No. - N° de référence de SEAG PW-\$WPG-113-10349	
File No. - N° de dossier WPG-7-40120 (113)	CCC No./N° CCC - FMS No./N° VME
Solicitation Closes - L'invitation prend fin at - à 02:00 PM on - le 2017-12-11	
Time Zone Fuseau horaire Central Standard Time CST	
F.O.B. - F.A.B. Plant-Usine: <input type="checkbox"/> Destination: <input checked="" type="checkbox"/> Other-Autre: <input type="checkbox"/>	
Address Enquiries to: - Adresser toutes questions à: Chubey, Karen	Buyer Id - Id de l'acheteur wpg113
Telephone No. - N° de téléphone (204) 291-5928 ()	FAX No. - N° de FAX (204) 983-7796
Destination - of Goods, Services, and Construction: Destination - des biens, services et construction:	

Instructions: See Herein

Instructions: Voir aux présentes

Delivery Required - Livraison exigée	Delivery Offered - Livraison proposée
Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur	
Telephone No. - N° de téléphone Facsimile No. - N° de télécopieur	
Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)	
Signature	Date

COMPACT TRACK LOADER

Amendment No. 002 is raised to answer questions and amend the Solicitation as follows:

Amendment No. 002 is raised to answer:

QUESTION 1:

Q1: Are the following modifications to the minimum mandatory performance specifications acceptable?

a) **Item # 2.2** Auxiliary hydraulic flow= 17-23 gpm

2.2- auxiliary hydr. Flow: Max. to **24 gpm**

ANSWER: A Maximum Hydraulic flow rate of 24 gpm is acceptable. Reference amendment 1.

b) **Item # 3.1** Rated operating capacity – 35% tipping load = 2240 – 2380 lbs

3.1- ROC: Max. to **2800 lbs**

ANSWER: A maximum Rated Operating Capacity of 2800 lbs. is acceptable. Reference amendment 1.

c) **Item # 3.2** Tipping load (lbs) = 6400 – 6800 lbs

3.2- Tipping load: Max. to **8000 lbs**

ANSWER: A maximum Tipping Load of 8000 lbs. is acceptable. Reference amendment 1.

d) **Item # 3.3** Breakout force (lbf)

Bucket = 6204 – 6500 lbf

3.3. Bucket breaking force: Max. to **7200 lbf**

ANSWER: A maximum Bucket Breaking Force of 7200 lbs. is acceptable. Reference amendment 1.

e) **Item #3.3** Lift arm = 4766- 5000 lbf

3.3. lift arm breaking force: Max. to **5900 lbf**

ANSWER: A maximum Lift Arm Breaking Force of 5900 lbf. is acceptable. Reference amendment 1.

f) **Item # 4.1** Travel speed (mph) = min 4.7 mph – max 7.1 mph

travel speed: max speed changes from 7.1 to **7.8 mph** & min speed changes from 4.7 to **4.8 mph**

ANSWER: A minimum 4.8 mph and maximum 7.8 mph Travel Speed is acceptable. Reference amendment 1.

g) Item # 6.3 Top/Rear window – (360 degree cab view)

360 degree is not possible for the cab visibility (**max 270**)

ANSWER: A 270 degree would be acceptable as it would be difficult to obtain a full 360 degree cab view if cab pillars are taken into account. Reference amendment 1.

h) Item # 6.12 Working lights (Front 2 / Rear 2)

Is it possible to have 1 rear working light instead of 2?

ANSWER: Due to safety concerns the unit needs to have 2 front and 2 rear working lights for extra visibility as unit is used to clear snow in public parking lots and a driveway leading out to a provincial highway.

i) Item #6.20 Skid steer must be compatible with each of the existing attachments that are listed below.

- a. Snow blower – Make : Allied (farm king), Model # F1534
- b. Pallet forks – Make : Kobota, Model # S6621A
- c. Street sweeper – Make : Worksite Pro, Model BP72

Do you know if they have the same hitching system?

ANSWER: Yes, all attachments use a Universal attachment system.

Amendment No. 002 is raised to amend:

AMENDMENT 1: Reference RFP page 12 ANNEX 'A' STATEMENT OF REQUIREMENT

DELETE:

COMPLIANCE MATRIX – MINIMUM MANDATORY PERFORMANCE SPECIFICATIONS in its entirety.

INSERT:

COMPLIANCE MATRIX – MINIMUM MANDATORY PERFORMANCE SPECIFICATIONS:

Requirement	Manufacturer Offered:	Model number Offered#
Compact Track Loader		

Item #	Requirements	Status (M) Mandatory (D) Desirable	Specification Met Indicate either Yes/No	Performance Specification Offered: Bidder should indicate how they meet the performance specification by recording this information in this column	Cross Reference: In this column, Bidders should cross-reference where this performance specification is indicated in their supporting documents.
1. General Requirements					
1.1	Equipment offered must be new and not used or refurbished	M			
1.2	Horsepower (kw) = minimum 74 Hp	M			
1.3	Type - Diesel - Turbo Charged	M			
2. Hydraulic System					
2.1	High flow (gpm) = 26-36 gpm	M			
2.2	Auxiliary hydraulic flow= 17-24 gpm	M			
3. Loader Performance					
3.1	Rated operating capacity – 35% tipping load = 2240 – 2800 lbs	M			
3.2	Tipping load (lbs) = 6400 – 8000 lbs	M			
3.3	Breakout force (lbf) Bucket = 6204 – 7200 lbf Lift arm = 4766- 5900 lbf	M			
4 Drive Train (rubber tracks)					
4.1	Travel speed (mph) = min 4.7 mph – max 7.8 mph	M			
4.2	Track (min. width) = 15 inches	M			
4.3	Track ground contact length (inches) = min. 56.5 in	M			
4.4	Track rollers (per side) – Min. 4	M			

Solicitation No. – N° de l'invitation
H3567-173030/A
Client Ref. No. - N° de réf. du client
H3567-173030

Amd. No. - N° de la modif.
002
File No. - N° du dossier
7342-H3567-173030

Buyer ID - Id de l'acheteur
wpg113
CCC No./N° CCC - FMS No./N° VME

4.5	Ground clearance = min. 9 inches	M			
5. Dimensions					
5.1	Bucket hinge pin height= Min. 119 in.	M			
5.2	Dump reach (inches) = Min. 34.5 in.	M			
6. Equipment Features, Controls & Safety					
6.1	Cab Enclosure pressurized with heat/ air conditioning	M			
6.2	Hand control Joy stick (loader & drive controls).	M			
6.3	Top/Rear window – (270 degree cab view)	M			
6.4	Suspension seat- adjustable	M			
6.5	Lap bar	M			
6.6	Seat belt	M			
6.7	Pull down arm rest	D			
6.8	Hand/Dial and Foot throttle	M			
6.9	Horn	M			
6.10	Backup alarm	M			
6.11	Strobe light	M			
6.12	Working lights (Front 2 / Rear 2)	M			
6.13	Glow plugs	M			
6.14	Hydraulic Quick Coupler	M			
6.15	Engine Block Heater	M			
6.16	Two speed travel – hi/low range	M			
6.17	Windshield wiper	M			
6.18	Rear view mirror	D			
6.19	Utility bucket with blade – min 60 in.	M			

Solicitation No. – N° de l'invitation
H3567-173030/A
Client Ref. No. - N° de réf. du client
H3567-173030

Amd. No. - N° de la modif.
002
File No. - N° du dossier
7342-H3567-173030

Buyer ID - Id de l'acheteur
wpg113
CCC No./N° CCC - FMS No./N° VME

6.20	Skid steer must be compatible with each of the existing attachments that are listed below. d. Snow blower – Make : Allied (farm king), Model # F1534 e. Pallet forks – Make : Kobota, Model # S6621A f. Street sweeper – Make : Worksite Pro, Model BP72	M			
7. Warranty and Other					
7.1	The Contractor must provide at least one (1) Parts and Service Manual. A CD of the manual is also acceptable	M			
7.2	The contractor must offer a minimum of 1 year full warranty including all parts and labour.	M			
7.3	Parts and Service – Available within 250 km of Hodgson, MB	M			

ALL OTHER TERMS AND CONDITIONS REMAIN THE SAME.