

Issued for Tender

1.1	Description of Work	.1	In general, work under this contract consist of: <ul style="list-style-type: none">.1 To remove 1 private office..2 To resize 3 Pr Offices, 1 Copy room, 3 Serveries..3 To construct 4 Quiet rooms, 1 Pr Office and 2 Small Meeting rooms..4 To refresh all finish materials (paint & flooring) throughout..5 To update all Mechanical and Electrical systems to support the densification of workstations..6 To update all Serveries to meet CSA-B651 for accessibilities..7 To make good all surfaces impacted by demolition/construction including ceilings..8 To reuse any redundant materials (i.e. doors, hardware, sidelights, etc.) to minimize waste going to landfill.
		.2	Site of Work is at: Bedford Institute of Oceanography in Dartmouth, NS.
1.2	Familiarization With Site	.1	Before submitting a bid, it is recommended that bidders visit the site to review and verify the form, nature and extent of the work, materials needed, the means of access and the temporary facilities required to perform the Work.
		.2	Obtain prior permission from the Departmental Representative before carrying out such site inspection.
1.3	Codes and Standards	.1	Perform work in accordance with the 2015 National Building Code of Canada and any other code of provincial or local application, including all amendments up to bid closing date, provided that in any case of conflict or discrepancy, the more stringent requirement shall apply.
		.2	Materials and workmanship must meet or exceed requirements of specified standards, codes and referenced documents.
1.4	Interpretation of Documents	.1	Supplementary to the Order of Precedence article of the General Conditions of the Contract, the Division 01 sections take precedence over the technical specification sections in other Divisions of the Specification Manual.

-
- | | | | |
|------|--------------------------|-----|---|
| 1.5 | <u>Setting Out Work</u> | .1 | Assume full responsibility for and execute complete layout of work to locations, lines and elevations indicated. |
|
 | | | |
| 1.6 | <u>Cost Breakdown</u> | .1 | Before submitting first progress claim submit breakdown of Contract price in detail as directed by Departmental Representative and aggregating contract price. Required forms will be provided for application of progress payment. |
| | | .2 | List items of work numerically following the same division/section number system of the specification manual and thereafter sub-divide into major work components and building systems as directed by Departmental Representative. |
| | | .3 | Upon approval, cost breakdown will be used as basis for progress payment. |
|
 | | | |
| 1.7 | <u>Document Required</u> | .1 | Maintain at job site, one copy each of the following: |
| | | .1 | Contract Drawings |
| | | .2 | Specifications |
| | | .3 | Addenda |
| | | .4 | Reviewed Shop Drawings |
| | | .5 | List of outstanding shop drawings |
| | | .6 | Change Orders |
| | | .7 | Other modifications to Contract |
| | | .8 | Field Test Reports |
| | | .9 | Copy of Approved Work Schedule |
| | | .10 | Health and Safety Plan and other safety related documents |
| | | .11 | Other documents as stipulated elsewhere in the Contract Documents. |

Issued for Tender

<u>1.8 Permits</u>	.1	In accordance with the General Conditions, obtain and pay for any certificates, licenses and permits required by authorities having jurisdiction.
<u>1.9 Alterations, Additions or Repairs to Existing Building</u>	.1	Execute work with least possible interference or disturbance to building operations, occupants, public and normal use of premises. Arrange with Departmental Representative to facilitate execution of work.
	.2	Where security has been reduced by work of Contract, provide temporary means to maintain security.
	.3	Material transportation is permitted afterhours. Elevators are to be protected. All damages to elevator finishes is the responsibility of the contractor.
	.4	Provide temporary dust screens, barriers, warning signs in locations where renovation and alteration work is adjacent to areas which will be operative during such work.
<u>1.10 Cutting, Fitting and Patching</u>	.1	Ensure that cutting and patching required by all trades is included in total bid price submitted for the work.

Issued for Tender

-
- | | | |
|------------------------|----|---|
| | .2 | Execute cutting including excavation, fitting and patching required to make work fit properly. |
| | .3 | Where new work connects with existing and where existing work is altered, cut, patch and make good to match existing work. |
| | .4 | Do not cut, bore, or sleeve load-bearing members, except where specifically approved by Departmental Representative. |
| | .5 | Make cuts with clean, true, smooth edges. Make patches inconspicuous in final assembly. |
| | .6 | Fit work airtight to pipes, sleeves ducts and conduits. |
| 1.11 Existing Services | .1 | Where work involves breaking into or connecting to existing services, carry out work at times directed by governing authorities, with minimum of disturbance to pedestrian, vehicular traffic and tenant operations. |
| | .2 | Before commencing work, establish location and extent of service lines in area of work and notify Departmental Representative of findings. |
| | .3 | Submit schedule to and obtain approval from Departmental Representative for any shut-down or closure of active service or facility. This includes disconnection of electrical power and communication services to tenant's operational areas. Adhere to approved schedule and provide notice to affected parties. |
| | .4 | Provide temporary services when directed by Departmental Representative to maintain critical building and tenant systems. |
| | .5 | Provide adequate bridging over trenches which cross sidewalks or roads to permit normal traffic. |

Issued for Tender

- .6 Where unknown services are encountered, immediately advise Departmental Representative and confirm findings in writing.
- .7 Protect, relocate or maintain existing active services as required. When inactive services are encountered, cap off in manner approved by authorities having jurisdiction over service. Record locations of maintained, re-routed and abandoned service lines.

1.12 Building Smoking
Environment

- .1 Comply with smoking restrictions.

END OF SECTION

1.1 Submittals

- .1 Upon acceptance of bid and prior to commencement of work, submit to Departmental Representative the following work management documents:
- .1 Work Schedule as specified herein.
 - .2 Shop Drawing Submittal Schedule specified in Section 01 33 00 - Submittal Procedures.
 - .3 Waste Management Plan specified in Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
 - .4 Health and Safety Plan specified in section 01 35 29 - Health and Safety Requirements.
 - .5 Hot Work Procedures specified in Section 01 35 24 - Special Procedures On Fire Safety Requirements.
 - .6 Lockout Procedures specified in Section 01 35 25 - Special Procedures On Lockout Requirements.
 - .7 Dust Control Plan specified in Section 01 50 00 - Temporary Facilities.

1.2 Work Schedule

- .1 Upon acceptance of bid submit:
- .1 Work schedule within five (5) calendar days of contract award.
- .2 Schedule to indicate all calendar dates from commencement to completion of all work within the time stated in the accepted bid.
- .3 Provide sufficient details in schedule to clearly illustrate entire implementation plan, depicting efficient coordination of tasks and resources, to achieve completion of work on time and permit effective monitoring of work progress in relation to established milestones.

- .4 Work schedule content to include as a minimum the following:
 - .1 Bar (GANTT) Charts, indicating all work activities, tasks and other project elements, their anticipated durations, planned dates for achieving key activities and major project milestones supported with;
 - .2 Written narrative on key elements of work illustrated in bar chart, providing sufficient details to demonstrate a reasonable implementation plan for completion of project within designated time.
- .5 Schedule work in cooperation with the Departmental Representative. Incorporate within Work Schedule, items identified by Departmental Representative during review of schedule.
- .6 Completed schedule shall be approved by Departmental Representative. When approved, take necessary measures to complete work within scheduled time. Do not change schedule without Departmental Representative's approval.
- .7 Ensure that all subtrades and subcontractors are made aware of the work restraints and operational restrictions specified.
- .8 Schedule Updates:
 - .1 Submit when requested by Departmental Representative.
 - .2 Provide information and pertinent details explaining reasons for necessary changes to implementation plan.
 - .3 Identify problem areas, anticipated delays, impact on schedule and proposed corrective measures to be taken.

	Issue for Tender
	<p>.9 Departmental Representative will make interim reviews and evaluate progress of work based on approved schedule. Frequency of such reviews will be as decided by Departmental Representative. Address and take corrective measures on items identified by reviews and as directed by Departmental Representative. Update schedule accordingly.</p> <p>.10 In every instance, change or deviation from the Work Schedule, no matter how minimal the risk or impact on safety or inconvenience to tenant or public might appear, will be subject to prior review and approval by the Departmental Representative.</p>
<u>1.3 Project Phasing</u>	<p>.1 Be aware that Facility and tenants must be kept operational for the full duration of work of this contract. Building services to areas under use by tenants must also be maintained at all times during the Facility's operational hours and as specifically defined in operational restrictions specified in this section.</p> <p>.2 Unless indicated or approved otherwise, complete all work of a particular phase prior to commencement of another phase.</p> <p>.3 Phasing: Phase 1 – Renovate 3rd floor (partial) + 5th floor; Phase 2 – Renovate 4th floor; Phase 3 – Renovate 2nd floor (partial) + 6th floor.</p> <p>.4 Allow 2 days per phase for furniture installation.</p>
<u>1.4 Operational Restrictions</u>	<p>.1 The Contractor must recognize that building occupants will be affected by implementation of this contract. The Contractor must perform the work with utmost regard to the safety and convenience of building occupants and users. All work activities must be planned and scheduled with this in mind. The Contractor will not be permitted to disturb any portion of the building without providing temporary facilities as necessary to ensure safe and direct passage through disturbed or otherwise affected areas.</p> <p>.2 Contractor to meet with the Departmental Representative on a weekly basis to identify intended work areas, activities and scheduling for the coming week.</p>

- .3 Off Hours: means a period of time which is outside the daily operational hours of the tenants of the Facility. For the purposes of this contract, Off-Hours are defined as follows:
 - .1 Weeknight Off-Hours: between the hours of 18:00 and 07:00 for each weekday Monday to Thursday inclusive.
 - .2 Weekend Off-Hours: between the hours of 18:00 Friday evening to 07:00 Monday morning.
 - .3 Dependent on the nature and location of the construction activity and due to an unanticipated operational requirement of the Tenant, certain off-hour periods may be redefined by adjusting the start and end time periods or cancellation of a specific off-hour work shift during the course of the Work.
 - .4 Note that off hours work is permitted provided prior approval is received from the Departmental Representative.
- .5 Departmental Representative reserves the right to stop certain daytime work activities, if the nature of that activity generates excessive noise or dust and have Contractor re-schedule that particular work to be performed during the Off-Hour period.
- .6 Facility circulation maintained:
 - .1 Ensure that entrances, corridors, stairwells, fire exits and other circulation routes are maintained free and clear providing safe and uninterrupted passage for Facility users and public at all times during the entire work.
 - .2 Maintain those areas clean and free of construction materials and equipment. Provide temporary dust barriers and other suitable enclosures to ensure users are not exposed to construction activities and are protected from exposure to dust, noise and hazardous conditions.

Issue for Tender	
.3	Provide temporary corridors, walkways, passageways, access to offices, etc. when required due to nature of work. Such circulation routes must be constructed to barrier free requirements unless approved otherwise by Departmental Representative.
.4	Maintain fire escape routes accessible and firefighting access open all times for the duration of the project.
.5	Do not under any circumstances block fire exit doors. Do not leave construction materials or debris in corridors, stairwells building entrances and exits.
.7	Safety Signage:
.1	Provide on site, and erect as required during progress of work, proper bilingual signage, mounted on self-supporting stands, warning the public and building occupants of construction activities in progress and alerting need to exercise caution in proceeding through disturbed areas of the facility, and directing building occupants through any detours which may be required.
.2	Signage to be professionally printed and mounted on wooden backing, coloured and to express messages as directed by the Departmental Representative.
.3	Generally maximum size of sign should be in the order of 1.0 square meters. Number of signs required will be dependent on number of areas in facility under renovation at any one time.
.4	Include costs for the supply and installation of these signs in the bid price.

		Issue for Tender
	.2	Cleaning of tenant occupied areas used by Contractor:
	.1	On a daily basis, clean lobbies, corridors, stairs and other circulation routes used by workers to gain access to work by conducting cleaning, vacuuming and washing of floors, walls and other soiled surfaces.
<u>1.5 Project Meetings</u>	.1	Departmental Representative will schedule project meetings on a bi-weekly basis and will minute minutes.
<u>1.6 Work Coordination</u>	.1	The General Contractor is responsible for coordinating the work of the various trades and predetermining where the work of such trades interfaces with each other.
	.1	Designate one person from own employ having overall responsibility to review contract documents and shop drawings, plan and manage such coordination.
	.2	The General Contractor shall convene meetings between trades whose work interfaces and ensure that they are fully aware of the areas and the extent of where interfacing is required.
	.1	Provide each trade with the plans and specs of the interfacing trade, as required, to assist them in planning and carrying out their respective work.
	.2	Develop coordination drawings when deemed required illustrating potential interference between work of various trades and distribute to all affected parties including structural trade.
	.1	Pay particularly close attention to overhead work above ceilings and within or near to building structural elements.
	.2	Coordination drawings to identify all building elements, services lines, rough-in points and indicate from where various services are coming.

-
- Issue for Tender
-
- .3 Review coordination drawings at purposely called meetings. Have subcontractors sign-off on drawings and publish minutes of each meeting.
 - .4 Plan and coordinate work in such a way to minimize quantity of service line offsets.
 - .5 Submit copy of coordination drawings and meeting minutes to Departmental Representative for information purposes.
 - .3 Submission of shop drawings and ordering of prefabricated equipment or prebuilt components shall only occur once coordination meeting for such items has taken place between trades and all conditions affecting the work of the interfacing trades has been made known and accounted for.
 - .4 Work Cooperation:
 - .1 Ensure cooperation between trades in order to facilitate the general progress of the work and avoid situations of spatial interference.
 - .2 Ensure that each trade provides all other trades reasonable opportunity for the completion of the work and in such a way as to prevent unnecessary delays, cutting, patching and the need to remove and replace completed work.
 - .5 No extra costs to the Contract will be considered by the Departmental Representative as a result of Contractor's failure to effectively coordinate all portions of the Work.
Disputes between the various trades as a result of their not being informed of the areas and extent of interface work shall be the sole responsibility of the General Contractor to be resolved at own cost.

END OF SECTION

Issued for Tender

1.1	Related Requirements	.1	Section 01 78 00 - Closeout Submittals.
1.2	Submittal General Requirements	.1	Submit to Departmental Representative for review requested submittals specified in various sections of the specifications including shop drawings, samples, permits, compliance certificates, test reports, work management plans and other data required as part of the work.
		.2	Submit with reasonable promptness and in orderly sequence so as to allow for Departmental Representative's review and not cause delay in Work. Failure to submit in ample time will not be considered sufficient reason for an extension of Contract time and no claim for extension by reason of such default will be allowed.
		.3	Do not proceed with work until relevant submissions have been reviewed.
		.4	Present shop drawings, product data, samples and mock-ups in SI Metric units.
		.5	Where items or information is not produced in SI Metric units, provide soft converted values.
		.6	Review submittals prior to submission. Ensure that necessary requirements have been determined and verified and that each submittal has been checked and co-ordinated with requirements of Work and Contract Documents.
		.1	Submittals not stamped, signed, dated and identified as to specific project will be returned unexamined by Departmental Representative and considered rejected.
		.7	Verify field measurements and affected adjacent Work are coordinated.

Issued for Tender

-
- .8 Notify Departmental Representative, in writing at time of submission, identifying deviations from requirements of Contract Documents stating reasons for deviations.
 - .9 Contractor's responsibility for errors, omissions or deviations in submission from requirements of Contract Documents is not relieved by Departmental Representative's review.
 - .10 Submittal format: Electronic
 - .11 Make changes or revision to submissions which Departmental Representative may require, consistent with Contract Documents and resubmit as directed by Departmental Representative. When resubmitting, identify in writing of any revisions other than those requested.
 - .12 Keep one reviewed copy of each submittal document on site for duration of Work.
- 1.3 Shop Drawings and Product Data
- .1 The term "shop drawings" means fabrication drawings, erection drawings, diagrams, illustrations, schedules, performance charts, technical product data, brochures, specifications, test reports installation instructions and other data which are to be provided by Contractor to illustrate compliance with specified materials and details of a portion of work.
 - .2 Shop Drawing Submittal Schedule:
 - .1 Submit within seven (7) working days of acceptance of bid a schedule listing all shop drawings to be submitted for project.

Issued for Tender

- .2 Schedule shall be in format acceptable to Departmental Representative and indicate proposed submission date for each item, status of review and anticipated product delivery date to site. Track all submissions for entire project.
 - .3 Revise schedule as work progresses. Identify items which have been reviewed and finalized and indicating those outstanding.
 - .4 Update schedule at stipulated dates or project time intervals predetermined and agreed upon with Departmental Representative at commencement of Work.
- .3 Shop Drawing Quantities: submit one electronic PDF copy.
- .4 Shop Drawings Format:
- .1 High resolution scan or print-to- PDF.
 - .2 Drawing to be original drawings or standard drawings modified to clearly illustrate work specific to project requirements.
 - .3 Product Data from manufacturer's standard catalogue sheets, brochures, literature, performance charts and diagrams, used to illustrate standard manufactured products, to be full colour, clearly marked indicating applicable data and deleting information not applicable to project.
 - .4 Non or poorly legible submissions/ information will not be accepted and will be returned not reviewed.

Issued for Tender

-
- .5 Shop Drawings Content:
 - .1 Indicate materials, methods of construction and attachment or anchorage, erection diagrams, connections, explanatory notes and other information necessary for completion of Work. Where items or equipment attach or connect to other items or equipment, confirm that all interrelated work have been coordinated, regardless of section or trade from which the adjacent work is being supplied and installed.
 - .2 Supplement manufacturer's standard drawings and literature with additional information to provide details applicable to project.
 - .3 Delete information not applicable to project on all submittals.
 - .6 Allow 7 calendar days for Departmental Representative's review of each submission.
 - .7 Adjustments or corrections made on shop drawings by Departmental Representative are not intended to change Contract Price. If adjustments affect value of Work, advise Departmental Representative in writing prior to proceeding with Work.
 - .8 If upon review by Departmental Representative, no errors or omissions are discovered or if only minor corrections and comments are made, fabrication and installation may proceed upon receipt of shop drawings. If shop drawings are rejected and noted to be Resubmitted, do not proceed with that portion of work until resubmission and review of corrected shop drawings, through same submission procedures indicated above.

Issued for Tender

-
- .9 Be advised that costs and expenses incurred by Departmental Representative to conduct more than one review of incorrectly prepared shop drawing submittal for a particular material, equipment or component of work may be assessed against the Contractor in the form of a financial holdback to the Contract.
 - .10 Accompany each submissions with transmittal letter, in duplicate, containing:
 - .1 Date.
 - .2 Project title and project number.
 - .3 Contractor's name and address.
 - .4 Identification and quantity of each shop drawing, product data and sample.
 - .5 Other pertinent data.
 - .11 Submissions shall include:
 - .1 Date and revision dates.
 - .2 Project title and project number.
 - .3 Name and address of:
 - .1 Subcontractor.
 - .2 Supplier.
 - .3 Manufacturer.
 - .4 Contractor's stamp, signed by Contractor's authorized Representative certifying approval of submissions, verification of field measurements and compliance with Contract Documents.
 - .5 Cross references to particular details of contract drawings and specifications section number for which shop drawing submission addresses.
 - .6 Details of appropriate portions of Work as applicable:
 - .1 Fabrication.
 - .2 Layout, showing dimensions, including identified field dimensions, and clearances.
 - .3 Setting or erection details.
 - .4 Capacities.
 - .5 Performance characteristics.
 - .6 Standards.
 - .7 Operating weight.
 - .8 Wiring diagrams.

Issued for Tender

- .9 Single line and schematic diagrams.
- .10 Relationship to adjacent work.
- .12 After Departmental Representative's review, distribute copies.
- .13 The review of shop drawings by the Departmental Representative or by an authorized Consultant or designate is for sole purpose of ascertaining conformance with general concept. This review shall not mean that Canada approves the detail design inherent in the shop drawings, responsibility for which shall remain with Contractor submitting same, and such review shall not relieve Contractor of responsibility for errors or omissions in shop drawings or of responsibility for meeting all requirements of the construction and Contract Documents. Without restricting generality of foregoing, Contractor is responsible for dimensions to be confirmed and correlated at job site, for information that pertains solely to fabrication processes or to techniques of construction and installation and for co-ordination of Work of all sub-trades.

1.4 Samples

- .1 Submit for review samples as specified in respective specification Sections. Label samples with origin and intended use.
- .2 Deliver samples to Departmental Representative's office or to other address as directed. Do not drop off samples at construction site except for pre-approved circumstances previously approved by Departmental Representative.
- .3 Notify Departmental Representative in writing, at time of submission of deviations in samples from requirements of Contract Documents.
- .4 Where colour, pattern or texture is criterion, submit full range of samples.

Issued for Tender

- .5 Adjustments made on samples by Departmental Representative are not intended to change Contract Price. If adjustments will result in a cost increase to the Contract notify Departmental Representative in writing prior to proceeding with Work.
- .6 Make changes in samples which Departmental Representative may require, consistent with Contract Documents.
- .7 Reviewed and accepted samples will become standard of workmanship and material against which installed Work will be verified.

END OF SECTION

1.1	<u>Related Requirements</u>	.1	Section 01 35 29 - Health and Safety Requirements
1.2	<u>References</u>	.1	Fire Protection Standards issued by Fire Protection Services, Labour Program Division of Service Canada: <ul style="list-style-type: none">.1 FCC No. 301-June 1982 Standard for Construction Operations..2 FCC No. 302-June 1982 Standard for Welding and Cutting.
		.2	FCC standards may be viewed at: <ul style="list-style-type: none">.1 http://www.hrsdc.gc.ca/en/lp/lo/fp/standards/commissioner.shtml
1.3	<u>Definitions</u>	.1	Hot Work defined as: <ul style="list-style-type: none">.1 Welding work.2 Cutting of materials by use of torch or other open flame devices.3 Grinding with equipment which produces sparks..4 Use of open flame torches such as for roofing work.
1.4	<u>Submittals</u>	.1	Submit copy of Hot Work Procedures and sample of Hot Work permit to Departmental Representative for review, within 14 calendar days of acceptance of bid.
		.2	Submit in accordance with section 01 33 00 - Submittal Procedures.
1.5	<u>Fire Safety Requirements</u>	.1	Implement and follow fire safety measures during Work. Comply with following: <ul style="list-style-type: none">.1 National Fire Code..2 Fire Protection Standards FCC 301 and FCC 302..3 Federal and Provincial Occupational Health and Safety Acts and Regulations.
		.2	In event of conflict between any provisions of above authorities the most stringent provision will apply. Should a dispute arise in determining the most stringent requirement, Departmental Representative will advise on the course of action to be followed.

Issued for Tender

-
- | | | | |
|-----|-----------------------------------|----|---|
| 1.6 | <u>Hot Work
Authorization</u> | .1 | Obtain Departmental Representative's written "Authorization to Proceed" before conducting any form of Hot Work on site. |
| | | .2 | To obtain authorization submit to Departmental Representative: <ul style="list-style-type: none">.1 Contractor's typewritten Hot Work Procedures to be followed on site as specified below..2 Description of the type and frequency of Hot Work required..3 Sample Hot Work Permit to be used. |
| | | .3 | Upon review and confirmation that effective fire safety measures will be implemented and followed during performance of hot work, Departmental Representative will give authorization to proceed as follows: <ul style="list-style-type: none">.1 Issue one written "Authorization to Proceed" covering the entire project for duration of work or;.2 Subdivide the work into pre- determined, individual activities, each activity requiring a separately written authorization to proceed. |
| | | .4 | Requirement for individual authorization will be based on: <ul style="list-style-type: none">.1 Nature or phasing of work;.2 Risk to Facility operations;.3 Quantity of various trades needing to perform hot work on project or;.4 Other situation deemed necessary by Departmental Representative to ensure fire safety on premises. |
| | | .5 | Do not perform any Hot Work until receipt of Departmental Representative's written "Authorization to Proceed" for that portion of work. |

Issued for Tender

-
- | | | |
|-----|---------------------|---|
| | .6 | In tenant occupied Facility, coordinate performance of Hot Work with Facility Manager through the Departmental Representative. When directed, perform Hot Work only during non-operative hours of the Facility. Follow Departmental Representative's directives in this regard. |
| 1.7 | Hot Work Procedures | |
-
- | | | |
|--|----|--|
| | .1 | Develop and implement safety procedures and work practices to be followed during the performance of Hot Work. |
| | .2 | Hot Work Procedures to include: <ul style="list-style-type: none">.1 Requirement to perform hazard assessment of site and immediate work area beforehand for each hot work event in accordance with Safety Plan specified in section 01 35 29 - Health and Safety Requirements..2 Use of a Hot Work Permit system with individually issued permit by Contractor's Superintendent to worker or subcontractor granting permission to proceed with Hot Work..3 Permit required for each Hot Work event..4 Designation of a person on site as a Fire Safety Watcher responsible to conduct a fire safety watch for a minimum duration of 60 minutes immediately following the completion of the Hot Work..5 Compliance with fire safety codes, standards and occupational health and safety regulations specified..6 Site specific rules and procedures in force at the site as provided by the Facility Manager. |
| | .3 | Generic procedures, if used, must be edited and supplemented with pertinent information tailored to reflect specific project conditions. Label document as being the Hot Work Procedures for this contract. |

Issued for Tender

- .4 Procedures shall clearly establish responsibilities of:
 - .1 Worker performing hot work,
 - .2 Person issuing the Hot Work Permit,
 - .3 Fire Safety Watcher,
 - .4 Subcontractor(s) and Contractor.
- .5 Brief all workers and subcontractors on Hot Work Procedures and of Permit system. Stringently enforce compliance.

1.8 Hot Work Permit

- .1 Hot Work Permit to include the following:
 - .1 Project name and project number;
 - .2 Building name and specific room or area where hot work will be performed;
 - .3 Date of issue;
 - .4 Description of hot work type needed;
 - .5 Special precautions to be followed, including type of fire extinguisher needed;
 - .6 Name and signature of permit issuer.
 - .7 Name of worker to which the permit is issued.
 - .8 Permit validity period not to exceed 8 hours. Indicate start time/date and termination time/date.
 - .9 Worker's signature with time/date of hot work completion.
 - .10 Stipulated time period of safety watch.
 - .11 Fire Safety Watcher's signature with time/date.
- .2 Permit to be typewritten form. Industry Standard forms shall only be used if all data specified above is included on form.
- .3 Each Hot Work Permit to be completed in full, signed and returned to Contractor's Superintendent for safe keeping on site.

1.9 Fire Protection and Alarm Systems

- .1 Fire protection and alarm systems shall not be:
 - .1 Obstructed.

Issued for Tender

- .2 Shut-off, unless approved by
Departmental Representative.
- .3 Left inactive at the end of a working
day or shift.

- .2 Do not use fire hydrants, standpipes and hose systems
for purposes other than firefighting.

1.10 Documents On
Site

- .1 Keep Hot Work Permits and Hazard assessment
documentation on site for duration of Work.
- .2 Upon request, make available to Departmental
Representative or to authorized safety
Representative for inspection.

END OF SECTION

1.1	Related Requirements	.1	Section 01 35 29 - Health and Safety
1.2	References	.1	Canadian Standards Association (CSA).
		.1	CSA C22.1-06 - Canadian Electrical Code, Part 1, Safety Standard for Electrical Installations.
		.2	CAN/CSA C22.3 No.1-06 - Overhead Systems.
		.3	CSA C22.3 No.7-06 - Underground Systems.
		.2	COSH: Canada Occupational Health and Safety Regulations made under Part II of the Canada Labour Code.
1.3	Definitions	.1	Electrical Facility: means any system, equipment, device, apparatus, wiring, conductor, assembly or part thereof that is used for the generation, transformation, transmission, distribution, storage, control, measurement or utilization of electrical energy, and that has an amperage and voltage that is dangerous to persons.
		.2	Guarantee of Isolation: means a guarantee by a competent person in control or in charge that a particular facility or equipment has been isolated.
		.3	De-energize: in the electrical sense, that a piece of equipment is isolated and grounded, e.g. if the equipment is not grounded, it cannot be considered de-energized (DEAD).
		.4	Guarded: means that an equipment or facility is covered, shielded, fenced, enclosed, inaccessible by location, or otherwise protected in a manner that, to the extent that is reasonably practicable, will prevent or reduce danger to any person who might touch or go near such item.

-
- | | | |
|---------------------------------------|----|--|
| | .5 | Isolate: means that an electrical facility, mechanical equipment or machinery is separated or disconnected from every source of electrical, mechanical, hydraulic, pneumatic or other kind of energy that is capable of making it dangerous. |
| | .6 | Live/alive: means that an electrical facility produces, contains, stores or is electrically connected to a source of alternating or direct current of an amperage and voltage that is dangerous or contains any hydraulic, pneumatic or other kind of energy that is capable of making the facility dangerous to persons. |
| 1.4 | | |
| <u>Compliance Requirements</u> | .1 | Comply with the following in regards to isolation and lockout of electrical facilities and equipment: <ul style="list-style-type: none">.1 Canadian Electrical Code.2 Federal and Provincial Occupational Health and Safety Acts and Regulations..3 Regulations and code of practise as applicable to mechanical equipment or other machinery being de- energized..4 Procedures specified herein. |
| | .2 | In event of conflict between any provisions of above authorities the most stringent provision will apply. |
| 1.5 | | |
| <u>Submittals</u> | .1 | Submit copy of lockout procedures, sample of lockout permit and lockout tags proposed for use in accordance with Section 01 33 00 - Submittal Procedures. Submit within 14 calendar days of acceptance of bid. |
| 1.6 | | |
| <u>Isolation of Existing Services</u> | .1 | Obtain Departmental Representative's written authorization prior to working on existing live or active electrical facilities and equipment and before proceeding with isolation of such item. |

Issued for Tender

- .2 To obtain authorization, submit to Departmental Representative the following documentation:
 - .1 Written request to isolate the particular service or facility and;
 - .2 Copy of Contractor's Lockout Procedures.
- .3 Make a Request for Isolation for each event, unless directed otherwise by Departmental Representative, as follows:
 - .1 Fill-out standard form in current use at the Facility as provided by Departmental Representative or;
 - .2 Where no form exist, make written request indicating:
 - .1 The equipment, system or service to be isolated and its location;
 - .2 Duration of isolation period (i.e.: start time & date and completion time & date).
 - .3 Voltage of service feed to system or equipment being isolated.
 - .4 Name of person making the request.
- .4 Do not proceed with isolation until receipt of written notification from Departmental Representative granting the Isolation Request and authorizing to proceed with the work.
 - .1 Note that Departmental Representative may designate another person at the Facility being authorized to grant the Isolation Request.
- .5 Conduct safe, orderly shutdown of equipment or facility. De-energize, isolate and lockout power and other sources of energy feeding the equipment or facility.
- .6 Determine in advance, as much as possible, in cooperation with the Departmental Representative, the type and frequency of situations which will require isolation of existing services.

Issued for Tender

1.7 Lockouts

- .7 Plan and schedule shut down of existing services in consultation with the Departmental Representative and the Facility Manager. Minimize impact and downtime of Facility operations. Follow Departmental Representative's directives in this regard.
- .8 Conduct hazard assessment as part of the process in accordance with health and safety requirements specified Section 01 35 29 - Health and Safety Requirements.
- .1 De-energize, isolate and lockout electrical facility, mechanical equipment and machinery from all potential sources of energy prior to working on such items.
- .2 Develop and implement clear and specific lockout procedures to be followed as part of the Work.
- .3 Prepare typed written Lockout Procedures describing safe work practices, procedures, worker responsibilities and sequence of activities to be followed on site by workforce to safely isolate an active piece of equipment or electrical facility and effectively lockout and tagout it's sources of energy.
- .4 Include as part of the Lockout Procedures a system of lockout permits managed by Contractor's Superintendent or other qualified person designated by him/her as being "in-charge" at the site.
 - .1 A lockout permit shall be issued to specific worker providing a Guarantee of Isolation before each event when work must be performed on a live equipment or electrical facility.
 - .2 Duties of person managing the permit system to include:
 - .1 Issuance of permits and lockout tags to workers.
 - .2 Determining permit duration.

Issued for Tender

- .3 Maintaining record of permits and tags issued.
 - .4 Making a Request for Isolation to Departmental Representative when required as specified above.
 - .5 Designating a Safety Watcher, when one is required based on type of work.
 - .6 Ensuring equipment or facility has been properly isolated.
 - .7 Collecting and safekeeping lockout tags returned by workers as a record of the event.
- .5 Clearly establish, describe and allocate responsibilities of:
- .1 Workers
 - .2 Person managing the lockout permit system.
 - .3 Safety Watcher.
 - .4 Subcontractor(s) and General Contractor.
- .6 Generic procedures, if used, must be edited and supplemented with pertinent information to reflect specific project requirements.
- .1 Incorporate site specific rules and procedures in force at site as provided by Facility Manager through the Departmental Representative.
 - .2 Clearly label the document as being the Lockout procedures applicable to work of this contract.
- .7 Use energy isolation lockout devices specifically designed and appropriate for type of facility or equipment being locked out.
- .8 Use industry standard lockout tags.
- .9 Provide appropriate safety grounding and guards as required.
- 1.8 Conformance
- .1 Brief all workers and subcontractors on requirements of this section.
Stringently enforce use and compliance.

Issued for Tender

- | | | | |
|-----|------------------------------|----|--|
| 1.9 | <u>Documents On
Site</u> | .1 | Post Lockout Procedures on site in common location for viewing by workers. |
| | | .2 | Keep copies of Request for Isolation forms and lockout permits and tags issued to workers on site for full duration of Work. |
| | | .3 | Upon request, make available to Departmental Representative or to authorized safety Representative for inspection. |

END OF SECTION

Issued for Tender

-
- | | | | |
|-----|----------------------|----|--|
| 1.1 | Related Requirements | .1 | Section 01 35 24 - Special Procedures on Fire Safety Requirements. |
| | | .2 | Section 01 35 25 - Special Procedures on Lockout Requirements |
-
- | | | | |
|-----|-------------|----|---|
| 1.2 | Definitions | .1 | COSH: Canada Occupational Health and Safety Regulations made under Part II of the Canada Labour Code. |
| | | .2 | Competent Person: means a person who is: <ul style="list-style-type: none">.1 Qualified by virtue of personal knowledge, training and experience to perform assigned work in a manner that will ensure the health and safety of persons in the workplace, and;.2 Knowledgeable about the provisions of occupational health and safety statutes and regulations that apply to the Work and;.3 Knowledgeable about potential or actual danger to health or safety associated with the Work. |
| | | .3 | Medical Aid Injury: any minor injury for which medical treatment was provided and the cost of which is covered by Workers' Compensation Board of the province in which the injury was incurred. |
| | | .4 | PPE: personal protective equipment |
| | | .5 | Work Site: where used in this section shall mean areas, located at the premises where Work is undertaken, used by Contractor to perform all of the activities associated with the performance of the Work. |
-
- | | | | |
|-----|------------|----|---|
| 1.3 | Submittals | .1 | Make submittals in accordance with Section 01 33 00 - Submittal Procedures. |
| | | .2 | Submit site-specific Health and Safety Plan prior to commencement of Work. <ul style="list-style-type: none">.1 Submit within five (5) work days of notification of Bid Acceptance.
Provide three (3) copies..2 Departmental Representative will review Health and Safety Plan and provide comments. |

Issued for Tender

-
- .3 Revise the Plan as appropriate and resubmit within five (5) work days after receipt of comments.
 - .4 Departmental Representative's review and comments made of the Plan shall not be construed as an endorsement, approval or implied warranty of any kind by Canada and does not reduce Contractor's overall responsibility for Occupational Health and Safety of the Work.
 - .5 Submit revisions and updates made to the Plan during the course of Work.
 - .3 Submit name of designated Health & Safety Site Representative and support documentation specified in the Safety Plan.
 - .4 Submit building permit, compliance certificates and other permits obtained.
 - .5 Submit copy of Letter in Good Standing from Provincial Workers Compensation or other department of labour organization.
 - .1 Submit update of Letter of Good Standing whenever expiration date occurs during the period of Work.
 - .6 Submit copies of reports or directions issued by Federal, Provincial and Territorial health and safety inspectors.
 - .7 Submit copies of incident reports.
 - .8 Submit WHMIS MSDS - Material Safety Data Sheets.
 - 1.4 Compliance Requirements
 - .1 Comply with Occupational Health and Safety Act for Province of Nova Scotia, and Regulations made pursuant to the Act.

- .2 Comply with Canada Labour Code - Part II (entitled Occupational Health and Safety) and the Canada Occupational Health and Safety Regulations (COSH) as well as any other regulations made pursuant to the Act.
 - .1 The Canada Labour Code can be viewed at:
[www.http://laws.justice.gc.ca/en/L-2/](http://laws.justice.gc.ca/en/L-2/)
 - .2 COSH can be viewed at:
[www.http://laws.justice.gc.ca/eng/SOR-86-304/ene.html](http://laws.justice.gc.ca/eng/SOR-86-304/ene.html)
 - .3 A copy may be obtained at: Canadian Government Publishing Public Works & Government Services Canada Ottawa, Ontario, K1A 0S9 Tel: (819) 956-4800 (1-800-635-7943)
Publication No. L31-85/2000 E or F)
- .3 Observe construction safety measures of:
 - .1 Part 8 of National Building Code
 - .2 Municipal by-laws and ordinances.
- .4 In case of conflict or discrepancy between above specified requirements, the more stringent shall apply.
- .5 Maintain Workers Compensation Coverage in good standing for duration of Contract. Provide proof of clearance through submission of Letter in Good Standing.
- .6 Medical Surveillance: Where prescribed by legislation or regulation, obtain and maintain worker medical surveillance documentation.

1.5 Responsibility

- .1 Be responsible for health and safety of persons on site, safety of property on site and for protection of persons and environment adjacent to the site to extent that they may be affected by conduct of Work.

-
- .2 Comply with and enforce compliance by all workers, sub-contractors and other persons granted access to Work Site with safety requirements of Contract Documents, applicable federal, provincial, and local by-laws, regulations, and ordinances, and with site-specific Health and Safety Plan.
- 1.6 Site Control and Access
- .1 Control the Work and entry points to Work Site. Approve and grant access only to workers and authorized persons. Immediately stop and remove non- authorized persons.
- .1 Departmental Representative will provide names of those persons authorized by Departmental Representative to enter onto Work Site and will ensure that such authorized persons have the required knowledge and training on Health and Safety pertinent to their reason for being at the site, however, Contractor remains responsible for the health and safety of authorized persons while at the Work Site.
- .2 Isolate Work Site from other areas of the premises by use of appropriate means.
- .1 Erect fences, hoarding, barricades and temporary lighting as required to effectively delineate the Work Site, stop non-authorized entry, and to protect pedestrians and vehicular traffic around and adjacent to the Work and create a safe environment. See Section 01 50 00 - Temporary Facilities for minimum acceptable requirements.
- .2 Post signage at entry points and other strategic locations indicating restricted access and conditions for access.
- .3 Use professionally made signs with bilingual message in the 2 official languages or international known graphic symbols.

-
- | | | |
|--------------------------------|----|--|
| | .4 | Provide safety orientation session to persons granted access to Work Site. Advise of hazards and safety rules to be observed while on site. |
| | .5 | Ensure persons granted site access wear appropriate PPE. Supply PPE to inspection authorities who require access to conduct tests or perform inspections. |
| | .6 | Secure Work Site against entry when inactive or unoccupied and to protect persons against harm. |
| <u>1.7 Protection</u> | .1 | Give precedence to safety and health of persons and protection of environment over cost and schedule considerations for Work. |
| | .2 | Should unforeseen or peculiar safety related hazard or condition become evident during performance of Work, immediately take measures to rectify situation and prevent damage or harm. Advise Departmental Representative verbally and in writing. |
| <u>1.8 Filing of Notice</u> | .1 | File Notice of Project with pertinent provincial health and safety authorities prior to beginning of Work. |
| | .1 | Departmental Representative will assist in locating address if needed. |
| <u>1.9 Permits</u> | .1 | Post permits, licenses and compliance certificates, specified in section 01 10 10 - General Instructions, at Work Site. |
| | .2 | Where a particular permit or compliance certificate cannot be obtained, notify Departmental Representative in writing and obtain approval to proceed before carrying out applicable portion of work. |
| <u>1.10 Hazard Assessments</u> | .1 | Perform site specific health and safety hazard assessment of the Work and its site. |

-
- | | | |
|--------------------------------|----|--|
| | .2 | Carryout initial assessment prior to commencement of Work with further assessments as needed during progress of work, including when new trades and subcontractors arrive on site. |
| | .3 | Record results and address in Health and Safety Plan. |
| | .4 | Keep documentation on site for entire duration of the Work. |
| 1.11 | | |
| <u>Project/Site Conditions</u> | .1 | Following are potential safety hazards at the site for which Work may involve contact with: |
| | .1 | Know latent site and environmental conditions |
| | .1 | Working from heights. |
| | .2 | Roof fastening coordination with existing electrical conduit below the roof deck. |
| | .3 | Coordination/alterations to existing gas line. |
| | .4 | Remove and reinstallation of existing equipment. |
| | .2 | Above items shall not be construed as being complete and inclusive of potential health and safety hazards encountered during work. |
| | .3 | Include above items in the hazard assessment of the Work. |
| | .4 | MSDS Data sheets of pertinent hazardous and controlled products stored on site can be obtained from Departmental Representative. |
| 1.12 | | |
| <u>Meetings</u> | .1 | Attend pre-construction health and safety meeting, convened and chaired by Departmental Representative, prior to commencement of Work, at time, date and location determined by Departmental Representative. Ensure attendance of: |
| | .1 | Superintendent of Work |
| | .2 | Designated Health & Safety Site Representative |
| | .3 | Subcontractors |

Issued for Tender

1.13 Health and
Safety Plan

- .2 Conduct regularly scheduled tool box and safety meetings during the Work in conformance with Occupational Health and Safety regulations.
- .3 Keep documents on site.
- .1 Prior to commencement of Work, develop written Health and Safety Plan specific to the Work. Implement, maintain, and enforce Plan for entire duration of Work and until final demobilization from site.
- .2 Health and Safety Plan shall include the following components:
 - .1 List of health risks and safety hazards identified by hazard assessment.
 - .2 Control measures used to mitigate risks and hazards identified.
 - .3 On-site Contingency and Emergency Response Plan as specified below.
 - .4 On-site Communication Plan as specified below.
 - .5 Name of Contractor's designated Health & Safety Site Representative and information showing proof of his/her competence and reporting relationship in Contractor's company.
 - .6 Names, competence and reporting relationship of other supervisory personnel used in the Work for occupational health and safety purposes.
- .3 On-site Contingency and Emergency Response Plan shall include:
 - .1 Operational procedures, evacuation measures and communication process to be implemented in the event of an emergency.
 - .2 Evacuation Plan: site and floor plan layouts showing escape routes, marshalling areas. Details on alarm notification methods, fire drills, location of firefighting equipment and other related data.

Issued for Tender

- .3 Name, duties and responsibilities of persons designated as Emergency Warden(s) and deputies.
- .4 Emergency Contacts: name and telephone number of officials from:
 - .1 General Contractor and subcontractors.
 - .2 Pertinent Federal and Provincial Departments and Authorities having jurisdiction.
 - .3 Local emergency resource organizations.
- .5 Harmonize Plan with Facility's Emergency Response and Evacuation Plan. Departmental Representative will provide pertinent data including name of PWGSC and Facility Management contacts.
- .4 On-site Communication Plan:
 - .1 Procedures for sharing of work related safety information to workers and subcontractors, including emergency and evacuation measures.
 - .2 List of critical work activities to be communicated with Facility Manager which have a risk of endangering health and safety of Facility users.
- .5 Address all activities of the Work including those of subcontractors.
- .6 Review Health and Safety Plan regularly during the Work. Update as conditions warrant to address emerging risks and hazards, such as whenever new trade or subcontractor arrive at Work Site.
- .7 Departmental Representative will respond in writing, where deficiencies or concerns are noted and may request re- submission of the Plan with correction of deficiencies or concerns.
- .8 Post copy of the Plan, and updates, prominently on Work Site.

Issued for Tender

- | | | | |
|------|-------------------------------|----|--|
| 1.14 | <u>Safety
Supervision</u> | .1 | Employ Health & Safety Site Representative responsible for daily supervision of health and safety of the Work. |
| | | .2 | Health & Safety Site Representative may be the Superintendent of the Work or other person designated by Contractor and shall be assigned the responsibility and authority to: <ul style="list-style-type: none">.1 Implement, monitor and enforce daily compliance with health and safety requirements of the Work.2 Monitor and enforce Contractor's site-specific Health and Safety Plan..3 Conduct site safety orientation session to persons granted access to Work Site..4 Ensure that persons allowed site access are knowledgeable and trained in health and safety pertinent to their activities at the site or are escorted by a competent person while on the Work Site..5 Stop the Work as deemed necessary for reasons of health and safety. |
| | | .3 | Health & Safety Site Representative must: <ul style="list-style-type: none">.1 Be qualified and competent person in occupational health and safety..2 Have site-related working experience specific to activities of the Work..3 Be on Work Site at all times during execution of the Work. |
| | | .4 | All supervisory personnel assigned to the Work shall also be competent persons. |
| | | .5 | Inspections: <ul style="list-style-type: none">.1 Conduct regularly scheduled safety inspections of the Work on a minimum bi-weekly basis. Record deficiencies and remedial action taken. |

Issued for Tender

-
- | | | |
|---------------------------------------|----|---|
| | .2 | Conduct Formal Inspections on a minimum monthly basis. Use standardized safety inspection forms. Distribute to subcontractors. |
| | .3 | Follow-up and ensure corrective measures are taken. |
| | .6 | Cooperate with Facility's Occupational Health and Safety representative should one be designated by Departmental Representative. |
| | .7 | Keep inspection reports and supervision related documentation on site. |
| <u>1.15 Training</u> | .1 | Use only skilled workers on Work Site who are effectively trained in occupational health and safety procedures and practices pertinent to their assigned task. |
| | .2 | Maintain employee records and evidence of training received. Make data available to Departmental Representative upon request. |
| | .3 | When unforeseen or peculiar safety- related hazard, or condition occur during performance of Work, follow procedures in place for Employee's Right to Refuse Work in accordance with Acts and Regulations of Province having jurisdiction and advise Departmental Representative verbally and in writing. |
| <u>1.16 Minimum Site Safety Rules</u> | .1 | Notwithstanding requirement to abide by federal and provincial health and safety regulations; ensure the following minimum safety rules are obeyed by persons granted access to Work Site: |
| | .1 | Wear appropriate PPE pertinent to the Work or assigned task; minimum being hard hat, safety footwear, safety glasses and hearing protection. |
| | .2 | Immediately report unsafe condition at site, near-miss accident, injury and damage. |
| | .3 | Maintain site and storage areas in a tidy condition free of hazards causing injury. |

Issued for Tender

-
- | | | |
|--|----|---|
| | .4 | Obey warning signs and safety tags. |
| | .2 | Brief persons of disciplinary protocols to be taken for non-compliance. Post rules on site. |
| 1.17 <u>Correction of Non-Compliance</u> | .1 | Immediately address health and safety non-compliance issues identified by authority having jurisdiction or by Departmental Representative. |
| | .2 | Provide Departmental Representative with written report of action taken to correct non-compliance of health and safety issues identified. |
| | .3 | Departmental Representative will stop Work if non-compliance of health and safety regulations is not corrected in a timely manner. |
| 1.18 <u>Incident Reporting</u> | .1 | Investigate and report the following incidents to Departmental Representative: <ul style="list-style-type: none">.1 Incidents requiring notification to Provincial Department of Occupational Safety and Health, Workers Compensation Board or to other regulatory Agency..2 Medical aid injuries..3 Property damage in excess of \$10,000.00,.4 Interruptions to Facility operations resulting in an operational lost to a Federal department in excess of \$5000.00. |
| | .2 | Submit report in writing. |
| 1.19 <u>Hazardous Products</u> | .1 | Comply with requirements of Workplace Hazardous Materials Information System (WHMIS). |
| | .2 | Keep MSDS data sheets for all products delivered to site. <ul style="list-style-type: none">.1 Post on site..2 Submit copy to Departmental Representative..3 For interior work in an occupied Facility, post additional copy in one or more publically accessible locations. |

Issued for Tender

- | | |
|---|--|
| <u>1.20 Powder Actuated
Devices</u> | .1 Use powder actuated fastening devices only after receipt of written permission from Departmental Representative. |
| <u>1.21 Site Records</u> | <p>.1 Maintain on Work Site copy of safety related documentation and reports stipulated to be produced in compliance with Acts and Regulations of authorities having jurisdiction and of those documents specified herein.</p> <p>.2 Upon request, make available to Departmental Representative or authorized Safety Officer for inspection.</p> |
| <u>1.22 Posting of
Documents</u> | <p>.1 Ensure applicable items, articles, notices and orders are posted in conspicuous location on Work Site in accordance with Acts and Regulations of Province having jurisdiction.</p> <p>.2 Post other documents as specified herein, including:
 .1 Site specific Health and Safety Plan
 .2 WHMIS data sheets
 .3 Other pertinent information.</p> |

END OF SECTION

Issued for Tender

- | | | |
|--|----|--|
| <u>1.1 Related Requirements</u> | .1 | Section 01 74 21 - Construction/
Demolition Waste Management and Disposal. |
| <u>1.2 Definitions</u> | .1 | Hazardous Material: Product, substance, or organism that is used for its original purpose; and that is either dangerous goods or a material that may cause adverse impact to the environment or adversely affect health of persons, animals, or plant life when released into the environment. |
| <u>1.3 Fires</u> | .1 | Fires and burning of rubbish on site not permitted. |
| <u>1.4 Hazardous Material Handling</u> | .1 | Store and handle hazardous materials in accordance with applicable federal and provincial laws, regulations, codes and guidelines. Store in location that will prevent spillage into the environment |
| | .2 | Label containers to WHMIS requirements and keep MSDS data sheets on site for all hazardous materials. |
| | .3 | Maintain inventory of hazardous materials and hazardous waste stored on site. List items by product name, quantity and date when storage began. |
| | .4 | Store and handle flammable and combustible materials in accordance with National Fire Code. |
| | .5 | Transport hazardous materials in accordance with federal Transportation of Dangerous Goods Regulations and applicable Provincial regulations. |
| <u>1.5 Disposal of Wastes</u> | .1 | Do not bury rubbish and waste materials on site. Dispose in accordance with project waste management requirements specified in Section 01 74 21 - Construction/Demolition Waste Management and Disposal. |

END OF SECTION

1.1 General

- .1 Due to nature of this Facility, and client operations therein, security regulations pertaining to site will be in place during the work resulting in need for:
 - .1 Control and limit movement of construction workers at the site and inside building;
 - .2 Escort and continuous supervision of workers by security personnel within facility;
 - .3 Specific rules and regulations as specified in this section and as directed by the Departmental Representative to be stringently followed.
- .2 It is the Contractor's responsibility to:
 - .1 Become familiar with and abide by security rules and regulations;
 - .2 Brief all workers and subcontractors in respect of the security regulations and ensure that they abide by all rules and directives.
- .3 The Departmental Representative will coordinate a pre-construction meeting between Contractor, Facility Management and Security Personnel who will provide details and directives on control and movement on site.
 - .1 Note that building's custodial responsibilities are currently being managed by PWGSC.
- .4 Any infraction of site security regulations on the part of the Contractor, members of work force or any Subcontractor in his employ, could result in:
 - .1 Financial penalties being levied against the Contractor and;
 - .2 Demand immediate removal of offending party from the site.
- .1 Security personnel required only when Contractor is inside building.

1.2 Security Personnel

- .2 Specific to work performed inside of building, contractor shall schedule activities such that one area

Issued for Tender

of the interior of the building is accessed at a time, unless otherwise approved by the Departmental Representative.

- .3 Departmental Representative will provide and pay for services of security personnel.

1.3 Security Passes

- .1 Visitor or worker ID Tags are required for all personnel requiring access inside the building, beyond the main public lobby or on site.
- .2 ID Tags will be provided by the Facility Security, issued to Contractor for distribution to authorized workers which shall also be placed on the Security Control List specified below.
- .3 All persons while on site, must wear the ID Tag issued to him regardless of daytime or nighttime work.
- .4 Be responsible to obtain ID Tags before work commences, including those required by subcontractors, and continually control their distribution and use by workers. Submit request for tags as early as possible prior to commencement of work.
- .5 For the duration of this contract, anyone not in possession of the ID Tag will not be allowed access on site.
- .6 Immediately report any lost, stolen or destroyed ID Tags to the Departmental Representative.

END OF SECTION

1.1 Inspection

- .1 Give timely notice requesting inspection of Work designated for special tests, inspections or approvals by Departmental Representative or by inspection authorities having jurisdiction.
- .2 In accordance with the General Conditions, Departmental Representative may order any part of Work to be examined if Work is suspected to be not in accordance with Contract Documents.
- .3 If Contractor covers or permits to be covered Work designated for special tests, inspections or approvals before such is made, uncover Work until particular inspections or tests have been fully and satisfactorily completed and until such time as Departmental Representative gives permission to proceed.
- .4 Pay costs to uncover and make good work disturbed by inspections and tests.

1.2 Testing

- .1 Tests on materials, equipment and building systems as specified in various sections of the Specifications is the responsibility of the Contractor except where stipulated otherwise.
 - .1 Provide all necessary instruments, equipment and qualified personnel to perform tests.
- .2 At completion of tests, turn over 2 sets of fully documented tests reports to the Departmental Representative. Submit in accordance with Section 01 33 00 - Submittal Procedures.
 - .1 Obtain additional copies for inclusion of a complete set in each of the maintenance manuals specified in Section 01 78 00 - Closeout Submittals.

Issued for Tender

- .3 Unspecified tests may also be made by Departmental Representative, at the discretion of the Departmental Representative. The costs of these tests will be paid for by the Departmental Representative.
- .4 Where tests or inspections reveal work not in accordance with contract requirements, Contractor shall pay costs for additional tests and inspections incurred by Departmental Representative as required to verify acceptability of corrected work.

1.3 Access to Work

- .1 Facilitate Departmental Representative's access to Work. If part of Work is being fabricated at locations other than construction site, make preparations to allow access to such Work whenever it is in progress.
- .2 Furnish labour and facility to provide access to the work being inspected and tested.
- .3 Co-operate to facilitate such inspections and tests.

1.4 Rejected Work

- .1 Remove and replace defective Work, whether result of poor workmanship, use of defective or damaged products and whether incorporated in Work or not, which has been identified by Departmental Representative as failing to conform to Contract Documents.
- .2 Make good damages to new and existing construction and finishes resulting from removal or replacement of defective work.

END OF SECTION

<u>1.1</u>	<u>References</u>	.1	Canadian Standards Association (CSA).
		.1	CSA Z797-09(2014), Code of Practice for Access Scaffold.
		.2	CAN/CSA-Z321-96 (R2006), Signs and Symbols for the Workplace.
<u>1.2</u>	<u>Site Access and Parking</u>	.1	The Departmental Representative will designate Contractor's access to project site as well as limited parking facilities for equipment and workers.
<u>1.3</u>	<u>Building Access</u>	.1	Use only access doors, and circulation routes within building as designated by Departmental Representative to access interior work.
<u>1.4</u>	<u>Contractor's Site Office</u>	.1	Be responsible for and provide own site office, if required, including electricity, heat, lights and telephone. Locate site office as directed by Departmental Representative.
<u>1.5</u>	<u>Material Storage</u>	.1	Laydown area for materials and equipment will be provided.
<u>1.6</u>	<u>Site Enclosures</u>	.1	Provide temporary fence to enclose various construction areas of work site.
		.2	Erect steel fence using new 1200 mm high galvanized steel wire fence fabric supported by steel posts spaced at maximum 2.4 m oc.
		.1	Provide one truck gate and one pedestrian gate.
		.2	Maintain fence in good repair.
		.3	Erect plastic mesh fence constructed as follows:
		.1	1200 mm height, constructed of high density polyethylene mesh fence fabric, orange in color.
		.2	Supported by steel T-bar posts or other similar framing, of sufficient quantity, adequate spacing and set firmly in ground to secure fence against sags.
		.3	Inspect fence regularly, repairing sags and damaged sections.
		.4	Incorporate within fence one operable truck gate and one pedestrian gate.

Issued for Tender

- | | |
|---|---|
| | <ul style="list-style-type: none"> .5 Make all gates lockable and provide keyed padlocks. .6 Obtain Departmental Representative's approval beforehand of location and layout of all temporary fence enclosures. .7 Provide battery powered lanterns around the perimeter of the site enclosure to clearly mark its location at night. .8 Provide warning signs affixed to all fenced areas, identifying those enclosed areas as "Construction Zones" with access restricted to only those persons so authorized by General Contractor. .9 Do not construe fencing as an acceptable replacement for pedestrian walkway and hoarding requirements specified below. |
| <p>1.7 Pedestrian Walkways and Hoarding</p> <hr/> | <ul style="list-style-type: none"> .1 Ensure maximum safety and security to facility users during the course of work. .2 Maintain access and egress to building entrances and fire exits designated by Departmental Representative to remain in use. Provide enclosed walkways when work is adjacent to such doors as follows: <ul style="list-style-type: none"> .1 Erect wooden pedestrian walkway complete with roof and side covers. .2 Install walkways as soon as work is in the vicinity of entrance and exit doors and poses a potential danger to facility users. .3 Construct to approximate size of 2.0 metre wide x 2.1 metre high x length as required to fully clear danger zone. .4 Provide signage and lighting. .5 Submit details of walkway size, location, layout and construction to Departmental Representative beforehand and obtain approval. .3 Adequately frame and brace hoarding and walkways to resist wind, and other weather or site conditions. |

-
- | | | | |
|-----|---|----|--|
| | | .4 | Erect such protective devices during Facility's non-operational off hour periods. |
| | | .5 | Obtain Departmental Representative's concurrence prior to removal of hoarding and walkways. |
| 1.8 | Interior Dust Control and Dust Barriers | .1 | Control creation and spread of dust and dirt to building interior and in particular to areas within premises still under use by occupants. |
-
- | | | | |
|--|--|----|---|
| | | .2 | Develop and implement a dust control plan, addressing effective measures to carry out work with least amount of dust being created and propagated. |
| | | .1 | Carefully evaluate the type of work to be undertaken and the physical layout of each work area on site. |
| | | .2 | Provide specifically tailored strategy for each work area. |
| | | .3 | Pre-determine location and placement of dust barriers to confine resulting dust to immediate work area. |
| | | .4 | Inform Departmental Representative of the proposed dust control measures to be followed at each work area and for each major dust generating activities. Obtain Departmental Representative's approval before proceeding with work. |
| | | .3 | Dust control plan to incorporate as a minimum the following dust protection and cleaning requirements: |
| | | .1 | Erect dustproof partitions completely around work area to fully isolate construction from other parts of the building. |

- .2 Construct dust partitions as follows:
 - .1 Use 10 mil polyethylene installed and sealed tightly to abutting walls, ceilings and floor with continuous duct tape along all edges and seams. Support in position with 38 x 89 wood framing at 400 mm o.c. Locate seams only at framing members and overlap sheeting by minimum of 150 mm.
- .3 Provide a "dust-tight" and lockable access door(s) within dust partition or between rooms for worker entry into work area. This is of particular importance for situations where excessive dust will be generated.
- .4 Provide additional dust barriers, placed tightly to underside of the floor/roof deck above, in locations where existing walls are used as part of the dust barrier system but simply terminate at the finished ceiling level resulting in an open space above, or other similar condition, permitting dust to migrate beyond the construction areas.
- .5 Make all dust barriers airtight, effectively blocking and stopping all dust migration.
- .6 Inspect dust barriers at various intervals during each work shift. Immediately fix tears, unsealed edges and maintain barriers effectively sealed for the entire work duration.
- .7 Shut down existing ventilation system feeding construction space, or disconnect and seal-off supply and return air ducts to stop dust from contaminating other areas.

-
- .8 Immediately clean areas in use by occupants and public contaminated by work.
 - .1 Vacuum carpets, wash floors and walls. Remove accumulated dust from all surfaces. Clean and remove smears, scuffs and marks.
 - .4 Meager attempts at controlling dust will not be tolerated. Failure to provide effective dust control during work and to perform satisfactory cleaning thereafter will result in Departmental Representative to proceed and obtain a separate cleaning service agency to perform cleaning at cost to Contractor
 - .5 Obtain Departmental Representative's approval before erecting any dust partitions simply to underside of finish ceiling.
 - .6 Construction of dust barriers, enclosures and placement of temporary protective devices to be performed during Facility non-operational off-hour periods.
- 1.9 Power
- .1 Power supply is available and will be provided for construction usage at no cost.
 - .1 Make arrangements for the use of such services through the Departmental Representative.
 - .2 Departmental Representative will designate and approve each location of existing power source to which connections can be made to obtain temporary power service.
 - .3 Connect to existing power supply in accordance with Canadian Electrical Code.
 - .2 Provide and maintain temporary lighting as required to conduct work. Ensure illumination level is not less than 162 lx in all locations.
- 1.10 Water Supply
- .1 Water supply is available in existing building on site and will be provided for construction usage at no cost.

-
- | | | | |
|------|------------------------------------|----|---|
| 1.11 | <u>Heating and
Ventilating</u> | .1 | Ventilating:
.1 Prevent accumulations of dust, fumes,
mists, vapours or gases in areas occupied
during construction.
.2 Provide local exhaust ventilation to prevent
harmful accumulation of hazardous
substances into atmosphere of occupied areas.
.3 Dispose of exhaust materials in manner
that will not result in harmful exposure
to persons.
.4 Ventilate storage spaces containing
hazardous or volatile materials.
.5 Ventilate temporary sanitary facilities.
.6 Continue operation of ventilation and exhaust
system for time after cessation of work
process to assure removal of harmful
contaminants.

.2 Maintain strict supervision of operation of temporary
heating and ventilating equipment to:
.1 Conform with applicable codes and standards.
.2 Enforce safe practices.
.3 Prevent abuse of services.
.4 Prevent damages to finishes.
.5 Vent direct-fired combustion units to outside
Vent direct-fired combustion units to outside. |
|------|------------------------------------|----|---|

-
- | | | | |
|------|--|----|--|
| 1.12 | <u>Removal of
Temporary Facilities</u> | .1 | Remove temporary facilities from site when
directed by Departmental Representative. |
|------|--|----|--|

END OF SECTION

-
- | | | |
|------------------------------|----|---|
| 1.1 General | .1 | Use new material and equipment unless otherwise specified. |
| | .2 | Within three (3) days of written request by Departmental Representative, submit following information for any materials and products proposed for supply: <ul style="list-style-type: none">.1 Name and address of manufacturer..2 Trade name, model and catalogue number..3 Performance, descriptive and test data..4 Compliance to specified standards..5 Manufacturer's installation or application instructions..6 Evidence of arrangements to procure..7 Evidence of manufacturer delivery problems or unforeseen delays. |
| | .3 | Provide material and equipment of specified design and quality, performing to published ratings and for which replacement parts are readily available. |
| | .4 | Use products of one manufacturer for equipment or material of same type or classification unless otherwise specified. |
| | .5 | Permanent labels, trademarks and nameplates on products are not acceptable in prominent locations, except where required for operating instructions, or when located in mechanical or electrical rooms. |
| <hr/> 1.2 Product Quality | .1 | Contractor shall be solely responsible for submitting relevant technical data and independent test reports to confirm whether a product or system proposed for use meets contract requirements and specified standards. |
| | .2 | Final decision as to whether a product or system meets contract requirements rest solely with the Departmental Representative in accordance with the General Conditions of the Contract. |

<u>1.3 Manufacturer's Instructions</u>	.1	Unless otherwise specified, comply with manufacturer's latest printed instructions for materials and installation methods to be used. Do not rely on labels or enclosure provided with products. Obtain written instructions directly from manufacturers.
	.2	Notify Departmental Representative in writing of any conflict between these specifications and manufacturer's instructions, so that Departmental Representative will designate which document is to be followed.
<u>1.4 Availability</u>	.1	Immediately notify Departmental Representative in writing of unforeseen or unanticipated material delivery problems by manufacturer. Provide support documentation as per paragraph 1.1.2 above.
<u>1.5 Workmanship</u>	.1	Ensure quality of work is of highest standard, executed by workers experienced and skilled in respective duties for which they are employed.
	.2	Remove unsuitable or incompetent workers from site as stipulated in the General Conditions of the Contract.
	.3	Ensure cooperation of workers in laying out work. Maintain efficient and continuous supervision on site at all times.
	.4	Coordinate work between trades and subcontractors. See section 01 14 10 - Scheduling and Management of Work in this regard.
	.5	Coordinate placement of openings, sleeves and accessories.

		Issued for Tender	
1.6	Fastenings - General	.1	Provide metal fastenings and accessories in same texture, colour and finish as base metal in which they occur. Prevent electrolytic action between dissimilar metals. Use non- corrosive fasteners, anchors and spacers for securing exterior work and in humid areas.
		.2	Space anchors within limits of load bearing or shear capacity and ensure that they provide positive permanent anchorage. Wood or organic material plugs not acceptable.
		.3	Keep exposed fastenings to minimum, space evenly and lay out neatly.
		.4	Fastenings which cause spalling or cracking of material to which anchorage is made, are not acceptable.
		.5	Do not use explosive actuated fastening devices unless approved by Departmental Representative. See section on Health and Safety Requirements in this regard.
1.7	Fastenings - Equipment	.1	Use fastenings of standard commercial sizes and patterns with material and finish suitable for service.
		.2	Use heavy hexagon heads, semi-finished unless otherwise specified.
		.3	Bolts may not project more than one diameter beyond nuts.
		.4	Use plain type washers on equipment, sheet metal and soft gasket lock type washers where vibrations occur and, use resilient washers with stainless steel.
1.8	Storage, Handling and Protection	.1	Deliver, handle and store materials in manner to prevent deterioration and soiling and in accordance with manufacturer's instructions when applicable.

Issued for Tender

- .2 Store packaged or bundled materials in original and undamaged condition with manufacturer's seal and labels intact. Do not remove from packaging or bundling until required in Work. Provide additional cover where manufacturer's packaging is insufficient to provide adequate protection.
- .3 Store products subject to damage from weather in weatherproof enclosures.
- .4 Store cementitious products clear of earth or concrete floors, and away from walls.
- .5 Keep sand, when used for grout or mortar materials, clean and dry. Store sand on wooden platforms and cover with waterproof tarpaulins during inclement weather.
- .6 Store sheet materials and lumber on flat, solid supports and keep clear of ground. Slope to shed moisture.
- .7 Store and mix paints in heated and ventilated room. Remove oily rags and other combustible debris from site daily. Take every precaution necessary to prevent spontaneous combustion.
- .8 Immediately remove damaged or rejected materials from site.
- .9 Touch-up damaged factory finished surfaces to Departmental Representative's satisfaction.
Use
touch-up materials to match original. Do not paint over name plates.

END OF SECTION

1.1 General	<div data-bbox="609 359 1399 432">.1 Conduct cleaning and disposal operations to comply with local ordinances and anti-pollution laws.</div> <div data-bbox="609 485 1399 558">.2 Store volatile waste in covered metal containers, and remove from premises at end of each working day.</div> <div data-bbox="609 611 1399 737">.3 Provide adequate ventilation during use of volatile or noxious substances. Use of building ventilation systems is not permitted for this purpose.</div>
1.2 Materials	<div data-bbox="609 789 1399 905">.1 Use only cleaning materials recommended by manufacturer of surface to be cleaned, and as recommended by cleaning material manufacturer.</div>
1.3 Cleaning During Construction	<div data-bbox="609 957 1399 1073">.1 Maintain work site and work areas in a tidy condition, free from accumulations of waste material and debris. Clean areas on a daily basis.</div> <div data-bbox="609 1104 1399 1178">.2 Provide on-site containers for collection of waste materials and debris.</div> <div data-bbox="609 1209 1399 1367">.3 Use separate collection bins, clearly marked as to purpose, for source separation and recycling of waste and debris in accordance with waste management requirements specified.</div> <div data-bbox="609 1398 1399 1472">.4 Remove waste materials, and debris from site as required by Departmental Representative.</div> <div data-bbox="609 1503 1399 1659">.5 Schedule cleaning operations so that resulting dust, debris and other contaminants will not fall on wet, newly painted surfaces nor contaminate building systems.</div>

- .6 Provide dust barriers, dividers, seals on doors and employ other dust control measures as required to ensure that dust and dirt, generated by work, are not transmitted to other existing areas of building. Should dust migrate into tenant occupied and public areas of building, employ such means as may be necessary to immediately clean all contaminated surfaces to the satisfaction of the Departmental Representative.
 - .1 See Section 01 50 00 - Temporary Facilities for requirements on dust control and for erection of dust partitions.
- .7 Immediately clean all dust, dirt, smears, scuffs and soiled surfaces in lobbies, corridors, stairwells and within tenant occupied areas resulting from the Work.
 - .1 Perform cleaning, dusting and floor washing as necessary to thoroughly clean all soiled surfaces.
- .8 Remove snow and ice from access doors used by workforce.

1.4 Final Cleaning

- .1 In preparation for acceptance of the completed work perform final cleaning in areas affected by the Work.
- .2 Remove grease, dust, dirt, stains, labels, fingerprints, marks and other foreign materials.
- .3 Replace items with broken pieces, scratches or disfigured.
- .4 Vacuum clean and dust building interiors.
- .5 Broom clean and wash exterior paved surfaces and walks; rake clean other surfaces of grounds.

- .6 Remove debris and surplus materials from crawl areas,
roof areas and other accessible concealed spaces.

END OF SECTION

Issued for Tender

1.1	Related Requirements	.1	Environment Procedures: Section 01 35 43 - Environmental Procedures.
1.2	General	.1	Carry out work placing maximum emphasis on the areas of: .1 Waste reduction; .2 Diversion of waste from landfill and; .3 Material Recycling.
1.3	Waste Management Plan	.1	Prior to commencement of work, prepare waste Management Workplan.
		.2	Workplan to include: .1 Waste audit. .2 Waste reduction practices. .3 Material source separation process. .4 Procedures for sending recyclables to recycling facilities. .5 Procedures for sending non- salvageable items and waste to approved waste processing facility or landfill site. .6 Training and supervising workforce on waste management at site.
		.3	Workplan to incorporate waste management requirements specified herein and in other sections of the Specifications.
		.4	Develop Workplan in collaboration with all subcontractors to ensure all waste management issues and opportunities are addressed.
		.5	Submit copy of Workplan to Departmental Representative for review and approval. .1 Make revisions to Plan as directed by Departmental Representative.
		.6	Implement and manage all aspects of Waste Management Workplan for duration of work.
		.7	Revise Plan as work progresses addressing new opportunities for diversion of waste from landfill.

Issued for Tender

1.4 Waste Audit

- .1 At project start-up, conduct waste audit of:
 - .1 Site conditions identifying salvageable and non-salvageable items and waste resulting from demolition and removal work.
 - .2 Projected waste resulting from product packaging and from material leftover after installation work.
- .2 Develop written list. Record type, composition and quantity of various salvageable items and waste anticipated, reasons for waste generation and operational factors which contribute to waste.

1.5 Waste Reduction

- .1 Based on waste audit, develop waste reduction program.
- .2 Structure program to prioritize actions, with waste reduction as first priority, followed by salvage and recycling effort, then disposal as solid waste.
- .3 Identify materials and equipment to be:
 - .1 Protected and turned over to Departmental Representative when indicated.
 - .2 Salvaged for resale by Contractor.
 - .3 Sent to recycling facility.
 - .4 Sent to waste processing/landfill site for their recycling effort
 - .5 Disposed of in approved landfill site.
- .4 Reduce construction waste during installation work. Undertake practices which will minimize waste and optimize full use of new materials on site, such as:
 - .1 Use of a central cutting area to allow for easy access to off-cuts;
 - .2 Use of off-cuts for blocking and bridging elsewhere.

Issued for Tender

-
- .3 Use of effective and strategically placed facilities on site for storage and staging of left-over or partially cut materials (such as gypsum board, plywood, ceiling tiles, insulation etc...) to allow for easy incorporation into work whenever possible avoiding unnecessary waste.
 - .5 Develop other strategies and innovative procedures to reduce waste such as minimizing the extent of packaging used for delivery of materials to site etc...
 - 1.6 Material Source Separation Process
 - .1 Develop and implement material source separation process at commencement of work as part of mobilization and waste management at site.
 - .2 Provide on-site facilities to collect, handle and store anticipated quantities of reusable, salvageable and recyclable materials.
 - .1 Use suitable containers for individual collection of items based on intended purpose.
 - .2 Locate to facilitate deposit but without hindering daily operations of existing building tenants.
 - .3 Clearly mark containers and stockpiles as to purpose and use.
 - .3 Perform demolition and removal of existing building components and equipment following a systematic deconstruction process.
 - .1 Separate materials and equipment at source, carefully dismantling, labelling and stockpiling alike items for the following purposes:
 - .1 Reinstallation into the work where indicated.
 - .2 Sending as many items as possible to locally available recycling facility.

Issued for Tender

-
- .3 Segregating remaining waste and debris into various individual waste categories for disposal in a "non-mixed state" as recommended by waste processing/landfill sites.
 - .4 Isolate product packaging and delivery containers from general waste stream. Send to recycling facility or return to supplier/manufacturer.
 - .5 Send leftover material resulting from installation work for recycling whenever possible.
 - .6 Establish methods whereby hazardous and toxic waste materials, and their containers, encountered or used in the course work are properly isolated, stored on site and disposed in accordance with applicable laws and regulations from authorities having jurisdiction.
 - .7 Isolate and store existing materials and equipment identified for re- incorporation into the Work. Protect against damage.
 - 1.7 Worker Training and Supervision
 - .1 Provide adequate training to workforce, through meetings and demonstrations, to emphasize purpose and worker responsibilities in carrying out the Waste Management Plan.
 - .2 Waste Management Coordinator: designate full-time person on site, experienced in waste management and having knowledge of the purpose and content of Waste Management Plan to:
 - .1 Oversee and supervise waste management during work.
 - .2 Provide instructions and directions to all workers and subcontractors on waste reduction, source separation and disposal practices.
 - .3 Post a copy of Plan in a prominent location on site for review by workers.

Issued for Tender

-
- | | | | |
|------|--|----|---|
| 1.8 | <u>Certification of
Material Diversion</u> | .1 | Submit to Departmental Representative, copies of certified weigh bills from authorized waste processing sites and sale receipts from recycling/reuse facilities confirming receipt of building materials and quantity of waste diverted from landfill. |
| | | .2 | Submit data at pre-determined project milestones as determined by Departmental Representative. |
| | | .3 | Compare actual quantities diverted from landfill with projections made during waste audit. |
|
 | | | |
| 1.9 | <u>Disposal
Requirements</u> | .1 | Burying or burning of rubbish and waste materials is prohibited. |
| | | .2 | Disposal of waste, volatile materials, mineral spirits, oil, or paint thinner into waterways, storm, or sanitary sewers is prohibited. |
| | | .3 | Dispose of waste only at approved waste processing facility or landfill sites approved by authority having jurisdiction. |
| | | .4 | Contact the authority having jurisdiction prior to commencement of work, to determine what, if any, demolition and construction waste materials have been banned from disposal in landfills and at transfer stations.
Take appropriate action to isolate such banned materials at site of work and dispose in strict accordance with provincial and municipal regulations. |
| | | .5 | Transport waste intended for landfill in separated condition, following rules and recommendations of Landfill Operator in support of their effort to divert, recycle and reduce amount of solid waste placed in landfill. |

Issued for Tender

-
- .6 Collect, bundle and transport salvaged materials to be recycled in separated categories and condition as directed by recycling facility. Ship materials only to approved recycling facilities.
 - .7 Sale of salvaged items by Contractor to other parties not permitted on site.

END OF SECTION

-
- | | | | |
|-----|-----------------------------|----|---|
| 1.1 | <u>Related Requirements</u> | .1 | Section 01 78 00 - Closeout Submittals. |
|-----|-----------------------------|----|---|
-
- | | | | |
|-----|-----------------------------------|----|---|
| 1.2 | <u>Inspection and Declaration</u> | .1 | Contractor's Inspection: Coordinate and perform, in concert with subcontractors, an inspection and check of all Work.
Identify and correct deficiencies, defects, repairs and perform outstanding items as required to complete work in conformance with Contract Documents. |
| | | .1 | Notify Departmental Representative in writing when deficiencies from Contractor's inspection have been rectified and that Work is deemed to be complete and ready for Departmental Representative's inspection of the completed work. |
| | | .2 | Departmental Representative's Inspection: Accompany Departmental Representative during all substantial and final inspections of the Work. |
| | | .1 | Address defects, faults and outstanding items of work identified by such inspections. |
| | | .2 | Advise Departmental Representative when all deficiencies identified have been rectified. |
| | | .3 | Note that Departmental Representative will not issue a Certificate of Substantial Performance of the work until such time that Contractor performs following work and turns over the specified documents: |
| | | .1 | Project record as-built documents; |
| | | .2 | Final Operations and Maintenance manuals; |
| | | .3 | Maintenance materials, parts and tools; |
| | | .4 | Compliance certificates from applicable authorities; |
| | | .5 | Reports resulting from designated tests; |
| | | .6 | Demonstration and training complete with user manuals; |
| | | .7 | Manufacturer's Guarantee certificates. |

Issued for Tender

- .8 Testing, adjusting and balancing of equipment and systems complete with submission of test reports.
- .9 Commissioning of equipment and systems specified.

- .4 Correct all discrepancies before Departmental Representative will issue the Certificate of Completion.

END OF SECTION

Issued for Tender

- | | | | |
|-----|---------------------------------|----|--|
| 1.1 | <u>Project Record Documents</u> | .1 | Departmental Representative will provide 2 white print sets of contract drawings and two (2) copies of Specifications Manual specifically for "as-built" purposes. |
| | | .2 | Maintain at site one set of the contract drawings and specifications to record actual as-built site conditions. |
| | | .3 | Maintain up-to-date, real time as-built drawings and specifications in good condition and make available for inspection by the Departmental Representative upon request. |
| | | .4 | As-Built Drawings: |
| | | .1 | Record changes in red ink on the prints. Mark only on one set of prints and at completion of work, neatly transfer notations to second set (also by use of red ink). |
| | | .2 | Submit both sets to Departmental Representative prior to application for Certificate of Substantial Performance. |
| | | .3 | Stamp all drawings with "As-Built Drawings". Label and place Contractor's signature and date. |
| | | .4 | Show all modifications, substitutions and deviations from what is shown on the contract drawings or in specifications. |
| | | .5 | Record following information: |
| | | .1 | Field changes of dimension and details; |
| | | .2 | Location of capped and terminated services and utilities; |
| | | .3 | Chases for mechanical, electrical and other services; |
| | | .4 | All structural steel installations to be fully dimensioned; |
| | | .5 | Any details produced in the course of the contract by the Departmental Representative to supplement or to change existing design drawings; |

Issued for Tender

- .6 All change orders issued over the course of the contract must be documented on the finished as-built documents, accurately and consistently depicting the changed condition as it applies to all affected drawing details.
- .5 As-built Specifications: legibly mark in red each item to record actual construction, including:
 - .1 Manufacturer, trade name, and catalogue number of each product actually installed, particularly items substituted from that specified.
 - .2 Changes made by Addenda and Change Orders.
 - .3 Mark up both copies of specifications; stamp "as-built", sign and date similarly to drawings as per above paragraph.
- .6 Maintain As-built documents current as the contract progresses. Departmental Representative will conduct reviews and inspections of the documents on a regular basis. Failure to maintain as- builds current and complete to satisfaction of the Departmental Representative shall be subject to financial penalties. Reviewed Shop.

Drawings

- .1 Provide a complete set of all shop drawings reviewed for project to incorporate into each copy of the Operations & Maintenance manuals.
- .2 Submit full sets at same time and as part of the contents of the Operation and Maintenance manuals specified.

1.2 Operations &
Maintenance Manual

- .1 O&M Manual - Definition: an organized compilation of operating and maintenance data including detailed technical information, documents and records describing operation and maintenance of individual products or systems as specified in individual sections of the specifications.
- .2 Manual Language: final manuals to be in English language.
- .3 Number of copies required:
 - .1 Upon review and acceptance by Departmental Representative, submit three (3) final copies. Interim copies are not to be considered as part of the final copies unless they have been fully revised and are identical to the final approved version.
- .4 Submission Date: submit complete operation and maintenance manual to Departmental Representative three (3) weeks prior to application for Certificate of Substantial Performance of the work.
- .5 Binding:
 - .1 Assemble, coordinate, bind and index required data into Operation and Maintenance Manual.
 - .2 Use vinyl, hard covered, 3 "D" ring binders, loose leaf, sized for 215 mm x 280 mm paper, with spine pocket.
 - .3 Where multiple binders are needed, correlate data into related consistent groupings.
 - .4 Identify contents of each binder on spine.
 - .5 Organize and divide data following same numerical system as the section numbers of the Specification Manual.

Issued for Tender

- .6 Dividers: separate each section by use of cardboard dividers and labels. Provide tabbed fly leaf for each individual product and system and give description of product or component.
- .7 Type lists and notes. Do not hand write.
- .8 Drawings, diagrams and manufacturers' literature must be legible. Provide with reinforced, punched binder tab. Bind in with text; fold larger drawings to size of text pages.
- .6 Manual Contents:
 - .1 Cover sheet containing:
 - .1 Date submitted.
 - .2 Project title, location and project number.
 - .3 Names and addresses of Contractor, and all Sub-contractors.
 - .2 Table of Contents: provide full table of contents in each binder(s), clearly indicate which contents are in each binder.
 - .3 List of maintenance materials.
 - .4 List of spare parts.
 - .5 List of special tools.
 - .6 Original or certified copy of warranties and product guarantees.
 - .7 Copy of approval documents and certificates issued by Inspection Authorities.
 - .8 Copy of reports and test results performed by Contractor as specified.
 - .9 Product Information (PI Data) on materials, equipment and systems as specified in various sections of the specifications. Data to include:
 - .1 List of equipment including manufacturer's name, supplier, local source of supplies and service depot(s). Provide full addresses and telephone numbers.

Issued for Tender

- .2 Nameplate information including equipment number, make, size, capacity, model number and serial number.
 - .3 Parts list.
 - .4 Installation details.
 - .5 Operating instructions.
 - .6 Maintenance instructions for equipment.
 - .7 Maintenance instructions for finishes.
- .7 Shop drawings:
- .1 Include complete set of reviewed shop drawings into each copy of the operations and maintenance manual.
 - .2 Fold and bind material professionally in a manner that corresponds with the specification section numbering system.
 - .3 When large quantity of data is submitted, place into separate binders of same size as O&M binders.
- .8 Equipment and Systems Data: the following list indicates the type of data and extent of information required to be included for each item of equipment and for each system:
- .1 Requirements as specified in individual specification sections.
- .9 Materials and Finishes Maintenance Data:
- .1 Building Products, Applied Materials, and Finishes: include product data, with catalogue number, size, composition, and colour and texture designations.
 - .2 Moisture-protection and Weather- exposed Products: include manufacturer's recommendations for cleaning agents and methods, precautions against detrimental agents and methods, and recommended schedule for cleaning and maintenance.
 - .3 Additional Requirements: as specified in individual specifications sections.

END OF SECTION