

RETURN BIDS TO: RETOURNER LES SOUMISSIONS A :

Bid Receiving/Réception des sousmissions Procurement & Contracting Services c/o Commissionaires, F Division 6101 Dewdney Ave Regina, SK S4P 3K7

Fax No. - No de FAX: (306) 780-5232

SOLICITATION AMENDMENT

MODIFICATION DE L'INVITATION

The referenced document is hereby revised; unless otherwise indicated, all other terms and conditions of the Solicitation remain the same.

Ce document est par la présente révisé; sauf indication contraire, les modalités de l'invitation demeurent les mêmes.

				T
Title - Sujet: Utility Vehicle (UTV)				Date March 29, 2018
Solicitation No. – N° de l'invitation M5000-18-4928/B– PW-18-00818690				Amendment No. – Nº de la modification 002
Client Ref 201804928	erence No No	. De Référe	nce du Cli	ent
Solicitatio	n Closes – L'in	vitation pre	nd fin	
At /à :	2 :00 pm			ntral Standard Time) ure Normale du Centre)
On / le :	April 4, 2018		•	
Delivered	s 2010 "DDP I Duty Paid" — Voir aux	GST – TF See hereir aux préser	n — Voir	Duty – Droits See herein — Voir aux présentes
services	n of Goods and — Voir aux prés		- Destination	ons des biens et
Instruction See herein	ns — Voir aux prés	sentes		
Adresser t	nquiries to – toute demande es, Senior Contr			1
Telephone 639-625-34	No. – No. de té 463	éléphone	Facsimile 306-780-5	No. – No. de télécopieur 232
Delivery R Livraison N/A			Delivery C Livraison N/A	
	rm Name, Addre t représentant c			ve – Raison sociale, trepreneur:
Telephone No. – No. de téléphone			Facsimile	No. – No. de télécopieur
Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) – Nom et titre de la personne autorisée à signer au nom du fournisseur/de l'entrepreneur (taper ou écrire en caractères d'imprimerie)				
Signature		Date		





This amendment is raised to address the following:

- To respond to questions received during the solicitation period; and
- To revise the solicitation accordingly, as applicable.

QUESTIONS AND ANSWERS

Question 12: Specification H Dimension 5. Ground Clearance. Please clarify what is mean by ground clearance. Does this mean the distance from the bottom of the vehicle frame to the ground, or the distance from the bottom of the axle to the ground?

Answer 12: Ground clearance is defined as "the minimum distance between the lower end of the vehicle body (or chassis) and the road".

Question 13: Specification K. Interior / Cab 1. Bucket Seats with double seating capacity – Minimum Will the RCMP accept a bench seat with double seating capacity?

Answer 13: Yes

Question 14: Specification L Exterior/Cab, Line 1- Roll Over Protective Structure ROPS Cab Frame with Steel Roof. Will the RCMP accept Certified R.O.P.S Cab Frame with upper Cross Members made of reinforced heavy gauge Steel, and Black Poly Roof?

Answer 14: Yes, a "Certified" R.O.P.S. frame with steel reinforcement for the Poly Roof would be acceptable. The specification has been amended to reflect this change.

SOLICITATION REVISIONS

1) On page fourteen (14) Annex "A" Requirement

DELETE: in its entirety

INSERT:

ANNEX "A"

REQUIREMENT

The Contractor must supply, deliver, unload and provide service, as required, for three (3) new (most current model year manufactured at bid closing) Utility Terrain Vehicle (UTV) to the Royal Canadian Mounted Police, to be delivered to Regina, SK, in accordance with the requirements specifications, terms and conditions detailed herein.

The Open Air 4 x4 Utility Terrain Vehicle (UTV) must include the following specifications:

- Must be new, most current Manufacturer Model Year still in production at bid closing;
- Conform to all applicable laws, regulations and industrial standards governing manufactures, safety, noise levels and pollution in effect in Canada at the time of manufacture; and
- Have systems and components capacities not greater than their published ratings (i.e. product or component brochures) or accompanied by proof of compliance



A. Engine

- 1. Liquid Cooled 4 cycle (Single Cylinder Gas Engine Minimum)
- 2. 560 cc(minimum) to 850 cc (maximum)
- 3. Electric start
- 4. Fuel injection
- 5. Automatic transmission including High, Low, Neutral, Reverse gears with selectable 2 WD and 4WD

B. Electrical System

- 1. 40 Amp alternator
- 2. 12 Volt battery, 1 amp minimum, must have step and rapid charging capability, including over voltage protection, short circuit protection, overload protection and thermal protection. One (1) battery tender to be supplied with each machine

C. Drive train

- 1. Travelling Speed Range, 0 40 KM (40 KM Maximum)
- 2. Gear selection/range mandatory: High/Low, Reverse, Neutral
- 3. 4 wheel drive with lockable rear differential

D. Suspension

- 1. Independent Macpherson Strut front steering Minimum
- 2. Independent coil over shock rear suspension- Minimum
- 3. Power steering wheel (no foot pedals or hand controls)
- 4. High performance all-purpose suspension

E. Tires

1. High performance all purpose, Turf/hard surface - standard manufacturer tire size for bidding machine

F. Brakes

- 1. Mechanical parking/emergency brake (may be disk or drum)
- 2. Front and rear Mandatory Disc or Drum Hydraulic Brake

G. Fuel System

1. Electric Fuel Pump – Minimum

H. Dimensions

- 1. Length 114 in (minimum)
- 2. Width 58 in (minimum)
- 3. Height 72 in. (minimum) to 79 in. (maximum)
- 4. Wheelbase 75 in. (minimum)
- 5. Ground Clearance 10 in. (minimum)
- 6. Fuel Tank Capacity 30 Litre (L) minimum

I. Cargo Box

- 1. The box must be made of steel or reinforced with steel
- 2. 750 lb Box Capacity Minimum
- 3. Power Lift Cargo Box
- 4. Quick latch tailgate
- 5. Rear Receiver hitch
- 6. Drawbar

J. <u>Instrumentation</u>

1. Mandatory Manufacturer standard Instrumentation Panel



K. Interior/Cab

- 1. Bucket seats with double seating capacity Minimum
- 2. 3 point restraint safety belts Minimum

L. Exterior/Cab

- 1. Roll Over Protective Structure (ROPS) Cab Frame with rigid roof
- 2. Deluxe lighting kit (including signal and brake lights) Minimum
- 3. Side mirror kit
- 4. Removable or Tip-out glass windshield
- 5. Must have (1) One Windshield wiper
- 6. Back-up alarm
- 7. Horn
- 8. Flooring: Industry Standard Flooring
- 9. Bush Guards Mandatory front and rear bush guards to protect lights
- 10. Bumpers Mandatory front and rear bumpers

M. Additional Features

1. **Shipping/Crating:** Shipped full assembled

2. Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the

Warranty manual. All manuals to be provided in English

3. **Keys:** Two (2) sets of keys – minimum

4. New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit.

5. Identification: Each machine must have an Identification Plate permanently marked and in an

inconspicuous and protected location containing the following information: Manufacturer; model; model year; serial number; Gross Vehicle Weight Rating (GVWR), and Contract

number.

6. Warranty: The warranty period will be twelve (12) months after the delivery and acceptance of the

unit or the length of the Contractor's or manufacturer's standard warranty period, whichever is longer. All costs related to warranty work must be included in price, non-

warranty maintenance and after sales service are to be charged separately

7. Service: Service/warranty and regular maintenance work must be performed within a 100 km

radius of the delivery location, by an authorized representative. The authorized representative must begin the repair service within 24 hours of notification at a service facility. The authorized representative must have ready access to regular maintenance and servicing parts and be able to access all parts not normally stocked from an

authorized parts dealer.



2) On page seventeen (17) Annex "C" Mandatory Technical Criteria

DELETE: in its entirety

INSERT:

ANNEX C Mandatory Technical Criteria

Bidders are required to indicate whether or not they comply with the mandatory specifications. Bidders must include **two (2) copies of descriptive literature of the make and model of the items offered in sufficient detail to clearly indicate compliance with each of the individual requirements** in the specifications and cross reference where this specification is located within the descriptive literature.

If specifications are not listed in the descriptive literature, bidders must provide documentation to support how the offered unit meets the specification.

Where weight, dimensions or other characteristics are shown as minimum or maximum, the bidder must indicate the manufacturer's figures.

The Royal Canadian Mounted Police is under no obligation to seek clarification of the bid(s) or the supporting technical documentation provided.

For evaluation purposes, indicate tr	ne Manufacturer, model and year of	the unit offered for evaluation
Manufacturer:,	Model:	, Year:
Failure to meet any of the following further consideration.	specifications will render your propo	osal non-compliant and will be given no

The following specifications must be met:

No.	Specification	Comp Yes	pliance No	Comments(s) / Cross Reference
	Must be new, most current Manufacturer Model Year still in production at bid closing;			
Α	Engine			
1.	Liquid Cooled 4 cycle (Single Cylinder Gas Engine – Minimum)			
2.	560 cc(minimum) to 850 cc (maximum)			
3.	Electric Start			
4.	Fuel Injection			
5.	Automatic transmission including High, Low, Neutral, Reverse gears with selectable 2 WD and 4WD			
B.	Electrical System			
1.	40 Amp alternator			
2.	12 Volt battery, 1 amp minimum, must have step and rapid charging capability, including over voltage protection, short			



	Deirectis numberation according and numberation and	
	circuit protection, overload protection and	
	thermal protection. One (1) battery tender	
	to be supplied with each machine.	
	Duling Tuelle	
C.	Drive Train	
1.	Travelling Speed Range, 0 – 40 KM (40 KM Maximum)	
2.	Gear selection/range mandatory:	
	High/Low, Reverse, Neutral	
3.	4 wheel drive with lockable rear	
	differential	
D.	Suspension	
1.	Independent Macpherson Strut front	
	steering – Minimum	
2.	Independent coil over shock rear	
	suspension- Minimum	
3.	Power steering wheel (no foot pedals or	
	hand controls)	
4.	High performance all-purpose suspension	
E.	Tires	
1.	High performance all purpose, Turf/hard	
	surface – standard manufacturer tire size	
	for bidding machine	
F.	Brakes	
		<u> </u>
1.	Mechanical parking/emergency brake	
1.	Mechanical parking/emergency brake (may be disk or drum)	
1.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum	
1.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System	
2.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System	
1. 2. G.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake	
1. 2. G.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System	
1. 2. G. 1.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump	
1. 2. G. 1. H. 1. 2.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum) Width – 58 in (minimum)	
1. 2. G. 1. H.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum)	
1. 2. G. 1. H. 1. 2.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum) Width – 58 in (minimum) Height – 72 in. (minimum) to 79 in. (maximum)	
1. 2. G. 1. 1. 2. 3. 4.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum) Width – 58 in (minimum) Height – 72 in. (minimum) to 79 in.	
1. 2. 1. 1. 2. 3. 4. 5.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum) Width – 58 in (minimum) Height – 72 in. (minimum) to 79 in. (maximum) Wheelbase – 75 in. (minimum) Ground Clearance – 10 in. 2.(minimum)	
1. 2. G. 1. 1. 2. 3. 4.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum) Width – 58 in (minimum) Height – 72 in. (minimum) to 79 in. (maximum) Wheelbase – 75 in. (minimum)	
1. 2. 1. 1. 2. 3. 4. 5.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum) Width – 58 in (minimum) Height – 72 in. (minimum) to 79 in. (maximum) Wheelbase – 75 in. (minimum) Ground Clearance – 10 in. 2.(minimum)	
1. 2. 1. 1. 2. 3. 4. 5.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum) Width – 58 in (minimum) Height – 72 in. (minimum) to 79 in. (maximum) Wheelbase – 75 in. (minimum) Ground Clearance – 10 in. 2.(minimum) Fuel Tank Capacity – 30 Litre (L)	
1. 2. 1. 1. 2. 3. 4. 5.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum) Width – 58 in (minimum) Height – 72 in. (minimum) to 79 in. (maximum) Wheelbase – 75 in. (minimum) Ground Clearance – 10 in. 2.(minimum) Fuel Tank Capacity – 30 Litre (L)	
1. 2. 1. 1. 2. 3. 4. 5. 6.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum) Width – 58 in (minimum) Height – 72 in. (minimum) to 79 in. (maximum) Wheelbase – 75 in. (minimum) Ground Clearance – 10 in. 2.(minimum) Fuel Tank Capacity – 30 Litre (L) minimum	
1. 2. 1. 1. 2. 3. 4. 5. 6. I	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum) Width – 58 in (minimum) Height – 72 in. (minimum) to 79 in. (maximum) Wheelbase – 75 in. (minimum) Ground Clearance – 10 in. 2.(minimum) Fuel Tank Capacity – 30 Litre (L) minimum Cargo Box	
1. 2. 1. 1. 2. 3. 4. 5. 6. I	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum) Width – 58 in (minimum) Height – 72 in. (minimum) to 79 in. (maximum) Wheelbase – 75 in. (minimum) Ground Clearance – 10 in. 2.(minimum) Fuel Tank Capacity – 30 Litre (L) minimum Cargo Box The box must be made of steel or	
1. 2. 1. 1. 2. 3. 4. 5. 6. I	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum) Width – 58 in (minimum) Height – 72 in. (minimum) to 79 in. (maximum) Wheelbase – 75 in. (minimum) Ground Clearance – 10 in. 2.(minimum) Fuel Tank Capacity – 30 Litre (L) minimum Cargo Box The box must be made of steel or reinforced with steel	
1. 2. 1. 1. 2. 3. 4. 5. 6. I 1. 2.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum) Width – 58 in (minimum) Height – 72 in. (minimum) to 79 in. (maximum) Wheelbase – 75 in. (minimum) Ground Clearance – 10 in. 2.(minimum) Fuel Tank Capacity – 30 Litre (L) minimum Cargo Box The box must be made of steel or reinforced with steel 750 lb Box Capacity – Minimum	
1. 2. 1. 1. 2. 3. 4. 5. 6. I 1. 2. 3.	Mechanical parking/emergency brake (may be disk or drum) Front and rear – Mandatory Disc or Drum Hydraulic Brake Fuel System Electric Fuel Pump Dimension Length - 114 in (minimum) Width – 58 in (minimum) Height – 72 in. (minimum) to 79 in. (maximum) Wheelbase – 75 in. (minimum) Ground Clearance – 10 in. 2.(minimum) Fuel Tank Capacity – 30 Litre (L) minimum Cargo Box The box must be made of steel or reinforced with steel 750 lb Box Capacity – Minimum Power Lift Cargo Box	



6.	Drawbar	
J	Instrumentation	
1.	Mandatory Manufacturer standard	
	Instrumentation Panel	
	motiamentation i and	
K	Interior/Cab	
1.	Bucket seats with double seating capacity	
١.	Minimum	
2.	3 point restraint safety belts – Minimum	
۷.	5 point restraint safety beits – Minimum	
	Futania (Oak	
L	Exterior/Cab	
1.	Roll Over Protective Structure (ROPS) Cab Frame with rigid roof	
2.	Deluxe lighting kit (including signal and	
	brake lights) – Minimum	
3.	Side mirror kit	
4.	Removable or Tip-out glass windshield	
5.	Must have (1) One Windshield wiper	
6.	Back up alarm	
7.	Horn	
8.	Flooring: Industry Standard Flooring	
9.	Bush Guards – Mandatory front and rear	
0.	bush guards to protect lights	
10.	Bumpers – Mandatory front and rear	
	bumpers	
	bumporo -	
М	Additional Features	
M .	Additional Features Shipping/Crating: Shipped fully	
M.	Shipping/Crating: Shipped fully	
1.	Shipping/Crating: Shipped fully assembled	
	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the	
1.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One	
1.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All	
1.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English.	
 2. 3. 	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum	
1.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement	
 2. 3. 	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the	
1. 2. 3. 4.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit.	
 2. 3. 	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit. Identification: Each machine must have	
1. 2. 3. 4.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit. Identification: Each machine must have an Identification Plate permanently	
1. 2. 3. 4.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit. Identification: Each machine must have an Identification Plate permanently marked and in an inconspicuous and	
1. 2. 3. 4.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit. Identification: Each machine must have an Identification Plate permanently marked and in an inconspicuous and protected location containing the following	
1. 2. 3. 4.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit. Identification: Each machine must have an Identification Plate permanently marked and in an inconspicuous and protected location containing the following information: Manufacturer; model; model	
1. 2. 3. 4.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit. Identification: Each machine must have an Identification Plate permanently marked and in an inconspicuous and protected location containing the following information: Manufacturer; model; model year; serial number; Gross Vehicle	
1. 2. 3. 4.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit. Identification: Each machine must have an Identification Plate permanently marked and in an inconspicuous and protected location containing the following information: Manufacturer; model; model year; serial number; Gross Vehicle Weight Rating (GVWR), and Contract	
1. 2. 3. 4.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit. Identification: Each machine must have an Identification Plate permanently marked and in an inconspicuous and protected location containing the following information: Manufacturer; model; model year; serial number; Gross Vehicle Weight Rating (GVWR), and Contract number.	
1. 2. 3. 4.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit. Identification: Each machine must have an Identification Plate permanently marked and in an inconspicuous and protected location containing the following information: Manufacturer; model; model year; serial number; Gross Vehicle Weight Rating (GVWR), and Contract number. Service: Service/warranty and regular	Distance between the delivery
1. 2. 3. 4.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit. Identification: Each machine must have an Identification Plate permanently marked and in an inconspicuous and protected location containing the following information: Manufacturer; model; model year; serial number; Gross Vehicle Weight Rating (GVWR), and Contract number. Service: Service/warranty and regular maintenance work must be performed	location and the service dealer
1. 2. 3. 4.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit. Identification: Each machine must have an Identification Plate permanently marked and in an inconspicuous and protected location containing the following information: Manufacturer; model; model year; serial number; Gross Vehicle Weight Rating (GVWR), and Contract number. Service: Service/warranty and regular maintenance work must be performed within a 100 km radius of each delivery	
1. 2. 3. 4.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit. Identification: Each machine must have an Identification Plate permanently marked and in an inconspicuous and protected location containing the following information: Manufacturer; model; model year; serial number; Gross Vehicle Weight Rating (GVWR), and Contract number. Service: Service/warranty and regular maintenance work must be performed within a 100 km radius of each delivery location, by an authorized service dealer	location and the service dealer and/or agent:km
1. 2. 3. 4.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit. Identification: Each machine must have an Identification Plate permanently marked and in an inconspicuous and protected location containing the following information: Manufacturer; model; model year; serial number; Gross Vehicle Weight Rating (GVWR), and Contract number. Service: Service/warranty and regular maintenance work must be performed within a 100 km radius of each delivery	location and the service dealer
1. 2. 3. 4.	Shipping/Crating: Shipped fully assembled Manuals: Two (2) hard copies of the Operators, Service/Parts manuals. One (1) hard copy of the Warranty manual. All manuals to be provided in English. Keys: Two (2) sets of keys – minimum New Vehicle Information Statement (NVIS) documents to be included with the delivery of the unit. Identification: Each machine must have an Identification Plate permanently marked and in an inconspicuous and protected location containing the following information: Manufacturer; model; model year; serial number; Gross Vehicle Weight Rating (GVWR), and Contract number. Service: Service/warranty and regular maintenance work must be performed within a 100 km radius of each delivery location, by an authorized service dealer	location and the service dealer and/or agent:km



agent must have ready access to regular maintenance and service parts and be	Address:
able to access all parts not normally stocked from an authorized parts dealer.	Telephone:
The Bidder must provide the name, address, telephone number and indicate the distance between the delivery location and the authorized service dealer and/or agent to provide after sales service, maintenance, warranty repairs, and a full range of repair parts for the unit offered.	

ALL OTHER TERMS AND CONDITIONS REMAIN THE SAME