



**RETURN BIDS TO:**

**RETOURNER LES SOUMISSIONS À:**

**Bid Receiving - PWGSC / Réception des soumissions -  
TPSGC**

**11 Laurier St. / 11, rue Laurier**

**Place du Portage, Phase III**

**Core 0B2 / Noyau 0B2**

**Gatineau, Québec K1A 0S5**

**Bid Fax: (819) 997-9776**

**SOLICITATION AMENDMENT  
MODIFICATION DE L'INVITATION**

The referenced document is hereby revised; unless otherwise indicated, all other terms and conditions of the Solicitation remain the same.

Ce document est par la présente révisé; sauf indication contraire, les modalités de l'invitation demeurent les mêmes.

**Comments - Commentaires**

**Vendor/Firm Name and Address**

**Raison sociale et adresse du  
fournisseur/de l'entrepreneur**

**Issuing Office - Bureau de distribution**

**Vehicles & Industrial Products Division**

**11 Laurier St./11, rue Laurier**

**7A2, Place du Portage, Phase III**

**Gatineau, Québec K1A 0S5**

|   |  |
|---|--|
| <b>Title - Sujet</b><br>Miscellaneous spare parts   |  |
| <b>Solicitation No. - N° de l'invitation</b><br>W8486-184844/A  | <b>Amendment No. - N° modif.</b><br>001      |
| <b>Client Reference No. - N° de référence du client</b><br>W8486-184844   | <b>Date</b><br>2018-04-05                    |
| <b>GETS Reference No. - N° de référence de SEAG</b><br>PW-\$\$HP-371-74534  |  |
| <b>File No. - N° de dossier</b><br>hp371.W8486-184844   | <b>CCC No./N° CCC - FMS No./N° VME</b>       |
| <b>Solicitation Closes - L'invitation prend fin</b><br><b>at - à 02:00 PM</b><br><b>on - le 2018-05-01</b>  |  |
| <b>Time Zone</b><br><b>Fuseau horaire</b><br>Eastern Daylight Saving<br>Time EDT  |  |
| <b>F.O.B. - F.A.B.</b><br><b>Plant-Usine:</b> <input type="checkbox"/> <b>Destination:</b> <input checked="" type="checkbox"/> <b>Other-Autre:</b> <input type="checkbox"/> |  |
| <b>Address Enquiries to: - Adresser toutes questions à:</b><br>Modérie, Christine   | <b>Buyer Id - Id de l'acheteur</b><br>hp371  |
| <b>Telephone No. - N° de téléphone</b><br>(873) 469-3327 ( )  | <b>FAX No. - N° de FAX</b><br>(819) 953-2953 |
| <b>Destination - of Goods, Services, and Construction:</b><br><b>Destination - des biens, services et construction:</b>   |  |

**Instructions: See Herein**

**Instructions: Voir aux présentes**

|  |  |
|--|--|
| <b>Delivery Required - Livraison exigée</b>  | <b>Delivery Offered - Livraison proposée</b> |
| <b>Vendor/Firm Name and Address</b><br><b>Raison sociale et adresse du fournisseur/de l'entrepreneur</b>   |  |
| <b>Telephone No. - N° de téléphone</b><br><b>Facsimile No. - N° de télécopieur</b>   |  |
| <b>Name and title of person authorized to sign on behalf of Vendor/Firm</b><br><b>(type or print)</b><br><b>Nom et titre de la personne autorisée à signer au nom du fournisseur/<br/>de l'entrepreneur (taper ou écrire en caractères d'imprimerie)</b> |  |
| <b>Signature</b>   | <b>Date</b>                                  |

Amendment No. 001 to the solicitation is raised to incorporate additional information to the line item description Detail and to change the Bid Solicitation closing date as follows:

Incorporate the additional informaiton for the following Items.

19 5330-12-3347146;  
21 5330-12-3253622;  
31 5331-01-1830991  
33 5330-12-3347147;  
34 5330-12-3347148;  
46 5330-01-6242920;  
49 5330-12-3462355; and  
59 5331-01-6134309

Change the Bid Solicitation closing date as follows:

DELETE: Solicitation Closes 2018-04-16  
INSERT: Solicitation Closes 2018-05-01

All other terms and conditions remain unchanged.

5330-12-334-7146, JOINT (SEAL)

|   |   |
|---|---|
| <b>MATERIAL</b>                             | OVERALL GESAMTARTIKEL KAUTSCHUK, ZELLULAR             |
| <b>MATERIAL DOCUMENT AND CLASSIFICATION</b> | OVERALL Z125V, D8435 MFR REF SINGLE MATERIAL RESPONSE |
| <b>CROSS-SECTIONAL SHAPE STYLE</b>          | SOLID SINGLE OR COMPOSITION                           |
| <b>CROSS-SECTIONAL THICKNESS</b>            | 4,0 MILLIMETERS NOMINAL                               |
| <b>STYLE DESIGNATOR</b>                     | NON-CIRCULAR  |
| <b>OVERALL LENGTH</b>                       | 251,0 MILLIMETERS NOMINAL                             |
| <b>OVERALL WIDTH</b>                        | 132,0 MILLIMETERS NOMINAL                             |
| <b>INSIDE CORNER RADIUS</b>                 | 4,0 MILLIMETERS NOMINAL                               |
| <b>OUTSIDE CORNER RADIUS</b>                | 6,0 MILLIMETERS NOMINAL                               |
| <b>APERTURE WIDTH</b>                       | 120,0 MILLIMETERS NOMINAL                             |
| <b>APERTURE LENGTH</b>                      | 239,0 MILLIMETERS NOMINAL                             |
| <b>SPECIAL FEATURES</b>                     | EINSEITIG KLEBEND                                     |

---

5330-12-325-3622, JOINT (SEAL)

|   |   |
|---|---|
| <b>MATERIAL</b>                             | OVERALL PLASTIC POLYAMIDE                               |
| <b>MATERIAL DOCUMENT AND CLASSIFICATION</b> | OVERALL EWP 210, D8175 MFR REF SINGLE MATERIAL RESPONSE |
| <b>CROSS-SECTIONAL SHAPE STYLE</b>          | SOLID SINGLE OR COMPOSITION                             |
| <b>CROSS-SECTIONAL THICKNESS</b>            | 1,5 MILLIMETERS NOMINAL                                 |
| <b>STYLE DESIGNATOR</b>                     | CIRCULAR  |
| <b>OUTSIDE DIAMETER</b>                     | 60,0 MILLIMETERS NOMINAL                                |
| <b>APERTURE DIAMETER</b>                    | 42,5 MILLIMETERS NOMINAL                                |

---

5331-01-183-0991, JOINT TORIQUE, (O-RING)

|                               |   |
|-------------------------------|---|
| <b>OUTSIDE DIAMETER</b>       | 1.887 INCHES NOMINAL                          |
| <b>TEMP RATING</b>            | -65.0 DEG FAHRENHEIT AND 275.0 DEG FAHRENHEIT |
| <b>CROSS-SECTIONAL HEIGHT</b> | 0.135 INCHES MINIMUM AND 0.143 INCHES MAXIMUM |
| <b>CENTER HOLE DIAMETER</b>   | 1.594 INCHES MINIMUM AND 1.624 INCHES MAXIMUM |
| <b>ELONGATION PERCENTAGE</b>  | 125 MAXIMUM                                   |
| <b>HARDNESS RATING</b>        | 75.0 SHORE DUROMETER A NOMINAL                |
| <b>MATERIAL</b>               | RUBBER BUTADIENE-ACRYLONITRILE CLASS NBR      |

5330-12-334-7147, GASKET

|  |                                       |
|--|---------------------------------------|
| <b>MATERIAL</b>  | OVERALL GESAMTARTIKEL KAUTSCHUK, KORK |
| <b>CROSS-SECTIONAL SHAPE</b>                                     | SOLID SINGLE OR COMPOSITION           |
| <b>STYLE</b>   |                                       |
| <b>CROSS-SECTIONAL THICKNESS</b>                                 | 0,8 MILLIMETERS NOMINAL               |
| <b>STYLE DESIGNATOR</b>  | NON-CIRCULAR                          |
| <b>HOLE DIAMETER</b>   | 3,2 MILLIMETERS NOMINAL               |
| <b>OVERALL LENGTH</b>  | 42,0 MILLIMETERS NOMINAL              |
| <b>OVERALL WIDTH</b>   | 42,0 MILLIMETERS NOMINAL              |
| <b>APERTURE DIAMETER</b>   | 37,5 MILLIMETERS NOMINAL              |
| <b>OUTSIDE CORNER RADIUS</b>                                     | 4,0 MILLIMETERS NOMINAL               |
| <b>CENTER TO CENTER DISTANCE BETWEEN BOLT HOLES ALONG WIDTH</b>  | 31,8 MILLIMETERS NOMINAL              |
| <b>CENTER TO CENTER DISTANCE BETWEEN BOLT HOLES ALONG LENGTH</b> | 31,8 MILLIMETERS NOMINAL              |
| <b>OUTSIDE EDGE TO BOLT HOLE CENTER DISTANCE ALONG WIDTH</b>     | 5,1 MILLIMETERS NOMINAL               |
| <b>OUTSIDE EDGE TO BOLT HOLE CENTER DISTANCE ALONG LENGTH</b>    | 5,1 MILLIMETERS NOMINAL               |
| <b>BOLT HOLE QUANTITY</b>  | 4                                     |
| <b>SPECIAL FEATURES</b>  | EINSEITIG SELBSTKLEBEND               |

5330-12-334-7148, GASKET

|  |  |
|--|--|
| <b>MATERIAL</b>  | OVERALL GESAMTARTIKEL KAUTSCHUK, ZELLULAR              |
| <b>MATERIAL DOCUMENT AND CLASSIFICATION</b>                      | OVERALL Z125V, D8435 MFR REF SINGLE MATERIAL RESPONSE  |
| <b>CROSS-SECTIONAL SHAPE STYLE</b>                               | SOLID SINGLE OR COMPOSITION                            |
| <b>CROSS-SECTIONAL THICKNESS</b>                                 | 3,0 MILLIMETERS NOMINAL                                |
| <b>STYLE DESIGNATOR</b>  | NON-CIRCULAR   |
| <b>HOLE DIAMETER</b>   | 6,0 MILLIMETERS NOMINAL                                |
| <b>OVERALL LENGTH</b>  | 255,0 MILLIMETERS NOMINAL                              |
| <b>OVERALL WIDTH</b>   | 128,0 MILLIMETERS NOMINAL                              |
| <b>INSIDE CORNER RADIUS</b>                                      | 2,0 MILLIMETERS NOMINAL                                |
| <b>OUTSIDE CORNER RADIUS</b>                                     | 6,0 MILLIMETERS NOMINAL                                |
| <b>APERTURE WIDTH</b>  | 110,0 MILLIMETERS NOMINAL                              |
| <b>APERTURE LENGTH</b>   | 237,0 MILLIMETERS NOMINAL                              |
| <b>CENTER TO CENTER DISTANCE BETWEEN BOLT HOLES ALONG LENGTH</b> | 75,0 MILLIMETERS NOMINAL AND 120,0 MILLIMETERS NOMINAL |
| <b>OUTSIDE EDGE TO BOLT HOLE CENTER DISTANCE ALONG WIDTH</b>     | 4,5 MILLIMETERS NOMINAL AND 64,0 MILLIMETERS NOMINAL   |
| <b>OUTSIDE EDGE TO BOLT HOLE CENTER DISTANCE ALONG LENGTH</b>    | 5,0 MILLIMETERS NOMINAL AND 30,0 MILLIMETERS NOMINAL   |
| <b>BOLT HOLE QUANTITY</b>  | 8  |

---

5330-01-624-2920, RUBBER SHEET, SOLID, CLOTH INSERT

|                                 |  |
|---------------------------------|--|
| <b>MINIMUM TENSILE STRENGTH</b> | 32 POUNDS PER SQUARE INCH  |
| <b>TEMP RATING</b>              | 0.00 DEG FAHRENHEIT AND 250.00 DEG FAHRENHEIT  |
| <b>COLOR</b>                    | BOTH SIDES BLACK   |
| <b>SPECIAL FEATURES</b>         | PLIES: 2, WEIGHT: .69LBS, AVAILABLE WIDTH: .72", OVERALL GAUGE: .099+/- .10", RECOMMENDED WORKING TENSION: 32LBS/", MINIMUM PULLEY DIAMETER: 2", MEETS FDA, COVER SURFACE 3/64", BOTTOM SURFACE: FRICTION. |

---

**WITCO CHEMICAL CORP**  
**CHEMPRENE DIV**  
COMPANY MIGHT BE OBSOLETE

---

5330-12-346-2355, GASKET

|   |   |
|---|---|
| <b>MATERIAL</b>                             | OVERALL PLASTIC POLYAMIDE   |
| <b>MATERIAL DOCUMENT AND CLASSIFICATION</b> | OVERALL KLINGERSIL C-4400, D1429 MFR REF SINGLE MATERIAL RESPONSE |
| <b>CROSS-SECTIONAL SHAPE STYLE</b>          | SOLID SINGLE OR COMPOSITION                                       |
| <b>CROSS-SECTIONAL THICKNESS</b>            | 1,0 MILLIMETERS NOMINAL   |
| <b>BOLT CIRCLE DIAMETER</b>                 | 68,0 MILLIMETERS NOMINAL AND 103,0 MILLIMETERS NOMINAL            |
| <b>SMALLEST BOLT HOLE DIAMETER</b>          | 4,5 MILLIMETERS NOMINAL   |
| <b>LARGEST BOLT HOLE DIAMETER</b>           | 5,5 MILLIMETERS NOMINAL   |
| <b>SMALLEST BOLT HOLE QUANTITY</b>          | 3   |
| <b>LARGEST BOLT HOLE QUANTITY</b>           | 4   |

---

5331-01-613-4309, O-RING

|   |                          |
|---|--------------------------|
| <b>MATERIAL</b>                                 | RUBBER                   |
| <b>COLOR</b>                                    | BLACK                    |
| <b>OUTSIDE DIAMETER</b>                         | 31.0 MILLIMETERS NOMINAL |
| <b>PERIPHERAL DIAMETER</b>                      | 31.0 MILLIMETERS NOMINAL |
| <b>CENTER HOLE DIAMETER</b>                     | 27.0 MILLIMETERS NOMINAL |
| <b>CROSS-SECTIONAL HEIGHT</b>                   | 2.0 MILLIMETERS NOMINAL  |
| <b>END ITEM IDENTIFICATION</b>                  | 6640-01-547-1760         |
| <b>PART NAME ASSIGNED BY CONTROLLING AGENCY</b> | O-RING                   |

---