

## ATTACHMENT 2 TO ANNEX A

## INTERCONNECTING PANEL SYSTEMS, SUPPORTED AND FREESTANDING SYSTEMS

## FINISHES

**1. GENERAL**

- 1.1 The Technical Authority (TA) will specify finishes prior to issuance of a Call-Up pursuant to the SO.
- 1.2 The Offeror must provide standard finishes, unless otherwise stated in the Offeror's SO agreement.
- 1.3 Offered products and components must include finish cards of required finishes.
- 1.4 The Offeror must provide all available finishes for offered products and components.

**2.0 PANEL FINISHES, WORK SURFACE FINISHES, WORKSPACE STORAGE FINISHES****Fabrics:**

- 2.1 Fabrics should contain a minimum recycled content of 40% polyester or other environmentally appropriate material.
- 2.2 Fabrics must have a minimum weight of 10oz. per linear yard.
- 2.3 Fabric must have Colorfastness to Light AATCC-16A-2004 Class 4 rating minimum.
- 2.4 All fabric must have a Class A fire rating base on ASTM E84 - Surface Burning Characteristics for Building Materials.
- 2.5 The Offered products must include entire selection of fabric conforming to Attachment 3 – Testing Requirements.
- 2.6 The Offered products must include a selection of fabrics of anti-microbial upholstery group for mobile pedestal seat cushions conforming to Attachment 3 - Testing Requirements.

**Laminates:**

- 2.7 The Offered products for worksurfaces must be high pressure laminates
- 2.8 The laminate offering must include entire selection of high pressure laminate.
- 2.9 The Offered products must include a white laminate and a walnut wood grain laminate.
- 2.10 High pressure laminates for horizontal work surfaces must be tested and meet the requirements of CAN/CGSB-44-227- Freestanding Office Desk Products and Components as noted in 3.12 in Attachment 3 to Annex A - Testing Requirements.
- 2.11 Edge trim color must match laminate color and should be made of a flat edge style 3mm pvc or pvc-free edge.

**Wood Veneer (Natural and Engineered):**

- 2.12 The Offered products must include a selection of wood veneer (Natural and Engineered) finishes.
- 2.13 The Offered products must include Natural American Walnut or substitute.
- 2.14 Veneer directions on work surfaces must be horizontal (i.e. left to right direction).
- 2.15 Solid or veneer must be FSC (Forest Stewardship Council) certified.
- 2.16 Veneer directions on work surfaces must be horizontal (i.e. left to right direction).
- 2.17 Veneer directions on vertical applications must be top to bottom.
- 2.18 All visible wood surfaces must have a clear finish, and be free from open knots.
- 2.19 The Offeror must provide wood veneer or engineered wood veneer for the manufacturer's wood trim finish. At the minimum, the Offeror must provide American Walnut (or substitute) wood trim finish.

**Surface Materials:**

- 2.20 Particleboard: must conform to ANSI A208.1, grade M2 or greater when used as substrate.
- 2.21 MDF (medium density fiberboard) core: must conform to ANSI/NPA A208.2 when used as substrate.

**Metal:**

- 2.22 The Offered products must include a minimum of five colors which must include at a minimum powder coat finish for Black, White, Silver at no additional cost.
- 2.23 Offeror must provide different metal finishes including matte and/or polished and/or satin and/or brushed finish.

**3.0 ACCESSORIES FINISHES**

- 3.1 Accessory rail finish to be painted metal to match panel trim.
- 3.2 Provide a hang-on coat hook in metal finish to match panel trim.
- 3.3 Integrated Freestanding Accessories must include, at the minimum, White and Black at no additional charge.

**4.0 BENCHING AND ACTIVITY BASED SYSTEMS FINISHES**

- 4.1 The Offered products must include all available of finishes in fabric, soft material, metals, laminate and wood veneer.

**5.0 FREE-STANDING, HEIGHT-ADJUSTABLE WORKSURFACES FINISHES**

- 5.1 Horizontal work surfaces must meet the performance requirements for high-pressure laminate. Refer to previous sections.

- 5.2 Horizontal work surfaces must be offered in Natural Wood Veneer and Engineered wood veneer and must meet the requirements for wood veneer noted in Attachment 3 to Annex A - Testing Requirements. For additional specification refer to previous sections 2.12 to 2.19.
- 5.3 The Offered products must include a selection of horizontal surfaces finishes which must include laminates which include solids, patterns and wood grains, as well as Natural and Engineered Wood Veneer which must include at a minimum American Walnut (or substitute).
- 5.4 The Offered products must include all metal finishes. At the minimum, the Offered products must include White, Platinum/Silver and Black.
- 5.5 The adhesion rating of the painted metal finish must be at least 4B when tested in accordance with ASTM D 3359, Method B.
- 5.6 The Edge trim color must match laminate color and must be made of a flat edge style 3mm pvc or pvc-free edge.
- 5.7 The Offered veneer products must include a matching wood edge.