



RETURN BIDS TO:

RETOURNER LES SOUMISSIONS À:

Bid Receiving - PWGSC / Réception des soumissions -
TPSGC

11 Laurier St./11 rue Laurier

Place du Portage, Phase III

Core 0B2 / Noyau 0B2

Gatineau, Québec K1A 0S5

SOLICITATION AMENDMENT MODIFICATION DE L'INVITATION

The referenced document is hereby revised; unless otherwise indicated, all other terms and conditions of the Solicitation remain the same.

Ce document est par la présente révisé; sauf indication contraire, les modalités de l'invitation demeurent les mêmes.

Comments - Commentaires

THIS DOCUMENT CONTAINS A SECURITY
REQUIREMENT

Vendor/Firm Name and Address

Raison sociale et adresse du
fournisseur/de l'entrepreneur

Issuing Office - Bureau de distribution

Construction Services Division/Division des services de
construction

11 Laurier St./11 Rue Laurier

3C2, Place du Portage

Phase III

Gatineau, Québec K1A 0S5

Title - Sujet LBP Security Upgrades - Constructio	
Solicitation No. - N° de l'invitation EP916-182156/A	Amendment No. - N° modif. 005
Client Reference No. - N° de référence du client 20182156	Date 2018-05-02
GETS Reference No. - N° de référence de SEAG PW-\$\$\$FG-362-74724	
File No. - N° de dossier fg362.EP916-182156	CCC No./N° CCC - FMS No./N° VME
Solicitation Closes - L'invitation prend fin at - à 02:00 PM on - le 2018-05-29	Time Zone Fuseau horaire Eastern Daylight Saving Time EDT
F.O.B. - F.A.B. Plant-Usine: <input type="checkbox"/> Destination: <input checked="" type="checkbox"/> Other-Autre: <input type="checkbox"/>	
Address Enquiries to: - Adresser toutes questions à: Kelly, Jessica	Buyer Id - Id de l'acheteur fg362
Telephone No. - N° de téléphone () - ()	FAX No. - N° de FAX () -
Destination - of Goods, Services, and Construction: Destination - des biens, services et construction:	

Instructions: See Herein

Instructions: Voir aux présentes

Delivery Required - Livraison exigée	Delivery Offered - Livraison proposée
Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur	
Telephone No. - N° de téléphone Facsimile No. - N° de télécopieur	
Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)	
Signature	Date

Solicitation No. - N° de l'invitation
EP916-182156

Amd. No. - N° de la modif.
005

Buyer ID - Id de l'acheteur
FG 362

Client Ref. No. - N° de réf. du client
20182156

File No. - N° du dossier
FG362 EP916-182156

CCC No./N° CCC - FMS No./N° VME
R.070731.011, R.070731.025, R.070731.042

The following changes to the tender documents are effective immediately. This amendment will form part of the contract documents.

Amendment 005 is issued for the following:

- (1) Issue Addendum 002
-

ALL OTHER TERMS AND CONDITIONS REMAIN THE SAME

Solicitation No. - N° de l'invitation
EP916-182156

Amd. No. - N° de la modif.
005

Buyer ID - Id de l'acheteur
FG 362

Client Ref. No. - N° de réf. du client
20182156

File No. - N° du dossier
FG362 EP916-182156

CCC No./N° CCC - FMS No./N° VME
R.070731.011, R.070731.025, R.070731.042

ADDENDUM 002

ADDENDUM No.

002

Project :

R.070731.002

The following changes in the bid documents are effective immediately. This addendum will form part of the contract documents

DRAWINGS

- .1 A111 SP - PLAN / PS - PLAN
 - .1 Detail 1/A111 – SUSSEX - PLAN - CONSTRUCTION
 - .1 Drawing Note 35 has been added to identify the exterior glazing requiring brute force resistant glazing at the front of the Sussex Pavilion. Refer to attached Drawing A111 r02.
- .2 A310 KEP – SP - ELEVATIONS / PS - ÉLÉVATIONS
 - .1 Detail 2/A310 - SP – ELEVATION EAST / ÉLÉVATION EST and Detail 3/A310 - SP – ELEVATION SOUTH / ÉLÉVATION SUD
 - .1 Drawing Note 28 has been added to identify the exterior glazing requiring brute force resistant glazing at the front of the Sussex Pavilion. Refer to attached Drawing A310 r02.
- .3 A517 DETAILS – EXTERIOR WALL / DÉTAILS – MURS EXTÉRIEURS
 - .1 Detail 1/A517 – SP-SECTION DETAIL / DÉTAIL EN COUPE
 - .1 Modify glass for guardrails to “Laminated tempered safety glass guardrail”. This modification is applicable for all glass guardrails.
 - .2 Add continuous anodized aluminum cap rail to glass guardrails. This modification is applicable for all glass guardrails.
 - .3 Refer to attached Drawing A517 r02.

SPECIFICATIONS

- .1 Section 05 75 13 – Glass Balustrade Railing System
 - .1 Add article 1.3.9 as follows:
 - .9 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-12.1-M90, Tempered or Laminated Safety Glass.
 - .2 Delete article 1.4.2.2 .
 - .3 Modify article 1.5.4.1 as follows:
 - .1 152 mm long sections of each different linear railing member, including handrails and aluminum base shoe.
 - .4 Add article 1.5.4.2 as follows:
 - .2 152 x 152 mm Glass Balustrade panel.
 - .5 Modify article 2.1.4.1 as follows:
 - .1 Glass: Provide two (2) layers of 10mm tempered laminated glass with 1.5mm ionoplast strengthening interlayer, uncoated, transparent flat glass meeting the requirements of ASTM C1048, Type FT, Condition A, Type 1, Quality q3. Products shall comply with properties indicated for class, thickness, and manufacturing process that have been tested for surface

ADDENDUM No. 002

Project : R.070731.002

The following changes in the bid documents are effective immediately. This addendum will form part of the contract documents

and edge compression according to ASTM C1048 and for impact strength according to 16 CFR Part 1201 for Category II materials.

- .6 Modify article 2.1.4.1 sentence .2 as follows:
 - .2 Thickness: 10 mm except where noted, and as required to support structural loads.
- .2 Section 08 80 50 – Glazing
 - .1 Add article 2.1.3.4 as follows:
 - .4 Insulating glass units: to CAN/CGSB-12.8, double unit - TYPE 3
 - .1 Glass: to CAN/CGSB-12.1.
 - .2 Exterior glass: brute force resistant, transparent glass,
 - .1 Thickness: refer to Technical Specification – Appendix B by Security.
 - .2 Brute force resistance rating: refer to Technical Specification – Appendix B by Security.
 - .3 Inter-cavity space thickness: with low conductivity spacers 13 mm.
 - .4 Interior glass: tempered, float transparent glass 6 mm thick.
 - .5 Glass coating: surface number 2, low "E" coating.
 - .6 Inert gas fill: argon, gas fill proportion: 90%.
 - .7 Glazing units to be installed on the public side of the pavilions are to have factory applied security film on surface number 4.

END OF ADDENDUM No. 002

PHGSC-A1 DM/G

