

PART 1 - GENERAL

- 1.1 REFERENCES .1 Canadian General Standards Board (CGSB)  
.1 CGSB 1.59, Alkyd Exterior Gloss Enamel.  
.2 CAN/CGSB 1.189, Latest Edition, Exterior Alkyd Primer for Wood.
- .2 Canadian Standards Association (CSA International)  
.1 CSA-O121-M, Latest Edition, Douglas Fir Plywood.
- .3 Public Works Government Services Canada (PWGSC) Standard Acquisition Clauses and Conditions (SACC)-ID: R0202D, Title: General Conditions 'C'.
- 1.2 INSTALLATION AND REMOVAL .1 Provide temporary controls in order to execute Work expeditiously.
- .2 Remove from site all such work after use.
- 1.3 WEATHER ENCLOSURES .1 Provide weather tight closures to unfinished door and window openings, tops of shafts and other openings in floors and roofs.
- .2 Close off floor areas where walls are not finished; seal off other openings; enclose building interior work for temporary heat.
- .3 Design enclosures to withstand wind pressure and snow loading.
- 1.4 DUST TIGHT SCREENS .1 Provide dust tight screens or insulated partitions to localize dust generating activities, and for protection of workers, finished areas of Work and public.
-

- 1.5 PROTECTION OF BUILDING FINISHES .1 Provide protection for finished and partially finished building finishes and equipment during performance of Work.
- .2 Provide necessary screens, covers, and hoardings.
- .3 Be responsible for damage incurred due to lack of or improper protection.

PART 2 - PRODUCTS

- 2.1 NOT USED .1 Not Used.

PART 3 - EXECUTION

- 3.1 NOT USED .1 Not Used.