

2018-06-08

PART 2 - PRODUCTS

2.1 THERMOSTAT .1 Line voltage, wall-mounted thermostat, for
(LINE heating and cooling control with:
VOLTAGE-HEATING AND .1 Full load rating: 16 A at 120 V.
COOLING) .2 Temperature setting range: 5 degrees C
to 30 degrees C.
.3 Thermometer range: 5 degrees C to 30
degrees C.
.4 Markings in 5 degree increments.
.5 Differential temperature fixed at 1.1
degrees C.

2.2 THERMOSTAT .1 Thermostat guards: lockable, clear plastic.
GUARDS Slots for air circulation to thermostat.

PART 3 - EXECUTION

3.1 EXAMINATION .1 Verification of Conditions: verify that
conditions of substrate previously installed
under other Sections or Contracts are
acceptable for electric and electronic control
systems installation in accordance with
manufacturer's written instructions.
.1 Visually inspect substrate in presence
of Departmental Representative.
.2 Inform Departmental Representative of
unacceptable conditions immediately upon
discovery.
.3 Proceed with installation only after
unacceptable conditions have been remedied and
after receipt of written approval to proceed
from Departmental Representative.

3.2 INSTALLATION .1 Install control devices.
.2 Install remote sensing device and capillary
tube in metallic conduit. Conduit enclosing

