



SEPW Architecture Inc.

109 - 3725 Pasqua Street, Regina, SK. S4S 6W8
ph: (306) 569-2255 fax: (306)359-6846

PROJECT

**Crawlspace Remediation
Fillmore, Saskatchewan**

PROJECT No.
49/2017

DATE
2018-05-31

SET No.

	Pages
PROCUREMENT AND CONTRACTING REQUIREMENTS GROUP	
<i>Procurement Requirements</i>	
Division 00 - Procurement and Contracting Requirements	
00 01 10 - Table of Contents	3
SPECIFICATIONS GROUP	
<i>General Requirements Subgroup</i>	
Division 01 - General Requirements	
01 11 00 - Summary of Work	3
01 14 00 - Work Restrictions	2
Security Clearance Forms and Instructions Appended to Section 01 14 00	13
01 31 19 - Project Meetings	2
01 32 16.07 - Construction Progress Schedules – Bar (Gantt) Chart	2
01 33 00 - Submittal Procedures	5
01 35 29.06 - Health and Safety Requirements	3
01 41 00 - Regulatory Requirements	1
01 45 00 - Quality Control	2
01 51 00 - Temporary Utilities	2
01 52 00 - Construction Facilities	4
01 56 00 - Temporary Barriers and Enclosures	2
01 61 00 - Common Product Requirements	4
01 73 00 - Execution	2
01 74 11 - Cleaning	2
01 74 21 - Construction / Demolition Waste Management and Disposal	2
01 77 00 - Closeout Procedures	2
01 78 00 - Closeout Submittals	7
01 79 00 - Demonstration and Training	2
<i>Facility Construction Subgroup</i>	
Division 02 - Existing Conditions	
02 41 99 - Demolition for Minor Works	3
Division 03 - Concrete	
03 10 00 - Concrete Forming and Accessories	5
03 20 00 - Concrete Reinforcing	4
03 30 00 - Cast-In-Place Concrete	9
03 35 00 - Concrete Finishing	2
Division 04 - Masonry	
04 04 99 - Masonry for Minor Works	4
Division 05 - Metals	
Division 06 - Wood, Plastics and Composites	
06 05 73 - Wood Treatment	2
06 10 00 - Rough Carpentry	4

Division 07 - Thermal and Moisture Protection	
07 13 13 - Bituminous Sheet Waterproofing	4
07 26 00 - Vapour Retarders	3
07 62 00 - Sheet Metal Flashing and Trim	3
07 84 00 - Firestopping	4
07 92 00 - Joint Sealants	5
Division 08 - Openings	
Division 09 - Finishes	
Division 10 - Specialties	
Division 11 - Equipment	
Division 12 - Furnishings	
Division 13 - Special Construction	
<i>Facility Services Subgroup</i>	
Division 21 - Fire Suppression	
Division 22 - Plumbing	
See Drawing A3	
Division 23 - Heating, Ventilation, and Air-Conditioning (HVAC)	
See Drawing A3	
Division 25 - Integrated Automation	
Division 26 - Electrical	
See Drawing E1	
Division 27 - Communications	
Division 28 - Electronic Safety and Security	
<i>Site and Infrastructure Subgroup</i>	
Division 31 - Earthwork	
31 14 13 - Soil Stripping and Stockpiling	2
31 22 13 - Rough Grading	2
31 23 33.01 - Excavating, Trenching and Backfilling	10
31 63 00 - Bored Piles	4
Division 32 - Exterior Improvements	
32 12 16 - Asphalt Paving	2
32 92 23 - Sodding	5
Division 33 - Utilities	
33 46 13.01 - Foundation and Underslab Drainage	3

LIST OF DRAWINGS

ARCHITECTURAL

- A0 GENERAL INFORMATION, SCHEDULES, SITE, PLAN, SITE DETAILS
- A1 DEMOLITION PLANS, REVISED PLANS
- A2 BUILDING SECTIONS, DETAILS
- A3 SUMP DETAIL, MECHANICAL SPECIFICATIONS

STRUCTURAL

- S1 PLAN, DETAILS & SPECIFICATIONS

ELECTRICAL

- E1 CRAWLSPACE AND MAIN FLOOR PLANS, SPECIFICATIONS

END OF SECTION

Part 1 General

1.1 WORK COVERED BY CONTRACT DOCUMENTS

- .1 Work of this Contract comprises of selective exterior excavation, crawlspace remediation, new foundation system, and new foundation waterproofing, at an existing Police Building. Work also includes minor renovations, removals, site grading, structural, mechanical, electrical, and landscaping work. The project is located in Fillmore, Saskatchewan and further identified as "Police Building Crawlspace Remediation."
- .2 During demolition and reconstruction, the contractor will be responsible for protection of all existing items within the building and around the exterior perimeter of the building, that remain in, and adjacent to, the work area.

1.2 WORK SEQUENCE

- .1 Construct Work in stages to accommodate Departmental Representatives' continued use of premises during construction.
- .2 Co-ordinate Progress Schedule and co-ordinate with Departmental Representative Occupancy during construction.
- .3 Maintain fire access/control.

1.3 CONTRACTOR USE OF PREMISES

- .1 Limit use of premises for storage, for Work, and for access, to allow Departmental Representative occupancy.
- .2 Co-ordinate use of premises under direction of Departmental Representative.
- .3 Obtain and pay for use of additional storage or work areas needed for operations under this Contract.
- .4 Remove or alter existing work to prevent injury or damage to portions of existing work which remain.
- .5 Repair or replace portions of existing work which have been altered during construction operations to match existing or adjoining work, as directed by Departmental Representative.
- .6 At completion of operations condition of existing work: equal to or better than that which existed before new work started.

1.4 DEPARTMENTAL REPRESENTATIVE OCCUPANCY

- .1 Departmental Representative will occupy premises during entire construction period for execution of normal operations.
- .2 Co-operate with Departmental Representative in scheduling operations to minimize conflict and to facilitate Departmental Representative usage.

1.5 ALTERATIONS, ADDITIONS OR REPAIRS TO EXISTING BUILDING

- .1 Execute work with least possible interference or disturbance to occupants, building operations, and normal use of premises. Arrange with Departmental Representative to facilitate execution of work.

1.6 EXISTING SERVICES

- .1 Notify, Departmental Representative and utility companies of intended interruption of services and obtain required permission.
- .2 Where Work involves breaking into or connecting to existing services, give Departmental Representative 72 hours' notice for necessary interruption of mechanical or electrical service throughout course of work. Minimize duration of interruptions. Carry out work at times as directed by governing authorities with minimum disturbance to tenant operations
- .3 Provide alternative routes for personnel.
- .4 Establish location and extent of service lines in area of work before starting Work. Notify Departmental Representative of findings.
- .5 Submit schedule to and obtain approval from Departmental Representative for all shut-down or closure of active service or facility including power and communications services. Adhere to approved schedule and provide notice to affected parties.
- .6 Provide temporary services to maintain critical building and tenant systems.
- .7 Where unknown services are encountered, immediately advise Departmental Representative and confirm findings in writing.
- .8 Protect, relocate, and maintain existing active services. When inactive services are encountered, cap off in manner approved by authorities having jurisdiction.
- .9 Record locations of maintained, re-routed, and abandoned service lines.
- .10 Construct barriers in accordance with Section 01 56 00 - Temporary Barriers and Enclosures.

1.7 PERMITS AND FEES

- .1 The Contractor shall obtain and pay for all building permits. Obtain and pay for all other permits, licenses, certificates, fees and governmental inspections or notices required for the performance of the work. Note: Permit drawings are the property of the Departmental Representative. Contractor to forward "approved" permit drawings and a copy of the building permit to the Departmental Representative prior to the submission of the first request for progress payment."

1.8 DOCUMENTS REQUIRED

- .1 Maintain at job site, one copy of each document as follows:
 - .1 Contract Documents (Drawings, Specifications, Addenda).
 - .2 Reviewed Shop Drawings.
 - .3 List of Outstanding Shop Drawings.
 - .4 Change Orders.
 - .5 Other Modifications to Contract.

- .6 Field Test Reports.
- .7 Copy of Approved Work Schedule.
- .8 Health and Safety Plan and Other Safety Related Documents.
- .9 Building Permit.
- .10 Other documents as specified.

END OF SECTION

Part 1 General

1.1 ACCESS AND EGRESS

- .1 Maintain temporary "access to" and "egress from" work areas, including stairs and ramps, independent of finished surfaces and in accordance with relevant municipal, provincial, federal, and other regulations.

1.2 USE OF SITE AND FACILITIES

- .1 Use of site will be under security escort at all times.
- .2 Execute work with least possible interference or disturbance to normal use of premises. Make arrangements with Departmental Representative to facilitate work as stated.
- .3 Maintain existing services to building and provide for personnel and vehicle access.
- .4 Where security is reduced by work provide temporary means to maintain security.
- .5 Closures: protect work temporarily until permanent enclosures are completed.

1.3 ALTERATIONS, ADDITIONS OR REPAIRS TO EXISTING BUILDING

- .1 Execute work with least possible interference or disturbance to occupants, building operations, and normal use of premises. Arrange with Departmental Representative to facilitate execution of work.

1.4 EXISTING SERVICES

- .1 Notify Departmental Representative and utility companies of intended interruption of services and obtain required permission.
- .2 Where Work involves breaking into or connecting to existing services, give Departmental Representative 72 hours of notice for necessary interruption of mechanical or electrical service throughout course of work. Keep duration of interruptions to a minimum. Carry out interruptions after normal working hours of occupants, preferably on weekends.
- .3 Provide for pedestrian and personnel traffic.
- .4 Construct barriers in accordance with Section 01 56 00 - Temporary Barriers and Enclosures and as shown in Drawings.

1.5 SPECIAL REQUIREMENTS

- .1 Electrical installation within occupied spaces to be carried out, Monday to Friday from 18:00 to 07:00 hours and on Saturdays and Sundays, unless otherwise approved by Departmental Representative.
- .2 Carry out noise generating Work Monday to Friday from 18:00 to 07:00 hours and on Saturdays and Sundays, unless otherwise approved by Departmental Representative.
- .3 Submit schedule in accordance with Section 01 32 16.07 - Construction Progress Schedule - Bar (GANTT) Chart.
- .4 Ensure Contractor's personnel employed on site become familiar with and obey regulations including safety, fire, traffic and security regulations.

- .5 Keep within limits of work and avenues of ingress and egress.
- .6 Deliver materials during normal working hours unless otherwise approved by Departmental Representative.

1.6 SECURITY

- .1 Where security has been reduced by Work of Contract, provide temporary means to maintain security. Provide written temporary means of security for review by Departmental Representative.
- .2 Security clearances:
 - .1 Personnel employed on this project will be subject to security check. Obtain requisite clearance, as instructed, for each individual who will be required to enter premises.
 - .2 Personnel will be checked daily at start of work shift.
 - .3 Contractor's personnel will require satisfactory RCMP initiated security screening in order to complete Work in premises and on site.
- .3 Security escort:
 - .1 Personnel employed on this project must be escorted when executing work in all areas during normal working hours. Personnel must be escorted in all areas after normal working hours.
 - .2 Submit an escort request to Departmental Representative at least 14 days before service is needed. For requests submitted within time noted above, costs of security escort will be paid for by Departmental Representative. Cost incurred by late request will be Contractor's responsibility.
 - .3 Any escort request may be cancelled free of charge if notification of cancellation is given at least 8 hours before scheduled time of escort. Cost incurred by late request will be Contractor's responsibility.
 - .4 Calculation of costs will be based on average hourly rate of security officer for minimum of 8 hours per day for late service request and 4 hours for late cancellations.

1.7 BUILDING SMOKING ENVIRONMENT

- .1 Comply with smoking restrictions. Smoking is not permitted in or around the building. Smoking is allowed only in areas indicated by Departmental Representative.

1.8 OCCUPIED SPACES

- .1 Coordinate the work with the continued occupancy of the complete building. Schedule work outside of the occupancy schedule in conjunction with Departmental Representative.
- .2 Provide detailed work plan for review and acceptance by the Departmental Representative.

END OF SECTION

RCMP Clearance Requirements (Law Enforcement Checks)

- .1 All personnel employed on this project will be subject to at a minimum, the RCMP Facilities Access Level 2 clearance requirements by the RCMP.
- .2 Prior to the commencement of the on-site activities, all personnel engaged in the execution of the work on the exterior or interior of an RCMP occupied and/or unoccupied building or outside on the grounds, shall have at a minimum, the requisite RCMP Facilities Access Level 2 clearance.
- .3 Immediately upon award of the contract, the Contractor shall prepare and submit the attached requisite forms, provided by the Departmental Representative (or failing that the RCMP Project Manager), for each Contractor employee and sub-contractor employee to be engaged in the work on the exterior or interior of an occupied and/or unoccupied building or outside on the grounds. In addition, Contractor's employees and sub-contractor employees must include with their requisite forms, government issued documents (driver's license/photo identification and birth certificate), for each Contractor employee and sub-contractor employee engaged in the work at the RCMP as noted above.

To eliminate delays in the clearance process, all clearance documents completed by the Contractor's employees and sub-contractor employees must be reviewed by the Contractor to ensure that all requested information has been provided, prior to submitting documents to the RCMP. Incomplete forms will be returned to the Contractor.

The Contractor's employees and sub-contractor employees shall only mobilize on site, once the requisite RCMP clearance has been granted.

- .4 The Contractor should batch the fully completed submissions, based on priority work on site and allow for a minimum twenty (20) working days processing time in the project schedule for the review to occur (from the date the completed documents are received by the RCMP). The inability to submit the fully completed requisite forms and documents will not be reason for an extension to the project schedule or additional compensation.
- .5 The Contractor's employees and subcontractor employees must be escorted at all times by a designate of the RCMP. This designate will be at no cost to the Contractor.
- .6 The Contractor shall give the RCMP 72 hours notice for work to be carried out during periods outside of the normal working hours of Monday to Friday, from 06:00 to 18:00 hours.
- .7 At the request of the Departmental Representative (or failing that the RCMP Project Manager), Contractor's employees and sub-contractor employees may be requested to undertake additional clearance requirements, to obtain the RCMP Reliability Status clearance. Additional clearance requirements would include submission of the completed TBS 330-60 form and Security Pre-Interview Questionnaire form, fingerprints for verification purposes (at no cost to the Contractor) and undertaking of an interview. This would enable the Contractor's employees or sub-contractor employees, whom have been granted the RCMP Reliability Status clearance, unescorted access to some occupied and/or unoccupied RCMP buildings, or outside on the grounds. Additional processing time (approximately forty working days) will be required for this clearance.



RCMP National Project Delivery Office, Regina
Contractor/Consultant Information Sheet



Page 1 of 2

PLEASE PRINT LEGIBLY / ALL INFORMATION MUST BE PROVIDED

NOTE: SUB-CONTRACTORS ARE TO CONTACT THE GENERAL CONTRACTOR FOR INSTRUCTIONS/QUESTIONS REGARDING COMPLETION OF FORMS - *NOT THE RCMP*

***CONTRACTORS/CONSULTANTS MUST PROVIDE
THE FOLLOWING INFORMATION:***

1. Your Complete Legal Name: (First/Middle or "no Middle Name"/ Last Name)	
2. Name of Company That You Work For:	
3. Company Telephone Number :	
4. Project That You Are Working On: (Name of Project/Building/City/Province)	
5. Access Period (Start & End Dates): (If exact dates unknown, estimated dates)	

CONTRACTORS/CONSULTANTS MUST PROVIDE PHOTOCOPIES OF:

	MARK YES / NO:
1. Driver's License (a clear copy of both the front and back of the document on the same page, certified to be a true copy by their supervisor or colleague as follows (handwrite/print): 'Certified True Copy'; thereafter, the person certifying true copy would print and sign their First and Last Name.	
2. Note: If you do not have a Driver's License, please provide other government issued photo identification (passport, treaty card).	
3. Birth Certificate (a clear copy of both the front and back of the document on one page, certified to be a true copy by their supervisor or colleague as follows (handwrite/print): 'Certified True Copy'; thereafter, the person certifying true copy would print and sign their First and Last Name.	

***CONTRACTORS/CONSULTANTS MUST PROVIDE THE FOLLOWING
DOCUMENTS WITH THEIR COMPLETED:***

1. **TBS 330-23E,**
2. **TBS 330-60E &**

3. SECURITY/RELIABILITY PRE-INTERVIEW QUESTIONNAIRE:

DOCUMENTS ATTACHED:	MARK YES / NO:
1. Two current Passport Style Photographs (do not have to be certified)	
2. Two sets of Fingerprints on Form C-216 ("Roll and Ink" style) – must be obtained from a Corp of Commissionaires office.	

CONTRACTORS / CONSULTANTS - PLEASE NOTE THE FOLLOWING:

Should an RCMP Access tag/card be issued to you, please note the following;

- 1) You are the sole user of the access tag and it must be visibly worn while working on the site.
- 2) The access tag is non-transferrable / cannot be used while working on projects other than the RCMP project it was issued for.
- 3) The access tag must be returned to the RCMP issuing office or site foreman (if approved) at the end of each day.
- 4) No access to areas that you have not been cleared will be allowed and if found in these areas your clearance will be revoked and you will be removed from the site.

Employee Signature:	Signed on Date:
---------------------	-----------------

EMPLOYER TO REVIEW (not employee applicant of this form), COMPLETE & SIGN:

In order to comply with Federal Government and RCMP policies and guidelines, in relation to the collection of personal information, the employer requesting the security checks must be satisfied that he/she can confirm the identity of the applicant.

The employer MUST (“employer” - your supervisor or a colleague of the company that you are employed by):

- 1) Request that their employees attend in person and provided two pieces of identification.
- 2) ID MUST include full date of birth and name of the individual ie, Driver's Licence - Birth Certificate, Passport, Firearms Licence. (One piece of ID must include the photograph and if using the Drivers Licence copy both the photo portion as well as the signature portion.)
- 3) If the employee has changed his/her name, ID MUST be provided with both the current as well as past names.

Type of ID: 1) _____ **Number** _____

2) **Number**

Employers Name: _____
(First Name and Last Name)

Employers Signature: _____

Date of signature: _____



**PERSONNEL SCREENING,
CONSENT AND AUTHORIZATION FORM**

OFFICE USE ONLY		
Reference number	Department/Organization number	File number

NOTE: For Privacy Act Statement refer to Section C of this form and for completion instructions refer to attached instructions.
Please typewrite or print in block letters.

A ADMINISTRATIVE INFORMATION (To be completed by the Authorized Departmental/Agency/Organizational Official)

<input type="checkbox"/> New	<input type="checkbox"/> Update	<input type="checkbox"/> Upgrade	<input type="checkbox"/> Transfer	<input type="checkbox"/> Supplemental	<input type="checkbox"/> Re-activation
------------------------------	---------------------------------	----------------------------------	-----------------------------------	---------------------------------------	--

The requested level of reliability/security check(s)

<input type="checkbox"/> Reliability Status	<input type="checkbox"/> Level I (CONFIDENTIAL)	<input type="checkbox"/> Level II (SECRET)	<input type="checkbox"/> Level III (TOP SECRET)
<input type="checkbox"/> Other _____			

PARTICULARS OF APPOINTMENT/ASSIGNMENT/CONTRACT

<input type="checkbox"/> Indeterminate	<input type="checkbox"/> Term	<input type="checkbox"/> Contract	<input type="checkbox"/> Industry	<input type="checkbox"/> Other (specify secondment, assignment, etc.) _____
--	-------------------------------	-----------------------------------	-----------------------------------	---

Justification for security screening requirement

Position/Competition/Contract number	Title	Group/Level (Rank if applicable)	
Employee ID number/PRI/Rank and Service number (if applicable)	If term or contract, indicate duration period ▶	From	To
Name and address of department / organization / agency	Name of official	Telephone number ()	Facsimile number ()

B BIOGRAPHICAL INFORMATION (To be completed by the applicant)

Surname (Last name)	Full given names (no initials) underline or circle usual name used	Family name at birth
---------------------	--	----------------------

All other names used (i.e., Nickname)	Sex <input type="checkbox"/> Male <input type="checkbox"/> Female	Date of birth Y M D	Country of birth	Date of entry into Canada if born outside Canada Y M D
---------------------------------------	---	------------------------	------------------	---

RESIDENCE (provide addresses for the last five years, starting with the most current) Home address	Daytime telephone number ()	E-mail address
---	------------------------------	----------------

1	Apartment number	Street number	Street name	Civic number (if applicable)	From Y M	To present
	City	Province or state	Postal code	Country	Telephone number ()	

2	Apartment number	Street number	Street name	Civic number (if applicable)	From Y M	To Y M
	City	Province or state	Postal code	Country	Telephone number ()	

Have you previously completed a Government of Canada security screening form? <input type="checkbox"/> Yes <input type="checkbox"/> No	If yes, give name of employer, level and year of screening. Y
--	---

CRIMINAL CONVICTIONS IN AND OUTSIDE OF CANADA (see instructions)

Have you ever been convicted of a criminal offence for which you have not been granted a pardon? <input type="checkbox"/> Yes <input type="checkbox"/> No	If yes, give details: (charge(s), name of police force, city, province/state, country and date of conviction) ▼
---	---

Charge(s)	Name of police force	City
Province/State	Country	Date of conviction ▶ Y M D



PERSONNEL SCREENING,
CONSENT AND AUTHORIZATION FORM

PROTECTED (when completed)

Surname and full given names	Date of birth Y M D
------------------------------	------------------------

C CONSENT AND VERIFICATION (To be completed by the applicant and authorized Departmental/Agency/Organizational Official)

Checks Required (See Instructions)	Applicant's initials	Name of official (print)	Official's initials	Official's Telephone number
1. <input type="checkbox"/> Date of birth, address, education, professional qualifications, employment history, personal character references				()
2. <input type="checkbox"/> Criminal record check				()
3. <input type="checkbox"/> Credit check (financial assessment, including credit records check)				()
4. <input type="checkbox"/> Loyalty (security assessment only)				
5. <input type="checkbox"/> Other (specify, see instructions) Law Enforcement Records Checks				()

The Privacy Act Statement
The information on this form is required for the purpose of providing a security screening assessment. It is collected under the authority of subsection 7(1) of the *Financial Administration Act* and the Government Security Policy (GSP) of the Government of Canada, and is protected by the provisions of the *Privacy Act* in institutions that are covered by the *Privacy Act*. Its collection is mandatory. A refusal to provide information will lead to a review of whether the person is eligible to hold the position or perform the contract that is associated with this Personnel Screening Request. Depending on the level of security screening required, the information collected by the government institution may be disclosed to the Royal Canadian Mounted Police (RCMP) and the Canadian Security Intelligence Service (CSIS), which conduct the requisite checks and/or investigation in accordance with the GSP and to entities outside the federal government (e.g. credit bureaus). It is used to support decisions on individuals working or applying to work through appointment, assignment or contract, transfers or promotions. It may also be used in the context of updating, or reviewing for cause, the reliability status, security clearance or site access, all of which may lead to a re-assessment of the applicable type of security screening. Information collected by the government institution, and information gathered from the requisite checks and/or investigation, may be used to support decisions, which may lead to discipline and/or termination of employment or contractual agreements. The personal information collected is described in Standard PIB PSU 917 (Personnel Security Screening) which is used by all government agencies, except the Department of National Defence PIB DND/PPE 834 (Personnel Security Investigation File), RCMP PIB CMP PPU 065 (Security/Reliability Screening Records), CSIS PIB SIS PPE 815 (Employee Security), and PWGSC PIB PWGSC PPU 015 (Personnel Clearance and Reliability Records) used for Canadian Industry Personnel. Personal information related to security assessments is also described in the CSIS PIB SIS PPU 005 (Security Assessments/Advice).

I, the undersigned, do consent to the disclosure of the preceding information including my photograph for its subsequent verification and/or use in an investigation for the purpose of providing a security screening assessment. By consenting to the above, I acknowledge that the verification and/or use in an investigation of the preceding information may also occur when the reliability status, security clearance or site access are updated or otherwise reviewed for cause under the Government Security Policy. My consent will remain valid until I no longer require a reliability status, a security clearance or a site access clearance, my employment or contract is terminated, or until I otherwise revoke my consent, in writing, to the authorized security official.

Signature

Date (Y/M/D)

D REVIEW (To be completed by the authorized Departmental/Agency/Organizational Official responsible for ensuring the completion of sections A, B and C)

Name and title	Telephone number
Address	Facsimile number

E APPROVAL (To be completed by authorized Departmental/Agency/Organizational Security Official only)

I, the undersigned, as the authorized security official, do hereby approve the following level of screening.

Reliability Status

☐ Approved Reliability Status ☐ Not approved

Name and title

Signature

Date (Y/M/D)

Security Clearance (if applicable)

☐ Level I ☐ Level II ☐ Level III ☐ Not recommended

Name and title

Signature

Date (Y/M/D)

Comments

PHOTO
(for Level III T.S.,
and/or upon request
- see instructions)



INSTRUCTIONS FOR PERSONNEL SCREENING CONSENT AND AUTHORIZATION FORM TBS/SCT 330-23E (Rev. 2002/02)

Once completed, this form shall be safeguarded and handled at the level of Protected A.

General:

If space allotted in any portion is insufficient please use separate sheet using same format.

1. Section A (Administrative Information) Authorized Departmental/Agency/Organizational Official

The Official, based on instructions issued by the Departmental Security Officer, may be responsible for determining, based on five year background history, what constitutes sufficient verification of personal data, educational and professional qualifications, and employment history. References are to be limited to those provided on the application for employment or equivalent forms.

SUPPLEMENTAL INFORMATION REQUIREMENTS

Persons who presently hold a SECURITY CLEARANCE and subsequently marry, remarry or commence a common-law partnership, in addition to having to update sections of the *Security Clearance Form (TBS/SCT 330-60)*, are required to submit an original *Personnel Screening, Consent and Authorization Form*, with the following parts completed:

Part A - As set forth in each question

Part B - As set forth in each question, excluding CRIMINAL CONVICTIONS IN AND OUTSIDE OF CANADA.

Part C - Applicant's signature and date only are required

"Other". This should be used to identify if the security screening is for Site Access, NATO, SIGINT etc.

2. Section B (Biographical Information)

To be completed by the **applicant**. If more space is required use a separate sheet of paper. Each sheet must be signed.

Country of Birth - For "NEW" requests, if born abroad of Canadian parents, please provide a copy of your Certificate of Registration of Birth Abroad. If you arrived in Canada less than five years ago, provide a copy of the Immigration Visa, Record of Landing document or a copy of passport.

- List only criminal convictions for which a pardon has NOT been granted. Include on a separate attached sheet of paper, if more than one conviction. Applicant must include those convictions outside Canada.
- Offences under the *National Defence Act* are to be included as well as convictions by courts-martial are to be recorded.

3. Section C (Consent and Verification)

A copy of Section "C" may be released to institutions to provide acknowledgement of consent.

Criminal record checks (fingerprints may be required) and credit checks are to be arranged through the Departmental Security Office or the delegated Officer.

Consent: may be given only by an applicant who has reached the age of majority, otherwise, the signature of a parent or guardian is mandatory.

The age of majority is:

19 years in NFLD., N.S., N.B., B.C., Yukon, Northwest Territories and Nunavut;

18 years in P.E.I., Que., Ont., Man., Sask. and Alta.

The applicant will provide initials in the "applicant's initials box".

The official who carried out the verification of the information will print their name, insert their initials and telephone number in the required space.

- Reliability Screening (for all types of screening identified within Section A): complete numbers 1 and 2 and 3 if applicable.
- Security Clearance (for all types of screening identified within Section A): complete numbers 1 to 4 and 5 where applicable.
- Other: number 5 is used only where prior Treasury Board of Canada Secretariat approval has been obtained.

4. Section D (Review)

To be completed by authorized Departmental/Agency/Organizational Official who is responsible for ensuring the completion of sections A to C as requested.

5. Section E (Approval)

Authorized Departmental/Agency/Organizational Security Official refers to the individuals as determined by departments, agencies, and organizations that may verify reliability information and/or approve/not approve reliability status and/or security clearances. Approved Reliability Status and Level I, II and III, as well as the signature of the authorized security official or manager are added for Government of Canada use only. Applicants are to be briefed, acknowledge, and be provided with a copy of the "Security Screening Certificate and Briefing Form (TBS/SCT 330-47)".

Note: Private sector organizations do not have the authority to approve any level of security screening.

Photographs: Departments/Agencies/Organizations are responsible for ensuring that three colour photographs of passport size are attached to the form for the investigating agency. Maximum dimensions are 50mm x 70mm and minimum are 43mm x 54mm. The face length from chin to crown of head must be between 25mm x 35mm. The photographs must be signed by the applicant and an authorized security official. The photographs must have been taken within the last six months. It is required for new or upgrade Level III security clearances for identification of the applicant during the security screening investigation by the investigating agency. The investigating agency may in specific incidents request a photograph for a Level I or II clearances when an investigation is required.

Surname	Date of birth
---------	---------------

RESIDENCE (Additional Information)

3	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From Y M	To Y M
	City		Province or state	Postal code	Country	Telephone number	
4	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From Y M	To Y M
	City		Province or state	Postal code	Country	Telephone number	
5	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From Y M	To Y M
	City		Province or state	Postal code	Country	Telephone number	
6	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From Y M	To Y M
	City		Province or state	Postal code	Country	Telephone number	
7	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From Y M	To Y M
	City		Province or state	Postal code	Country	Telephone number	
8	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From Y M	To Y M
	City		Province or state	Postal code	Country	Telephone number	
9	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From Y M	To Y M
	City		Province or state	Postal code	Country	Telephone number	
10	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From Y M	To Y M
	City		Province or state	Postal code	Country	Telephone number	
11	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From Y M	To Y M
	City		Province or state	Postal code	Country	Telephone number	
12	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From Y M	To Y M
	City		Province or state	Postal code	Country	Telephone number	
13	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From Y M	To Y M
	City		Province or state	Postal code	Country	Telephone number	

**ADDITIONAL INSTRUCTIONS FOR COMPLETION OF
GOVERNMENT OF CANADA PERSONNEL SCREENING, CONSENT AND
AUTHORIZATION FORM (Form No. TBS 330-23E)**

NOTE:

All information requested on TBS 330-23E **MUST** be provided (do not leave any “blanks”, provide partial information, and do not use any abbreviations - ie. CA for Canada).

Failure to provide requested information will result in forms being returned to applicants.

Page 1 of Form:

Section A. Administrative Information.: Do not complete (completed by the RCMP).

Section B. Biographical Info.: To be completed by applicant:

1. Surname: Your Last Name that you currently use – ie. “Smith”
2. Full Given Names (no initials):
 - a. Your First Name and Middle Name (s) ie. “Cameron John”
**If you do not have a middle name, state “no middle name” on the form.
**Circle or underline your usual name used (whether you go by your first name or middle name).
3. Family Name at Birth: Your Last Name when you were born - ie. “Smith” (do not include “Same”)
4. All other names used: Abbreviation(s) of name(s) used (ie. “Dave”/David, “Charlie”/Charles) or nicknames.
5. Sex: Place “x” in box beside male or female.
6. Date of Birth: provide the Year, Month and Day you were born ie. 2012-01-01 (must provide all in this format)
7. Country of Birth: - the Country that you were born in ie. Canada (no abbreviations such as “CA”)
8. Date of entry into Canada if born outside Canada: - ie. 2012-01-01 (Year, Month, Day format)
9. Daytime telephone number: Your telephone number that the RCMP can reach you at in the daytime, including your area code.
10. E-mail address: Your e-mail address at work, or if you do not have one at work, your home e-mail address.
11. Residence(s): provide addresses where you have permanently or temporarily resided for the last **five years**, starting with the most current home address. Must be consecutive dates – no breaks in time periods.
**Do not fill in address in grey/shaded area beside “Home address”; fill in current address in the boxes under “Home address”.
 - a. Apartment Number - fill in if you have one; if you do not live in an apartment, leave blank.
 - b. Street Number – your house number ie. “421”
 - c. Street Name – ie. “Smith Street/George Avenue; or “4th Street” if no name (no abbreviations)
If you do not have a street address or you live on a farm/acreage, please provide your legal land descriptions (ie. SW-30-23-45-W4th) – **NO POST OFFICE BOX NUMBERS.

**ADDITIONAL INSTRUCTIONS FOR COMPLETION OF
GOVERNMENT OF CANADA PERSONNEL SCREENING, CONSENT AND
AUTHORIZATION FORM (Form No. TBS 330-23E)**

- d. From – the year and month that you moved to your current / previous residence(s);
**If you cannot recall the month, please state above the M – “unknown”
- e. To – “Present” or the year and month that you moved/vacated your previous residences (not current residence).
- f. City – the name of the city or town that you currently and previously resided in.
- g. Province or State – the name of the province or state that you currently and previously resided in (no abbreviations ie. “AB” or “SK”).
- h. Postal Code – your current and previous postal codes.
- i. Country – the name of the country that you currently and previously resided in (no abbreviations).
- j. Telephone Number – your current and previous home telephone numbers, including area code.
- Note: i. If you do not have enough space on the attached form to list all addresses for the last five years, please use the attached form titled “TBS 330-23E Residence Additional Info”.
- ii. You must include your “Surname” and Date of Birth at the top of the page as requested.
- **NO POST OFFICE BOX NUMBERS;**
- **DATES MUST BE CONSECUTIVE–NO BREAKS IN TIME PERIODS (as stated in 11.)**
12. Have you previously completed a Government of Canada security screening form?:
- a. “No” or
- b. “Yes” – if “Yes”, please provide details. If you cannot recall some or all of the details (ie. year of screening, state “cannot recall”).
13. Criminal Convictions:
- a. “No” OR
- b. “Yes” - if “Yes”, please provide details. If you cannot recall some or all of the details (ie. date of conviction, state “cannot recall”).

Page 2 of Form:

Top of Page 2: To be completed by applicant:

1. Surname (your last name) followed by a comma – ie. Smith,
2. Full given names – your first name and then your middle name
**If you do not have a middle name, state “no middle name” on the form.
**Circle or underline your usual name used (ie. whether you go by your first name or middle name).
3. Date of birth - provide – Year, Month, Day ie. 2012-01-01 (must provide all in this format / no blanks)

Section C. Consent and Verification: To be completed by applicant:

1. a.) Place a “Checkmark” in Boxes 1. to 5; then:
b.) Initial under “Applicant’s Initials” column – **numbers 1. to 5. (you must initial all boxes-1 to 5).**
2. Read the Privacy Act Statement and sign above “Signature” and “Date (Y/M/D)”

Section D. Review: do not complete (completed by RCMP)

Section E. Approval: do not complete (completed by RCMP)

NOTE: RCMP FACILITIES ACCESS LEVEL 2 CLEARANCE – Photographs ARE NOT required.
RCMP “RELIABILITY STATUS CLEARANCES” – Photographs ARE required.

Updated July 22, 2013

SAMPLE OF COMPLETED Document

1 of 3



Government of Canada
Gouvernement du Canada

PROTECTED (when completed)

PERSONNEL SCREENING, CONSENT AND AUTHORIZATION FORM

Reference number

Department/Organization number

File number

NOTE: For Privacy Act Statement refer to Section C of this form and for completion instructions refer to attached instructions.
Please typewrite or print in block letters.

A ADMINISTRATIVE INFORMATION (To be completed by the Authorized Departmental/Agency/Organizational Official)

☐ New ☐ Update ☐ Upgrade ☐ Transfer ☐ Supplemental ☐ Re-activation

The requested level of reliability/security check(s)

☐ Reliability Status ☐ Level I (CONFIDENTIAL) ☐ Level II (SECRET) ☐ Level III (TOP SECRET)

☐ Other

PARTICULARS OF APPOINTMENT/ASSIGNMENT/CONTRACT

☐ Indeterminate ☐ Term ☐ Contract ☐ Industry ☐ Other (specify secondment, assignment, etc.)

Justification for security screening requirement

Position/Compensation/Contract number	Title		Group/Level (Rank if applicable)
Employee ID number/PR/IRank and Service number (if applicable)	If term or contract, indicate duration period	From	To
Name and address of department / organization / agency	Name of official	Telephone number ()	Facsimile number ()

B BIOGRAPHICAL INFORMATION (to be completed by the applicant)

Surname (Last name) SMITH	Full given names (no initials) underline or circle usual name used <u>John</u> (nomiddle name)	Family name at birth SMITH
All other names used (i.e. Nickname) Johnny	Sex <input checked="" type="checkbox"/> Male <input type="checkbox"/> Female	Date of birth 19600127
	Country of birth CANADA	Date of entry into Canada if born outside Canada Y M D

RESIDENCE (provide addresses for the last five years, starting with the most current) Home address:	Daytime telephone number (306) 201-1433	E-mail address JSmith@telus.net
--	---	---

1	Apartment number	Street number	Street name	Civic number (if applicable)	From Y M	To present
		1257	Cooper Avenue		201001	
	City	Province or state	Postal code	Country	Telephone number	
	PEACE RIVER	ALBERTA	T63 2X9	CANADA	(780) 261-1493	

2	Apartment number	Street number	Street name	Civic number (if applicable)	From Y M	To Y M
			12-13-57-W2		200903	201001
	City	Province or state	Postal code	Country	Telephone number	
	GRAND CACHE	ALBERTA	TOG 7X3	CANADA	(780) 234-2102	

Have you previously completed a Government of Canada security screening form?	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	If yes, give name of employer, level and year of screening. CORRECTIONAL SERVICES CANADA 2010
---	---	---

CRIMINAL CONVICTIONS IN AND OUTSIDE OF CANADA (see instructions)

Have you ever been convicted of a criminal offence for which you have not been granted a pardon?	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	If yes, give details. (charge(s), name of police force, city, province/state, country and date of conviction)
--	---	---

Charge(s) DRIVING UNDER THE INFLUENCE OF ALCOHOL	Name of police force EDMONTON POLICE SERVICE	City EDMONTON
Province/State ALBERTA	Country CANADA	Date of conviction Y M D 2010102011

20f3

Surname	SMITH, John (no middle name)	Date of birth	1960-01-27	PROTECTED A (When completed)
---------	------------------------------	---------------	------------	------------------------------

RESIDENCE (Additional Information)

3	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From	To
			1-87-18-W4			2007 01	2009 03
	City	Province or state	Postal code	Country	Telephone number		
	SASKATOON	SASKATCHEWAN	S0G3C0	CANADA	(306) 231-7192		
4	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From	To
		20	HILL AVENUE			2004 01	2007 01
	City	Province or state	Postal code	Country	Telephone number		
	CALGARY	ALBERTA	T0G3C0	CANADA	(403) 239-7186		
5	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From	To
	City	Province or state	Postal code	Country	Telephone number		
6	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From	To
	City	Province or state	Postal code	Country	Telephone number		
7	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From	To
	City	Province or state	Postal code	Country	Telephone number		
8	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From	To
	City	Province or state	Postal code	Country	Telephone number		
9	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From	To
	City	Province or state	Postal code	Country	Telephone number		
10	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From	To
	City	Province or state	Postal code	Country	Telephone number		
11	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From	To
	City	Province or state	Postal code	Country	Telephone number		
12	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From	To
	City	Province or state	Postal code	Country	Telephone number		
13	Apartment number	Street Number	Street Name		Civic Number (if applicable)	From	To
	City	Province or state	Postal code	Country	Telephone number		

Government
of CanadaGouvernement
du CanadaPERSONNEL SCREENING,
CONSENT AND AUTHORIZATION FORM

PROTECTED (when completed)

Surname and full given names SMITH, John (nomiddle name)	Date of birth 11^Y 9^M 10^D 2017
--	--

C CONSENT AND VERIFICATION (To be completed by the applicant and authorized Departmental/Agency/Organizational Official)				
Checks Required (See Instructions)	Applicant's initials	Name of official (print)	Official's initials	Official's Telephone number
1. <input checked="" type="checkbox"/> Date of birth, address, education, professional qualifications, employment history, personal character references	JS			()
2. <input checked="" type="checkbox"/> Criminal record check	JS			()
3. <input checked="" type="checkbox"/> Credit check (financial assessment, including credit records check)	JS			()
4. <input checked="" type="checkbox"/> Loyalty (security assessment only)	JS			()
5. <input checked="" type="checkbox"/> Other (Law Enforcement Records Checks)	JS			()

The Privacy Act Statement

The information on this form is required for the purpose of providing a security screening assessment. It is collected under the authority of subsection 7(1) of the *Financial Administration Act* and the *Government Security Policy (GSP)* of the Government of Canada, and is protected by the provisions of the *Privacy Act* in institutions that are covered by the *Privacy Act*. Its collection is mandatory. A refusal to provide information will lead to a review of whether the person is eligible to hold the position or perform the contract that is associated with this Personnel Screening Request. Depending on the level of security screening required, the information collected by the government institution may be disclosed to the Royal Canadian Mounted Police (RCMP) and the Canadian Security Intelligence Service (CSIS), which conduct the requisite checks and/or investigation in accordance with the GSP and to entities outside the federal government (e.g. credit bureaus). It is used to support decisions on individuals working or applying to work through appointment, assignment or contract, transfers or promotions. It may also be used in the context of updating, or reviewing for cause, the reliability status, security clearance or site access, all of which may lead to a re-assessment of the applicable type of security screening. Information collected by the government institution, and information gathered from the requisite checks and/or investigation, may be used to support decisions, which may lead to discipline and/or termination of employment or contractual agreements. The personal information collected in investigation, may be used to support (Personnel Security Screening) which is used by all government agencies, except the Department of National Defence PIB DND/PPE 834 (Personnel Security Investigation File), RCMP PIB CMP PPU 065 (Security/Reliability Screening Records), CSIS PIB SIS PPE 815 (Employee Security), and PWGSC PIB PWGSC PPU 015 (Personnel Clearance and Reliability Records) used for Canadian Industry Personnel. Personal information related to security assessments is also described in the CSIS PIB SIS PPU 006 (Security Assessments/Advice).

I, the undersigned, do consent to the disclosure of the preceding information including my photograph for its subsequent verification and/or use in an investigation for the purpose of providing a security screening assessment. By consenting to the above, I acknowledge that the verification and/or use in an investigation of the preceding information may also occur when the reliability status, security clearance or site access are updated or otherwise reviewed for cause under the Government Security Policy. My consent will remain valid until I no longer require a reliability status, a security clearance or a site access clearance, my employment or contract is terminated, or until I otherwise revoke my consent, in writing, to the authorized security official.

John Smith
Signature

2011-12-01
Date (Y/M/D)

D REVIEW (To be completed by the authorized Departmental/Agency/Organizational Official responsible for ensuring the completion of sections A, B and C)	
Name and title	Telephone number
Address	Facsimile number
E APPROVAL (To be completed by authorized Departmental/Agency/Organizational Security Official only)	
I, the undersigned, as the authorized security official, do hereby approve the following level of screening.	
Reliability Status	
<input type="checkbox"/> Approved Reliability Status	<input type="checkbox"/> Not approved
Name and title	
Signature	
Date (Y/M/D)	
Security Clearance (if applicable)	
<input type="checkbox"/> Level I	<input type="checkbox"/> Level II
<input type="checkbox"/> Level III	<input type="checkbox"/> Not recommended
Name and title	
Signature	
Date (Y/M/D)	
Comments	

PHOTO
(for Level III T.S.,
and/or upon request
- see instructions)



Government
of Canada

Gouvernement
du Canada

INSTRUCTIONS FOR PERSONNEL SCREENING CONSENT AND AUTHORIZATION FORM TBS/SCT 330-23E (Rev. 2002/02)

Once completed, this form shall be safeguarded and handled at the level of Protected A.

General:

If space allotted in any portion is insufficient please use separate sheet using same format.

1. Section A (Administrative Information) Authorized Departmental/Agency/Organizational Official

The Official, based on instructions issued by the Departmental Security Officer, may be responsible for determining, based on five year background history, what constitutes sufficient verification of personal data, educational and professional qualifications, and employment history. References are to be limited to those provided on the application for employment or equivalent forms.

SUPPLEMENTAL INFORMATION REQUIREMENTS

Persons who presently hold a SECURITY CLEARANCE and subsequently marry, remarry or commence a common-law partnership, in addition to having to update sections of the *Security Clearance Form (TBS/SCT 330-60)*, are required to submit an original *Personnel Screening, Consent and Authorization Form*, with the following parts completed:

Part A - As set forth in each question

Part B - As set forth in each question, excluding CRIMINAL CONVICTIONS IN AND OUTSIDE OF CANADA.

Part C - Applicant's signature and date only are required

"Other". This should be used to identify if the security screening is for Site Access, NATO, SIGINT etc.

2. Section B (Biographical Information)

To be completed by the applicant. If more space is required use a separate sheet of paper. → attached "Residence (Additional Information) Form."

Country of Birth - For "NEW" requests, if born abroad of Canadian parents, please provide a copy of your Certificate of Registration of Birth Abroad. If you arrived in Canada less than five years ago, provide a copy of the Immigration Visa, Record of Landing document or a copy of passport.

- List only criminal convictions for which a pardon has NOT been granted. Include on a separate attached sheet of paper, if more than one conviction. Applicant must include those convictions outside Canada. Hereafter sign the separate attached sheet of paper.
- Offences under the *National Defence Act* are to be included as well as convictions by courts-martial are to be recorded.

3. Section C (Consent and Verification)

A copy of Section "C" may be released to institutions to provide acknowledgement of consent.

Criminal record checks (fingerprints may be required) and credit checks are to be arranged through the Departmental Security Office or the delegated Officer.

Consent: may be given only by an applicant who has reached the age of majority, otherwise, the signature of a parent or guardian is mandatory.

The age of majority is:

19 years in Nfld., N.S., N.B., B.C., Yukon, Northwest Territories and Nunavut;
18 years in P.E.I., Que., Ont., Man., Sask. and Alta.

The applicant will provide initials in the "applicant's initials box". - Box 1-5

- The official who carried out the verification of the information will print their name, insert their initials and telephone number in the required space (RCMP employee only)
- Reliability Screening (for all types of screening identified within Section A): complete numbers 1 and 2 and 3 if applicable.
- Security Clearance (for all types of screening identified within Section A): complete numbers 1 to 4 and 5 where applicable.
- Other: number 5 is used only where prior Treasury Board of Canada Secretariat approval has been obtained.

4. Section D (Review)

To be completed by authorized Departmental/Agency/Organizational Official who is responsible for ensuring the completion of sections A to C as requested.

5. Section E (Approval)

Authorized Departmental/Agency/Organizational Security Official refers to the individuals as determined by departments, agencies, and organizations that may verify reliability information and/or approve/not approve reliability status and/or security clearances. Approved Reliability Status and Level I, II and III, as well as the signature of the authorized security official or manager are added for Government of Canada use only. Applicants are to be briefed, acknowledge, and be provided with a copy of the "Security Screening Certificate and Briefing Form (TBS/SCT 330-47)".
Note: Private sector organizations do not have the authority to approve any level of security screening.

Photographs: Departments/Agencies/Organizations are responsible for ensuring that three colour photographs of passport size are attached to the form for the investigating agency. Maximum dimensions are 50mm x 70mm and minimum are 43mm x 54mm. The face length from chin to crown of head must be between 25mm x 35mm. The photographs must be signed by the applicant and an authorized security official. The photographs must have been taken within the last six months. It is required for new or upgrade Level III security clearances for identification of the applicant during the security screening investigation by the investigating agency. The investigating agency may in specific incidents request a photograph for a Level I or II clearances when an investigation is required.

✦ ENSURE ATTACHED "ADDITIONAL INSTRUCTIONS"
ARE REVIEWED/FOLLOWED (more detailed information
on how to complete TBS 330-23E)

Part 1 General

1.1 ADMINISTRATIVE

- .1 Project meetings will be scheduled throughout the progress of the work and at the call of Departmental Representative.
- .2 Provide physical space and make arrangements for meetings.
- .3 Departmental Representative will chair the Pre-Construction Meeting and the Start-Up meeting. The Consultant will chair all subsequent meetings.
- .4 Representative of Contractor, Subcontractor and suppliers attending meetings will be qualified and authorized to act on behalf of party each represents.

1.2 PRECONSTRUCTION MEETING

- .1 Within 15 days after award of Contract, request a meeting of parties in contract to discuss and resolve administrative procedures and responsibilities.
- .2 Agenda to include:
 - .1 Appointment of official representative of participants in the Work.
 - .2 Schedule of Work: in accordance with Section 01 32 16.07 - Construction Progress Schedules - Bar (GANTT) Chart.
 - .3 Schedule of submission of shop drawings, samples, colour chips. Submit submittals in accordance with Section 01 33 00 - Submittal Procedures.
 - .4 Requirements for temporary facilities, site sign, offices, storage sheds, utilities, fences in accordance with Section 01 52 00 - Construction Facilities.
 - .5 Delivery schedule of specified equipment.
 - .6 Site security in accordance with Section 01 56 00 - Temporary Barriers and Enclosures.
 - .7 Proposed changes, change orders, procedures, approvals required, mark-up percentages permitted, time extensions, overtime, administrative requirements.
 - .8 Departmental Representative provided products.
 - .9 Record drawings in accordance with Section 01 33 00 - Submittal Procedures.
 - .10 Maintenance manuals in accordance with Section 01 78 00 - Closeout Submittals.
 - .11 Take-over procedures, acceptance, warranties in accordance with Section 01 78 00 - Closeout Submittals.
 - .12 Monthly progress claims, administrative procedures, photographs, hold backs.
 - .13 Appointment of inspection and testing agencies or firms.
 - .14 Insurances, transcript of policies.

1.3 PROGRESS MEETINGS

- .1 During course of Work, progress meetings will be held on a regular basis. Schedule to be determined.

- .2 Contractor, major Subcontractors involved in Work, Departmental Representative, Owner, and Consultant are to be in attendance.
- .3 Minutes of meetings will be recorded by the Consultant and circulated to all parties within 3 working days.
- .4 Agenda to include the following:
 - .1 Review, approval of minutes of previous meeting.
 - .2 Review of Work progress since previous meeting.
 - .3 Field observations, problems, conflicts.
 - .4 Problems which impede construction schedule.
 - .5 Review of off-site fabrication delivery schedules.
 - .6 Corrective measures and procedures to regain projected schedule.
 - .7 Revision to construction schedule.
 - .8 Progress schedule, during succeeding work period.
 - .9 Review submittal schedules: expedite as required.
 - .10 Maintenance of quality standards.
 - .11 Review proposed changes to determine how there will affect the construction schedule and completion date.
 - .12 Other business.

END OF SECTION

Part 1 General

1.1 DEFINITIONS

- .1 Activity: element of Work performed during course of Project. Activity normally has expected duration and expected cost and expected resource requirements. Activities can be subdivided into tasks.
- .2 Bar Chart (GANTT Chart): graphic display of schedule-related information. In typical bar chart, activities or other Project elements are listed down left side of chart, dates are shown across top, and activity durations are shown as date-placed horizontal bars. Generally, Bar Chart should be derived from commercially available computerized project management system.
- .3 Baseline: original approved plan (for project, work package, or activity), plus or minus approved scope changes.
- .4 Construction Work Week: Monday to Friday, inclusive, will provide five-day work week and define schedule calendar working days as part of Bar (GANTT) Chart submission.
- .5 Duration: number of work periods (not including holidays or other nonworking periods) required to complete activity or other project element. Usually expressed as workdays or workweeks.
- .6 Milestone: significant event in project, usually completion of major deliverable.
- .7 Project Schedule: planned dates for performing activities and the planned dates for meeting milestones. Dynamic, detailed record of tasks or activities that must be accomplished to satisfy Project objectives. Monitoring and control process involves using Project Schedule in executing and controlling activities and is used as basis for decision making throughout project life cycle.
- .8 Project Planning, Monitoring and Control System: overall system operated by Departmental Representative to enable monitoring of project work in relation to established milestones.

1.2 REQUIREMENTS

- .1 Ensure Project Schedule and Detail Schedules are practical and remain within specified Contract duration.
- .2 Plan to complete Work in accordance with prescribed milestones and time frame.
- .3 Limit activity durations to maximum of approximately 10 working days, to allow for progress reporting.
- .4 Ensure that it is understood that Award of Contract or time of beginning, rate of progress, Interim Certificate and Final Certificate as defined times of completion are of essence of this contract.

1.3 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00 - Submittal Procedures.

- .2 Submit Project Schedule to Departmental Representative and Consultant within 7 working days of Award of Contract.
- .3 Provide schedule in PDF format, sized so that description of work can be clearly read when printed out.

1.4 PROJECT MILESTONES

- .1 Project milestones form interim targets for Project Schedule.
 - .1 Project milestones will be identified through discussion with the Contractor and Departmental Representative at the outset of the project.

1.5 PROJECT SCHEDULE

- .1 Develop detailed Project Schedule.
- .2 Ensure detailed Project Schedule includes as minimum milestone and activity types as follows:
 - .1 Award.
 - .2 Shop Drawings, Samples.
 - .3 Mobilization.
 - .4 Exterior work.
 - .5 Structural.
 - .6 Plumbing.
 - .7 Electrical.
 - .8 Piping.
 - .9 Heating, Ventilating, and Air Conditioning.
 - .10 Fire Systems.
 - .11 Testing and Commissioning.
 - .12 Supplied equipment long delivery items.

1.6 PROJECT SCHEDULE REPORTING

- .1 Update Project Schedule on a bi-weekly basis reflecting activity changes and completions, as well as activities in progress.
- .2 Include as part of Project Schedule, narrative report identifying Work status to date, comparing current progress to baseline, presenting current forecasts, defining problem areas, anticipated delays and impact with possible mitigation.

1.7 PROJECT MEETINGS

- .1 Discuss Project Schedule at regular site meetings, identify activities that are behind schedule and provide measures to regain slippage. Activities considered behind schedule are those with projected start or completion dates later than current approved dates shown on baseline schedule.
- .2 Weather related delays with their remedial measures will be discussed and negotiated.

END OF SECTION

Part 1 General

1.1 ADMINISTRATIVE

- .1 Submit to Departmental Representative submittals listed for review. Submit promptly and in orderly sequence to not cause delay in Work. Failure to submit in ample time is not considered sufficient reason for extension of Contract Time and no claim for extension by reason of such default will be allowed.
- .2 Do not proceed with Work affected by submittal until review is complete.
- .3 Present shop drawings, product data, samples and mock-ups in SI Metric units.
- .4 Where items or information is not produced in SI Metric units converted values are acceptable.
- .5 Review submittals prior to submission to Departmental Representative. This review represents that necessary requirements have been determined and verified, or will be, and that each submittal has been checked and co-ordinated with requirements of Work and Contract Documents. Submittals not stamped, signed, dated and identified as to specific project will be returned without being examined and considered rejected.
- .6 Notify Departmental Representative, in writing at time of submission, identifying deviations from requirements of Contract Documents stating reasons for deviations.
- .7 Verify field measurements and affected adjacent Work are co-ordinated.
- .8 Contractor's responsibility for errors and omissions in submission is not relieved by Departmental Representative's review of submittals.
- .9 Contractor's responsibility for deviations in submission from requirements of Contract Documents is not relieved by Departmental Representative review.
- .10 Keep one reviewed copy of each submission on site.

1.2 SHOP DRAWINGS AND PRODUCT DATA

- .1 The term "shop drawings" means drawings, diagrams, illustrations, schedules, performance charts, brochures and other data which are to be provided by Contractor to illustrate details of a portion of Work.
- .2 Submit drawings stamped and signed by professional engineer registered or licensed in Province of Saskatchewan, Canada.
- .3 Indicate materials, methods of construction and attachment or anchorage, erection diagrams, connections, explanatory notes and other information necessary for completion of Work. Where articles or equipment attach or connect to other articles or equipment, indicate that such items have been co-ordinated, regardless of Section under which adjacent items will be supplied and installed. Indicate cross references to design drawings and specifications.
- .4 Allow 7 working days for Departmental Representative's review of each submission.

- .5 Adjustments made on shop drawings by Departmental Representative are not intended to change Contract Price. If adjustments affect value of Work, state such in writing to Departmental Representative prior to proceeding with Work.
- .6 Make changes in shop drawings as Departmental Representative may require, consistent with Contract Documents. When resubmitting, notify Departmental Representative in writing of revisions other than those requested.
- .7 Accompany submissions with transmittal letter, containing:
 - .1 Date.
 - .2 Project title and number.
 - .3 Contractor's name and address.
 - .4 Identification and quantity of each shop drawing, product data and sample.
 - .5 Other pertinent data.
- .8 Submissions include:
 - .1 Date and revision dates.
 - .2 Project title and number.
 - .3 Name and address of:
 - .1 Subcontractor.
 - .2 Supplier.
 - .3 Manufacturer.
 - .4 Contractor's stamp, signed by Contractor's authorized representative certifying approval of submissions, verification of field measurements and compliance with Contract Documents.
 - .5 Details of appropriate portions of Work as applicable:
 - .1 Fabrication.
 - .2 Layout, showing dimensions, including identified field dimensions, and clearances.
 - .3 Setting or erection details.
 - .4 Capacities.
 - .5 Performance characteristics.
 - .6 Standards.
 - .7 Operating weight.
 - .8 Wiring diagrams.
 - .9 Single line and schematic diagrams.
 - .10 Relationship to adjacent work.
- .9 After Departmental Representative's review, distribute copies.
- .10 Submit electronic copy of shop drawings for each requirement requested in specification Sections and as Departmental Representative may reasonably request.
- .11 Submit electronic copy of product data sheets or brochures for requirements requested in specification Sections and as requested by Departmental Representative where shop drawings will not be prepared due to standardized manufacture of product.

- .12 Submit electronic copy of test reports for requirements requested in specification Sections and as requested by Departmental Representative.
 - .1 Report signed by authorized official of testing laboratory that material, product or system identical to material, product or system to be provided has been tested in accord with specified requirements.
 - .2 Testing must have been within 3 years of date of contract award for project.
- .13 Submit electronic copy of certificates for requirements requested in specification Sections and as requested by Departmental Representative.
 - .1 Statements printed on manufacturer's letterhead and signed by responsible officials of manufacturer of product, system or material attesting that product, system or material meets specification requirements.
 - .2 Certificates must be dated after award of project contract complete with project name.
- .14 Submit electronic copy of manufacturer's instructions for requirements requested in specification Sections and as requested by Departmental Representative.
 - .1 Pre-printed material describing installation of product, system or material, including special notices and Material Safety Data Sheets concerning impedances, hazards and safety precautions.
- .15 Submit electronic copy of Manufacturer's Field Reports for requirements requested in specification Sections and as requested by Departmental Representative.
- .16 Documentation of the testing and verification actions taken by manufacturer's representative to confirm compliance with manufacturer's standards or instructions.
- .17 Submit electronic copy of Operation and Maintenance Data for requirements requested in specification Sections and as requested by Departmental Representative.
- .18 Delete information not applicable to project.
- .19 Supplement standard information to provide details applicable to project.
- .20 If upon review by Departmental Representative, no errors or omissions are discovered or if only minor corrections are made, copy will be returned, and fabrication and installation of Work may proceed. If shop drawings are rejected, noted copy will be returned and resubmission of corrected shop drawings, through same procedure indicated above, must be performed before fabrication and installation of Work may proceed.
- .21 The review of shop drawings by Departmental Representative is for sole purpose of ascertaining conformance with general concept.
 - .1 This review shall not mean that Departmental Representative approves detail design inherent in shop drawings, responsibility for which shall remain with Contractor submitting same, and such review shall not relieve Contractor of responsibility for errors or omissions in shop drawings or of responsibility for meeting requirements of construction and Contract Documents.
 - .2 Without restricting generality of foregoing, Contractor is responsible for dimensions to be confirmed and correlated at job site, for information that pertains solely to fabrication processes or to techniques of construction and installation and for co-ordination of Work of sub-trades.

- .22 Electronic submission of Shop Drawings
 - .1 Electronic Shop Drawings (PDF format) shall not exceed 11x17 actual size. Electronic transfer of shop drawings relies on Architect and Engineering Consultants to print a record copy for their files - this can be done providing shop drawings do not exceed 11x17. Larger shop drawings will require hard copies for review.
 - .2 General Contractor to review shop drawing and place their electronic stamp signifying review.
 - .3 General Contractor to email all shop drawings to Architect with copy to Engineering Consultant as applicable.
 - .4 Engineering Consultant to review and place their electronic stamp / marks up, then email to Architect only (Engineering Consultant will not copy anyone else).
 - .5 Architect to check for coordination and transmit reviewed shop drawings by email to General Contractor.

1.3 SAMPLES

- .1 Submit for review samples in duplicate as requested in respective specification Sections. Label samples with origin and intended use.
- .2 Deliver samples prepaid to Departmental Representative's business address.
- .3 Notify Departmental Representative in writing, at time of submission of deviations in samples from requirements of Contract Documents.
- .4 Where colour, pattern or texture is criterion, submit full range of samples.
- .5 Adjustments made on samples by Departmental Representative are not intended to change Contract Price. If adjustments affect value of Work, state such in writing to Departmental Representative prior to proceeding with Work.
- .6 Make changes in samples which Departmental Representative may require, consistent with Contract Documents.
- .7 Reviewed and accepted samples will become standard of workmanship and material against which installed Work will be verified.

1.4 MOCK-UPS

- .1 Erect mock-ups in accordance with 01 45 00 - Quality Control.

1.5 PHOTOGRAPHIC DOCUMENTATION

- .1 Submittals in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Submit electronic copy of colour digital photography in jpg format, standard resolution, as work proceeds, monthly with progress statement, and as directed by Departmental Representative.
- .3 Photographs shall be taken at all construction milestones and anytime a problem arises. The minimum requirement is for photographs to be taken on a weekly basis.
- .4 Project identification: name and number of project and date of exposure indicated.

- .5 Digital photographs stored on CD-ROM, DVD, or USB drive, shall be submitted with the Operation and Maintenance Manuals.

1.6 CERTIFICATES AND TRANSCRIPTS

- .1 Immediately after award of Contract, submit Workers' Compensation Board status.
- .2 Submit transcription of insurance immediately after award of Contract.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 Canada Labour Code, Part 2, Canada Occupational Safety and Health Regulations
- .2 Province of Saskatchewan
 - .1 Occupational Health and Safety Act, 1993, S.S. - Updated 2012.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Submit site-specific Health and Safety Plan: Within 7 days after date of Notice to Proceed and prior to commencement of Work. Health and Safety Plan must include:
 - .1 Results of site specific safety hazard assessment.
 - .2 Results of safety and health risk or hazard analysis for site tasks and operation found in work plan.
- .3 Submit 1 copy of Contractor's authorized representative's worksite health and safety inspection reports to Departmental Representative, weekly.
- .4 Submit copies of reports or directions issued by Federal, Provincial and Territorial health and safety inspectors.
- .5 Submit copies of incident and accident reports.
- .6 Submit WHMIS MSDS - Material Safety Data Sheets in accordance with Section 01 33 00 - Submittal Requirements and as specified in each applicable Section.
- .7 Departmental Representative will review Contractor's site-specific Health and Safety Plan and provide comments to Contractor within 7 days after receipt of plan. Revise plan as appropriate and resubmit plan to Departmental Representative within 5 days after receipt of comments from Departmental Representative.
- .8 Departmental Representative's review of Contractor's final Health and Safety plan should not be construed as approval and does not reduce the Contractor's overall responsibility for construction Health and Safety.
- .9 Medical Surveillance: where prescribed by legislation, regulation or safety program, submit certification of medical surveillance for site personnel prior to commencement of Work, and submit additional certifications for any new site personnel to Departmental Representative.
- .10 Submit on-site Contingency and Emergency Response Plan: address standard operating procedures to be implemented during emergency situations.

1.3 FILING OF NOTICE

- .1 File Notice of Project with Provincial and Municipal authorities prior to beginning of Work.
- .2 Contractor shall agree to install proper site separation and identification to maintain time and space at all times throughout life of project.

1.4 SAFETY ASSESSMENT

- .1 Perform site specific safety hazard assessment related to project.

1.5 MEETINGS

- .1 Schedule and administer Health and Safety meeting with Departmental Representative prior to commencement of Work.

1.6 REGULATORY REQUIREMENTS

- .1 Do Work in accordance with Section 01 41 00 - Regulatory Requirements.

1.7 GENERAL REQUIREMENTS

- .1 Develop written site-specific Health and Safety Plan based on hazard assessment prior to beginning site Work and continue to implement, maintain, and enforce plan until final demobilization from site. Health and Safety Plan must address project specifications.
- .2 Departmental Representative may respond in writing, where deficiencies or concerns are noted and may request re-submission with correction of deficiencies or concerns.

1.8 RESPONSIBILITY

- .1 Be responsible for health and safety of persons on site, safety of property on site and for protection of persons adjacent to site and environment to extent that they may be affected by conduct of Work.
- .2 Comply with and enforce compliance by employees with safety requirements of Contract Documents, applicable federal, provincial, territorial and local statutes, regulations, and ordinances, and with site-specific Health and Safety Plan.

1.9 COMPLIANCE REQUIREMENTS

- .1 Comply with Occupational Health and Safety Regulations, 1996.
- .2 Comply with Canada Labour Code, Canada Occupational Safety and Health Regulations.

1.10 UNFORSEEN HAZARDS

- .1 When unforeseen or peculiar safety-related factor, hazard, or condition occur during performance of Work, advise Safety Coordinator and follow procedures in accordance with Acts and Regulations of Province having jurisdiction and Departmental Representative verbally and in writing.

1.11 HEALTH AND SAFETY CO-ORDINATOR

- .1 Employ and assign to Work, competent and authorized representative as Health and Safety Coordinator. Health and Safety Coordinator must:
 - .1 Have site-related working experience specific to activities associated with the scope of this work.
 - .2 Have working knowledge of occupational safety and health regulations.
 - .3 Be responsible for completing Contractor's Health and Safety Training Sessions and ensuring that personnel not successfully completing required training are not permitted to enter site to perform Work.

- .4 Be responsible for implementing, enforcing daily and monitoring site-specific Contractor's Health and Safety Plan.
- .5 Be on site during execution of Work and report directly to and be under direction of site supervisor.

1.12 POSTING OF DOCUMENTS

- .1 Ensure applicable items, articles, notices and orders are posted in conspicuous location on site in accordance with Acts and Regulations of Province having jurisdiction, and in consultation with Departmental Representative.

1.13 CORRECTION OF NON-COMPLIANCE

- .1 Immediately address health and safety non-compliance issues identified by authority having jurisdiction or by Departmental Representative.
- .2 Provide Departmental Representative with written report of action taken to correct non-compliance of health and safety issues identified.
- .3 Departmental Representative may stop Work if non-compliance of health and safety regulations is not corrected.

1.14 BLASTING

- .1 Blasting or other use of explosives is not permitted.

1.15 POWDER ACTUATED DEVICES

- .1 Use powder actuated devices only after receipt of written permission from Departmental Representative.

1.16 WORK STOPPAGE

- .1 Give precedence to safety and health of public and site personnel and protection of environment over cost and schedule considerations for Work.

END OF SECTION

Part 1 General

1.1 REFERENCES AND CODES

- .1 Perform Work in accordance with National Building Code of Canada (NBC) including amendments up to tender closing date and other codes of provincial or local application provided that in case of conflict or discrepancy, more stringent requirements apply.
- .2 Meet or exceed requirements of:
 - .1 Contract documents.
 - .2 Specified standards, codes and referenced documents.

1.2 HAZARDOUS MATERIAL DISCOVERY

- .1 Asbestos: demolition of spray or trowel-applied asbestos is hazardous to health. Stop work immediately when material resembling spray or trowel-applied asbestos is encountered during demolition work. Notify Departmental Representative.
- .2 PCB: Polychlorinated Biphenyl: stop work immediately when material resembling Polychlorinated Biphenyl is encountered during demolition work. Notify Departmental Representative.
- .3 Mould: stop work immediately when material resembling mould is encountered during demolition work. Notify Departmental Representative.
- .4 Notify Departmental Representative if suspicious material is encountered elsewhere within this work.

1.3 BUILDING SMOKING ENVIRONMENT

- .1 Comply with smoking restrictions and municipal by-laws.
- .2 Smoking is not permitted in or around the building. Smoking is allowed only in areas indicated by Departmental Representative.

END OF SECTION

Part 1 General

1.1 INSPECTION

- .1 Allow Departmental Representative access to Work. If part of Work is in preparation at locations other than Place of Work, allow access to such Work whenever it is in progress.
- .2 Give timely notice requesting inspection if Work is designated for special tests, inspections or approvals by Departmental Representative instructions, or law of Place of Work.
- .3 If Contractor covers or permits to be covered Work that has been designated for special tests, inspections or approvals before such is made, uncover such Work, have inspections or tests satisfactorily completed and make good such Work.
- .4 Departmental Representative will order part of Work to be examined if Work is suspected to be not in accordance with Contract Documents. If, upon examination such work is found not in accordance with Contract Documents, correct such Work and pay cost of examination and correction. If such Work is found in accordance with Contract Documents, Departmental Representative shall pay cost of examination and replacement.

1.2 ACCESS TO WORK

- .1 Allow inspection/testing agencies access to Work, off site manufacturing and fabrication plants.
- .2 Co-operate to provide reasonable facilities for such access.

1.3 PROCEDURES

- .1 Notify appropriate agency and Departmental Representative in advance of requirement for tests, in order that attendance arrangements can be made.
- .2 Submit samples and/or materials required for testing, as specifically requested in specifications. Submit with reasonable promptness and in orderly sequence to not cause delays in Work.
- .3 Provide labour and facilities to obtain and handle samples and materials on site. Provide sufficient space to store and cure test samples.

1.4 REJECTED WORK

- .1 Remove defective Work, whether result of poor workmanship, use of defective products or damage and whether incorporated in Work or not, which has been rejected by Departmental Representative as failing to conform to Contract Documents. Replace or re-execute in accordance with Contract Documents.
- .2 Make good other Contractor's work damaged by such removals or replacements promptly.
- .3 If in opinion of Departmental Representative, it is not expedient to correct defective Work or Work not performed in accordance with Contract Documents, Departmental Representative will deduct from Contract Price difference in value between Work

performed and that called for by Contract Documents, amount of which will be determined by Departmental Representative.

1.5 REPORTS

- .1 Submit 2 copies of inspection and test reports to Departmental Representative.
- .2 Provide copies to subcontractor of work being inspected or tested and manufacturer or fabricator of material being inspected or tested.

1.6 TESTS AND MIX DESIGNS

- .1 Furnish test results and mix designs as requested.
- .2 Cost of tests and mix designs beyond those called for in Contract Documents or beyond those required by law of Place of Work will be appraised by Departmental Representative and may be authorized as recoverable.

1.7 MOCK-UPS

- .1 Prepare mock-ups for Work specifically requested in specifications. Include for Work of Sections required to provide mock-ups.
- .2 Construct in locations acceptable to Departmental Representative.
- .3 Prepare mock-ups for Departmental Representative review with reasonable promptness and in orderly sequence, to not cause delays in Work.
- .4 Failure to prepare mock-ups in ample time is not considered sufficient reason for extension of Contract Time and no claim for extension by reason of such default will be allowed.
- .5 Specification section identifies whether mock-up may remain as part of Work or if it is to be removed and when.

1.8 EQUIPMENT AND SYSTEMS

- .1 Submit adjustment and balancing reports for mechanical, electrical, and building equipment systems.

END OF SECTION

Part 1 General

1.1 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00 - Submittal Procedures.

1.2 INSTALLATION AND REMOVAL

- .1 Provide temporary utilities controls to execute work expeditiously.
- .2 Remove from site all such work after use.

1.3 WATER SUPPLY

- .1 Departmental Representative will provide continuous supply of potable water for construction use.
- .2 Departmental Representative has the right to limit water usage if it is deemed that excessive amounts of water is being used.

1.4 TEMPORARY HEATING AND VENTILATION

- .1 Provide temporary heating required during construction period, including attendance, maintenance, and fuel.
- .2 Construction heaters used inside building must be vented to outside or be non-flameless type. Solid fuel salamanders are not permitted.
- .3 Provide temporary heat and ventilation in enclosed areas as required to:
 - .1 Facilitate progress of Work.
 - .2 Protect Work and products against dampness and cold.
 - .3 Prevent moisture condensation on surfaces.
 - .4 Provide ambient temperatures and humidity levels for storage, installation and curing of materials.
 - .5 Provide adequate ventilation to meet health regulations for safe working environment.
- .4 Maintain temperatures of minimum 10 degrees C in areas where construction is in progress.
- .5 Ventilating:
 - .1 Prevent accumulation of dust, fumes, mists, vapours and gases in areas occupied during construction.
 - .2 Provide local exhaust ventilation to prevent harmful accumulation of hazardous substances into atmosphere of occupied areas.
 - .3 Dispose of exhaust materials in manner that will not result in harmful exposure to persons.
 - .4 Ventilate storage spaces containing hazardous or volatile materials.
 - .5 Ventilate temporary sanitary facilities.

- .6 Continue operation of ventilation and exhaust system for time after cessation of work process to assure removal of harmful contaminants.
- .6 Maintain strict supervision of operation of temporary heating and ventilating equipment to:
 - .1 Conform with applicable codes and standards.
 - .2 Enforce safe practices.
 - .3 Prevent abuse of services.
 - .4 Prevent damage to finishes.
 - .5 Vent direct-fired combustion units to outside.
- .7 Be responsible for damage to Work due to failure in providing adequate heat and protection during construction.

1.5 TEMPORARY POWER AND LIGHT

- .1 Provide and maintain temporary lighting throughout project.
- .2 Existing power systems, located within the crawlspace and on the perimeter of the building, may be utilized. Existing power systems within occupied spaces will not be allowed for temporary connections.
- .3 Departmental Representative has the right to limit power usage if it is deemed that excessive amounts of power is being used.

1.6 TEMPORARY COMMUNICATION FACILITIES

- .1 Provide and pay for temporary telephone, fax, data hook up, and line equipment necessary for own use and use of Departmental Representative.

1.7 FIRE PROTECTION

- .1 Provide and maintain temporary fire protection equipment during performance of Work required by Authorities Having Jurisdiction and governing codes, regulations and bylaws.
- .2 Burning rubbish and construction waste materials is not permitted on site.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 Canadian Standards Association (CSA International)
 - .1 CAN/CSA-S269.2-M1987(R2003), Access Scaffolding for Construction Purposes.
 - .2 CAN/CSA-Z321-96(R2001), Signs and Symbols for the Occupational Environment.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00 - Submittal Procedures.

1.3 INSTALLATION AND REMOVAL

- .1 Prepare site plan indicating proposed location and dimensions of area to be fenced and used by Contractor, number of trailers to be used, avenues of ingress/egress to fenced area and details of fence installation.
- .2 Identify areas which have to be gravelled to prevent tracking of mud.
- .3 Indicate use of supplemental or other staging area.
- .4 Provide construction facilities to execute work expeditiously.
- .5 Remove from site all such work after use.

1.4 BRIDGING

- .1 Construct temporary bridges over excavations to allow for access of public and occupants to enter and exit building at all doorways. Provide guardrails to meet requirements of Occupational Health and Safety at all drops of over 600mm.

1.5 SCAFFOLDING

- .1 Scaffolding in accordance with CAN/CSA-S269.2.
- .2 Provide and maintain scaffolding and ladders.

1.6 SITE STORAGE/LOADING

- .1 Confine work and operations of employees by Contract Documents. Do not unreasonably encumber premises with products.
- .2 Do not load or permit to load any part of Work with weight or force that will endanger Work.

1.7 HOISTING

- .1 Provide, operate and maintain hoists required for moving of workers, materials and equipment. Make financial arrangements with Subcontractors for their use of hoists.
- .2 Hoists to be operated by qualified operator.

1.8 SITE STORAGE/LOADING

- .1 Confine work and operations of employees by Contract Documents. Do not unreasonably encumber premises with products.
- .2 Do not load or permit to load any part of Work with weight or force that will endanger Work.

1.9 CONSTRUCTION PARKING

- .1 Parking may be permitted on site but may also be limited. Parking arrangements will be reviewed with Departmental Representative at project start up.
- .2 Provide and maintain adequate access to project site.

1.10 SECURITY

- .1 Provide and pay for responsible security personnel to guard site and contents of site after working hours and during holidays.

1.11 OFFICES

- .1 Provide and maintain, during the entire progress of the Work, a suitable office on the site, for own use, with suitable tables or benches for the examination of drawings, specifications, etc., and where all notices and instructions from the Consultant may be received and acknowledged. Provide suitable meeting space for site meetings. Provide adequate heating, ventilating and lighting. Maintain in clean condition. Location of these offices to be coordinated with the Departmental Representative.
- .2 Provide marked and fully stocked first-aid case in a readily available location.

1.12 EQUIPMENT, TOOL AND MATERIALS STORAGE

- .1 Provide and maintain, in clean and orderly condition, lockable weatherproof sheds for storage of tools, equipment and materials.
- .2 Locate materials not required to be stored in weatherproof sheds on site in manner to cause least interference with work activities.

1.13 SANITARY FACILITIES

- .1 Provide sanitary facilities for work force in accordance with governing regulations and ordinances.
- .2 Post notices and take precautions as required by local health authorities. Keep area and premises in sanitary condition.
- .3 Contractor shall be responsible for cleaning and maintenance of designated facilities.

1.14 CONSTRUCTION SIGNAGE

- .1 Provide and erect construction safety signs.
- .2 No other signs or advertisements, other than warning signs, are permitted on site.
- .3 Signs and notices for safety and instruction in both official languages. Graphic symbols in accordance with CAN/CSA-Z321.

- .4 Maintain approved signs and notices in good condition for duration of project and dispose of off site on completion of project or earlier if directed by Departmental Representative.

1.15 PROTECTION AND MAINTENANCE OF TRAFFIC

- .1 Maintain and protect traffic on affected roads during construction period except as otherwise specifically directed by Departmental Representative.
- .2 Provide measures for protection and diversion of traffic, including provision of watch-persons and flag-persons, erection of barricades, placing of lights around and in front of equipment and work, and erection and maintenance of adequate warning, danger, and direction signs
- .3 Protect travelling public from damage to person and property.
- .4 Contractor's traffic on roads selected for hauling material to and from site to interfere as little as possible with public traffic.
- .5 Verify adequacy of existing roads and allowable load limit on these roads. Contractor: responsible for repair of damage to roads caused by construction operations.
- .6 Provide necessary lighting, signs, barricades, and distinctive markings for safe movement of traffic.
- .7 Dust control: adequate to ensure safe operation at all times.
- .8 Provide snow removal during period of Work.

1.16 CLEAN-UP

- .1 Remove construction debris, waste materials, packaging material from work site daily.
- .2 Clean dirt or mud tracked onto paved or surfaced roadways.
- .3 Store materials resulting from demolition activities that are salvageable.
- .4 Stack stored new or salvaged material not in construction facilities.

Part 2 Products

2.1 NOT USED

- .1 Not Used.

Part 3 Execution

3.1 TEMPORARY EROSION AND SEDIMENTATION CONTROL

- .1 Provide temporary erosion and sedimentation control measures to prevent soil erosion and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways, according to requirements of authorities having jurisdiction.
- .2 Inspect, repair, and maintain erosion and sedimentation control measures during construction until permanent vegetation has been established.

- .3 Remove erosion and sedimentation controls and restore and stabilize areas disturbed during removal.

END OF SECTION

Part 1 General

1.1 INSTALLATION AND REMOVAL

- .1 Provide temporary controls to execute Work expeditiously.
- .2 Remove from site all such work after use.

1.2 HOARDING

- .1 Erect temporary site enclosures using 2.44m high chainlink fence with steel posts spaced at maximum 2.4m on centre. Maintain fence in good repair.
- .2 Provide one lockable truck entrance gate and at least one pedestrian door as directed and conforming to applicable traffic restrictions on adjacent streets. Equip gates with locks and keys.

1.3 GUARD RAILS AND BARRICADES

- .1 Provide as indicated and as required by governing authorities.

1.4 WEATHER ENCLOSURES

- .1 Provide weather tight closures to unfinished openings, trench openings, tops of shafts and other openings in the building.
- .2 Close off floor areas where walls are not finished; seal off other openings; enclose building interior work for temporary heat.
- .3 Design enclosures to withstand wind pressure and snow loading.

1.5 DUST TIGHT SCREENS

- .1 Provide dust tight screens or insulated partitions to localize dust and dirt generating activities, and for protection of workers, finished areas of Work and public.
- .2 Maintain and relocate protection until such work is complete.

1.6 ACCESS TO SITE

- .1 Provide and maintain access roads, sidewalk crossings, ramps and construction runways as may be required for access to Work.

1.7 PUBLIC TRAFFIC FLOW

- .1 Provide and maintain competent signal flag operators, traffic signals, barricades and flares, lights, or lanterns as required to perform Work and protect public.

1.8 FIRE ROUTES

- .1 Maintain access to property including overhead clearances for use by emergency response vehicles.

1.9 PROTECTION FOR OFF-SITE AND PUBLIC PROPERTY

- .1 Protect surrounding private and public property from damage during performance of Work.
- .2 Be responsible for damage incurred.

1.10 PROTECTION OF BUILDING FINISHES

- .1 Provide protection for finished and partially finished building finishes and equipment during performance of Work.
- .2 Provide necessary screens, covers, and hoardings.
- .3 Confirm with Departmental Representative locations and installation schedule 3 days prior to installation.
- .4 Be responsible for damage incurred due to lack of or improper protection.

1.11 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 Within text of each specification section, reference may be made to reference standards.
- .2 Conform to these reference standards, in whole or in part as specifically requested in specifications.
- .3 If there is question as to whether products or systems are in conformance with applicable standards, Departmental Representative reserves right to have such products or systems tested to prove or disprove conformance.
- .4 Cost for such testing will be born by Departmental Representative in event of conformance with Contract Documents or by Contractor in event of non-conformance.

1.2 QUALITY

- .1 Products, materials, equipment and articles incorporated in Work shall be new, not damaged or defective, and of best quality for purpose intended. If requested, furnish evidence as to type, source and quality of products provided.
- .2 Procurement policy is to acquire, in cost effective manner, items containing highest percentage of recycled and recovered materials practicable consistent with maintaining satisfactory levels of competition. Make reasonable efforts to use recycled and recovered materials and in otherwise utilizing recycled and recovered materials in execution of work.
- .3 Defective products, whenever identified prior to completion of Work, will be rejected, regardless of previous inspections. Inspection does not relieve responsibility but is precaution against oversight or error. Remove and replace defective products at own expense and be responsible for delays and expenses caused by rejection.
- .4 Should disputes arise as to quality or fitness of products, decision rests strictly with Departmental Representative based upon requirements of Contract Documents.
- .5 Unless otherwise indicated in specifications, maintain uniformity of manufacture for any particular or like item throughout building.
- .6 Permanent labels, trademarks and nameplates on products are not acceptable in prominent locations, except where required for operating instructions, or when located in mechanical or electrical rooms.

1.3 AVAILABILITY

- .1 Immediately upon signing Contract, review product delivery requirements and anticipate foreseeable supply delays for items. If delays in supply of products are foreseeable, notify Departmental Representative of such, in order that substitutions or other remedial action may be authorized in ample time to prevent delay in performance of Work.
- .2 In event of failure to notify Departmental Representative at commencement of Work and should it subsequently appear that Work may be delayed for such reason, Departmental Representative reserves right to substitute more readily available products of similar character, at no increase in Contract Price or Contract Time.

1.4 STORAGE, HANDLING AND PROTECTION

- .1 Handle and store products in manner to prevent damage, adulteration, deterioration and soiling and in accordance with manufacturer's instructions when applicable.
- .2 Store packaged or bundled products in original and undamaged condition with manufacturer's seal and labels intact. Do not remove from packaging or bundling until required in Work.
- .3 Store products subject to damage from weather in weatherproof enclosures.
- .4 Store cementitious products clear of earth or concrete floors, and away from walls.
- .5 Keep sand, when used for grout or mortar materials, clean and dry. Store sand on wooden platforms and cover with waterproof tarpaulins during inclement weather.
- .6 Store sheet materials, lumber, steel members, and flahings on flat, solid supports and keep clear of ground. Slope to shed moisture.
- .7 Remove and replace damaged products at own expense and to satisfaction of Departmental Representative.
- .8 Touch-up damaged factory finished surfaces to Departmental Representative's satisfaction. Use touch-up materials to match original. Do not paint over name plates.

1.5 TRANSPORTATION

- .1 Pay costs of transportation of products required in performance of Work.

1.6 MANUFACTURER'S INSTRUCTIONS

- .1 Unless otherwise indicated in specifications, install or erect products in accordance with manufacturer's instructions. Do not rely on labels or enclosures provided with products. Obtain written instructions directly from manufacturers.
- .2 Notify Departmental Representative in writing, of conflicts between specifications and manufacturer's instructions, so that Departmental Representative will establish course of action.
- .3 Improper installation or erection of products, due to failure in complying with these requirements, authorizes Departmental Representative to require removal and re-installation at no increase in Contract Price or Contract Time.

1.7 QUALITY OF WORK

- .1 Ensure Quality of Work is of highest standard, executed by workers experienced and skilled in respective duties for which they are employed. Immediately Departmental Representative if required Work is such as to make it impractical to produce required results.
- .2 Do not employ anyone unskilled in their required duties. Departmental Representative reserves right to require dismissal from site, workers deemed incompetent or careless.
- .3 Decisions as to standard or fitness of Quality of Work in cases of dispute rest solely with Departmental Representative, whose decision is final.

1.8 CO-ORDINATION

- .1 Ensure co-operation of workers in laying out Work. Maintain efficient and continuous supervision.
- .2 Be responsible for coordination and placement of openings, sleeves and accessories.

1.9 CONCEALMENT

- .1 In finished areas conceal pipes, ducts and wiring, except where indicated otherwise.
- .2 Before installation inform Departmental Representative if there is interference. Install as directed by Departmental Representative.

1.10 REMEDIAL WORK

- .1 Perform remedial work required to repair or replace parts or portions of Work identified as defective or unacceptable. Co-ordinate adjacent affected Work as required.
- .2 Perform remedial work by specialists familiar with materials affected. Perform in a manner to neither damage nor put at risk any portion of Work.

1.11 LOCATION OF FIXTURES

- .1 Consider location of fixtures, outlets, and mechanical and electrical items indicated as approximate.
- .2 Inform Departmental Representative of conflicting installation. Install as directed.

1.12 FASTENINGS

- .1 Provide metal fastenings and accessories in same texture, colour and finish as adjacent materials, unless indicated otherwise.
- .2 Prevent electrolytic action between dissimilar metals and materials.
- .3 Use non-corrosive hot dip galvanized steel fasteners and anchors for securing exterior work, unless stainless steel or other material is specifically requested in affected specification Section.
- .4 Space anchors within individual load limit or shear capacity and ensure they provide positive permanent anchorage. Wood, or any other organic material plugs are not acceptable.
- .5 Keep exposed fastenings to a minimum, space evenly and install neatly.
- .6 Fastenings which cause spalling or cracking of material to which anchorage is made are not acceptable.

1.13 FASTENINGS - EQUIPMENT

- .1 Use fastenings of standard commercial sizes and patterns with material and finish suitable for service.
- .2 Use heavy hexagon heads, semi-finished unless otherwise specified. Use No. 304 stainless steel for exterior areas.
- .3 Bolts may not project more than one diameter beyond nuts.

- .4 Use plain type washers on equipment, sheet metal and soft gasket lock type washers where vibrations occur. Use resilient washers with stainless steel.

1.14 PROTECTION OF WORK IN PROGRESS

- .1 Prevent overloading of parts of building. Do not cut, drill or sleeve load bearing structural member, unless specifically indicated without written approval Departmental Representative.

1.15 EXISTING UTILITIES

- .1 When breaking into or connecting to existing services or utilities, execute Work at times directed by local governing authorities, with minimum of disturbance to Work, and/or building occupants.
- .2 Protect, relocate or maintain existing active services. When services are encountered, cap off in manner approved by authority having jurisdiction. Stake and record location of capped service.

END OF SECTION

Part 1 General

1.1 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submittals: in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Submit written request in advance of cutting or alteration which affects:
 - .1 Structural integrity of elements of project.
 - .2 Integrity of weather-exposed or moisture-resistant elements.
 - .3 Efficiency, maintenance, or safety of operational elements.
 - .4 Visual qualities of sight-exposed elements.
 - .5 Work of Departmental Representative or separate contractor.
- .3 Include in request:
 - .1 Identification of project.
 - .2 Location and description of affected Work.
 - .3 Statement on necessity for cutting or alteration.
 - .4 Description of proposed Work, and products to be used.
 - .5 Alternatives to cutting and patching.
 - .6 Effect on Work of Departmental Representative or separate contractor.
 - .7 Written permission of affected separate contractor.
 - .8 Date and time work will be executed.

1.2 FORMS

- .1 Special forms required during the course of this Work include, but are not limited to, the following:
 - .1 Building permit.
 - .2 Hot work.
 - .3 Confined space entry.
 - .4 Fire watch plan.
 - .5 Detailed work plan.

1.3 MATERIALS

- .1 Required for original installation.
- .2 Change in Materials: Submit request for substitution in accordance with Section 01 33 00 - Submittal Procedures.

1.4 PREPARATION

- .1 Inspect existing conditions, including elements subject to damage or movement during cutting and patching.
- .2 After uncovering, inspect conditions affecting performance of Work.

- .3 Beginning of cutting or patching means acceptance of existing conditions.
- .4 Provide supports to assure structural integrity of surroundings; provide devices and methods to protect other portions of project from damage.
- .5 Provide protection from elements for areas which are to be exposed by uncovering work; maintain excavations free of water.

1.5 EXECUTION

- .1 Execute cutting, fitting, and patching to complete Work.
- .2 Fit several parts together, to integrate with other Work.
- .3 Uncover Work to install ill-timed Work.
- .4 Remove and replace defective and non-conforming Work.
- .5 Provide openings in non-structural elements of Work for penetrations of mechanical and electrical Work.
- .6 Execute Work by methods to avoid damage to other Work, and which will provide proper surfaces to receive patching and finishing.
- .7 Employ original installer to perform cutting and patching for weather-exposed and moisture-resistant elements, and sight-exposed surfaces.
- .8 Cut rigid materials using masonry saw or core drill. Pneumatic or impact tools not allowed on masonry work without prior approval.
- .9 Restore work with new products in accordance with requirements of Contract Documents.
- .10 Fit Work to pipes, sleeves, ducts, conduit, and other penetrations through surfaces.
- .11 At penetration of fire rated wall, ceiling, or floor construction, completely seal voids with firestopping material in accordance with Section 07 84 00 - Firestopping, full thickness of the construction element.
- .12 Refinish surfaces to match adjacent finishes: Refinish continuous surfaces to nearest intersection. Refinish assemblies by refinishing entire unit.
- .13 Conceal pipes, ducts and wiring in floor, wall and ceiling construction of finished areas except where indicated otherwise.

1.6 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 Maintain Work in tidy condition, free from accumulation of waste products and debris, other than that caused by Departmental Representative or other Contractors.
- .2 Remove waste materials from site at daily regularly scheduled times or dispose of as directed by Departmental Representative. Do not burn waste materials on site.
- .3 Clear snow and ice from access to building, bank/pile snow in designated areas only.
- .4 Make arrangements with and obtain permits from authorities having jurisdiction for disposal of waste and debris.
- .5 Provide on-site containers for collection of waste materials, debris, and recycling.
- .6 Provide and use marked separate bins for recycling. Refer to Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
- .7 Dispose of waste materials and debris off site.
- .8 Clean interior areas prior to start of finishing work and maintain areas free of dust and other contaminants during finishing operations.
- .9 Store volatile waste in covered metal containers and remove from premises at end of each working day.
- .10 Provide adequate ventilation during use of volatile or noxious substances. Use of building ventilation systems is not permitted for this purpose.
- .11 Use only cleaning materials recommended by manufacturer of surface to be cleaned, and as recommended by cleaning material manufacturer.
- .12 Schedule cleaning operations so that resulting dust, debris, and other contaminants will not fall on wet, newly painted surfaces nor contaminate building systems.

1.2 FINAL CLEANING

- .1 When Work is Substantially Performed remove surplus products, tools, construction machinery, and equipment not required for performance of remaining Work.
- .2 Remove waste products and debris other than that caused by others and leave Work clean and suitable for occupancy.
- .3 Prior to final review remove surplus products, tools, construction machinery, and equipment.
- .4 Remove waste products and debris other than that caused by Departmental Representative or other Contractors.
- .5 Remove waste materials from site at regularly scheduled times or dispose of as directed by Departmental Representative. Do not burn waste materials on site.
- .6 Make arrangements with and obtain permits from authorities having jurisdiction for disposal of waste and debris.

- .7 Inspect finishes, fitments and equipment and ensure specified workmanship and operation.
- .8 Broom clean and wash exterior walks, steps and surfaces; rake clean other surfaces of grounds.
- .9 Remove dirt and other disfiguration from exterior surfaces.
- .10 Sweep and wash clean paved areas.
- .11 Clean equipment and fixtures to sanitary condition; clean or replace filters of mechanical equipment.
- .12 Remove debris and surplus materials from crawl areas, excavations, and other accessible concealed spaces.
- .13 Remove snow and ice from access to building.

1.3 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.

END OF SECTION

Part 1 General

1.1 WASTE MANAGEMENT GOALS

- .1 Minimize amount of non-hazardous solid waste generated by project and accomplish maximum source reduction, reuse and recycling of solid waste produced by activities.
- .2 Protect the environment and prevent environmental pollution damage.

1.2 DEFINITIONS

- .1 Recyclable: ability of product or material to be recovered at end of its life cycle and re-manufactured into new product for reuse.
- .2 Recycle: process by which waste and recyclable materials are transformed or collected for purpose of being transferred into new products.
- .3 Recycling: process of sorting, cleansing, treating and reconstituting solid waste and other discarded materials for purpose of using in altered form. Recycling does not include burning, incinerating, or thermally destroying waste.
- .4 Reuse: repeated use of product in same form but not necessarily for same purpose. Reuse includes:
 - .1 Salvaging reusable materials from re-modelling projects, before demolition stage, for resale, reuse on current project or for storage for use on future projects.
 - .2 Returning reusable items including pallets or unused products to vendors.
- .5 Salvage: removal of structural and non-structural materials from deconstruction/disassembly projects for purpose of reuse or recycling.
- .6 Separate Condition: refers to waste sorted into individual types.
- .7 Source Separation: act of keeping different types of waste materials separate beginning from the point they became waste.

1.3 USE OF SITE AND FACILITIES

- .1 Execute Work with minimal interference and disturbance to normal use of premises.
- .2 Maintain security measures established by facility provide temporary security measures approved by Departmental Representative.

1.4 STORAGE, HANDLING AND PROTECTION

- .1 Store, materials to be reused, recycled and salvaged in locations as directed by Departmental Representative.
- .2 Unless specified otherwise, materials for removal become Contractor's property. Verify with Departmental Representative.
- .3 Separate non-salvageable materials from salvaged items. Transport and deliver non-salvageable items to licensed disposal facility.
- .4 Protect structural components not removed and salvaged materials from movement or damage.

- .5 Provide on-site facilities and containers for collection and storage of reusable and recyclable materials.
- .6 Separate and store materials produced during project in designated areas.
- .7 Prevent contamination of materials to be salvaged and recycled and handle materials in accordance with requirements for acceptance by designated processing facilities.
 - .1 On-site source separation is recommended.
 - .2 Remove co-mingled materials to off site processing facility for separation.

1.5 DISPOSAL OF WASTES

- .1 Do not bury rubbish or waste materials.
- .2 Do not dispose of oil, mineral spirits, volatile materials, waste, and paint thinner into waterways, storm, or sanitary sewers.

1.6 SCHEDULING

- .1 Co-ordinate Work with other activities at site to ensure timely and orderly progress of Work.

Part 2 Products

2.1 NOT USED

- .1 Not Used.

Part 3 Execution

3.1 APPLICATION

- .1 Handle waste materials not reused, salvaged, or recycled in accordance with appropriate regulations and codes.

3.2 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.
 - .2 Source separate materials to be reused/recycled into specified sort areas.

END OF SECTION

Part 1 General

1.1 ADMINISTRATIVE REQUIREMENTS

- .1 Acceptance of Work Procedures:
 - .1 Contractor's Inspection: Contractor: conduct inspection of Work, identify deficiencies and defects, and repair as required to conform to Contract Documents.
 - .1 Notify Departmental Representative in writing of satisfactory completion of Contractor's inspection and submit verification that corrections have been made.
 - .2 Request Departmental Representative review.
 - .2 Departmental Representative Review:
 - .1 Departmental Representative and Contractor to review Work and identify defects and deficiencies.
 - .2 Contractor to correct Work as directed.
 - .3 Completion Tasks: submit written certificates in English that tasks have been performed as follows:
 - .1 Work: completed and inspected for compliance with Contract Documents.
 - .2 Defects: corrected and deficiencies completed.
 - .3 Equipment and systems: tested, balanced, adjusted, and fully operational.
 - .4 Certificates required by Fire Commissioner and Utility companies: submitted.
 - .5 Operation of systems: demonstrated to Departmental Representative's personnel.
 - .6 Commissioning of mechanical systems: completed in accordance with Departmental Representative.
 - .7 Work: complete and ready for final inspection.
 - .4 Final Inspection:
 - .1 When completion tasks are done, request final review of Work by Departmental Representative, and Contractor.
 - .2 When Work is incomplete according to Departmental Representative, complete outstanding items and request re-inspection.
- .5 Declaration of Substantial Performance: when Departmental Representative considers deficiencies and defects corrected and requirements of Contract substantially performed, make application for Certificate of Substantial Performance.
- .6 Commencement of Lien and Warranty Periods: date of Departmental Representative's acceptance of submitted declaration of Substantial Performance to be date for commencement for warranty period and commencement of lien period unless required otherwise by lien statute of Place of Work.

- .7 Final Payment:
 - .1 When Departmental Representative considers final deficiencies and defects corrected and requirements of Contract met, make application for final payment.
- .8 Payment of Holdback: after issuance of Certificate of Substantial Performance of Work, submit application for payment of holdback amount in accordance with contractual agreement.

1.2 FINAL CLEANING

- .1 Clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Remove surplus materials, excess materials, rubbish, tools and equipment.
- .2 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.

END OF SECTION

Part 1 General

1.1 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Prepare instructions and data using personnel experienced in maintenance and operation of described products.
- .3 Copy will be returned after final review, with Departmental Representative's comments.
- .4 Two weeks prior to Substantial Performance of the Work, submit to Departmental Representative, three final copies (2 hard copies and 1 electronic) of operating and maintenance manuals in English.
- .5 Provide spare parts, maintenance materials and special tools of same quality and manufacture as products provided in Work.
- .6 Provide evidence, if requested, for type, source and quality of products supplied.

1.2 FORMAT

- .1 Organize data as instructional manual.
- .2 Provide two (2) bound copies and one (1) PDF copy on 1 CD, DVD, or USB drive.
- .3 Binders: cloth, hard covered, 3 post expandable, loose leaf paper size 219 x 279 mm. Colour 'black' Provide two (2) copies.
- .4 CD or DVD: closed session format, write protected and free from errors and viruses.
- .5 USB Drive: portable data storage device, which includes flash memory and integrated USB interface.
- .6 When multiple binders and discs are used correlate data into related consistent groupings.
 - .1 Identify contents of each binder on spine.
- .7 Cover: identify each binder with type or printed title 'Project Record Documents'; list title of project and identify subject matter of contents. Lettering to be 'gold' colour.
- .8 Provide printed title on CD or DVD version to coincide with title on bound version.
- .9 Provide engraved tag, titled to coincide with title on bound version, secured to USB drive with connector ring.
- .10 Arrange content by systems, under Section numbers and sequence of Table of Contents.
- .11 Provide tabbed fly leaf for each separate product and system, with typed description of product and major component parts of equipment.
- .12 Text: manufacturer's printed data, or typewritten data.
- .13 Drawings: provide with reinforced punched binder tab.
 - .1 Bind in with text; fold larger drawings to size of text pages.

1.3 CONTENTS - PROJECT RECORD DOCUMENTS

- .1 Table of Contents for Each Volume: provide title of project;
 - .1 Date of submission; names.
 - .2 Addresses, and telephone numbers of Owner, Consultants, General Contractor, and Sub-Trades, with name of responsible parties.
 - .3 Schedule of products and systems, indexed to content of volume.
- .2 For each product or system:
 - .1 List names, addresses and telephone numbers of subcontractors and suppliers, including local source of supplies and replacement parts.
- .3 Shop Drawings: copies of submitted shop drawings, complete with reviewed stamps, comments, and mark-ups.
- .4 Product Data: mark each sheet to identify specific products and component parts, and data applicable to installation; delete inapplicable information.
- .5 Drawings: supplement product data to illustrate relations of component parts of equipment and systems, to show control and flow diagrams.
- .6 Typewritten Text: as required to supplement product data.
 - .1 Provide logical sequence of instructions for each procedure, incorporating manufacturer's instructions specified in Section 01 45 00 - Quality Control.
- .7 Training: refer to Section 01 79 00 - Demonstration and Training.

1.4 AS -BUILT DOCUMENTS AND SAMPLES

- .1 Maintain, in addition to requirements in General Conditions, at site for Departmental Representative one record copy of:
 - .1 Contract Drawings.
 - .2 Specifications.
 - .3 Addenda.
 - .4 Change Orders and other modifications to Contract.
 - .5 Supplemental Instructions.
 - .6 Request for Information submissions.
 - .7 Reviewed shop drawings, product data, and samples.
 - .8 Field test records.
 - .9 Inspection certificates.
 - .10 Manufacturer's certificates.
- .2 Store record documents and samples in field office apart from documents used for construction.
 - .1 Provide files, racks, and secure storage.
- .3 Label record documents and file in accordance with Section number listings in List of Contents of this Project Manual.
 - .1 Label each document "PROJECT RECORD" in neat, large, printed letters.

- .4 Maintain record documents in clean, dry and legible condition.
 - .1 Do not use record documents for construction purposes.
- .5 Keep record documents and samples available for inspection by Departmental Representative.

1.5 RECORDING INFORMATION ON PROJECT RECORD DOCUMENTS

- .1 Record information on set of drawings, and in copy of Project Manual.
- .2 Use felt tip marking pens, maintaining separate colours for each major system, for recording information.
- .3 Record information concurrently with construction progress.
 - .1 Do not conceal Work until required information is recorded.
- .4 Contract Drawings and shop drawings: mark each item to record actual construction, including:
 - .1 Measured depths of elements of foundation in relation to finish first floor datum.
 - .2 Measured horizontal and vertical locations of underground utilities and appurtenances, referenced to permanent surface improvements.
 - .3 Measured locations of internal utilities and appurtenances, referenced to visible and accessible features of construction.
 - .4 Field changes of dimension and detail.
 - .5 Changes made by change orders.
 - .6 Details not on original Contract Drawings.
 - .7 Referenced Standards to related shop drawings and modifications.
- .5 Specifications: mark each item to record actual construction, including:
 - .1 Manufacturer, trade name, and catalogue number of each product actually installed, particularly optional items and substitute items.
 - .2 Changes made by Addenda and change orders.
- .6 Other Documents: maintain manufacturer's certifications, inspection certifications, and field test records, required by individual specifications sections.
- .7 Provide digital photos for site records.

1.6 EQUIPMENT AND SYSTEMS

- .1 For each item of equipment and each system include description of unit or system, and component parts.
 - .1 Give function, normal operation characteristics and limiting conditions.
 - .2 Include performance curves, with engineering data and tests, and complete nomenclature and commercial number of replaceable parts.
- .2 Include installed colour coded wiring diagrams.
- .3 Operating Procedures: include start-up, break-in, and routine normal operating instructions and sequences.

- .1 Include regulation, control, stopping, shut-down, and emergency instructions.
- .2 Include summer, winter, and any special operating instructions.
- .4 Maintenance Requirements: include routine procedures and guide for trouble-shooting; disassembly, repair, and reassembly instructions; and alignment, adjusting, balancing, and checking instructions.
- .5 Provide servicing and lubrication schedule, and list of lubricants required.
- .6 Include manufacturer's printed operation and maintenance instructions.
- .7 Include sequence of operation by controls manufacturer.
- .8 Provide original manufacturer's parts list, illustrations, assembly drawings, and diagrams required for maintenance.
- .9 Provide installed control diagrams by controls manufacturer.
- .10 Provide Contractor's co-ordination drawings, with installed colour coded piping diagrams.
- .11 Provide list of original manufacturer's spare parts, current prices, and recommended quantities to be maintained in storage.
- .12 Include test reports as specified in Section 01 45 00- Quality Control.
- .13 Additional requirements: as specified in individual specification sections.

1.7 MATERIALS AND FINISHES

- .1 Building products, applied materials, and finishes: include product data, with catalogue number, size, composition, and colour and texture designations.
 - .1 Provide information for re-ordering custom manufactured products.
- .2 Instructions for cleaning agents and methods, precautions against detrimental agents and methods, and recommended schedule for cleaning and maintenance.
- .3 Moisture-protection and weather-exposed products: include manufacturer's recommendations for cleaning agents and methods, precautions against detrimental agents and methods, and recommended schedule for cleaning and maintenance.
- .4 Additional requirements: as specified in individual specifications sections.

1.8 MAINTENANCE MATERIALS

- .1 Spare Parts:
 - .1 Provide spare parts, in quantities specified in individual specification sections.
 - .2 Provide items of same manufacture and quality as items in Work.
 - .3 Deliver to location as directed; place and store.
 - .4 Receive and catalogue items.
 - .1 Submit inventory listing to Departmental Representative.
 - .2 Include approved listings in Maintenance Manual.
 - .5 Obtain receipt for delivered products and submit prior to final payment.

- .2 Extra Stock Materials:
 - .1 Provide maintenance and extra materials, in quantities specified in individual specification sections.
 - .2 Provide items of same manufacture and quality as items in Work.
 - .3 Deliver to location as directed; place and store.
 - .4 Receive and catalogue items.
 - .1 Submit inventory listing to Departmental Representative.
 - .2 Include approved listings in Maintenance Manual.
 - .5 Obtain receipt for delivered products and submit prior to final payment.
- .3 Special Tools:
 - .1 Provide special tools, in quantities specified in individual specification section.
 - .2 Provide items with tags identifying their associated function and equipment.
 - .3 Deliver to location as directed; place and store.
 - .4 Receive and catalogue items.
 - .1 Submit inventory listing to Departmental Representative.
 - .2 Include approved listings in Maintenance Manual.

1.9 PROGRESS PHOTOGRAPHS

- .1 Provide two (2) CDs, DVDs, or USB drives.
- .2 DVD or CD: closed session format, write protected and free from errors and viruses.
- .3 USB drive: portable data storage device, which includes flash memory and integrated USB interface.
- .4 Provide printed title on DVD/CD version to coincide with title on Operation and maintenance manuals.
- .5 Provide engraved tag, titled to coincide with title on bound version, secured to USB drive with connector ring.
- .6 Digital photographs shall be in jpg format.
- .7 Arrange contents chronologically by date photographs were taken.
- .8 Digital photographs stored on CD-ROM, DVD, or USB drive, shall be submitted with the Operation and Maintenance Manuals.

1.10 DELIVERY, STORAGE AND HANDLING

- .1 Store spare parts, maintenance materials, and special tools in manner to prevent damage or deterioration.
- .2 Store in original and undamaged condition with manufacturer's seal and labels intact.
- .3 Store components subject to damage from weather in weatherproof enclosures.
- .4 Store paints and freezable materials in a heated and ventilated room.
- .5 Remove and replace damaged products at own expense and for review by Departmental Representative.

1.11 WARRANTIES AND BONDS

- .1 Submit, warranty information made available during construction phase, to Departmental Representative.
- .2 Assemble approved information in binder, submit upon acceptance of work and organize binder as follows:
 - .1 Separate each warranty or bond with index tab sheets keyed to Table of Contents listing.
 - .2 List subcontractor, supplier, and manufacturer, with name, address, and telephone number of responsible principal.
 - .3 Obtain warranties and bonds, executed in duplicate by subcontractors, suppliers, and manufacturers, within ten days after completion of applicable item of work.
 - .4 Verify that documents are in proper form, contain full information, and are notarized.
 - .5 Retain warranties and bonds until time specified for submittal.
- .3 Except for items put into use with Departmental Representative's permission, leave date of beginning of time of warranty until Date of Substantial Performance is determined.
- .4 Conduct joint 10-month warranty inspection, measured from time of acceptance, by Departmental Representative.
- .5 Include information contained in warranty as follows:
 - .1 Roles and responsibilities of personnel associated with warranty process, including points of contact and telephone numbers within the organizations of Contractors, subcontractors, manufacturers or suppliers involved.
 - .2 Listing and status of delivery of Certificates of Warranty for extended warranty items.
 - .3 Provide list for each warranted equipment, item, feature of construction or system indicating:
 - .1 Name of item.
 - .2 Model and serial numbers.
 - .3 Location where installed.
 - .4 Name and phone numbers of manufacturers or suppliers.
 - .5 Names, addresses and telephone numbers of sources of spare parts.
 - .6 Warranties and terms of warranty: include one-year overall warranty of construction. Indicate items that have extended warranties and show separate warranty expiration dates.
 - .7 Cross-reference to warranty certificates as applicable.
 - .8 Starting point and duration of warranty period.
 - .9 Summary of maintenance procedures required to continue warranty in force.
 - .10 Cross-Reference to specific pertinent Operation and Maintenance manuals.
 - .11 Organization, names and phone numbers of persons to call for warranty service.

- .12 Typical response time and repair time expected for various warranted equipment.
- .4 Procedure and status of tagging of equipment covered by extended warranties.
- .5 Post copies of instructions near selected pieces of equipment where operation is critical for warranty and/or safety reasons.
- .6 Respond in timely manner to oral or written notification of required construction warranty repair work.
- .7 Written verification to follow oral instructions.
- .1 Failure to respond will be cause for the Departmental Representative to proceed with action against Contractor.

END OF SECTION

Part 1 General

1.1 ADMINISTRATIVE REQUIREMENTS

- .1 Demonstrate operation and maintenance of equipment and systems to Departmental Representative's personnel two weeks prior to date of substantial performance.
- .2 Departmental Representative: provide list of personnel to receive instructions, and co-ordinate their attendance at agreed-upon times.
- .3 Preparation:
 - .1 Verify conditions for demonstration and instructions comply with requirements.
 - .2 Verify designated personnel are present.
 - .3 Ensure equipment has been inspected and put into operation.
 - .4 Ensure testing, adjusting, and balancing has been performed and equipment and systems are fully operational.
- .4 Demonstration and Instructions:
 - .1 Demonstrate start-up, operation, control, adjustment, trouble-shooting, servicing, and maintenance of each item of equipment at scheduled times, at the equipment location.
 - .2 Instruct personnel in phases of operation and maintenance using operation and maintenance manuals as basis of instruction.
 - .3 Review contents of manual in detail to explain aspects of operation and maintenance.
 - .4 Prepare and insert additional data in operations and maintenance manuals when needed during instructions.
- .5 Time Allocated for Instructions: ensure amount of time required for instruction of each item of equipment or system.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Submit schedule of time and date for demonstration of each item of equipment and each system two weeks prior to designated dates, for Departmental Representative's approval.
- .3 Submit reports within one week after completion of demonstration, that demonstration and instructions have been satisfactorily completed.
- .4 Give time and date of each demonstration, with list of persons present.
- .5 Provide copies of completed operation and maintenance manuals for use in demonstrations and instructions.

1.3 QUALITY ASSURANCE

- .1 When specified in individual Sections requiring manufacturer to provide authorized representative to demonstrate operation of equipment and systems:
 - .1 Instruct Departmental Representative's personnel.

- .2 Provide written report that demonstration and instructions have been completed.
- .3 Provide sign-in sheet signed by the instructor and all attendees.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 CSA International
 - .1 CSA S350-M1980(R2003), Code of Practice for Safety in Demolition of Structures.
- .2 National Research Council Canada (NRC)
 - .1 National Building Code of Canada 2015 (NBC).
 - .2 National Fire Code of Canada 2015 (NFC).

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures and 01 74 21 - Construction/Demolition Waste Management Disposal.
- .2 Submit demolition drawings:
 - .1 Before proceeding with demolition of structure, removal of fill material adjacent to concrete piles, and where required by Authority Having Jurisdiction submit for review by Departmental Representative shoring drawings, prepared by qualified structural engineer registered in the Province of Saskatchewan in Canada, showing proposed method.
- .3 Sustainable Design Submittals:
 - .1 Construction Waste Management:
 - .1 Submit project Waste Reduction Workplan highlighting recycling and salvage requirements.
 - .2 Erosion and Sedimentation Control: submit erosion and sedimentation control plan in accordance with Authorities Having jurisdiction.

1.3 SITE CONDITIONS

- .1 Take precautions to protect environment.
- .2 If material resembling spray or trowel-applied asbestos or other designated substance listed as hazardous be encountered, stop work, take preventative measures, and notify Departmental Representative immediately.
 - .1 Proceed only after receipt of written instructions have been received from Departmental Representative.
- .3 Notify Departmental Representative before disrupting building access and services.

Part 2 Products

2.1 NOT USED

- .1 Not used.

Part 3 Execution

3.1 EXAMINATION

- .1 Inspect building and site with Departmental Representative and verify extent and location of items designated for removal, disposal, alternative disposal, recycling, salvage and items to remain.
- .2 Locate and protect utilities. Preserve active utilities traversing site in operating condition.
- .3 Notify and obtain approval of utility companies before starting demolition.
- .4 Disconnect, cap, plug or divert, as required, existing public utilities within the property where they interfere with the execution of the work, in conformity with the requirements of the authorities having jurisdiction. Mark the location of these and previously capped or plugged services on the site and indicate location (horizontal and vertical) on the record drawings. Support, shore up, and maintain pipes and conduits encountered.
 - .1 Immediately notify Departmental Representative and utility company concerned in case of damage to any utility or service, designated to remain in place.
 - .2 Immediately notify the Departmental Representative should uncharted utility or service be encountered and await instruction in writing regarding remedial action.
 - .3 Provide temporary signage notifying occupants when public utilities and associated spaces are unusable. Warning signs notifying closures are to be posted at least 48 hours prior to work commencing.

3.2 PREPARATION

- .1 Temporary Erosion and Sedimentation Control:
 - .1 Provide temporary erosion and sedimentation control measures to prevent soil erosion and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways, according to: requirements of authorities having jurisdiction.
 - .2 Inspect, repair, and maintain erosion and sedimentation control measures during demolition.
 - .3 Remove erosion and sedimentation controls and restore and stabilize areas disturbed during removal after completion of demolition work.
- .2 Protection of In-Place Conditions:
 - .1 Prevent movement, settlement, or damage to adjacent and landscaping features, structures, utilities, and parts of building to remain in place. Provide bracing and shoring required.
 - .2 Keep noise, dust, and inconvenience to occupants to minimum.
 - .3 Protect building systems, services and equipment.
 - .4 Provide temporary dust screens, covers, railings, supports and other protection as required.
 - .5 Do Work in accordance with Section 01 35 29.06 - Health and Safety Requirements.

- .3 Demolition/Removal:
 - .1 Remove items as indicated.
 - .2 Removal of pavement, concrete slab, soil, hard and soft landscaping.
 - .3 Removal of Pavement and concrete slab:
 - .1 Square up adjacent surfaces to remain in place by saw cutting or other method approved by Departmental Representative.
 - .2 Protect adjacent joints and load transfer devices.
 - .3 Protect underlying and adjacent granular materials.

3.3 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
- .3 Refer to demolition drawings and specifications for items to be salvaged for reuse.
- .4 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

END OF SECTION

Part 1 General

1.1 WORK INCLUDED

- .1 Form for all cast-in-place concrete indicated on drawings and subsequently remove all such forms.

1.2 DESIGN AND CODE REQUIREMENTS

- .1 Formwork and supporting falsework shall be designed and constructed in accordance with the requirements of CAN/CSA S269.3-M92 (R2013) and CAN/CSA A23.1-14 as applicable to the work.
- .2 Assume full responsibility for the design and for the adequacy and safety of all formwork and falsework.
- .3 The design and erection of formwork and related supporting works shall comply with construction safety legislation and regulations.

1.3 HANDLING AND STORAGE

- .1 Deliver, handle and store formwork materials to prevent weathering, warping or damage detrimental to the strength of the materials or to the surface to be formed.
- .2 Ensure that formwork surfaces which will be in contact with concrete are not contaminated by foreign matter. Handle and erect the fabricated formwork so as to prevent damage.

Part 2 Products

2.1 QUALITY AND STRENGTH

- .1 The quality and strength of formwork material shall comply with the requirements set forth in this Specification and CAN/CSA A23.1-14.

2.2 FINISHES

- .1 Form materials for concrete surfaces which will be exposed to view, or which require smooth and uniform surfaces for applied finishes or other purposes, shall consist of square edges, smooth panels of plywood, metal or plastic to approval of the Departmental Representative. The panels shall be square and made in a true plane, clean, free of holes, surface markings and defects.
- .2 Square edged, tongue and groove or shiplap lumber may be used to form concrete which will not be exposed to view or which does not require smooth uniform surface for other purposes.

2.3 MATERIALS

- .1 Form plywood: exterior grade, Douglas Fir conforming to CSA Standard O121-08. Plywood shall be resin coated one side (in contact with concrete). Use sound undamaged plywood with clean true edges. Make up or patching strips between panels shall be kept to a minimum.
- .2 Lumber for forms, falsework, shoring and bracing: conform to CAN/CSA O141-05 (R2014) for Softwood Lumber, and the applicable authorized grading authority. All lumber shall be a grade to which allowable unit stresses may be assigned in accordance with the National Building Code. All lumber shall be grade marked by the authorized grading authority.
- .3 Form Ties: Fabricated units having a minimum working strength when assembled of 21 MPa and shall be adjustable in lengths to permit tightening and alignment of forms. Ties shall be made with breakback ends or other means of removing the tie end to a depth of at least 25 mm from the concrete surface, after the forms are removed. Flat tie for Architectural exposed concrete to include plastic cones leaving no metal within 20 mm of surface.
- .4 Form release agent: Proprietary material which will not stain the concrete or impair the natural bonding or colour characteristics of coating intended for use on the concrete.
- .5 Tubular column forms: round spirally wound laminated fibre forms, internally treated with release material.
- .6 Dovetail anchor slots: minimum 0.6 mm galvanized steel with insulation filled slots.
- .7 Pre-moulded joint fillers:
 - .1 Bituminous impregnated fibreboard: ASTM D1751-7 (2013).
 - .2 Vinyl Foam: to ASTM D1752-04a (2013) Type I, flexible grade.
 - .3 Standard Cork: to ASTM D1752-04a (2013) Type II.

Part 3 Execution

3.1 CONDITION OF SURFACES

- .1 Examine the excavations and foundations for adequate working room and support for the work of this section.
- .2 Verify lines, levels and centre lines before proceeding with the work and ensure that dimensions agree with drawings.
- .3 Report to the Departmental Representative discrepancies in other work which affect the work of this section.

3.2 PREPARATION

- .1 Coat the inside surfaces of forms with a form release agent, used in accordance with the manufacturer's instructions.
- .2 Apply the agent prior to placing reinforcing steel, anchoring devices and embedded parts.

3.3 ASSEMBLY AND ERECTION

- .1 Construct the formwork and shoring and bracing to meet the design and code requirements, accurately so that the resultant finished concrete shall conform to the shapes, lines and dimensions shown on the drawings, within the specified tolerances.
- .2 Formwork shall be so arranged and assembled as to permit easy dismantling and stripping so that the concrete will not be damaged during its removal.
- .3 Review locations of ties and form panels for exposed concrete work with the Departmental Representative.
- .4 Check and correct formwork as required, both horizontally and vertically, during the placing of the concrete.
- .5 Construct formwork to maintain the following maximum tolerances:
 - .1 Deviation from horizontal and vertical lines:
6 mm in 3000 mm
20 mm in 12000 mm.
 - .2 Deviation of building dimensions indicated on Drawings and position of columns, walls and partitions:
6 mm.
 - .3 Deviation in cross sectional dimensions of columns or beams or in thickness of slabs and walls:
 ± 6 mm.
 - .4 Camber slabs and beams:
10 mm per 3000 mm of span unless indicated on drawings.

3.4 JOINTS IN FORMS

- .1 Make form joints tight in order to prevent leakage of mortar.
- .2 Clean all edges and contact surfaces before erection.
- .3 Where required, install pvc waterstop to manufacturer's instructions and without displacing reinforcement. Do not distort or pierce waterstop.

3.5 SHORING AND BRACING

- .1 Provide bracing to ensure the stability of the formwork as a whole.

- .2 Prop or strengthen all previously constructed parts liable to be overstressed by construction loads.
- .3 Arrange forms to allow stripping without removal of the principal shores, where these are required to remain in place.

3.6 EMBEDDED PARTS AND OPENINGS

- .1 Provide formed openings where required for pipes, conduit, sleeves and other work to be embedded in and passing through concrete members. Accurately locate and set in place items which are to be cast directly into the concrete. Co-ordinate the work of other sections and co-operate with the trade involved in the forming and setting of openings, slots, recesses, chases, sleeves, bolts, anchors and other inserts. No such forming or setting of openings, slots, recesses, chases, sleeves, or parts shall be done unless specifically shown on the drawings or approved prior to installation.
- .2 Provide temporary ports or openings where required to facilitate cleaning and inspection. Openings at the bottom of forms shall be located so that flushing water will drain from the forms.
- .3 Close the temporary ports or openings with tight fitting panels, flush with the inside face of the forms, neatly fitted so that the joints will not be apparent in exposed concrete surfaces.
- .4 Do not eliminate or displace reinforcement to accommodate hardware. If inserts cannot be located as specified, obtain approval in writing or all modifications from the Departmental Representative before placing concrete.

3.7 FIELD QUALITY CONTROL

- .1 Inspect and check the completed formwork, shoring and bracing to ensure that the work is in accordance with the formwork design, and that the supports, fastenings, wedges, ties and parts are secure. The Engineer responsible for the design of the formwork shall assist in this inspection.
- .2 Inform the Departmental Representative when the formwork is complete and has been cleaned. Obtain the approval of the engineer responsible for the design of the formwork and the general approval of the Departmental Representative before placing concrete.

3.8 CLEANING

- .1 Clean the forms as erection proceeds to remove foreign matter.
- .2 Remove cuttings, shavings and debris from within the forms.
- .3 Flush the completed forms with water or air jet to remove remaining foreign matter. Ensure that water and debris drain to the exterior through the clean-out ports.

3.9 WINTER CONSTRUCTION

- .1 Remove ice and snow from within the forms.
- .2 The use of de-icing salts will not be permitted.
- .3 Unless formwork and concrete construction proceed within a heated enclosure, do not use water to clean out completed forms. Use compressed air or other means to remove foreign matter.

3.10 REMOVAL OF FORMWORK

- .1 Notify the Departmental Representative before removing formwork.
- .2 Remove formwork progressively and in accordance with the reference code requirements, and so that no shock loads or imbalanced loads are imposed on the structure.
- .3 Do not remove forms and shoring before concrete has attained sufficient strength to ensure safety of structure. If evidence to verify concrete strength is not available, the forms and shores shall not be removed before the following minimum intervals after concrete is placed.
 - .1 Grade beams - 4 days.
 - .2 Slabs - 21 days.
- .4 Loosen forms carefully. Do not wedge pry bars, hammers or tools against concrete surfaces.
- .5 Leave forms loosely in place, against vertical surfaces, for protection until complete removal is approved by Departmental Representative.
- .6 Store removed forms, for exposed architectural concrete, in a manner that surfaces to be in contact with fresh concrete will not be damaged. Marked or scored forms will be rejected.
- .7 Re-shore structural members where required due to design requirements or construction conditions and as required to permit progressive construction.
- .8 Remove forms not directly supporting weight of concrete as soon as stripping operations will not damage concrete.
- .9 Re-use of formwork and falsework is subject to the requirements of CAN/CSA A23.1-14.

END OF SECTION

Part 1 General

1.1 WORK INCLUDED

- .1 Furnish and install all bonded reinforcement and associated items required and indicated on the Drawings for all cast-in-place concrete and reinforced masonry work.

1.2 INSPECTION AND TESTING

- .1 Upon request, provide certified copy of mill test report of steel supplied, showing physical and chemical analysis.

1.3 REFERENCE STANDARDS

- .1 Do reinforcing work in accordance with CSA A23.1-14 and welding of reinforcement with CSA W186-M1990 (R2007).

1.4 SUBMITTALS

- .1 Prepare, check and submit reinforcing steel and mesh placing drawings and bar bending and cutting schedules for all steel reinforcement shown or specified in accordance with Section 01 33 00 - Submittal Procedures.
- .2 All drawings and schedules shall be prepared and checked under the direct supervision of a qualified professional engineer who is experienced in this work.
- .3 Clearly indicate bar sizes, spacing, location and quantities of reinforcement, mesh, chairs, spacers and hangers with identifying code marks to permit correct placement without reference to structural drawings; to ACI - 315 Manual of Standard Practice and Metric Supplement 1977 by Reinforcing Steel Institute of Ontario.
- .4 Design and detail lap lengths and bar development lengths to CSA A23.3-14, unless specified on drawings.
- .5 Review of shop drawings for size and arrangement of principal and auxiliary members only. Such review will not relieve the Contractor of responsibility for general and detail dimension and fit, or any errors or omissions.

1.5 SUBSTITUTES

- .1 Substitution of different size bars permitted only upon written approval of the Departmental Representative.

1.6 DELIVERY AND STORAGE

- .1 Reinforcing steel, welded wire fabric and accessories shall be delivered, handled and stored in a manner which prevents contamination from bond reducing or foreign matter and damage to its fabricated form.

Part 2 Products

2.1 MATERIALS

- .1 *All reinforcing steel:* unless noted otherwise on the drawings or herein shall be deformed bars of new billet steel conforming to the current CAN/CSA G.30.18-09(R2014) Grade 400, plain finish for all bars. Minimum splice for 10 M bars to be 450 mm. Minimum lap splice for all other bars to be 36 bar diameters or 675 mm, whichever is greater.
- .2 *Weldable reinforcing bars:* high strength ductile, deformed bars to CAN/CSA G30.18-09 (R2014), Grade 400.
- .3 *Column ties and beam stirrups:* shall conform to the current CAN/CSA G30.18-09 (R2014), Grade 300.
- .4 *Welded wire fabric:* to CSA G30.5-M1983 (R1998). Provide in the flat sheets only.
- .5 *Tie wires:* shall be 1.29 mm or heavier annealed wire or a patented system approved by the Departmental Representative.
- .6 *Reinforcing steel supports:* shall conform to ACI Standard 315 unless otherwise approved by the Departmental Representative.
- .7 *Mechanical splices:* subject to the approval of the Departmental Representative.

2.2 FABRICATION

- .1 Fabricate bends, splices and ties and supply bar supports and accessories in accordance with the requirements of CAN-A23.3-14. Spacing and arrangements of supports in accordance with ACI 315.
- .2 All intermediate grade reinforcing bars shall be bent cold without hickeying. All high strength steel shall be preheated.
- .3 Reinforcing bars shall not be straightened or rebent.
- .4 Location of reinforcement splices not shown on the drawings subject to approval by the Consultant and shall, for beams and slabs be away from points of maximum stress in the steel.
- .5 *Welding of reinforcing bars:* use only weldable bars, preheat and weld to CSA W186-1990 (R2012).

Part 3 Execution

3.1 EXAMINATION

- .1 Examine the work upon which this section depends and report any discrepancies to the Consultant.
- .2 Commencement of the work shall imply acceptance of conditions.

3.2 PLACING

- .1 Reinforcement of the size and shapes shown on the drawings shall be accurately placed in accordance with the approved shop drawings, the structural drawings and the requirements of the current National Building Code.
- .2 Clear distances between parallel bars, except for columns, shall be not less than 1.4 times the diameter of the bar, or 30 mm or 1.4 times the maximum size of the coarse aggregate. Bars placed in two or more layers shall be placed directly above and below each other.
- .3 Clear distance between bars in columns shall be not less than 1.4 the nominal diameter of the bar or 40 mm or 1.4 times the maximum size of the coarse aggregate. Bars placed in two or more layers shall be placed directly above and below each other.
- .4 Reinforcing steel shall, where not otherwise shown on the structural drawings, be protected by the clear cover of concrete over the reinforcement as follows:
 - .1 Where concrete is formed against earth, not less than 75 mm.
 - .2 Where concrete placed against forms is to be exposed to the weather or be in contact with the ground, not less than 50 mm for bars larger than 15 M, and not less than 40 mm for bars 15 M and smaller.
 - .3 In slabs and walls not exposed to the ground or weather, not less than 20 mm.
 - .4 In beams, girders and columns not exposed to the ground or weather, not less than 40 mm to principal reinforcement, ties and stirrups.

The foregoing clear covers shall be maintained within 5 mm.

- .5 Reinforcement shall be adequately supported by metal chairs, spacers or hangers and secured against displacement within the tolerance permitted and in accordance with the latest ACI Standard 315.
- .6 For slabs on grade, footings or similar construction, concrete blocks may be used in place of metal chairs
- .7 Unless specifically detailed otherwise, all exterior slabs, walks and pads abutting building foundations to be dowelled with 15 M at 400 on centre, extending minimum 750 mm into slab.
- .8 Review with the Departmental Representative, placement of reinforcement prior to concreting.
- .9 Notify the Departmental Representative twenty-four (24) hours prior to placing concrete.

3.3 CLEANING

- .1 All materials shall be clean and free of all form oil or deleterious materials.
- .2 All deleterious material shall be removed from the surface of the reinforcing steel in a manner acceptable to the Consultant.

3.4

WELDING

- .1 Do welding to meet requirements of CSA W186-M1990 (R2012). Have welding performed by workmen qualified under CSA W47.1-09 (R2014). Welding only by written authority of the Departmental Representative.

END OF SECTION

Part 1 General

1.1 WORK INCLUDED

- .1 Cast-in-Place Concrete required for this work is indicated in drawings and includes, but is not necessarily limited to:
 - .1 Concrete Beams
 - .2 Concrete Slabs
 - .3 Miscellaneous Concrete
 - .4 Finishing of all Formed Concrete Surfaces

1.2 REFERENCES

- .1 American Society for Testing Materials International (ASTM)
 - .1 ASTM C260/C260M-10a, Standard Specification for Air-Entraining Admixtures for Concrete.
 - .2 ASTM C309-07, Standard Specification for Liquid Membrane-Forming Compounds for Curing Concrete.
 - .3 ASTM C494/C494M-08A, Standard Specification for Chemical Admixtures for Concrete.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB 51.34-M86, Vapour Barrier, Polyethylene Sheet for Use in Building Construction.
- .3 Canadian Standards Association (CSA)
 - .1 CSA A23.1-14/A23.2-14, Concrete Materials and Methods of Concrete Construction/Methods of Test for Concrete.
 - .2 CSA A23.3-04(R2010), Design of Concrete Structures.
 - .3 CSA A3000-13, Cementitious Materials Compendium.

1.3 QUALITY ASSURANCE

- .1 Provide at least one person who shall be present at all times during execution of this portion of the Work and who shall be thoroughly trained and experienced in placing the types of concrete specified and who shall direct all work performed under this Section.
- .2 For finishing of exposed surfaces of the concrete, use only thoroughly trained and experienced journeyman concrete finishers.
- .3 Perform cast-in-place concrete work to requirements of CSA-A23.1-14 - Concrete Materials and Methods of Concrete Construction.

1.4 PRODUCT HANDLING

- .1 Use all means necessary to protect cast-in-place concrete materials before, during and after installation and to protect the installed work and materials of all other trades.

- .2 In the event of damage, immediately make all repairs and replacements necessary to approval of the Departmental Representative and at no additional cost to the Departmental Representative.

1.5 INSPECTION AND TESTING

- .1 Inspection and testing will be performed by a firm approved by the Departmental Representative and paid for by the Contractor. Unless approved otherwise, the testing agency must perform all aspects of testing including cylinder preparation.
- .2 Provide free access to all portions of work and co-operate with appointed firm.
- .3 Submit proposed mix design for each class of concrete to Departmental Representative for review, two (2) weeks prior to commencement of work.
- .4 Tests of cement and aggregates may be performed to ensure conformance with requirements stated herein.
- .5 One concrete test, consisting of three test cylinders, will be taken for every 50 cubic meters or less of each class of concrete placed. One cylinder to be tested at seven (7) days, the remaining two cylinders to be tested at twenty-eight (28) days.
- .6 One (1) additional test cylinder will be taken during cold weather concreting and be cured on job site under same conditions of concrete it represents.
- .7 One (1) slump test and one (1) air content test will be taken for each set of test cylinders taken.
- .8 Testing of concrete will be performed in accordance with CSA-A23.2-14 - Method of Test for Concrete.
- .9 Test results will be issued to the Contractor, Consultant, and Departmental Representative. Test reports are to be numbered consecutively beginning with number one.
- .10 Required retesting will be paid for by the Contractor.
- .11 The Departmental Representative may order additional testing any time even though the required tests indicate the strength requirements have been met. In this instance, the Departmental Representative will pay for those tests that meet the specified requirements and the Contractor will pay for those that do not.
- .12 Non-destructive methods for testing concrete shall be according to CSA A23.2-14.

1.6 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.

Part 2 Products

2.1 CONCRETE MATERIALS

- .1 *Cement:* Normal - N and Sulphate Resistant - HS Portland Type, to CSA A3000 - "Portland Cements".

- .2 *Fine and Coarse Aggregates:* conforming to CSA-A23.1-14 - Concrete Materials and Methods of Concrete Construction. The fine and coarse aggregate for concrete floor slabs and finish toppings shall contain a maximum of 0.4% low density particles as determined by CSA Test A23.2-09 - Low Density Material in Aggregate. Test results shall be submitted to Departmental Representative for review.
- .3 *Water:* clean and free from injurious amounts of oil, alkali, organic matter, or other deleterious material.

2.2 ADMIXTURES

- .1 *Air Entrainment:* to ASTM C260-10 - Air-Entraining Admixtures for Concrete.
- .2 *Chemical:* to ASTM C494-15a - Chemical Admixtures for Concrete; water reducing, strength increasing type WN - normal setting.
- .3 *Pozzolan Mineral:* to CSA A3000-13 - Supplementary Cementing Materials and Their Use in Concrete Construction, fly ash permitted only as approved by Departmental Representative.

2.3 ACCESSORIES

- .1 *Vapour Barrier:* 6 mil polyethylene film, to CAN/CGSB 51.34, Type 1 - low permeance heavy duty.
- .2 *Curing Compounds:* shall conform to the requirements of the latest issue of ASTM Standard C309.
- .3 *Non-shrink Grout:* premixed compound consisting of non-metallic aggregate, cement, water reducing and plasticizing agents; capable of developing minimum compressive strength of 20 MPa at 3 days and 50 MPa at 28 days. CPD Non-Shrink Grout by CPD Construction Products or approved substitutions.
- .4 *Void Form: to comply with either of the following:*
 - .1 Biodegradable Void Form: biodegradable, 150 mm deep, structurally sufficient to support weight of wet concrete and other superimposed loads without collapsing until concrete has gained sufficient strength to support these loads after which time the form must promptly degrade. Do not wrap void form. Do not place void form on poly ground sheet. The onus is entirely on the Contractor and Supplier to ensure that the void form is installed to perform as intended.
 - .2 Compressible Void Form: GeoVoid (below slabs) or Geospan (below grade beams) compressible void form by Plasti-Fab designed for 150 mm soil heave, installed to supplier's specifications.
- .5 *Joint Filler:* pre-moulded bituminous impregnated cane fibre board Flexcell as manufactured by Sternson or approved substitution.
- .6 *Vertical Joint Sealant:* non-sag polyurethane sealant designed for use on vertical surfaces. Vulkem 116 as manufactured by Mameco Ltd. or approved equal. Install strictly in accordance with manufacturer's recommendations.
- .7 *Horizontal Joint Sealant:* three component chemically curing, self-levelling, polyurethane joint sealant, THC-900 as manufactured by Tremco or approved substitution. Colour selection by Departmental Representative. Install strictly in accordance with manufacturer's recommendations.

- .8 *Concrete Expansion Anchors:* to be Hilti Kwik-Bolt or approved equivalent. Sized as per drawings. Minimum embedment length of all Hilti Kwik-Bolt to be 150 mm unless noted otherwise.
- .9 *Concrete Inserts with Bolt Extension:* Concrete inserts to be Hilti HKD Anchors or approved equivalent, sized as detailed on drawings. Bolt extensions to be mild steel threaded extensions sized as detailed on drawings.
- .10 *Concrete Patching Material:* pre-packaged, polymer modified, cementitious product containing graded natural aggregate, EMACO R300 - Rapid Setting Mortar as manufactured by Master Builders or approved equivalent.
- .11 *Bonding Agent:* Approved high polymer polyvinyl acetate emulsion applied in strict accordance with manufacturer's recommendations for proposed application. Daraweld-C, Acrylbond by Allied or approved equal. Mix bonding agent with Portland cement, sand and water to manufacturer's recommendation to achieve an uniform slurry and scrubbed into the surface. Ensure surface is free from all laitance, dirt, dust, debris, grease or other substances. Clean surface with acid etching and hosing down. Neutralize acid if necessary.
- .12 *Epoxy Bonding Agent:* Approved mineral filled polymer/epoxy adhesive formulated to bond new concrete to cured concrete. Apply in strict conformance with manufacturer's written recommendations for proposed application. ST-432 by Sternson, SIKADUR HI-MOD by Sika, CONCREXIVE 1001-LPL by Adhesive Engineering Company or approved equal.
- .13 *Cement Grout Capsules:* reinforcing steel detailed to be installed in pre-placed concrete to be anchored using Lafarge Fondu Cement Grout Capsules M3RR or approved equal.

2.4 CONCRETE MIXES

- .1 Mechanical mix concrete in accordance with the requirements of CSA-A23.1-14.
- .2 All concrete shall have the following minimum properties.

Based on 2015 National Building Code

Location	Exposure Class	Comp. Strength (MPa) and Age	Aggregate	Air Entrainment	Slump
1. Piling	S-2	32 @ 56 d	40	3 - 6	80 \pm 30
2. Grade Beams/Walls in Contact with Soil	S-2	32 @ 56 d	20	4 - 7	80 \pm 30
3. Exterior Grade Supported Slabs	C-2	32 @ 28 d	20	5 - 8	80 \pm 30

Minimum cement content for Type 50 cement to be 280 kg/m³.
Maximum free water/cement ratio for Type 50 cement to be 0.5.

Semi-lightweight concrete to have unit weight of 2075 \pm 75kg/m³.
Lightweight concrete to have unit weight of 1850 \pm 75kg/m³.

- .3 Submit proposed mix design to Inspection and Testing Firm, to Consultant, and to Departmental Representative, two (2) weeks prior to commencement of work. Provide certification that mix proportions selected will produce concrete of specified quality and that strength will comply with CSA-A23.1-14.
- .4 Each load of ready-mixed or transit-mixed concrete delivered to the project site shall be accompanied by duplicate delivery slips providing the following information:
 - .1 Name of ready-mix batch plant
 - .2 Serial number of ticket
 - .3 Date and truck number
 - .4 Name of contractor
 - .5 Specific designation of project
 - .6 Specific class of concrete
 - .7 Amount of concrete in cubic metres
 - .8 Time of loading or first mixing of aggregate, cement and water.
- .5 Use accelerating admixtures in cold weather only when approved by Departmental Representative. If approved, the use of admixture will not relax cold weather placement requirements. Use calcium chloride only as approved by the Departmental Representative.
- .6 Use set-retarding admixtures during hot weather only when approved by Departmental Representative.
- .7 Use of plasticizers only when approved by Departmental Representative.
- .8 Concrete mix for exposed aggregate finish and sandblasted finish shall be designed as a low slump, gap-graded mix with a maximum amount of screened and washed crushed coarse aggregate.

Part 3 Execution

3.1 INSPECTION

- .1 Prior to all work of this Section, carefully inspect the installed work of all other trades and verify that all such work is complete to the point where this installation may properly commence.
- .2 Verify that all items to be embedded in concrete are in place.
- .3 Verify that concrete may be placed to the lines and elevations indicated on the Drawings, with all required clearance from reinforcement.

3.2 DISCREPANCIES

- .1 In the event of discrepancy, immediately notify the Departmental Representative.
- .2 Do not proceed with installation in areas of discrepancy until all such discrepancies have been fully resolved.

3.3 PREPARATION

- .1 Remove all wood scraps and debris from the formed areas in which concrete will be placed.
- .2 Thoroughly clean the forms to ensure proper placement and bonding of concrete.
- .3 Thoroughly wet the forms, except in freezing weather, or oil them; remove all standing water.
- .4 Thoroughly clean all transporting and handling equipment.

3.4 PLACING CONCRETE

- .1 Place concrete in accordance with requirements of CSA-A23.1-14 and as indicated on Drawings.
- .2 Notify Departmental Representative, Consultant, and Inspection and Testing Firm a minimum of forty-eight (48) hours prior to commencement of concreting operations.
- .3 Ensure all anchors, seats, plates and other items to be cast into concrete are placed, held securely and will not cause undue hardship in placing concrete.
- .4 Maintain accurate records of poured concrete items. Record date, location of pour, quantity, air temperature and test samples taken.
- .5 Ensure reinforcement, inserts, embedded parts, formed joints and fitments are not disturbed during concrete placement.
- .6 Prepare previously placed concrete by cleaning with steel brush.
- .7 Pour concrete continuously between predetermined construction and control joints. All construction joints subject to approval of the Departmental Representative.
- .8 Approval to place concrete shall be contingent on the formwork and reinforcing steel placement and evidence that the Departmental Representative can place the planned casting without stopping.
- .9 Excessive honeycomb or embedded debris in concrete is not acceptable. Remove and replace defective concrete. Excessive honeycomb is when eraser end of a pencil fits into cavity.

3.5 COLD WEATHER REQUIREMENTS

- .1 When the air temperature is at or below 5°C. or when there is a probability of it falling to this limit during the placing or curing period, cold weather requirements shall be applicable.
- .2 Provide heating equipment or heating plant on the job ready for use when concrete is being placed during cold weather. Such equipment shall be adequate for the purpose of maintaining the required temperature during the placing and curing of the concrete. The methods used for heating shall be approved by the Departmental Representative. Equipment inducing carbon monoxide gas in the building shall not be accepted.
- .3 Concrete shall not be placed on or against reinforcement, formwork, ground or any surface that is at a temperature less than 5°C.

- .4 The temperature of the concrete at all surfaces shall be maintained at not less than 15°C for three (3) days, or at not less than 10°C for five days after placing. Means shall be provided to humidify the air within enclosures and to keep the concrete and formwork continuously moist if dry heat is used. The concrete shall be kept above freezing temperature for a period of seven (7) days and shall be kept from alternate freezing and thawing for at least fourteen (14) days after placement.
- .5 At the end of the specified protection period the temperature of the concrete shall be reduced gradually at a rate not exceeding that shown in CSA-A23.1-14.
- .6 Accelerator or so-called anti-freeze compounds shall not be permitted unless otherwise approved in writing by the Departmental Representative.
- .7 All protective coverings shall be kept clear of the concrete and form surfaces to permit free circulation of air and shall be maintained intact for at least twenty-four (24) hours after artificial heat is discontinued.

3.6 HOT WEATHER REQUIREMENTS

- .1 When the air temperature exceeds 27°C, hot weather requirements shall be applicable.
- .2 Time of initial mixing to complete discharge shall not exceed 1 hour and 15 minutes and concrete placed shall not exceed 27°C.
- .3 Concrete forming surfaces and reinforcing steel shall be sprinkled with cool water just prior to placing concrete. Standing water or puddles shall be removed prior to concrete placement.
- .4 Special wind protection will be required as directed by the Departmental Representative.
- .5 Columns, walls, beams and slabs shall be kept continuously damp for twenty-four (24) hours by normal curing procedures as outlined by this Specification. Slabs cured by the applications of sealing, shall have curing compound applied immediately after finishing of the slab but before evaporation of surface moisture.
- .6 The use of water reducing agents shall be subject to the approval of the Departmental Representative when hot weather conditions prevail.

3.7 CONSTRUCTION JOINTS AND WATERSTOPS

- .1 The location and detail of all construction joints not detailed on the drawings shall be approved by the Departmental Representative.
- .2 Where fresh concrete is to be placed against concrete which has set or has partially set, the surface of the set or partially set concrete shall be roughened, cleaned of all laitance, and thoroughly soaked with water prior to the placement of fresh concrete.
- .3 In general, the construction joints in floor and roof systems shall be located in the middle of the spans of slabs, beams and girders. Proper key and dowels or extensions of reinforcing shall be provided at all construction joints.
- .4 Concrete placed in wall and column forms shall be struck off flush with the underside of the floor and roof systems.

3.8 DEFECTIVE CONCRETE

- .1 Concrete not meeting the requirements of the Specifications and drawings shall be considered defective concrete.
- .2 Concrete not conforming to the lines, details and grade specified herein or as shown on the drawings shall be modified or replaced at the Contractor's expense and to the satisfaction of the Departmental Representative. Finished lines, dimensions and surfaces shall be correct and true within tolerances specified in the Formwork Section of these Specifications.
- .3 Concrete not properly placed resulting in excessive honeycombing and all honeycombing and other defects in critical areas of stress, shall be repaired or replaced at the Contractor's expense and to the satisfaction of the Departmental Representative.
- .4 Concrete of insufficient strength or improper consistency shall be, as required by the Departmental Representative, subject to one or more of the following:
 - .1 Changes in mix proportions for the remainder of the work.
 - .2 Cores drilled and tested from the areas in question as directed by the Departmental Representative and in accordance with CSA-A23.2-14. The test results shall be indicative of the in-place concrete.
 - .3 Load testing of the structural elements in accordance with CSA-A23.3-14.
 - .4 The changes in the mix proportions and the testing shall be at the Contractor's expense.
 - .5 Concrete failing to meet the strength requirements of this Specification shall be strengthened or replaced at the Contractor's expense and to the satisfaction of the Departmental Representative.

3.9 PATCHING CONCRETE

- .1 After the removal of the forms concrete surfaces may be subject to inspection by the Departmental Representative.
- .2 All exposed metal form ties, nails, wires, shall be removed, fins broken off and all loose concrete removed.
- .3 Form tie pockets shall be thoroughly wetted and patched with patching concrete followed by proper curing.
- .4 Honeycombed and other defective surfaces shall be chipped away to a depth of not less than 25 mm with the edges perpendicular to the surface, thoroughly wetted and patched with patching concrete followed by proper curing.
- .5 Patching concrete shall be thoroughly compacted into place and finished in such a manner as to match the adjoining concrete. The design mix of the patching concrete shall be approved by the Departmental Representative.

3.10 FINISHING OF FORMED SURFACES

- .1 On exposed formed concrete surfaces, except at unfinished areas: remove blemishes, formwork joint marks by rubbing with carborundum block and water. Leave finished surfaces smooth, unmarred. Complete rubbing within twenty-four (24) hours for stripping formwork.

3.11 ANCHOR BOLTS AND WELDMENTS

- .1 Set anchor bolts and weldments to the following tolerances:
 - .1 Alignment: $\pm 3\text{mm}$ of location, plumb and true.
 - .2 Projection: $\pm 6\text{mm}$ of elevations called for.

3.12 SIDEWALKS

- .1 Unless specifically detailed otherwise on drawings or in specifications, sidewalks shall be constructed to the following details.
- .2 Use forms for edges of concrete wall to provide straight lines and smooth curves.
- .3 Located asphalt impregnated fireboard joint filled at 4.5 metre centres and where walks abut walls and other vertical surfaces. Joint filler to be full area of concrete section.
- .4 Slabs to be 125 thick cast over 6 mil poly and 200 compacted granular fill. Reinforce with 10 M at 300 mm on centre each way at mid-depth of slab.
- .5 Install tooled joints at 1.5 metres on centre.
- .6 Round all edges, including edges of control joints and tooled joints, with 12 mm radius edging tool.
- .7 Provide exposed surfaces of all sidewalks with medium broomed finish, to match existing.
- .8 Slope walks and slabs as detailed on drawings.

END OF SECTION

Part 1 General

1.1 WORK INCLUDED

- .1 Finish separate floor toppings, slabs on fill and monolithic floor slabs.
- .2 Apply concrete sealer.
- .3 Cure finished surfaces.

Part 2 Products

2.1 COMPOUNDS/HARDENERS/SEALERS

- .1 *Curing Compound:* chlorinated liquid rubber to CGSB 90-GP-1a, Type 1.
- .2 *Non-metallic Surface Sealer:* premixed natural mineral type; "Eurocure 700, by Elsro Ltd., "Flor Seal" by Sternson Ltd., "Master Seal" by Master Builders, "Sealtight CS-309" by W. R. Meadows or approved equal.
- .3 *Penetrating Epoxy Sealer:* Acceptable products "905 Penetrating Epoxy" by Cementation Company (Canada) Ltd., or Cappar's Niklepoxy Penetrant Sealer".
- .4 *Horizontal Joint Sealer:* three-component, chemically curing, self-levelling polyurethane joint sealant. THC-900 as manufactured by Tremco. Color selection by Departmental Representative. Install strictly in accordance with manufacturer's recommendations.
- .5 *Bonding Agent:* Approved high polymere polyvinyl acetate emulsion applied in strict accordance with manufacturer's recommendations for proposed application. Daraweld - C or approved equal.
- .6 *Epoxy Bonding Agent:* Approved mineral filled polymer/epoxy adhesive formulated to bond new concrete to cured concrete. Apply in strict conformance with manufacturer's written recommendations for proposed application. ST-432 by Sternson, SIKADUR HI-MOD by Sika, CONCRESLIVE 1001-LPL by Adhesive Engineering Company or approved equal.

Part 3 Execution

3.1 FLOOR FINISHING

- .1 Finish concrete floor surfaces in accordance with CSA A23.1-14.
- .2 Uniformly spread, screed and float concrete. Do not use grate tampers or mesh rollers. Do not spread concrete by vibration. Bring surfaces to levels indicated on Drawings.

3.2 CURING AND PROTECTION

1. All equipment needed for the curing and protection of the concrete shall be on hand and ready for use before actual placing is started.
2. All exposed non-formed surfaces shall be kept continuously moist for a minimum of seven consecutive days after placement of the concrete. The water for curing shall be clean and free from any materials that will cause staining or discolouration of the concrete. A liquid, membrane forming, curing compound shall be used under circumstances where the application of moisture is impracticable and where such compounds will not jeopardize the appearance of the concrete nor the bonding of future floor finishes.
3. Special curing techniques shall be employed when the concrete is subject to drying conditions such as high temperatures, low relative humidity and high winds. Concrete wall and column forms shall be kept continuously moist.
4. Freshly placed concrete shall be protected from the effects of direct sunshine, drying winds, cold, excessive heat and running water by the use of adequate tarpaulins or other suitable material to cover completely or enclose all freshly finished surfaces until the end of the curing period specified.

END OF SECTION

Part 1 General

1.1 REFERENCES

- .1 CSA International
 - .1 CAN/CSA-A82-14, Fired Masonry Brick Made from Clay or Shale.
 - .2 CAN/CSA-A179-14, Mortar and Grout for Unit Masonry.
 - .3 CAN/CSA-A370-14, Connectors for Masonry.
 - .4 CAN/CSA A371-14, Masonry Construction for Buildings.
 - .5 CSA S304-14, Design of Masonry Structures, includes update No. 1 (2015)
- .2 Health Canada / Workplace Hazardous Materials Information System (WHMIS)
 - .1 Material Safety Data Sheets (MSDS).

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for masonry products and include product characteristics, performance criteria, physical size, finish and limitations.
 - .2 Submit 1 copy of WHMIS MSDS in accordance with Section 01 35 29.06 - Health and Safety Requirements.
- .3 Samples:
 - .1 Submit for review and acceptance of each unit.
 - .2 Samples will be returned for inclusion into work.
- .4 Sustainable Design Submittals:
 - .1 Construction Waste Management:
 - .1 Submit project Waste Management Plan highlighting recycling and salvage requirements.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials off ground and in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect masonry products from damage.
 - .3 Replace defective or damaged materials with new.

- .4 Develop Construction Waste Management Plan related to Work of this Section.

Part 2 Products

2.1 MASONRY UNITS

- .1 Burned clay brick: to CAN/CSA-A82.
 - .1 Type: FBX.
 - .2 Grade: EG (exterior grade).
 - .3 Size: 57x90x190 modular (to match existing)
 - .4 Colour and texture: to match existing face brick on building.

2.2 REINFORCEMENT AND CONNECTORS

- .1 Connectors shall be corrosion resistant: to CAN/CSA-A370.

2.3 MORTAR AND GROUT

- .1 Mortar: to CAN/CSA-A179.
 - .1 Use aggregate passing 1.18 mm sieve where 6 mm thick joints are indicated.
 - .2 Colour: ground coloured natural aggregates or metallic oxide pigments.
- .2 Mortar Type: N based on property specifications.
- .3 Following applies regardless of mortar types and uses specified above:
 - .1 Mortar for grouted reinforced masonry: type S based on property specifications.
- .4 Grout: to CAN/CSA-A179, Table 3.

2.4 ACCESSORIES

- .1 Nailing Inserts: 0.5 mm minimum thickness, galvanized.
- .2 Bolts: 12 mm diameter x 150 mm long with ends bent 50 mm at 90 degrees.
- .3 Coatings: VOC limit 100 g/L maximum.

Part 3 Execution

3.1 EXAMINATION

- .1 Verification of Conditions: verify conditions of substrates previously installed under other Sections or Contracts are acceptable for product installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 INSTALLATION

- .1 Do masonry work in accordance with CAN/CSA-A371 except where specified otherwise.
 - .1 Bond: running stretcher bond with vertical joints in perpendicular alignment and centred on adjacent stretchers above and below.
 - .2 Coursing height: 200 mm for three bricks and three joints.
 - .3 Jointing: tool where exposed to provide smooth compressed concave surface.
- .2 Build masonry plumb, level, and true to line, with vertical joints in alignment.
- .3 Layout coursing and bond to achieve correct coursing heights, and continuity of bond above and below openings, with minimum of cutting.

3.3 CONSTRUCTION

- .1 Exposed masonry:
 - .1 Remove chipped, cracked, and otherwise damaged units, in exposed masonry and replace with undamaged units.
- .2 Provision for movement:
 - .1 Leave 6 mm space between top of non-load bearing walls and partitions and structural elements. Do not use wedges.
 - .2 Built masonry to tie in with stabilizers, with provision for vertical movement.
- .3 Interface with other work:
 - .1 Make good existing work. Use materials to match existing.

3.4 REINFORCING AND CONNECTING

- .1 Install masonry connectors and reinforcement in accordance with CAN/CSA-A370 and CAN/CSA-A371.
- .2 Prior to placing mortar, obtain Departmental Representative's approval of placement of reinforcement and connectors.

3.5 BONDING AND TYING

- .1 Tie masonry veneer to backing in accordance with NBC, CAN/CSA-A371, CSA S304.1 and as indicated.

3.6 GROUTING

- .1 Grout masonry in accordance with CAN/CSA-A179, CAN/CSA-A371 and CSA S304.1 and as indicated.

3.7 LATERAL SUPPORT AND ANCHORAGE

- .1 Supply and install lateral support and anchorage in accordance with CSA S304.1.

3.8 SITE TOLERANCES

- .1 Tolerances of CAN/CSA-A371 apply.

3.9 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

3.10 PROTECTION

- .1 Protect masonry and other work from marking and other damage. Protect completed work from mortar droppings. Use non-staining coverings.
- .2 Repair damage to adjacent materials caused by masonry products installation.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 American Wood-Preservers' Association (AWPA)
 - .1 AWP A M2-01, Standard for Inspection of Treated Wood Products.
 - .2 AWP A M4-06, Standard for the Care of Preservative-Treated Wood Products.
- .2 Canadian Standards Association (CSA International)
 - .1 CSA O80 Series-97(R2002) - O80S2-05, Wood Preservation.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit Submittal submissions: in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Quality assurance submittals:
 - .1 Submit certificates in accordance with Section 01 33 00 - Submittal Procedures.
 - .2 For products treated with preservative by pressure impregnation submit following information certified by authorized signing officer of treatment plant:
 - .1 Information listed in AWP A M2 and revisions specified in CSA O80 Series, Supplementary Requirement to AWP A M2 applicable to specified treatment.
 - .2 Moisture content after drying following treatment with water-borne preservative.

1.3 QUALITY ASSURANCE

- .1 Plant inspection of products treated with preservative by pressure impregnation will be carried out by designated testing laboratory to AWP A M2, and revisions specified in CSA O80 Series, Supplementary Requirements to AWP A M2.
- .2 Inspection and testing of insert materials will be carried out by Departmental Representative.

1.4 DELIVERY, STORAGE, AND HANDLING

- .1 Waste Management and Disposal:
 - .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.

Part 2 Products

2.1 MATERIALS

- .1 Solid lumber and plywood.
- .2 Preservative: to CSA-O80 Series, water-borne, for clear finish.

- .3 Preservatives: maximum VOC limit 350g/L.

Part 3 Execution

3.1 APPLICATION: PRESERVATIVE

- .1 Treat solid lumber and plywood to CSA O80 Series.
.2 Following water-borne preservative treatment, dry material to maximum moisture content of 19%.

3.2 APPLICATION: FIELD TREATMENT

- .1 Comply with AWP A M4 and revisions specified in CSA O80 Series, Supplementary Requirements to AWP A M2.
.2 Remove chemical deposits on treated wood to receive applied finish.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 ASTM International
 - .1 ASTM A653/A653M-11, Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvaneal) by the Hot-Dip Process.
 - .2 ASTM C1396/C1396M-11, Standard Specification for Gypsum Board.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-51.34-M86, Vapour Barrier, Polyethylene Sheet for Use in Building Construction and amendment.
- .3 CSA International
 - .1 CSA B111-1974(R2003), Wire Nails, Spikes and Staples.
 - .2 CSA O112.9-10, Evaluation of Adhesives for Structural Wood Products (Exterior Exposure).
 - .3 CSA O121-08, Douglas Fir Plywood.
 - .4 CSA O141-05(R2009), Softwood Lumber.
 - .5 CSA O151-09, Canadian Softwood Plywood.
 - .6 CSA O325-07, Construction Sheathing.
- .4 National Lumber Grades Authority (NLGA)
 - .1 Standard Grading Rules for Canadian Lumber 2010.
- .5 National Research Council Canada (NRC)
 - .1 National Building Code of Canada 2015 (NBC).

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for wood products and accessories and include product characteristics, performance criteria, physical size, finish and limitations.

1.3 QUALITY ASSURANCE

- .1 Lumber by grade stamp of an agency certified by Canadian Lumber Standards Accreditation Board.
- .2 Plywood, particleboard, OSB and wood based composite panels in accordance with CSA and ANSI standards.

1.4 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.

- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect from damage.
 - .3 Replace defective or damaged materials with new.

Part 2 Products

2.1 FRAMING STRUCTURAL AND PANEL MATERIALS

- .1 Lumber: softwood, S4S, moisture content 19% (S-dry) or less in accordance with following standards:
 - .1 CSA O141.
 - .2 NLGA Standard Grading Rules for Canadian Lumber.
- .2 Framing and board lumber: in accordance with National Building Code of Canada (NBC)
- .3 Furring, blocking, nailing strips, rough bucks, and backing:
 - .1 Board sizes: "Standard" or better grade.
 - .2 Dimension sizes: "Standard" light framing or better grade.
 - .3 Post and timbers sizes: "Standard" or better grade.
- .4 Plywood, OSB and wood based composite panels: to CSA O325.
- .5 Douglas fir plywood (DFP): to CSA O121, standard construction.
- .6 Canadian softwood plywood (CSP): to CSA O151, standard construction.
- .7 Gypsum sheathing: to ASTM C1396/C1396M.

2.2 ACCESSORIES

- .1 Polyethylene film: to CAN/CGSB-51.34, Type 1, 0.15 mm thick.
- .2 Sealants: in accordance with Section 07 92 00 - Joint Sealants.
- .3 General purpose adhesive: to CSA O112.9.
- .4 Nails, spikes and staples: to CSA B111.
- .5 Bolts: 12.5 mm diameter unless indicated otherwise, complete with nuts and washers.
- .6 Proprietary fasteners: toggle bolts, expansion shields and lag bolts, screws and lead or inorganic fibre plugs, recommended for purpose by manufacturer.
- .7 Fastener Finishes:
 - .1 Galvanizing: to ASTM A653, use galvanized fasteners for all areas.

Part 3 Execution

3.1 EXAMINATION

- .1 Verification of Conditions: verify conditions of substrates previously installed under other Sections or Contracts are acceptable for product installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 PREPARATION

- .1 Treat surfaces of material with wood preservative, before installation.
- .2 Apply preservative by dipping, or by brush to completely saturate and maintain wet film on surface for minimum 3-minute soak on lumber and one-minute soak on plywood.
- .3 Re-treat surfaces exposed by cutting, trimming or boring with liberal brush application of preservative before installation.
- .4 Treat material as indicated.

3.3 MATERIAL USAGE

- .1 Exterior sheathing:
 - .1 Plywood, DFP or CSP sheathing grade or PP standard sheathing grade.
- .2 Rock bed border:
 - .1 Preservative treated board lumber.
- .3 Crawlspace vapour retarder:
 - .1 Preservative treated board lumber.

3.4 INSTALLATION

- .1 Install members true to line, levels and elevations, square and plumb.
- .2 Construct continuous members from pieces of longest practical length.
- .3 Install spanning members with "crown-edge" up.
- .4 Select exposed framing for appearance. Install panel and lumber materials so that grade-marks and other defacing marks are concealed or are removed by sanding where materials are left exposed.
- .5 Install furring and blocking as required to space-out and support wall and ceiling finishes, facings, electrical equipment mounting boards, and other work as required.
- .6 Install rough bucks, nailers and linings to rough openings as required to provide backing for frames and other work.

- .7 Install wood backing, nailers, and other wood supports as required and secure using galvanized fasteners.
- .8 Use dust collectors and high-quality respirator masks when cutting or sanding wood panels.
- .9 Frame, anchor, fasten, tie and brace members to provide necessary strength and rigidity.
- .10 Countersink bolts where necessary to provide clearance for other work.
- .11 Use nailing disks for soft sheathing as recommended by sheathing manufacturer.

3.5 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.

3.6 PROTECTION

- .1 Protect installed products and components from damage during construction.
- .2 Repair damage to adjacent materials caused by rough carpentry installation.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-37.5-M89, Cutback Asphalt Plastic Cement.
 - .2 CGSB 37-GP-6Ma-83, Asphalt, Cutback, Unfilled, for Waterproofing.
 - .3 CGSB 37-GP-9Ma-83, Primer, Asphalt, Unfilled, for Asphalt Roofing, Waterproofing and Waterproofing.
 - .4 CGSB 37-GP-11M-76(R1984), Application of Cutback Asphalt Plastic Cement.
 - .5 CGSB 37-GP-15M-76(R1984), Application of Asphalt Primer for Asphalt Roofing, Waterproofing and Waterproofing.
 - .6 CGSB 37-GP-64M, Mat Reinforcing, Fibrous Glass, for Membrane Waterproofing Systems and Built-Up Roofing.
- .2 Health Canada
 - .1 Workplace Hazardous Materials Information System (WHMIS)
 - .1 Material Safety Data Sheets (MSDS).

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for bituminous waterproofing application and include product characteristics, performance criteria, physical size, finish and limitations.
 - .2 Submit copy of WHMIS MSDS in accordance with Section 01 35 29.06 - Health and Safety Requirements.
- .3 Manufacturer's Instructions: provide to indicate special handling criteria, installation sequence, protection requirements, and cleaning procedures.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect waterproofing materials from damage.
 - .3 Replace defective or damaged materials with new.

1.4 SITE CONDITIONS

- .1 Ambient Conditions: temperature, relative humidity, moisture content.
 - .1 Apply waterproofing materials only when surfaces and ambient temperatures are within manufacturers' prescribed limits.
 - .2 Do not proceed with Work when wind chill effect would tend to set bitumen before proper curing takes place.
 - .3 Maintain air temperature and substrate temperature at waterproofing installation area above 5 degrees C for 24 hours before, during and 24 hours after installation.
 - .4 Do not apply waterproofing in wet weather.
- .2 Safety: comply with requirements of Workplace Hazardous Materials Information System (WHMIS) regarding use, handling, storage, and disposal of asphalt, sealing compounds, primers and caulking materials.
- .3 Ventilation:
 - .1 Ventilate area of Work as directed by Departmental Representative by use of approved portable supply and exhaust fans.
 - .2 Ventilate enclosed spaces in accordance with Section 01 51 00 - Temporary Utilities.
 - .3 Provide continuous ventilation during and after waterproofing application. Provide continuous ventilation for 7 days after completion of waterproofing installation.

Part 2 Products

2.1 MATERIALS

- .1 Membrane:
 - .1 For self adhering application: to CGSB-37-GP-64M.
 - .1 Glass reinforcing mat impregnated and coated with SBS modified bitumen.
 - .2 Width of roll: 1 metre.
 - .3 Thickness of material: 1.5 mm.
 - .4 Acceptable materials: IKO Aquabarrier FP
 - .5 Acceptable manufacturers: equivalent product by Soprema or Henry Company
- .2 Sealing compound: plastic cutback asphalt cement to CAN/CGSB-37.5.
- .3 Primer: to CGSB 37-GP-9Ma.
 - .1 Use primer on all exposed surfaces to be coated.
 - .2 Primer shall be compatible with membrane material and manufacturer by same manufacturer as membrane.

- .4 Drainage Composite:
 - .1 High-strength, polystyrene core with non-woven filter fabric.
 - .2 Acceptable materials: Carlisle, CCW MiraDrain 6000 or approved alternate.
 - .3 Install using Carlisle, CAV-Grip low VOC Contact adhesive or approved alternate.

Part 3 Execution

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for bituminous waterproofing application installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 WORKMANSHIP

- .1 Keep hot asphalt:
 - .1 Below its flash point.
 - .2 At or below its final blowing temperature.
 - .3 Within its equiviscous temperature range at place of application.

3.3 PREPARATION

- .1 Before applying waterproofing:
 - .1 Remove all remaining soil from existing grade beam using a stiff brush and other method that will leave surface suitable for the installation of primer and proper adhesion of the waterproofing membrane.
 - .2 Seal exterior joints between foundation walls and footings, joints between concrete floor slab and foundation and around penetrations through waterproofing with sealing compound.

3.4 APPLICATION - WATERPROOFING

- .1 Do waterproofing in accordance with CGSB 37-GP-64M and in accordance with manufacturer's written instructions.
- .2 Lap all joints in accordance with manufacture's written instructions and seal exposed edges at laps with mastic sealant.
- .3 Do sealing work in accordance with CGSB 37-GP-11M.
- .4 Do priming of surface in accordance with CGSB 37-GP-15M.

- .5 Apply primer to CGSB primer standard.
- .6 Apply waterproofing in accordance with applicable CGSB application standard.

3.5 APPLICATION – DRAINAGE COMPOSITE

- .1 Install drainage composite with flat side against wall and filter fabric toward the soil. Install from top of grade (underside of flashing) to the underside of the grade beam.
- .2 Apply spray contact adhesive to wall in circular spray pattern in accordance with manufacturer's recommended coverage. Do not install directly onto drainage composite.
- .3 Install drainage composite when adhesive is tacky but does not transfer to finger when touched.
- .4 Install in vertical pattern on wall. At exposed end condition wrap excess fabric behind core to prevent soil from infiltrating behind panels.
- .5 At exposed top condition, adhere a strip of geotextile fabric to prevent soil or other foreign material from infiltrating the dimple core or sufficiently remove the dimple core from the fabric to wrap the fabric over and behind the dimple core.
- .6 Limit ultraviolet exposure by backfilling within 7 days after initial installation.
- .7 Dispose of empty canisters of adhesive in accordance with local and provincial regulations.

3.6 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

3.7 PROTECTION

- .1 Protect installed products and components from damage during construction.
- .2 Repair damage to adjacent materials caused by waterproofing application.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 ASTM International (ASTM)
 - .1 ASTM D4833/D4833M-07(2013)e1, Standard Test Method for Index Puncture Resistance of Geomembranes and Related Products
 - .2 ASTM E84-17, Standard Test Method for Surface Burning Characteristics of Building Materials.
 - .3 ASTM E96/E96M-16, Standard Test Methods for Water Vapor Transmission of Materials
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-51.34-M86, Vapour Barrier, Polyethylene Sheet, for Use in Building Construction.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for vapour retarders and include product characteristics, performance criteria, physical size, finish and limitations.
 - .2 Submit copy of WHMIS MSDS in accordance with Section 01 35 29.06 - Health and Safety Requirements.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials indoors, in dry location, and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect specified materials from damage.
 - .3 Replace defective or damaged materials with new.

Part 2 Products

2.1 SHEET VAPOUR BARRIER - CRAWLSPACE

- .1 Polyethylene film: 0.36mm thick, fire retardant, high-density cross laminated polyethylene vapour retarder.

- .1 Colour: white
- .2 Weight: 28kg/100m²
- .3 Tongue tear: 89N
- .4 Trapezoidal Tear: 129N
- .5 Puncture Strength: 138 MPa to ASTM D4833
- .6 Permeance: 1.606 NG/PA·S·m² to ASTM E-6
- .7 Fire Retardancy: flame spread of 5, smoke development of 100 to ASTM E84.
- .8 Product: Permalon X-200FR or approved alternate.

2.2 ACCESSORIES

- .1 Joint sealing tape: 0.9mm thick minimum, mastic tape, air resistant pressure sensitive adhesive tape, as recommended by vapour barrier manufacturer, 150 mm wide for lap joints and perimeter seals, 100 mm wide elsewhere.
- .2 Sealant: compatible with vapour retarder materials, recommended by vapour retarder manufacturer.

Part 3 Execution

3.1 INSTALLATION

- .1 Ensure services are installed and inspected prior to installation of retarder.
- .2 Install sheet vapour retarder on crawlspace substrate to form continuous retarder.
- .3 Use sheets of largest practical size to minimize joints.
- .4 Ensure surface beneath vapour retarder is smooth, level, and compacted, with no sharp projections.
- .5 Inspect for continuity. Repair punctures and tears with mastic tape before work is concealed. Immediately repair holes in vapour retarder once detected.
- .6 Seal around columns, piles, pipes, and other penetrations in accordance with manufacturer's written instructions.

3.2 LAP JOINT SEALS

- .1 Seal lap joints of sheet vapour retarder with approved sealant and mastic tape.
 - .1 Ensure vapour retarder surfaces to receive sealant and mastic tape are clean and dry.
 - .2 Attach first sheet to substrate.
 - .3 Apply continuous bead of sealant over solid backing at joint.
 - .4 Lap adjoining sheet minimum 150 mm and press into sealant bead.
 - .5 Install mastic tape as per manufacturer's written instructions.
 - .6 Ensure that no gaps exist in sealant bead. Smooth out folds and ripples occurring in sheet over sealant.

3.3 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
 - .1 Remove insulation material spilled during installation and leave work area ready for application of wall board.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 American Society for Testing and Materials International (ASTM)
 - .1 ASTM A653/A653M-07, Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process.
 - .2 ASTM D523-89(1999), Standard Test Method for Specular Gloss.
 - .3 ASTM D822-01(2006), Standard Practice for Filtered Open-Flame Carbon-Arc Exposures of Paint and Related Coatings.
- .2 Health Canada/Workplace Hazardous Materials Information System (WHMIS)
 - .1 Material Safety Data Sheets (MSDS).

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
 - .1 Submit manufacturer's printed product literature for sheet metal flashing systems materials, specifications and datasheet and include product characteristics, performance criteria, physical size, finish and limitations.
- .3 Samples:
 - .1 Submit 150 mm long samples of each type of sheet metal material, finishes and colours.
- .4 Quality assurance submittals: submit following in accordance with Section 01 45 00 - Quality Control.
 - .1 Manufacturer's Instructions: submit manufacturer's installation instructions and special handling criteria, installation sequence, and cleaning procedures.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements.
- .2 Waste Management and Disposal:
 - .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.

Part 2 Products

2.1 SHEET METAL MATERIALS

- .1 Zinc coated steel sheet: 1.6 mm thickness (16ga.), commercial quality to ASTM A653/A653M, with Z275 designation zinc coating.

2.2 PREFINISHED STEEL SHEET

- .1 Prefinished steel with factory applied polyvinylidene fluoride.
 - .1 Class F1S.
 - .2 Colour selected by Departmental Representative from manufacturer's standard range.
 - .3 Specular gloss: 30 units +/- in accordance with ASTM D523.
 - .4 Coating thickness: not less than 22 micrometres.
 - .5 Resistance to accelerated weathering for chalk rating of 8, colour fade 5 units or less and erosion rate less than 20% to ASTM D822 as follows:
 - .1 Outdoor exposure period 2500 hours.
 - .2 Humidity resistance exposure period 5000 hours.

2.3 ACCESSORIES

- .1 Isolation coating: alkali resistant bituminous paint.
- .2 Sealants: one or two-part urethane, Type 2, colour as selected by Departmental Representative from standard range of manufacture's colours.
- .3 Fasteners: manufacturer's standard type suitable for use with installation of metal flashing; with soft neoprene washers; fasteners cap same colour as exterior metal flashing. Exposed fasteners same finish as metal flashing.
- .4 Washers: of same material as sheet metal, 1 mm thick with rubber packings.

2.4 FABRICATION

- .1 Fabricate metal flashings and other sheet metal work as indicated.
- .2 Form pieces in 2400 mm maximum lengths.
 - .1 Make allowance for expansion at joints.
- .3 Hem exposed edges on underside 12 mm.
 - .1 Mitre and seal corners with sealant.
- .4 Form sections square, true and accurate to size, free from distortion and other defects detrimental to appearance or performance.
- .5 Apply isolation coating to metal surfaces to be embedded in concrete or mortar.

2.5 METAL FLASHINGS

- .1 Form flashings and copings to profiles indicated of sheet steel.

Part 3 Execution

3.1 MANUFACTURER'S INSTRUCTIONS

- .1 Compliance: comply with manufacturer's written recommendations, including product technical bulletins, handling, storage and installation instructions, and datasheets.

3.2 INSTALLATION

- .1 Install sheet metal work as detailed.
- .2 Use concealed fastenings except where approved before installation.
- .3 Lock end joints and caulk with sealant.
- .4 Insert metal flashing to form weather tight junction.
- .5 Caulk flashing at fastener, behind flashing, with sealant.

3.3 FIELD QUALITY CONTROL

- .1 Manufacturer's Field Services:
 - .1 Provide manufacturer's field services consisting of product use recommendations and periodic site visits for inspection of product installation in accordance with manufacturer's instructions.

3.4 CLEANING

- .1 Proceed in accordance with Section 01 74 11 - Cleaning.
- .2 On completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.
- .3 Leave work areas clean, free from grease, finger marks and stains.

END OF SECTION

Part 1 General

1.1 REFERENCES

- .1 Health Canada/Workplace Hazardous Materials Information System (WHMIS)
 - .1 Material Safety Data Sheets (MSDS).
- .2 National Research Council Canada (NRC)
 - .1 National Building Code of Canada 2015 (NBC).
- .3 Underwriter's Laboratories of Canada (ULC)
 - .1 ULC-S101-14, Standard Methods of Fire Endurance Tests of Building Construction and Materials.
 - .2 ULC-S115-1995, Fire Tests of Fire Stop Systems.

1.2 DEFINITIONS

- .1 Fire Stop Material: device intended to close off opening or penetration during fire or materials that fill openings in wall or floor assembly where penetration is by cables, cable trays, conduits, ducts and pipes and poke-through termination devices, including electrical outlet boxes along with their means of support through wall or floor openings.
- .2 Single Component Fire Stop System: fire stop material that has Listed Systems Design and is used individually without use of high temperature insulation or other materials to create fire stop system.
- .3 Multiple Component Fire Stop System: exact group of fire stop materials that are identified within Listed Systems Design to create on site fire stop system.
- .4 Tightly Fitted; (ref: NBC Part 3.1.9.1.1 and 9.10.9.6.1): penetrating items that are cast in place in buildings of noncombustible construction or have "0" annular space in buildings of combustible construction.
 - .1 Words "tightly fitted" should ensure that integrity of fire separation is such that it prevents passage of smoke and hot gases to unexposed side of fire separation.

1.3 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
 - .1 Submit manufacturer's printed product literature, specifications and datasheet and include product characteristics, performance criteria, physical size, finish and limitations.
 - .2 Submit copy of WHMIS MSDS - Material Safety Data Sheets in accordance with Section 01 35 29.06 - Health and Safety Requirements.
- .3 Shop Drawings:
 - .1 Submit ULC listed assemblies to show location, proposed material, reinforcement, anchorage, fastenings and method of installation.

- .2 Construction details should accurately reflect actual job conditions.
- .4 Quality assurance submittals: submit following in accordance with Section 01 45 00 - Quality Control.
 - .1 Test reports: in accordance with CAN-ULC-S101 for fire endurance and CAN-ULC-S102 for surface burning characteristics.
 - .1 Submit certified test reports from approved independent testing laboratories, indicating compliance of applied fire stopping with specifications for specified performance characteristics and physical properties.
 - .2 Manufacturer's Instructions: submit manufacturer's installation instructions and special handling criteria, installation sequence, and cleaning procedures.

1.4 QUALITY ASSURANCE

- .1 Qualifications:
 - .1 Installer: company or person specializing in fire stopping installations approved by manufacturer with 5 years documented experience.

1.5 DELIVERY, STORAGE AND HANDLING

- .1 Packing, shipping, handling and unloading:
 - .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements.
 - .2 Deliver, store and handle materials in accordance with manufacturer's written instructions.
 - .3 Deliver materials to the site in undamaged condition and in original unopened containers, marked to indicate brand name, manufacturer, ULC markings.
- .2 Storage and Protection:
 - .1 Store materials in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Replace defective or damaged materials with new.
- .3 Waste Management and Disposal:
 - .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.

Part 2 Products

2.1 MATERIALS

- .1 Fire stopping and smoke seal systems: in accordance with CAN-ULC-S115.
 - .1 Asbestos-free materials and systems capable of maintaining effective barrier against flame, smoke and gases in compliance with requirements of CAN-ULC-S115 and not to exceed opening sizes for which they are intended.
 - .2 Fire stop system rating: as indicated on drawings.

- .2 Re-penetrable fire stop system for power and communication cables.
- .3 Service penetration assemblies: systems tested to CAN-ULC-S115.
- .4 Service penetration fire stop components: certified by test laboratory to CAN-ULC-S115.
- .5 Fire-resistance rating of installed fire stopping assembly in accordance with NBC.
- .6 Fire stopping and smoke seals at openings intended for ease of re-entry such as cables: elastomeric seal.
- .7 Fire stopping and smoke seals at openings around penetrations for pipes, ductwork and other mechanical items requiring sound and vibration control: elastomeric seal.
- .8 Primers: to manufacturer's recommendation for specific material, substrate, and end use.
- .9 Water (if applicable): potable, clean and free from injurious amounts of deleterious substances.
- .10 Damming and backup materials, supports and anchoring devices: to manufacturer's recommendations, and in accordance with tested assembly being installed as acceptable to authorities having jurisdiction.
- .11 Sealants for vertical joints: non-sagging.

Part 3 Execution

3.1 MANUFACTURER'S INSTRUCTIONS

- .1 Compliance: comply with manufacturer's written recommendations or specifications, including product technical bulletins, handling, storage and installation instructions, and datasheets.

3.2 PREPARATION

- .1 Examine sizes and conditions of voids to be filled to establish correct thicknesses and installation of materials.
 - .1 Ensure that substrates and surfaces are clean, dry and frost free.
- .2 Prepare surfaces in contact with fire stopping materials and smoke seals to manufacturer's instructions.
- .3 Maintain insulation around pipes and ducts penetrating fire separation without interruption to vapour barrier.
- .4 Mask where necessary to avoid spillage and over coating onto adjoining surfaces; remove stains on adjacent surfaces.

3.3 INSTALLATION

- .1 Install fire stopping and smoke seal material and components in accordance with manufacturer's certified tested system listing.
- .2 Seal holes or voids made by through penetrations, poke-through termination devices, and unpenetrated openings or joints to ensure continuity and integrity of fire separation are maintained.

- .3 Provide temporary forming as required and remove forming only after materials have gained sufficient strength and after initial curing.
- .4 Tool or trowel exposed surfaces to neat finish.
- .5 Remove excess compound promptly as work progresses and upon completion.

3.4 SPECIAL REQUIREMENTS

- .1 Location of special requirements for fire stopping and smoke seal materials at openings and penetrations in fire resistant rated assemblies are as follows:
 - .1 Designed for re-entry, removable at: electrical and communication penetrations.

3.5 SEQUENCES OF OPERATION

- .1 Proceed with installation only when submittals have been reviewed by Departmental Representative.
- .2 Mechanical pipe insulation: certified fire stop system component. Ensure pipe insulation installation precedes fire stopping.

3.6 FIELD QUALITY CONTROL

- .1 Inspections: notify Departmental Representative when ready for inspection and prior to concealing or enclosing fire stopping materials and service penetration assemblies.

3.7 CLEANING

- .1 Proceed in accordance with Section 01 74 11 - Cleaning.
- .2 On completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.
- .3 Remove temporary dams after initial set of fire stopping and smoke seal materials.

3.8 SCHEDULE

- .1 Fire stop and smoke seal at:
 - .1 Penetrations through fire-resistance rated masonry, concrete, and gypsum board partitions and walls.
 - .2 Top of fire-resistance rated masonry and gypsum board partitions.
 - .3 Intersection of fire-resistance rated masonry and gypsum board partitions.
 - .4 Penetrations through fire-resistance rated floor slabs, ceilings and roofs.
 - .5 Openings and sleeves installed for future use through fire separations.
 - .6 Around mechanical and electrical assemblies penetrating fire separations.
 - .7 Rigid ducts: greater than 129 cm²: fire stopping to consist of bead of fire stopping material between retaining angle and fire separation and between retaining angle and duct, on each side of fire separation.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 ASTM International
 - .1 ASTM E814-13a(2017), Standard Test Method for Fire Tests on Penetration Firestop Systems.
 - .2 ASTM E1996-17, Standard Specification for Performance of Exterior Windows, Curtain Walls, Doors, and Impact Protective Systems Impacted by Windborne Debris in Hurricanes.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-19.13-M87, Sealing Compound, One-component, Elastomeric, Chemical Curing.
 - .2 CAN/CGSB-19.24-M90, Multi-component, Chemical Curing Sealing Compound.
- .3 Health Canada/Workplace Hazardous Materials Information System (WHMIS)
 - .1 Material Safety Data Sheets (MSDS).

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for joint sealants and include product characteristics, performance criteria, physical size, finish and limitations.
 - .2 Manufacturer's product to describe:
 - .1 Caulking compound.
 - .2 Primers.
 - .3 Sealing compound, each type, including compatibility when different sealants are in contact with each other.
 - .3 Submit 1 copy of WHMIS MSDS in accordance with Section 01 35 29.06 - Health and Safety Requirements.
- .3 Manufacturer's Instructions:
 - .1 Submit instructions to include installation instructions for each product used.

1.3 CLOSEOUT SUBMITTALS

- .1 Submit in accordance with Section 01 78 00 - Closeout Submittals.
- .2 Operation and Maintenance Data: submit operation and maintenance data for incorporation into manual.

1.4 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect joint sealants from damage.
 - .3 Replace defective or damaged materials with new.

1.5 SITE CONDITIONS

- .1 Ambient Conditions:
 - .1 Proceed with installation of joint sealants only when:
 - .1 Ambient and substrate temperature conditions are within limits permitted by joint sealant manufacturer or are above 4.4 degrees C.
 - .2 Joint substrates are dry.
 - .3 Conform to manufacturer's recommended temperatures, relative humidity, and substrate moisture content for application and curing of sealants including special conditions governing use.
- .2 Joint-Width Conditions:
 - .1 Proceed with installation of joint sealants only where joint widths are more than those allowed by joint sealant manufacturer for applications indicated.
- .3 Joint-Substrate Conditions:
 - .1 Proceed with installation of joint sealants only after contaminants capable of interfering with adhesion are removed from joint substrates.

1.6 ENVIRONMENTAL REQUIREMENTS

- .1 Comply with requirements of Workplace Hazardous Materials Information System (WHMIS) regarding use, handling, storage, and disposal of hazardous materials; and regarding labelling and provision of Material Safety Data Sheets (MSDS) acceptable to Health Canada.
- .2 Conform to manufacturer's recommended temperatures, relative humidity, and substrate moisture content for application and curing of sealants including special conditions governing use.
- .3 Ventilate area of work as directed by Departmental Representative by use of approved portable supply and exhaust fans.

Part 2 Products

2.1 SEALANT MATERIALS

- .1 Do not use caulking that emits strong odours, contains toxic chemicals or is not certified as mould resistant in air handling units.
- .2 When low toxicity caulks are not possible, confine usage to areas which off gas to exterior, are contained behind air barriers, or are applied several months before occupancy to maximize off gas time.
- .3 Where sealants are qualified with primers use only these primers.

2.2 SEALANT MATERIAL DESIGNATIONS

- .1 Type 1 - Urethanes three part:
 - .1 Non-sag: to CAN/CGSB-19.24, Type 2, Class B, colour as selected by Departmental Representative from standard range of manufacturer's colours.
- .2 Type 2 - Urethanes one part:
 - .1 Non-sag: to CAN/CGSB-19.13, Type 2, colour as selected by Departmental Representative from standard range of manufacturer's colours.
- .3 Type 3 - Silicones one part:
 - .1 To CAN/CGSB-19.13, Type 2, colour as selected by Departmental Representative from standard range of manufacturer's colours.
- .4 Preformed compressible and non-compressible back-up materials:
 - .1 Polyethylene, urethane, neoprene or vinyl foam:
 - .1 Extruded closed cell foam backer rod.
 - .2 Size: oversize 30 to 50 %.
 - .2 Neoprene or butyl rubber:
 - .1 Round solid rod, Shore A hardness 70.
 - .3 High density foam:
 - .1 Extruded closed cell polyvinyl chloride (PVC), extruded polyethylene, closed cell, Shore A hardness 20, tensile strength 140 to 200 kPa, extruded polyolefin foam, 32 kg/m³ density, or neoprene foam backer, size as recommended by manufacturer.
 - .4 Bond breaker tape:
 - .1 Polyethylene bond breaker tape which will not bond to sealant.

2.3 SEALANT SELECTION

- .1 Exterior sealant: sealant type: 1 or 2 (colour selected by Departmental Representative)
- .2 Seal interior perimeters of exterior openings as detailed on drawings: sealant type: 3
- .3 In additional locations as noted on the drawings: confirm with Departmental Representative.

2.4 JOINT CLEANER

- .1 Non-corrosive and non-staining type, compatible with joint forming materials and sealant in accordance with sealant manufacturer's written recommendations.
- .2 Primer: in accordance with sealant manufacturer's written recommendations.

Part 3 Execution

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for joint sealants installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 SURFACE PREPARATION

- .1 Examine joint sizes and conditions to establish correct depth to width relationship for installation of backup materials and sealants.
- .2 Clean bonding joint surfaces of harmful matter substances including dust, rust, oil grease, and other matter which may impair Work.
- .3 Do not apply sealants to joint surfaces treated with sealer, curing compound, water repellent, or other coatings unless tests have been performed to ensure compatibility of materials. Remove coatings as required.
- .4 Ensure joint surfaces are dry and frost free.
- .5 Prepare surfaces in accordance with manufacturer's directions.

3.3 PRIMING

- .1 Where necessary to prevent staining, mask adjacent surfaces prior to priming and caulking.
- .2 Prime sides of joints in accordance with sealant manufacturer's instructions immediately prior to caulking.

3.4 BACKUP MATERIAL

- .1 Apply bond breaker tape where required to manufacturer's instructions.
- .2 Install joint filler to achieve correct joint depth and shape, with approximately 30% compression.

3.5 MIXING

- .1 Mix materials in strict accordance with sealant manufacturer's instructions.

3.6 APPLICATION

- .1 Sealant:
 - .1 Apply sealant in accordance with manufacturer's written instructions.
 - .2 Mask edges of joint where irregular surface or sensitive joint border exists to provide neat joint.
 - .3 Apply sealant in continuous beads.
 - .4 Apply sealant using gun with proper size nozzle.
 - .5 Use sufficient pressure to fill voids and joints solid.
 - .6 Form surface of sealant with full bead, smooth, free from ridges, wrinkles, sags, air pockets, embedded impurities.
 - .7 Tool exposed surfaces before skinning begins to give slightly concave shape.
 - .8 Remove excess compound promptly as work progresses and upon completion.
- .2 Curing:
 - .1 Cure sealants in accordance with sealant manufacturer's instructions.
 - .2 Do not cover up sealants until proper curing has taken place.

3.7 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Leave Work area clean at end of each day.
 - .2 Clean adjacent surfaces immediately.
 - .3 Remove excess and droppings, using recommended cleaners as work progresses.
 - .4 Remove masking tape after initial set of sealant.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.

3.8 PROTECTION

- .1 Protect installed products and components from damage during construction.
- .2 Repair damage to adjacent materials caused by joint sealants installation.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 U.S. Environmental Protection Agency (EPA)/Office of Water
 - .1 EPA 832R92005, Storm Water Management for Construction Activities:
 Developing Pollution Prevention Plans and Best Management Practices.

Part 2 Products

2.1 NOT USED

- .1 Not Used.

Part 3 Execution

3.1 TEMPORARY EROSION AND SEDIMENTATION CONTROL

- .1 Provide temporary erosion and sedimentation control measures to prevent soil erosion and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways, according to requirements of authorities having jurisdiction.
- .2 Inspect, repair, and maintain erosion and sedimentation control measures during construction until permanent vegetation has been established.
- .3 Remove erosion and sedimentation controls and restore and stabilize areas disturbed during removal.

3.2 STRIPPING OF TOPSOIL

- .1 Ensure that procedures are conducted in accordance with applicable Municipal requirements.
- .2 Remove topsoil before construction procedures commence to avoid compaction of topsoil.
- .3 Handle topsoil only when it is dry and warm.
- .4 Remove vegetation from targeted areas by non-chemical means and dispose of stripped vegetation by alternative disposal.
- .5 Remove brush from targeted area by non-chemical means and dispose of through alternative disposal.
- .6 Strip topsoil to depths as indicated and as directed by Departmental Representative.
 - .1 Avoid mixing topsoil with subsoil.
- .7 Pile topsoil in berms in locations as directed by Departmental Representative.
 - .1 Stockpile height not to exceed 3 m.
- .8 Dispose of unused topsoil off-site.

- .9 Protect stockpiles from contamination and compaction.
- .10 Cover topsoil that has been piled for long term storage, with trefoil or grass to maintain agricultural potential of soil.

3.3 PREPARATION OF GRADE

- .1 Verify that grades are correct and notify Departmental Representative if discrepancies occur. Do not begin work until instructed by Departmental Representative.
 - .1 Grade area only when soil is dry to lessen soil compaction.
 - .2 Grade soil to match existing elevations, ensuring positive drainage.

3.4 PLACING OF TOPSOIL

- .1 Place topsoil only after Departmental Representative has accepted subgrade.
- .2 Spread topsoil during dry conditions in uniform layers not exceeding 150mm, over unfrozen subgrade free of standing water.
- .3 Establish traffic patterns for equipment to prevent driving on topsoil after it has been spread to avoid compaction.
- .4 Cultivate soil following spreading procedures.

3.5 CLEANING

- .1 Proceed in accordance with Section 01 74 11- Cleaning.
- .2 On completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 ASTM International
 - .1 ASTM D698-07e1, Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort (600 kN-m/m³).
- .2 Underwriters' Laboratories of Canada (ULC)

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Sustainable Design Submittals:
 - .1 Construction Waste Management:
 - .1 Erosion and Sedimentation Control: submit copy of erosion and sedimentation control plan in accordance with authorities having jurisdiction.

1.3 EXISTING CONDITIONS

- .1 Known underground and surface utility lines and buried objects are as indicated on site plan. Contractor to verify and protect all underground and surface utility lines and buried objects.
- .2 Refer to dewatering in Section 31 23 33.01 - Excavating, Trenching and Backfilling.

Part 2 Products

2.1 MATERIALS

- .1 Fill material: Refer to Section 31 23 33.01 - Excavating, Trenching and Backfilling.
- .2 Excavated or graded material existing on site suitable to use as fill for grading work if approved by Departmental Representative.

Part 3 Execution

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for rough grading installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 GRADING

- .1 Rough grade to levels, profiles, and contours allowing for surface treatment as indicated.
- .2 Rough grade to following depths below finish grades: 150 mm
- .3 Slope rough grade away from building matching existing site elevations.
- .4 Grade ditches to depth required for maximum run-off.
- .5 Prior to placing fill over existing ground, scarify surface to depth of 150 mm minimum before placing fill over existing ground. Maintain fill and existing surface at approximately same moisture content to facilitate bonding.
- .6 Compact filled and disturbed areas to maximum dry density to ASTM D698, as follows:
 - .1 95% under landscaped areas.
 - .2 97% under paved and walk areas.
- .7 Do not disturb soil within branch spread of trees or shrubs to remain.

3.3 TESTING

- .1 Inspection and testing of soil compaction will be carried out by testing laboratory designated by ULC. Costs of tests will be paid by Contractor.
- .2 Submit testing procedure, frequency of tests, testing laboratory as designated by ULC or certified testing personnel to Departmental Representative for review.

3.4 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

3.5 PROTECTION

- .1 Protect existing trees, landscaping, natural features, bench marks, buildings, walkways, pavement, surface and underground utility lines which are to remain as directed by Departmental Representative. If damaged, restore to original or better condition unless directed otherwise.
- .2 Maintain roads to prevent accumulation of construction related debris on roads.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 American Society for Testing and Materials International (ASTM)
 - .1 ASTM C117-04, Standard Test Method for Material Finer than 0.075 mm (No.200) Sieve in Mineral Aggregates by Washing.
 - .2 ASTM C136-05, Standard Test Method for Sieve Analysis of Fine and Coarse Aggregates.
 - .3 ASTM D422-632002, Standard Test Method for Particle-Size Analysis of Soils.
 - .4 ASTM D698-00ae1, Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/ft³) (600 kN-m/m³).
 - .5 ASTM D1557-02e1, Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Modified Effort (56,000 ft-lbf/ft³) (2,700 kN-m/m³).
 - .6 ASTM D4318-05, Standard Test Methods for Liquid Limit, Plastic Limit, and Plasticity Index of Soils.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-8.1-88, Sieves, Testing, Woven Wire, Inch Series.
 - .2 CAN/CGSB-8.2-M88, Sieves, Testing, Woven Wire, Metric.
- .3 Canadian Standards Association (CSA International)
 - .1 CAN/CSA-A3000-03, Cementitious Materials Compendium (Consists of A3001, A3002, A3003, A3004 and A3005).
 - .1 CSA-A3001-03, Cementitious Materials for Use in Concrete.
 - .2 CSA-A23.1/A23.2-04, Concrete Materials and Methods of Concrete Construction/Methods of Test and Standard Practices for Concrete.

1.2 DEFINITIONS

- .1 Unclassified excavation: excavation of deposits of whatever character encountered in Work.
- .2 Topsoil:
 - .1 Material capable of supporting good vegetative growth and suitable for use in top dressing, landscaping and seeding.
 - .2 Material reasonably free from subsoil, clay lumps, brush, objectionable weeds, and other litter, and free from cobbles, stumps, roots, and other objectionable material larger than 25 mm (1") in any dimension.
- .3 Waste material: excavated material unsuitable for use in Work or surplus to requirements.
- .4 Borrow material: material obtained from locations outside area to be graded and required for construction of fill areas or for other portions of Work.
- .5 Recycled fill material: material, considered inert, obtained from alternate sources and engineered to meet requirements of fill areas.

- .6 Unsuitable materials:
- .1 Weak, chemically unstable, and compressible materials.
 - .2 Frost susceptible materials:
 - .1 Fine grained soils with plasticity index less than 10 when tested to ASTM D4318, and gradation within limits specified when tested to ASTM C136 and ASTM D422: Sieve sizes to CAN/CGSB-8.2.
 - .2 Table:

Sieve Designation	% Passing
2.00 mm	100
0.10 mm	45 - 100
0.02 mm	10 - 80
0.005 mm	0 - 45
 - .3 Coarse grained soils containing more than 20% by mass passing 0.075 mm sieve.
- .7 Unshrinkable fill: very weak mixture of cement, concrete aggregates and water that resists settlement when placed in utility trenches, and capable of being readily excavated.

1.3 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Make submittals in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Quality Control: in accordance with Section 01 45 00 - Quality Control:
 - .1 Submit condition survey of existing conditions as described in EXISTING CONDITIONS article of this Section.
 - .2 Submit for review by Departmental Representative proposed dewatering methods as described in PART 3 of this Section.
 - .3 Submit to Departmental Representative written notice at least 7 days prior to excavation work, to ensure cross sections are taken.
 - .4 Submit to Departmental Representative written notice when bottom of excavation is reached.
 - .5 Submit to Departmental Representative results and reports as described in PART 3 of this Section.
- .3 Preconstruction Submittals:
 - .1 Submit construction equipment list for major equipment to be used in this section prior to start of Work.
 - .2 Submit records of underground utility locates, indicating: location plan of existing utilities as found in field and clearance record from utility authority.
- .4 Samples:
 - .1 Submit samples in accordance with Section 01 33 00 - Submittal Procedures.
 - .2 Inform Departmental Representative at least 4 weeks prior to beginning Work, of proposed source of fill materials and provide access for sampling.
 - .3 Submit 70 kg samples of type of fill specified including representative samples of excavated material.

- .4 Ship samples prepaid to Departmental Representative, in tightly closed containers to prevent contamination and exposure to elements.

1.4 QUALITY ASSURANCE

- .1 Submit design and supporting data at least 2 weeks prior to beginning Work.
- .2 Design and supporting data submitted to bear stamp and signature of qualified professional engineer registered or licensed in Province of Saskatchewan, Canada.
- .3 Keep design and supporting data on site.
- .4 Engage services of qualified professional Engineer who is registered or licensed in Province of Saskatchewan, Canada in which Work is to be carried out to design and inspect cofferdams, shoring, bracing and underpinning required for Work.
- .5 Do not use soil material until written report of soil test results are reviewed by Departmental Representative.
- .6 Health and Safety Requirements:
 - .1 Do construction occupational health and safety in accordance with Section 01 35 29.06 - Health and Safety Requirements.

1.5 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
- .2 Divert excess materials from landfill to local facility, where available.

1.6 EXISTING CONDITIONS

- .1 Buried services:
 - .1 Before commencing work verify and protect location of buried services on and adjacent to site.
 - .2 Arrange with appropriate authority for relocation of buried services that interfere with execution of work: pay costs of relocating services.
 - .3 Remove obsolete buried services within 2 m of foundations: cap cut-offs.
 - .4 Size, depth and location of existing utilities and structures as indicated are for guidance only. Completeness and accuracy are not guaranteed.
 - .5 Prior to beginning excavation Work, notify applicable Departmental Representative and authorities having jurisdiction, establish location and state of use of buried utilities and structures. Contractor to clearly mark such locations to prevent disturbance during Work.
 - .6 Confirm locations of buried utilities by careful soil hydrovac methods and test excavations.
 - .7 Maintain and protect from damage, water, sewer, gas, electric, telephone and other utilities and structures encountered.
 - .8 Where utility lines or structures exist in area of excavation, obtain direction of Departmental Representative before removing or re-routing. Costs for such Work to be borne by the Contractor.

- .9 Record location of maintained, re-routed and abandoned underground lines.
- .10 Confirm locations of recent excavations adjacent to area of excavation.
- .2 Existing buildings and surface features:
 - .1 Conduct, with Departmental Representative, condition survey of existing buildings, trees and other plants, lawns, fencing, service poles, wires, pavement, survey bench marks and monuments which may be affected by Work.
 - .2 Protect existing buildings and surface features from damage while Work is in progress. In event of damage, immediately make repair as directed by Departmental Representative.
 - .3 Where required for excavation, cut roots or branches as directed by Departmental Representative.

Part 2 Products

2.1 MATERIALS

- .1 Type 1, Type 2, Type 8, and Type 32 fill: properties to meet the following requirements:
 - .1 Crushed, pit run or screened stone, gravel or sand.
 - .2 Gradations to be within limits specified when tested to ASTM C117 and ASTM C136. Sieve sizes to CAN/CGSB-8.1 and CAN/CGSB-8.2.
 - .3 Table:

Sieve Designation	% Passing			
	Aggregate Base (Type 1)	Granular Sub-Base (Type 2)	Granular Sub-Base (Type 8)	Granular Base (Type 32 or 33)
75 mm	-	100		
50 mm	-	-	100	
37.5 mm	-	-	-	
25 mm	100	-	-	
19 mm	75-100	-	-	100
12.5 mm	-	-	-	75 - 100
9.5 mm	50-100	-	-	
4.75 mm	30-70	22-85	-	50 - 75
2.00 mm	20-45	-	0 - 90	32 - 52
0.900 mm	-	-	-	20 - 35
0.425 mm	10-25	5-30	0 - 60	15 - 25
0.180 mm	-	-	0 - 25	8 - 15
0.075 mm	3-8	0-10	0 - 15	6 - 11
Plasticity Index			0 - 6	0 - 6
Fractured Face %				50 minimum
Light Weight Pieces %				5 minimum

- .2 Type 3 fill: selected material from excavation or other sources, approved by Departmental Representative for use intended, unfrozen and free from rocks larger than 75 mm, cinders, ashes, sods, refuse or other deleterious materials.
- .3 Unshrinkable fill: proportioned and mixed to provide:
 - .1 Maximum compressive strength of 0.4 MPa at 28 days.

- .2 Maximum cement content of 25 kg/m³: to CSA-A3001.
- .3 Minimum strength of 0.07 MPa at 24 h.
- .4 Concrete aggregates: to CSA-A23.1/A23.2.
- .5 Cement: Type GU.
- .6 Slump: 160 to 200 mm.
- .4 Geotextile filter:
 - .1 Non-woven synthetic fibre fabric, supplied in rolls.
 - .2 Composed of: minimum 85% by mass of polyester or polypropylene with inhibitors added to base plastic to resist deterioration by ultra-violet and heat exposure for 60 days.
- .5 Topsoil:
 - .1 The mix shall be 65% loamy topsoil and 35% peat moss, by volume. Topsoil shall be a friable loam, neither heavy clay nor of a light sandy nature, and shall be capable of supporting good plant growth.
 - .2 The topsoil shall be taken from a source free from couch grass and other noxious weeds and grasses.
- .6 Granular Drain Rock:
 - .1 Crushed pit run or screened stone or gravel.
 - .2 Gradations to be within limits specified when tested to ASTM C136 and ASTM C117. Sieve sizes to CAN/CGSB-8.1 and CAN/CGSB-8.2.

Table:

Sieve Designation	% Passing
19 mm	100
12.5 mm	-
9.5 mm	-
4.75 mm	25 - 85
2.00 mm	-
0.425 mm	5 - 30
0.180 mm	-
0.075 mm	0 - 10

- .7 Granular topping:
 - .1 Screenings: hard, durable, crushed stone particles, free from clay lumps, cementation, organic material, frozen material and other deleterious materials.
 - .2 Gradations: within limits specified when tested to ASTM C136 and ASTM C117.
 - .3 Table:

Sieve Designation	% Passing
9.5 mm	100
4.75 mm	50-100
2.00 mm	30-65
0.425 mm	10-30
0.075 mm	5-10

- .8 Earth fill: unfrozen, clean medium plasticity silty clay or silty clay matrix till, free of sticks, roots, stones larger than 75 mm, concrete, and other debris.

Part 3 Execution

3.1 TEMPORARY EROSION AND SEDIMENTATION CONTROL

- .1 Provide temporary erosion and sedimentation control measures to prevent soil erosion and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways, according to requirements of authorities having jurisdiction.
- .2 Inspect, repair, and maintain erosion and sedimentation control measures during construction until permanent vegetation has been established.
- .3 Remove erosion and sedimentation controls and restore and stabilize areas disturbed during removal.

3.2 SITE PREPARATION

- .1 Remove obstructions, ice and snow, from surfaces to be excavated within limits indicated.
- .2 Cut pavement or sidewalk neatly along limits of proposed excavation in order that surface may break evenly and.

3.3 PREPARATION/PROTECTION

- .1 Protect existing features in accordance with Section 01 56 00 - Temporary Barriers and Enclosures and applicable local regulations.
- .2 Keep excavations clean, free of standing water, and loose soil.
- .3 Where soil is subject to significant volume change due to change in moisture content, cover and protect to Departmental Representative approval.
- .4 Protect natural and man-made features required to remain undisturbed. Unless otherwise indicated or located in an area to be occupied by new construction, protect existing trees from damage.
- .5 Protect buried services that are required to remain undisturbed.

3.4 STOCKPILING

- .1 Stockpile fill materials in areas designated by Departmental Representative.
 - .1 Stockpile granular materials in manner to prevent segregation.
- .2 Protect fill materials from contamination.
- .3 Implement sufficient erosion and sediment control measures to prevent sediment release off construction boundaries and into water bodies.

3.5 COFFERDAMS, SHORING, BRACING AND UNDERPINNING

- .1 Maintain sides and slopes of excavations in safe condition by appropriate methods and in accordance with Section 01 35 29.06 - Health and Safety Requirements and Health and Safety Act for the Province of Saskatchewan.

- .1 Where conditions are unstable, Departmental Representative to verify and advise methods.
- .2 Obtain permit from authority having jurisdiction for temporary diversion of water course.
- .3 Construct temporary Works to depths, heights and locations as indicated.
- .4 During backfill operation:
 - .1 Unless otherwise indicated or directed by Departmental Representative, remove sheeting and shoring from excavations.
 - .2 Do not remove bracing until backfilling has reached respective levels of such bracing.
 - .3 Pull sheeting in increments that will ensure compacted backfill is maintained at elevation at least 500 mm above toe of sheeting.
- .5 When sheeting is required to remain in place, cut off tops at elevations as indicated.
- .6 Upon completion of substructure construction:
 - .1 Remove cofferdams, shoring and bracing.
 - .2 Remove excess materials from site and restore watercourses.

3.6 DEWATERING AND HEAVE PREVENTION

- .1 Keep excavations free of water while Work is in progress.
- .2 Provide for approval by Departmental Representative review details of proposed dewatering or heave prevention methods, including dikes, well points, and sheet pile cut-offs.
- .3 Avoid excavation below groundwater table if quick condition or heave is likely to occur.
 - .1 Prevent piping or bottom heave of excavations by groundwater lowering, sheet pile cut-offs, or other means.
- .4 Protect open excavations against flooding and damage due to surface run-off.
- .5 Dispose of water in manner not detrimental to public and private property, or portion of Work completed or under construction.
 - .1 Provide and maintain temporary drainage ditches and other diversions outside of excavation limits.

3.7 EXCAVATION

- .1 Excavate to lines, grades, elevations and dimensions as indicated and as directed by Departmental Representative.
- .2 Remove all obstructions encountered during excavation.
- .3 Excavation must not interfere with bearing capacity of adjacent foundations.
- .4 Do not disturb soil within branch spread of trees or shrubs that are to remain.
 - .1 If excavating through roots, excavate by hand and cut roots with sharp axe or saw.

- .5 For trench excavation, unless otherwise authorized by Departmental Representative in writing, do not excavate more than 30m of trench in advance of installation operations and do not leave open more than 15m at end of day's operation.
- .6 Keep excavated and stockpiled materials safe distance away from edge of trench as directed by Departmental Representative.
- .7 Restrict vehicle operations directly adjacent to open trenches.
- .8 Dispose of surplus and unsuitable excavated material off site.
- .9 Do not obstruct flow of surface drainage or natural watercourses.
- .10 Earth bottoms of excavations to be undisturbed soil, level, free from loose, soft or organic matter.
- .11 Notify Departmental Representative when bottom of excavation is reached.
- .12 Obtain Departmental Representative approval of completed excavation.
- .13 Remove unsuitable material from trench bottom including those that extend below required elevations to extent and depth as directed by Departmental Representative.
- .14 Correct unauthorized over-excavation as follows:
 - .1 Fill under bearing surfaces and footings with fill concrete, Type 2 fill compacted to not less than 100% of corrected Standard Proctor maximum dry.
 - .2 Fill under other areas with Type 2 fill compacted to not less than 95% of corrected Standard Proctor maximum dry density.
- .15 Hand trim, make firm and remove loose material and debris from excavations.
 - .1 Where material at bottom of excavation is disturbed, compact foundation soil to density at least equal to undisturbed soil.
 - .2 Clean out rock seams and fill with concrete mortar or grout to approval of Departmental Representative.
- .16 Install geotextiles where indicated.

3.8 FILL TYPES AND COMPACTION

- .1 Use types of fill as indicated or specified below. Compaction densities are percentages of maximum densities obtained from ASTM D698 and ASTM D1557.
 - .1 Exterior side of perimeter walls: use Type 3 fill to subgrade level. Compact to 95% of corrected maximum dry density.
 - .2 Within building area: use Type 2 to underside of base course for floor slabs. Compact to 100% of corrected maximum dry density.
 - .3 Under concrete slabs: provide 150 mm compacted thickness base course of Type 1 fill to underside of slab. Compact base course to 100%.
 - .4 Under sodded areas: refer to Section 32 92 23 - Sodding.
 - .5 Place unshrinkable fill in areas as indicated.

3.9 BEDDING AND SURROUND OF UNDERGROUND SERVICES

- .1 Place and compact granular material for bedding and surround of underground services as indicated.
- .2 Place bedding and surround material in unfrozen condition.

3.10 BACKFILLING

- .1 Vibratory compaction equipment: provide list of equipment.
- .2 Do not proceed with backfilling operations until completion of following:
 - .1 Departmental Representative has reviewed and approved installations.
 - .2 Departmental Representative has reviewed and approved of construction below finish grade.
 - .3 Inspection, testing, approval, and recording location of underground utilities.
 - .4 Removal of shoring and bracing; backfilling of voids with satisfactory soil material.
- .3 Areas to be backfilled to be free from debris, snow, ice, water and frozen ground.
- .4 Do not use backfill material which is frozen or contains ice, snow or debris.
- .5 Place backfill material in uniform layers not exceeding 150 mm compacted thickness up to grades indicated. Compact each layer before placing succeeding layer.
- .6 Backfilling around installations:
 - .1 Place bedding and surround material as specified.
 - .2 Do not backfill around or over cast-in-place concrete within 24 hours after placing of concrete.
 - .3 Place layers simultaneously on both sides of installed Work to equalize loading.
 - .4 Where temporary unbalanced earth pressures are liable to develop on walls or other structures:
 - .1 If approved by Departmental Representative, erect bracing or shoring to counteract unbalance, and leave in place until removal is approved by Departmental Representative.
- .7 Place unshrinkable fill in areas as indicated.
- .8 Consolidate and level unshrinkable fill with internal vibrators.
- .9 Install drainage system in backfill as indicated.

3.11 RESTORATION

- .1 Upon completion of Work, remove waste materials and debris in accordance to Section 01 74 21 - Construction/Demolition Waste Management and Disposal, trim slopes, and correct defects as directed by Departmental Representative.
- .2 Replace topsoil as indicated and as directed by Departmental Representative.
- .3 Reinstall lawns to elevation which existed before excavation.
- .4 Reinstall pavements and sidewalks disturbed by excavation to thickness, structure and elevation which existed before excavation.

- .5 Clean and reinstate areas affected by Work as directed by Departmental Representative.
- .6 Use temporary plating to support traffic loads over unshrinkable fill for initial 24 hours.
- .7 Protect newly graded areas from traffic and erosion and maintain free of trash or debris.

END OF SECTION

Part 1 General

1.1 WORK INCLUDED

- .1 Bored friction piles with reinforcing steel as detailed.
- .2 Establish and/or verify required cut-off elevations.
- .3 Correct as directed all piles not meeting requirements of this specification at no expense to Departmental Representative.
- .4 Leave site neat, tidy, free of plant and/or equipment and in safe condition. Remove excavation material from site or deposit on site as directed.

1.2 REFERENCE STANDARDS

- .1 CAN/CSA A23.1-14 - "Concrete Materials and Methods of Concrete Construction".
- .2 CAN/CSA A23.2-14 - "Methods of Test for Concrete".
- .3 CAN/CSA G30.18-09 (R2014) - "Billet Steel Bars for Concrete Reinforcement".

1.3 CONCRETE TESTING

- .1 Testing of concrete is to be performed by an independent Inspection and Testing Firm approved by the Departmental Representative and paid for by the Contractor. Required retesting will be paid for by the Contractor. Unless approved otherwise, the testing agency must perform all aspects of testing including cylinder preparation.
- .2 Provide free access to all portions of work and co-operate with appointed firm.
- .3 Submit proposed mix design to Inspection and Testing Firm and Departmental Representative two weeks prior to commencement of work.
- .4 Tests for cement and aggregate may be performed to ensure conformance with requirements stated herein.
- .5 One set of three (3) concrete test cylinders will be taken for each day's pour, or for each 50 cubic metres, whichever is lesser. One cylinder shall be tested at 7 days, the remaining two cylinders shall be tested at 28 days.
- .6 One (1) additional test cylinder shall be taken during cold weather concreting and be cured on job site under same conditions of concrete it represents.
- .7 One slump test and one air content test will be taken for each set of test cylinders taken.
- .8 Testing of concrete will be performed in accordance with CAN/CSA A23.2-14.

1.4 FIELD RECORDS/DRAWINGS

- .1 Maintain accurate records of all piles poured. Records are to include the following incorporated on the Contractor's record drawings:
 - .1 Date and time of casting.
 - .2 Sizes, depths and location of piles.
 - .3 Sequence of placing.

- .4 Final cut-off elevation.
- .5 Reinforcement, size and length.
- .2 Submit three (3) copies of record drawings to the Departmental Representative.
- .3 Drawing to be the same scale and line reference as the contract drawings.

Part 2 Products

2.1 REINFORCING STEEL

- .1 Reinforcing Steel: deformed steel bars conforming to requirements of CAN/CSA G30.18-09 (R2014); 400 MPa yield strength.
- .2 Reinforcement to conform to standards specified under Section 03 20 00 Concrete Reinforcement. Submit shop drawings of reinforcing steel to Departmental Representative in accordance with the requirements of Section 03 20 00.
- .3 Length of reinforcement to be as shown on drawings.
- .4 No splicing in reinforcement permitted unless specifically shown on drawings or approved by Departmental Representative. Where splices permitted length = 36 bar diameters minimum; adjacent splices staggered minimum full lap length.
- .5 Welding ties to main reinforcement not permitted.

2.2 CONCRETE MATERIALS

- .1 *Cement:* Sulphate Resistant Symbol S-2 Portland, conforming to CSA A3000-13.
- .2 *Coarse and Fine Aggregates:* Standard concrete type, conforming to CSA A23.1-14.
- .3 *Water:* Clean and free of injurious amounts of oil, alkali, organic matter of other deleterious material.

2.3 ADMIXTURES

- .1 *Air Entrainment:* to ASTM C260-10 "Air Entraining Admixtures for Concrete."
- .2 *Chemicals:* to ASTM C494-15a - M78 "Chemical Admixtures for Concrete"; water reducing, strength increasing Type WN - normal setting.
- .3 *Pozzolanic Mineral:* to CSA A3000-13 "Supplementary Cementing Materials and Their Use in Concrete Construction." Type "C" or Type "F" fly ash permitted to a maximum to 15% by weight of cementitious materials.
- .4 Use of calcium chloride in concrete permitted only as approved by Departmental Representative.

2.4 CONCRETE MIX

- .1 Mix concrete in accordance with Section 03 30 00 - Cast-In-Place Concrete.

2.5 CASING

- .1 Removable steel protective casing adequate for its function.

Part 3 Installation

3.1 LAYOUT

- .1 Place piles accurately in locations as called for on drawings. Registered Land Surveyor of the Province of Saskatchewan to carry out pile location survey.
- .2 Maximum permissible error in location 40 mm in any direction. Place piles not more than 2% of their lengths out of plumb or batter called for on drawings. Elevation of top of piles to be within 25 mm of elevation called for on drawings. Reinforcing steel clearances within 15 mm of dimension called for on drawings.
- .3 Minimum pile diameter as per drawings.
- .4 Piles placed outside above tolerances may be rejected by the Departmental Representative. Place additional piles and pile caps as directed by the Departmental Representative to replace rejected piles entirely at the Contractor's expense.

3.2 PROCEDURE FOR BORING PILES

- .1 Bore piles using power augers to suit diameters and lengths of piles indicated on drawings. Where called for on drawings, enlarge bottom of shaft using only personnel well experienced in this Trade. Provide to the Departmental Representative on request experience record of personnel actually engaged in the work.
- .2 Boulders encountered in drilling shall be removed and pile continued to full depth. Should removal of boulders be impractical, consult with Departmental Representative.
- .3 Casings shall be installed in shafts as required to prevent sloughing during drilling and for the retention of ground water. If casing is required, advise Departmental Representative prior to placing concrete in shaft.
- .4 Provide de-watering as necessary before any concrete is placed.
- .5 Remove all tailings and debris from area of bore holes prior to casting concrete. Cover bore hole to prevent loose materials falling in during removal.
- .6 After hole drilled, place reinforcing steel and concrete. Do not drill any holes which cannot be reinforced and filled with concrete the same day as drilled.

3.3 PLACING REINFORCING STEEL

- .1 Place reinforcing steel in such a manner to prevent loose earth and debris from falling into the hole.
- .2 Place reinforcing at proper elevation and hold during course of placing concrete. Placing of steel will not be allowed after concrete poured.

3.4 PLACING CONCRETE

- .1 De-water holes, sleeves or not, before any concrete is placed.
- .2 Before commencing placing concrete obtain Departmental Representative's approval of proposed method of transporting and placing concrete.
- .3 Form piles projecting above grade with removable steel sleeves or wax coated cardboard fibre forms.

- .4 Place concrete continuously to final cut-off elevation as soon as possible after hole drilled, cleaned out and reinforcing steel secured in position. Take every care to ensure that hole is completely filled with concrete. *CONCRETE MUST BE PLACED IN THE DRY. UNDER NO CIRCUMSTANCES WILL TREMIE CONCRETE BE PERMITTED.*
- .5 Where steel casings are used they shall be withdrawn as the concrete is deposited, keeping the concrete at a level above bottom of the sleeve.
- .6 Vibrate top 3 M of concrete in shaft.
- .7 Protect tops of piles against loss of moisture.
- .8 Cold weather provisions of CAN/CSA A23.1-14 shall apply. Protect tops of piles against freezing during curing period with adequate insulation and covering. Provide supplementary heat as temperatures dictate.
- .9 When concrete is being placed through a frozen ground surface, the diameter of the portion of the pile surface passing through the frozen ground shall be increased by 100 mm.

3.5 CUTOFF AND LENGTH

- .1 Length of friction piles indicated on drawings to be from cutoff elevation.

END OF SECTION

Part 1 General

1.1 REFERENCES

- .1 Saskatchewan Highways and Transportation Specifications, January 1996.
- .2 American Society for Testing and Materials International, (ASTM)
 - .1 ASTM D698-00a, Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/ft³ (600 kN-m/m³)).

Part 2 Products

2.1 MATERIALS

- .1 Granular Sub-Base Course: Type 8 in accordance with Section 31 23 33.01 - Excavating, Trenching and Backfilling.
- .2 Granular Base Course: Type 32 or 33 in accordance with Section 31 23 33.01 - Excavating, Trenching and Backfilling.
- .3 Asphalt concrete: spreader-laid hot mix to Saskatchewan Highways and Transportation Mix Design Type 2 (Specification No. 4100). Use AC 150-200A asphalt cement as defined by Saskatchewan Highways and Transportation Specifications for Manufactures Materials (SMM101).

Part 3 Execution

3.1 PAVEMENT STRUCTURE / COMPACTION

- .1 Pavement structure thickness:
 - .1 50 mm asphalt concrete.
 - .2 150 mm Granular Base Course compacted to minimum of 100% Standard Proctor density.
 - .3 250 mm Granular Sub-Base Course compacted to minimum of 97% Standard Proctor density.

3.2 SUBGRADE PREPARATION

- .1 Remove loose fill and other deleterious materials from the proposed pavement area and compact the upper 150 mm of subgrade to at least 96 percent of standard Proctor density at optimum moisture content.
- .2 Provide geotextile with a grab tensile strength of 1000 N as required over subgrade soils.
- .3 In areas where there is to be no grade raise above the existing ground surface, excavate/subcut the clay to a minimum depth of 0.3 metres below the underside of the granular sub-base. Select clay removed during the subcut that is free from objectionable materials may be stockpiled in an approved storage area, for later re-use. If unconsolidated clay fills or unusually dry clays are encountered below the initial subcut depth, then the subcutting shall be increased to the underside of such materials.

- .4 The final excavated areas are to be inspected for approval. If any undesirable materials are found they shall be removed. Upon approval, scarify and moisture condition to a depth of 150 mm. Recompact subgrade to a minimum average of 96 percent of Standard Proctor maximum dry density, with no reading falling below 95 percent at a minimum of 1 to 2 percent above optimum moisture content. Compaction shall be undertaken using a heavy sheepfoot vibratory compactor. Should areas require special attention, take remedial construction measures to rectify.
- .5 Areas that require a grade raise above the existing ground surface or that will require a significant grade raise shall use select fill consisting of pit run sand, containing less than 10% particles finer than a 80um sieve, to the underside of the sub-base course. All granular fill placed above the subgrade elevation should be placed in thin lifts (maximum 150mm loose) and compacted to a minimum of 98% of standard Proctor density.
- .6 Grade finished subgrade surface to promote sub-drainage beneath the pavement structure.
- .7 Final surface elevations of paved areas shall be positively sloped towards catchbasins and as shown on grading drawing.
- .8 All fill materials are to be placed and uniformly compacted in 150mm maximum lifts.
- .9 Cohesive soils shall be compacted to the following:
 - .1 Bottom lifts: compact to minimum average 97 percent of Standard Proctor maximum dry density at a minimum of 1 to 2% wet of optimum water content. No individual density test shall be below 96% of Standard Proctor maximum dry density.
 - .2 Upper two lifts: (minimum combined thickness of 300mm) compact to minimum 98 percent of Standard Proctor maximum dry density at a minimum of 1% wet of optimum water content.
- .10 Do not allow prepared subgrade to dry out prior to placement of the sub-base material.

3.3 FIELD QUALITY CONTROL

- .1 Inspection and testing of asphalt paving will be carried out by designated testing laboratory.
- .2 Costs of tests will be paid by Contractor.

3.4 FINISH TOLERANCES

- .1 Finished asphalt surface to be within 5mm of design elevation but not uniformly high or low.
- .2 Finished asphalt surface not to have irregularities exceeding 5 mm when checked with 4.5m straight edge placed in any direction.

END OF SECTION

Part 1 General

1.1 ADMINISTRATIVE REQUIREMENTS

- .1 Scheduling:
 - .1 Schedule sod laying to coincide with preparation of soil surface.
 - .2 Schedule sod installation when frost is not present in ground.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for sod, geotextile and fertilizer and include product characteristics, performance criteria, physical size, finish and limitations.
 - .2 Submit 1 copy of WHMIS MSDS in accordance with Section 01 35 29.06 - Health and Safety Requirements.
- .3 Certificates: submit product certificates signed by manufacturer certifying materials comply with specified performance characteristics and criteria and physical requirements of seed mix, seed purity, and sod quality.

1.3 QUALITY ASSURANCE

- .1 Qualifications:
 - .1 Landscape Planting Supervisor: Landscape Industry Certified Technician with Softscape Installation designation.
 - .2 Landscape Maintenance Supervisor: Landscape Industry Certified Technician with Turf Maintenance designation.

1.4 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and in accordance with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials in accordance with supplier's recommendations.
 - .2 Replace defective or damaged materials with new.

Part 2 Products

2.1 MATERIALS

- .1 Number One Turf Grass Nursery Sod: sod that has been especially sown and cultivated in nursery fields as turf grass crop.

- .1 Turf Grass Nursery Sod types:
 - .1 Number One Kentucky Bluegrass Sod - Fescue Sod: Nursery Sod grown solely from seed mixture of cultivars of Kentucky Bluegrass and Chewing Fescue or Creeping Red Fescue, containing not less than 75% Kentucky Bluegrass cultivars and 15% Chewing Fescue or Creeping Red Fescue cultivar.
- .2 Turf Grass Nursery Sod quality:
 - .1 Not more than 1 broadleaf weed and up to 1% native grasses per 40 square metres.
 - .2 Density of sod sufficient so that no soil is visible from height of 1500 mm when mown to height of 50 mm.
 - .3 Mowing height limit: 35 to 65 mm.
 - .4 Soil portion of sod: 6 to 15 mm in thickness.
- .2 Sod establishment support:
 - .1 Geotextile fabric: biodegradable, Non-woven synthetic fibre fabric.
 - .2 Wooden pegs: 17 x 8 x 200 mm.
 - .3 Biodegradable starch pegs: 17 x 8 x 200 mm.
- .3 Water:
 - .1 Supplied by Departmental Representative at designated source.
- .4 Fertilizer:
 - .1 To Canada "Fertilizers Act" and Fertilizers Regulations.
 - .2 Complete, synthetic, slow release with 65% of nitrogen content in water-insoluble form.

2.2 SOURCE QUALITY CONTROL

- .1 Obtain written approval from Departmental Representative of sod at source.
- .2 When proposed source of sod is approved, use no other source without written authorization from Departmental Representative.

Part 3 Execution

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for sod installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 PREPARATION

- .1 Verify that grades are correct and prepared in accordance with Section 31 23 33 - Excavating, Trenching, and Backfilling. If discrepancies occur, notify Departmental Representative and commence work when instructed by Departmental Representative.
- .2 Do not perform work under adverse field conditions such as frozen soil, excessively wet soil or soil covered with snow, ice, or standing water.
- .3 Fine grade surface free of humps and hollows to smooth, even grade, to match existing elevations, to tolerance of plus or minus 8 mm, for Turf Grass Nursery Sod, surface to drain naturally.
- .4 Remove and dispose of weeds; debris; stones 50 mm in diameter and larger; soil contaminated by oil, gasoline and other deleterious materials; off site in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.

3.3 SOD PLACEMENT

- .1 Ensure sod placement is done under supervision.
- .2 Lay sod within 24 hours of being lifted if air temperature exceeds 20 degrees C.
- .3 Lay sod sections in rows, joints staggered. Butt sections closely without overlapping or leaving gaps between sections. Cut out irregular or thin sections with sharp implements.
- .4 Roll sod as per supplier's written instructions. Provide close contact between sod and soil by light rolling. Use of heavy roller to correct irregularities in grade is not permitted.

3.4 SOD PLACEMENT ON SLOPES AND PEGGING

- .1 Install and secure geotextile fabric in areas indicated, in accordance with manufacturer's instructions.
- .2 Start laying sod at bottom of slopes.
- .3 Peg sod on slopes steeper than 3 horizontal to 1 vertical, within 1 m of catch basins and within 1 m of drainage channels and ditches to following pattern:
 - .1 100 mm below top edge at 200 mm on centre for first sod sections along contours of slopes.
 - .2 Not less than 6 pegs per square metre.
 - .3 Not less than 9 pegs per square metre in drainage structures. Adjust pattern as directed by Departmental Representative.
 - .4 Drive pegs to 20 mm above soil surface of sod sections.

3.5 FERTILIZING PROGRAM

- .1 Fertilize during establishment and warranty periods. Fertilize at application rates as per printed instruction from fertilizer manufacturer.

3.6 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Leave Work area clean at end of each day.

- .2 Keep pavement and area adjacent to site clean and free from mud, dirt, and debris at all times.

- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.

- .1 Clean and reinstate areas affected by Work.

3.7 PROTECTION BARRIERS

- .1 Protect newly sodded areas from deterioration with snow fence on rigid frame.
- .2 Remove protection after inspection and acceptance from Departmental Representative.

3.8 MAINTENANCE DURING ESTABLISHMENT PERIOD

- .1 Perform following operations from time of installation until acceptance.
 - .1 Water sodded areas in sufficient quantities and at frequency required to maintain optimum soil moisture condition to depth of 75 to 100 mm.
 - .2 Cut grass to 50 mm when or prior to it reaching height of 75mm.
 - .3 Maintain sodded areas 95% weed free.
 - .4 Fertilize areas in accordance with fertilizing program. Spread half of required amount of fertilizer in one direction and remainder at right angles. Water immediately following application.
 - .5 Temporary barriers or signage to be maintained where required to protect newly established sod.

3.9 ACCEPTANCE

- .1 Turf Grass Nursery Sod areas will be accepted by Departmental Representative provided that:
 - .1 Sodded areas are properly established.
 - .2 Sod is free of bare and dead spots.
 - .3 No surface soil is visible from height of 1500 mm when grass has been cut to height of 50 mm.
 - .4 Sodded areas have been cut minimum 2 times prior to acceptance.
- .2 Areas sodded in fall will be accepted in following spring one month after start of growing season provided acceptance conditions are fulfilled.
- .3 When environmental conditions allow, all sodded areas showing shrinkage cracks shall be top-dressed and seeded with a seed mix matching the original.

3.10 MAINTENANCE DURING WARRANTY PERIOD

- .1 Perform following operations from time of acceptance until end of warranty period:
 - .1 Water sodded Turf Grass Nursery Sod areas at weekly intervals to obtain optimum soil moisture conditions to depth of 100 mm.
- .2 Repair and resod dead or bare spots to satisfaction of Departmental Representative.

- .3 Cut grass and remove clippings as directed by Departmental Representative to height as follows:
 - .1 Turf Grass Nursery Sod:
 - .1 50 mm during normal growing conditions.
 - .2 Cut grass at 2-week intervals or as directed by Departmental Representative, but at intervals so that approximately one third of growth is removed in single cut.
 - .3 Fertilize areas in accordance with fertilizing program. Spread half of required amount of fertilizer in one direction and remainder at right angles and water in well.
 - .4 Eliminate weeds by mechanical or chemical means to extent acceptable to Departmental Representative.

END OF SECTION

Part 1 General

1.1 REFERENCE STANDARDS

- .1 ASTM International
 - .1 ASTM D698-07e1, Standard Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/ft³(600 kN-m/m³
- .2 CSA International
 - .1 CSA A23.1/A23.2-09, Concrete Materials and Methods of Concrete Construction/Test Methods and Standard Practices for Concrete.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for drainage material and include product characteristics, performance criteria, physical size, finish and limitations.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials in accordance with manufacturer's recommendations.
 - .2 Store and protect from damage.
 - .3 Replace defective or damaged materials with new.

1.4 SITE CONDITIONS

- .1 Known underground utility lines and buried objects are as indicated on plans. Locate, verify, and protect all underground services utilities prior to commencement of work.

Part 2 Products

2.1 BEDDING AND SURROUND MATERIALS

- .1 Flexible plastic tubing and fittings: perforated, nominal inside diameter 150 mm.
- .2 Granular drain rock: see Section 31 23 33.01 - Excavating, Trenching and Backfilling.
- .3 Geotextile filter: see Section 31 23 33.01 - Excavating, Trenching and Backfilling.

2.2 BACKFILL MATERIAL

- .1 Type 2, in accordance with Section 31 23 33.01 - Excavating, Trenching and Backfilling.
- .2 Excavated or graded material existing on site may be suitable to use if approved by Departmental Representative.

Part 3 Execution

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for drainage materials installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.
- .2 Make sure graded base conforms with required drainage pattern before placing bedding material.
- .3 Make sure improper slopes, unstable areas, areas requiring additional compaction or other unsatisfactory conditions are corrected to approval of Departmental Representative.

3.2 BEDDING PREPARATION

- .1 Cut trenches in subgrade and place bedding materials in uniform layers not exceeding 150 mm compacted thickness to depth as indicated.
- .2 Shape bed true to grade and to provide continuous, uniform bearing surface for tubing.
- .3 Shape transverse depressions, as required, to suit joints.
- .4 Compact each layer full width of bed to at least 95% maximum density to ASTM D698.
- .5 Fill excavation below design elevation of bottom of specified bedding with compacted bedding material.

3.3 PIPE OR TUBING INSTALLATION

- .1 Make sure tubing interior and coupling surfaces are clean before laying.
- .2 Lay perforated tubing to slope of 1:150. For pipe face perforations and coupling slots downward.
- .3 Grade bedding to establish tubing slope.
- .4 Install end plugs at ends of collector drains to protect tubing ends from damage and ingress of foreign material.
- .5 Provide flush cleanouts where directed by Departmental Representative.
- .6 Connect drainage system to building weeping tile system, as indicated.

3.4 PIPE OR TUBING SURROUND MATERIAL

- .1 Upon completion of tubing laying and after Departmental Representative has reviewed and approved Work in place, surround, cover and install geotextile filter and tubing as indicated.
- .2 Hand place surround material in uniform layers not exceeding 150 mm compacted thickness, as indicated. Do not drop material within 300 mm of tubing.
- .3 Place layers uniformly and simultaneously on each side of tubing.
- .4 Compact each layer from tubing invert to mid-height of tubing to at least 95% maximum density to ASTM D698.
- .5 Compact each layer from mid-height of tubing to underside of backfill to at least 95% maximum density to ASTM D698.
- .6 Place low strength unshrinkable fill where compaction cannot be achieved using mechanical methods.

3.5 BACKFILL MATERIAL

- .1 Place backfill material above tubing surround in uniform layers not exceeding 150 mm compacted thickness up to grades as indicated.
- .2 Compact to at least 95% maximum density to ASTM D698.
- .3 Use appropriate compaction equipment.
 - .1 Conduct hand tamping around confined areas of pipe.
 - .2 Do not use water or other hydraulic means to place or consolidate backfill material.

3.6 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
- .3 Waste Management: separate waste materials for recycling and reuse in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

END OF SECTION