

# HX55360001

HX55-P

## HX55-P R LED 115/230 NC MODULE PROTECTION

Elnumber:

EAN-nr: 4036538580055

Stock code: M

Perimeter lights are used to mark and illuminate the perimeter of helideck. These lights help the helicopter pilots to locate the helideck for safe landing at night. Perimeter lights are available as surface mounted versions in different types of assembly, but the product series also includes recessed versions.



Technical data	
IP classification	67
Maximum ambient temperature (°C)	55
Minimum ambient temperature (°C)	-40
EX gas classification	Ex
Dimensions	
Net weight (kg)	4
Gross weight (kg)	4.4
Diameter (mm)	216
Length (mm)	142
Body	
Colour of body	Black
Body material	Aluminium
Optic	
Material of diffuser	Polycarbonate
Optic	LENS Clear

Electrical data	
Maximum frequency +5% (Hz)	60
Maximum voltage +10% (V)	230
Minimum frequency -5% (Hz)	50
Minimum Voltage -10% (V)	115
Light data	
Light source	LED Green
Termination	
Type of cable gland	M20-Polyamide
Number of cable glands	1
Minimum cable diameter	6
Maximum cable diameter	13
Ready for mounting	Recessed
Remarks	
Remarks	With base container adapter, with module protection.