



































































LEGEND		
LINE TYPES	SYMBOL	DESCRIPTION
———— NEW/PROPOSED WORK ——— OR E INDICATES EXISTING TO REMAIN ----- OR X INDICATES DEMOLITION ——— ENCLOSURE R INDICATES RELOCATION	                 	FUSIBLE DISCONNECT SWITCH VARIABLE SPEED CONTROL FIRE ALARM PANEL FIRE ALARM HORN FIRE ALARM COMBINATION HORN/STROBE FIRE ALARM MANUAL PULL STATION FIRE ALARM HEAT DETECTOR THERMOSTAT, WALL MOUNTED UTILITY METER POWER TRANSFORMER CURRENT TRANSFORMER POTENTIAL TRANSFORMER CIRCUIT BREAKER DISCONNECT SWITCH, NON-FUSIBLE MOTOR OVERLOAD CONTACT CONTACTOR OR RELAY COIL DOOR OPERATOR PUSH PLATE SWITCH
SYMBOL	DESCRIPTION	
 A — INDICATES FIXTURE TYPE b — INDICATES CONTROL GROUP B-21 — INDICATES CIRCUIT NUMBER X — INDICATES FLUORESCENT OR INCANDESCENT FIXTURE TO BE DEMOLISHED		
 77x610mm FIXTURE		
 202x1219mm FIXTURE		
 304x1219mm RECESSED FIXTURE		
 WALL MOUNTED LINEAR FIXTURE		
 DOWN LIGHT FIXTURE, SUSPENDED		
 DOWN LIGHT FIXTURE, RECESS MOUNTED		
 WALLPACK		
 TRACK LIGHT		
  TYPICAL FOR ALL SWITCH SYMBOLS		
  		
 LIGHT SWITCH 1, 2, 3, AND 4 GANG RESPECTIVELY		
 a — INDICATES CONTROL GROUP LV — INDICATES LOW VOLTAGE		
 a — INDICATES CONTROL GROUP		
 a — INDICATES CONTROL GROUP		
 a — INDICATES CONTROL GROUP		
 DC-1 — INDICATES DC SOURCE		
 DC-1 — INDICATES DC SOURCE		
 DC-1 — INDICATES DC SOURCE		
 SHADING — INDICATES PICTOGRAM ORIENTATION ARROW — INDICATES DIRECTION OF EGRESS		
 EXIT SIGN & EMERGENCY LIGHTING COMBINATION UNIT, WALL MOUNTED		
 TELEPHONE (VOICE) OUTLET		
 DATA OUTLET		
 WP — INDICATES WEATHERPROOF C/W COVER GFCI — INDICATES GROUND FAULT CIRCUIT INTERRUPTER		
 GFCI — INDICATES GROUND FAULT CIRCUIT INTERRUPTER WP — INDICATES WEATHERPROOF C/W COVER		
 DUPLEX RECEPTACLE, MOUNTED IN CEILING		
 DUPLEX SPLIT CIRCUIT RECEPTACLE		
 GFCI — INDICATES GROUND FAULT CIRCUIT INTERRUPTER		
 SINGLE RECEPTACLE 240V, MOUNTED ABOVE COUNTER TOP		
 GENERATOR INLET		
 POWER DIRECT CONNECTION		
 SINGLE PHASE MOTOR		
 WP — INDICATES WEATHERPROOF		
 PANELBOARD, RECESS MOUNTED		
 PANELBOARD, SURFACE MOUNTED		
 CONTROL PANEL		
 MISCELLANEOUS EQUIPMENT		
 MANUAL MOTOR STARTER		
 MAGNETIC MOTOR STARTER		

LUMINAIRE SCHEDULE				
TYPE	DESCRIPTION	APPROVED PRODUCTS	LAMP(S)	MOUNTING
A	LED LINEAR 1.2m STRIP LIGHTING, 120V, CSA OR cUL APPROVED	PHILIPS: #FSS-4-40L-840-UNV-DIM LITHONIA: #4SNLED-LD5-41SL-LN-UNV-L840-CD1-U HUBBEL: #CSL4-4040	LED 4000 LUMEN 4000K CCT 80 CRI 31W	MOUNTED ON CEILING JOISTS.
B	WALL MOUNTED LED LIGHT, WEATHER PROOF IP65 RATED, 120V, RATED FOR BUILDING EXTERIOR, IDA DARK-SKY APPROVED, BLACK COLOUR, CSA OR cUL APPROVED	BEGA: #33329-K27 LIGMAN: #8WLED-W27-01-120 	LED 366 LUMEN 2700K CCT 90 CRI 6W	WALL MOUNTED
C1	LED LINEAR STRIP LIGHTING, 610mm, 120V, CSA OR cUL APPROVED.	LITHONIA: #2SNLED-LD5-18SL-LN-L840 ATARA: #54260144	LED 1800 LUMEN 4000K CCT 80 CRI 16W	CEILING MOUNTED UNLESS INDICATED AS SUSPENDED
C2	LED LINEAR STRIP LIGHTING, 1220mm, 120V, CSA OR cUL APPROVED.	LITHONIA: #4SNLED-LD5-18SL-LN-L840 ATARA: #54261143	LED 1800 LUMEN 4000K CCT 80 CRI 14W	CEILING MOUNTED UNLESS INDICATED AS SUSPENDED
D	ROUND LED DOWNLIGHT, 120V, NON-IC RATED, RATED FOR DAMP LOCATIONS, CSA OR cUL APPROVED.	SPEC LIGHTING: #SR3MO-XT30L-E-1-RD3N-27K-WD-MW-WL LITHONIA: #LDN7RV-27/30-LR-7-AR-LD-MVOLT-GZ10-WL ELITE: #HH6-LED-3000L-DIM10-120-WD-27K-85+-6501-CL-WH	LED 3000 LUMEN 2700K CCT 80 CRI 34W	RECESSED IN CEILING
F	152mm LED ROUND DOWNLIGHT, RATED FOR DAMP LOCATIONS, 120V, CSA OR cUL APPROVED	PHILIPS: #L6RRE1VA-L6R15827VA-L6RDW LITHONIA: #LDN6RV-40/15-LR-6-AR-LD-120-GZ10-WL ELITE: #1500L-DIM10-120-MD-85+-LED-6115-CL-WH	LED 1500 LUMEN 4000K CCT 80 CRI 13W	RECESSED IN CEILING
G	SURFACE MOUNTED LED LINEAR 1.2m LIGHTING, 120V, CSA OR cUL APPROVED.	PHILIPS: #FSW-4-40L-840-UNV-DIM LITHONIA: #BLWP4-40L-ADSM-MVOLT-GZ10-LP840 CREE: #S-WR-4-40L-40K-10V	LED 4000 LUMEN 4000K CCT 80 CRI 31W	CEILING MOUNTED
H1	152mm RECESSED LED POT LIGHT, 0-10V DIMMING, 120V, CSA OR cUL APPROVED	LITHONIA: #LDN6-40/10-L06-AR-LD-120-GZ10 PHILIPS: #DN589B LED10/840 PSD C D150 WH WB WP GM CREE: #LR6-10L-40K-GU24	LED 1000 LUMEN 4000K CCT 80 CRI 13W	RECESSED IN CEILING
H2	152mm RECESSED LED POT LIGHT, 0-10V DIMMING, 120V, CSA OR cUL APPROVED	LITHONIA: #LDN6-40/15-L06-AR-LD-120-GZ10 PHILIPS: #L6RRZ101VA-L6R158040VA-L6RDD CREE: #CR6T-1600L-40K-12-E26GU24	LED 1500 LUMEN 4000K CCT 80 CRI 21W	RECESSED IN CEILING
J	102mm SUSPENDED LED POT LIGHT, 0-10V DIMMING, 120V, CSA OR cUL APPROVED	SYSTEMLUX: 1770-B0-830-50 LITELINE: #APF7015-30-38-WH EATON: LSR6B-10-D010-P-EC6B-80-30-6LB-M-0-LI	LED 1000 LUMEN 3000K CCT 80 CRI 13W	SUSPENDED FROM CEILING 3.0m A.F.F.
K	LED LINEAR 1.2m STRIP LIGHTING WITH WIREGUARD, 120V, CSA OR cUL APPROVED	PHILIPS: #FSS-4-55-L840-UNV-DIM-FSSWG4 LITHONIA: #ZL1D-L48-5000LM-FST-MVOLT-40K-80CRI-WH-WGZ48	LED 5500 LUMEN 4000K CCT 80 CRI 45W	SUSPENDED FROM CEILING 3.0m A.F.F.
QA	LED TRACK HEAD, INTEGRATED HEAT SINK, DIMMING 120V, CSA OR cUL APPROVED, COMPLETE WITH TWO CIRCUIT TRACK.	PHILIPS: #TH-10-9-30-NF-1-W ALCON: #13118-W-25-DLV-30K-C90 LITON: #LTD37410B-B25-DLV-T30-C90 SISTEMALUX: #1770-B0-930-20-120-01-D10	LED 1100 LUMEN 3000K CCT 90 CRI 16W	CEILING MOUNTED
QB	LED TRACK HEAD, INTEGRATED HEAT SINK, DIMMING 120V, CSA OR cUL APPROVED, COMPLETE WITH: TWO CIRCUIT TRACK, SUSPENSION TRUSS, AND CABLE SUSPENSION WITH CEILING CANOPY.	PHILIPS: #TH-10-9-30-NF-1-W ALCON: #13118-W-25-DLV-30K-C90 LITON: #LTD37410B-B25-DLV-T30-C90 SISTEMALUX: #1770-B0-930-20-120-01-D10	LED 1100 LUMEN 3000K CCT 90 CRI 16W	SUSPENDED FROM CEILING 3.0m A.F.F.
QC	LED TRACK HEAD, INTEGRATED HEAT SINK, DIMMING 120V, CSA OR cUL APPROVED, COMPLETE WITH: TWO CIRCUIT TRACK, SUSPENSION TRUSS, AND CABLE SUSPENSION WITH CEILING CANOPY.	PHILIPS: #TH-10-9-30-NF-1-W ALCON: #13118-W-25-DLV-30K-C90 LITON: #LTD37410B-B25-DLV-T30-C90 SISTEMALUX: #1770-B0-930-20-120-01-D10	LED 1100 LUMEN 3000K CCT 90 CRI 16W	SUSPENDED FROM CEILING 4.0m A.F.F.
QD	LED TRACK HEAD, INTEGRATED HEAT SINK, DIMMING 120V, CSA OR cUL APPROVED, COMPLETE WITH: BASIC TRACK, SUSPENSION TRUSS, AND CABLE SUSPENSION WITH CEILING CANOPY.	PHILIPS: #TH-10-9-30-NF-1-W ACLON: #13118-W-25-DLV-30K-C90 LITON: #LTD37410B-B25-DLV-T30-C90 SISTEMALUX: #1770-B0-930-20-120-01-D10	LED 1100 LUMEN 3000K CCT 90 CRI 16W	MOUNTED ON TOP OF FRAMING 2.1m ABOVE ELEVATED PLATFORM
QE	LED TRACK HEAD, INTEGRATED HEAT SINK, DIMMING 120V, CSA OR cUL APPROVED, COMPLETE WITH: BASIC TRACK, SUSPENSION TRUSS, AND CABLE SUSPENSION WITH CEILING CANOPY.	PHILIPS: #TH-10-9-30-NF-1-W ACLON: #13118-W-25-DLV-30K-C90 LITON: #LTD37410B-B25-DLV-T30-C90 SISTEMALUX: #1770-B0-930-20-120-01-D10	LED 1100 LUMEN 3000K CCT 90 CRI 16W	MOUNTED ON UNDERSIDE OF FRAMING 1.8m ABOVE ELEVATED PLATFORM
RA	LED TRACK HEAD, INTEGRATED HEAT SINK, DIMMING 120V, CSA OR cUL APPROVED, COMPLETE WITH BASIC TRACK.	PHILIPS: #LC-06-930-W-TE JUNO: #T252L-30K-90CRI-NFL ALCON: #13104-10-WH-25-30K-120-1	LED 600 LUMEN 3000K CCT 90 CRI 10W	CEILING MOUNTED AT 2.7m A.F.F.
RB	LED TRACK HEAD, INTEGRATED HEAT SINK, DIMMING 120V, CSA OR cUL APPROVED, COMPLETE WITH: BASIC TRACK, SUSPENSION TRUSS, AND CABLE SUSPENSION WITH CEILING CANOPY.	PHILIPS: #LC-06-930-W-TE JUNO: #T252L-30K-90CRI-NFL ALCON: #13104-10-WH-25-30K-120-1	LED 600 LUMEN 3000K CCT 90 CRI 10W	CEILING MOUNTED AT 3.0m A.F.F.

EMERGENCY AND EXIT LIGHTING SCHEDULE				
TYPE	DESCRIPTION	MANUFACTURER'S CATALOGUE NO.	LAMP(S)	MOUNTING
	EMERGENCY LIGHTING BATTERY UNIT C/W DUAL HEADS, 36W / 12V BATTERY, 120VAC INPUT, 4W LED HEADS, CSA APPROVED.	STANPRO #SLA-12036-2S-4WLR-WH AIMLITE #EBST-12036-2MD-4WLR-WHT LUMACELL #RG12S-36-2-LD7	2 — 4W/12V LED	WALL MOUNTED AT 2.3m A.F.F.
	DUAL HEAD REMOTE MOUNTED EMERGENCY LIGHTING FIXTURE, 4W, 12V LED HEADS, CSA APPROVED.	STANPRO #S2-06-24-4W-LR-WH AIMLITE #RMMD-2-06-24-4W-LR-WHT LUMACELL #M-QM-2-LD7	2 — 4W/12V LED	WALL MOUNTED AT 2.3m A.F.F.
	EMERGENCY LIGHTING PICTOGRAM COMBINATION UNIT C/W DUAL HEADS, 36W / 12V BATTERY, 120VAC INPUT, 4W LED HEADS, CSA APPROVED.	STANPRO: #PRMPN-2 AIMLITE: #CPRNR-2 LUMACELL: #LCSC-2LEDWR	2 — 4W/12V LED	WALL MOUNTED ABOVE DOOR
	WALL MOUNTED ILLUMINATED EXIT SIGN, RUNNING MAN PICTOGRAM, 120VAC/12VDC, BATTERY BACK-UP, SINGLE FACE.	STANPRO: #RMPS-1-WH-UDC AIMLITE: #RPSP-1-WHT-UNVDC LUMACELL: #LCS-U	LED	WALL MOUNTED ABOVE DOOR



Government of Canada


Gouvernement du Canada


Parks Canada

Parcs Canada

Newfoundland East Field Unit

Unité de gestion de Terre-neuve Est



C02	2018/11/28	ISSUED FOR ADDENDUM	S.M.	
C01	2018/10/15	ISSUED FOR TENDER	L.M.	
No.	Date	Description	Drawn by Dessiné par	Approved Approuvé

A

B


Detail number  
Sheet number

A Numéro de détail  
B Numéro de la feuille

Linear dimensions  
en millimètres

Dimensions linéaires  
en millimètres

Consultant's Name  
Nom de l'expert-conseil



SNC • LAVALIN

SNC • LAVALIN Inc.  
Halifax, Nova Scotia, Canada  
Member of the SNC • LAVALIN Group

Eng. Stamp  
Sceau de l'ingénieur

Project title/Titre du projet

TERRA NOVA VISITOR CENTRE  
REHABILITATION UPGRADES

GLOVERTOWN, NL

Drawing title/Titre du dessin

LEGEND & LUMINAIRE  
SCHEDULES

Designed by/Concept par  
S.M.

Date  
2018/08/29

Drawn by/Dessiné par  
S.M.

Date  
2018/08/29

Checked by/Vérifié par  
D.C. / J.L.

Date  
—

Project No./No. du projet  
1326

Scale/Echelle  
N.T.S.

Sheet No./  
Nude la feuille

Drawing Set No./No. de série du dessin  
E-01

GSC-A1