



1. Is the Contractor's responsibility to refer to all information in the Specification Document.
2. Is the Contractor's responsibility to refer to this drawing in conjunction with all other drawings in this package. Report any discrepancies between drawings to prior to commencing with construction.
3. Contractor will be held responsible for any damage done to existing partitions, ceiling, finishes and all other components to remain and to adjacent spaces.
4. Symbols are for quantity and location only. Refer to Electrical drawings for additional information.
5. All light fixtures to be centered within acoustical ceiling tiles, unless otherwise noted.
6. All light fixture dimensions are O.C., unless noted otherwise.
7. Contractor to ensure location of ceiling lights do not interfere with any structural or mechanical components. Advise Department Representative of any conflicts prior to ordering fixtures and commencing work. Contractor will be responsible for the cost of relocating any new building construction should he fail to report conflicts prior to installation.
8. Contractor to mark location of wall mounted, recessed down light and pendant light fixtures for approval by Department Representative prior to installation. Acoustical ceiling tiles and/or gypsum board will not be approved to be replaced or repaired by the Contractor at own expense.
9. Contractor to remove and re-install suspended T-bar ceiling grid as required for mechanical demolition. Refer to Mechanical drawings. Contractor to avoid cutting main suspension "T's" wherever possible.
10. Contractor to supply and install new suspended T-bar ceiling grid at heights specified on drawings.
11. All new and existing gypsum board ceiling and bulkhead to be painted P1, unless otherwise noted.
12. Replace any existing suspension "T's" that are bent or severely damaged.
13. Supply and install suspended T-bar ceiling grid cover plates where required to patch perforations within T-bar grid from previous partition. Contractor to carry allowances of \$800 Style and color to match existing. Ensure transition is smooth and seamless.
14. Refer to Electrical drawings for electrical outlet location within ceiling plenum for sound masking speakers.

