



RETURN BIDS TO:

RETOURNER LES SOUMISSIONS À:

Bid Receiving - PWGSC / Réception des soumissions -
TPSGC

11 Laurier St./ 11, rue Laurier

Place du Portage, Phase III

Core 0B2 / Noyau 0B2

Gatineau, Québec K1A 0S5

Bid Fax: (819) 997-9776

SOLICITATION AMENDMENT MODIFICATION DE L'INVITATION

The referenced document is hereby revised; unless otherwise indicated, all other terms and conditions of the Solicitation remain the same.

Ce document est par la présente révisé; sauf indication contraire, les modalités de l'invitation demeurent les mêmes.

Comments - Commentaires

Vendor/Firm Name and Address

Raison sociale et adresse du
fournisseur/de l'entrepreneur

Issuing Office - Bureau de distribution

Clothing and Textiles Division / Division des vêtements
et des textiles

L'Esplanade Laurier,

East Tower 7th Floor

Tour est 7e étage

140 O'Connor, rue O'Connor,

Ottawa

Ontario

K1A 0R5

Title - Sujet General Purpose Combat Boots	
Solicitation No. - N° de l'invitation W8486-184068/B	Amendment No. - N° modif. 010
Client Reference No. - N° de référence du client 6000394288	Date 2019-08-12
GETS Reference No. - N° de référence de SEAG PW-\$\$PR-760-77166	
File No. - N° de dossier pr760.W8486-184068	CCC No./N° CCC - FMS No./N° VME
Solicitation Closes - L'invitation prend fin at - à 02:00 PM on - le 2019-09-24	
Time Zone Fuseau horaire Eastern Daylight Saving Time EDT	
F.O.B. - F.A.B. Plant-Usine: <input type="checkbox"/> Destination: <input type="checkbox"/> Other-Autre: <input type="checkbox"/>	
Address Enquiries to: - Adresser toutes questions à: Richard, Josette	Buyer Id - Id de l'acheteur pr760
Telephone No. - N° de téléphone (613) 462-4128 ()	FAX No. - N° de FAX (613) 943-7970
Destination - of Goods, Services, and Construction: Destination - des biens, services et construction:	

Instructions: See Herein

Instructions: Voir aux présentes

Delivery Required - Livraison exigée	Delivery Offered - Livraison proposée
Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur	
Telephone No. - N° de téléphone Facsimile No. - N° de télécopieur	
Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)	
Signature	Date

AMENDMENT 010

This amendment is raised to answer questions from potential bidders.

QUESTION 33:

If the Direct injection bidders are afforded the option to use an insole of Texon then can the same option be given to the Goodyear welt bidders as the material can be used in both processes?

Texon is a less expensive material than Summuntex (with less cushion I must add) and we feel that the only reason the Direct Injection bidders have asked for this option is to gain an advantage on price.

It is our position that the boot made with an insole of Summuntex will provide the forces with a more comfortable piece of footwear than one made with Texon.

ANSWER:

DSSPM 2-3-87-6449 specifies a technical and/or performance requirements and not specific name brands. DND will allow submissions utilizing insoles conforming to either Annex B, paragraph 3.6.12.1 to 3.6.12.3 inclusive or 3.6.12.4 regardless of sole attachment method.

As a result, the following amendment is made to Annex B:

Delete paragraph 3.6.12.4 in its entirety. Replace with the following:

"3.6.12.4 Alternate Requirements for Insoles: As an alternate to the requirements for insoles identified in paragraph 3.6.12.1 to 3.6.12.3 inclusive, insoles utilized in the boot must be cut from cellulose material with no recycled content applicable for use in Goodyear Welt or injection moulded construction. It must be a minimum of 2.5 mm gauge. The insole must be resistant to bacterial and fungal growth."

QUESTION 34:

In amendment #7 questions 26 and 27 a bidder asked for the correct way to measure the thickness of the rubber outsole and referenced the minimum thickness of 8 mm for the DND 602-1 outsole.

In amendment #4 question 14 it was brought up that the measurement of the DND 602-1 outsole was incorrect and the thickness at the forepart of the outsole was revised to 13mm.

Please confirm that the dimensions of the DND 602-1 outsole are to be 13mm at the forepart of the outsole and 30mm at the heel +/- .5mm.

ANSWER:

To clarify:

- a. Question 26 and Question 27 referenced Annex B, paragraph 3.6.14.6.3 which details thickness of the rubber used as the outsole when utilizing an outsole and tread pattern design option **other than DND 602-1** (all others identified in Table V as Option 2 to 6 inclusive); and
- b. Question 14 references Annex A, paragraph 3.6.14.1 (finished thickness of the sole components) and references Table V, outsole Option 1 (**unit sole using mold DND 602-1**). As stated in the response for Question 14, for this requirement, DND requires the thickness of the DND 602-1 unit sole to be 13 mm at the forepart and 30 mm at the heel.

All other terms and conditions remain unchanged.