
PART 1 GENERAL

1.1 REFERENCE STANDARDS

- .1 ASTM International
 - .1 ASTM F1913-04(2014), Standard Specification for Sheet Vinyl Floor Covering without Backing.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for resilient sheet flooring and include product characteristics, performance criteria, physical size, finish and limitations.
- .3 Samples:
 - .1 Submit duplicate 300 x 300 mm sample pieces of sheet material, 300 mm long base and treads.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials indoors in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect specified materials from nicks, scratches, and blemishes.
 - .3 Replace defective or damaged materials with new.

1.4 SITE CONDITIONS

- .1 Ambient Conditions:
 - .1 Maintain air temperature and structural base temperature at flooring installation area above 20 degrees for 48 hours before, during and 48 hours after installation.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Sheet vinyl without backing: to ASTM F 1913, commercial.
 - .1 Type: II - PVC binder content 34%.

- .2 Pattern: embossed.
 - .3 Texture: printed to simulate marble.
 - .4 Colour: selected by Departmental Representative.
 - .5 Thickness: 2 mm.
 - .6 Description: an unbacked, non-layered, homogeneous sheet vinyl flooring. Protected by a UV-cured polyurethane finish, colour and pattern detail dispersed uniformly throughout the insoluble in water, and resistant to cleaning agents and light.
- .2 Resilient base: continuous, top set, complete with premoulded end stops and external corners:
- .1 Type: rubber.
 - .2 Style: cove.
 - .3 Thickness: 2.03 mm.
 - .4 Height: 101.6 mm.
 - .5 Lengths: cut lengths minimum 2400 mm.
 - .6 Colour: selected by Departmental Representative.
- .3 Resilient stair tread: vinyl, 50 mm vertical face, round nose, full tread deep, 5 mm thick, ribbed surface with contrasting colour strip for the visually impaired:
- .1 Photoluminescent Visually Impaired Vinyl Stair Treads – flooring accessories as shown in the finish schedule or listed herein as vinyl stair treads shall be Photoluminescent Visually-Impaired Vinyl Stair Treads and be designated by style PVIHD:
 - .1 Square nosing, nose shall have a depth of 5.0 cm and the underside hinges to accommodate various ADA recommended stair pan angles.
 - .2 Continuous 5.0 cm wide band and nose edge accent strip of photoluminescent material co-extruded into the stair tread.
 - .3 The photoluminescent material shall have a photometric value of not less than 3.5 hours when tested in accordance with SIN Specification #67510-1.
 - .4 The colour shall be selected by the Departmental Representative.
 - .5 Stair risers: vinyl, solid colour pattern, colour as selected by Departmental Representative.
- .4 Primers and adhesives: of types recommended by resilient flooring manufacturer for specific material on applicable substrate, above, on or below grade.
- .5 Sub-floor filler and leveller: white premix latex requiring water only to produce cementitious paste as recommended by flooring manufacturer for use with their product.
- .6 Metal edge strips:
- .1 Aluminum extruded, smooth, mill finish stainless steel with lip to extend under floor finish, shoulder flush with top of adjacent floor finish.
- .7 External corner protectors: stainless steel, type recommended by flooring manufacturer.
- .8 Edging to floor penetrations: stainless steel, type recommended by flooring manufacturer.
- .9 Sealer and wax: type recommended by resilient flooring material manufacturer for material type and location.

PART 3 EXECUTION

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for resilient sheet flooring installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied.

3.2 SITE VERIFICATION OF CONDITIONS

- .1 Ensure concrete floors are clean and dry by using test methods recommended by flooring manufacturer.

3.3 PREPARATION

- .1 Remove existing resilient flooring.
- .2 Remove or treat old adhesives to prevent residual, old flooring adhesives from bleeding through to new flooring and/or interfering with the bonding of new adhesives.
- .3 Clean floor and apply filler; trowel and float to leave smooth, flat hard surface. Prohibit traffic until filler cured and dry.
- .4 Remove sub-floor ridges and bumps. Fill low spots, cracks, joints, holes and other defects with sub-floor filler.
- .5 Prime concrete slab to resilient flooring manufacturer's printed instructions.

3.4 APPLICATION: FLOORING

- .1 Provide high ventilation rate, with maximum outside air, during installation, and for 48 to 72 hours after installation. If possible, vent directly to outside. Do not let contaminated air recirculate through district or whole building air distribution system. Maintain extra ventilation for at least 1 month following building occupation.
- .2 Apply adhesive uniformly using recommended trowel. Do not spread more adhesive than can be covered by flooring before initial set takes place.
- .3 Lay flooring with seams parallel to building lines to produce a minimum number of seams. Border widths minimum 1/3 width of full material.
- .4 Run sheets in direction of traffic. Double cut sheet joints heat weld according to manufacturer's printed instructions.
- .5 As installation progresses, and after installation roll flooring with 45 kg minimum roller to ensure full adhesion.
- .6 Cut flooring around fixed objects.
- .7 Install feature strips and floor markings where indicated. Fit joints tightly.
- .8 Install flooring in pan type floor access covers. Maintain floor pattern.
- .9 Continue flooring over areas which will be under built-in furniture.
- .10 Continue flooring through areas to receive movable type partitions without interrupting floor pattern.
- .11 Terminate flooring at centreline of door in openings where adjacent floor finish or colour is dissimilar.
- .12 Install metal edge strips at unprotected or exposed edges where flooring terminates.

3.5 APPLICATION: STAIRS

- .1 Install stair treads and stair risers one piece for full width of stair. Adhere over entire surface and fit accurately.

3.6 APPLICATION: BASE

- .1 Lay out base to keep number of joints at minimum.
- .2 Clean substrate and prime with one coat of adhesive.
- .3 Apply adhesive to back of base.
- .4 Set base against wall and floor surfaces tightly by using 3 kg hand roller.
- .5 Install straight and level to variation of 1:1000.
- .6 Scribe and fit to door frames and other obstructions. Use premoulded end pieces at flush door frames.
- .7 Cope internal corners. Use premoulded corner units for right angle external corners. Use formed straight base material for external corners of other angles.
- .8 Use toeless type base where floor finish will be carpet, coved type elsewhere.
- .9 Install toeless type base before installation of carpet on floors.
- .10 Heat weld base in accordance with manufacturer's printed instructions.

3.7 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
 - .1 Clean flooring and base surfaces to flooring manufacturer's printed instructions.

3.8 PROTECTION

- .1 Protect new floors from time of final set of adhesive until final inspection.
- .2 Prohibit traffic on floor for 48 hours after installation.

END OF SECTION