

THIS IS A METRIC PROJECT. UNLESS OTHERWISE NOTED, ALL DIMENSIONS ARE IN MILLIMETERS AND ALL FORCES ARE IN METRIC UNITS (PER TG-ABBR-02).

2. PRIOR TO CONSTRUCTION, REVIEW STRUCTURAL DRAWINGS IN CONJUNCTION WITH DRAWINGS PROVIDED BY ALL OTHER CONSULTANTS. CONFIRM ALL DIMENSIONS, ELEVATIONS AND HEADROOM CLEARANCES, AND COORDINATE ALL OPENINGS, SLEEVES AND EMBEDDED ITEMS.

3. REPORT ANY DISCREPANCIES OR CONFLICTS BEFORE PROCEEDING WITH THE WORK.

4. DO NOT CUT OR DRILL ANY OPENINGS IN STRUCTURAL MEMBERS WITHOUT WRITTEN PERMISSION FROM DEPARTMENTAL REPRESENTATIVE.

5. EXISTING STRUCTURAL INFORMATION IS BASED UPON THE FOLLOWING DRAWINGS:

5.1. DRAWINGS TITLED EASTERN BLOCK, OTTAWA - FIREPROOFING, ALTERATIONS, AND ADDITIONS TO SECOND FLOOR AND ROOF, PREPARED BY PUBLIC WORKS DEPARTMENT OF CANADA CHIEF ARCHITECTS, DATED 1916, AND REPORT TITLED RESTORATION/RENOVATIONS PROGRAM EAST BLOCK, PARLIAMENT HILL, OTTAWA, PREPARED BY PUBLIC WORKS CANADA HQ, BUILDING DESIGN UNIT, STRUCTURAL SECTION, DATED MARCH 1977.

5.2. DRAWINGS TITLED RESTORATION/RENOVATION PROGRAM EAST BLOCK, PARLIAMENT HILL OTTAWA, PREPARED BY PUBLIC WORKS CANADA, DATED MARCH 1980.

6. VERIFY EXISTING DIMENSIONS AND CONDITIONS ON SITE PRIOR TO CONSTRUCTION.

7. USE THESE DRAWINGS ONLY FOR THE PURPOSE IDENTIFIED IN THE REVISIONS COLUMN. DO NOT CONSTRUCT FROM THESE DRAWINGS UNLESS MARKED "ISSUED FOR CONSTRUCTION".

8. DO NOT USE INFORMATION ON THESE DRAWINGS FOR ANY OTHER PROJECT OR WORKS.

9. DO NOT SCALE THESE DRAWINGS.

10. UNLESS OTHERWISE NOTED ON DRAWINGS, FOLLOW TYPICAL DETAILS SHOWN ON S01 DRAWING SERIES. TYPICAL DETAILS SHOW STRUCTURAL INTENT RATHER THAN ACTUAL CONDITIONS FOR THIS PROJECT. IF A TYPICAL DETAIL INCLUDES A CROSS REFERENCE TO ANOTHER TYPICAL DETAIL WHICH IS NOT INCLUDED IN THE DRAWING SET, THE CROSS-REFERENCED DETAIL IS NOT APPLICABLE ON THIS PROJECT.

11. REFER TO ARCHITECTURAL DRAWINGS AND SPECIFICATIONS FOR REQUIRED FIRE RATING, SPRAYED FIREPROOFING, INTUMESCENT PAINTINGS AND ALL OTHER MEASURES REQUIRED TO ACHIEVE IT.

DRAWINGS SHOW COMPLETED STRUCTURE ONLY. THEY DO NOT SHOW TEMPORARY WORKS FOR WHICH THE CONTRACTOR IS RESPONSIBLE AND WHICH MAY BE REQUIRED FOR EXECUTION OF THE PROJECT, INCLUDING TEMPORARY SHORING, BRACING, GUYS AND TIE DOWNS. THE CONTRACTOR TO ESTABLISH CONSTRUCTION PROCEDURE AND SEQUENCE TO ENSURE SAFETY OF THE WHOLE STRUCTURE AND ALL ITS COMPONENTS DURING ERECTION.

12. DESIGN AND CONSTRUCTION REVIEW OF ALL TEMPORARY WORKS TO BE CARRIED OUT BY A PROFESSIONAL ENGINEER RETAINED BY THE CONTRACTOR, LICENSED IN THE PLACE WHERE THE PROJECT IS LOCATED.

13. CONSTRUCTION LOADS ON COMPLETED STRUCTURE NOT TO EXCEED DESIGN LOADS INDICATED ON DRAWINGS. FULL DESIGN LOADS MAY ONLY BE APPLIED AFTER THE CONCRETE REACHES ITS DESIGN STRENGTH.

14. UNLESS SHOWN ON STRUCTURAL DRAWINGS, DESIGN OF NON- STRUCTURAL AND SECONDARY STRUCTURAL ELEMENTS AND THEIR CONNECTIONS TO THE PRIMARY BUILDING STRUCTURE ARE NOT WITHIN THE SCOPE OF SERVICES PROVIDED BY DEPARTMENTAL REPRESENTATIVE. SUCH ELEMENTS INCLUDE (BUT ARE NOT LIMITED TO) THE FOLLOWING:

1. PARTITIONS; MASONRY, GLASS, WOOD AND STEEL STUDS, PREFABRICATED PANELS

2. BULKHEADS, SUSPENDED CEILINGS, INTERIOR AND EXTERIOR SIGNAGE.

3. MASONRY, STONE OR PRECAST VENEER CONNECTIONS TO BACKUP STRUCTURE.

4. SUPPORTS FOR MECHANICAL AND ELECTRICAL EQUIPMENT; HANGERS, BRACES, POSTS, RACKS, SLEEPERS, SEISMIC RESTRAINTS, SUPPORT PLATFORMS AND PADS, SERVICE PLATFORMS.

DEPARTMENTAL REPRESENTATIVE WILL NOT REVIEW DESIGN, DETAILING AND INSTALLATION OF THESE ELEMENTS, FOR WHICH SUPPLIERS AND / OR SPECIALTY PROFESSIONAL ENGINEERS ARE RESPONSIBLE; THE ONLY REVIEW PROVIDED (WHERE APPLICABLE) WILL BE FOR IMPACT ON THE BASE BUILDING STRUCTURE.

15. MAINTAIN A QUALITY CONTROL PLAN FOR STRUCTURAL WORK, AND MAKE IT AVAILABLE TO THE CONSULTANT UPON REQUEST. AT A MINIMUM, THE PLAN TO INCLUDE:

1. NAMES OF PERSONNEL RESPONSIBLE FOR EXECUTION OF THE PLAN.

2. MEANS AND METHODS FOR CONFIRMING MATERIAL COMPLIANCE WITH SPECIFICATIONS AND ASSOCIATED DOCUMENTATION PROCEDURES.

3. PROGRAM FOR CONFIRMING AND DOCUMENTING COMPLIANCE WITH REQUIRED SUB-TRADE QUALIFICATIONS AND QUALIFICATIONS OF THEIR INDIVIDUAL EMPLOYEES AND SUB-CONTRACTORS.

4. PROCEDURES FOR REVIEWING FIELD COMPLIANCE WITH CONSTRUCTION DOCUMENTS, INCLUDING DOCUMENTATION OF LOCATIONS REVIEWED, PHOTOGRAPHS TAKEN AND TIMING OF REVIEW. THE CONTRACTOR'S REVIEW TO BE COMPLETED PRIOR TO REVIEW BY THE CONSULTANT.

5. PROCEDURES FOR RECTIFYING DEFICIENCIES NOTED BY THE CONTRACTOR, SUB-CONTRACTORS, CONSULTANTS AND INDEPENDENT INSPECTION AGENCIES.

16. FOR INSPECTION AND TESTING REQUIREMENTS, REFER TO SPECIFICATIONS.

17. IN CASE OF DISCREPANCY BETWEEN GENERAL NOTES, DRAWINGS AND SPECIFICATIONS, COMPLY WITH THE MOST STRINGENT

1. RENOVATION OF THE EXISTING BUILDING IS CONSIDERED "BASIC", AS STIPULATED BY PART 11 OF THE ONTARIO BUILDING CODE. MODIFICATIONS TO THE BUILDING STRUCTURE ARE DESIGNED TO MAINTAIN ITS EXISTING PERFORMANCE LEVEL; ADEQUACY OF THE BASE BUILDING STRUCTURE REMAINS THE RESPONSIBILITY OF THE ORIGINAL STRUCTURAL ENGINEER.
2. STEEL ELEMENTS ARE DESIGNED PER CSA S16-14 - LIMIT STATE DESIGN OF STEEL STRUCTURES.
3. SELF WEIGHT (SWT) IS DUE TO THE WEIGHT OF THE STRUCTURE ITSELF. IT VARIES WITH THE STRUCTURAL SYSTEM, AND INCLUDES CONCRETE TOPPINGS ON STEEL DECK.
4. SUPERIMPOSED DEAD LOADS (SDL) ARE NON-STRUCTURAL DEAD LOADS DUE TO NON-STRUCTURAL TOPPINGS, FINISHES, PARTITIONS, ROOFING MATERIALS, SUSPENDED EQUIPMENT, PAVERS, SOIL, ETC.
5. DEAD LOAD (DL) IS THE SELF WEIGHT OF THE STRUCTURE PLUS THE SUPERIMPOSED DEAD LOAD.
6. UNLESS OTHERWISE NOTED, DESIGN LOADS SHOWN ON DRAWINGS ARE SPECIFIED (UNFACTORED) LOADS, TO BE USED FOR ULS DESIGN. FOR SLS DESIGN, THESE LOADS CAN BE REDUCED BY MULTIPLYING WITH THE RATIO OF APPROPRIATE IMPORTANCE FACTORS  $w(SLS) / w(ULS)$  GIVEN BELOW.
7. IF ONLY ONE VALUE IS GIVEN FOR A LOAD, CONSIDER IT LIVE LOAD.

1. REFER TO SPECIFICATIONS FOR SHOP DRAWINGS WHICH NEED TO BE SUBMITTED FOR REVIEW.
2. REVIEW OF SHOP DRAWINGS BY DEPARTMENTAL REPRESENTATIVE IS ON A SAMPLING BASIS, FOR GENERAL CONFORMITY WITH STRUCTURAL CONTRACT DOCUMENTS. IT IS NOT A DETAILED CHECK AND MUST NOT BE CONSTRUED AS RELIEVING THE CONTRACTOR OF HIS RESPONSIBILITY TO MAKE THE DRAWINGS ACCURATE AND IN CONFORMITY WITH ALL THE CONTRACT DOCUMENTS, TO REVIEW SHOP DRAWINGS AND TO COORDINATE WORK OF INTERFACING TRADES AND MANUFACTURE OF INTERFACING PRODUCTS.
3. REVIEW OF SHOP DRAWINGS DOES NOT IMPLY ANY CHANGE IN ANY OTHER CONSULTANTS' OR PROFESSIONALS' RESPONSIBILITIES RELATED TO DESIGN OF SPECIFIC ITEMS AS OUTLINED BY THE SPECIFICATIONS.
4. ALLOW A MINIMUM OF 10 WORKING DAYS FOR REVIEW OF EACH SUBMISSION OF SHOP DRAWINGS IN DEPARTMENTAL REPRESENTATIVE OFFICE. ALLOW MORE TIME WHEN LARGE QUANTITIES OF SHOP DRAWINGS ARE SUBMITTED. SUBMIT IN GENERAL CONFORMITY WITH THE SEQUENCE OF CONSTRUCTION INTENDED.
5. AFTER REVIEW, THE DRAWINGS WILL BE STAMPED AND RETURNED. DO NOT COMMENCE FABRICATION UNTIL RETURNED SHOP DRAWINGS HAVE BEEN EXAMINED.
6. SHOP DRAWINGS MARKED "REVIEWED" CAN BE USED FOR FABRICATION. DO NOT MAKE ANY CHANGES OR ADDITIONS TO THESE DRAWINGS WITHOUT NOTIFYING THE CONSULTANT.
7. SHOP DRAWINGS MARKED "REVIEWED AS NOTED" CAN BE USED FOR FABRICATION AFTER THE REVISIONS NOTED ARE IMPLEMENTED. DO NOT MAKE ANY FURTHER CHANGES OR ADDITIONS TO THESE DRAWINGS WITHOUT NOTIFYING THE CONSULTANT.
8. SHOP DRAWINGS MARKED "REVISE AND RESUBMIT" REQUIRE SUBSTANTIAL REVISIONS AND MUST BE RESUBMITTED FOR ADDITIONAL REVIEW PRIOR TO FABRICATION. ALL CHANGES AND ADDITIONS TO THE PREVIOUS SUBMISSION TO BE CLEARLY IDENTIFIED ON THE RESUBMITTED DRAWINGS. ONLY THE IDENTIFIED CHANGES WILL BE REVIEWED ON RE-SUBMISSION.
9. SHOP DRAWINGS MARKED "REVIEWED FOR IMPACT ON BASE STRUCTURE ONLY" SHOW WORKS WHICH ARE NOT WITHIN THE SCOPE OF STRUCTURAL CONSULTING SERVICES BUT AFFECT BEHAVIOUR OF THE BASE STRUCTURE. DEPARTMENTAL REPRESENTATIVE WILL NOT REVIEW DESIGN OF THESE WORKS AND ASSUMES THAT THE INDICATED WEIGHTS AND ALL OTHER LOADS IMPOSED ON THE BASE STRUCTURE ARE CORRECTLY IDENTIFIED BY THE DESIGNER / SUPPLIER OF THESE ELEMENTS.
10. DRAWINGS MARKED "NOT REVIEWED" SHOW WORKS WHICH ARE NOT WITHIN THE SCOPE OF STRUCTURAL CONSULTING SERVICES AND DO NOT IMPACT THE BASE BUILDING STRUCTURE.
11. DEPARTMENTAL REPRESENTATIVE WILL NOT REVIEW DESIGN AND IMPLEMENTATION OF ANY TEMPORARY WORKS, NOR ASSESS IMPACT OF THESE WORKS ON THE BASE STRUCTURE. THE CONTRACTOR AND / OR THE PROFESSIONAL ENGINEER ENGAGED BY THE CONTRACTOR MUST ENSURE THAT THE BASE STRUCTURE IS NOT ADVERSELY AFFECTED BY THE TEMPORARY WORKS AND CONSTRUCTION PROCESS AND THAT TEMPORARY LOADS DO NOT EXCEED THE DESIGN LOADS INDICATED ON STRUCTURAL DRAWINGS.
12. DO NOT USE SHOP DRAWINGS AS A MEANS TO PROPOSE SUBSTITUTIONS OR ALTERNATIVES TO THE MATERIALS, PRODUCTS OR DETAILS INDICATED IN CONTRACT DOCUMENTS. SUCH SHOP DRAWINGS WILL BE MARKED "REVISE AND RESUBMIT".
13. PROVIDE FINAL RECORD DRAWINGS AFTER ALL CORRECTIONS ARE MADE.

14. DEPARTMENTAL REPRESENTATIVE WILL PROVIDE PERIODIC FIELD REVIEW OF A REPRESENTATIVE SAMPLE OF THE STRUCTURAL WORKS DETAILED ON THESE DRAWINGS FOR GENERAL CONFORMANCE WITH CONTRACT DOCUMENTS. THESE REVIEWS DO NOT REPLACE THE CONTRACTOR'S RESPONSIBILITY TO IMPLEMENT AND MAINTAIN A QUALITY CONTROL PROGRAM, AND DO NOT MAKE DEPARTMENTAL REPRESENTATIVE A GUARANTOR OF THE CONTRACTOR'S WORK.

15. CONSTRUCTION REVIEW REPORTS WILL OUTLINE ANY DEFICIENCIES FOUND.

16. ASSIST DEPARTMENTAL REPRESENTATIVE DURING FIELD REVIEW, AND PROVIDE SAFE ACCESS TO WORK AREAS AS REQUIRED.

17. CHECK THE WORK PRIOR TO FIELD REVIEW TO CONFIRM IT IS COMPLETED AND IN ACCORDANCE WITH CONTRACT DOCUMENTS.

18. BRING TO THE ATTENTION OF DEPARTMENTAL REPRESENTATIVE ANY DEFICIENCIES FOUND IN THE WORK TOGETHER WITH A PROPOSAL FOR REMEDY. DEPARTMENTAL REPRESENTATIVE WILL DECIDE WHAT CORRECTIVE ACTION MAY BE TAKEN AND ISSUE THE NECESSARY INSTRUCTIONS.

19. PROVIDE REASONABLE NOTICE (NOT LESS THAN 24 HOURS) TO ALLOW FOR THE FIELD REVIEW OF THE FOLLOWING:

a. STRUCTURAL STEEL BEFORE COVERING

20. SCHEDULE REVIEW WORK TO OCCUR DURING NORMAL BUSINESS HOURS.

21. ORGANIZE FOR FIELD REVIEW OF ALL PROPRIETARY PRODUCTS AND OTHER STRUCTURAL WORKS DESIGNED BY SPECIALTY ENGINEERS. THE REVIEW TO BE BY THE ENGINEERS RESPONSIBLE FOR THE DESIGN OR BY OTHER ENGINEERS DESIGNATED BY THE ENGINEERS RESPONSIBLE FOR THE DESIGN AND LICENSED IN THE PLACE WHERE THE PROJECT IS LOCATED. SUBMIT CONSTRUCTION REVIEW REPORTS FOR CONSULTANT'S RECORD.

1. EXISTING CONDITIONS ARE ASSUMED. SURVEY THE EXISTING STRUCTURE AFTER REMOVING FINISHES AND REPORT ANY VARIATIONS TO DEPARTMENTAL REPRESENTATIVE BEFORE PROCEEDING WITH THE WORK.
2. DESIGN OF STRUCTURAL WORKS RELATED TO THE EXISTING BUILDING HAS BEEN CARRIED OUT AS FAR AS PRACTICAL. GIVEN LIMITED AVAILABILITY OF THE EXISTING DRAWINGS AND LIMITED RECORDS OF THE STRUCTURAL MODIFICATIONS LIKELY TO HAVE BEEN MADE, THROUGH THE LIFE OF THE BUILDING, MODIFICATIONS TO THE PROPOSED STRUCTURAL FRAMING AND / OR DETAILS MAY BE REQUIRED. IF EXISTING CONDITIONS ARE FOUND TO BE DIFFERENT FROM THOSE ASSUMED AND SHOWN ON DRAWINGS.
3. TAKE ALL PRECAUTIONS NECESSARY TO PROTECT EXISTING STRUCTURES DURING DEMOLITION AND NEW CONSTRUCTION.
4. DISCONNECT ALL SERVICES IN THE AREAS AFFECTED BY DEMOLITION AND NEW CONSTRUCTION. REROUTE SERVICES AS REQUIRED TO KEEP THE REMAINDER OF THE BUILDING OPERATIONAL.
5. SAFELY STORE ALL STRUCTURAL ELEMENTS AND OTHER PRODUCTS WHICH ARE TO BE RE-USED.
6. REMOVE FROM SITE ALL OTHER STRUCTURAL ELEMENTS AND PRODUCTS WHICH ARE NOT INDICATED TO BE HANDED OVER TO THE OWNER.
7. SCHEDULE WORK TO MINIMIZE EFFECT ON THE EXISTING BUILDING OPERATION. USE EQUIPMENT AND PROCEDURES TO MINIMIZE NOISE, DUST AND VIBRATIONS. SUBMIT PROPOSED SCHEDULE FOR REVIEW BY THE CONSULTANT AND THE OWNER.
8. ALL DEMOLITION, SHORING AND OTHER TEMPORARY WORKS TO BE DESIGNED BY A PROFESSIONAL ENGINEER RETAINED BY THE CONTRACTOR, LICENSED IN THE PLACE WHERE THE PROJECT IS LOCATED. PREPARE DRAWINGS SIGNED AND SEALED BY THAT ENGINEER SHOWING DEMOLITION PROCEDURE AND SEQUENCE AND ALL THE NECESSARY SHORING.
9. INSTALL AND AFTERWARDS REMOVE ALL TEMPORARY SHORING AND BRACING REQUIRED TO ENSURE THE INTEGRITY OF THE EXISTING STRUCTURE DURING CONSTRUCTION.
10. DO NOT ALTER MATERIAL PROPERTIES OF THE STRUCTURAL STEEL WHICH IS TO REMAIN BY CUTTING AND DEMOLITION PROCEDURE.
11. ASSESS CAPACITY OF THE EXISTING STRUCTURE AND CONSTRUCTION LOADS APPLIED TO IT. PROVIDE ADEQUATE SHORING IF THE LOADS EXCEED THE EXISTING STRUCTURAL CAPACITY.
12. MAKE GOOD ALL EXISTING WORK DISTURBED BY THE SHORING OPERATIONS, DEMOLITION, EXCAVATION AND OTHER CONSTRUCTION PROCEDURES.

1. USE DRILLING AND INSTALLATION TOOLS AND PROCEDURES PER MANUFACTURERS' RECOMMENDATIONS.
2. DO NOT CUT REINFORCEMENT TO ACCOMMODATE DRILLED ANCHORS AND DOWELS.
3. WHEN OBSTRUCTIONS PREVENT DRILLING HOLES IN SPECIFIED LOCATIONS TO THE REQUIRED DEPTH, RELOCATE AT NO EXTRA COST TO THE CONTRACT. OBTAIN DEPARTMENTAL REPRESENTATIVE APPROVAL OF NEW LOCATIONS BEFORE DRILLING HOLES. FILL ALL ABANDONED HOLES WITH MIN. 30MPa GROUT. DO NOT TIGHTEN ANCHORS UNTIL GROUT IN ADJACENT ABANDONED HOLES REACHES 75% fc'.

1. CARRY A PRICE TO RETAIN AN INDEPENDENT TESTING COMPANY TO LOCATE AND MARK EXISTING REINFORCEMENT AND CONDUIT IN THE AREAS OF PROPOSED OPENINGS USING A NON-DESTRUCTIVE METHOD. IF LOCATIONS ARE NOT ACCEPTABLE TO DEPARTMENTAL REPRESENTATIVE, RELOCATE PROPOSED OPENINGS AND REPEAT PROCESS AT NO EXTRA COST TO THE CONTRACT.
2. CORING: DO NOT CUT EXISTING REINFORCEMENT OR CONDUIT WHEN CORING EXISTING CONCRETE UNLESS APPROVED IN ADVANCE BY DEPARTMENTAL REPRESENTATIVE. SAVE COMPLETE LENGTH OF ALL CORES AND LABEL WITH LOCATION TAKEN. MAKE ALL CORES AVAILABLE FOR REVIEW, DO NOT DISPOSE OF CORES WITHOUT DEPARTMENTAL REPRESENTATIVE APPROVAL.
3. CUTTING: DO NOT CUT EXISTING REINFORCEMENT AND CONDUIT UNLESS APPROVED IN ADVANCE BY DEPARTMENTAL REPRESENTATIVE. DO NOT OVERCUT OPENINGS. CORE FOUR CORNERS AND ENDS OF INTERMEDIATE SAWCUTS OF ALL OPENINGS PRIOR TO CUTTING SIDES AND INTERMEDIATE LINES. CHIP CORNERS SQUARE AFTER SAWCUTTING IF NECESSARY. IF NEW REINFORCEMENT IS REQUIRED AT AN OPENING, INSTALL IT BEFORE CUTTING OR SHORE THE STRUCTURE UNTIL THE NEW REINFORCEMENT IS INSTALLED.
4. OBTAIN APPROVAL FROM DEPARTMENTAL REPRESENTATIVE BEFORE CORING OR CUTTING EXISTING SLABS, BEAMS OR WALLS.
5. REMOVE TOPPINGS PRIOR TO LOCATING REINFORCEMENT AND CONDUIT.
6. MARK LOCATIONS AND SIZES OF CORES AND OPENINGS AND LOCATIONS OF REINFORCEMENT AND CONDUIT USING INDELEIBLE MARKERS AS FOLLOWS:
  1. RED FOR TOP BARS
  2. GREEN FOR BOTTOM BARS
  3. BLACK FOR CORES, OPENINGS AND CONDUIT.
7. RELOCATE PROPOSED OPENINGS AND REPEAT PROCESS AT NO EXTRA COST TO THE CONTRACT IF PROPOSED LOCATIONS ARE NOT ACCEPTABLE TO DEPARTMENTAL REPRESENTATIVE.
8. IF NEW REINFORCEMENT IS REQUIRED AT AN OPENING, INSTALL REINFORCEMENT BEFORE CUTTING OPENING OR SHORE UP STRUCTURE UNTIL NEW REINFORCEMENT IS INSTALLED

1. CONFORM TO CSA S16 "LIMIT STATES DESIGN OF STEEL STRUCTURES".
2. FABRICATOR TO BE CERTIFIED BY THE CANADIAN WELDING BUREAU UNDER REQUIREMENTS OF CSA W47.1, DIVISION 1 OR 2, AND/OR CSA W55.3.
3. WELDERS TO BE CWB CERTIFIED. WELDING TO BE IN ACCORDANCE WITH CSA W59.
4. MATERIALS (TO CSA G40.21 UNLESS NOTED OTHERWISE):
  - WIDE FLANGE SECTIONS, CHANNELS AND ANGLES: GRADE 350W
  - PLATES, BARS: GRADE 300W
  - BOLTS, NUTS AND WASHERS: ASTM F3125/F3125M
  - SHOP PAINT: CISC/CPMA 1-73A
  - SHOP PRIMER PAINT: CISC/CPMA 2-75
  - WELDING MATERIALS: CSA W48 AND CSA W59
5. SHOP DRAWINGS FOR STRUCTURAL STEEL, STEEL CONNECTIONS, AND STEEL JOISTS TO BE SIGNED AND SEALED BY A PROFESSIONAL ENGINEER RESPONSIBLE FOR THEIR DESIGN, RETAINED BY THE CONTRACTOR AND REGISTERED IN THE PLACE THE PROJECT IS LOCATED. ENGINEER TO CARRY MINIMUM \$1,000,000 IN LIABILITY INSURANCE.
6. DO NOT SPLICE SECTIONS WITHOUT PRIOR ACCEPTANCE BY THE CONSULTANT AND SUBMISSION OF PERTINENT SHOP DRAWINGS. ACCEPTED SPLICES TO DEVELOP THE FULL MOMENT CAPACITY OF THE SECTION. EACH SPLICE TO BE GIVEN A NON-DESTRUCTIVE TEST BY AN INDEPENDENT INSPECTION COMPANY ACCEPTABLE TO DEPARTMENTAL REPRESENTATIVE. TESTING TO BE AT THE CONTRACTOR'S EXPENSE. EVALUATE RESULTS IN ACCORDANCE WITH CSA W59 AND REPORT TO DEPARTMENTAL REPRESENTATIVE.
7. DO NOT CUT HOLES OR OTHERWISE MODIFY STRUCTURAL MEMBERS ON SITE.
8. DO NOT OVERSIZE ANCHOR ROD HOLES FOR SITE TOLERANCES. USE HOLE SIZES SUGGESTED IN THE CISC "HANDBOOK OF STEEL CONSTRUCTION".
9. PROTECT COMBUSTIBLE MATERIALS AND FINISHES DURING WELDING OPERATIONS.
10. UNLESS OTHERWISE NOTED, CLEAN STEEL TO SSPC SP1 (SOLVENT CLEANING) AND APPLY ONE COAT OF SHOP PAINT.
11. CLEAN STEEL WHICH WILL RECEIVE A FINISHED COAT OF PAINT ON SITE TO SSPC SP7 (BRUSH OFF BLAST CLEANING) AND APPLY SHOP PRIMER.



|                    |                               |
|--------------------|-------------------------------|
| DRAWN BY<br>WDD    | DRAWING NO.<br><br><b>S01</b> |
| REVIEWED BY<br>MAA |                               |