



1. ALL EXISTING SERVICES SHOWN ARE BASED ON EXISTING DRAWINGS AND SITE VISUAL SURVEY. CONTRACTOR SHALL VERIFY LOCATION AND PIPE RUNS ON SITE PRIOR TO CONSTRUCTION.
2. ANY INTERFERING SERVICE (OR SERVICES) THAT ARE NOT BE SHOWN ON THE DRAWINGS AND ARE EXPOSED DURING CONSTRUCTION SHALL BE VERIFIED BY THE CONTRACTOR AS TO THE SOURCE AND ROUTING AND SHALL BE REPORTED TO THE DEPARTMENTAL REPRESENTATIVE FOR RESOLUTION.
3. CONTRACTOR SHALL COORDINATE WITH BUILDING OPERATOR FOR SHUTTING DOWN AND RECONNECTING BUILDING SERVICES.
4. CONTRACTOR SHALL COORDINATE WITH THE OTHER TRADES FOR ROUTING OF NEW PIPING.

1. DEMOLISH EXISTING EXHAUST DUCT AND EXHAUST GRILLES AS INDICATED. TEMPORARILY COVER OPEN END OF EXHAUST DUCT UNTIL NEW CONNECTION IS MADE.
2. DEMOLISH EXISTING SPRINKLER HEADS AS INDICATED AND CAP THE PIPES UNTIL NEW CONNECTION IS MADE.

1. PROVIDE NEW DUCTS AND GRILLES AS INDICATED, REFER TO SCHEDULE ON M03 AND CONNECT TO EXISTING EXHAUST SYSTEM.
2. PROVIDE NEW SPRINKLER HEAD AS INDICATED. CONTRACTOR SHALL ADJUST SPRINKLER HEAD LOCATION BASED ON NEW CEILING GRIDS.

WSP

DATE SEP-1979	PROJECT NO. R.011972.148.
SCALE AS INDICATED	
DRAWN BY A.Z	DRAWING NO. M02
REVIEWED BY C.S	