TYPE:	2MP INDOOR FIXED (1920x1080P) CAMERA W/ VERIFOCUS
SYMBOL:	M 121
DESCRIPTION:	COLOR DAY/NIGHT IP (POE) CAMERA (2MP) W/ REMOTE AUTO FOCUS/ZOOM LENS. VARIFOCAL LENS (2.8mm TO 12mm) W/ HORIZONTAL FIELD OF VIEW 113° TO 33°.8. 1080P RESOLUTION AT 60 FRAMES PER SECOND. HIGH IMPACT, VANDAL RESISTANT ALUMINUM HOUSING W/ POLYCARBONATE DOME, IP66 RATED, POWER IEEE 802.3AF.
LOCATIONS:	INTERIOR
MOUNTING:	SURFACE: CEILING OR WALL
CABLING:	1x CAT6 (IP VIDEO & CAMERA POWER)
ELECTRICAL:	POWER OVER ETHERNET (12VDC) 9W

TYPE:	PAN TILT ZOOM 2MP (1080P) CAMERA
SYMBOL:	M 122
DESCRIPTION:	COLOR DAY/NIGHT IP (POE) PTZ CAMERA (HDTV) WITH WIDE DYNAMIC RANGE, 36X OPTICAL ZOOM, MOTION DETECTION, & IMAGE STABILIZATION. ZOOM (HORIZONTAL ANGLE OF VIEW: 3°.68–60°.6 IN 1080P) LENS. PAN: 360° & TILT: –20°–90°, WITH VARIABLE SPEED OF 0°.1–240° PER SECOND. RESOLUTION OF 1080P AT 25 FRAMES PER SECOND IN MOTION JPEG. VANDAL RESISTANT HOUSING IP66 RATED, CLEAR ACRYLIC DOME. HIGH POWER POE.
LOCATIONS:	INTERIOR
MOUNTING:	ARM: WALL
CABLING:	1x CAT6 (IP VIDEO & CAMERA POWER)
ELECTRICAL:	POWER OVER ETHERNET (24VDC)

TYPE:	2MP EXTERIOR (1080P) VARIFOCAL CAMERA W/ INFRARED
SYMBOL:	M 321
DESCRIPTION:	COLOR DAY/NIGHT IP (POE) CAMERA (1MP) W/ REMOTE AUTO FOCUS/ZOOM LENS. VARIFOCAL LENS (2.8MM TO 12MM) W/ HORIZONTAL FIELD OF VIEW 113° TO 33°.8. 1080P RESOLUTION AT 60 FRAMES PER SECOND. HIGH IMPACT, VANDAL RESISTANT ALUMINUM HOUSING W/ POLYCARBONATE DOME, IP66 RATED, POWER IEEE 802.3AF.
LOCATIONS:	BUILDING EXTERIOR, COURTYARD FENCE
MOUNTING:	ARM: WALL OR POLE, ADD EXTENSION FOR COURTYARD FENCES
CABLING:	1x CAT6 (IP VIDEO & CAMERA POWER)
ELECTRICAL:	(24VAC) 17W.

TYPE:	PAN TILT ZOOM 2MP EXTERIOR (1920x1080P) CAMERA W/ INFRARED
SYMBOL:	322
DESCRIPTION:	COLOR DAY/NIGHT IP (POE) PTZ CAMERA (HDTV) WITH WIDE DYNAMIC RANGE, 36x OPTICAL ZOOM, MOTION DETECTION, & IMAGE STABILIZATION. ZOOM (HORIZONTAL ANGLE OF VIEW: 3°.68–60°.6 IN 1080P) LENS. PAN: 360° & TILT: –20°–90°, WITH VARIABLE SPEED OF 0°.1–240° PER SECOND. RESOLUTION OF 1080P AT 25 FRAMES PER SECOND IN MOTION JPEG. VANDAL & WEATHER RESISTANT HOUSING IP66 RATED, COMES WITH BUILT IN HEATER FOR –40° START–UO AND OPERATION. CLEAR ACRYLIC DOME. HIGH POWER POE.
LOCATIONS:	BUILDING EXTERIOR
MOUNTING:	ARM: WALL OR POLE
CABLING:	1x CAT6 (IP VIDEO & CAMERA POWER)
ELECTRICAL:	HIGH POWER OVER ETHERNET (24VAC) 60W.

Public Works and Government Services Canada
Travaux publics et Services gouvernementaux Canada

REAL PROPERTY SERVICES
Western Region
SERVICES IMMOBILIERS
Région de l'ouest

GENERAL NOTES

This drawing and all it's contents are protected by copyright, and shall not be reproduced, in whole or in part without the expressed written consent of Casola Kappe Architects Ltd. These drawings are not to be scaled. All dimensions are to face of stud or sheathing unless noted otherwise. Contractor must verify all dimensions, drawings, details and specifications. Any discrepancies are to be reported to Casola Kappe Architects Ltd. prior to proceeding with work; this includes any errors or omissions.

ARCHITECT

casola·kappe ARCHITECTS
#300 - 1410 1st street sw , calgary, alberta T2R 0V8
bus (403) 287-9960 fax (403) 287-9962 info@ckarch.ca

CONSULTANT

wsp
1200, 10909 Jasper Avenue NW
Edmonton, AB, Canada T5J 3L9
Tel.: +1 780-410-6740
Fax: +1 780-449-4050
wsp.com

171-04394-00

PROFESSIONAL ENGINEER
W.M. JACKSON
MEMBER 16138
13 11 13
YR. MO. DAY
SASKATCHEWAN

Revision	Description	Date
1	ISSUED FOR TENDER	2015/11/13

Client / client

CORRECTIONAL SERVICES CANADA

Project / Projet

BOW UNIT REDEVELOPMENT

Designed by / Conçu par: KK

Drawn by / Dessiné par: SMA

Approved by / Approuvé par:

PWGSC Project Manager / Administrateur de Projets TPSGC: EH

Drawing title / Titre du dessin

BOW UNIT
CAMERA SCHEDULE

Project no./No. du projet	Drawing no./No. du dessin	Revision no.
R.082215.001	T201	1