


# REPUBLIC ARCHITECTURE INC

385 St. Mary Avenue  
Winnipeg, MB R3C 0N1

T 204 989 0102  
F 204 989 0094  
www.republicarchitecture.ca



APEGA PERMIT TO PRACTICE NO.  
11944  
06/03/2020

## NORR

2300, 411 1st Street SE,  
Calgary, Alberta, Canada T2G 4Y5  
norr.com

NORR ARCHITECTS ENGINEERS PLANNERS  
A Partnership of Limited Companies  
NORR is a trademark owned by Norrman Group Inc. and is used under license.

Victor Smith, Architect, AAA, B.Arch, MABC  
Bruce McKenzie, Architect, AAA, B.Arch, MABC  
A. Shiro Siddhartha, Architect, AAA, B.Arch, MABC  
Anirban Tootia, P.Eng, APEGA  
Chris Pal, P.Eng, APEGA

Revision	Description	Date
4	ISSUED FOR CONSTRUCTION	2020/03/06
3	ISSUED FOR 90% REVIEW	2019/08/29
2	ISSUED FOR 60% REVIEW	2019/05/09
1	ISSUED FOR 30% REVIEW	2018/03/14

Client

PSPC

10025 JASPER AVE  
EDMONTON, ALBERTA, T5J 1S6  
PH. 780-919-9445

Project Title  
JASPER STAFF HOUSING CONSTRUCTION

DUPLEX

720 PATRICIA STREET,  
JASPER, AB, T0E 1E0

Designed by  
H. HUANG

Drawn by  
D. GREGOIRE

Approved by  
M. ABUALQUMSSAN


Project Manager / Administrateur de Projets  
ROB HAFFER

Drawing Title  
FOUNDATION PLAN AND LOWER LEVEL PLUMBING PLAN

Project no./No. du projet  
R.100429.001

Drawing no./No. du dessin  
M2.1

Revision no.  
4




1  
M2.1  
MECHANICAL FOUNDATION PLAN  
SCALE: 1 : 50

### KEYNOTES:

- BACK WATER VALVE C/W ACCESS LID. REFER TO M1.2 DETAIL 10.
- (600X600)X2000 DEEP RESIDENTIAL PLASTIC STORM SUMP WITH REMOVABLE COVER WITH GASKET C/W SUMP PUMP P-1. REFER TO DRAWING M1.2 DETAIL 9.
- 50Ø PUMPED WEEPING TILE, DISCHARGE TO LANDSCAPE.
- WEEPING TILE REFER TO ARCHITECTURAL DRAWINGS.
- RADON PIPING TO RUN BELOW SLAB. REFER TO DRAWING 3.1 KEYNOTE 6 FOR CONTINUITY.
- ROUGH IN AND CAP SANITARY DRAINS FOR FUTURE BASEMENT BATH ROOM FIXTURES.

### PLUMBING GENERAL NOTES:

- SUPPLY AND INSTALL ALL FIRE STOPPING MATERIAL AND ENSURE THAT ALL FIRE PENETRATIONS ARE PROTECTED AS REQUIRED BY THE NATIONAL BUILDING CODE AND THE LOCAL AUTHORITIES.
- PROVIDE PLUMBING VENTING AS REQUIRED AND AS PER CODE.
- PROVIDE P-TRAP C/W TRAP PRIMER FOR ALL FLOOR DRAINS AS REQUIRED AND AS PER CODE.
- COORDINATE SANITARY RISERS AND VENT LINES WITH STRUCTURAL FRAMING BEFORE INSTALLATION.
- PROVIDE SLEEVES AS REQUIRED THRU FOOTINGS, PADS AND STRUCTURAL SLABS FOR MECHANICAL.
- COORDINATE AND SLEEVE FOR ALL PLUMBING FIXTURES.
- PROVIDE SHUT-OFF VALVES C/W ACCESS PANELS IN ALL SUITES FOR COLD WATER, HOT WATER LINES.
- PROVIDE CLEANOUTS ON EVERY LEADER, SOIL OR WASTE STACK AS REQUIRED AND AS PER CODE.
- SLOPE ALL 100Ø SANITARY PIPING @ 1% AND SLOPE ALL SANITARY PIPING LESS THAN 100Ø @ 2%.
- ENSURE ALL MECHANICAL IS INSTALLED AT A MINIMUM HEAD HEIGHT OF 2.1M.
- OFFSET SOIL OR WASTE RISERS FROM EACH OTHER AS REQUIRED AND AS PER THE PLUMBING CODE.
- ALL PIPING TO BE IN BULKHEAD OR PENETRATING ACROSS THE BEAM. COORDINATE HOLES LOCATION WITH STRUCTURAL PRIOR TO DRILL.
- PROVIDE LOCAL ISOLATION VALVES AT EACH FIXTURE FOR DCW AND DHW.
- CAST IRON SCHEDULE 40 ELBOWS SHALL ONLY BE USED FOR ALL SANITARY PIPES PENETRATING LOWER LEVEL FLOOR SLAB. NO PVC PIPE TO BE ALLOWED.



2  
M2.1  
LOWER LEVEL PLUMBING PLAN  
SCALE: 1 : 50

### KEYNOTES:

- 25Ø DCW UP THROUGH GROUND TO MECHANICAL ROOM. INSTALL BACKFLOW PREVENTER AT 25Ø DCW IN MECHANICAL ROOM TO SUPPLY TO EACH SUITE. REFER TO DRAWING M1.2 DETAIL 8.
- RUN DCW, DHW, SAN PIPING IN JOIST SPACE TO/FROM PLUMBING FIXTURE.
- GAS METER WITH PRESSURE REDUCING VALVE TO REDUCE GAS PRESSURE TO 3.5 KPA. INSTALL 25Ø GAS LINE UP AND INTO BASEMENT FLOOR CEILING SPACE. CLEAR, UNOBSTRUCTED AREA NEAR GAS METERS REQUIRE 2.2M x 0.9M CLEARANCE.
- 15Ø GAS LINE @ 3.5KPA TO CONNECT TO FURNACE IN MECHANICAL ROOM AS PER MANUFACTURER'S RECOMMENDATIONS.
- 15Ø GAS LINE @ 3.5KPA TO CONNECT TO DOMESTIC WATER HEATER IN MECHANICAL ROOM AS PER MANUFACTURER'S RECOMMENDATIONS.
- 20Ø DCW FROM MECHANICAL ROOM TO NON FREEZE HOSE BIBB.
- 25MM WATER METER INSTALLATION REFER TO DRAWING M1.2 DETAIL 8.
- 75Ø TO BELOW.
- DOMESTIC HOT AND COLD WATER MANIFOLD.
- WASHER TO BE CONNECTED TO 15Ø DCW/DHW COMPLETE WITH LAUNDRY BOX INSTALLATION.