

Part 1 General

1.1 SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for corner guards; include product characteristics, performance criteria, physical size, finish and limitations.
 - .2 Submit WHMIS SDS in accordance with Section 01 35 29.06 - Health and Safety Requirements. Indicate VOC's for adhesives.
- .3 Installation Drawings: Indicate on drawings large scale details, materials, finishes, dimensions, anchorage and assembly.
- .4 Samples: Submit duplicate 50 mm long samples of profiles for corner guards.

1.2 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store, and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
- .2 Deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials indoors in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect corner guards from nicks, scratches, and blemishes.
 - .3 Replace defective or damaged materials with new.

Part 2 Products

2.1 MATERIALS

- .1 Corner Guards: Surface mount stainless steel corner guards, 50 mm leg, 3 mm (1/8 inch) radius, edge burrs removed.
 - .1 Material: Minimum thickness 1.6 mm (0.063 inch, 16 gauge), stainless steel, type 304 or 316.
 - .2 Finish: No. 4 satin finish, grain oriented parallel with length.
 - .3 Height: Full height of corner.

2.2 ACCESSORIES

- .1 Adhesive: Water resistant type as recommended by manufacturer for substrate.

Part 3 Execution

3.1 EXAMINATION

- .1 Verify that conditions of substrate are acceptable for corner guard installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate.
 - .2 Inform Departmental Representative of unacceptable conditions.
 - .3 Proceed with installation only after unacceptable conditions have been remedied.

3.2 MANUFACTURER'S INSTRUCTIONS

- .1 Comply with manufacturer's written data, including product technical bulletins, installation instructions, and data sheets.

3.3 INSTALLATION

- .1 Install units on solid backing and erect with materials and components straight, tight and in alignment.
- .2 Adhere corner guards to substrate at locations as indicated.

3.4 CLEANING

- .1 Progress Cleaning: Clean in accordance with Section 01 74 00 - Cleaning.
 - .1 Leave Work area clean at end of each day.
- .2 Perform cleaning after installation to remove construction and accumulated environmental dirt.
- .3 Clean surfaces after installation using manufacturer's written recommended cleaning procedures.
- .4 Final Cleaning: Upon completion, remove surplus materials, rubbish, tools, and equipment in accordance with Section 01 74 00 - Cleaning.
- .5 Waste Management: Remove waste materials in accordance with Section 01 74 19 - Construction/Demolition Waste Management and Disposal.

3.5 PROTECTION

- .1 Protect installed products and components from damage during construction.
- .2 Repair damage to adjacent materials caused by corner guard installation.

END OF SECTION

Part 1 General

1.1 REFERENCES

- .1 ASTM International
 - .1 ASTM C1503-08 (2013), Silvered Flat Glass Mirror.

1.2 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data: Provide manufacturer's printed product literature and data sheets; include product characteristics, performance criteria, physical size, finish and limitations.
- .3 Shop Drawings:
 - .1 Indicate size and description of components, base material, surface finish inside and out, hardware and locks, attachment devices, description of rough-in-frame, building-in details of anchors for grab bars.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store, and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
- .2 Deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials indoors in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect toilet and bathroom accessories from nicks, scratches, and blemishes.
 - .3 Replace defective and damaged materials with new.

Part 2 Products

2.1 COMPONENTS

- .1 Provide toilet and bath accessories from a single manufacturer's matching series.
- .2 Towel Bars: Provide one each, 610 mm long and 450 mm long, chrome finished towel bars in each bathroom.
- .3 Toilet Paper Holder: Provide one chrome finished toilet paper holder in each bathroom.
- .4 Towel Ring: Provide one chrome finished towel ring in each bathroom.
- .5 For above items, provide matching products from one manufacturer's series.

- .6 Clothes hook: Surface mounted, Type 304 stainless steel with satin finish, with concealed mounting plate.
 - .1 Acceptable products:
 - .1 ASI 10-7340-S.
 - .2 Bobrick B-76717.
 - .3 Frost 1138-S.
- .7 Mirror: Silvered back flat glass to ASTM C1503, edges ground and polished smooth.
 - .1 Mounting clips: Stainless or plated steel, J-shaped profile, adjustable.
- .8 Shower rod: Stainless or chromed steel, 25 mm (1 inch) diameter, 0.7 mm (0.028 inch) wall thickness, curved, with matching flanges for mounting; chrome finish. Length: 1524 mm (60 inches).

2.2 FABRICATION

- .1 Weld and grind joints of fabricated components flush and smooth.
- .2 Wherever possible form exposed surfaces from one sheet of stock, free of joints.
- .3 Brake form sheet metal work with 1.5 mm radius bends.
- .4 Form surfaces flat without distortion. Maintain flat surfaces without scratches or dents.
- .5 Back-paint components where contact is made with building finishes to prevent electrolysis.
- .6 Shop assemble components and package complete with anchors and fittings.
- .7 Deliver inserts and rough-in frames to job site at appropriate time for building-in. Provide templates, details and instructions for building in anchors and inserts.
- .8 Provide steel anchor plates and components for installation on studding and building framing.

Part 3 Execution

3.1 EXAMINATION

- .1 Verify that conditions of substrates and surfaces to receive toilet and bathroom accessories are acceptable for product installation in accordance with manufacturer's instructions prior to toilet and bathroom accessories installation.
- .2 Inform Departmental Representative of unacceptable conditions.
- .3 Proceed with installation only after unacceptable conditions have been remedied.

3.2 INSTALLATION

- .1 Install and secure accessories rigidly in place as follows:

- .1 Stud walls: Install steel back-plate to stud prior to plaster or drywall finish. Provide plate with threaded studs or plugs.
- .2 Hollow masonry units, existing plaster or drywall: Use toggle bolts drilled into cell or wall cavity.
- .3 Solid masonry, marble, stone or concrete: Use bolts with lead expansion sleeves set into drilled holes.
- .4 Toilet and shower compartments: Use male to female through bolts.
- .2 Use tamper proof screws/bolts for fasteners.
- .3 Fill units with necessary supplies shortly before final acceptance of building.

3.3 ADJUSTING

- .1 Adjust toilet and bathroom accessories components and systems for correct function and operation in accordance with manufacturer's written instructions.
- .2 Lubricate moving parts to operate smoothly and fit accurately.

3.4 CLEANING

- .1 Progress Cleaning: Clean in accordance with Section 01 74 00 - Cleaning.
- .2 Leave Work area clean at end of each day.
- .3 Final Cleaning: Upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 00 - Cleaning.
- .4 Waste Management: Remove waste materials in accordance with Section 01 74 19 - Construction/Demolition Waste Management and Disposal.

3.5 PROTECTION

- .1 Protect installed products and components from damage during construction.
- .2 Repair damage to adjacent materials caused by toilet and bathroom accessories installation.

END OF SECTION