



FLOAT COLLAR CAN  
BUOY C/W  
INTERNAL  
CONCRETE  
BALLAST. SEE  
SPECS

450 MIN.  
500 MAX.

50MM Ø PICK-UP RING  
ST.STEEL

75  
100 MIN

DAM

350-400

75  
100 MIN

280-300

600  
750 MINIMUM.

900 EXPOSURE MINIMUM

#### BUOY COLOURS

**INTERNATIONAL ORANGE**

CMYK 0/88/94/27

RGB 186/22/12

HSL 3,88,39

HEXIDECIMAL #BA160C

US FED STD 595 - COLOUR 12197

**BACKGROUND WHITE**

CMYK 0/0/0/0

RGB 255/255/255

HEXIDECIMAL #FFFFFF

WATER

305  
MINIMUM

914MM MINIMUM

13MM THICK X 50MM Ø SIDE  
ATTACHMENT RING.  
ST.STEEL

Parcs Canada Parks Canada



Project title / Titre du projet

STANDARDS FOR PUBLIC SAFETY ITEMS AT DAMS

Drawing title / Titre du dessin

STANDARD BUOY FOR UPSTREAM OF DAM AT BOOM

Drawn by/ Dessiné par

S.Gauthier

Date

DEC.2014

Checked by/ Vérifié par

Asset No.

Dwg.no.

B1

Canada

PARCS CANADA  
EXECUTIVE DIRECTOR'S OFFICE, WATERWAYS