

CHAIR BUILDER (G3) 07 2020

CHAIR TYPE	QTY: 130				
■ Rotary Chair (up	to 275 lbs)				
☐ Rotary Chair large occupant (275 to 400 lbs)					
□ Rotary Stool					

Continuance of Certifications and additional information:

ny SA certification(s) or additional information to confirm/review chair criteria of product proposed

	prior to contract award within a time period specified by the Identified User.								
	Criteria Instructions	Requirement Choices (Dimensions reflect Specifications for Office Seating (SA))							
A	Headrest Choose only 1	 Yes – Adjustable and Removable (if applicable, indicate type of adjustment in additional criteria below) *Recommended with Standard Back Height ■ No 							
В	Backrest Height Choose only 1	■ Standard = height between 450 mm (17.7 in.) to 660 mm (26.0 in.) □ High = height greater than 660 mm (26.0 in.) □ No preference							
В	Backrest Style Preference(s) Choose ALL that are acceptable	☐ No preference note: style represents overall shape design may vary							
С	Lumbar Support Choose ALL that are acceptable	Adjustable □ Up/Down = min. 50 mm (2.0 in.) height adjustment between 150mm (5.9 in.) to 250 mm (9.8 in.) ■ Up/Down & In/Out							
	are acceptable	\square Fixed = between 150 mm (5.9 in.) to 250 mm (9.8 in.) above seat							
D	Armrests Choose ALL that	Adjustable Criteria ■ Height adjustable = min. 63 mm (2.5 in.) adjustment between 176 mm (6.9 in.) to 289 mm (11.4 in.) ■ Width adjustable = min.75 mm (3.0 in.) adjustment between 443 mm (17.0 in.) to 493 mm (19.4 in.) ■ Pivot adjustable = min. 20 degrees inward and min. 10 degrees outward							
	are acceptable	☐ Fixed = height range between 200 mm (7.9 in.) to 250 mm (9.8 in.)							
		□ None							
	Seat Depth	■ Adjustable = min. 50 mm (2.0 in.) adjustment within the range 420 mm (16.5 in.) to 460 mm (18.1 in.)							
Е	Choose ALL that are acceptable	☐ Fixed		n.) to 420 mm (16.5 in.) 0 mm (16.5 in.) to 460 m nm (18.1 in.)	m (18.1 in.)				
F	Seat Width	Refer to chair type above Rotary chairs and stools = min. width of 450 mm (17.7in.) Rotary Large Occupant models = min. width of 560 mm (22.0 in.)							
	Seat Height Choose ALL that are acceptable	Rotary Chair	■ Adjustable	Standard = includes 417 mm (16.4 in.) or less to 512 mm (20.2in.) or more Low = includes 376 mm (14.8 in.) to 439 mm (17.3 in.) other = *see additional criteria below for Home Use					
G			☐ Fixed = between 417 mm (16.4 in.) to 512 mm (20.2 in.)						
		Rotary Stool choose 1	<u>-</u>		ge from 580 mm (23 in.) than 670 mm (27.5 in)	to 840 mm (33 in.)			
Н	Tilt Mechanism Choose ALL that are acceptable	□ Synchro-tilt = Typically pivot point is under center of seat and when reclined the users feet are lifted off the floor. (seat and backrest tilt together in a ratio > 1:1) □ Unison-tilt = Typically pivot point is under front of seat and when reclined users feet remain on the floor. (seat and backrest tilt together in a ratio of 1:1) ■ Independent-tilt = Seat and backrest angle adjust independently of each other							
-	Seat and Backrest Locks Choose ALL that are acceptable	☐ Setup Position = chair locks into position with seat flat and backrest straight ■ Multiple Positions = chair locks into setup position plus other angles for seat and backrest							
J	Casters	■ carpet □ hard surface							
L	Foot Ring	Standard with stool models only							
	Upholstery	Backrest	☐ Upholstery	■ Breath	nable material (Mesh)	☐ Other			
		Seat	■ Upholstery	☐ Breath	nable material (Mesh)	☐ Other			
	Additional Criteria	EX1 – Seat height - Acceptable "Home use range" - Seat Height Rotary Chair adjustable with the following requirements: Must have a minimum of 127 mm (5.0 in) of height adjustment, includes 482.6 mm (19 in.) or less to 546.1 mm (21.5 in.) or more. EX2 – All chairs for the Chair builder are required in Black							