



Procurement and Contracting Services
30 Victoria Street
Gatineau, Quebec K1A 0M6

REQUEST FOR PROPOSAL AMENDMENT

The Request for Proposal is hereby amended; unless otherwise indicated, all other terms and conditions of the Request for Proposal remain the same.

RFP Amendment No. 5	RFP Amendment Date: December 1, 2020
Office of the Chief Electoral Officer File No. ECCS-RFP-20-0454	
Title: EC78645 Signature Guide Card	
Request for Proposal Closing Date: December 4, 2020 at 1:00 p.m. (Gatineau time)	
ENQUIRIES – address enquiries to the Contracting Authority: Office of the Chief Electoral Officer of Canada Procurement and Contracting Services 30 Victoria Street Gatineau, Quebec K1A 0M6 proposition-proposal@elections.ca	
Attention: Chantal Sabourin	Email: proposition-proposal@elections.ca

Part 1. Interpretation

- 1.1** Elections Canada hereby amends in accordance with this amendment the Request for Proposal bearing number ECCS-RFP-20-0454 and dated October 23, 2020 (the “RFP”). This amendment hereby forms part of the RFP.
- 1.2** Unless defined herein or unless the context otherwise requires, all of the words and phrases defined in the RFP and used in this amendment shall have the same meanings assigned to them in the RFP.

Part 2. Questions and Answers

The following question(s) have been asked in response to the Request for Proposal and Elections Canada hereby answers as follows:

2.1 Question No. 20

Question:

Can 2mm aluminum be replaced by a plastic with similar rigidity (acrylic) and thickness?

Answer:

For this requirement, we require the aluminum as per the specifications. The aluminum has already been tested and approved and switching material will take too much time for testing purposes.

2.2 Question No. 21

Question:

Annex A article 1.6.3 says the rubber backing is .03937 (1 mm) thick. The sample we picked up has a .060 (1.5 mm) thick backing. Is the .06 backing okay to use?

Answer:

It is possible that the rubber backing can vary but it must not surpass the 1.5mm thickness. It must also be at least 1mm thick.