



RETURN BIDS TO:

RETOURNER LES SOUMISSIONS À:

Bid Receiving Public Works and Government
Services Canada/Réception des soumissions/Travaux
publics et Services gouvernementaux Canada
See herein for bid submission
instructions/

Voir la présente pour les
instructions sur la présentation
d'une soumission

NA
Ontario

SOLICITATION AMENDMENT MODIFICATION DE L'INVITATION

The referenced document is hereby revised; unless otherwise
indicated, all other terms and conditions of the Solicitation
remain the same.

Ce document est par la présente révisé; sauf indication contraire,
les modalités de l'invitation demeurent les mêmes.

Comments - Commentaires

Vendor/Firm Name and Address
Raison sociale et adresse du
fournisseur/de l'entrepreneur

Issuing Office - Bureau de distribution

Public Works and Government Services / Travaux
publics et services gouvernementaux
Kingston Procurement
Des Acquisitions Kingston
86 Clarence Street, 2nd floor
Kingston
Ontario
K7L 1X3

Title - Sujet X-Ray Generating Systems	
Solicitation No. - N° de l'invitation W3474-212582/A	Amendment No. - N° modif. 003
Client Reference No. - N° de référence du client W3474-21-2582	Date 2020-12-14
GETS Reference No. - N° de référence de SEAG PW-\$KIN-535-8197	
File No. - N° de dossier KIN-0-54107 (535)	CCC No./N° CCC - FMS No./N° VME
Solicitation Closes - L'invitation prend fin at - à 02:00 PM Eastern Standard Time EST on - le 2021-01-08 Heure Normale du l'Est HNE	
F.O.B. - F.A.B. Specified Herein - Précisé dans les présentes Plant-Usine: <input type="checkbox"/> Destination: <input type="checkbox"/> Other-Autre: <input checked="" type="checkbox"/>	
Address Enquiries to: - Adresser toutes questions à: Carriere, Nancy	Buyer Id - Id de l'acheteur kin535
Telephone No. - N° de téléphone (613) 286-5423 ()	FAX No. - N° de FAX () -
Destination - of Goods, Services, and Construction: Destination - des biens, services et construction: Aerospace and Telecommunication Engineering Support Squadron 8 Wing / CFB Trenton Astra, ON K0K 3W0	

Instructions: See Herein

Instructions: Voir aux présentes

Delivery Required - Livraison exigée	Delivery Offered - Livraison proposée
Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur	
Telephone No. - N° de téléphone Facsimile No. - N° de télécopieur	
Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)	
Signature	Date

Amendment 003 is being raised for the following:

A. REFER: PART 4 - EVALUATION PROCEDURES AND BASIS OF SELECTION

4.1.1 Technical Evaluation

4.1.1.1 Mandatory Technical Criteria

Bidders must ensure full compliance with the mandatory requirements to be considered responsive. Failure to clearly demonstrate full compliance or provide supporting documentation will result in the offer being found non-compliant.

The mandatory criteria are:

MTC#3	The Tube Head must include the following functions/capabilities:	
	a. Must be air cooled;	
	b. Must have a maximum power rating of 750 Watts;	
	c. Must have a focal spot size of 1.00 mm as defined by EN12543-2 or ASTM 1165; and	
	d. Must include a laser pointer	

DELETE: In its entirety

INSERT: PART 4 - EVALUATION PROCEDURES AND BASIS OF SELECTION

4.1.1 Technical Evaluation

4.1.1.1 Mandatory Technical Criteria

Bidders must ensure full compliance with the mandatory requirements to be considered responsive. Failure to clearly demonstrate full compliance or provide supporting documentation will result in the offer being found non-compliant.

The mandatory criteria are:

MTC#3	The Tube Head must include the following functions/capabilities:	
	a. Must be air cooled;	
	b. Must have a minimum power rating of 750 Watts;	
	c. Must have a focal spot size of 1.00 mm as defined by EN12543-2 or ASTM 1165; and	
	d. Must include a laser pointer	

B. REFER: ANNEX "A", REQUIREMENT, 3.0 SCOPE OF REQUIREMENT

3.1 MANDATORY REQUIREMENTS

3.1.2 Tube Head must:

- (a) be air cooled;
- (b) weigh not more than 25 kg (55 lbs.);
- (c) have a diameter no greater than 25.4 cm (10 inches);
- (d) have a focal spot size of 1.00 mm (0.039 inch) or less as defined by EN12543-2 or ASTM E 1165.
- (e) have a tube certificate which includes a film image of the focal spot size provided;
- (f) have an adjustable high voltage output operating range from 10 kV to a maximum 200 kV;
- (g) have an adjustable Amperage range from 0.5m A to 5.0 m A;
- (h) be adjustable in 1 kV and 0.1 mA increments;
- (i) have a unit exposure duration setting from 1 sec to 99 minutes 59 seconds in 1 second increments;
- (j) have a maximum X-ray power rating of 750 Watts or greater;**
- (k) be capable of a continuous exposure time of a minimum of 1 hour at 200kV / 5.0 mA;**
- (l) have, as a maximum, a projected beam angle of 40 degrees X 60 degrees;
- (m) be capable of operating in temperatures between -20 to +50 Celsius (-4F to +122 F);
- (n) be capable of operating on AC mains voltages spanning 85 to 260 VAC;
- (o) be capable of operating on AC mains frequencies between 45 to 65 Hz;
- (p) include a laser pointer;
- (q) include a tube head pressure relief valve if applicable;
- (r) include a tube head thermal cut-out;
- (s) include a tube head pressure gauge if applicable; and
- (t) include a low pressure cut-out safety feature if applicable

DELETE: In its entirety

INSERT: ANNEX "A", REQUIREMENT, 3.0 SCOPE OF REQUIREMENT

3.1 MANDATORY REQUIREMENTS

3.1.2 Tube Head must:

- (a) be air cooled;
- (b) weigh not more than 25 kg (55 lbs.);
- (c) have a diameter no greater than 25.4 cm (10 inches);
- (d) have a focal spot size of 1.00 mm (0.039 inch) or less as defined by EN12543-2 or ASTM E 1165.
- (e) have a tube certificate which includes a film image of the focal spot size provided;
- (f) have an adjustable high voltage output operating range from 10 kV to a maximum 200 kV;
- (g) have an adjustable Amperage range from 0.5m A to 5.0 m A;
- (h) be adjustable in 1 kV and 0.1 mA increments;
- (i) have a unit exposure duration setting from 1 sec to 99 minutes 59 seconds in 1 second increments;
- (j) have a minimum X-ray power rating of 750 Watts or greater;**
- (k) be capable of a continuous exposure time of a minimum of 1 hour at 200kV;**
- (l) have, as a maximum, a projected beam angle of 40 degrees X 60 degrees;
- (m) be capable of operating in temperatures between -20 to +50 Celsius (-4F to +122 F);
- (n) be capable of operating on AC mains voltages spanning 85 to 260 VAC;

- (o) be capable of operating on AC mains frequencies between 45 to 65 Hz;
- (p) include a laser pointer;
- (q) include a tube head pressure relief valve if applicable;
- (r) include a tube head thermal cut-out;
- (s) include a tube head pressure gauge if applicable; and
- (t) include a low pressure cut-out safety feature if applicable

ALL OTHER TERMS AND CONDITIONS REMAIN THE SAME