

Part 1 General

1.1 REFERENCE STANDARDS

- .1 ASTM International, (latest edition)
 - .1 ASTM C260/C260M, Standard Specification for Air-Entraining Admixtures for Concrete.
 - .2 ASTM C309, Standard Specification for Liquid Membrane-Forming Compounds for Curing Concrete.
 - .3 ASTM C494/C494M, Standard Specification for Chemical Admixtures for Concrete.
 - .4 ASTM C1017/C1017M, Standard Specification for Chemical Admixtures for Use in Producing Flowing Concrete.
 - .5 ASTM D412, Standard Test Methods for Vulcanized Rubber and Thermoplastic Elastomers-Tension.
 - .6 ASTM D62, Standard Test Method for Tear Strength of Conventional Vulcanized Rubber and Thermoplastic Elastomer.
 - .7 ASTM D1751, Standard Specification for Preformed Expansion Joint Filler for Concrete Paving and Structural Construction (Non-extruding and Resilient Bituminous Types).
 - .8 ASTM D1752, Standard Specification for Preformed Sponge Rubber Cork and Recycled PVC Expansion Joint Fillers for Concrete Paving and Structural Construction.
- .2 Canadian General Standards Board (CGSB), (latest edition)
 - .1 CAN/CGSB-37.2-M88, Emulsified Asphalt, Mineral Colloid-Type, Unfilled, for Damp-proofing and Waterproofing and for Roof Coatings.
 - .2 CAN/CGSB-51.34, Vapour Barrier, Polyethylene Sheet for Use in Building Construction.
- .3 CSA International, (latest edition)
 - .1 CSA A23.1/A23.2, Concrete Materials and Methods of Concrete Construction/Methods of Test and Standard Practices for Concrete.
 - .2 CSA A283, Qualification Code for Concrete Testing Laboratories.
 - .3 CSA A3000, Cementitious Materials Compendium (Consists of A3001, A3002, A3003, A3004 and A3005).

1.2 ABBREVIATIONS AND ACRONYMS

- .1 Limestone Cement: hydraulic cement, blended hydraulic cement (XXb - b denotes blended) and Portland-limestone cement.
 - .1 Type GU, GUb and GUL - General use cement.
 - .2 Type MS and MSb - Moderate sulphate-resistant cement.
 - .3 Type MH, MHb and MHL - Moderate heat of hydration cement.
 - .4 Type HE, HEb and HEL - High early-strength cement.

- .5 Type LH, LHb and LHL - Low heat of hydration cement.
- .6 Type HS and HSb - High sulphate-resistant cement.
- .2 Fly ash:
 - .1 Type F - with CaO content less than 8%.
 - .2 Type CI - with CaO content ranging from 8 to 20%.
 - .3 Type CH - with CaO greater than 20%.
- .3 GGBFS - Ground, granulated blast-furnace slag.
- .4 SF - Silica fume with high silicon dioxide (SiO₂) content
- .5 N - Natural pozzolans

1.3 ADMINISTRATIVE REQUIREMENTS

- .1 Upon request, pre-installation Meetings: in accordance with Section 01 45 00 Quality Control, convene pre-installation meeting one week prior to beginning concrete works.
 - .1 Ensure speciality contractor - finishing, forming attend.
 - .1 Verify project requirements.

1.4 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00- Submittal Procedures.
- .2 Provide concrete mix design shop drawings. The shop drawings shall be stamped by a professional engineer registered in the Yukon.
- .3 Provide shop drawings showing min. embedment length and adhesive anchoring system for holdowns and dowels to existing and/or new concrete structure. The shop drawings shall be stamped by a professional engineer registered in the Yukon.
- .4 Provide testing results reports for review by Departmental Representative and do not proceed without written approval when deviations from mix design or parameters are found.
- .5 Concrete pours: provide accurate records of poured concrete items indicating date and location of pour, quality, air temperature and test samples taken as described in PART 3 - FIELD QUALITY CONTROL.
- .6 Concrete hauling time: provide for review by Departmental Representative deviations exceeding maximum allowable time of 120 minutes for concrete to be delivered to site of Work and discharged after batching.
- .7 Provide two copies of WHMIS MSDS in accordance with Section 01 35 29.06- Health and Safety Requirements.

1.5 QUALITY ASSURANCE

- .1 Quality Assurance: in accordance with Section 01 45 00- Quality Control.
- .2 Provide Departmental Representative, minimum 4 weeks prior to starting concrete work, with valid and recognized certificate from plant delivering concrete.

- .1 Provide test data and certification by qualified independent inspection and testing laboratory that materials and mix designs used in concrete mixture will meet specified requirements.
- .3 Quality Control Plan: provide written report to Departmental Representative verifying compliance that concrete in place meets performance requirements of concrete as established in PART 2 - PRODUCTS.

1.6 DELIVERY, STORAGE AND HANDLING

- .1 Delivery and Acceptance Requirements:
 - .1 Concrete hauling time: deliver to site of Work and discharged within 120 minutes maximum after batching.
 - .1 Do not modify maximum time limit without receipt of prior written agreement from Departmental Representative and concrete producer as described in CSA A23.1/A23.2.
 - .2 Deviations to be submitted for review by Departmental Representative.
 - .2 Concrete delivery: ensure continuous concrete delivery from plant meets CSA A23.1/A23.2.
- .2 Packaging Waste Management: remove for reuse and return of packaging materials in accordance with Section 01 74 19- Construction/Demolition Waste Management and Disposal.

Part 2 Products

2.1 DESIGN CRITERIA

- .1 Prescription: to CSA A23.1/A23.2, and as described in MIXES of PART 2 - PRODUCTS.

2.2 MATERIALS

- .1 Portland Cement: to CSA A3001, Type GU.
 - .1 Reduction in cement from Base Mix to Actual Supplementary Cementing Materials (SCMs) Mix, as percentage.
- .2 Blended hydraulic cement: Type HSb to CSA A3001.
- .3 Portland-limestone cement: Type GUL to CSA A3001.
- .4 Supplementary cementing materials: with minimum 20 % GGBFS, by mass of total cementitious materials to CSA A3001.
- .5 Water: to CSA A23.1.
- .6 Aggregates: to CSA A23.1/A23.2
- .7 Admixtures:
 - .1 Air entraining admixture: to ASTM C260.
 - .2 Chemical admixture: to ASTM C494. Departmental Representative to approve accelerating or set retarding admixtures during cold and hot weather placing.

- .3 Corrosion-inhibiting admixture: to C 494 Type S.
- .4 Lithium-based admixture: to C 494 Type.
- .5 Shrinkage-reducing admixture (SRA): to C 494 Type S.
- .6 Viscosity-modifying agent (VMA): to C 494 Type S.
- .8 Shrinkage compensating grout: premixed compound consisting of metallic aggregate, Portland cement, water reducing and plasticizing agents to CSA A23.1/A23.2.
 - .1 Compressive strength 50MPa at 28 days.
- .9 Non-premixed dry pack grout: composition of non-metallic aggregate Portland cement with sufficient water for mixture to retain its shape when made into ball by hand and capable of developing compressive strength of 50MPa at 28 days.
- .10 Pre-moulded joint fillers:
 - .1 Bituminous impregnated fibre board: to ASTM D1751.
 - .2 Sponge rubber: to ASTM D1752, Type I, flexible grade.
 - .3 Standard cork: to ASTM D1752, Type II.
- .11 Weep hole tubes: plastic.
- .12 Dovetail anchor slots: minimum 0.6 mm thick galvanized steel with insulation filled slots.

2.3 MIXES

- .1 Provide concrete mix to meet requirements shown on drawing S002, Concrete mix to CSA A23.1.
 - .1 Ensure materials used in concrete mix have been submitted for testing and meet requirements of CSA A23.1.
 - .2 Ensure concrete supplier meets performance criteria as established below and provide verification of compliance as in Quality Control Plan.
 - .3 Provide quality management plan to ensure verification of concrete quality to specified performance.

Part 3 Execution

3.1 PREPARATION

- .1 Obtain Departmental Representative's written approval before placing concrete.
 - .1 Provide 5 business days minimum notice prior to placing of concrete.
- .2 Place concrete reinforcing in accordance with Section 03 20 00- Concrete Reinforcing.
- .3 During concreting operations:
 - .1 Development of cold joints not allowed.
 - .2 Ensure concrete delivery and handling facilitate placing with minimum of re-handling, and without damage to existing structure or Work.
- .4 Pumping of concrete will not be permitted.

- .5 Ensure reinforcement and inserts are not disturbed during concrete placement.
- .6 Prior to placing of concrete obtain Departmental Representative's approval of proposed method for protection of concrete during placing and curing in adverse weather.
- .7 Protect previous Work from staining.
- .8 Clean and remove stains prior to application for concrete finishes.
- .9 Maintain accurate records of poured concrete items to indicate date, location of pour, quality, workability, air content, temperature and test samples taken.
- .10 In locations where, new concrete is dowelled to existing work, drill holes in existing concrete.
 - .1 Place steel dowels of deformed steel reinforcing bars and pack solidly with epoxy grout to anchor and hold dowels in positions as indicated.
- .11 Do not place load upon new concrete until authorized by Departmental Representative.

3.2 INSTALLATION/APPLICATION

- .1 Do cast-in-place concrete work to CSA A23.1/A23.2.
- .2 Sleeves and inserts:
 - .1 Do not permit penetrations, sleeves, ducts, pipes or other openings to pass through joists, beams, column capitals or columns, except where indicated or approved by Departmental Representative.
 - .2 Where approved by Departmental Representative, set sleeves, ties, pipe hangers and other inserts and openings as indicated or specified elsewhere.
 - .3 Sleeves and openings greater than 100 x 100 mm not indicated, must be reviewed by Departmental Representative.
 - .4 Do not eliminate or displace reinforcement to accommodate hardware. If inserts cannot be located as specified, obtain written approval of modifications from Departmental Representative before placing of concrete.
 - .5 Confirm locations and sizes of sleeves and openings shown on drawings.
 - .6 Set special inserts for strength testing as indicated and as required by non-destructive method of testing concrete.
- .3 Anchor bolts:
 - .1 Set anchor bolts to templates in co-ordination with appropriate trade prior to placing concrete.
 - .2 Grout anchor bolts in preformed holes or holes drilled after concrete has set only after receipt of written approval from Departmental Representative.
 - .1 Formed holes: 100 mm minimum diameter.
 - .2 Drilled holes: to manufacturers' recommendations.
 - .3 Protect anchor bolt holes from water accumulations, snow and ice build-ups.
 - .4 Set bolts and fill holes with shrinkage compensating grout.
- .4 Grout under base plates and machinery using procedures in accordance with manufacturer's recommendations which result in 100 % contact over grouted area.
- .5 Finishing and curing:

- .1 Finish concrete to CSA A23.1/A23.2.
 - .1 Composite deck shall be trowelled.
- .2 Use procedures as reviewed by Departmental Representative to remove excess bleed water. Ensure surface is not damaged.
- .6 Joint fillers:
 - .1 Furnish filler for each joint in single piece for depth and width required for joint, unless otherwise authorized by Departmental Representative.
 - .2 When more than one piece is required for joint, fasten abutting ends and hold securely to shape by stapling or other positive fastening.
 - .3 Locate and form isolation joints as indicated.
 - .4 Install joint filler.
 - .5 Use 12 mm thick joint filler to separate slabs-on-grade from vertical surfaces and extend joint filler from bottom of slab to within 12 mm of finished slab surface unless indicated otherwise.

SURFACE TOLERANCE

- .7 Concrete tolerance to CSA A23.1 to tolerance schedule as indicated.

3.3 FIELD QUALITY CONTROL

- .1 Site tests: conduct tests as follows in accordance with Section 01 45 00- Quality Control and submit report as described in PART 1 - ACTION AND INFORMATIONAL SUBMITTALS.
 - .1 Concrete pours.
 - .2 Slump.
 - .3 Air content.
 - .4 Compressive strength at 7, 14 and 28 days. Prepare min. 1 cylinder for each strength test plus one more, so total 4 cylinders.
 - .5 Air and concrete temperature.
- .2 Inspection and testing of concrete and concrete materials will be carried out by testing laboratory designated by Departmental Representative for review to CSA A23.1/A23.2.
 - .1 Ensure testing laboratory is certified to CSA A283.
- .3 Ensure test results are distributed for discussion at pre-pouring concrete meeting between testing laboratory and Departmental Representative.
- .4 Contractor will pay for costs of tests as specified in Section 01 45 00 Quality Control.
- .5 Non-Destructive Methods for Testing Concrete: to CSA A23.1/A23.2.
- .6 Inspection or testing by Departmental Representative will not augment or replace Contractor quality control nor relieve Contractor of his contractual responsibility.

3.4 CLEANING

- .1 Clean in accordance with Section 01 74 00- Cleaning.

- .2 Waste Management: separate waste materials for reuse in accordance with Section 01 74 21.
 - .1 Divert unused concrete materials from landfill to local facility after receipt of written approval from Departmental Representative.
 - .2 Provide appropriate area on job site where concrete trucks can be safely washed.
 - .3 Divert unused admixtures and additive materials (pigments, fibres) from landfill to official hazardous material collection site as approved by Departmental Representative.
 - .4 Do not dispose of unused admixtures and additive materials into sewer systems, into lakes, streams, onto ground or in other location where it will pose health or environmental hazard.
 - .5 Prevent admixtures and additive materials from entering drinking water supplies or streams.
 - .6 Using appropriate safety precautions, collect liquid or solidify liquid with inert, non-combustible material and remove for disposal.
 - .7 Dispose of waste in accordance with applicable local, Provincial/Territorial and National regulations.

END OF SECTION