

1 General

1.1 RELATED REQUIREMENTS

- .1 Section 06 20 00 - Finish Carpentry
- .2 Section 07 21 13 - Board Insulation.
- .3 Section 07 21 16 - Blanket Insulation.
- .4 Section 07 92 00 - Joint Sealants.
- .5 Section 08 31 00 - Access Doors & Panels.
- .6 Section 08 50 00 - Windows.
- .7 Section 09 21 16.08 - Gypsum Board Assemblies for Minor Works.

1.2 REFERENCE STANDARDS

- .1 CSA Group (CSA)
 - .1 CSA B111-1974 (R2003), Wire Nails, Spikes and Staples.
 - .2 CSA O121-08, Douglas Fir Plywood.
 - .3 CSA O141-05 (R2009), Softwood Lumber.
 - .4 CSA O151-09, Canadian Softwood Plywood.
 - .5 CAN/CSA-O325.0-07, Construction Sheathing.
 - .6 CAN/CSA-Z809-08, Sustainable Forest Management.
- .2 National Research Council Canada (NRC)
 - .1 National Building Code of Canada 2015 (NBC).
- .3 Forest Stewardship Council (FSC)
 - .1 FSC-STD-01-001-2004, FSC Principle and Criteria for Forest Stewardship.
- .4 Green Seal Environmental Standards (GS)
 - .1 GS-11-11, Paints and Coatings.
- .5 National Lumber Grades Authority (NLGA)
 - .1 Standard grading rules for Canadian Lumber 2010.
- .6 Sustainable Forestry Initiative (SFI)
 - .1 SFI-2010-2014 Standard.

1.3 SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
 - .1 Submit manufacturer s instructions, printed product literature and data sheets and include product characteristics, performance criteria, physical size, finish and limitations.

1.4 QUALITY ASSURANCE

- .1 Lumber identification: by grade stamp of an agency certified by Canadian Lumber Standards Accreditation Board.
- .2 Plywood identification: by grade mark in accordance with applicable CSA standards.
- .3 Plywood, OSB and wood based composite panel construction sheathing identification: by grademark in accordance with applicable CSA standards.
- .4 Sustainable Standards Certification:
 - .1 Certified Wood: submit listing of wood products and materials used in accordance with CAN/CSA-Z809 or FSC or SFI.

1.5 DELIVERY STORAGE AND HANDLING

- .1 Delivery, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements.
 - .2 Delivery and Acceptance Requirements: deliver materials to site in original factory
-

packaging, labelled with manufacturer s name and address.

- .3 Storage and Handling Requirements:
 - .1 Store materials off ground, indoors in dry location and in accordance with manufacturer s recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect wood from nicks, scratches, and blemishes.
 - .3 Replace defective or damaged materials with new.

2 Products

2.1 MATERIALS

- .1 Lumber: unless specified otherwise, softwood, S4S, moisture content 19% or less in accordance with following standards:
 - .1 CAN/CSA-O141.
 - .2 NLGA Standard Grading Rules for Canadian Lumber.
 - .3 CAN/CSA-Z809 or FSC or SFI certified.
- .2 Furring, blocking, nailing strips, grounds, rough bucks, curbs, fascia backing and sleepers:
 - .1 S2S
 - .2 Board
 - .3 Dimension
- .3 Panel Materials:
 - .1 Douglas fir plywood (DFP): to CSA O121, standard construction.
 - .1 Urea-formaldehyde free.
 - .2 Canadian softwood plywood (CSP): to CSA O151, standard construction.
 - .1 Urea-formaldehyde free.
 - .3 Plywood, OSB and wood based composite panels: to CAN/CSA-O325.
 - .1 Urea-formaldehyde free.
- .4 Wood Preservative:
 - .1 Surface-applied wood preservative: coloured, copper naphthenate or 5% pentachlorophenol solution, water repellent preservative.
 - .2 Pentachlorophenol use is restricted to building components that are in ground contact and subject to decay or insect attack only. Where used, pentachlorophenol-treated wood must be covered with two coats of an appropriate sealer.
 - .3 Structures built with wood treated with pentachlorophenol and inorganic arsenicals must not be used for storing food nor should the wood come in contact with drinking water.
- .5 Electrical Equipment Backboard:
 - .1 Provide for two (2) electrical equipment backboards for mounting electrical equipment as indicated. Use 19 mm thick x 1220 mm wide x 2440 mm long plywood coated on all sides with intumescent paint. Exact location of electrical equipment backboards is to be coordinated onsite with electrical subcontractor.

2.2 ACCESSORIES

- .1 Fasteners: to CAN/CSA-G164, for exterior work, fire-retardant treated lumber and pressure- preservative treated lumber.
 - .2 Nails, spikes and staples: to CSA B111.
 - .3 Proprietary fasteners: toggle bolts, expansion shields and lag bolts, screws and lead or inorganic fibre plugs, explosive actuated fastening devices, recommended for purpose by manufacturer.
-

3 Execution

3.1 EXAMINATION

- .1 Verification of Conditions: verify conditions of substrates previously installed under other Sections or Contracts are acceptable for rough carpentry installation in accordance with manufacturer s written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 INSTALLATION

- .1 Comply with requirements of National Building Code of Canada (NBC), supplemented by the following paragraphs.
- .2 Install furring and blocking as required to space-out and support casework, wall and ceiling finishes, facings, fascia, soffit, siding, windows and other work as required.
- .3 Align and plumb faces of furring and blocking to tolerance of 1:600.
- .4 Install rough bucks, nailers and linings to rough openings as required to provide backing for frames and other work.
- .5 Install wood cants, fascia backing, nailers, curbs and other wood supports as required and secure using galvanized fasteners.
- .6 Use caution when working with particle board. Use dust collectors and high quality respirator masks.
- .7 Frame, anchor, fasten, tie and brace members to provide necessary strength and rigidity.
- .8 Countersink bolts where necessary to provide clearance for other work.

3.3 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 00 - Cleaning.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 00 - Cleaning.
- .3 Waste Management:
 - .1 Separate waste materials for reuse or recycling in accordance with Section 01 74 19 - Waste Management and Disposal.
 - .2 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

END OF SECTION
