

Part 1 General

1.1 RELATED SECTIONS

- .1 Section 01 33 00 - Submittal Procedures.

1.2 SHOP DRAWINGS

- .1 Submit shop drawings in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Submit catalogue details for each type of door illustrating profiles, dimensions and methods of assembly.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with manufacturer's instructions.
- .2 Apply temporary protective coating to finished surfaces. Remove coating after erection. Do not use coatings that will become hard to remove or leave residue.
- .3 Leave protective covering in place until final cleaning of Building.

Part 2 Products

2.1 WALL-MOUNTED ACCESS DOORS

- .1 Sizes: Except as indicated otherwise, to be minimum sizes as follows:
 - .1 For body entry: 600 x 600 mm.
 - .2 For hand entry: 300 x 300 mm.
- .2 Construction: Rounded safety corners, concealed hinges, screwdriver latch, anchor straps, able to open 180o.
- .3 Materials:
 - .1 Tiled or marble surfaces and other special areas: Stainless steel with brushed satin or polished finish as directed by the Departmental Representative.
 - .2 Other areas: Prime coated steel.

Part 3 Execution

3.1 INSTALLATION

- .1 Shall be neat, square, caulked, trimmed (if necessary), smooth.

3.2 LOCATION

- .1 Location: Ensure that equipment is within view and accessible for operating, inspecting, adjusting, servicing without using special tools.

END OF SECTION