
PWGSC Ontario	SPECIFICATION	Section 00 00 00
Region Project	TITLE SHEET	Page 1
KW405-180719/001/PWL		2021-07-14

PROJECT TITLE CCIW Transformer Recapitalization

PROJECT NUMBER KW405-180719/001/PWL

PROJECT DATE 2021-07-14

<u>Section</u>	<u>Title</u>	<u>Pages</u>
<u>Division 00 - Procurement and Contracting Requirements</u>		
00 00 00	SPECIFICATION TITLE SHEET	1
00 01 11	LIST OF CONTENTS	2
<u>Division 01 - General Requirements</u>		
01 11 00	SUMMARY OF WORK	3
01 14 00	WORK RESTRICTIONS	3
01 31 16	PROJECT MANAGEMENT AND COORDINATION	5
01 31 19	PROJECT MEETINGS	2
01 32 00	CONSTRUCTION PROGRESS DOCUMENTATION	1
01 32 16	CONSTRUCTION PROGRESS SCHEDULE - BAR (GANTT) CHART	3
01 33 00	SUBMITTAL PROCEDURES	5
01 35 29	HEALTH AND SAFETY REQUIREMENTS	5
01 35 43	ENVIRONMENTAL PROCEDURES	3
01 41 00	REGULATORY REQUIREMENTS	2
01 42 13	ABBREVIATIONS AND ACRONYMS	10
01 45 00	QUALITY CONTROL	3
01 51 00	TEMPORARY UTILITIES	3
01 52 00	CONSTRUCTION FACILITIES	4
01 56 00	TEMPORARY BARRIERS AND ENCLOSURES	3
01 61 00	COMMON PRODUCT REQUIREMENTS	6
01 71 00	EXAMINATION AND PREPARATION	2
01 73 00	EXECUTION	3
01 74 11	CLEANING	3
01 74 20	CONSTRUCTION/DEMOLITION WASTE MANAGEMENT AND DISPOSAL	2
01 77 00	CLOSEOUT PROCEDURES	1
01 78 00	CLOSEOUT SUBMITTALS	7
01 79 00	DEMONSTRATION AND TRAINING	2
01 91 00	COMMISSIONING - GENERAL REQUIREMENTS	3
01 91 13	GENERAL COMMISSIONING (CX) REQUIREMENTS	9
01 91 20	PROJECT COMMISSIONING	5
01 91 31	COMMISSIONING (CX) PLAN	8
01 91 33	COMMISSIONING FORMS	3
01 91 41	COMMISSIONING: TRAINING	3
01 91 51	BUILDING MANAGEMENT MANUAL (BMM)	4
<u>Division 02 - EXISTING CONDITIONS</u>		
02 27 23	THERMOGRAPHIC ASSESSMENT ELECTRICAL SYSTEMS	10
02 41 13	SELECTIVE SITE DEMOLITION	6
02 41 99	DEMOLITION FOR MINOR WORKS	3
02 50 13	MANAGEMENT OF TOXIC WASTE	2
02 81 01	HAZARDOUS MATERIALS	4
02 84 00	POLYCHLORINATE BIPHENYL REMEDIATION	10
<u>Division 07 - THERMAL AND MOISTURE PROTECTION</u>		
07 84 00	FIRE STOPPING	5
<u>DIVISION 23 - HEATING, VENTILATING AND AIR CONDITIONING</u>		
23 09 33	ELECTRIC AND ELECTRONIC CONTROL SYSTEM FOR HVAC	3

<u>Section</u>	<u>Title</u>	<u>Pages</u>
DIVISION 26	<u>ELECTRICAL</u>	
26 05 00	COMMON WORK RESULTS FOR ELECTRICAL	8
26 05 03	ELECTRICAL COORDINATION STUDY	4
26 05 14	POWER CABLE AND OVERHEAD CONDUCTORS (1001 V)	2
26 05 20	WIRE AND BOX CONNECTORS (0-1000 V)	3
26 05 21	WIRES AND CABLES (0-1000 V)	3
26 05 22	CONNECTORS AND TERMINATIONS	2
26 05 27	GROUNDING - PRIMARY	4
26 05 28	GROUNDING - SECONDARY	5
26 05 29	HANGERS AND SUPPORTS FOR ELECTRICAL SYSTEMS	3
26 05 31	SPLITTERS, JUNCTION, PULL BOXES AND CABINETS	2
26 05 32	OUTLET BOXES, CONDUIT BOXES AND FITTINGS	2
26 05 33	RACEWAY AND BOXES FOR ELECTRICAL SYSTEMS	3
26 05 34	CONDUITS, CONDUIT FASTENINGS AND CONDUIT FITTINGS	4
26 05 36	CABLE TRAYS FOR ELECTRIC SYSTEMS	2
26 12 13	LIQUID FILLED, MEDIUM VOLTAGE TRANSFORMERS	5

PART 1 - GENERAL

1.1 SECTION INCLUDES

- .1 Title and description of Work.
- .2 Contract Method.
- .3 Work by others.
- .4 Future work.
- .5 Work sequence.
- .6 Contractor use of premises.
- .7 Owner occupancy.
- .8 Partial Owner occupancy.
- .9 Alterations to existing facility.

1.2 PRECEDENCE

- .1 For Federal Government projects, Division 01 Sections take precedence over technical specification sections in other Divisions of this Project Manual.

1.3 WORK COVERED BY CONTRACT DOCUMENTS

- .1 Work of this Contract comprises general construction and modification to the existing site to allow for replacement of three transformers, located at Canada Centre of Inland Water at Burlington, ON. Include all required services and verifications like phase rotation, orientation etc. to be completed with the existing electrical system in order to successfully replace and operate the new transformers.
- .2 Contingency allowance to cover for:
 - .1 Diesel Fuel No.2 to keep the rental generator running during electrical shutdowns.
 - .2 Burlington Hydro electrical isolation fees.
 - .3 Potential unknowns around areas of excavations.
 - .4 Third party Commissioning Agent fees.

1.4 CONTRACT METHOD

- .1 Construct work under lump sum contract.
- .2 Relations and responsibilities between Contractor and subcontractors and suppliers assigned by Owner are as defined in Conditions of Contract. Assigned Subcontractors must, in addition:
 - .1 Furnish to Contractor, bonds covering faithful performance of subcontracted work and payment of obligations thereunder when

Contractor is required to furnish such bonds to Departmental Representative.

- .2 Purchase and maintain liability insurance to protect Contractor from claims for not less than limits of liability which Contractor is required to provide to Departmental Representative.

1.5 COST BREAKDOWN

- .1 Within 48 hours of notification of acceptance of bid furnish a cost breakdown by Section aggregating contract price.
- .2 Show separately cost of equipment purchased exempt from Ontario Retail Sales Tax under your Ontario Sales Tax licence number.
- .3 Within 48 hours of acceptance of bid submit a list of subcontractors.

1.6 WORK SEQUENCE

- .1 Construct Work in stages to accommodate Owner's continued use of premises during construction.
- .2 Coordinate Progress Schedule and coordinate with Owner Occupancy during construction.
- .3 Required stages:
 - .1 Stage 1 - Replacement of Transformer T1, as noted on the contract documents.
 - .2 Stage 2 - Replacement of Transformer T2, as noted on the contract documents.
 - .3 Stage 3 - Replacement of Transformer T3, as noted on the contract documents.
4. Provide a dead insulator for Burlington Hydro (BHI) to terminate New 1-1/0 Al.O/H neutral conductor at pole location P#20832 as per contract documents.
5. Provide new neutral conductor from the demarcation point pole P#20832 to the HV switchgears location as per Burlington Hydro Specifications.
- .6 Maintain fire access/control.

1.7 CONTRACTOR USE OF PREMISES

- .1 Contractor has unrestricted use of site as indicated by Departmental representative until Substantial Performance.
- .2 Contractor shall limit use of premises for Work, for storage, and for access, to allow;
 - .1 Owner occupancy.
 - .2 Work by other contractors.
 - .3 Public usage.
- .3 Coordinate use of premises under direction of Departmental Representative.
- .4 Obtain and pay for use of additional storage or work areas needed for

operations under this Contract.

1.8 OWNER OCCUPANCY

- .1 Owner will occupy premises during entire construction period for execution of normal operations.
- .2 Cooperate with Owner in scheduling operations to minimize conflict and to facilitate Owner usage.

1.9 ALTERATIONS TO EXISTING BUILDING

- .1 Remove in good order, turn over to Department, and store within building where designated by Departmental Representative:
 - .1 Power Transformers. Drain insulated oil from transformers prior to handing them over.
- .2 Provide new openings required in existing construction.
- .3 Block in openings where items removed with material and finish to match existing adjoining construction.
- .4 Undercut existing doors to clear new carpet.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not used.

PART 1 - GENERAL

1.1 ACCESS AND EGRESS

- .1 Design, construct and maintain temporary "access to" and "egress from" work areas, including stairs, runways, ramps or ladders and scaffolding, independent of finished surfaces and in accordance with relevant municipal, provincial and other regulations.

1.2 USE OF SITE AND FACILITIES

- .1 Execute work with least possible interference or disturbance to normal use of premises. Make arrangements with Departmental Representative to facilitate work as stated.
- .2 Maintain existing services to building and provide for personnel and vehicle access.
- .3 Where security is reduced by work provide temporary means to maintain security.
- .4 Departmental Representative will assign sanitary facilities for use by Contractor's personnel. Keep facilities clean.
- .5 Closures: protect work temporarily until permanent enclosures are completed.

1.3 ALTERATIONS, ADDITIONS OR REPAIRS TO EXISTING BUILDING

- .1 Execute work with least possible interference or disturbance to building operations, occupants, public and normal use of premises. Arrange with Departmental Representative to facilitate execution of work.

1.4 EXISTING SERVICES

- .1 Notify, Departmental Representative utility companies of intended interruption of services and obtain required permission.
- .2 Where Work involves breaking into or connecting to existing services, give Departmental Representative 48 hours of notice for necessary interruption of mechanical or electrical service throughout course of work. Keep duration of interruptions minimum. Carry out interruptions after normal working hours of occupants, preferably on weekends.
- .3 Provide route for personnel, pedestrian and vehicular traffic.
- .4 Construct barriers in accordance with Section 01 56 00.

1.5 SPECIAL REQUIREMENTS

- .1 Carry out noise generating Work Monday to Friday from 18:00 to 07:00 hours and on Saturdays, Sundays, and statutory holidays.

- .2 Submit schedule in accordance with Section 01 32 16.06 - Construction Progress Schedule - Critical Path Method (CPM) and 01 32 16.07 - Construction Progress Schedule - Bar (GANTT) Chart.
- .3 Ensure Contractor's personnel employed on site become familiar with and obey regulations including safety, fire, traffic and security regulations.
- .4 Keep within limits of work and avenues of ingress and egress.
- .5 Ingress and egress of Contractor vehicles at site is limited to 3.
- .6 Deliver materials outside of peak traffic hours 17:00 to 07:00 and 13:00 to 15:00 unless otherwise approved by Departmental Representative.
- .7 Prior to cutting or drilling horizontal or vertical surfaces including concrete, concrete block or other structural substrate, determine location of reinforcing, service lines, pipes, conduits or other items by x-ray, ground penetrating radar or other appropriate method. Submit findings to Departmental Representative prior to cutting or drilling.

1.6 SECURITY

- .1 Where security has been reduced by Work of Contract, provide temporary means to maintain security.
- .2 Security clearances:
 - .1 Personnel employed on this project will be subject to security check. Obtain PWGSC clearance (CISD), as instructed, for each individual who will require to enter premises.
 - .2 Personnel will be checked daily at start of work shift and provided with pass which must be worn at all times. Pass must be returned at end of work shift and personnel checked out.
- .3 Security escort:
 - .1 Personnel employed on this project must be escorted when executing work in non-public areas during normal working hours. Personnel must be escorted in all areas after normal working hours.
 - .2 Submit an escort request to Departmental Representative at least 14 days before service is needed. For requests submitted within time noted above, costs of security escort will be paid for by Departmental Representative. Cost incurred by late request will be Contractor's responsibility.
 - .3 Any escort request may be cancelled free of charge if notification of cancellation is given at least 4 hours before scheduled time of escort. Cost incurred by late request will be Contractor's responsibility.
 - .4 Calculation of costs will be based on average hourly rate of security officer for minimum of 8 hours per day for late service request and of 4 hours for late cancellations.

1.7 BUILDING SMOKING ENVIRONMENT

- .1 Comply with smoking restrictions. Smoking is not permitted.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 SECTION INCLUDES

- .1 Coordination Work with other contractors
- .2 Scheduled preconstruction progress and final meetings.

1.2 RELATED SECTIONS

- .1 Section 01 11 00 - Summary of Work.
- .2 Section 01 91 00 - Commissioning - General Requirements.

1.3 DESCRIPTION

- .1 Coordination of progress schedules, submittals, use of site, temporary utilities, construction facilities and construction Work, with progress of Work of other contractors, under instructions of Departmental Representative.

1.4 PROJECT MEETINGS

- .1 Schedule and administer weekly project meetings throughout progress of Work as determined by Departmental Representative.
- .2 Prepare agenda for meetings.
- .3 Distribute written notice of each meeting four days in advance of meeting date to Departmental Representative.
- .4 Provide physical space and make arrangements for meetings.
- .5 Preside at meetings.
- .6 Record minutes. Include significant proceedings and decisions. Identify action by parties.
- .7 Reproduce and distribute copies of minutes within three days after each meeting and transmit to meeting participants, affected parties not in attendance and Departmental Representative.

1.5 CONSTRUCTION ORGANIZATION AND START-UP

- .1 Within 15 days after award of Contract, request a meeting of parties in contract to discuss and resolve administrative procedures and responsibilities.
- .2 Departmental Representative, Senior representatives of the Contractor and major Subcontractors, field inspectors and supervisors will be in attendance.

- .3 Establish time and location of meeting and notify parties concerned minimum 5 days before meeting.
- .4 Agenda to include following:
 - .1 Appointment of official representative of participants in Work.
 - .2 Schedule of Work, progress scheduling in accordance with Section 01 32 16.
 - .3 Schedule of submission of shop drawings in accordance with Section 01 33 00.
 - .4 Requirements for temporary facilities, site sign, offices, storage sheds, utilities, fences in accordance with Section 01 51 00.
 - .5 Delivery schedule of specified equipment in accordance with Section 01 32 00.
 - .6 Site security in accordance with Section 01 52 00.
 - .7 Proposed changes, change orders, procedures, approvals required, mark-up percentages permitted, time extensions, overtime, and administrative requirements (GC).
 - .8 Departmental Representative provided Products.
 - .9 Record drawings in accordance with Section 01 78 00.
 - .10 Maintenance in accordance with Section 01 78 00.
 - .11 Commissioning in accordance with Section 01 91 00.
 - .12 Take-over procedures, acceptance, and warranties in accordance with Section 01 77 00 and 01 78 00.
 - .13 Monthly progress claims, administrative procedures, photographs, and holdbacks (GC).
 - .14 Appointment of inspection and testing agencies or firms in accordance with Section 01 45 00.
 - .15 Insurances and transcript of policies (GC).
- .5 Comply with Departmental Representative's allocation of mobilization areas of site; for field offices and sheds, storage, access, traffic, and parking facilities.
- .6 During construction coordinate use of site and facilities through Departmental Representative's procedures for intra-project communications: Submittals, reports and records, schedules, coordination of drawings, recommendations, and resolution of ambiguities and conflicts.
- .7 Comply with instructions of Departmental Representative for use of temporary utilities and construction facilities.
- .8 Coordinate field engineering and layout work with Departmental Representative.

1.6 ON-SITE DOCUMENTS

- .1 Maintain at job site, one copy each of the following:
 - .1 Contract drawings.
 - .2 Specifications.
 - .3 Amendments.
 - .4 Reviewed shop drawings.
 - .5 Change orders.
 - .6 Other modifications to Contract.

- .7 Field test reports.
- .8 Copy of approved Work schedule.
- .9 Manufacturers' installation and application instructions.
- .10 Labour conditions and wage schedules.
- .11 Material Safety Data Sheets.
- .12 Labour and Material Bonds.
- .13 All applicable Municipal Permits.

1.7 SCHEDULES

- .1 Submit preliminary construction progress schedule in accordance with Section 01 32 00 and Commissioning Schedule in accordance with Section 01 91 00 to Departmental Representative coordinated with Departmental Representative's project schedule.
- .2 After review, revise and resubmit schedule to comply with revised project schedule.
- .3 During progress of Work revise and resubmit as directed by Departmental Representative.

1.8 CONSTRUCTION PROGRESS MEETINGS

- .1 During course of Work and 4 weeks prior to project completion, schedule progress meetings weekly.
- .2 Schedule separate commissioning meetings in accordance with Section 01 91 00.
- .3 Contractor, major subcontractors involved in Work and Departmental Representative are to be in attendance.
- .4 Notify parties minimum 7 days prior to meetings.
- .5 Unless directed otherwise by Departmental Representative, record minutes of meetings. Minutes shall be circulated to attending parties and affected parties not in attendance within 3 days after meeting.
- .6 Agenda to include following:
 - .1 Review, approval of minutes of previous meeting.
 - .2 Review of Work progress since previous meeting.
 - .3 Field observations, problems, conflicts.
 - .4 Problems which impede construction schedule.
 - .5 Review of off-site fabrication delivery schedules.
 - .6 Corrective measures and procedures to regain projected schedule.
 - .7 Revision to construction schedule.
 - .8 Progress schedule, during succeeding work period.
 - .9 Review submittal schedules: expedite as required.
 - .10 Maintenance of quality standards.
 - .11 Review proposed changes for effect on construction schedule and on completion date.
 - .12 Other business.

1.9 SUBMITTALS

- .1 Make submittal to Departmental Representative for review.
- .2 Submit preliminary shop drawings, product data and samples in accordance with Section 01 33 00 and 01 91 00 for review for compliance with Contract Documents; for field dimensions and clearances, for relation to available space, and for relation to Work of other contracts. After review, revise and resubmit for transmittal to Departmental Representative.
- .3 Submit requests for payment for review, and for transmittal to Departmental Representative.
- .4 Submit requests for interpretation of Contract Documents, and obtain instructions through Departmental Representative.
- .5 Process substitutions through Departmental Representative.
- .6 Process change orders through Departmental Representative.
- .7 Deliver closeout submittals for review and preliminary inspections, for transmittal to Departmental Representative.

1.10 COORDINATION DRAWINGS

- .1 Provide information required by Departmental Representative for preparation of coordination drawings.
- .2 Review and approve revised drawings for submittal to Departmental Representative.

1.11 CLOSEOUT PROCEDURES

- .1 Notify Departmental Representative when Work is considered ready for Substantial Performance.
- .2 Accompany Departmental Representative on preliminary inspection to determine items listed for completion or correction.
- .3 Comply with Departmental Representative's instructions for correction of items of Work listed in executed certificate of Substantial Performance and for access to Owner-occupied areas.
- .4 Notify Departmental Representative of instructions for completion of items of Work determined in Departmental Representative's final inspection.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

.1 Not Used.

PART 1 - GENERAL

1.1 ADMINISTRATIVE

- .1 Schedule and administer project meetings throughout the progress of the work at the call of Departmental Representative.
- .2 Prepare agenda for meetings.
- .3 Distribute written notice of each meeting 4 days in advance of meeting date to Departmental Representative.
- .4 Provide physical space and make arrangements for meetings.
- .5 Preside at meetings.
- .6 Unless directed otherwise by Departmental Representative, record minutes of meetings. Minutes shall be circulated to attending parties and affected parties not in attendance within 3 days after meeting.
- .7 Representative of Contractor, Subcontractor and suppliers attending meetings will be qualified and authorized to act on behalf of party each represents.

1.2 PRECONSTRUCTION MEETING

- .1 Within 15 days after award of Contract, request a meeting of parties in contract to discuss and resolve administrative procedures and responsibilities.
- .2 Departmental Representative, Contractor, major Subcontractors, field inspectors and supervisors will be in attendance.
- .3 Establish time and location of meeting and notify parties concerned minimum 5 days before meeting.
- .4 Incorporate mutually agreed variations to Contract Documents into Agreement, prior to signing.
- .5 Agenda to include:
 - .1 Appointment of official representative of participants in the Work.
 - .2 Schedule of Work: in accordance with Section 01 32 16.06 and 01 32 16.07.
 - .3 Schedule of submission of shop drawings, samples, mock-ups, colour chips. Submit submittals in accordance with Section 01 33 00.
 - .4 Requirements for temporary facilities, site sign, offices, storage sheds, utilities, fences in accordance with Section 01 52 00.
 - .5 Delivery schedule of specified equipment.
 - .6 Site security in accordance with Sections 01 35 13 and 01 56 00.
 - .7 Health and safety in accordance with Section 01 35 29.06.
 - .8 Proposed changes, change orders, procedures, approvals required, mark-up percentages permitted, time extensions, overtime,

- administrative requirements.
- .9 Owner provided products.
- .10 Record drawings and specifications in accordance with Sections 01 33 00 and 01 78 00.
- .11 Maintenance manuals in accordance with Section 01 78 00.
- .12 Take-over procedures, acceptance, warranties in accordance with Section 01 78 00.
- .13 Monthly progress claims, administrative procedures, photographs, hold backs.
- .14 Appointment of inspection and testing agencies or firms.
- .15 Insurances, transcript of policies.

1.3 PROGRESS MEETINGS

- .1 During course of Work and 4 weeks prior to project completion, schedule progress meetings weekly.
- .2 Contractor, major Subcontractors involved in Work and Departmental Representative are to be in attendance.
- .3 Notify parties minimum 5 days prior to meetings.
- .4 Record minutes of meetings and circulate to attending parties and affected parties not in attendance within 3 days after meeting.
- .5 Agenda to include the following:
 - .1 Review, approval of minutes of previous meeting.
 - .2 Review of Work progress since previous meeting.
 - .3 Field observations, problems, conflicts.
 - .4 Problems which impede construction schedule.
 - .5 Review of off-site fabrication delivery schedules.
 - .6 Corrective measures and procedures to regain projected schedule.
 - .7 Revision to construction schedule.
 - .8 Progress schedule, during succeeding work period.
 - .9 Review submittal schedules: expedite as required.
 - .10 Maintenance of quality standards.
 - .11 Review proposed changes for effect on construction schedule and on completion date.
 - .12 Other business.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 RELATED SECTIONS

- .1 Section 01 77 00 - Closeout Procedures.

1.2 ELECTRONIC COPY

- .1 Submit electronic copy of colour digital photography in jpg format, fine resolution.
- .2 Identification: name and number of project and date of exposure indicated.
- .3 Number of viewpoints: 4. Locations of viewpoints determined by Departmental Representative.
- .4 Frequency: as directed by Departmental Representative.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 DEFINITIONS

- .1 Activity: element of Work performed during course of Project. Activity normally has expected duration, and expected cost and expected resource requirements. Activities can be subdivided into tasks.
- .2 Bar Chart (GANTT Chart): graphic display of schedule-related information. In typical bar chart, activities or other Project elements are listed down left side of chart, dates are shown across top, and activity durations are shown as date-placed horizontal bars. Generally Bar Chart should be derived from commercially available computerized project management system.
- .3 Baseline: original approved plan (for project, work package, or activity), plus or minus approved scope changes.
- .4 Construction Work per Week: Monday to Friday, inclusive, will provide five (5) day work per week and define schedule calendar working days as part of Bar (GANTT) Chart submission.
- .5 Duration: number of work periods (not including holidays or other nonworking periods) required to complete activity or other project element. Usually expressed as workdays or workweeks.
- .6 Master Plan: summary-level schedule that identifies major activities and key milestones.
- .7 Milestone: significant event in project, usually completion of major deliverable.
- .8 Project Schedule: planned dates for performing activities and the planned dates for meeting milestones. Dynamic, detailed record of tasks or activities that must be accomplished to satisfy Project objectives. Monitoring and control process involves using Project Schedule in executing and controlling activities and is used as basis for decision making throughout project life cycle.
- .9 Project Planning, Monitoring and Control System: overall system operated by Departmental Representative to enable monitoring of project work in relation to established milestones.

1.2 REQUIREMENTS

- .1 Ensure Master Plan and Detail Schedules are practical and remain within specified Contract duration.
- .2 Plan to complete Work in accordance with prescribed milestones and time frame.
- .3 Limit activity durations to maximum of approximately 10 working days, to allow for progress reporting.

- .4 Ensure that it is understood that Award of Contract or time of beginning, rate of progress, Certificate of Substantial Performance and Certificate of Completion as defined times of completion are of essence of this contract.

1.3 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.
- .2 Submit to Departmental Representative within 5 working days of Award of Contract Bar (GANTT) Chart as Master Plan for planning, monitoring and reporting of project progress.
- .3 Submit Project Schedule to Departmental Representative within 5 working days of receipt of acceptance of Master Plan.

1.4 PROJECT MILESTONES

- .1 Project milestones form interim targets for Project Schedule.
 - .1 Long delivery equipment shop drawings within 20 working days of Award of Contract date.
 - .2 Certificate of Substantial Performance by or before Contract end date.
 - .3 Project must be completed in its entirety by or before contract end date.

1.5 MASTER PLAN

- .1 Structure schedule to allow orderly planning, organizing and execution of Work as Bar Chart (GANTT).
- .2 Departmental Representative will review and return revised schedules within 5 working days.
- .3 Revise impractical schedule and resubmit within 5 working days.
- .4 Accepted revised schedule will become Master Plan and be used as baseline for updates.

1.6 PROJECT SCHEDULE

- .1 Develop detailed Project Schedule derived from Master Plan.
- .2 Ensure detailed Project Schedule includes as minimum milestone and activity types as follows:
 - .1 Award.
 - .2 Shop Drawings, Samples.
 - .3 Permits.
 - .4 Mobilization.
 - .5 Electrical.
 - .6 Controls.
 - .7 Testing and Commissioning.

- .8 Supplied equipment long delivery items.
- .9 Departmental Representative supplied equipment required dates.

1.7 PROJECT SCHEDULE REPORTING

- .1 Update Project Schedule on weekly basis reflecting activity changes and completions, as well as activities in progress.
- .2 Include as part of Project Schedule, narrative report identifying Work status to date, comparing current progress to baseline, presenting current forecasts, defining problem areas, anticipated delays and impact with possible mitigation.

1.8 PROJECT MEETINGS

- .1 Discuss Project Schedule at regular site meetings specified in Section 01 31 19, identify activities that are behind schedule and provide measures to regain slippage. Activities considered behind schedule are those with projected start or completion dates later than current approved dates shown on baseline schedule.
- .2 Weather related delays with their remedial measures will be discussed and negotiated.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not used.

PART 1 - GENERAL

1.1 ADMINISTRATIVE

- .1 Submit to Departmental Representative submittals listed for review. Submit promptly and in orderly sequence to not cause delay in Work. Failure to submit in ample time is not considered sufficient reason for extension of Contract Time and no claim for extension by reason of such default will be allowed.
- .2 Do not proceed with Work affected by submittal until review is complete.
- .3 Present shop drawings, product data, samples and mock-ups in SI Metric units.
- .4 Where items or information is not produced in SI Metric units converted values are acceptable.
- .5 Review submittals prior to submission to Departmental Representative. This review represents that necessary requirements have been determined and verified, or will be, and that each submittal has been checked and co-ordinated with requirements of Work and Contract Documents. Submittals not stamped, signed, dated and identified as to specific project will be returned without being examined and considered rejected.
- .6 Notify Departmental Representative, in writing at time of submission, identifying deviations from requirements of Contract Documents stating reasons for deviations.
- .7 Verify field measurements and affected adjacent Work are co-ordinated.
- .8 Contractor's responsibility for errors and omissions in submission is not relieved by Departmental Representative's review of submittals.
- .9 Contractor's responsibility for deviations in submission from requirements of Contract Documents is not relieved by Departmental Representative review.
- .10 Keep one reviewed copy of each submission on site.
- .11 Submit number of hard copies specified for each type and format of submittal and also submit in electronic format as pdf files. Forward pdf, NMSEdit Professional spp, MS Word, MS Excel, MS Project and Autocad dwg files on USB compatible with PWGSC encryption requirements or through email or alternate electronic file sharing service such as ftp, as directed by Departmental Representative.

1.2 SHOP DRAWINGS AND PRODUCT DATA

- .1 The term "shop drawings" means drawings, diagrams, illustrations, schedules, performance charts, brochures and other data which are to be provided by Contractor to illustrate details of a portion of Work.
- .2 Submit drawings stamped and signed by professional engineer registered or

licensed in Province of Ontario of Canada.

- .3 Indicate materials, methods of construction and attachment or anchorage, erection diagrams, connections, explanatory notes and other information necessary for completion of Work. Where articles or equipment attach or connect to other articles or equipment, indicate that such items have been co-ordinated, regardless of Section under which adjacent items will be supplied and installed. Indicate cross references to design drawings and specifications.
- .4 Allow 5 working days for Departmental Representative's review of each submission.
- .5 Adjustments made on shop drawings by Departmental Representative are not intended to change Contract Price. If adjustments affect value of Work, state such in writing to Departmental Representative prior to proceeding with Work.
- .6 Make changes in shop drawings as Departmental Representative may require, consistent with Contract Documents. When resubmitting, notify Departmental Representative in writing of revisions other than those requested.
- .7 Accompany submissions with transmittal letter, in duplicate, containing:
 - .1 Date.
 - .2 Project title and number.
 - .3 Contractor's name and address.
 - .4 Identification and quantity of each shop drawing, product data and sample.
 - .5 Other pertinent data.
- .8 Submissions shall include:
 - .1 Date and revision dates.
 - .2 Project title and number.
 - .3 Name and address of:
 - .1 Subcontractor.
 - .2 Supplier.
 - .3 Manufacturer.
 - .4 Contractor's stamp, signed by Contractor's authorized representative certifying approval of submissions, verification of field measurements and compliance with Contract Documents.
 - .5 Details of appropriate portions of Work as applicable:
 - .1 Fabrication.
 - .2 Layout, showing dimensions, including identified field dimensions, and clearances.
 - .3 Setting or erection details.
 - .4 Capacities.
 - .5 Performance characteristics.
 - .6 Standards.
 - .7 Operating weight.
 - .8 Wiring diagrams.
 - .9 Single line and schematic diagrams.
 - .10 Relationship to adjacent work.

- .9 After Departmental Representative's review, distribute copies.
- .10 Submit three hard copies and one electronic copy of shop drawings for each requirement requested in specification Sections and as Departmental Representative may reasonably request.
- .11 Submit three hard copies and one electronic copy of product data sheets or brochures for requirements requested in specification Sections and as requested by Departmental Representative where shop drawings will not be prepared due to standardized manufacture of product.
- .12 Submit three hard copies and one electronic copy of test reports for requirements requested in specification Sections and as requested by Departmental Representative.
 - .1 Report signed by authorized official of testing laboratory that material, product or system identical to material, product or system to be provided has been tested in accord with specified requirements.
 - .2 Testing must have been within 3 years of date of contract award for project.
- .13 Submit three hard copies and one electronic copy of certificates for requirements requested in specification Sections and as requested by Departmental Representative.
 - .1 Statements printed on manufacturer's letterhead and signed by responsible officials of manufacturer of product, system or material attesting that product, system or material meets specification requirements.
 - .2 Certificates must be dated after award of project contract complete with project name.
- .14 Submit three hard copies and one electronic copy of manufacturers instructions for requirements requested in specification Sections and as requested by Departmental Representative.
 - .1 Pre-printed material describing installation of product, system or material, including special notices and Material Safety Data Sheets concerning impedances, hazards and safety precautions.
- .15 Submit three hard copies and one electronic copy of Manufacturer's Field Reports for requirements requested in specification Sections and as requested by Departmental Representative.
- .16 Documentation of the testing and verification actions taken by manufacturer's representative to confirm compliance with manufacturer's standards or instructions.
- .17 Submit three hard copies and one electronic copy of Operation and Maintenance Data for requirements requested in specification Sections and as requested by Departmental Representative.
- .18 Delete information not applicable to project.
- .19 Supplement standard information to provide details applicable to project.

- .20 If upon review by Departmental Representative, no errors or omissions are discovered or if only minor corrections are made, copies will be returned and fabrication and installation of Work may proceed. If shop drawings are rejected, noted copy will be returned and resubmission of corrected shop drawings, through same procedure indicated above, must be performed before fabrication and installation of Work may proceed.
- .21 The review of shop drawings by Environment and Climate Change Canada (ECCC) is for sole purpose of ascertaining conformance with general concept.
 - .1 This review shall not mean that ECCC approves detail design inherent in shop drawings, responsibility for which shall remain with Contractor submitting same, and such review shall not relieve Contractor of responsibility for errors or omissions in shop drawings or of responsibility for meeting requirements of construction and Contract Documents.
 - .2 Without restricting generality of foregoing, Contractor is responsible for dimensions to be confirmed and correlated at job site, for information that pertains solely to fabrication processes or to techniques of construction and installation and for co-ordination of Work of sub-trades.

1.3 PHOTOGRAPHIC DOCUMENTATION

- .1 Submit electronic copy of colour digital photography in jpg format, fine resolution monthly with progress statement and as directed by Departmental Representative.
- .2 Project identification: name and number of project and date of exposure indicated.
- .3 Number of viewpoints: 4 locations.
 - .1 Viewpoints and their location as determined by Departmental Representative.
- .4 Frequency of photographic documentation: weekly and as directed by Departmental Representative.
 - .1 Upon completion of: as directed by Departmental Representative.

1.4 CERTIFICATES AND TRANSCRIPTS

- .1 Immediately after award of Contract, submit Workplace Safety and Insurance Board Experience Report.
- .2 Submit transcription of insurance immediately after award of Contract.

1.5 FEES, PERMITS AND CERTIFICATES

- .1 Provide authorities having jurisdiction with information requested.
- .2 Pay fees and obtain certificates and permits required.
- .3 Furnish certificates and permits.

- .4 Submit acceptable certificate stating that suspended ceiling systems provide adequate support for electrical fixtures, as required by current bulletin of Electrical Safety Authority (ESA.)

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 REFERENCES

- .1 Canada Labour Code, Part 2, Canada Occupational Safety and Health Regulations.
- .2 Canadian Standards Association (CSA): Canada
 - .1 CSA S350-M1980(R2003), Code of Practice for Safety in Demolition of Structures.
- .3 National Building Code 2015 (NBC):
 - .1 NBC 2015, Division B, Part 8 Safety Measures at Construction and Demolition Sites.
- .4 National Fire Code 2015 (NFC):
 - .1 NFC 2015, Division B, Part 5 Hazardous Processes and Operations, subsection 5.6.1.3 Fire Safety Plan.
- .5 Province of Ontario:
 - .1 Occupational Health and Safety Act Revised Statutes of Ontario 1990, Chapter O.1 as amended, and Regulations for Construction Projects, O. Reg. 213/91 as amended.
 - .2 O. Reg. 490/09, Designated Substances.
 - .3 Workplace Safety and Insurance Act, 1997.
 - .4 Municipal statutes and authorities.
- .6 Treasury Board of Canada Secretariat (TBS):
 - .1 Treasury Board, Fire Protection Standard April 1, 2010
www.tbs-sct.gc.ca/pol/doc-eng.aspx?id=17316§ion=text.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
- .2 Submit site-specific Health and Safety Plan: Within 7 days after date of Notice to Proceed and prior to commencement of Work. Health and Safety Plan must include:
 - .1 Results of site specific safety hazard assessment.
 - .2 Results of safety and health risk or hazard analysis for site tasks and operation found in work plan.
 - .3 Measures and controls to be implemented to address identified safety hazards and risks.
- .3 Provide a Fire Safety Plan, specific to the work location, in accordance with NBC, Division B, Article 8.1.1.1.3 prior to commencement of work. The plan shall be coordinated with, and integrated into, the existing Facility Emergency Procedures and Evacuation Plan in place at the site. Departmental Representative will provide Facility, Emergency Procedures and Evacuation Plan. Deliver two copies of the Fire Safety Plan to the Departmental Representative not later than 14 days before commencing work.

- .4 Contractor's and Sub-contractors' Safety Communication Plan.
- .5 Contingency and Emergency Response Plan addressing standard operating procedures specific to the project site to be implemented during emergency situations. Coordinate plan with existing Facility Emergency Response requirements and procedures provided by Departmental Representative.
- .6 Departmental Representative will review Contractor's site-specific Health and Safety Plan and provide comments to Contractor within 5 days after receipt of plan. Revise plan as appropriate and resubmit plan to Departmental Representative within 3 days after receipt of comments from Departmental Representative.
- .7 Departmental Representative's review of Contractor's final Health and Safety plan should not be construed as approval and does not reduce the Contractor's overall responsibility for construction Health and Safety.
- .8 Submit names of personnel and alternates responsible for site safety and health.
- .9 Submit records of Contractor's Health and Safety meetings when requested.
- .10 Submit Contractor's authorized representative's work site health and safety inspection reports to Departmental Representative, weekly.
- .11 Submit copies of orders, directions or reports issued by health and safety inspectors of the authorities having jurisdiction.
- .12 Submit copies of incident and accident reports.
- .13 Submit Material Safety Data Sheets (MSDS).
- .14 Submit Workplace Safety and Insurance Board (WSIB)- Experience Rating Report.
- .15 Medical Surveillance: where prescribed by legislation, regulation or safety program, submit certification of medical surveillance for site personnel, in accordance with O. Reg. 490, prior to commencement of Work, and submit additional certifications for any new site personnel to Departmental Representative.

1.3 FILING OF NOTICE

- .1 File Notice of Project with Provincial authorities prior to commencement of Work.

1.4 WORK PERMIT

- .1 Obtain building permits related to project prior to commencement of Work.
- .2 Obtain 'Permit to Work Form' from AFD Contractor.
- .3 Obtain Hot Work Permit from Chief Plant Maintenance.

1.5 SAFETY ASSESSMENT

- .1 Perform site specific safety hazard assessment related to project.

1.6 MEETINGS

- .1 Schedule and administer Health and Safety meeting with Departmental Representative prior to commencement of Work.

1.7 REGULATORY REQUIREMENTS

- .1 Comply with the Acts and regulations of the Province of Ontario.
- .2 Comply with specified standards and regulations to ensure safe operations at site.

1.8 PROJECT/SITE CONDITIONS

- .1 Work at site will involve contact with:
 - .1 Silica in concrete, concrete block, concrete brick and ceramic tile.
 - .2 PCBs in transformer oil.

1.9 GENERAL REQUIREMENTS

- .1 Develop written site-specific Health and Safety Plan based on hazard assessment prior to beginning site Work and continue to implement, maintain, and enforce plan until final demobilization from site. Health and Safety Plan must address project specifications.
- .2 Departmental Representative may respond in writing, where deficiencies or concerns are noted and may request re-submission with correction of deficiencies or concerns either accepting or requesting improvements.
- .3 Relief from or substitution for any portion or provision of minimum Health and Safety standards specified herein or reviewed site-specific Health and Safety Plan shall be submitted to Departmental Representative in writing.

1.10 COMPLIANCE REQUIREMENTS

- .1 Comply with Ontario Occupational Health and Safety Act, R.S.O. 1990 Chapter 0.1, as amended.

1.11 RESPONSIBILITY

- .1 Be responsible for health and safety of persons on site, safety of property on site and for protection of persons adjacent to site and environment to extent that they may be affected by conduct of Work.
- .2 Comply with and enforce compliance by employees with safety requirements of Contract Documents, applicable federal, provincial, territorial and local statutes, regulations, and ordinances, and with site-specific Health

and Safety Plan.

- .3 Where applicable the Contractor shall be designated "Constructor", as defined by Occupational Health and Safety Act and Regulations for Construction Projects for the Province of Ontario.

1.12 UNFORSEEN HAZARDS

- .1 Should any unforeseen or peculiar safety-related factor, hazard, or condition become evident during performance of Work, immediately stop work and advise Departmental Representative verbally and in writing.
- .2 Follow procedures in place for Employees Right to Refuse Work as specified in the Occupational Health and Safety Act for the Province of Ontario.

1.13 HEALTH AND SAFETY CO-ORDINATOR

- .1 Employ and assign to Work, competent and authorized representative as Health and Safety Co-ordinator. Health and Safety Co-ordinator must:
 - .1 Have site-related working experience specific to activities associated with high voltage level.
 - .2 Have working knowledge of occupational safety and health regulations.
 - .3 Be responsible for completing Contractor's Health and Safety Training Sessions and ensuring that personnel not successfully completing required training are not permitted to enter site to perform Work.
 - .4 Be responsible for implementing, enforcing daily and monitoring site-specific Contractor's Health and Safety Plan.
 - .5 Be on site during execution of Work and report directly to and be under direction of Registered Occupational Hygienist.

1.14 POSTING OF DOCUMENTS

- .1 Ensure applicable items, articles, notices and orders are posted in conspicuous location on site in accordance with Acts and Regulations of Province of Ontario, and in consultation with Departmental Representative.
 - .1 Contractor's Safety Policy.
 - .2 Constructor's Name.
 - .3 Notice of Project.
 - .4 Name, trade, and employer of Health and Safety Representative or Joint Health and Safety Committee members (if applicable).
 - .5 Ministry of Labour Orders and reports.
 - .6 Occupational Health and Safety Act and Regulations for Construction Projects for Province of Ontario.
 - .7 Address and phone number of nearest Ministry of Labour office.
 - .8 Material Safety Data Sheets.
 - .9 Written Emergency Response Plan.
 - .10 Site Specific Safety Plan.
 - .11 Valid certificate of first aider on duty.
 - .12 WSIB "In Case of Injury At Work" poster.
 - .13 Location of toilet and cleanup facilities.

1.15 CORRECTION OF NON-COMPLIANCE

- .1 Immediately address health and safety non-compliance issues identified by authority having jurisdiction or by Departmental Representative.
- .2 Provide Departmental Representative with written report of action taken to correct non-compliance of health and safety issues identified.
- .3 Departmental Representative may stop Work if non-compliance of health and safety regulations is not corrected.

1.16 BLASTING

- .1 Blasting or other use of explosives is not permitted without prior receipt of written instruction by Departmental Representative.

1.17 POWDER ACTUATED DEVICES

- .1 Use powder actuated devices only after receipt of written permission from Departmental Representative.

1.18 WORK STOPPAGE

- .1 Give precedence to safety and health of public and site personnel and protection of environment over cost and schedule considerations for Work.
- .2 Assign responsibility and obligation to Health and Safety Coordinator to stop or start Work when, at Health and Safety Coordinator's discretion, it is necessary or advisable for reasons of health or safety. Departmental Representative may also stop Work for health and safety considerations.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not used.

PART 1 - GENERAL

1.1 RELATED REQUIREMENTS

- .1 Section 26 12 13.
- .2 Section 26 05 00.

1.2 DEFINITIONS

- .1 Environmental Pollution and Damage: presence of chemical, physical, biological elements or agents which adversely affect human health and welfare; unfavourably alter ecological balances of importance to human life; affect other species of importance to humans; or degrade environment aesthetically, culturally and/or historically.
- .2 Environmental Protection: prevention/control of pollution and habitat or environment disruption during construction.

1.3 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for review and include product characteristics, performance criteria, physical size, finish and limitations.
 - .2 Submit 2 copies of WHMIS MSDS.
- .3 Before commencing construction activities or delivery of materials to site, submit Environmental Protection Plan for review by Departmental Representative.
- .4 Environmental Protection Plan must include comprehensive overview of known or potential environmental issues to be addressed during construction.
- .5 Address topics at level of detail commensurate with environmental issue and required construction tasks.
- .6 Include in Environmental Protection Plan:
 - .1 Names of persons responsible for ensuring adherence to Environmental Protection Plan.
 - .2 Names and qualifications of persons responsible for manifesting hazardous waste to be removed from site.
 - .3 Names and qualifications of persons responsible for training site personnel.
 - .4 Descriptions of environmental protection personnel training program.
 - .5 Work area plan showing proposed activity in each portion of area and identifying areas of limited use or non-use.
 - .1 Plan to include measures for marking limits of use areas and methods for protection of features to be preserved within authorized work areas.
 - .6 Spill Control Plan to include procedures, instructions, and reports

- to be used in event of unforeseen spill of regulated substance.
- .7 Non-Hazardous solid waste disposal plan identifying methods and locations for solid waste disposal including clearing debris.
 - .8 Air pollution control plan detailing provisions to assure that dust, debris, materials, and trash, are contained on project site.
 - .9 Contaminant Prevention Plan identifying potentially hazardous substances to be used on job site; intended actions to prevent introduction of such materials into air, water, or ground; and detailing provisions for compliance with Federal, Provincial, and Municipal laws and regulations for storage and handling of these materials.

1.4 FIRES

- .1 Fires and burning of rubbish on site is not permitted.

1.5 WORK ADJACENT TO WATERWAYS

- .1 Construction equipment to be operated on land only.
- .2 Use waterway beds for borrow material only after written receipt of approval from Departmental Representative.
- .3 Waterways to be kept free of excavated fill, waste material and debris.
- .4 Design and construct temporary crossings to minimize erosion to waterways.
- .5 Do not skid logs or construction materials across waterways.
- .6 Avoid indicated spawning beds when constructing temporary crossings of waterways.
- .7 Blasting is allowed only above water and 100 m minimum from indicated spawning beds.

1.6 POLLUTION CONTROL

- .1 Maintain temporary erosion and pollution control features installed under this Contract.
- .2 Control emissions from equipment and plant in accordance with local authorities' emission requirements.
- .3 Prevent sandblasting and other extraneous materials from contaminating air and waterways beyond application area.
 - .1 Provide temporary enclosures where directed by Departmental Representative.
- .4 Cover or wet down dry materials and rubbish to prevent blowing dust and debris. Provide dust control for temporary roads.

1.7 NOTIFICATION

- .1 Departmental Representative will notify Contractor in writing of observed noncompliance with Federal, Provincial or Municipal environmental laws or regulations, permits, and other elements of Contractor's Environmental Protection plan.
- .2 Contractor: after receipt of such notice, inform Departmental Representative of proposed corrective action and take such action for approval by Departmental Representative.
 - .1 Take action only after receipt of written approval by Departmental Representative.
- .3 Departmental Representative will issue stop order of work until satisfactory corrective action has been taken.
- .4 No time extensions granted or equitable adjustments allowed to Contractor for such suspensions.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
- .2 Bury rubbish and waste materials on site where directed after receipt of written approval from Departmental Representative.
- .3 Ensure public waterways, storm and sanitary sewers remain free of waste and volatile materials disposal.
- .4 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .5 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

PART 1 - GENERAL

1.1 REFERENCES AND CODES

- .1 Perform Work in accordance with National Building Code of Canada (NBC) 2015, National Fire Code of Canada (NFC) 2015 and Ontario Building Code (OBC) 2012, including all amendments up to bid closing date and other codes of provincial or local application provided that in case of conflict or discrepancy, more stringent requirements apply as directed by the Departmental Representative.
- .2 Meet or exceed requirements of:
 - .1 Contract documents.
 - .2 Specified standards, codes and referenced documents.

1.2 HAZARDOUS MATERIAL DISCOVERY

- .1 Stop work immediately and notify Departmental Representative if materials which may contain designated substances or PCB's, other than those identified in Section 01 35 29 are discovered in course of work.

1.3 BUILDING SMOKING ENVIRONMENT

- .1 Comply with smoking restrictions.

1.4 ACCESSIBLE DESIGN

- .1 Comply with CSA B651-12 (R20170, Accessible Design for the Built Environment, unless specified otherwise. In any case of conflict or discrepancy between the building codes and CSA B651, the requirements of CSA B651 shall apply.

1.5 STATISTICAL INFORMATION

- .1 Provide statistical information to Departmental Representative:
 - .1 Within ten working days after March 31 and September 30 occurring between commencement of work and final completion
 - .2 Within ten working days after final completion.
- .2 Include in statistical information:
 - .1 Statement of total person days of labour used on site in performance of contract, including labour provided under sub-contracts.
 - .2 Estimate of total value in dollars of material delivered to site and installed, including material provided and installed under sub-contracts.
- .3 This information is required by Government of Canada solely to provide statistics that will aid in assessing socio-economic benefits of this project.

1.6 TAXES

- .1 Pay applicable Federal, Provincial and Municipal taxes.

1.7 EXAMINATION

- .1 Examine existing conditions and determine conditions affecting work.
- .2 Conduct concrete floor moisture testing using Calcium Chloride moisture tests.
 - .1 Submit test results to Departmental Representative for approval prior to installing any flooring. Conduct one test per 100 m² of area being covered.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 ABBREVIATIONS AND ACRONYMS

- .1 The abbreviations and acronyms are commonly found in the Project Manual and represent the associated organizations or terms.

1.2 MATERIALS, EQUIPMENT AND METHODS

- .1 A:
- .1 AB: anchor bolt.
 - .2 AC: acoustic.
 - .3 AC PAN: acoustic panel.
 - .4 ACU: acoustic unit ceiling.
 - .5 AFF: above finished floor.
 - .6 AC PLAS: acoustic plaster.
 - .7 ACT: acoustic tile.
 - .8 ACR CU LVR: acrylic cube louvre.
 - .9 ADH: adhesive.
 - .10 ADJ: adjustable.
 - .11 A/C: air conditioner.
 - .12 AHU: air handling unit.
 - .13 AL: aluminum.
 - .14 ANOD: anodized.
 - .15 APPROX: approximate.
 - .16 ARCH: architecture.
 - .17 ARCH BLK: architectural block.
 - .18 AVB: air vapour barrier.
- .2 B:
- .1 B: base.
 - .2 BEAST: benthic assessment of sediment.
 - .3 BH: bore hole.
 - .4 BHP: brake horse power.
 - .5 BL: bottom layer.
 - .6 BLK: block.
 - .7 BLKD: bulkhead.
 - .8 BM: beam.
 - .9 BOT: bottom.
 - .10 BMP: best management practice.
 - .11 B PL: base plate.
 - .12 BRG: bearing.
 - .13 BRK: brick.
 - .14 BSMT: basement.
 - .15 BTEX: benzene, toluene, ethylbenzene and xylenes.
 - .16 BUR: built-up roof.
- .3 C:
- .1 CAL: caliper.
 - .2 CANTIL: cantilever.
 - .3 CB: catch basin.
 - .4 CC: centre to centre.

- .5 CCN: contemplated change notice.
 - .6 CDF: controlled density fill.
 - .7 CEC: Canadian Electrical Code.
 - .8 CF: chair fabric.
 - .9 CHAN: channel.
 - .10 CHS: Canadian hydrographic service.
 - .11 CJ: construction joint.
 - .12 CL: centreline.
 - .13 CK: cork.
 - .14 CLG: ceiling.
 - .15 CLR: clear.
 - .16 COL: column.
 - .17 CONC: concrete.
 - .18 CONC BLK: concrete block.
 - .19 CONC BRK: concrete brick.
 - .20 CONT: continuous.
 - .21 CONT J: control joint.
 - .22 COMPL: complete.
 - .23 CM: centimetre. (Nursery stock).
 - .24 CP: circulating pump.
 - .25 CPL: cement plaster.
 - .26 CPM: critical path method.
 - .27 CPT: carpet.
 - .28 CPTT: carpet tile.
 - .29 CT: ceramic tile.
 - .30 CTE: connect to existing.
 - .31 CV: control valve.
 - .32 CVT: conductive vinyl tile.
 - .33 C/W: complete with.
- .4 D:
- .1 D: deep.
 - .2 dB: decibels.
 - .3 DB: dry-bulb.
 - .4 DD: dutch door.
 - .5 DEG: degree.
 - .6 DF: drinking fountain.
 - .7 DIA: diameter.
 - .8 DIM: dimension.
 - .9 DL: dead load.
 - .10 DMNT: demountable.
 - .11 DP: dampproofing.
 - .12 DR: door.
 - .13 DRP: drapery.
 - .14 DWL: dowel.
- .5 E:
- .1 EA: each.
 - .2 EC: epoxy coating.
 - .3 ECF: engineered containment facility.
 - .4 EE: each end.
 - .5 EF: each face (architectural/structural).
 - .6 EF: exhaust fan (mechanical/electrical).

- .7 EL: elevation.
 - .8 ELEC: electric.
 - .9 ELEV: elevator.
 - .10 EM: expanded metal.
 - .11 ENCL: enclosure.
 - .12 EQ: equal.
 - .13 ET: expansion tank.
 - .14 EXH: exhaust.
 - .15 EXIST: existing.
 - .16 EXPJ: expansion joint.
 - .17 EXP STRUCT: exposed structure.
 - .18 EXT: exterior.
 - .19 EW: each way.
 - .20 EWT: entering water temperature.
- .6 F:
- .1 FC: fuel contributed.
 - .2 FD: floor drain.
 - .3 FDN: foundation.
 - .4 FEAT W: feature wall.
 - .5 FEXT: fire extinguisher.
 - .6 FH: fire hose.
 - .7 FHC: fire hose cabinet.
 - .8 FHR: fire hose rack.
 - .9 FIN: finish.
 - .10 FIP: federal identity program.
 - .11 FL: floor.
 - .12 FLD: field.
 - .13 FLUOR: fluorescent.
 - .14 FR: frame.
 - .15 FRR: fire resistance rating.
 - .16 FTG: footing.
- .7 G:
- .1 GALV: galvanized steel.
 - .2 GB: grab bar.
 - .3 GBD: gypsum board.
 - .4 GC: General Conditions.
 - .5 GF: ground floor.
 - .6 GFCI: ground fault circuit interrupter.
 - .7 GL: glass or glazing.
 - .8 GL BLK: glass block.
 - .9 GPC: gypsum plaster ceiling.
 - .10 GPW: gypsum plaster wall.
 - .11 GT: glass tile.
- .8 H:
- .1 HB: hose bib.
 - .2 HC: hollow core.
 - .3 HCWD: hollow core wood door.
 - .4 HD: hand dryer.
 - .5 HDW: hardware.
 - .6 HDWD: hardwood.

- .7 HEX: heat exchanger.
 - .8 HM: hollow metal.
 - .9 HOR: horizontal.
 - .10 HOR EF: horizontal each face.
 - .11 HP: hydro pole.
 - .12 HPA: Hamilton Port Authority.
 - .13 HR: hour.
 - .14 HRV: heat recovery ventilator.
 - .15 HT: height.
 - .16 HTR: heater.
 - .17 HUM: humidifier.
 - .18 HWT: hot water tank.
 - .19 HYD: hydrant.
 - .20 HZ: Hertz frequency, cycles per second.
- .9 I:
- .1 ICF: insulated concrete formwork.
 - .2 ID: inside diameter.
 - .3 INS: insulation.
 - .4 INTLK: interlock.
- .10 J:
- .1 JT: joint.
- .11 K:
- .1 KPL: kick plate.
- .12 L:
- .1 LAT: leaving air temperature.
 - .2 LAV: lavatory.
 - .3 LDG: landing.
 - .4 LG: long.
 - .5 LINO: linoleum.
 - .6 LL: live load.
 - .7 LT: light.
 - .8 LWT: leaving water temperature.
- .13 M:
- .1 MAS: masonry.
 - .2 MAS FL: masonry flashing.
 - .3 MAX: maximum.
 - .4 MBG: metal bar grating.
 - .5 MCL: metal cube louvre.
 - .6 MECH: mechanical.
 - .7 MET: metal.
 - .8 MET DK: metal deck.
 - .9 MET FL: metal flashing.
 - .10 MET GRID CLG: metal grid ceiling.
 - .11 MET GRTG: metal grating.
 - .12 MET LIN CLG: metal linear ceiling.
 - .13 MET T PTN: metal toilet partition.
 - .14 MH: maintenance hole.
 - .15 MIN: minimum.

- .16 MLP: metal lath and plaster.
- .17 MO: masonry opening.
- .18 MR: marble.
- .19 MT: metal threshold.
- .20 MWP: membrane waterproofing.

- .14 N:
 - .1 NBC: national building code.
 - .2 NC: normally closed.
 - .3 NF: near face.
 - .4 NFC: national fire code.
 - .5 NIC: not in contract.
 - .6 NO: number.
 - .7 NRC: noise reduction coefficient.
 - .8 NRP: non removable pin.
 - .9 NTS: not to scale.

- .15 O:
 - .1 OA: outside air.
 - .2 OBC: Ontario building code.
 - .3 OC: on centre.
 - .4 OD: outside diameter.
 - .5 OPNG: opening.
 - .6 OPR: operator.
 - .7 OVHD: overhead.
 - .8 OWSJ: open web steel joist.

- .16 P:
 - .1 P: prefinished.
 - .2 PAH: polynuclear aromatic hydrocarbons.
 - .3 PARG: parging.
 - .4 PCC: precast concrete.
 - .5 PCT: porcelain ceramic tile.
 - .6 PED ACS FLG: pedestal access flooring.
 - .7 PF: panel fabric.
 - .8 PH: phase.
 - .9 PL: plate.
 - .10 PLAM: plastic laminate.
 - .11 PLAS: plaster.
 - .12 PLYWD: plywood.
 - .13 PR: pair.
 - .14 PREFAB: prefabricated.
 - .15 PREFIN: prefinished.
 - .16 PRESS: pressure.
 - .17 PRFL: profile.
 - .18 PRV: pressure regulating valve.
 - .19 PT: paint.
 - .20 PTD: paper towel dispenser.
 - .21 PTN: partition.
 - .22 PVC: polyvinyl chloride.

- .17 Q:
 - .1 QTB: quarry tile base.

- .2 QTF: quarry tile floor.
.3 QTR: quarry tile roof.
- .18 R:
.1 R: radius.
.2 RA: return air.
.3 RAD: return air damper.
.4 RB: resilient base.
.5 RC: reinforced concrete.
.6 RCPT: receptacle.
.7 RD: roof drain.
.8 REINF: reinforced/reinforcing.
.9 REQD: required.
.10 REQT: requirement.
.11 RFT: rubber floor tile.
.12 RM: room.
.13 RO: rough opening.
.14 RP: radiant panel.
.15 RRS: recycled rubber sheet.
.16 RRT: recycled rubber tile.
.17 RSD: rolling steel door.
.18 RSF: rubber sheet flooring.
.19 RT: rubber tile.
.20 RTU: roof top unit.
.21 RWL: rain water leader.
- .19 S:
.1 SA: supply air.
.2 SAN SEW: sanitary sewer.
.3 SCHED: schedule.
.4 SC: solid core.
.5 SCRN: screen.
.6 SCWD: solid core wood door.
.7 SD: smoke developed.
.8 SDT: static dissipative tile.
.9 SECT: section.
.10 SH: sill height.
.11 SIM: similar.
.12 SL: sliding.
.13 SLR: sealer.
.14 SPEC: specification.
.15 SS: stainless steel.
.16 STD: standard.
.17 STL: steel.
.18 STL BM: steel beam.
.19 STC: sound transmission class.
.20 STL FL DK: steel floor deck.
.21 STL PL: steel plate.
.22 STN: stone.
.23 STR: structure or structural.
.24 ST SEW: storm sewer.
.25 S&U: stain and urethane.
.26 S&V: stain and varnish.

- .27 SVT: solid vinyl tile.
- .20 T:
- .1 T: top.
 - .2 T&B: top and bottom.
 - .3 TCB: turbidity control plan.
 - .4 TEL: telephone.
 - .5 TER: terrazzo.
 - .6 TERT: terrazzo tile.
 - .7 THKNS: thickness.
 - .8 THR: threshold.
 - .9 TMPD: tempered.
 - .10 TOPG: topping.
 - .11 TRANSV: transverse.
 - .12 TYP: typical.
- .21 U:
- .1 U: urethane.
 - .2 U/C: undercut.
 - .3 UGRD: underground.
 - .4 UNO: unless noted otherwise.
 - .5 UOS: unless otherwise specified.
 - .6 U/S: underside.
 - .7 UR: urinal.
- .22 V:
- .1 V: volt.
 - .2 VCF: vinyl coated fabric.
 - .3 VCT: vinyl composition tile.
 - .4 VEL: velocity.
 - .5 VERT: vertical.
 - .6 VERT B: vertical blinds.
 - .7 VERT EF: vertical each face.
 - .8 VSF: vinyl sheet flooring.
 - .9 VPT: vinyl plank flooring.
 - .10 VT: vinyl tile.
 - .11 VWC: vinyl wall covering.
- .23 W:
- .1 WB: wet-bulb.
 - .2 WC: water closet.
 - .3 W-C: wall connectors.
 - .4 WD: wood.
 - .5 WDV: wood veneer.
 - .6 WG: water gauge.
 - .7 WH: wall hydrant.
 - .8 WHMIS: workplace hazardous materials information system.
 - .9 WP: waterproofing.
 - .10 WR: washroom.
 - .11 WSIB: workplace safety and insurance board.
 - .12 WT: weight.
 - .13 WTP: water treatment plant.

1.3 STANDARDS ORGANIZATIONS

- .1 Standards writing organizations:
 - .1 AA - Aluminum Association.
 - .2 ACPA - American Concrete Pipe Association.
 - .3 ANSI - American National Standards Institute.
 - .4 ASHRAE - American Society of Heating and Refrigerating and Air-Conditioning Engineers.
 - .5 ASTM - American Society for Testing and Materials.
 - .6 AWI/AWMAC - Architectural Woodwork Institute/Architectural Woodwork Manufacturers Association of Canada.
 - .7 AWPA - American Wood Preservers' Association.
 - .8 AWWA - American Water Works Association.
 - .9 BHMA - Builders Hardware Manufacturers Association.
 - .10 CCDC - Canadian Construction Documents Committee.
 - .11 CCMPA - Canadian Concrete Masonry Producers Association.
 - .12 CGSB - Canadian General Standards Board.
 - .13 CNTA - Canadian Nursery Trades Association.
 - .14 CPCA - Canadian Painting Contractors Association.
 - .15 CRCA - Canadian Roofing Contractors Association.
 - .16 CSA - Canadian Standards Association.
 - .17 CSC - Construction Specifications Canada.
 - .18 CSDMA - Canadian Steel Door Manufacturers Association.
 - .19 CSI - Construction Specifications Institute.
 - .20 CSSBI - Canadian Sheet Steel Building Institute.
 - .21 CRCA - Canadian Roofing Contractors Association.
 - .22 DHI - Door and Hardware Insitute.
 - .23 EEMAC - Electrical and Electronic Manufacturer's Association of Canada.
 - .24 ESA - Electrical Safety Authority.
 - .25 FCC - Fire Commissioner of Canada.
 - .26 FSC - Forest Stewardship Council.
 - .27 GANA - Glass Association of North America.
 - .28 HMMA - Hollow Metal Manufacturers Association.
 - .29 IEEE - Institute of Electrical and Electronics Engineers Inc.
 - .30 ISO - International Organization for Standardization.
 - .31 IWFA - International Window Film Association.
 - .32 LEED - LEED Canada, Leadership in Energy and Environmental Design.
 - .33 MPI - Master Painters Insitute.
 - .34 NAAMM - National Association of Architectural Metal Manufacturers.
 - .35 NCPI - National Clay Pipe Institute.
 - .36 NEMA - National Electrical Manufacturers Association.
 - .37 NFPA - National Fire Protection Association.
 - .38 OPSD - Ontario Provincial Standard Drawings.
 - .39 OPSS - Ontario Provincial Standard Specifications.
 - .40 PPI - Plasctics Pipe Institute.
 - .41 SDI - Steel Door Intitute.
 - .42 SCAQMD - South Coast Air Quality Management District.
 - .43 TIA - Telecommunications Industry Association.
 - .44 TIAC - Thermal Insulation Association of Canada.
 - .45 TTMAC - Terrazzo Tile and Marble Association of Canada.
 - .46 UL - Underwriters Laboratories.
 - .47 ULC - Underwriters Laboratories of Canada.

- .48 US EPA - United States Environmental Protection Agency.
- .49 WH - Warnock Hersey.

1.4 FEDERAL GOVERNMENT DEPART- MENTS AND AGENGIES

- .1 Departments, agencies and crown corporations.
 - .1 CEAA - Canadian Environmental Assessment Agency.
 - .2 CSC - Correctional Service Canada.
 - .3 CRA - Canada Revenue Agency.
 - .4 DND - Department of National Defence.
 - .5 EC - Environment Canada.
 - .6 FHBRO - Federal Heritage Buildings Review Office.
 - .7 HC - Health Canada.
 - .8 HCD - Heritage Conservation Directorate.
 - .9 LC - Labour Canada.
 - .10 PC - Parks Canada.
 - .11 PSPC - Public Service Procurement Canada.
 - .12 PWGSC - Public Works and Government Services Canada.
 - .13 RCMP - Royal Canadian Mounted Police.
 - .14 TBS - Treasury Board Secretariat.
 - .15 TC - Transport Canada.

1.5 PROVINCIAL GOVERNMENT DEPART- MENTS AND AGENGIES

- .1 MOEE - Ontario Ministry of Environment and Energy.
- .2 MOL - Ontario Ministry of Labour.
- .3 MTO and MOT - Ontario Ministry of Transportation.
- .4 TSSA - Technical Standards and Safety Authority.

1.6 INTERNATIONAL GOVERNMENT DEPART- MENTS AND AGENCIES

- .1 DOHMH - New York City Department of Health and Mental Hygiene, USA.
- .2 GSA - Government Services Administration, USA.

1.7 UNITS OF MEASURE METRIC

- .1 The following abbreviations of units of measure are commonly found in the Project Manual:
 - .1 C: Celsius.
 - .2 cm: centimetre.
 - .3 kg: kilogram.
 - .4 kg/m³: kilogram per cubic metre.
 - .5 kN: kilonewton.
 - .6 kPa: kilopascals.
 - .7 kw: kilowatts.
 - .8 l/s: litre per second.
 - .9 m: metre.
 - .10 m³: cubic metre.
 - .11 mg/kg: milligrams per kilogram.

- .12 mg/L: milligrams per litre.
- .13 mm: millimetres.
- .14 MPa: megapascal.
- .15 NTU: nephelometric turbidity unit.
- .16 ppm: parts per million.
- .17 ug/L: micrograms per litre.
- .18 ug/m³: micrograms per cubic metre.

1.8 UNITS OF MEASURE IMPERIAL

- .1 The following abbreviations of units of measure are commonly found in the Project Manual:
 - .1 BTU: British thermal units.
 - .2 CFM: cubic feet per minute.
 - .3 F: Fahrenheit.
 - .4 ft: foot/feet.
 - .5 FPI: fins per inch.
 - .6 FPM: feet per minute.
 - .7 ga: gauge.
 - .8 gpm: gallons per minute.
 - .9 in: inches.
 - .10 lbs: pounds.
 - .11 NTU: nephelometric turbidity unit.
 - .12 psi: pounds-force per square inch.
 - .13 PSIG: PSI gauge.
 - .14 ppm: parts per million.
 - .15 RPM: revolutions per minute.

1.9 LEED TERMS

- .1 Acronyms specific to LEED:
 - .1 CI: commercial interiors.
 - .2 EQ: environmental quality.
 - .3 MR: material and resources.
 - .4 NC: new construction.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 SECTION INCLUDES

- .1 Inspection and testing, administrative and enforcement requirements.
- .2 Tests and mix designs.
- .3 Equipment and system adjust and balance.

1.2 RELATED SECTIONS

- .1 Section 01 21 00 - Allowances.
- .2 Section 01 91 00 - Commissioning - General Requirements.

1.3 INSPECTION

- .1 Allow Departmental Representative access to Work. If part of Work is in preparation at locations other than Place of Work, allow access to such Work whenever it is in progress.
- .2 Give timely notice requesting inspection if Work is designated for special tests, inspections or approvals by Departmental Representative instructions, or law of Place of Work.
- .3 If Contractor covers or permits to be covered Work that has been designated for special tests, inspections or approvals before such is made, uncover such Work, have inspections or tests satisfactorily completed and make good such Work.
- .4 Departmental Representative may order any part of Work to be examined if Work is suspected to be not in accordance with Contract Documents. If, upon examination such work is found not in accordance with Contract Documents, correct such Work and pay cost of examination and correction. If such Work is found in accordance with Contract Documents, Departmental Representative shall pay cost of examination and replacement.

1.4 INDEPENDENT INSPECTION AGENCIES

- .1 Independent Inspection/Testing Agencies will be engaged by Departmental Representative for purpose of inspecting and/or testing portions of Work under Section 01 29 83, above and beyond those required of the Contractor.
- .2 Allocated costs: to Section 01 21 00.
- .3 Provide equipment required for executing inspection and testing by appointed agencies.
- .4 Employment of inspection/testing agencies does not relax responsibility to perform Work in accordance with Contract Documents.

- .5 If defects are revealed during inspection and/or testing, appointed agency will request additional inspection and/or testing to ascertain full degree of defect. Correct defect and irregularities as advised by Departmental Representative at no cost to Departmental Representative. Pay costs for retesting and reinspection.

1.5 ACCESS TO WORK

- .1 Allow inspection/testing agencies access to Work, off site manufacturing and fabrication plants.
- .2 Co-operate to provide reasonable facilities for such access.

1.6 PROCEDURES

- .1 Notify appropriate agency and Departmental Representative in advance of requirement for tests, in order that attendance arrangements can be made.
- .2 Submit samples and/or materials required for testing, as specifically requested in specifications. Submit with reasonable promptness and in an orderly sequence so as not to cause delay in Work.
- .3 Provide labour and facilities to obtain and handle samples and materials on site. Provide sufficient space to store and cure test samples.

1.7 REJECTED WORK

- .1 Remove defective Work, whether result of poor workmanship, use of defective products or damage and whether incorporated in Work or not, which has been rejected by Departmental Representative as failing to conform to Contract Documents. Replace or re-execute in accordance with Contract Documents.
- .2 Make good other Contractor's work damaged by such removals or replacements promptly.
- .3 If in opinion of Departmental Representative it is not expedient to correct defective Work or Work not performed in accordance with Contract Documents, Departmental Representative may deduct from Contract Amount difference in value between Work performed and that called for by Contract Documents, amount of which shall be determined by Departmental Representative.

1.8 REPORTS

- .1 Submit 4 copies of inspection and test reports to Departmental Representative.
- .2 Provide copies to Subcontractor of work being inspected or tested, manufacturer or fabricator of material being inspected or tested.

1.9 EQUIPMENT AND SYSTEMS

- .1 Submit testing, adjusting and balancing reports for mechanical, electrical

system and building equipment.

- .2 Submit Commissioning Documentation in accordance with Section 01 91 00.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 SECTION INCLUDES

- .1 Temporary utilities.

1.2 RELATED SECTIONS

- .1 Section 01 52 00 - Construction Facilities.
- .2 Section 01 56 00 - Temporary Barriers and Enclosures.

1.3 REFERENCES

1.4 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.

1.5 INSTALLATION AND REMOVAL

- .1 Provide temporary utilities controls in order to execute work expeditiously.
- .2 Remove from site all such work after use.

1.6 TEMPORARY HEATING AND VENTILATION

- .1 Provide temporary heating required during construction period, including attendance, maintenance and fuel.
- .2 Construction heaters used inside building must be vented to outside or be non-flameless type. Solid fuel salamanders are not permitted.
- .3 Provide temporary heat and ventilation in enclosed areas as required to:
 - .1 Facilitate progress of Work.
 - .2 Protect Work and products against dampness and cold.
 - .3 Prevent moisture condensation on surfaces.
 - .4 Provide ambient temperatures and humidity levels for storage, installation and curing of materials.
 - .5 Provide adequate ventilation to meet health regulations for safe working environment.
- .4 Maintain temperatures of minimum 10°C in areas where construction is in progress.
- .5 Ventilating:
 - .1 Prevent accumulations of dust, fumes, mists, vapours or gases in areas occupied during construction.
 - .2 Provide local exhaust ventilation to prevent harmful accumulation of hazardous substances into atmosphere of occupied areas.
 - .3 Dispose of exhaust materials in manner that will not result in harmful exposure to persons.

- .4 Ventilate storage spaces containing hazardous or volatile materials.
- .5 Ventilate temporary sanitary facilities.
- .6 Continue operation of ventilation and exhaust system for time after cessation of work process to assure removal of harmful contaminants.

- .6 Permanent heating system of building, may not be used when available. Be responsible for damage to heating system if use is permitted.

- .7 Pay costs for maintaining temporary heat, when using permanent heating system.

- .8 Maintain strict supervision of operation of temporary heating and ventilating equipment to:
 - .1 Conform with applicable codes and standards.
 - .2 Enforce safe practices.
 - .3 Prevent abuse of services.
 - .4 Prevent damage to finishes.
 - .5 Vent direct-fired combustion units to outside.

- .9 Be responsible for damage to Work due to failure in providing adequate heat and protection during construction.

1.7 TEMPORARY POWER AND LIGHT

- .1 Provide and pay for temporary electrical generator to provide power during construction to buildings affected by electrical shutdowns as indicated on contract documents.

- .2 Arrange for connection with Departmental Representative. Pay all costs for installation, maintenance and removal.

- .3 Temporary power for electric cranes and other equipment is responsibility of Contractor.

- .4 Provide and maintain temporary lighting throughout project. Ensure level of illumination on all floors and stairs is not less than 162 lx.

1.8 FIRE PROTECTION

- .1 Provide and maintain temporary fire protection equipment during performance of Work required by insurance companies having jurisdiction and governing codes, regulations and bylaws.

- .2 Burning rubbish and construction waste materials is not permitted on site.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 TEMPORARY EROSION AND SEDIMENTATION CONTROL

.1 Not Used.

PART 1 - GENERAL

1.1 SECTION INCLUDES

- .1 Construction aids.
- .2 Office and sheds.
- .3 Parking.
- .4 Project identification.

1.2 REFERENCES

- .1 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-1.189-2000, Exterior Alkyd Primer for Wood.
 - .2 CAN/CGSB-1.59-97, Alkyd Exterior Gloss Enamel.
- .2 Canadian Standards Association (CSA International)
 - .1 CSA A23.1-14/A23.2-14, Concrete Materials and Methods of Concrete Construction/Test Methods and Standard Practices for Concrete.
 - .2 CSA 0121-17, Douglas Fir Plywood.
 - .3 CSA Z797-09(R2014), Code of practice for Access Scaffold.
 - .4 CAN/CSA-Z321-96(R2006), Signs and Symbols for the Occupational Environment, withdrawn but still available from CSA, CCOHS and Techstreet.

1.3 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.

1.4 INSTALLATION AND REMOVAL

- .1 Prepare site plan indicating proposed location and dimensions of area to be fenced and used by Contractor, number of trailers to be used, avenues of ingress/egress to fenced area and details of fence installation.
- .2 Identify areas which have to be gravelled to prevent tracking of mud.
- .3 Indicate use of supplemental or other staging area.
- .4 Provide construction facilities in order to execute work expeditiously.
- .5 Remove from site all such work after use.

1.5 SCAFFOLDING

- .1 Scaffolding in accordance with CSA Z797.
- .2 Provide and maintain scaffolding, ramps, ladders, swing staging, platforms and temporary stairs.

1.6 HOISTING

- .1 Provide, operate and maintain hoists/cranes required for moving of workers, materials and equipment. Make financial arrangements with Subcontractors for use thereof.
- .2 Hoists/cranes shall be operated by qualified operator.

1.7 SITE STORAGE/LOADING

- .1 Confine work and operations of employees to areas defined by Contract Documents. Do not unreasonably encumber premises with products.
- .2 Do not load or permit to load any part of Work with a weight or force that will endanger the Work.

1.8 CONSTRUCTION PARKING

- .1 Parking will be permitted on site provided it does not disrupt performance of Work.
- .2 Provide and maintain adequate access to project site.
- .3 Build and maintain temporary roads where indicated or directed by Departmental Representative and provide snow removal during period of Work.
- .4 If authorized to use existing roads for access to project site, maintain such roads for duration of Contract and make good damage resulting from Contractors' use of roads.
- .5 Clean construction runways and taxi areas where used by Contractor's equipment.

1.09 EQUIPMENT, TOOL AND MATERIALS STORAGE

- .1 Provide and maintain, in a clean and orderly condition, lockable weatherproof sheds for storage of tools, equipment and materials.
- .2 Locate materials not required to be stored in weatherproof sheds on site in a manner to cause least interference with work activities.

1.10 SANITARY FACILITIES

- .1 Provide sanitary facilities for work force in accordance with governing regulations and ordinances.
- .2 Post notices and take such precautions as required by local health authorities. Keep area and premises in sanitary condition.

1.11 CONSTRUCTION SIGNAGE

- .1 Provide and erect, within three weeks of signing Contract, a project sign in a location designated by Departmental Representative.
- .2 Construction sign 1.2 x 2.4] m, of wood frame and plywood construction painted with exhibit lettering produced by a professional sign painter.
- .3 Indicate on sign, name of Owner, Consultant and Contractor, of a design style established by Departmental Representative.
- .4 No other signs or advertisements, other than warning signs, are permitted on site.
- .5 Provide project identification site sign comprising foundation, framing, and one 1200 x 2400 mm signboard as detailed and as described below.
 - .1 Foundations: 15 MPa concrete to CSA A23.1/A23.2 minimum 200 mm x 900 mm deep.
 - .2 Framework and battens: SPF, pressure treated minimum 89 x 89 mm.
 - .3 Signboard: 19 mm Medium Density Overlaid Douglas Fir Plywood to CSA O121.
 - .4 Paint: alkyd enamel to CAN/CGSB-1.59 over exterior alkyd primer to CAN/CGSB-1.189.
 - .5 Fasteners: hot-dip galvanized steel nails and carriage bolts.
 - .6 Vinyl sign face: printed project identification, self adhesive, vinyl film overlay, supplied by Departmental Representative.
- .6 Locate project identification sign as directed by Departmental Representative and construct as follows:
 - .1 Build concrete foundation, erect framework, and attach signboard to framing.
 - .2 Paint all surfaces of signboard and framing with one coat primer and two coats enamel. Colour white on signboard face, black on other surfaces.
 - .3 Apply vinyl sign face overlay to painted signboard face in accordance with installation instruction supplied.
- .7 Direct requests for approval to erect a Consultant/Contractor signboard to Departmental Representative. For consideration general appearance of Consultant/Contractor signboard must conform to project identification site sign. Wording shall be in both official languages.
- .8 Signs and notices for safety and instruction shall be in both official languages. Graphic symbols shall conform to CAN/CSA-Z321.
- .9 Maintain approved signs and notices in good condition for duration of project, and dispose of off site on completion of project or earlier if directed by Departmental Representative.

1.12 PROTECTION AND MAINTENANCE OF TRAFFIC

- .1 Maintain and protect traffic on affected roads during construction period except as otherwise specifically directed by Departmental Representative.
- .2 Provide measures for protection and diversion of traffic, including provision of watch-persons and flag-persons, erection of barricades, placing of lights around and in front of equipment and work, and erection and maintenance of adequate warning, danger, and direction signs
- .3 Protect travelling public from damage to person and property.
- .4 Contractor's traffic on roads selected for hauling material to and from site to interfere as little as possible with public traffic.
- .5 Verify adequacy of existing roads and allowable load limit on these roads. Contractor: responsible for repair of damage to roads caused by construction operations.
- .6 Provide necessary lighting, signs, barricades, and distinctive markings for safe movement of traffic.
- .7 Dust control: adequate to ensure safe operation at all times.
- .8 Provide snow removal during period of Work.
- .9 Remove, upon completion of work, haul roads designated by Departmental Representative.

1.13 CLEAN-UP

- .1 Remove construction debris, waste materials, packaging material from work site daily.
- .2 Clean dirt or mud tracked onto paved or surfaced roadways.
- .3 Store materials resulting from demolition activities that are salvageable.
- .4 Stack stored new or salvaged material.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

- .1 Not Used.

PART 1 - GENERAL

1.1 SECTION INCLUDES

- .1 Barriers.
- .2 Environmental Controls.
- .3 Traffic Controls.
- .4 Fire Routes.

1.2 RELATED SECTIONS

- .1 Section 01 51 00 - Temporary Utilities.
- .2 Section 01 52 00 - Construction Facilities.

1.3 REFERENCES

- .1 Canadian General Standards Board (CGSB):
 - .1 CAN/CGSB-1.189-2000, Exterior Alkyd Primer for Wood.
 - .2 CAN/CGSB-1.59-97, Alkyd Exterior Gloss Enamel.
- .2 Canadian Standards Association (CSA):
 - .1 CSA O121-17, Douglas Fir Plywood.
- .3 Public Works Government Services Canada (PWGSC) Standard
 - .1 PWGSC Standard Acquisition Clauses and Conditions (SACC)-ID: R0202D,
Title: General Conditions 'C', In Effect as Of: May 14, 2004.

1.4 INSTALLATION AND REMOVAL

- .1 Provide temporary controls in order to execute Work expeditiously.
- .2 Remove from site all such work after use.

1.5 HOARDING

- .1 Erect temporary site enclosures using 38 x 89 mm construction grade lumber framing at 600 mm o.c. and 1200 x 2400 x 13 mm exterior grade fir plywood to CSA O121.
- .2 Apply plywood panels vertically flush and butt jointed unless otherwise indicated.
- .3 Provide onelockable truck entrance gates and at least one pedestrian door as directed and conforming to applicable traffic restrictions on adjacent streets. Equip gates with locks and keys.
- .4 Erect and maintain pedestrian walkways including roof and side covers, complete with signs and electrical lighting as required by law.

- .5 Paint public side of site enclosure in selected colours with one coat primer to CAN/CGSB-1.189 and one coat exterior paint to CAN/CGSB-1.59. Maintain public side of enclosure in clean condition.
- .6 Erect temporary site enclosure using new 1.2 m high snow fence wired to rolled steel "T" bar fence posts spaced at 2.4 m o.c. Provide one lockable truck gate. Maintain fence in good repair.
- .7 Provide barriers around trees and plants designated to remain. Protect from damage by equipment and construction procedures.
- .8 Erect temporary site enclosure using modular freestanding fencing: galvanized, minimum 1.8 m high, chain link or welded steel mesh, pipe rail. Provide two lockable truck entrance gates and at least one pedestrian door as directed and conforming to applicable traffic restrictions on adjacent streets. Equip gates with locks and keys. Maintain fence in good repair.

1.6 GUARD RAILS AND BARRICADES

- .1 Provide secure, rigid guard rails and barricades around deep excavations, open shafts, open stair wells, open edges of floors and roofs..
- .2 Provide as required by governing authorities.

1.7 WEATHER ENCLOSURES

- .1 Provide weather tight closures to unfinished door and window openings, tops of shafts and other openings in floors and roofs.
- .2 Close off floor areas where walls are not finished; seal off other openings; enclose building interior work for temporary heat.
- .3 Design enclosures to withstand wind pressure and snow loading.

1.8 DUST TIGHT SCREENS

- .1 Provide dust tight screens or insulated partitions to localize dust generating activities, and for protection of workers, finished areas of Work and public.
- .2 Maintain and relocate protection until such work is complete.

1.9 ACCESS TO SITE

- .1 Provide and maintain access roads, sidewalk crossings, ramps and construction runways as may be required for access to Work.

1.10 PUBLIC TRAFFIC FLOW

- .1 Provide and maintain competent signal flag operators, traffic signals, barricades and flares, lights, or lanterns as required to perform Work and protect the public.

1.11 FIRE ROUTES

- .1 Maintain access to property including overhead clearances for use by emergency response vehicles.

1.12 PROTECTION FOR OFF-SITE AND PUBLIC PROPERTY

- .1 Protect surrounding private and public property from damage during performance of Work.
- .2 Be responsible for damage incurred.

1.13 PROTECTION OF BUILDING FINISHES

- .1 Provide protection for finished and partially finished building finishes and equipment during performance of Work.
- .2 Provide necessary screens, covers, and hoardings.
- .3 Confirm with Departmental Representative locations and installation schedule 3 days prior to installation.
- .4 Be responsible for damage incurred due to lack of or improper protection.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 SECTION INCLUDES

- .1 Product quality, availability, storage, handling, protection, and transportation.
- .2 Manufacturer's instructions.
- .3 Quality of Work, coordination and fastenings.
- .4 Existing facilities.

1.2 RELATED SECTIONS

- .1 Section 01 45 00 - Quality Control.

1.3 REFERENCES

- .1 Within text of specifications, reference may be made to reference standards.
- .2 Conform to these standards, in whole or in part as specifically requested in specifications.
- .3 If there is question as to whether any product or system is in conformance with applicable standards, Departmental Representative reserves right to have such products or systems tested to prove or disprove conformance.
- .4 The cost for such testing will be born by Departmental Representative in event of conformance with Contract Documents or by Contractor in event of non-conformance.
- .5 Conform to latest date of issue of referenced standards in effect on date of submission of Bids, except where specific date or issue is specifically noted.
- .6 OPSS Ontario Provincial Standard Specifications and OPSD Ontario Provincial Standard Drawings quoted in these specifications are available online at <http://www.raqsa.mto.gov.on.ca/techpubs/ops.nsf/OPSHomepage>.

1.4 QUALITY

- .1 Products, materials, equipment and articles (referred to as products throughout specifications) incorporated in Work shall be new, not damaged or defective, and of best quality (compatible with specifications) for purpose intended. If requested, furnish evidence as to type, source and quality of Products provided.
- .2 Defective products, whenever identified prior to completion of Work, will be rejected, regardless of previous inspections. Inspection does not relieve responsibility, but is precaution against oversight or error. Remove and replace defective products at own expense and be responsible for delays

and expenses caused by rejection.

- .3 Should any dispute arise as to quality or fitness of products, decision rests strictly with Departmental Representative based upon requirements of Contract Documents.
- .4 Unless otherwise indicated in specifications, maintain uniformity of manufacture for any particular or like item throughout building.
- .5 Permanent labels, trademarks and nameplates on products are not acceptable in prominent locations, except where required for operating instructions, or when located in mechanical or electrical rooms.

1.5 AVAILABILITY

- .1 Immediately upon signing Contract, review product delivery requirements and anticipate foreseeable supply delays for any items. If delays in supply of products are foreseeable, notify Departmental Representative of such, in order that substitutions or other remedial action may be authorized in ample time to prevent delay in performance of Work.
- .2 In event of failure to notify Departmental Representative at commencement of Work and should it subsequently appear that Work may be delayed for such reason, Departmental Representative reserves right to substitute more readily available products of similar character, at no increase in Contract Price or Contract Time.

1.6 METRIC SIZED MATERIALS

- .1 SI metric units of measurement are used exclusively on the drawings and in the specifications for this project.
- .2 The Contractor is required to provide metric products in the sizes called for in the Contract Documents except where a valid claim can be made that a particular product is not available on the Canadian market.
- .3 Claims for exemptions from use of metric sized products shall be in writing and fully substantiated with supportive documentation. Promptly submit application to Departmental Representative for consideration and ruling. Non-metric sized products may not be used unless Contractor's application has been approved in writing by the Departmental Representative.
- .4 Difficulties caused by the Contractor's lack of planning and effort to obtain modular metric sized products which are available on the Canadian market will not be considered sufficient reasons for claiming that they cannot be provided.
- .5 Claims for additional costs due to provision of specified modular metric sized products will not be considered.

1.7 STORAGE, HANDLING AND PROTECTION

- .1 Handle and store products in manner to prevent damage, adulteration,

deterioration and soiling and in accordance with manufacturer's instructions when applicable.

- .2 Store packaged or bundled products in original and undamaged condition with manufacturer's seal and labels intact. Do not remove from packaging or bundling until required in Work.
- .3 Store products subject to damage from weather in weatherproof enclosures.
- .4 Store cementitious products clear of earth or concrete floors, and away from walls.
- .5 Keep sand, when used for grout or mortar materials, clean and dry. Store sand on wooden platforms and cover with waterproof tarpaulins during inclement weather.
- .6 Store sheet materials and lumber on flat, solid supports and keep clear of ground. Slope to shed moisture.
- .7 Store and mix paints in heated and ventilated room. Remove oily rags and other combustible debris from site daily. Take every precaution necessary to prevent spontaneous combustion.
- .8 Remove and replace damaged products at own expense and to satisfaction of Departmental Representative.
- .9 Touch-up damaged factory finished surfaces to Departmental Representative's satisfaction. Use touch-up materials to match original. Do not paint over name plates.

1.8 TRANSPORTATION

- .1 Pay costs of transportation of products required in performance of Work.
- .2 Transportation cost of products supplied by Owner will be paid for by Departmental Representative. Unload, handle and store such products.

1.9 MANUFACTURER'S INSTRUCTIONS

- .1 Unless otherwise indicated in specifications, install or erect products in accordance with manufacturer's instructions. Do not rely on labels or enclosures provided with products. Obtain written instructions directly from manufacturers.
- .2 Notify Departmental Representative in writing, of conflicts between specifications and manufacturer's instructions, so that Departmental Representative may establish course of action.
- .3 Improper installation or erection of products, due to failure in complying with these requirements, authorizes Departmental Representative to require removal and re-installation at no increase in Contract Price or Contract Time.

1.10 QUALITY OF WORK

- .1 Ensure Quality of Work is of highest standard, executed by workers experienced and skilled in respective duties for which they are employed. Immediately notify Departmental Representative if required Work is such as to make it impractical to produce required results.
- .2 Do not employ anyone unskilled in their required duties. Departmental Representative reserves right to require dismissal from site, workers deemed incompetent or careless.
- .3 Decisions as to standard or fitness of Quality of Work in cases of dispute rest solely with Departmental Representative, whose decision is final.

1.11 CO-ORDINATION

- .1 Ensure cooperation of workers in laying out Work. Maintain efficient and continuous supervision.
- .2 Be responsible for coordination and placement of openings, sleeves and accessories.

1.12 CONCEALMENT

- .1 In finished areas, conceal pipes, ducts and wiring in floors, walls and ceilings, except where indicated otherwise.
- .2 Before installation, inform Departmental Representative if there is interference. Install as directed by Departmental Representative.

1.13 REMEDIAL WORK

- .1 Refer to Section 01 73 03.
- .2 Perform remedial work required to repair or replace parts or portions of Work identified as defective or unacceptable. Coordinate adjacent affected Work as required.
- .3 Perform remedial work by specialists familiar with materials affected. Perform in a manner to neither damage nor put at risk any portion of Work.

1.14 LOCATION OF FIXTURES

- .1 Consider location of fixtures, outlets, and mechanical and electrical items indicated as approximate.
- .2 Inform Departmental Representative of conflicting installation. Install as directed.

1.15 FASTENINGS

- .1 Provide metal fastenings and accessories in same texture, colour and finish as adjacent materials, unless indicated otherwise.

- .2 Prevent electrolytic action between dissimilar metals and materials.
- .3 Use non-corrosive hot dip galvanized steel fasteners and anchors for securing exterior work, unless stainless steel or other material is specifically requested in affected specification Section.
- .4 Space anchors within individual load limit or shear capacity and ensure they provide positive permanent anchorage. Wood, or any other organic material plugs are not acceptable.
- .5 Keep exposed fastenings to a minimum, space evenly and install neatly.
- .6 Fastenings which cause spalling or cracking of material to which anchorage is made are not acceptable.

1.16 FASTENINGS - EQUIPMENT

- .1 Use fastenings of standard commercial sizes and patterns with material and finish suitable for service.
- .2 Use heavy hexagon heads, semi-finished unless otherwise specified. Use No.304 stainless steel for exterior areas.
- .3 Bolts may not project more than one diameter beyond nuts.
- .4 Use plain type washers on equipment, sheet metal and soft gasket lock type washers where vibrations occur. Use resilient washers with stainless steel.

1.17 PROTECTION OF WORK IN PROGRESS

- .1 Prevent overloading of any part of building. Do not cut, drill or sleeve any load bearing structural member, unless specifically indicated without written approval of Departmental Representative.

1.18 EXISTING UTILITIES

- .1 When breaking into or connecting to existing services or utilities, execute Work at times directed by local governing authorities, with minimum of disturbance to Work, building occupants and pedestrian and vehicular traffic.
- .2 Protect, relocate or maintain existing active services. When services are encountered, cap off in manner approved by authority having jurisdiction. Stake and record location of capped service.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

.1 Not Used.

PART 1 - GENERAL

1.1 SECTION INCLUDES

- .1 Field engineering survey services to measure and stake site.
- .2 Survey services to establish and confirm inverts for Work.
- .3 Recording of subsurface conditions found.

1.2 REFERENCES

- .1 Owner's identification of existing survey control points and property limits.

1.3 QUALIFICATIONS OF SURVEYOR

- .1 Qualified registered land surveyor, licensed to practise in Place of Work, acceptable to Departmental Representative.

1.4 SURVEY REFERENCE POINTS

- .1 Existing base horizontal and vertical control points are designated on drawings.
- .2 Locate, confirm and protect control points prior to starting site work. Preserve permanent reference points during construction.
- .3 Make no changes or relocations without prior written notice to Departmental Representative.
- .4 Report to Departmental Representative when reference point is lost or destroyed, or requires relocation because of necessary changes in grades or locations.
- .5 Require surveyor to replace control points in accordance with original survey control.

1.5 SURVEY REQUIREMENTS

- .1 Establish lines and levels for electrical work.
- .2 Survey the existing system clearances, dimensions and distances.

1.6 EXISTING SERVICES

- .1 Before commencing work, establish location and extent of service lines in area of Work and notify Departmental Representative of findings.
- .2 Remove abandoned service lines within 2 m of structures. Cap or otherwise seal lines at cut-off points as directed by Departmental Representative.

1.7 LOCATION OF EQUIPMENT AND FIXTURES

- .1 Location of equipment, fixtures and outlets indicated or specified are to be considered as approximate.
- .2 Locate equipment, fixtures and distribution systems to provide minimum interference and maximum usable space and in accordance with manufacturer's recommendations for safety, access and maintenance.
- .3 Inform Departmental Representative of impending installation and obtain approval for actual location.
- .4 Submit field drawings to indicate relative position of various services and equipment when required by Departmental Representative.

1.8 RECORDS

- .1 Maintain a complete, accurate log of control and survey work as it progresses.
- .2 On completion of foundations and major site improvements, prepare a certified survey showing dimensions, locations, angles and elevations of Work.
- .3 Record locations of maintained, re-routed and abandoned service lines.

1.9 SUBMITTALS

- .1 Submit name and address of Surveyor to Departmental Representative.
- .2 On request of Departmental Representative, submit documentation to verify accuracy of field engineering work.
- .3 Submit certificate signed by surveyor certifying and noting those elevations and locations of completed Work that conform and do not conform with Contract Documents.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 SUBMITTALS

- .1 Submittals: in accordance with Section 01 33 00.
- .2 Submit written request in advance of cutting or alteration which affects:
 - .1 Structural integrity of elements of project.
 - .2 Integrity of weather-exposed or moisture-resistant elements.
 - .3 Efficiency, maintenance, or safety of operational elements.
 - .4 Visual qualities of sight-exposed elements.
 - .5 Work of Owner or separate contractor.
- .3 Include in request:
 - .1 Identification of project.
 - .2 Location and description of affected Work.
 - .3 Statement on necessity for cutting or alteration.
 - .4 Description of proposed Work, and products to be used.
 - .5 Alternatives to cutting and patching.
 - .6 Effect on Work of Owner or separate contractor.
 - .7 Written permission of affected separate contractor.
 - .8 Date and time work will be executed.

1.2 MATERIALS

- .1 Required for original installation.
- .2 Change in Materials: Submit request for substitution in accordance with Section 01 33 00.

1.3 PREPARATION

- .1 Inspect existing conditions, including elements subject to damage or movement during cutting and patching.
- .2 After uncovering, inspect conditions affecting performance of Work.
- .3 Beginning of cutting or patching means acceptance of existing conditions.
- .4 Provide supports to assure structural integrity of surroundings; provide devices and methods to protect other portions of project from damage.
- .5 Provide protection from elements for areas which are to be exposed by uncovering work; maintain excavations free of water.

1.4 EXECUTION

- .1 Execute cutting, fitting, and patching including excavation and fill to complete Work.
- .2 Fit several parts together, to integrate with other Work.

- .3 Uncover Work to install ill-timed Work.
- .4 Remove and replace defective and non-conforming Work.
- .5 Remove samples of installed Work for testing.
- .6 Provide openings in non-structural elements of Work for penetrations of mechanical and electrical Work.
- .7 Execute Work by methods to avoid damage to other Work, and which will provide proper surfaces to receive patching and finishing.
- .8 Employ original installer to perform cutting and patching for weather-exposed and moisture-resistant elements, and sight-exposed surfaces.
- .9 Cut rigid materials using masonry saw or core drill. Pneumatic or impact tools not allowed on masonry work without prior approval.
- .10 Restore work with new products in accordance with requirements of Contract Documents.
- .11 Submit proposed materials, finishes and installation method for patching to Departmental Representative for approval, prior to patching.
- .12 Refinish surfaces to match adjacent finishes: Refinish continuous surfaces to nearest intersection. Refinish assemblies by refinishing entire unit.
- .13 Fit Work airtight to pipes, sleeves, ducts, conduit, and other penetrations through surfaces.
- .14 At penetration of fire rated wall, ceiling, or floor construction, completely seal voids with firestopping material in accordance with Section 07 84 00, full thickness of the construction element.
- .15 Conceal pipes, ducts and wiring in floor, wall and ceiling construction of finished areas except where indicated otherwise.

1.5 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials for reuse, recycling, composting and anaerobic digestion in accordance with Section 01 74 20.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

.1 Not Used.

PART 1 - GENERAL

1.1 SECTION INCLUDES

- .1 Progressive cleaning.
- .2 Final cleaning.

1.2 PROJECT CLEANLINESS

- .1 Maintain Work in tidy condition, free from accumulation of waste products and debris, other than that caused by Owner or other Contractors.
- .2 Remove waste materials from site at regularly scheduled times or dispose of as directed by Departmental Representative. Do not burn waste materials on site.
- .3 Clear snow and ice from access to building, bank/pile snow in designated areas only.
- .4 Make arrangements with and obtain permits from authorities having jurisdiction for disposal of waste and debris.
- .5 Provide on-site containers for collection of waste materials and debris.
- .6 Provide and use clearly marked separate bins for recycling. Refer to Section 01 74 20.
- .7 Remove waste material and debris from site and deposit in waste container at end of each working day.
- .8 Dispose of waste materials and debris off site.
- .9 Clean interior areas prior to start of finish work, and maintain areas free of dust and other contaminants during finishing operations.
- .10 Store volatile waste in covered metal containers, and remove from premises at end of each working day.
- .11 Provide adequate ventilation during use of volatile or noxious substances. Use of building ventilation systems is not permitted for this purpose.
- .12 Use only cleaning materials recommended by manufacturer of surface to be cleaned, and as recommended by cleaning material manufacturer.
- .13 Schedule cleaning operations so that resulting dust, debris and other contaminants will not fall on wet, newly painted surfaces nor contaminate building systems.

1.3 FINAL CLEANING

- .1 When Work is Substantially Performed, remove surplus products, tools,

- construction machinery and equipment not required for performance of remaining Work.
- .2 Remove waste products and debris other than that caused by others, and leave Work clean and suitable for occupancy.
 - .3 Prior to final review, remove surplus products, tools, construction machinery and equipment.
 - .4 Remove waste products and debris other than that caused by Owner or other Contractors.
 - .5 Remove waste materials from site at regularly scheduled times or dispose of as directed by Departmental Representative. Do not burn waste materials on site.
 - .6 Make arrangements with and obtain permits from authorities having jurisdiction for disposal of waste and debris.
 - .7 Clean and polish glass, mirrors, hardware, wall tile, stainless steel, chrome, porcelain enamel, baked enamel, plastic laminate, and mechanical and electrical fixtures. Replace broken, scratched or disfigured glass.
 - .8 Remove stains, spots, marks and dirt from decorative work, electrical and mechanical fixtures, furniture fitments, walls, and floors.
 - .9 Clean lighting reflectors, lenses, and other lighting surfaces.
 - .10 HEPA vacuum clean and dust building interiors, behind grilles, louvres and screens.
 - .11 Wax, seal, shampoo or prepare floor finishes, as recommended by manufacturer.
 - .12 Inspect finishes, fitments and equipment and ensure specified workmanship and operation.
 - .13 Broom clean and wash exterior walks, steps and surfaces; rake clean other surfaces of grounds.
 - .14 Remove dirt and other disfiguration from exterior surfaces.
 - .15 Clean and sweep roofs, gutters, areaways, and sunken wells.
 - .16 Sweep and wash clean paved areas.
 - .17 Clean equipment and fixtures to a sanitary condition; clean or replace filters of mechanical equipment.
 - .18 Clean roofs, downspouts, and drainage systems.
 - .19 Remove debris and surplus materials from crawl areas and other accessible concealed spaces.

.20 Remove snow and ice from access to building.

PART 2 - PRODUCTS

2.1 NOT USED

.1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

.1 Not Used.

PART 1 - GENERAL

1.1 CONSTRUCTION & DEMOLITION WASTE

- .1 Carefully deconstruct and source separate materials/equipment and divert, from D&C waste destined for landfill to maximum extent possible. Target for this project is [95% diversion from landfill. Reuse, recycle, compost, anaerobic digest or sell material for reuse except where indicated otherwise. On site sales are not permitted.
- .2 Source separate waste and maintain waste audits in accordance with the Environmental Protection Act, Ontario Regulation 102/94 and Ontario Regulation 103/94.
 - .1 Provide facilities for collection, handling and storage of source separated wastes.
 - .2 Source separate the following waste:
 - .1 Brick and portland cement concrete.
 - .2 Corrugated cardboard.
 - .3 Wood, not including painted or treated wood or laminated wood.
 - .4 Gypsum board, unpainted.
 - .5 Steel.
 - .6 Items indicated in Section 02 42 93, Deconstruction and Waste Products Workplan Summary.
- .3 Submit a waste reduction workplan indicating the materials and quantities of material that will be recycled and diverted from landfill.
 - .1 Indicate how material being removed from the site will be reused, recycled, composted or anaerobically digested using Section 02 42 93, Deconstruction and Waste Products Workplan Summary.
- .4 Submit proof that all waste is being disposed of at a licensed land fill site or waste transfer site. A copy of the disposal/waste transfer site's license and a letter verifying that said landfill site will accept the waste must be supplied to Departmental Representative prior to removal of waste from the demolition site.

1.2 WASTE PROCESSING SITES

- .1 Province of: Ontario.
 - .1 Ministry of Environment and Energy, 135 St. Clair Avenue West, Toronto, ON, M4V 1P5.
 - .2 Telephone: 800-565-4923 or 416-323-4321.
 - .3 Fax: 416-323-4682.
- .2 Recycling Council of Ontario: 215 Spadina Avenue, #225, Toronto, ON, M5T 2C7.
 - .1 Telephone: 416-657-2797 or 1-888-501-9637.
 - .2 Fax: 416-960-8053.
 - .3 Email: rco@rco.on.ca.
 - .4 Internet: <http://www.rco.on.ca/>.

PART 2 - PRODUCTS

2.1 NOT USED

.1 Not Used.

PART 3 - EXECUTION

3.1 CANADIAN GOVERNMENTAL DEPARTMENTS CHIEF RESPONSIBILITY FOR THE ENVIRONMENT

.1 Government Chief Responsibility for the Environment.

Province	Address	General Inquiries	Fax
Ontario	Ministry of Environment and Energy 135 St Clair Avenue West Toronto, ON M4V 1P5	(416) 323-4321 (800) 565-4923	(416) 323-4682
	Environment Canada Toronto, ON	(416) 734-4494	

PART 1 - GENERAL

1.1 INSPECTION AND DECLARATION

- .1 Contractor's Inspection: Contractor and all Subcontractors shall conduct an inspection of Work, identify deficiencies and defects, and repair as required to conform to Contract Documents.
 - .1 Notify Departmental Representative in writing of satisfactory completion of Contractor's Inspection and that corrections have been made.
 - .2 Request Departmental Representative's Inspection.
- .2 Departmental Representative's Inspection: Departmental Representative and Contractor will perform inspection of Work to identify obvious defects or deficiencies. Contractor to correct Work accordingly.
- .3 Completion: submit written certificate that following have been performed:
 - .1 Work has been completed and inspected for compliance with Contract Documents.
 - .2 Defects have been corrected and deficiencies have been completed.
 - .3 Equipment and systems have been tested, adjusted and balanced and are fully operational.
 - .4 Certificates required by PWGSC Fire Protection Engineer and Utility companies have been submitted.
 - .5 Operation of systems have been demonstrated to Owner's personnel.
 - .6 Work is complete and ready for final inspection.
- .4 Final Inspection: when items noted above are completed, request final inspection of Work by Departmental Representative and Contractor. If Work is deemed incomplete by Departmental Representative, complete outstanding items and request reinspection.

1.2 CLEANING

- .1 In accordance with Section 01 74 11.
- .2 Remove waste and surplus materials, rubbish and construction facilities from the site in accordance with Section 01 74 20.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 SECTION INCLUDES

- .1 As-built, samples, and specifications.
- .2 Equipment and systems.
- .3 Product data, materials and finishes, and related information.
- .4 Operation and maintenance data.
- .5 Spare parts, special tools and maintenance materials.
- .6 Warranties and bonds.
- .7 Final site survey.

1.2 RELATED SECTIONS

- .1 Section 01 91 00 - Commissioning - General Requirements.
- .2 Section 01 91 20 - Project Commissioning.
- .3 Section 01 79 00 - Demonstration and Training.
- .4 Section 01 91 13 - General Commissioning Requirements

1.3 SUBMISSION

- .1 Prepare instructions and data using personnel experienced in maintenance and operation of described products.
- .2 Copy will be returned after final inspection, with Departmental Representative's comments.
- .3 Revise content of documents as required prior to final submittal.
- .4 Two weeks prior to Substantial Performance of the Work, submit to the Departmental Representative, four final copies of maintenance manuals and commissioning documentation in English.
- .5 Ensure spare parts, maintenance materials and special tools provided are new, undamaged or defective, and of same quality and manufacture as products provided in Work.
- .6 If requested, furnish evidence as to type, source and quality of products provided.
- .7 Defective products will be rejected, regardless of previous inspections. Replace products at own expense.

- .8 Pay costs of transportation.

1.4 FORMAT

- .1 Organize data in the form of an instructional manual.
- .2 Binders: vinyl, hard covered, 3 'D' ring, loose leaf 219 x 279 mm with spine and face pockets.
- .3 When multiple binders are used, correlate data into related consistent groupings. Identify contents of each binder on spine.
- .4 Cover: Identify each binder with type or printed title 'Project Record Documents'; list title of project and identify subject matter of contents.
- .5 Arrange content by systems, under Section numbers and sequence of Table of Contents.
- .6 Provide tabbed fly leaf for each separate product and system, with typed description of product and major component parts of equipment.
- .7 Text: Manufacturer's printed data, or typewritten data.
- .8 Drawings: provide with reinforced punched binder tab. Bind in with text; fold larger drawings to size of text pages.
- .9 Provide 1:1 scaled CAD files in dwg format. Forward pdf, NMSEdit Professional spp, MS Word, MS Excel, MS Project and Autocad dwg files on USB compatible with PWGSC encryption requirements or through email or alternate electronic file sharing service such as ftp, as directed by Departmental Representative.

1.5 CONTENTS - EACH VOLUME

- .1 Table of Contents: provide title of project;
 - .1 Date of submission; names,
 - .2 Addresses, and telephone numbers of Contractor with name of responsible parties;
 - .3 Schedule of products and systems, indexed to content of volume.
- .2 For each product or system:
 - .1 List names, addresses and telephone numbers of subcontractors and suppliers, including local source of supplies and replacement parts.
- .3 Product Data: mark each sheet to clearly identify specific products and component parts, and data applicable to installation; delete inapplicable information.
- .4 Drawings: supplement product data to illustrate relations of component parts of equipment and systems, to show control and flow diagrams.
- .5 Typewritten Text: as required to supplement product data. Provide logical sequence of instructions for each procedure, incorporating manufacturer's

instructions specified in Section 01 45 00.

- .6 Training: Refer to Section 01 79 00 and 01 91 00.

1.6 AS-BUILTS AND SAMPLES

- .1 In addition to requirements in General Conditions, maintain at the site for Departmental Representative one record copy of:
- .1 Contract Drawings.
 - .2 Specifications.
 - .3 Amendments and addenda.
 - .4 Change Orders and other modifications to the Contract.
 - .5 Reviewed shop drawings, product data, and samples.
 - .6 Field test records.
 - .7 Inspection certificates.
 - .8 Manufacturer's certificates.
- .2 Store record documents and samples in field office apart from documents used for construction. Provide files, racks, and secure storage.
- .3 Label record documents and file in accordance with Section number listings in List of Contents of this Project Manual. Label each document "PROJECT RECORD" in neat, large, printed letters.
- .4 Maintain record documents in clean, dry and legible condition. Do not use record documents for construction purposes.
- .5 Keep record documents and samples available for inspection by Departmental Representative.
- .6 Turn one set, paper copy and electronic copy, of AS-BUILT drawings and specifications over to Departmental Representative on completion of work. Submit files on USB compatible with PWGSC encryption requirements or through email or alternate electronic file sharing service such as ftp, as directed by Departmental Representative.
- .7 If project is completed without significant deviations from Contract drawings and specifications submit to Departmental Representative one set of drawings and specifications marked "AS-BUILT".

1.7 RECORDING ACTUAL SITE CONDITIONS

- .1 Record information on set of black line opaque drawings, and in copy of Project Manual, provided by Departmental Representative.
- .2 Provide felt tip marking pens, maintaining separate colours for each major system, for recording information.
- .3 Record information concurrently with construction progress. Do not conceal Work until required information is recorded.

- .4 Contract Drawings and shop drawings: legibly mark each item to record actual construction, including:
 - .1 Measured depths of elements of foundation in relation to finish first floor datum.
 - .2 Measured horizontal and vertical locations of underground utilities and appurtenances, referenced to permanent surface improvements.
 - .3 Measured locations of internal utilities and appurtenances, referenced to visible and accessible features of construction.
 - .4 Field changes of dimension and detail.
 - .5 Changes made by change orders.
 - .6 Details not on original Contract Drawings.
 - .7 References to related shop drawings and modifications.
- .5 Specifications: legibly mark each item to record actual construction, including:
 - .1 Manufacturer, trade name, and catalogue number of each product actually installed, particularly optional items and substitute items.
 - .2 Changes made by Amendments and change orders.
- .6 Other Documents: maintain manufacturer's certifications, inspection certifications, field test records, required by individual specifications sections.

1.8 FINAL SURVEY

- .1 Submit final site survey certificate in accordance with Section 01 71 00, certifying that elevations and locations of completed Work are in conformance, or non-conformance with Contract Documents.

1.9 EQUIPMENT AND SYSTEMS

- .1 Each Item of Equipment and Each System: include description of unit or system, and component parts. Give function, normal operation characteristics, and limiting conditions. Include performance curves, with engineering data and tests, and complete nomenclature and commercial number of replaceable parts.
- .2 Panel board circuit directories: provide electrical service characteristics, controls, and communications.
- .3 Include installed colour coded wiring diagrams.
- .4 Operating Procedures: include start-up, break-in, and routine normal operating instructions and sequences. Include regulation, control, stopping, shut-down, and emergency instructions. Include summer, winter, and any special operating instructions.
- .5 Maintenance Requirements: include routine procedures and guide for trouble-shooting; disassembly, repair, and reassembly instructions; and alignment, adjusting, balancing, and checking instructions.
- .6 Provide servicing and lubrication schedule, and list of lubricants required.

- .7 Include manufacturer's printed operation and maintenance instructions.
- .8 Include sequence of operation by controls manufacturer.
- .9 Provide original manufacturer's parts list, illustrations, assembly drawings, and diagrams required for maintenance.
- .10 Provide installed control diagrams by controls manufacturer.
- .11 Provide Contractor's coordination drawings, with installed colour coded piping diagrams.
- .12 Provide charts of valve tag numbers, with location and function of each valve, keyed to flow and control diagrams.
- .13 Provide list of original manufacturer's spare parts, current prices, and recommended quantities to be maintained in storage.
- .14 Include test and balancing reports as specified in Section 01 45 00 and 01 91 00.
- .15 Additional requirements: As specified in individual specification sections.

1.10 MATERIALS AND FINISHES

- .1 Building Products, Applied Materials, and Finishes: include product data, with catalogue number, size, composition, and colour and texture designations. Provide information for re-ordering custom manufactured products.
- .2 Instructions for cleaning agents and methods, precautions against detrimental agents and methods, and recommended schedule for cleaning and maintenance.
- .3 Moisture-protection and Weather-exposed Products: include manufacturer's recommendations for cleaning agents and methods, precautions against detrimental agents and methods, and recommended schedule for cleaning and maintenance.
- .4 Additional Requirements: as specified in individual specifications sections.

1.11 SPARE PARTS

- .1 Provide spare parts, in quantities specified in individual specification sections.
- .2 Provide items of same manufacture and quality as items in Work.
- .3 Deliver to location as directed by Departmental Representative; place and store.
- .4 Receive and catalogue all items. Submit inventory listing to Departmental

Representative. Include approved listings in Maintenance Manual.

- .5 Obtain receipt for delivered products and submit prior to final payment.

1.12 MAINTENANCE MATERIALS

- .1 Provide maintenance and extra materials, in quantities specified in individual specification sections.
- .2 Provide items of same manufacture and quality as items in Work.
- .3 Deliver to location as directed by Departmental Representative; place and store.
- .4 Receive and catalogue all items. Submit inventory listing to Departmental Representative. Include approved listings in Maintenance Manual.
- .5 Obtain receipt for delivered products and submit prior to final payment.

1.13 SPECIAL TOOLS

- .1 Provide special tools, in quantities specified in individual specification section.
- .2 Provide items with tags identifying their associated function and equipment.
- .3 Deliver to location as directed by Departmental Representative; place and store.
- .4 Receive and catalogue all items. Submit inventory listing to Departmental Representative. Include approved listings in Maintenance Manual.

1.14 STORAGE, HANDLING AND PROTECTION

- .1 Store spare parts, maintenance materials, and special tools in manner to prevent damage or deterioration.
- .2 Store in original and undamaged condition with manufacturer's seal and labels intact.
- .3 Store components subject to damage from weather in weatherproof enclosures.
- .4 Store paints and freezable materials in a heated and ventilated room.
- .5 Remove and replace damaged products at own expense and to satisfaction of Departmental Representative.

1.15 WARRANTIES AND BONDS

- .1 Separate each warranty or bond with index tab sheets keyed to Table of Contents listing.
- .2 List subcontractor, supplier, and manufacturer, with name, address, and

telephone number of responsible principal.

- .3 Obtain warranties and bonds, executed in duplicate by subcontractors, suppliers, and manufacturers, within ten days after completion of the applicable item of work.
- .4 Except for items put into use with Owner's permission, leave date of beginning of time of warranty until the Date of Certificate of Substantial Performance is determined.
- .5 Verify that documents are in proper form, contain full information, and are notarized.
- .6 Co-execute submittals when required.
- .7 Retain warranties and bonds until time specified for submittal.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 SECTION INCLUDES

- .1 Procedures for demonstration and instruction of equipment and systems to Owner's O&M personnel.
- .2 O&M personnel includes property facility manager, building operators, maintenance staff, security staff and technical specialists, as applicable.

1.2 DESCRIPTION

- .1 Demonstrate scheduled operation and maintenance of equipment and systems to Departmental Representative's personnel two weeks prior to date of final inspection and substantial performance.
- .2 Departmental Representative will provide list of personnel to receive instructions, and will coordinate their attendance at agreed-upon times.

1.3 QUALITY CONTROL

- .1 When specified in individual Sections, require manufacturer to provide authorized representative to demonstrate operation of equipment and systems, instruct Owner's personnel, and provide written report that demonstration and instructions have been completed.
- .2 Submit training schedule of time and date for demonstration and training of each item of equipment and each system in accordance with the training plan four weeks prior to designated dates, for Departmental Representative's approval.
- .3 Submit reports within one week after completion of demonstration, that demonstration and instructions have been satisfactorily completed.
- .4 Report shall give time and date of each demonstration and training, with list of persons present.

1.4 CONDITIONS FOR DEMONSTRATIONS

- .1 Equipment has been inspected and put into operation in accordance with Section 01 91 00.
- .2 Testing, adjusting, and balancing has been performed in accordance with Section 01 91 00 and equipment and systems are fully operational.
- .3 Provide copies of completed operation and maintenance manuals for use in demonstrations and instructions.

1.5 PREPARATION

- .1 Verify that conditions for demonstration and instructions comply with requirements.

- .2 Verify that designated O&M personnel are present.

1.6 DEMONSTRATION AND INSTRUCTIONS

- .1 Demonstrate start-up, operation, control, adjustment, trouble-shooting, servicing, and maintenance of each item of equipment at scheduled times, at the designated location.
- .2 Instruct personnel in all phases of operation and maintenance using operation and maintenance manuals as the basis of instruction.
- .3 Review contents of manual in detail to explain all aspects of operation and maintenance.
- .4 Prepare and insert additional data in operations and maintenance manuals when the need for additional data becomes apparent during instructions.

1.7 TIME ALLOCATED FOR INSTRUCTIONS

- .1 Ensure amount of time required for instruction of each item of equipment or system as follows:
 - .1 Transformers.
 - .2 Neutral Grounding Resistors.
 - .3 Building Automation System (BAS).
 - .4 High Voltage connections.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 SECTION INCLUDES

- .1 Includes general requirements for commissioning facilities and facility systems.
- .2 Testing and Commissioning to be carried out by third party Testing Organization employed by the Contractor.

1.2 RELATED SECTIONS

- .1 Section 01 91 13 - General Commissioning Requirements.
Section 01 91 20 - Project Commissioning
Section 01 91 31 - Commissioning Plan
Section 01 91 33 - Commissioning Forms
Section 01 91 41 - Training

1.3 QUALITY ASSURANCE

- .1 Provide testing & commissioning organization services under provisions specified in Section

1.4 REFERENCES

- .1 ASHRAE Guideline 202P Commissioning Process for Buildings and Systems.
- .2 ASHRAE Guideline 4-2008(RA 2013), Preparation of Operating and Maintenance Documentation for Building System.
- .3 NETA Standard for Acceptance Testing Specifications for Electrical Power Distribution Equipment and Systems 2009.

1.5 SUBMITTALS

- .1 Within 15 working days of Award of Contract, submit name of Commissioning Administrator who has managerial responsibilities for coordination of all commissioning activities by the Testing Organization.
- .2 Submit documentation to confirm commissioning personnel in compliance with quality assurance provision.
- .3 Submit preliminary specimen copies of each type of startup checklist, product information and performance verification report forms proposed for use.
- .4 Submit completed report forms within 3 days after completion of each testing to Consultant for review and verification.
- .5 Fifteen days prior to Substantial Performance, submit final reports on

applicable forms for functional performance verification.

- .6 Submit post-commissioning reports of testing, adjusting, and balancing postponed due to seasonal, climatic, occupancy, or other reasons beyond Contractor's control, promptly after execution of those services.
- .7 Submit all other commissioning documentation in accordance with Section 01 91 20, 01 91 31 and 01 91 33

1.6 REPORT FORMS

- .1 Testing organization shall make reports.
- .2 Report forms shall include:
 - .1 Startup Checklists.
 - .2 Product Information (PI) Report forms.
 - .3 Performance Verification (PV) Report forms.
- .3 Ensure each form bears signature of recorder, and that of supervisor of reporting organization.
- .4 Submit signed form to Departmental Representative for review and approval. After approval, immediately submit form bearing Commissioning Administrator's signature to Departmental Representative.
- .5 Identify each instrument used for testing, adjusting and balancing and its latest date of calibration.

1.7 CONTRACTOR'S RESPONSIBILITIES

- .1 Prepare each system for testing and balancing.
- .2 Cooperate with testing organization and provide access to equipment and systems.
- .3 Provide personnel and operate systems at designated times, and under conditions required for proper testing and adjusting.
- .4 Notify testing organization and Departmental Representative 7 days prior to time project will be ready for testing, adjusting, and balancing.
- .5 Accurately record data for each step.
- .6 Report to Departmental Representative any deficiencies or defects noted during performance of services.
- .7 Correct deficiencies identified in accordance with Departmental Representative's written instructions.

1.8 PREPARATION

- .1 Provide instruments required for testing and adjusting.

- .2 Make instruments available to Departmental Representative to facilitate spot checks during testing and functional performance verification.
- .3 Retain possession of instruments and remove at completion of services.
- .4 Verify systems installation is complete and in continuous operation.

1.9 EXECUTION

- .1 Test equipment and adjust devices for Electrical systems (Transformers and associated HV/ LV switch gear).

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 SUMMARY

- .1 Section Includes:
 - .1 General requirements relating to commissioning of project's components and systems, specifying general requirements to PV of components, equipment, sub-systems, systems, and integrated systems.
- .2 Related Sections:
 - .1 Refer to 01 91 00 for list of related sections.
- .3 Acronyms:
 - .1 AFD - Alternate Forms of Delivery, service provider.
 - .2 BMM - Building Management Manual.
 - .3 Cx - Commissioning.
 - .4 EMCS - Energy Monitoring and Control Systems.
 - .5 O&M - Operation and Maintenance.
 - .6 PI - Product Information.
 - .7 PV - Performance Verification.
 - .8 TAB - Testing, Adjusting and Balancing.

1.2 GENERAL

- .1 Cx is a planned program of tests, procedures and checks carried out systematically on systems and integrated systems of the finished Project. Cx is performed after systems and integrated systems are completely installed, functional and Contractor's Performance Verification responsibilities have been completed and approved. Objectives:
 - .1 Verify installed equipment, systems and integrated systems operate in accordance with contract documents and design criteria and intent.
 - .2 Ensure appropriate documentation is compiled into the BMM.
 - .3 Effectively train O&M staff.
- .2 Contractor assists in Cx process, operating equipment and systems, troubleshooting and making adjustments as required.
 - .1 Systems to be operated at full capacity under various modes to determine if they function correctly and consistently at peak efficiency. Systems to be interactively with each other as intended in accordance with Contract Documents and design criteria.
 - .2 During these checks, adjustments to be made to enhance performance to meet environmental or user requirements.
- .3 Design Criteria: as per client's requirements or determined by designer. To meet Project functional and operational requirements.

1.3 COMMISSIONING OVERVIEW

- .1 For Cx responsibilities refer to Section 01 91 20.
- .2 Cx to be a line item of Contractor's cost breakdown.

- .3 Cx activities supplement field quality and testing procedures described in relevant technical sections.
- .4 Cx is conducted in concert with activities performed during stage of project delivery. Cx ensures the completed systems are constructed and proven to operate satisfactorily under weather, environmental and occupancy conditions to meet functional and operational requirements. Cx activities includes transfer of critical knowledge to facility operational personnel.
- .5 Departmental Representative will issue Certificate of Substantial Performance when:
 - .1 Completed Cx documentation has been received, reviewed for suitability and approved by Departmental Representative.
 - .2 Equipment, components and systems have been commissioned.
 - .3 O&M training has been completed.

1.4 NON-CONFORMANCE TO PERFORMANCE VERIFICATION REQUIREMENTS

- .1 Should equipment, system components, and associated controls be incorrectly installed or malfunction during Cx, correct deficiencies, re-verify equipment and components within the unfunctional system, including related systems as deemed required by Departmental Representative, to ensure effective performance.
- .2 Costs for corrective work, additional tests, inspections, to determine acceptability and proper performance of such items to be borne by Contractor. Above costs to be in form of progress payment reductions or hold-back assessments.

1.5 PRE-CX REVIEW

- .1 Before Construction:
 - .1 Review contract documents, confirm by writing to Departmental Representative.
 - .1 Adequacy of provisions for Cx.
 - .2 Aspects of design and installation pertinent to success of Cx.
- .2 During Construction:
 - .1 Co-ordinate provision, location and installation of provisions for Cx.
- .3 Before start of Cx:
 - .1 Have completed Cx Plan up-to-date.
 - .2 Ensure installation of related components, equipment, sub-systems, systems is complete.
 - .3 Fully understand Cx requirements and procedures.
 - .4 Have Cx documentation shelf-ready.
 - .5 Understand completely design criteria and intent and special features.
 - .6 Submit complete start-up documentation to Departmental Representative.
 - .7 Have Cx schedules up-to-date.

- .8 Ensure systems have been cleaned thoroughly.
- .9 Ensure "As-Built" system schematics are available.

- .4 Inform Departmental Representative in writing of discrepancies and deficiencies on finished works.

1.6 CONFLICTS

- .1 Report conflicts between requirements of this section and other sections to Departmental Representative before start-up and obtain clarification.
- .2 Failure to report conflict and obtain clarification will result in application of most stringent requirement.

1.7 SUBMITTALS

- .1 Submittals: in accordance with Section 01 33 00.
 - .1 Submit no later than 4 weeks prior to commencement of commissioning
 - .1 Name of Contractor's Cx agent (company) and Commissioning Administrator representing that company.
 - .2 Draft Cx documentation.
 - .3 Preliminary Cx schedule.
 - .2 Submit proposed Cx procedures to Departmental Representative where not specified and obtain written approval at least 8 weeks prior to start of Cx.
 - .3 Provide additional documentation relating to Cx process required by Departmental Representative.

1.8 COMMISSIONING DOCUMENTATION

- .1 Refer to Section 01 91 20.
- .2 Departmental Representative to review and approve Cx documentation.
- .3 Provide completed and approved Cx documentation to Departmental Representative.

1.9 COMMISSIONING SCHEDULE

- .1 Provide detailed Cx schedule as part of construction schedule in accordance with Section 01 32 16.
- .2 Provide adequate time for Cx activities prescribed in technical sections and commissioning sections including:
 - .1 Approval of Cx reports.
 - .2 Verification of reported results.
 - .3 Repairs, retesting, re-commissioning, re-verification.
 - .4 Training.

1.10 COMMISSIONING MEETINGS

- .1 Convene regular Cx meetings following project meetings as required below.

- .2 Purpose: to resolve issues, monitor progress, identify deficiencies, relating to Cx.
- .3 Continue Cx meetings on regular basis until commissioning deliverables have been addressed.
- .4 Initial Cx meeting (Cx Kick-Off) to be called by Departmental Representative to review progress, discuss schedule of equipment start-up activities and prepare for Cx. Issues at meeting to include:
 - .1 Review duties and responsibilities of Contractor and subcontractors, addressing delays and potential problems.
 - .2 Determine the degree of involvement of trades and manufacturer's representatives in the commissioning process.
- .5 Thereafter Cx meetings to be held biweekly until project completion and as required during equipment start-up and functional testing period.
- .6 Meeting will be chaired by Testing Organisation who will record and distribute minutes.
- .7 Ensure subcontractors and relevant manufacturer representatives are present at all Cx meetings as required.

1.11 STARTING AND TESTING

- .1 Contractor assumes liabilities and costs for inspections. Including disassembly and re-assembly after approval, starting, testing and adjusting, including supply of testing equipment.

1.12 WITNESSING OF STARTING AND TESTING

- .1 Provide 7 days notice prior to commencement.
- .2 Departmental Representative to witness of start-up and testing.
- .3 Contractor's Cx Agent to be present at tests performed and documented by sub-trades, suppliers and equipment manufacturers.

1.13 MANUFACTURER'S INVOLVEMENT

- .1 Factory testing: manufacturer to:
 - .1 Coordinate time and location of testing.
 - .2 Provide testing documentation for approval by Departmental Representative.
 - .3 Arrange for Departmental Representative to witness tests.
 - .4 Obtain written approval of test results and documentation from Departmental Representative before delivery to site.
- .2 Obtain manufacturers installation, start-up and operations instructions prior to start-up of components, equipment and systems and review with Departmental Representative.
 - .1 Compare completed installation with manufacturer's published data, record discrepancies, and review with manufacturer.

- .2 Modify procedures detrimental to equipment performance and review same with manufacturer before start-up.
- .3 Integrity of warranties:
 - .1 Use manufacturer's trained start-up personnel where specified elsewhere in other divisions or required to maintain integrity of warranty.
 - .2 Verify with manufacturer that testing as specified will not void warranties.
- .4 Qualifications of manufacturer's personnel:
 - .1 Experienced in design, installation and operation of equipment and systems.
 - .2 Ability to interpret test results accurately.
 - .3 To report results in clear, concise, logical manner.

1.14 PROCEDURES

- .1 Verify that equipment and systems are complete, clean, and operating in normal and safe manner prior to conducting start-up, testing and Cx.
- .2 Conduct start-up and testing in following distinct phases:
 - .1 Included in delivery and installation:
 - .1 Verification of conformity to specification, approved shop drawings and completion of PI report forms.
 - .2 Visual inspection of quality of installation.
 - .2 Start-up: follow accepted start-up procedures.
 - .3 Operational testing: document equipment performance.
 - .4 System PV: include repetition of tests after correcting deficiencies.
 - .5 Post-substantial performance verification: to include fine-tuning.
- .3 Correct deficiencies and obtain approval from Departmental Representative after distinct phases have been completed and before commencing next phase.
- .4 Document require tests on approved PV forms.
- .5 Failure to follow accepted start-up procedures will result in re-evaluation of equipment by an independent testing agency selected by Departmental Representative. If results reveal that equipment start-up was not in accordance with requirements, and resulted in damage to equipment, implement following:
 - .1 Minor equipment/systems: implement corrective measures approved by Departmental Representative.
 - .2 Major equipment/systems: if evaluation report concludes that damage is minor, implement corrective measures approved by Departmental Representative.
 - .3 If evaluation report concludes that major damage has occurred, Departmental Representative shall reject equipment.
 - .1 Rejected equipment to be remove from site and replace with new.
 - .2 Subject new equipment/systems to specified start-up procedures.

1.15 START-UP DOCUMENTATION

- .1 Assemble start-up documentation and submit to Departmental Representative for approval before commencement of commissioning.
- .2 Start-up documentation to include:
 - .1 Factory and on-site test certificates for specified equipment.
 - .2 Pre-start-up inspection reports.
 - .3 Signed installation/start-up check lists.
 - .4 Start-up reports,
 - .5 Step-by-step description of complete start-up procedures, to permit Departmental Representative to repeat start-up at any time.

1.16 OPERATION AND MAINTENANCE OF EQUIPMENT AND SYSTEMS

- .1 After start-up, operate and maintain equipment and systems as directed by equipment/system manufacturer.
- .2 With assistance of manufacturer develop written maintenance program and submit Departmental Representative for approval before implementation.
- .3 Operate and maintain systems for length of time required for commissioning to be completed.
- .4 After completion of commissioning, operate and maintain systems until issuance of certificate of substantial completion.

1.17 TEST RESULTS

- .1 If start-up, testing and/or PV produce unacceptable results, repair, replace or repeat specified starting and/or PV procedures until acceptable results are achieved.
- .2 Provide manpower and materials, assume costs for re-commissioning.

1.18 START OF COMMISSIONING

- .1 Notify Departmental Representative at least 4 weeks prior to start of Cx.
- .2 Start Cx after elements of building affecting start-up and performance verification of systems have been completed.

1.19 INSTRUMENTS/EQUIPMENT

- .1 Submit to Departmental Representative for review and approval:
 - .1 Complete list of instruments proposed to be used.
 - .2 Listed data including, serial number, current calibration certificate, calibration date, calibration expiry date and calibration accuracy.
- .2 Provide the following equipment as required:
 - .1 2-way radios.
 - .2 Ladders.
 - .3 Equipment as required to complete work.

1.20 COMMISSIONING PERFORMANCE VERIFICATION

- .1 Carry out Cx:
 - .1 Under actual operating conditions, over entire operating range, in all modes.
 - .2 On independent systems and interacting systems.
- .2 Cx procedures to be repeatable and reported results are to be verifiable.
- .3 Follow equipment manufacturer's operating instructions.
- .4 EMCS trending to be available as supporting documentation for performance verification.

1.21 WITNESSING COMMISSIONING

- .1 Departmental Representative to witness activities and verify results.

1.22 AUTHORITIES HAVING JURISDICTION

- .1 Where specified start-up, testing or commissioning procedures duplicate verification requirements of authority having jurisdiction, arrange for authority to witness procedures so as to avoid duplication of tests and to facilitate expedient acceptance of facility.
- .2 Obtain certificates of approval, acceptance and compliance with rules and regulation of authority having jurisdiction.
- .3 Provide copies to Departmental Representative within 5 days of test and with Cx report.

1.23 REPEAT VERIFICATIONS

- .1 Assume costs incurred by Departmental Representative for third and subsequent verifications where:
 - .1 Verification of reported results fail to receive Departmental Representative's approval.
 - .2 Repetition of second verification again fails to receive approval.
 - .3 Departmental Representative deems Contractor's request for second verification was premature.

1.24 SUNDRY CHECKS AND ADJUSTMENTS

- .1 Make adjustments and changes which become apparent as Cx proceeds.
- .2 Perform static and operational checks as applicable and as required.

1.25 DEFICIENCIES, FAULTS, DEFECTS

- .1 Correct deficiencies found during start-up and Cx to satisfaction of Departmental Representative.

- .2 Report problems, faults or defects affecting Cx to Departmental Representative in writing. Stop Cx until problems are rectified. Proceed with written approval from Departmental Representative.

1.26 COMPLETION OF COMMISSIONING

- .1 Upon completion of Cx leave systems in normal operating mode.
- .2 Except for warranty and seasonal verification activities specified in Cx specifications, complete Cx prior to issuance of certificate of substantial completion.
- .3 Cx to be considered complete when contract Cx deliverables have been submitted and accepted by Departmental Representative.

1.27 ACTIVITIES UPON COMPLETION OF COMMISSIONING

- .1 When changes are made to baseline components or system settings established during Cx process, provide updated Cx form for affected item.

1.28 TRAINING

- .1 In accordance with Section 01 91 41.

1.29 MAINTENANCE MATERIALS, SPARE PARTS, SPECIAL TOOLS

- .1 Supply, deliver, and document maintenance materials, spare parts, and special tools as specified in contract.

1.30 OCCUPANCY

- .1 Cooperate fully with Departmental Representative during stages of acceptance and occupancy of facility.

1.31 INSTALLED INSTRUMENTATION

- .1 Use instruments installed under Contract for TAB and PV if:
 - .1 Accuracy complies with these specifications.
 - .2 Calibration certificates have been deposited with Departmental Representative.
- .2 Calibrated EMCS sensors may be used to obtain performance data provided that sensor calibration has been completed and accepted.

1.32 PERFORMANCE VERIFICATION TOLERANCES

- .1 Application tolerances:
 - .1 Specified range of acceptable deviations of measured values from specified values or specified design criteria.
- .2 Instrument accuracy tolerances:
 - .1 To be of higher order of magnitude than equipment or system being tested.

- .3 Measurement tolerances during verification:
 - .1 Unless otherwise specified actual values to be within +/-2% of recorded values.

1.33 OWNER'S PERFORMANCE TESTING

- .1 Performance testing of equipment or system by Departmental Representative will not relieve Contractor from compliance with specified start-up and testing procedures.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 RELATED SECTIONS

- .1 Refer to 01 91 00 for list of related commissioning sections.

1.2 GENERAL

- .1 The "Commissioning" for this project is defined as a planned program of activities which enhance quality management and information transfer that extends throughout all stages of project delivery.
- .2 The commissioning activities shall include the standard activities and the enhanced activities which are traditionally not provided by the design and construction industry and which are defined in this document.

1.3 REFERENCE STANDARDS

- .1 The most stringent requirements of the following commissioning standards and guidelines shall apply:
 - .1 ASHRAE Guideline 4-2008(RA 2013), Preparation of Operating and Maintenance Documentation for Building System.
 - .2 NETA Standard for Acceptance Testing Specifications for Electrical Power Distribution Equipment and Systems 2009.

1.4 ROLES AND RESPONSIBILITIES

- .1 The key members of the commissioning team include the Contractor, the Departmental Representative, and the PWGSC Commissioning Manager (or its representative).
 - .1 It is the Contractor's responsibility to engage a qualified independent System Commissioning Administrator (SCA) to represent the Contractor including the Sub-Contractors. The SCA as represented by the Cx Administrator shall be responsible for carrying out the Contractor's commissioning activities.
 - .2 The PWGSC Commissioning Manager (or its representative) will be assisted by the Consultant and other project team members for overview of the commissioning activities on behalf of the PWGSC Project Manager.
- .2 The Contractor is responsible for the following standard commissioning activities and enhanced commissioning activities during project construction, commissioning and operation phases.
 - .1 Construction Phase:
 - .1 Designate an experienced personnel on commissioning as single point of contact for all matters relating to commissioning.
 - .2 Conduct separate commissioning meetings and prepare minutes of meeting in preparation for the main commissioning process.
 - .3 Submit shop drawings (standard activity).
 - .4 Conduct equipment installation and startup tests, and submit test reports (standard activity).
 - .5 Conduct testing for insulation resistance, turns ratio, winding

- resistance, capacitance and/or Doble tests prior to unloading the transformers at site. Conduct these tests once again prior to energization of the transformers.
- .6 Conduct System Startup Verification Testing and complete Startup Checklists and PI Report forms (enhanced activity).
- .2 Commissioning Phase:
 - .1 Conduct commissioning meetings and prepare minutes of meeting.
 - .2 Conduct Functional Performance Testing and complete PV Report forms (enhanced activity).
 - .3 Demonstrate system operation (standard activity).
 - .4 Submit Maintenance Manuals (formerly called O&M Manuals) (standard activity).
 - .5 Submit "As-Built" drawings and specifications (standard activity).
 - .6 Conduct O&M training (standard activity).
 - .3 Operation Phase:
 - .1 Conduct [separate] commissioning meetings and prepare minutes of meeting.
 - .2 Conduct deferred Functional Performance Testing and complete PV Report forms (enhanced activity).
 - .3 Provide fine-tuning (standard activity).
 - .4 Provide specified inspection and maintenance services during warranty period (standard activity).
- .3 The Testing Organization will carry out the following commissioning activities related to the Contractor:
 - .1 Prepare Startup Checklists, PI and PV Report Forms and Functional Performance Test Forms (enhanced activity).
 - .2 Prepare Standard Operation Procedures (SOP) Manual (formerly called Systems Manual) (enhanced activity).
 - .3 Review and approve shop drawings (standard activity).
 - .4 Review and inspect installation, and prepare construction deficiencies report (standard activity).
 - .5 Direct and approve System Startup Verification Testing (enhanced activity).
 - .6 Direct and approve Functional Performance Testing (enhanced activity).
 - .7 Review and approve Maintenance Manuals (standard activity).
 - .8 Review and approve "As-Built" drawings and specifications (standard activity).
 - .9 [Update Standard Operating Procedures (SOP) Manual] (enhanced activity).
 - .10 Review O&M training (standard activity).
 - .11 Prepare commissioning report (enhanced activity).
 - .12 Witness post-acceptance commissioning testing (enhanced activity).
 - .13 Direct and approve post-acceptance fine-tuning and review warranty services (standard activity).
 - .14 Update commissioning report (enhanced activity).
 - .4 The Departmental Representative will carry out the following commissioning activities related to the Contractor and the Consultant:
 - .1 Review and approve Startup Checklists, PI and PV Report Forms prepared by the Consultant.

- .2 Witness System Startup Verification Testing conducted by the Contractor and review test reports.
- .3 Witness Functional Performance Testing conducted by the Contractor and review test reports.
- .4 Review and approve O&M training conducted by the Contractor.
- .5 Review commissioning documentation submitted by the Contractor and Consultant.
- .6 Review and approved commissioning report prepared by the Consultant.
- .7 Witness the post-acceptance commissioning testing conducted by the Contractor and review test reports.
- .8 Review and approve updated commissioning report prepared by the Consultant.

1.5 SCHEDULING

- .1 No later than 4 weeks prior to commencement of commissioning activities, and two weeks before the commissioning kickoff meeting, the Contractor shall submit bar chart commissioning schedules indicating anticipated date of start, duration, and date of completion for the following key activities:
 - .1 Commissioning meetings.
 - .2 Shop drawings.
 - .3 Pre-startup installation inspections and tests.
 - .4 System and Equipment Startup and Verification.
 - .5 TAB.
 - .6 Functional Performance Test.
 - .7 Maintenance Manuals.
 - .8 "As-Built" drawings and specifications.
 - .9 O&M Training.
 - .10 O&M Training report.
- .2 Bar chart commissioning schedule shall be prepared for each component, equipment, sub-system, system and integrated system to be commissioned as listed under paragraph 1.11.
- .3 The Commissioning shall be carried out to meet the approved project schedule.

1.6 CONTRACTOR'S COMMISSIONING DOCUMENTATION

- .1 The Contractor's Commissioning Documentation shall include the following:
 - .1 Commissioning Schedule.
 - .2 Minutes of Commissioning meetings.
 - .3 Shop drawings and product data.
 - .4 Installation inspection and test reports.
 - .5 TAB reports.
 - .6 Startup Checklists.
 - .7 Product Information (PI) Report forms.
 - .8 Performance Verification (PV) Report forms.
 - .9 "As-Built" drawings and specifications.
 - .10 Maintenance Manuals.
 - .11 O&M Training Schedule
 - .12 O&M Training Report.

1.7 PRE-COMMISSIONING TESTING - STARTUPS

- .1 Requirements of Pre-commissioning Verification: a full range of checks and tests to determine that all components, equipment, systems, and interfaces between systems (eg., emergency, fire, and life safety) operate in accordance with contact documents. This includes all operating modes, interlocks, control responses, and specific responses to abnormal or emergency conditions. Verification of the proper operation of the control system also includes verifying the interface of the control system with the TAB criteria and the response of EMCS controllers and sensors. Also, the Consultant shall select, at random, 10 percent of the reported TAB and EMCS data for verification, and a failure of selected items shall result in the rejection of the final TAB report or the report of system startup and testing.
- .2 The Startup Checklists and PI Report forms shall be completed by the Contractor and verified by the Consultant.

1.8 COMMISSIONING TESTING

- .1 Commissioning Testing shall include System Operation Demonstration and Functional Performance Testing of all systems to be commissioned. Test each system independently and then in unison with integrated systems.
- .2 Requirements of Functional Performance Testing (FPT): FPT shall determine if the systems are providing the required services in accordance with the finalized design intent. If FPT cannot be completed due to seasonal reasons, lack of occupancy, deficiencies beyond the scope of the mechanical work, or any other reason, this shall be noted along with an indication of when tests will be rescheduled. If any identified performance deficiencies need to be corrected, the tests shall be repeated after corrective work is carried out, and this process shall continue until acceptable performance is achieved.
- .3 The PV Report forms shall be completed by the Contractor and verified by the Consultant.

1.9 EXTENT OF COMMISSIONING

- .1 Systems to be commissioned with the comprehensive commissioning to include:
 - .1 New Transformers including LV and HV connections and distribution

1.10 O&M TRAINING

- .1 The Contractor shall provide qualified training instructors to conduct O&M training.
- .2 Four weeks prior to commencement of O&M training, the Contractor shall submit training schedule with course outline, agenda and a copy of training manual in accordance with the training plan for review by the Consultant and the PWGSC Commissioning Manager.
- .3 Training shall include familiarization sessions, hands-on instruction, and

classroom sessions.

- .4 Classroom training shall include: review of Maintenance Manuals, [Standard Operating Procedures (SOP) Manual], System Operational Procedures for all modes of operation, acceptable tolerances for system adjustments and procedures for dealing with abnormal and emergency situations.

1.11 COMMISSIONING REPORT AND POST-ACCEPTANCE COMMISSIONING

- .1 When the acceptable Functional Performance Testing, O&M Training, and commissioning documentation have been completed, the Consultant shall prepare a commissioning report. The report will identify the completed functional performance tests, the deferred functional performance tests, construction deficiencies, design deficiencies, user's changes of requirement, and outstanding commissioning issues. The report will provide review comments on test results, O&M training and commissioning documentation, and will recommend follow-up actions to be taken during post-acceptance commissioning.
- .2 The Project Manager will not issue the certificate of substantial completion until the commissioning report with a recommendation of acceptance is submitted by the PWGSC Commissioning Manager.

1.12 ADDITIONAL COMMISSIONING REQUIREMENTS

- .1 Refer to other specifications sections for additional commissioning requirements.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not used.

PART 1 - GENERAL

1.1 SUMMARY

- .1 Section Includes:
 - .1 Description of overall structure of Cx Plan and roles and responsibilities of Cx team.
- .2 Related Sections:
 - .1 Refer to Section 01 91 00 for list of related commissioning specifications

1.2 REFERENCES

- .1 American Water Works Association (AWWA)
- .2 National Fire Protection Association (NFPA)
 - .1 NFPA 13-2016, Standard for the Installation of Sprinkler Systems.
 - .2 NFPA 14-2016, Standard for the Installation of Standpipe and Systems.
 - .3 NFPA 20-2016, Standard for the Installation of Stationary Fire Pumps for Fire Protection.
- .3 Public Works and Government Services Canada (PWGSC)
 - .1 PWGSC - Commissioning Guidelines CP.4 -3rd edition-03.
- .4 Underwriters' Laboratories of Canada (ULC)

1.3 GENERAL

- .1 Provide a fully functional system:
 - .1 Systems, equipment and components meet user's functional requirements before date of acceptance, and operate consistently at peak efficiencies and within specified energy budgets under normal loads.
 - .2 Department O&M personnel have been fully trained in aspects of installed systems.
 - .3 Optimized life cycle costs.
 - .4 Complete documentation relating to installed equipment and systems.
- .2 Term "Cx" in this section means "Commissioning".
- .3 Use this Cx Plan as master planning document for Cx:
 - .1 Outlines organization, scheduling, allocation of resources, documentation, pertaining to implementation of Cx.
 - .2 Communicates responsibilities of team members involved in Cx Scheduling, documentation requirements, and verification procedures.
 - .3 Sets out deliverables relating to O&M, process and administration of Cx.
 - .4 Describes process of verification of how built works meet department requirements.
 - .5 Produces a complete functional system prior to issuance of Certificate of Occupancy.
 - .6 Management tool that sets out scope, standards, roles and

responsibilities, expectations, deliverables, and provides:

- .1 Overview of Cx.
 - .2 General description of elements that make up Cx Plan.
 - .3 Process and methodology for successful Cx.
- .4 Acronyms:
- .1 Cx - Commissioning.
 - .2 BMM - Building Management Manual.
 - .3 EMCS - Energy Monitoring and Control Systems.
 - .4 MSDS - Material Safety Data Sheets.
 - .5 PI - Product Information.
 - .6 PV - Performance Verification.
 - .7 TAB - Testing, Adjusting and Balancing.
 - .8 WHMIS - Workplace Hazardous Materials Information System.
- .5 Commissioning terms used in this Section:
- .1 Bumping: short term start-up to prove ability to start and prove correct rotation.
 - .2 Deferred Cx - Cx activities delayed for reasons beyond Contractor's control due to lack of occupancy, weather conditions, need for heating/cooling loads.

1.4 DEVELOPMENT OF 100% CX PLAN

- .1 Cx Plan to be 100% completed within 8 weeks of award of contract to take into account:
 - .1 Approved shop drawings and product data.
 - .2 Approved changes to contract.
 - .3 Contractor's project schedule.
 - .4 Cx schedule.
 - .5 Contractor's, sub-contractor's, suppliers' requirements.
 - .6 Project construction team's and Cx team's requirements.
- .2 Submit completed Cx Plan to Departmental Representative and obtain written approval.

1.5 REFINEMENT OF CX PLAN

- .1 During construction phase, revise, refine and update Cx Plan to include:
 - .1 Changes resulting from Client program modifications.
 - .2 Approved design and construction changes.
- .2 Revise, refine and update as directed by Departmental Representative during construction phase. At each revision, indicate revision number and date.
- .3 Submit each revised Cx Plan to Departmental Representative for review and obtain written approval.
- .4 Include testing parameters at full range of operating conditions and check responses of equipment and systems.

1.6 COMPOSITION, ROLES AND RESPONSIBILITIES OF CX TEAM

- .1 Departmental Representative to maintain overall responsibility for project and is sole point of contact between members of commissioning team.
- .2 Project Manager will select Cx Team consisting of following members:
 - .1 PWGSC Design Quality Review Team: during construction, will conduct periodic site reviews to observe general progress.
 - .2 PWGSC Quality Assurance Commissioning Manager: ensures Cx activities are carried out to ensure delivery of a fully operational project including:
 - .1 Review of Cx documentation from operational perspective.
 - .2 Review for performance, reliability, durability of operation, accessibility, maintainability, operational efficiency under conditions of operation.
 - .3 Protection of health, safety and comfort of occupants and O&M personnel.
 - .4 Monitoring of Cx activities, training, development of Cx documentation.
 - .5 Work closely with members of Cx Team.
- .3 Departmental Representative is responsible for:
 - .1 Organizing Cx.
 - .2 Monitoring operations Cx activities.
 - .3 Witnessing, certifying accuracy of reported results.
 - .4 Witnessing and certifying TAB and other tests.
 - .5 Developing BMM.
 - .6 Ensuring implementation of final Cx Plan.
 - .7 Performing verification of performance of installed systems and equipment.
 - .8 Implementation of Training Plan.
- .4 Construction Team: contractor, sub-contractors, suppliers and support disciplines, is responsible for construction/installation in accordance with contract documents, including:
 - .1 Testing.
 - .2 TAB.
 - .3 Performance of Cx activities.
 - .4 Delivery of training and Cx documentation.
 - .5 Assigning one person as point of contact with Consultant and PWGSC Cx Manager for administrative and coordination purposes.
- .5 Contractor's Testing Organization implements specified Cx activities including:
 - .1 Demonstrations.
 - .2 Training.
 - .3 Testing.
 - .4 Preparation, submission of test reports.

1.7 CX PARTICIPANTS

- .1 Employ the following Cx participants to verify performance of equipment and systems:
 - .1 Installation contractor/subcontractor:
 - .1 Equipment and systems except as noted.
 - .2 Equipment manufacturer: equipment specified to be installed and

- started by manufacturer.
- .1 To include performance verification.
- .3 Testing Organization:
 - .1 Possessing specialist qualifications and installations providing environments essential to client's program but are outside scope or expertise of Cx specialists on this project.
- .2 Ensure that each Cx participant:
 - .1 Could complete work within scheduled time frame.
 - .2 Is available for emergency and troubleshooting service during first year of occupancy by user for adjustments and modifications outside responsibility of O&M personnel
- .3 Provide names of participants to Departmental Representative and details of instruments and procedures to be followed minimum 4 weeks prior to starting date of Cx for review and approval.

1.8 RISK ASSESSMENT

- .1 Testing Organization to provide risk assessment to PWGSC requirements as an appendix to the Commissioning Plan.

1.9 EXTENT OF CX

- .1 Commission electrical systems and equipment:
 - .1 High voltage:
 - .1 High voltage switch gear and transformation equipment.
 - .2 High voltage distribution systems.
 - .2 Low voltage below 750 V:
 - .1 Low voltage equipment.
 - .2 Low voltage distribution systems.
 - .3 Controls and Monitoring:
 - .1 Function of all control and monitoring systems as specified

1.10 DELIVERABLES RELATING TO O&M PERSPECTIVES

- .1 General requirements:
 - .1 Compile English documentation.
 - .2 Documentation to be computer-compatible format ready for inputting for data management.
- .2 Provide deliverables:
 - .1 Warranties.
 - .2 Project record documentation.
 - .3 Inventory of spare parts, special tools and maintenance materials.
 - .4 Maintenance Management System (MMS) identification system used.
 - .5 WHMIS information.
 - .6 MSDS data sheets.
 - .7 Electrical Panel inventory containing detailed inventory of electrical circuitry for each panel board. Duplicate of inventory inside each panel.

1.11 DELIVERABLES RELATING TO THE CX PROCESS

- .1 General:
 - .1 Start-up, testing and Cx requirements, conditions for acceptance and specifications form part of relevant technical sections of these specifications.
- .2 Definitions:
 - .1 Cx as used in this section includes:
 - .1 Cx of components, equipment, systems, subsystems, and integrated systems.
 - .2 Factory inspections and performance verification tests.
- .3 Deliverables: provide:
 - .1 Cx Specifications.
 - .2 Startup, pre-Cx activities and documentation for systems, and equipment.
 - .3 Completed installation checklists (ICL).
 - .4 Completed product information (PI) report forms.
 - .5 Completed performance verification (PV) report forms.
 - .6 Results of Performance Verification Tests and Inspections.
 - .7 Description of Cx activities and documentation.
 - .8 Description of Cx of integrated systems and documentation.
 - .9 Training Plans.
 - .10 Cx Reports.
 - .11 Prescribed activities during warranty period.
- .4 Departmental Representative to witness and certify tests and reports of results provided to the Contractor.

1.12 PRE-CX ACTIVITIES AND RELATED DOCUMENTATION

- .1 Items listed in this Cx Plan include the following:
 - .1 Pre-Start-Up inspections: by Departmental Representative prior to permission to start up and rectification of deficiencies to Departmental Representative's satisfaction.
 - .2 Departmental Representative to use approved check lists.
 - .3 Departmental Representative will monitor some of these pre-start-up inspections.
 - .4 Include completed documentation with Cx report.
 - .5 Conduct pre-start-up tests: conduct pressure, static, flushing, cleaning, and "bumping" during construction as specified in technical sections. To be witnessed and certified by Departmental Representative and does not form part of Cx specifications.
 - .6 Departmental Representative will monitor some of these inspections and tests.
 - .7 Include completed documentation in Cx report.

1.13 START-UP

- .1 Start-up components, equipment and systems.

- .2 Equipment manufacturer, supplier, installing specialist sub-contractor, as appropriate, to start-up, under Contractor's direction.
- .3 Departmental Representative to monitor all of these start-up activities.
 - .1 Rectify start-up deficiencies to satisfaction of Departmental Representative.
- .4 Performance Verification (PV):
 - .1 Approved Cx Agent to perform.
 - .1 Repeat when necessary until results are acceptable to Departmental Representative.
 - .2 Use procedures modified generic procedures to suit project requirements.
 - .3 Departmental Representative to witness and certify reported results using approved PI and PV forms.
 - .4 Departmental Representative to approve completed PV reports and provide to Departmental Representative.
 - .5 Departmental Representative reserves right to verify up reported results at random.
 - .6 Failure of randomly selected item shall result in rejection of PV report or report of system startup and testing.

1.14 CX ACTIVITIES AND RELATED DOCUMENTATION

- .1 Perform Cx by specified Cx agency using procedures developed by Testing Organization and approved by Departmental Representative.
- .2 Departmental Representative to monitor Cx activities.
- .3 Upon satisfactory completion, Cx agency performing tests to prepare Cx Report using approved PV forms.
- .4 Departmental Representative to witness, certify reported results of, Cx activities and forward to Departmental Representative.
- .5 Departmental Representative reserves right to verify a percentage of reported results at no cost to contract.

1.15 CX OF INTEGRATED SYSTEMS AND RELATED DOCUMENTATION

- .1 Cx to be performed by specified Cx specialist, using procedures developed by Testing Organization and approved by Departmental Representative.
- .2 Tests to be witnessed by Departmental Representative and documented on approved report forms.
- .3 Upon satisfactory completion, Testing Organization to prepare Cx Report, to be submitted to Departmental Representative for review.
- .4 Departmental Representative reserves right to verify percentage of reported results.

- .5 Identification:
 - .1 In later stages of Cx, before hand-over and acceptance Departmental Representative, Contractor, Department and Cx Administrator to co-operate to complete inventory data sheets and provide assistance to PWGSC in full implementation of MMS identification system of components, equipment, sub-systems, systems.

1.16 INSTALLATION CHECK LISTS (ICL)

- .1 Refer to Section 01 91 33.

1.17 PRODUCT INFORMATION (PI) REPORT FORMS

- .1 Refer to Section 01 91 33.

1.18 PERFORMANCE VERIFICATION (PV) REPORT

- .1 Refer to Section 01 91 33.

1.19 DELIVERABLES RELATING TO ADMINISTRATION OF CX

- .1 General:
 - .1 Because of risk assessment, complete Cx of occupancy, weather and seasonal-sensitive equipment and systems in these areas before building is occupied.

1.20 CX SCHEDULES

- .1 Prepare detailed critical path Cx Schedule and submit to Departmental Representative for review and approval same time as project Construction Schedule. Include:
 - .1 Milestones, testing, documentation, training and Cx activities of components, equipment, subsystems, systems and integrated systems, including to suit construction schedule and commissioning specifications.
 - .2 Detailed training schedule to demonstrate no conflicts with testing, completion of project and hand-over to Department.
- .2 After approval, incorporate Cx Schedule into Construction Schedule.
- .3 Consultant, Contractor, Contractor's Cx agent, and Departmental Representative will monitor progress of Cx against this schedule.

1.21 CX REPORTS

- .1 Submit reports of tests, witnessed and certified by Departmental Representative to Departmental Representative who will verify reported results.
- .2 Include completed and certified PV reports in properly formatted Cx Reports.
- .3 Before reports are accepted, reported results to be subject to verification by Departmental Representative.

1.22 TESTS TO BE PERFORMED BY OWNER/USER

- .1 None is anticipated on this project.

1.23 TRAINING PLANS

- .1 Refer to Section 01 91 41.

1.24 FINAL SETTINGS

- .1 Upon completion of Cx to satisfaction of Departmental Representative lock control devices in their final positions, indelibly mark settings marked and include in Cx Reports.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 SUMMARY

- .1 Section Includes:
 - .1 Commissioning forms to be completed for equipment, system and integrated system.
- .2 Related Sections:
 - .1 Refer to 01 91 00

1.2 INSTALLATION/START-UP CHECK LISTS

- .1 Include the following data:
 - .1 Product manufacturer's installation instructions and recommended checks.
 - .2 Special procedures as specified in relevant technical sections.
 - .3 Items considered good installation and engineering industry practices deemed appropriate for proper and efficient operation.
- .2 Equipment manufacturer's installation/start-up check lists are acceptable for use. As deemed necessary by Departmental Representative supplemental additional data lists will be required for specific project conditions.
- .3 Use check lists for equipment installation. Document check list verifying checks have been made, indicate deficiencies and corrective action taken.
- .4 Installer to sign check lists upon completion, certifying stated checks and inspections have been performed. Return completed check lists to Departmental Representative. Check lists will be required during Commissioning and will be included in Building Maintenance Manual (BMM) at completion of project.
- .5 Use of check lists will not be considered part of commissioning process but will be stringently used for equipment pre-start and start-up procedures.

1.3 PRODUCT INFORMATION (PI) REPORT FORMS

- .1 Product Information (PI) forms compiles gathered data on items of equipment produced by equipment manufacturer, includes nameplate information, parts list, operating instructions, maintenance guidelines and pertinent technical data and recommended checks that is necessary to prepare for start-up and functional testing and used during operation and maintenance of equipment. This documentation is included in the BMM at completion of work.
- .2 Prior to Performance Verification (PV) of systems complete items on PI forms related to systems and obtain Departmental Representative's approval.

1.4 PERFORMANCE VERIFICATION (PV) FORMS

- .1 PV forms to be used for checks, running dynamic tests and adjustments carried out on equipment and systems to ensure correct operation, efficiently and function independently and interactively with other systems as intended with project requirements.
- .2 PV report forms include those developed by Contractor records measured data and readings taken during functional testing and Performance Verification procedures.
- .3 Prior to PV of integrated system, complete PV forms of related systems and obtain Departmental Representative's approval.

1.5 COMMISSIONING FORMS

- .1 Use Commissioning forms to verify installation and record performance when starting equipment and systems.
- .2 Strategy for Use:
 - .1 Testing Organization provides Departmental Representative project-specific Commissioning forms with Specification data included for approval.
 - .2 Contractor will provide required shop drawings information and verify correct installation and operation of items indicated on these forms.
 - .3 Confirm operation as per design criteria and intent.
 - .4 Identify variances between design and operation and reasons for variances.
 - .5 Verify operation in specified normal and emergency modes and under specified load conditions.
 - .6 Record analytical and substantiating data.
 - .7 Verify reported results.
 - .8 Form to bear signatures of recording technician and reviewed and signed off by Departmental Representative.
 - .9 Submit immediately after tests are performed.
 - .10 Reported results in true measured SI unit values.
 - .11 Provide Departmental Representative with originals of completed forms.
 - .12 Maintain copy on site during start-up, testing and commissioning period.

1.6 LANGUAGE

- .1 To suit the language profile of the awarded contract.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

.1 Not Used.

PART 1 - GENERAL

1.1 SUMMARY

- .1 Section Includes:
 - .1 This Section specifies roles and responsibilities of Commissioning Training.
- .2 Related Sections:
 - .1 See 01 91 00

1.2 TRAINEES

- .1 Trainees: personnel selected for operating and maintaining this facility. Includes Facility Manager, building operators, maintenance staff, security staff, and technical specialists as required.
- .2 Trainees will be available for training during later stages of construction for purposes of familiarization with systems.

1.3 INSTRUCTORS

- .1 Testing Organization will provide:
 - .1 Descriptions of systems.
 - .2 Instruction on design philosophy, design criteria, and design intent.
- .2 Contractor and certified factory-trained manufacturers' personnel: to provide instruction on the following:
 - .1 Start-Up, operation, shut-down of equipment, components and systems.
 - .2 Control features, reasons for, results of, implications on associated systems of, adjustment of set points of control and safety devices.
 - .3 Instructions on servicing, maintenance and adjustment of systems, equipment and components.
- .3 Contractor and equipment manufacturer to provide instruction on:
 - .1 Start-up, operation, maintenance and shut-down of equipment they have certified installation, started up and carried out PV tests.

1.4 TRAINING OBJECTIVES

- .1 Training to be detailed and duration to ensure:
 - .1 Safe, reliable, cost-effective, energy-efficient operation of systems in normal and emergency modes under all conditions.
 - .2 Effective on-going inspection, measurements of system performance.
 - .3 Proper preventive maintenance, diagnosis and trouble-shooting.
 - .4 Ability to update documentation.
 - .5 Ability to operate equipment and systems under emergency conditions until appropriate qualified assistance arrives.

1.5 TRAINING MATERIALS

- .1 Instructors to be responsible for content and quality.

- .2 Training materials to include:
 - .1 "As-Built" Contract Documents.
 - .2 Operating Manual.
 - .3 Maintenance Manual.
 - .4 Management Manual.
 - .5 Video Recording of training sessions
- .3 Departmental Representative will review training manuals.
- .4 Training materials to be in a format that permits future training procedures to same degree of detail.
- .5 Supplement training materials:
 - .1 Transparencies for overhead projectors.
 - .2 Multimedia presentations.
 - .3 Manufacturer's training videos.
 - .4 Equipment models.

1.6 SCHEDULING

- .1 Include in Commissioning Schedule time for training.
- .2 Deliver training during regular working hours, training sessions to be maximum three hours in length.
- .3 Training to be completed prior to acceptance of facility.

1.7 7 RESPONSIBILITIES

- .1 Be responsible for:
 - .1 Implementation of training activities,
 - .2 Coordination among instructors,
 - .3 Quality of training, training materials,
 - .4 Video recording of training sessions
- .2 Departmental Representative will evaluate training and materials.
- .3 Upon completion of training, provide written report, signed by Instructors, witnessed by Departmental Representative.

1.8 TRAINING CONTENT

- .1 Training to include demonstrations by Instructors using the installed equipment and systems.
- .2 Content includes:
 - .1 Review of facility and occupancy profile.
 - .2 Functional requirements.
 - .3 System philosophy, limitations of systems and emergency procedures.
 - .4 Review of system layout, equipment, components and controls.
 - .5 Equipment and system start-up, operation, monitoring, servicing, maintenance and shut-down procedures.

- .6 System operating sequences, including step-by-step directions for starting up, shut-down, operation of valves, dampers, switches, adjustment of control settings and emergency procedures.
 - .7 Maintenance and servicing.
 - .8 Trouble-shooting diagnosis.
 - .9 Inter-action among systems during integrated operation.
 - .10 Review of O&M documentation.
- .3 Provide specialized training as specified in relevant Technical Sections of the construction specifications.

1.9 VIDEO-BASED TRAINING

- .1 Manufacturer's videotapes/DVDs/Blu-ray to be used as training tool with Departmental Representative's review and written approval 4 weeks prior to commencement of scheduled training.
- .2 On-Site training videos:
 - .1 Videotape or record training sessions for use during future training.
 - .2 To be performed after systems are fully commissioned.
 - .3 Organize into several short modules to permit incorporation of changes.
- .3 Production methods to be professional quality.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 SUMMARY

- .1 Section Includes:
 - .1 This section is limited to portions of the Building Management Manual (BMM) provided to Departmental Representative by Contractor.
- .2 Related Sections:
 - .1 Section 01 91 00 - Commissioning - General Requirements
 - .2 Section 23 09 00 - Electric and Electronic Control System for HVAC
- .3 Acronyms:
 - .1 BMM - Building Management Manual.
 - .2 Cx - Commissioning.
 - .3 PI - Product Information.
 - .4 PV - Performance Verification.
 - .5 WHMIS - Workplace Hazardous Materials Information System.

1.2 GENERAL REQUIREMENTS

- .1 Standard letter size paper 216 mm x 279 mm.
- .2 Methodology used to facilitate updating.
- .3 Drawings, diagrams and schematics to be professionally developed.
- .4 Electronic copy of data to be in a format accepted and approved by Departmental Representative.

1.3 APPROVALS

- .1 Prior to commencement, co-ordinate requirements for preparation, submission and approval with Departmental Representative.

1.4 GENERAL INFORMATION

- .1 Provide Departmental Representative the following for insertion into appropriate Part and Section of BMM:
 - .1 Complete list of names, addresses, telephone and fax numbers of Contractor, sub-contractors that participated in delivery of project - as indicated in Section 1.2 of BMM.
 - .2 Summary of architectural, structural, fire protection, mechanical and electrical systems installed and commissioned - as indicated in Section 1.4 of BMM.
 - .1 Including sequence of operation as finalized after commissioning is complete as indicated in Section 2.0 of BMM.
 - .3 Description of building operation under conditions of heightened security and emergencies as indicated in Section 2.0 of BMM.
 - .4 System, equipment and components Maintenance Management System (MMS) identification - Section 2.1 of BMM.
 - .5 Information on operation and maintenance of architectural systems

- and equipment installed and commissioned - Section 2.0 of BMM.
- .6 Information on operation and maintenance of fire protection and life safety systems and equipment installed and commissioned - Section 2.0 of BMM.
 - .7 Information on operation and maintenance of mechanical systems and equipment installed and commissioned - Section 2.0 of BMM.
 - .8 Operating and maintenance manual - Section 3.2 of BMM.
 - .9 Final commissioning plan as actually implemented.
 - .10 Completed commissioning checklists.
 - .11 Commissioning test procedures employed.
 - .12 Completed Product Information (PI) and Performance Verification (PV) report forms, approved and accepted by Departmental Representative.
 - .13 Commissioning reports.

1.5 CONTENTS OF OPERATING AND MAINTENANCE MANUAL

- .1 For detailed requirements refer to Section 01 78 00.
- .2 Departmental Representative to review and approve format and organization within 12 weeks of award of contract.
- .3 Include original manufactures brochures and written information on products and equipment installed on this project.
- .4 Record and organize for easy access and retrieval of information contained in BMM.
- .5 Include completed PI report forms, data and information from other sources as required.
- .6 Inventory directory relating to information on installed systems, equipment and components.
- .7 Approved project shop-drawings, product and maintenance data.
- .8 Manufacturer's data and recommendations relating: manufacturing process, installation, commissioning, start-up, O&M, shutdown and training materials.
- .9 Inventory and location of spare parts, special tools and maintenance materials.
- .10 Warranty information.
- .11 Inspection certificates with expiration dates, which require on-going re-certification inspections.
- .12 Maintenance program supporting information including:
 - .1 Recommended maintenance procedures and schedule.
 - .2 Information to removal and replacement of equipment including, required equipment, points of lift and means of entry and egress.

1.6 LIFE SAFETY COMPLIANCE (LSC) MANUAL

- .1 Samples of LSC Manual will be available from Departmental Representative.
- .2 Content of Manual:
 - .1 All possible Emergency situations modes including: presence of fire and smoke, power failure, lose of water or pressure, chemical spills and refrigerant release.
 - .2 Failure of elevators and escalators.
 - .3 HVAC emergencies and fuel supply failures.
 - .4 Intrusion and security breach.
 - .5 Emergency provisions for natural disasters, bomb threats and other disruptive situations.
 - .6 Dedicated emergency generators for high security projects, medical facilities and computer systems.
 - .7 Emergency control procedures for fire, power and major equipment failure.
 - .8 Emergency contacts and numbers.
 - .9 Manual to be readily available and comprehensible to non-technical readers.

1.7 SUPPORTING DOCUMENTATION FOR INSERTION INTO SUPPORTING APPENDICES

- .1 Provide Departmental Representative supporting documentation relating to installed equipment and system, including:
 - .1 General:
 - .1 Finalized commissioning plan.
 - .2 WHMIS information manual.
 - .3 Approved "as-built" drawings and specifications.
 - .4 Procedures used during commissioning.
 - .5 Cross-Reference to specification sections.
 - .2 Architectural and structural:
 - .1 Inspection certificates, construction permits.
 - .2 Roof anchor log books.
 - .3 PV reports.
 - .3 Fire prevention, suppression and protection:
 - .1 Test reports.
 - .2 Smoke test reports.
 - .3 PV reports.
 - .4 Mechanical:
 - .1 Installation permits, inspection certificates.
 - .2 Piping pressure test certificates.
 - .3 Ducting leakage test reports.
 - .4 TAB and PV reports.
 - .5 Charts of valves and steam traps.
 - .6 Copies of posted instructions.
 - .5 Electrical:
 - .1 Installation permits, inspection certificates.
 - .2 TAB and PV reports.
 - .3 Electrical work log book.
 - .4 Charts and schedules.
 - .5 Locations of cables and components.
 - .6 Copies of posted instructions.

- .2 Assist Departmental Representative with preparation of BMM.

1.8 IDENTIFICATION OF FACILITY

- .1 When submitting information to Departmental Representative for incorporation into BMM, use following system for identification of documentation:
 - .1 Facility electrical system.
 - .2 Electrical equipment (Transformer, NGR, HV switchgears and LV switchgears).
 - .3 Alarm signals to BAS system.

1.9 USE OF CURRENT TECHNOLOGY

- .1 Use current technology for production of documentation. Emphasis on ease of accessibility at all times, maintain in up-to-date state, compatibility with user's requirements.
- .2 Obtain Departmental Representative's approval before starting Work.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not used.

PART 1 - GENERAL

1.1 REFERENCES

- .1 American Society for Nondestructive Testing (ASNT)
 - .1 Recommended Practice SNT-TC-1A (2001), Non-Destructive Testing.
- .2 National Electrical Contractors Association (NECA)
- .3 National Electrical Testing Association (NETA)
 - .1 NETA Maintenance Testing Specifications-2005, Section 9.0 Thermographic Survey.
- .4 National Fire Protection Association (NFPA)
 - .1 NFPA 70E 2015, Standard for Electrical Safety in the Workplace.

1.2 DEFINITIONS

- .1 Thermographic Inspection: analysis of electrical equipment and components using thermal imaging equipment to observe thermal anomalies providing specific information indicating localized, abnormally warm or cool connections that could indicate potential problems using equipment operated by qualified infrared thermographic technologist having specific knowledge of electrical equipment, electrical site safety and as follows:
 - .1 Quantitative Inspection: inspection procedure using measurements of infrared radiation, assigning specific numeric values to observed deficient patterns, and presenting that information in Thermographic Inspection Report.
- .2 Thermographic Inspection Report: organized document stating inspection purpose, description of components being inspected, general findings, and recommendations including, but not limited to appropriately analyzed thermal images with corresponding visual photographs to express observed deficient conditions, statements interpreting observed deficient conditions.
 - .1 Quantitative Thermographic Inspection Report: developed by means of quantitative thermographic inspection where measurement of infrared radiation is used to determine relative fault severity. Recommendations identify corrective measures required to fix deficient conditions
- .3 Limited Approach Boundary: approach limit at distance from exposed live part of electrical equipment within where potential shock hazard exists as defined by NFPA 70E and as determined by following analyses:
 - .1 Shock Hazard Analysis: determines shock hazard that personnel will be exposed to, boundary requirements, and personal protective equipment requirements to minimize electrical shock hazard.
 - .2 Flash Hazard Analysis: determines arc flash hazard, establishes safe working distance and personal protective equipment required within Limited Approach Boundary.

1.3 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.
- .2 Provide 4 copies of Thermographic Inspection Report to Departmental Representative.
- .3 If available submit baseline data from previous inspections.
- .4 Submit inspection plan before starting work of thermographic inspection indicating path of travel and equipment being inspected, record following information:
 - .1 Loading conditions or situations that may affect thermographic scans.
 - .2 Removal of accessories affecting calibration of thermographic scanning instruments.
 - .3 Equipment labels and performance data.
- .5 Submit Quantitative Thermographic Inspection Report containing specific test results listed in this section, organized in accordance with NETA Maintenance Testing Specifications, and as follows:
 - .1 Scoping statement and problem identification.
 - .2 Names and qualifications of personnel performing inspections, interpreting data and preparing Thermographic Inspection Report.
 - .3 Record thermal anomalies ranging outside of expected observations and identify the following:
 - .1 Description of component being inspected.
 - .2 Voltage, amperage rating and phase of component.
 - .3 Exact location of component.
 - .4 Date and time of inspection.
 - .5 Modifications to inspection route, or equipment not available or inaccessible at time of inspection.
 - .6 Specialized camera accessories (i.e.: spark shield).
 - .4 Record quantitative information including, but not limited, the following:
 - .1 Surface temperature of component being inspected.
 - .2 Estimated or measured surface emissivity of component.
 - .3 Component rating or size.
 - .4 Actual load condition on electrical equipment (percentage), calculated by dividing measured amperage used by rated amperage.
 - .5 Surface temperature of defined reference component, including temperature change across component.
 - .6 Background temperature.
 - .7 Ambient air temperature.
 - .8 Abnormal physical conditions based on visual inspection.
 - .9 Difference in temperature between inspected component and defined reference component, ambient air temperature, or both.
 - .10 Inside wind speed or convection currents.
 - .11 Environmental conditions during inspection including influences from solar gain, moisture and wind.
 - .5 Record testing methods used to confirm findings including, but not limited to, the following:
 - .1 Voltage or current checks.

- .2 System load.
- .3 Ultrasound.
- .4 Oil analysis.
- .5 Power monitoring.
- .6 Fault gas analysis.
- .7 Motor testing.
- .6 Types of equipment used and methods of confirmation including, but not limited to, as follows:
 - .1 Electrical testing equipment, ammeter and voltage meter.
 - .2 Infrared radiometer, air flow sensor, temperature and relative humidity equipment used in inspections along with calibration information for equipment.
 - .3 List of various lenses used to obtain infrared thermographic imagery and temperature data.
 - .4 Emissivity values used to calibrate temperature readings.
- .7 Diagnoses and identification of suspected problems including photographs and commentary indicating severity and types of thermal anomalies detected, with corrective actions prioritized by thermographic evidence and the following contributory factors:
 - .1 Probability of failure including, but not limited to, the following:
 - .1 History.
 - .2 Load.
 - .3 Convection.
 - .4 Reliability of measurement.
 - .5 Temperature.
 - .6 Temperature rise.
 - .7 Rate of temperature rise.
 - .2 Consequence of Failure including, but not limited to, the following:
 - .1 Safety.
 - .2 Criticality.
 - .3 Environmental.
 - .4 Cost.
 - .5 Quality.
 - .3 Indicate temperature calibration parameters on thermal image data including, but not limited to, emissivity and reflected background temperature.
- .8 List of all equipment that could not be inspected and reasons for no inspection:
 - .1 Equipment not found.
 - .2 Equipment not running or under.
 - .3 Equipment not adequately loaded.
 - .4 Equipment loaded but not running long enough.
 - .5 Low duty cycle.
 - .6 Panel could not be opened.
 - .7 Line of sight not available.
 - .8 Emissivity too low.
 - .9 Environmental conditions unfavourable.
- .9 Interpretation of observed conditions and deficiencies including probable causes of each thermal anomaly detected listing priority ratings and actions as follows:
 - .1 Low probability or consequence of failure: recommend no action

- required until next scheduled inspection.
- .2 Unknown or uncertain probability of failure, or increased risk of consequence of failure: recommend increased monitoring frequency, and alternative diagnostic technology to further define severity or cause of anomaly.
 - .3 High probability of failure high or severe consequence of failure: recommend solutions and related additional inspections that may be required to verify that repairs have been completed.
- .10 Attachments and appendices including, but not limited to, drawings, electrical equipment schedules, visual images, thermographic images, and calculations used to determine electrical equipment fault severity.
- .6 Submit calibration report dated within one year prior to inspection demonstrating that temperature measuring thermal imaging equipment is accurately measuring surface temperature in accordance with equipment manufacturer's specifications.
- .7 Information obtained during inspection and for preparing Thermographic Inspection Report is considered proprietary for use of Departmental Representative; submit original data used to prepare Thermographic Inspection Report as separate package.

1.4 QUALITY ASSURANCE

- .1 Qualifications: provide personnel having minimum 3 years of related experience and having following minimum levels of training:
- .1 Thermal Imaging Equipment Operators:
 - .1 Use thermal imaging equipment operators having training in courses recognized by ASNT covering basic infrared camera operation, infrared theory and practical thermographic application in common thermal inspections relating to inspection of electrical equipment and electrical site safety, and having qualified and tested to full compliance with ASNT TC-1A TIR Level 1 and an Employers Written Practice for Personnel qualification for electrical equipment inspections.
 - .2 Provide Certificate of Qualification showing full compliance certification by accredited third party ASNT Level III.
 - .2 Reporters:
 - .1 Use reporters having training in courses recognized by ASNT covering enhanced infrared camera operation, expanded infrared theory, and detailed practical thermographic application in common thermal inspections relating to electrical equipment, having specific training in electrical equipment inspections and electrical site safety, having capability of interpreting common electrical deficiencies, causes and effects, and having qualified and tested to full compliance with ASNT TC-1A TIR Level II and an Employer's Written Practice for Personnel qualification for electrical equipment inspections.
 - .2 Provide Certificate of Qualification showing full compliance certification by accredited third party ASNT Level III.

- .3 Report Author:
 - .1 Use authors familiar with electrical systems and components similar to those being inspected, who is capable of providing conclusions and recommendations within Thermographic Inspection Report and having technical or professional training in electrical installations from an accredited college or university, and having qualified and tested to full compliance with ASNT TC-1A TIR Level II and an Employer's Written Practice for Personnel qualification for electrical equipment inspections.
 - .2 Provide Certificate of Qualification showing full compliance certification by accredited third party ASNT Level III.
- .4 Licensed Electrician:
 - .1 Use only electricians licensed by provincial Authorities Having Jurisdiction to open panels, cabinets, and transformer covers, and for obtaining amperage and voltage readings.

1.5 SCHEDULING

- .1 Notify Departmental Representative to provide representative who can obtain necessary security clearances for thermographic inspection agency for regular and after hours work on both interior and exterior of building.
- .2 Notify Departmental Representative to provide electrician and/or site representative who is knowledgeable with facility and electrical equipment and components, and who is able to assist thermographic inspection agency in identifying components forming part of total building electrical system.

PART 2 - PRODUCTS

2.1 EQUIPMENT

- .1 Thermographic Imaging Equipment: radiometric, temperature sensing, digital thermal imaging system capable of working at exterior ambient temperatures experienced in field and meeting following minimum requirements; spot radiometers will not be acceptable:
 - .1 Minimum Detectable Temperature Difference (MDTD): 0.2 degrees C differentiation at 30 degrees C or better, having a range of -20 degrees C to 300 degrees C or better.
 - .2 Performance Range: capable of working at exterior ambient temperatures, with actual MDTD not to decrease to less than 0.2 degrees C on (blackbody equivalent) temperature of surface being detected, have capability of taking direct temperature measurements and be adjustable for emissivity with camera or with image processing software.
 - .3 Minimum Spatial Resolution: Instantaneous Field of View (IFOV).
 - .1 For interior inspections: 120 x 160 FPA: 3 milliradians or better.
 - .2 For exterior inspections: 240 x 320 FPA: 1.5 milliradians or better.
 - .4 Minimum Measurement Resolution: Instantaneous Field of View for Measurement Purposes (IFOV Measure).
 - .1 For interior inspections: 120 x 160 FPA or better, consisting

- of minimum 10,000 true detector pixels, distance to target surface and spot size ratio to be better than 100:1.
- .2 For exterior inspections: 240 x 320 FPA or better, consisting of minimum 40,000 true detector pixels, distance to target surface and spot size ratio to be better than 100:1.
- .5 Level, Span and Emissivity Storage Settings: minimum 12 bit mapping protocol image format to allow for picture readjustment of stored data.
- .6 Digital Image Format: non-proprietary.
- .7 Video Output: NTSC compatible video stored in MPEG video file format from which minimum 2 mega pixel still images can be extracted, having date/time stamping and capability for post-processing to enhance observed conditions.
- .2 Related Equipment: provide related equipment for performing thermographic inspection including, but not limited to, as follows:
- .1 Ambient Air and Contact Thermometer.
- .2 Relative Humidity Meter.
- .3 Anemometer.
- .4 Air Flow Meter.
- .5 Analog or digital video camera and/or recorder.
- .6 Standard, Wide Angle and Telephoto Lenses for Visible and Infrared Cameras.
- .7 Tools required to safely access panels, enclosure doors, and equipment.
- .8 Mirrors for observing equipment where direct line of site is not possible.
- .9 Electricians tape; black, having emissivity of 0.95 for normalizing reflective surfaces.
- .10 Voltage and amperage measuring devices.
- .11 Visible Still Image (35 mm) or Digital Cameras having a minimum 4 mega pixel image resolution.
- .12 Appropriate personal protective equipment meeting requirements for arc potential energy level, calculated for specific equipment in accordance with NFPA 70E.
- .13 Other equipment or supplies necessary to complete electrical equipment inspection.

PART 3 - EXECUTION

3.1 MANUFACTURER'S INSTRUCTIONS

- .1 Compliance: comply with manufacturer's written recommendations or specifications, including product technical bulletins, handling, storage and installation instructions, and datasheets.

3.2 EXAMINATION

- .1 Examine drawings and specifications to become familiar with building electrical systems and equipment design.

- .2 Confirm that equipment is operating and under normal load for sufficient time, and as follows:
 - .1 Arrange with site representative to start equipment sufficiently in advance to allow equipment to reach operating temperature
 - .2 Locate and identify equipment being inspected and confirm that equipment is clearly labelled.
 - .3 Record observed conditions or deviations, and note any changes on inspection plan.

3.3 PREPARATION

- .1 Confirm calibration of infrared radiometer equipment over range of (blackbody equivalent) temperatures measured by scan and include confirmation of calibration as part of final Thermographic Inspection Report.
- .2 Conduct pre-inspection safety briefing with personnel performing inspection:
 - .1 Establish Limited Approach Boundary and work practices in accordance NFPA 70E.
 - .2 Ensure that personnel are familiar with and are wearing appropriate personal protective equipment.
- .3 Locate and identify the equipment to be inspected.
 - .1 If equipment is not clearly or properly identified work with Departmental Representative to verify equipment to be inspected and have it properly labeled.
 - .2 Prepare route list and line diagram of equipment to be inspected.
- .4 Notify personnel within thermographic inspection area of procedures and equipment being inspected, arrange for removal and replacement of accessories or attachments affecting calibration of thermographic scanning instruments.
- .5 Clean electrical equipment enclosures free of dust, debris or liquids that might spill into inspection area when they are opened.
- .6 Obtain baseline images and data from Departmental Representative for comparison purposes during inspection, record changes to baseline information in Thermographic Inspection Report.

3.4 THERMOGRAPHIC INSPECTION

- .1 Wear appropriate PPE for allowed working distance, as outlined in NFPA 70E.
- .2 Perform thermographic scans on equipment and panels operating at full load for minimum of 1 hour after temperature has stabilized; shield opened panels to protect against air currents that could distort readings.
- .3 Perform thermographic scans in accordance with ASNT SNT-TC-1A, and to minimize time spent within Limited Approach Boundary using properly focused scanning equipment having correct range, span and level settings, with correctly combined object size and inspection distance set for

- equipment IFOV.
- .4 Thermal images should be acquired for measurement purposes at appropriate distances such that distance of target surfaces to spot size ratio is less than 100:1. Equipment shall be used in such manner as to measure spot sizes of 6 mm or greater. For spot sizes of 6 mm:
 - .1 Equipment having 120 x 160 pixel resolution with IFOV of 3 milliradians or better should limit distance to target surfaces to 2 m or less.
 - .2 Equipment having 240 x 320 pixel resolution with IFOV of 1.5 milliradians or better should limit distance to target surfaces to 4 m or less.
 - .3 Appropriate telephoto lenses should be used for inspection work where spatial resolution as stated above cannot be met with standard lenses.
 - .4 Increased spot size resolution will result in proportional increased maximum distances to target surfaces.
 - .5 Scan exterior of equipment enclosures for thermal anomalies before opening doors or panels and as follows:
 - .1 Keep personnel away from potential arc flash zone in accordance with NFPA 70E.
 - .2 Open doors or panels where scan indicates no thermal anomalies consistent with internal electrical fault.
 - .3 Take suitable precautions before opening panels where thermal anomalies indicate potential for severe internal electrical fault.
 - .4 Store doors and panels in location that poses no potential hazard (i.e.: falling into open enclosure, blocking an exit, or similar hazardous condition) to allow unobstructed access to equipment enclosure.
 - .5 Remove clear or tinted plastic and glass covering electrical components.
 - .6 Perform visual inspection using licensed electrician and confirm that systems are safe before starting scans on interior of enclosures.
 - .7 Inspect infrared viewing windows and make sure they are clean and secure.
 - .6 Protect scanned area from localized air movement of forced convection currents and complete scanning in manner to avoid temperature changes in temperature that could reduce reliability of data.
 - .7 Verify that thermal anomalies are not thermal reflections by moving inspection position or changing viewing angle.
 - .8 Notify licensed electrician of faults that create unsafe condition for performance of electrical inspection (i.e.: severely loose conductors).
 - .9 Notify Departmental Representative of equipment and wiring that could not be inspected and state reasons for no inspection.
 - .1 Advise follow up measures required to inspect this equipment.
 - .10 Notify Departmental Representative of thermal anomalies that cannot be explained by normal variations in load (i.e.: temperature differences between phases in 3 phase system, abnormally warm or cool conditions, or

other irregular temperature variations), record summary of findings and make recommendations for corrective measures to be taken.

- .11 Notify Departmental Representative of thermal anomalies having immediate concern and that has high probability of failure high or severe consequence of failure.

3.5 ELECTRICAL INSPECTION

- .1 Conduct visual inspection to determine cause of anomaly, record observed conditions using still image or digital camera from same angle and distance as thermographic scan.
- .2 Conduct load test reading with equipment at maximum loading using licensed electrician after completion of thermographic scanning to determine:
 - .1 Load is even among three phases.
 - .2 Loads are at least 40% of maximum operating load.
- .3 Reinstall doors, panels, and clear or tinted plastic and glass covers in accordance with NFPA 70E to match equipment manufacturers original installation before starting inspection of each subsequent piece of equipment.

3.6 RECORDING

- .1 Record observed thermal anomalies for, but not limited to, following electrical equipment types:
 - .1 Switches: connections, latch end, hinge end, and fuse connection.
 - .2 Bolted or compression line connections.
 - .3 Insulators.
 - .4 Dry Transformers: high and low side connections, coil temperatures (all phases), and surge protection.
 - .5 Switchgear: bus connections, compression connections, bus stabs, breakers (directly viewable) and surge protection.
 - .6 Motor Control Cabinets (MCC): lug and crimp connections, connections-to-bus, fuses, fuse clips, relays, overload heaters, breaker line/load conductor phase connections and breaker contacts (indirectly viewable), neutral connections and conductors.
 - .7 Distribution and Lighting Panels: line side connections, breaker-to-bus connections, breaker lug connections, breaker contacts (indirectly viewable), neutral connections and conductors, and cabinet heaters.
 - .8 Disconnect Enclosures: disconnect switch contacts (latch and hinge sides), fuses, fuse clips, crimp and lug connections, and neutral connections and conductors.
 - .9 Batteries: charging or discharging minimum 20 minutes prior to inspection, terminal connections and cell temperatures compared to other cells.
 - .10 Exposed Bus and Ventilated Bus Duct: directly viewable through ventilation slots, scan bus with particular attention to narrow span, IFOV, localized heating, and reflection issues.
- .2 Document observations for each piece of inspected electrical equipment and

list probability or consequence of failure including, but not limited to, following:

- .1 Equipment Inspected, No Anomaly Found: record only load and running condition.
- .2 Equipment Inspected, Anomaly Found: record thermographic and visible light image load and running condition, include statement of condition and recommend immediate repairs and re-inspection.
- .3 Equipment Not Inspected: record reasons including, but not limited to, the following:
 - .1 Equipment not found.
 - .2 Equipment not running.
 - .3 Equipment not adequately loaded.
 - .4 Equipment loaded but not running for sufficient time period.
 - .5 Low duty cycle.
 - .6 Panel could not be opened.
 - .7 Line of sight not available.
 - .8 Emissivity too low.
 - .9 Environmental conditions unfavourable.
- .3 Verify that electrician has secured area or returned doors, panels, and interlocks to normal operating position before moving to next piece of equipment.

3.7 RE-INSPECTIONS

- .1 Re-inspect items reported in Thermographic Inspection Report after repairs have been made, perform re-inspections in same manner as original inspections.
- .2 Prepare follow-up summary referencing original Thermographic Inspection Report using before and after images confirming that repairs were successfully completed or indicating that repairs were not effective at repairing deficient areas.
- .3 Repeat thermographic re-inspection indicating insufficient repairs to confirm compliance with specified requirements after subsequent repairs are made.
- .4 Costs for repairs to correct electrical deficiencies and subsequent re-inspections will be responsibility of Contractor.

3.8 CLEANING

- .1 Proceed in accordance with Section 01 74 11.
- .2 On completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.

PART 1 - GENERAL

1.1 REFERENCES

- .1 Definitions:
 - .1 Demolition: rapid destruction of building following removal of hazardous materials.
 - .2 Hazardous Materials: dangerous substances, dangerous goods, hazardous commodities and hazardous products, may include but not limited to: asbestos PCB's, CFC's, HCFC's poisons, corrosive agents, flammable substances, ammunition, explosives, radioactive substances, or other material that can endanger human health or wellbeing or environment if handled improperly.
 - .3 Waste Audit (WA): detailed inventory of materials in building. Indicates quantities of reuse, recycling and landfill.
 - .1 Involves quantifying by volume/weight amounts of materials and wastes generated during construction, demolition, deconstruction, or renovation project.
 - .2 Indicates quantities of reuse, recycling and landfill.
 - .4 Waste Management Coordinator (WMC): contractor representative responsible for supervising waste management activities as well as coordinating related, required submittal and reporting requirements.
 - .5 Waste Reduction Workplan (WRW): written report which addresses opportunities for reduction, reuse, or recycling of materials. WRW is based on information acquired from WA.
- .2 Reference Standards:
 - .1 Canadian Council of Ministers of the Environment (CCME)
 - .2 Health Canada/Workplace Hazardous Materials Information System (WHMIS)
 - .1 Material Safety Data Sheets (MSDS).
 - .3 Transport Canada (TC)
 - .1 Transportation of Dangerous Goods Act, 1992 (TDGA), c. 34.

1.2 ADMINISTRATIVE REQUIREMENTS

- .1 Site Meetings.
 - .1 Convene pre-demolition meeting one week prior to beginning work of this Section in accordance with Section 01 32 16.06 and 01 32 16.07 to:
 - .1 Verify project requirements.
 - .2 Review installation and substrate conditions.
 - .3 Co-ordination with other building subtrades.
 - .4 Review manufacturer's installation instructions and warranty requirements.
 - .2 Arrange for site visit with Departmental Representative to examine existing site conditions adjacent to demolition work, prior to start of Work.
 - .3 Hold project meetings every week.
 - .4 Ensure key personnel, site supervisor, project manager, WMC attend.

- .5 Reporting Requirements: WMC to complete.
 - .6 WMC must provide written report on status of waste diversion activity at each meeting.
 - .7 Departmental Representative will provide written notification of change of meeting schedule established upon contract award 24 hours prior to scheduled meeting.
- .2 Scheduling: meet project time lines without compromising specified minimum rates of material diversion.
 - .1 Notify Departmental Representative in writing when unforeseen delays occur.

1.3 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
- .2 Shop Drawings:
 - .1 Submit drawings stamped and signed by professional engineer registered or licensed in Province of Ontario, Canada.
 - .2 Submit for approval drawings, diagrams or details showing sequence of demolition work and supporting structures and underpinning, where required by authorities having jurisdiction.
- .3 Hazardous Materials:
 - .1 Provide description of Hazardous Materials and Notification of Filing with proper authorities prior to beginning of Work as required.
- .4 Waste Reduction Workplan:
 - .1 Prior to beginning of Work on site submit detailed Waste Reduction Workplan in accordance with Section 01 74 20 and indicate:
 - .1 Descriptions of and anticipated quantities in percentages of materials to be salvaged reused, recycled and landfilled.
 - .2 Schedule of selective demolition.
 - .3 Number and location of dumpsters.
 - .4 Anticipated frequency of tippage.
 - .5 Name and address of haulers, waste facilities, waste receiving organizations.
- .5 Certificates:
 - .1 Submit one copy certified weigh bills, bills of lading and receipts from authorized disposal sites and reuse and recycling facilities for material removed from site on weekly basis and upon request of Departmental Representative.
 - .2 Written authorization from Departmental Representative is required to deviate from haulers, facilities and receiving organizations listed in Waste Reduction Workplan.

1.5 QUALITY ASSURANCE

- .1 Regulatory Requirements: ensure Work is performed in compliance with CEPA, CEAA, TDGA and applicable Provincial/Territorial regulations.

1.6 DELIVERY, STORAGE AND HANDLING

- .1 Store and manage hazardous materials in accordance with Section 01 35 43.
- .2 Storage and Protection.
 - .1 Protect in accordance with Section 31 23 33.01.
 - .2 Protect existing items designated to remain and items designated for salvage. In event of damage to such items, immediately replace or make repairs to approval of Departmental Representative and at no cost to Departmental Representative.
 - .3 Remove and store materials to be salvaged, in manner to prevent damage.
 - .4 Store and protect in accordance with requirements for maximum preservation of material.
 - .5 Handle salvaged materials as new materials.
- .4 Packaging Waste Management: remove for reuse and return by manufacturer of pallets, crates, padding and packaging materials as specified in accordance with Section 01 74 20.

1.7 SITE CONDITIONS

- .1 Site Environmental Requirements.
 - .1 Perform work in accordance with Section 01 35 43.
 - .2 Ensure that selective demolition work does not adversely affect adjacent watercourses, groundwater and wildlife, or contribute to excess air and noise pollution.
 - .3 Do not dispose of waste of volatile materials including but not limited to, mineral spirits, oil, petroleum based lubricants, or toxic cleaning solutions into watercourses, storm or sanitary sewers.
 - .1 Ensure proper disposal procedures are maintained throughout the project.
 - .4 Do not pump water containing suspended materials into watercourses, storm or sanitary sewers or onto adjacent properties.
 - .5 Control disposal or runoff of water containing suspended materials or other harmful substances in accordance with local authorities and as directed by Departmental Representative.
 - .6 Protect trees, plants and foliage on site and adjacent properties where indicated.
- .2 Existing Conditions.
 - .1 Remove contaminated or hazardous materials listed as hazardous, as defined by authorities having jurisdiction and as directed by Departmental Representative from site, prior to start of demolition Work, and dispose of at designated disposal facilities in safe manner in accordance with TDGA and other applicable regulatory requirements and Section 02 81 01.
 - .2 List of hazardous materials:
 - .1 Transformer oil.
 - .3 Drain and remove from site the transformers oil prior to return the transformers to the Owner. Ship the transformers to the location indicated by Departmental Representative at no cost.

PART 2 - PRODUCTS

2.1 EQUIPMENT

- .1 Leave machinery running only while in use, except where extreme temperatures prohibit shutting machinery down.

PART 3 - EXECUTION

3.1 PREPARATION

- .1 Inspect site with Departmental Representative and verify extent and location of items designated for removal, disposal, alternative disposal, recycling, salvage and items to remain.
- .2 Locate and protect utilities. Preserve active utilities traversing site in operating condition.
- .3 Notify and obtain approval of utility companies before starting demolition.
- .4 Disconnect high voltage power as per Burlington Hydro and Canadian Electrical Code requirements and as directed by Departmental Representative.
 - .1 Underground Storage Tanks: remove and dispose of in accordance with

3.2 REMOVAL OF HAZARDOUS WASTES

- .1 Remove contaminated or dangerous materials defined by authorities having jurisdiction, relating to environmental protection, from site and dispose of in safe manner to minimize danger at site or during disposal.

3.3 REMOVAL OPERATIONS

- .1 Remove items as indicated.
- .2 Do not disturb items designated to remain in place.
- .3 Removal of pavements, curbs and gutters:
 - .1 Square up adjacent surfaces to remain in place by saw cutting or other method approved by Departmental Representative.
 - .2 Protect adjacent joints and load transfer devices.
 - .3 Protect underlying and adjacent granular materials.
- .4 Prevent contamination with base course aggregates, when removing asphalt pavement for subsequent incorporation into hot mix asphalt concrete paving,
- .5 Disposal of Material:
 - .1 Dispose of materials not designated for salvage or reuse on site as instructed by Departmental Representative at authorized facilities approved in Waste Reduction Workplan.

3.4 REMOVAL FROM SITE

- .1 Remove stockpiled material as directed by Departmental Representative, when it interferes with operations of project.
- .2 Remove stockpiles of like materials by alternate disposal option once collection of materials is complete.
- .3 Transport material designated for alternate disposal using approved haulers, facilities, receiving organizations listed in Waste Reduction Workplan and in accordance with applicable regulations.
 - .1 Written authorization from Departmental Representative is required to deviate from haulers, facilities, receiving organizations listed in Waste Reduction Workplan.
- .4 Dispose of materials not designated for alternate disposal in accordance with applicable regulations.
 - .1 Disposal Facilities: approved and listed in Waste Reduction Workplan.
 - .2 Written authorization from Departmental Representative is required to deviate from disposal facilities listed in Waste Reduction Workplan.

3.5 RESTORATION

- .1 Restore areas and existing works outside areas of demolition to conditions that existed prior to beginning of Work and match condition of adjacent, undisturbed areas.
- .2 Use soil treatments and procedures which are not harmful to health, are not injurious to plants, and do not endanger wildlife, adjacent water courses or ground water.

3.6 FIELD QUALITY CONTROL

- .1 Verification requirements in accordance with Section 01 47 17, include:
 - .1 Materials and resources.
 - .2 Storage and collection of recyclables.
 - .3 Construction waste management.
 - .4 Resource reuse.
 - .5 Recycled content.
 - .6 Local/regional materials.
 - .7 Wood.
 - .8 Low-emitting materials.

3.7 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
 - .2 Remove debris, trim surfaces and leave work site clean, upon completion of Work
 - .3 Use cleaning solutions and procedures which are not harmful to health, are not injurious to plants, and do not endanger wildlife, adjacent water courses or ground water.

- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

3.8 PROTECTION

- .1 Repair damage to adjacent materials or property caused by selective site demolition.

PART 1 - GENERAL

1.1 RELATED REQUIREMENTS

- .1 Section 02 41 23 - Selective Site Demolition
- .2 Section 02 50 13 - Management of Toxic Waste
- .3 Section 02 81 01 - Hazardous Materials
- .4 Section 02 84 00 - Polychlorinate Biphenyl Remediation

1.2 REFERENCES

- .1 CSA International
 - .1 CSA S350-M1980(R2003), Code of Practice for Safety in Demolition of Structures.
- .2 Department of Justice Canada (Jus)
 - .1 Canadian Environmental Assessment Act (CEAA), 2012.
 - .2 Canadian Environmental Protection Act (CEPA), 2012.
 - .1 Transportation of Dangerous Goods Act (TDGA), 1992, c. 34.
 - .2 Hazardous Materials Information Review Act, 1985.
- .3 National Fire Protection Association (NFPA)
 - .1 NFPA 241 - 96, Standard for Safeguarding Construction, Alteration, and Demolition Operations.
- .4 National Research Council Canada (NRC)
 - .1 National Building Code of Canada 2015 (NBC).
 - .2 National Fire Code of Canada 2015 (NFC).
- .5 U.S. Environmental Protection Agency (EPA)/Office of Water
 - .1 EPA 832/R-92-005, Storm Water Management for Construction Activities: Developing Pollution Prevention Plans and Best Management Practices.

1.3 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Sections 01 33 00 and 01 74 20.
- .2 Submit demolition drawings:
 - .1 Submit for review and approval by Departmental Representative shoring and underpinning drawings stamped and signed by professional engineer registered or licensed in the Province of Ontario Canada, showing proposed method.

1.4 SITE CONDITIONS

- .1 Review "Designated Substance Report" and take precautions to protect environment.
- .2 If material resembling spray or trowel-applied asbestos or other designated substance listed as hazardous be encountered, stop work, take preventative measures, and notify Departmental Representative immediately.
 - .1 Proceed only after receipt of written instructions have been received from Departmental Representative.
- .3 Notify Departmental Representative before disrupting [building] access or services.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not used.

PART 3 - EXECUTION

3.1 EXAMINATION

- .1 Inspect building and site with Departmental Representative and verify extent and location of items designated for removal, disposal, alternative disposal, recycling, salvage and items to remain.
- .2 Locate and protect utilities. Preserve active utilities traversing site in operating condition.
- .3 Notify and obtain approval of utility companies before starting demolition.
- .4 Disconnect, cap, plug or divert, as required, existing public utilities within the property where they interfere with the execution of the work, in conformity with the requirements of the authorities having jurisdiction. Mark the location of these and previously capped or plugged services on the site and indicate location (horizontal and vertical) on the record drawings. Support, shore up and maintain pipes and conduits encountered.
 - .1 Immediately notify Departmental Representative and utility company concerned in case of damage to any utility or service, designated to remain in place.
 - .2 Immediately notify the Departmental Representative should uncharted utility or service be encountered, and await instruction in writing regarding remedial action.

3.2 PROTECTION

- .1 Prevent movement, settlement, or damage to adjacent structures, utilities, and parts of building to remain in place. Provide bracing and shoring required.

- .2 Keep noise, dust, and inconvenience to occupants to minimum.
- .3 Protect building systems, services and equipment.
- .4 Provide temporary dust screens, covers, railings, supports and other protection as required.

3.3 PREPARATION

- .1 Protection of In-Place Conditions:
 - .1 Prevent movement, settlement, or damage to adjacent structures, utilities, and parts of building to remain in place. Provide bracing and shoring required.
 - .2 Keep noise, dust, and inconvenience to occupants to minimum.
 - .3 Protect building systems, services and equipment.
 - .4 Provide temporary dust screens, covers, railings, supports and other protection as required.
 - .5 Do Work in accordance with Section 01 35 29.
- .2 Demolition/Removal:
 - .1 Remove items as indicated.
 - .2 Removal of Pavements, Curbs and Gutters:
 - .1 Square up adjacent surfaces to remain in place by saw cutting or other method approved by Departmental Representative.
 - .2 Protect adjacent joints and load transfer devices.
 - .3 Protect underlying and adjacent granular materials.
 - .3 Remove parts of existing [building] to permit new construction.
 - .4 Trim edges of partially demolished building elements to tolerances as defined by Departmental Representative to suit future use.

3.4 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .3 Refer to demolition drawings and specifications for items to be salvaged for reuse.
- .4 Waste Management: separate waste materials for reuse and recycling in accordance with Sections 01 74 20 and 01 35 21.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

PART 1 - GENERAL

1.1 REFERENCES

- .1 Canadian Environmental Protection Act, 1999 (CEPA 1999).
- .2 Health Canada/Workplace Hazardous Materials Information System (WHMIS)
 - .1 Material Safety Data Sheets (MSDS).
- .3 National Fire Code of Canada, 2015.
- .4 Transportation of Dangerous Goods Act (TDGA), 1999 c. 34.
- .5 Transportation of Dangerous Goods Regulations (TDGR), T-19.01-SOR/2003-400.
- .6 Storage of PCB Material Regulations, SOR/92-507.
- .7 PCB Waste Export Regulations, 1996, SOR/97-109.

1.2 DEFINITIONS

- .1 Toxic: substance is considered toxic if it is listed on Toxic Substances List found in Schedule 1 of CEPA.
- .2 List of Toxic Substances: found in Schedule 1 of CEPA, lists substances that have been assessed as toxic. Federal Government can make regulations with respect to a substance specified on List of Toxic Substances. Column II of this list identifies type of regulation applicable to each substance.
- .3 PCBs: includes chlorobiphenyls referred to in Column I of item 1 of the List of Toxic Substances in Schedule I of Canadian Environmental Protection Act.

1.3 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Submit WHMIS MSDS - Material Safety Data Sheets.
 - .2 Submit photocopy of shipping documents and waste manifests and export notices to Departmental Representative when shipping toxic wastes off site.
 - .3 Maintain 1 copy of product data in readily accessible file on site.

1.4 DELIVERY, STORAGE, AND HANDLING

- .1 Store and handle toxic wastes in accordance with applicable federal and provincial laws, regulations, codes, and guidelines.
- .2 Store and handle flammable and combustible wastes in accordance with current National Fire Code of Canada requirements.

- .3 Co-ordinate storage of toxic wastes with Departmental Representative and follow internal requirements for labelling and storage of wastes.
- .4 Observe smoking regulations, smoking is prohibited in area where toxic wastes are stored, used, or handled.
- .5 Report spills or accidents involving toxic wastes immediately to Departmental Representative and to appropriate regulatory authorities. Take reasonable measures to contain the release while ensuring health and safety is protected.
- .6 Transport toxic wastes in accordance with federal Transportation of Dangerous Goods Act, Transportation of Dangerous Goods Regulations, and applicable provincial regulations.
- .7 Use authorized/licensed carrier to transport toxic waste.
- .8 Co-ordinate transportation and disposal of toxic wastes with Departmental Representative.
- .9 Dispose of toxic wastes generated on site in accordance with applicable federal and provincial acts, regulations, and guidelines.
- .10 Ensure toxic waste is shipped to authorized/licensed treatment or disposal facility and that liability insurance requirements are met.
- .11 Minimize generation of toxic waste to maximum extent practicable. Take necessary precautions to avoid mixing clean and contaminated wastes.
- .12 Identify and evaluate recycling and reclamation options as alternatives to land disposal in compliance with LEED credit MR 2, such as:
 - .1 Hazardous wastes recycled in manner constituting disposal.
 - .2 Hazardous waste burned for energy recovery.
 - .3 Lead-acid battery recycling.
 - .4 Hazardous wastes with economically recoverable precious metals.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.

PART 1 - GENERAL

1.1 REFERENCES

- .1 Definitions:
 - .1 Dangerous Goods: product, substance, or organism specifically listed or meets hazard criteria established in Transportation of Dangerous Goods Regulations.
 - .2 Hazardous Material: product, substance, or organism used for its original purpose; and is either dangerous goods or material that will cause adverse impact to environment or adversely affect health of persons, animals, or plant life when released into the environment.
 - .3 Hazardous Waste: hazardous material no longer used for its original purpose and that is intended for recycling, treatment or disposal.
- .2 Reference Standards:
 - .1 Canadian Environmental Protection Act, 1999 (CEPA 1999)
 - .1 Export and Import of Hazardous Waste and Hazardous Recyclable Material Regulations (SOR/2005-149).
 - .2 Department of Justice Canada (Jus)
 - .1 Transportation of Dangerous Goods Act, 1992 (TDG Act) 1992, (c. 34).
 - .2 Transportation of Dangerous Goods Regulations (T-19.01-SOR/2001-286).
 - .3 Green Seal Environmental Standards (GS)
 - .1 GS-11-2008, 2nd Edition, Paints and Coatings.
 - .2 GS-36-00, Commercial Adhesives.
 - .4 Health Canada / Workplace Hazardous Materials Information System (WHMIS)
 - .1 Material Safety Data Sheets (MSDS).
 - .5 National Research Council Canada Institute for Research in Construction (NRC-IRC)
 - .1 National Fire Code of Canada 2015.
- .3 South Coast Air Quality Management District (SCAQMD), California State, Regulation XI. Source Specific Standards
 - .1 SCAQMD Rule 1113-A2007, Architectural Coatings.
 - .2 SCAQMD Rule 1168-A2005, Adhesive and Sealant Applications.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for hazardous materials and include product characteristics, performance criteria, physical size, finish and limitations.
 - .2 Submit two copies of WHMIS MSDS in accordance with Sections 01 35 29 and 01 35 43 to Departmental Representative for each hazardous material required prior to bringing hazardous material on site.

- .3 Submit hazardous materials management plan to Departmental Representative that identifies hazardous materials, usage, location, personal protective equipment requirements, and disposal arrangements.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Transport hazardous materials and wastes in accordance with Transportation of Dangerous Goods Act, Transportation of Dangerous Goods Regulations, and applicable provincial regulations.
- .4 Storage and Handling Requirements:
 - .1 Co-ordinate storage of hazardous materials with Departmental Representative and abide by internal requirements for labelling and storage of materials and wastes.
 - .2 Store and handle hazardous materials and wastes in accordance with applicable federal and provincial laws, regulations, codes, and guidelines.
 - .3 Store and handle flammable and combustible materials in accordance with National Fire Code of Canada requirements.
 - .4 Keep no more than 45 litres of flammable and combustible liquids such as gasoline, kerosene and naphtha for ready use.
 - .1 Store flammable and combustible liquids in approved safety cans bearing the Underwriters' Laboratory of Canada or Factory Mutual seal of approval.
 - .2 Storage of quantities of flammable and combustible liquids exceeding 45 litres for work purposes requires the written approval of the Departmental Representative.
 - .5 Transfer of flammable and combustible liquids is prohibited within buildings.
 - .6 Transfer flammable and combustible liquids away from open flames or heat-producing devices.
 - .7 Solvents or cleaning agents must be non-flammable or have flash point above 38 degrees C.
 - .8 Store flammable and combustible waste liquids for disposal in approved containers located in safe, ventilated area. Keep quantities to minimum.
 - .9 Observe smoking regulations, smoking is prohibited in areas where hazardous materials are stored, used, or handled.
 - .10 Storage requirements for quantities of hazardous materials and wastes in excess of 5 kg for solids, and 5 litres for liquids:
 - .1 Store hazardous materials and wastes in closed and sealed containers.
 - .2 Label containers of hazardous materials and wastes in accordance with WHMIS.
 - .3 Store hazardous materials and wastes in containers compatible with that material or waste.

- .4 Segregate incompatible materials and wastes.
 - .5 Ensure that different hazardous materials or hazardous wastes are stored in separate containers.
 - .6 Store hazardous materials and wastes in secure storage area with controlled access.
 - .7 Maintain clear egress from storage area.
 - .8 Store hazardous materials and wastes in location that will prevent them from spilling into environment.
 - .9 Have appropriate emergency spill response equipment available near storage area, including personal protective equipment.
 - .10 Maintain inventory of hazardous materials and wastes, including product name, quantity, and date when storage began.
 - .11 Ensure personnel have been trained in accordance with Workplace Hazardous Materials Information System (WHMIS) requirements.
 - .12 Report spills or accidents immediately to Departmental Representative. Submit a written spill report to Departmental Representative within 24 hours of incident.
- .5 Packaging Waste Management: remove for reuse and return by manufacturer of pallets, crates, padding, and packaging materials as specified in accordance with Section 01 74 20.

PART 2 - PRODUCTS

2.1 MATERIALS

- .1 Description:
 - .1 Bring on site only quantities hazardous material required to perform Work.
 - .2 Maintain MSDS in proximity to where materials are being used. Communicate this location to personnel who may have contact with hazardous materials.
 - .3 Sustainability Characteristics:
 - .1 Adhesives and Sealants in accordance with Section 07 92 00 and 01 35 21.
 - .1 Adhesives and Sealants: maximum VOC limit to SCAQMD Rule 1168 and to GS-36.
 - .2 Primers, Paints, Coatings in accordance with manufacturer's recommendations for surface conditions and Section 09 91 23, 09 91 23.01 and 01 35 21].
 - .1 Primer: maximum VOC limit 250 g/L to GS-11 and to SCAQMD Rule 1113.
 - .2 Paints: maximum VOC limit 50 g/L to GS-11 and to SCAQMD Rule 1113.
 - .3 Coatings: maximum VOC limit to SCAQMD Rule 1113.

PART 3 - EXECUTION

3.1 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.

- .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20 and 01 35 21.
 - .1 Dispose of hazardous waste materials in accordance with applicable federal and provincial acts, regulations, and guidelines.
 - .2 Recycle hazardous wastes for which there is approved, cost effective recycling process available.
 - .3 Send hazardous wastes to authorized hazardous waste disposal or treatment facilities.
 - .4 Burning, diluting, or mixing hazardous wastes for purpose of disposal is prohibited.
 - .5 Disposal of hazardous materials in waterways, storm or sanitary sewers, or in municipal solid waste landfills is prohibited.
 - .6 Dispose of hazardous wastes in timely fashion in accordance with applicable provincial regulations.
 - .7 Minimize generation of hazardous waste to maximum extent practicable. Take necessary precautions to avoid mixing clean and contaminated wastes.
 - .8 Identify and evaluate recycling and reclamation options as alternatives to land disposal, such as:
 - .1 Hazardous wastes recycled in manner constituting disposal.
 - .2 Hazardous waste burned for energy recovery.
 - .3 Lead-acid battery recycling.
 - .4 Hazardous wastes with economically recoverable precious metals.

PART 1 - GENERAL

1.1 SECTION INCLUDES

- .1 Procedures and materials required for the safe handling, management and storage of polychlorinated biphenyl (PCB) material.

1.2 REFERENCES

- .1 American Board of Industrial Hygiene (ABIH)
- .2 Canadian Council of Ministers of the Environment (CCME)
 - .1 PN1205-1995, PCB Transformer Decontamination: Standards and Protocols.
- .3 Department of Justice Canada (Jus)/CEPA SOR/92-507-SOR/2000-102, Storage of PCB Material Regulations
 - .1 Canadian Environmental Protection Act, 1999 (CEPA).
- .4 Environment Canada
 - .1 Manual for Spills of Hazardous Materials-1985.
- .5 Saskatchewan: Consolidated Statutes of Saskatchewan/Environmental Management and Protection Act 2002
 - .1 The PCB Waste Storage Regulations 21/89, R.R.S., c. E-10.2.
- .6 Transport Canada (TC)
 - .1 Transportation of Dangerous Goods Act, 1992 (TDGA).
- .7 Chlorobiphenyls Regulations (SOR/91-152; Amended SOR/2000-102)
 - .1 Regulations Respecting Mobile System for the Destruction and Treatment of Chlorobiphenyls that are Operated by or Under Contract with Federal Institutions (SOR/90-5; amended SOR/93-231 and SOR/2000-105).
 - .2 Regulations Respecting the Storage of Material Containing Chlorobiphenyls (PCBs) SOR/92-507, Amended SOR/2000-102).
 - .3 Regulations Respecting the Import and Export of Hazardous Wastes (SOR/92-637; Amended 94-459; SOR 94-684; SOR/2000-103).
 - .4 Waste Management - PCBs, R.R.O. Regulation 362/90.
 - .5 Mobile PCB Destruction Facilities, R.R.O. Regulation 352/90.
 - .6 Regulation 347, General Waste Management, as Amended.

1.3 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.
- .2 Prior to starting work, Contractor performing work of this section to provide:
 - .1 Workplace Safety and Insurance Board Clearance Certificate.
 - .2 Insurance certificates.
 - .3 Company Health and Safety Policy.
 - .4 Certificate of Approval for Transportation of PCB Waste and Location

- of Destruction Facility.
- .5 WHMIS Training Certificates for Personnel.
- .6 Material Safety Data Sheets for chemicals or material to be used.
- .3 Submittals to Local Fire Department and Departmental Representative.
 - .1 2 copies of books and records listed under Record Keeping of Control Submittals Article in PART 1 of this Section.
- .4 Waste location and description including:
 - .1 Building in which PCB waste is stored.
 - .2 Size of property used for storage site.
 - .3 Precise location of PCB waste at storage site.
 - .4 Container storage method used.
 - .5 Spill containment features in place at storage site.
 - .6 Security measures in place at storage site.
 - .7 Fire detection systems in place at storage site.

1.4 CONTROL SUBMITTALS

- .1 Co-ordinate procedural requirements with Section 01 45 00.
- .2 Record keeping: maintain and make available for review by environmental officer and Departmental Representative.
 - .1 Receipt of waste showing:
 - .1 Date of receipt of waste.
 - .2 Description of PCB waste including nameplate description, serial number, PCB registration number and quantity.
 - .3 Condition of PCB waste.
 - .4 Source of PCB waste.
 - .5 Name of carrier of PCB waste.
 - .6 Name of individual who accepted receipt of PCB waste.
 - .2 Removal of waste showing:
 - .1 Date of removal of PCB waste.
 - .2 Description of PCB waste including nameplate description, serial number, PCB registration number and quantity.
 - .3 Condition of PCB waste.
 - .4 Name of carrier of PCB waste.
 - .5 Destination of PCB waste.
 - .6 Name of individual authorizing transport of PCB waste.
 - .3 Monthly inspection, repair and replacement reports.
 - .4 Submit records to Departmental Representative as requested.

1.5 QUALITY ASSURANCE

- .1 Co-ordinate with Section 01 45 00.
- .2 Instruct personnel on dangers of PCB exposure, respirator use, decontamination and applicable Federal, Provincial/Territorial and Municipal Regulations.
- .3 Obtain services of industrial hygienist certified by American Board of Industrial Hygiene to certify training, review and approve PCB removal plan, including determination of need for personnel protective equipment (PPE)

in performing PCB removal work.

- .4 Complete work so that at no time do PCB's contaminate to the building, site and environment.

1.6 SUPERVISION

- .1 Provide on site, a supervisor, with authority to oversee health and safety, remediation methods, scheduling, labour and equipment requirements.
- .2 One supervisor for every 10 workers is required.

1.7 DELIVERY, STORAGE AND HANDLING

- .1 Place materials defined as hazardous or toxic in designated containers.
- .2 Handle and dispose of hazardous materials in accordance with the CEPA, TDGA, Regional and Municipal regulations.
- .3 Owners or operators of storage sites.
 - .1 Provide method for determining concentration of PCBs in particular waste at request of environment officer or inspector or Departmental Representative.
 - .2 Ensure personnel are familiar with and understand current PCB waste management procedures and use of personal protection equipment and clean-up techniques.
- .4 Disposal of PCB waste generated by removal activities must comply with Federal, Provincial, Territorial and Municipal regulations.
 - .1 Dispose of PCB waste in leak proof drums.
 - .2 Containers must be labelled with appropriate warning labels.
- .5 Create manifests describing and listing waste created and transport containers by approved means to licenced facility for storage.
 - .1 For each bulk load of PCBs: identity PCB waste, earliest date of removal from service for disposal, and weight in kilograms of the PCB waste.
 - .2 For each PCB Article Container or PCB Container: unique identifying number, type of PCB waste (i.e., soil, debris, small capacitors), earliest date of removal from service for disposal, and weight in kilograms of PCB waste contained.
 - .3 For each PCB Article not in PCB Container or PCB Article Container: serial number if available, or other identification if there is no serial number, date of removal from service for disposal, and weight in kilograms of PCB waste in each PCB Article.

PART 2 - PRODUCTS

2.1 STORAGE GENERAL

- .1 Storage of PCB materials in accordance with CEPA SOR/92-507 and Authority having jurisdiction.

2.2 STORAGE ENCLOSURE

- .1 Isolate PCB control area by physical boundaries to prevent unauthorized entry of personnel.
- .2 Food, drink and smoking materials are not permitted in areas where PCBs are handled or PCB items are stored.
- .3 Room, building or structure with lockable entrance.
- .4 Temporary storage facility to be a fully enclosed block wall room within building with appropriate warning signs.
- .5 Woven mesh wire fence or other fence with similar characteristics at least 2.5 metres high, with lockable entrance.
- .6 Smoking is not permitted within 15 m of PCB control area.
 - .1 Provide and post "No Smoking" signs as directed by Departmental Representative.

2.3 STORAGE CONTAINERS

- .1 Exterior containers:
 - .1 Structurally-sound and weather-sealed to hold PCB solids, PCB light ballasts, drained PCB containers or drained PCB equipment.
- .2 PCB solid or liquid storage.
 - .1 Drums and containers:
 - .1 Designed with sufficient durability and strength to prevent PCB solids or liquids from being released into environment, affected by weather, or contaminated by external sources.
 - .2 Steel or other material approved by Departmental Representative.
 - .2 Drums:
 - .1 Capacity no greater than 205 litres.
 - .2 Steel of minimum [1.2 mm for solids and 1.52 mm for liquids.
 - .3 Ensure removable steel lid securely attached and complete with PCB-resistant gasket for solids and closed-head double-bung steel drum.
 - .4 Paint or treat interior and exterior to prevent rusting.
 - .3 Drum Liners:
 - .1 0.15 mm thick clear polyethylene bag, 914 mm x 1524 mm, with opening at 914 mm end.

2.4 FLOORING AND ACCESSORIES

- .1 Constructed of steel, concrete, other material as approved by Departmental Representative.
- .2 Curbing, sufficient siding to contain at least twice volume of PCB liquid contained in largest item of PCB equipment on site or 25 percent of volume of PCB liquid on site, whichever is greater.

- .3 PCB Absorbing Surfaces:
 - .1 Floor, curbing, siding, sealed with durable PCB-resistant coating.
- .4 Floor Opening, Floor Drains and Sumps:
 - .1 Closed and sealed to prevent escape of liquid.

2.5 EMERGENCY RESPONSE EQUIPMENT AND SYSTEMS

- .1 Storage site clean-up materials:
 - .1 Ensure availability at all time of sorbent or solvents, for clean-up of liquid or solids.
 - .2 Ensure availability at all times of inert absorbent in sufficient quantity to contain minor leakage.
 - .1 Place in bottom of each container holding PCB equipment or fluorescent lighting ballasts.
- .2 Respirators: Certified by the National Institute of Occupational Safety and Health (NIOSH) or other testing agency acceptable to the Ministry of Labour.
 - .1 Use approved full-face organic vapour cartridge respirator for exposure to hot PCB.
 - .2 Vapour concentration less than or equal to 5 mg/m³.
 - .1 Supplied-air respirator with full face piece, helmet or hood.
 - .2 Self-contained breathing apparatus with full face piece.
 - .3 Vapour concentration greater than 5 mg/m³ or unknown concentrations.
 - .1 Self-contained breathing apparatus with full face piece operated in positive pressure mode.
 - .2 Type C supplied-air respirator with full face piece operated in positive pressure of continuous flow mode and auxiliary self-contained breathing apparatus operated in positive pressure mode.

2.6 WARNING SIGNS AND LABELS

- .1 Label electrical transformers, electromagnets and other equipment containing chlorobiphenyls in concentration exceeding 1% with black and white, serialized, "ATTENTION PCB" label, measuring 150 x 150 mm, as approved by Departmental Representative in accordance with Manual of Spills of Hazardous Materials.
- .2 Label equipment and containers of equipment containing chlorobiphenyls in concentration exceeding 50 parts per million by weight but not greater than 1% with non-serialized, Warning Label for PCB-Contaminated Equipment measuring 150 x 150 mm, as approved by Departmental Representative in accordance with Manual of Spills of Hazardous Materials.
- .3 Label containers of equipment, and drained containers containing chlorobiphenyls in concentration exceeding 1% with non-serialized, black and white, "ATTENTION PCB" label, measuring 150 x 150 mm, as approved by Departmental Representative in accordance with Manual of Spills of Hazardous Materials.
- .4 Label containers of PCB material and drained containers of PCB material

with chlorobiphenyl concentration exceeding 50 parts per million by weight with non-serialized, Warning Label for PCB-Contaminated Equipment, measuring 150 x 150 mm as approved by Departmental Representative in accordance with Manual of Spills of Hazardous Materials.

- .5 Label doors to storage sites, fencing and other security barriers enclosing storage sites with non-serialized, black and white, "ATTENTION PCB" label, measuring 150 x 150 mm or as approved by Departmental Representative in accordance with Manual of Spills of Hazardous Materials.
- .6 Maintain signs and labels in clear and legible condition.

PART 3 - EXECUTION

3.1 GENERAL

- .1 Do construction occupational health and safety in accordance with Section 01 35 29.
- .2 Store PCB waste materials to CEPA SOR/92-507.
- .3 Select PCB removal procedure to minimize contamination of work areas with PCB or other PCB-contaminated debris/waste. Handle PCBs such that no skin contact occurs.
- .4 As feasible, do not carry out PCB handling operations in confined spaces. Confined space means space having limited means of egress and inadequate cross ventilation.
- .5 Ensure that work operations or processes involving PCB or PCB-contaminated materials are conducted in accordance with Federal, Provincial/Territorial and Municipal Regulations and applicable requirements of this Section, including but not limited to:
 - .1 Obtaining advance approval of PCB storage sites.
 - .2 Notify Departmental Representative prior to beginning operations.
 - .3 Report leaks and spills to Departmental Representative.
 - .4 Maintain access log of employees working in PCB control area and provide copy to Departmental Representative upon completion of operations.
 - .5 Inspect PCB and PCB-contaminated items and waste containers for leaks and forward copies of inspection reports to Departmental Representative.
 - .6 Maintain spill kit for emergency spills entitled "PCB Spill Kit".
 - .7 Maintain inspection, inventory and spill records.

3.2 ACCESS TO STORAGE SITE

- .1 Keep entrance to site locked or guarded.
- .2 Maintain register at site containing name, address, telephone number and place of business of each person who enters, or is authorized to enter site.
- .3 Permit only authorized personnel to enter site.

3.3 ACCESS TO STORED MATERIAL

- .1 Store materials and equipment to permit easy access for inspection.

3.4 STORAGE PRACTICES

- .1 Stack containers only if designed for stacking.
- .2 Stack liquid containers or drums no higher than 2 containers.
- .3 Separate stacked drums from each other with pallets.
- .4 Store material to prevent it catching fire.
- .5 Store material to prevent it being released.
- .6 Store PCB material together, and away from other stored materials.
- .7 Exterior:
 - .1 Cover PCB liquid containers with waterproof roof or cover extending beyond curbing or sides of container.
 - .2 Elevate PCB waste containers and PCB equipment on pallets or other suitable devices to reduce corrosion.
 - .3 Store transformers on skids.
- .8 Interior:
 - .1 Place on skids or pallets PCB equipment and containers of PCB material not permanently secured to floor or surface.

3.5 HANDLING TRANSFORMERS

- .1 Decontamination of stored waste PCB transformers:
 - .1 Drain dielectric fluid at installation location.
 - .2 Send fluid to approved incinerator for destruction.
 - .3 Drain transformer, switches, and regulators of free flowing liquid prior to transportation. Place drained liquids in DOT certified drums. Drums to contain not more than 190 L of oil.
 - .4 Transport transformer carcass to decontamination facility.
- .2 Re-use of transformers:
 - .1 Dielectric fluid concentration:
 - .1 Mineral oil transformers:
 - .1 Decontaminate by retrofilling, on-line chemical treatment.
 - .2 PCB fluid concentration no greater than 50 ppm verified by 90-day test.
 - .2 Askarel transformers:
 - .1 Decontaminate by series retrofilling, in-situ processing.
 - .2 PCB fluid concentration no greater than 50 ppm verified by 90-day test.
 - .3 PCB fluid concentration no greater than 50 ppm verified

on an annual basis for three years after completion of decontamination process.

- .4 Silicone as final dielectric fluid:
 - .1 PCB fluid concentration no greater than 50 ppm verified for ten years at five year intervals.
- .5 Porous materials:
 - .1 Considered PCB waste unless shown otherwise.
 - .2 destroyed by methods approved for PCB waste.

- .3 Recycling of Transformers:
 - .1 Dielectric fluid concentration.
 - .2 Return the transformers without oil to Owner. Ship transformers to the location indicated by Departmental representative at no cost.
 - .1 PCB fluid concentration no greater than 50 ppm verified by 90-day test in accordance with The PCB Waste Storage Regulations 21/89.
 - .2 Surface contamination:
 - .1 Solvent cleaned:
 - .1 10 ug/100 cm².
 - .2 Shredded and incinerated:
 - .1 Less than 0.5 ppm by weight.
- .4 Landfilling of Transformers:
 - .1 PCB fluid concentration no greater than 50 ppm before draining.

3.6 HANDLING LIQUID CHLOROBIPHENYL (54% CHLORINE)

- .1 Use impervious clothing (nitrile), gloves, face shields 200 mm minimum and other appropriate protective clothing necessary to prevent skin contact. Do not use natural rubber, neoprene, or polyvinyl chloride (PVC).
- .2 Place contaminated clothing in closed containers for storage. Dispose of contaminated clothing in same manner as PCBs.
- .3 Ensure that contaminated non-pervious clothing is removed promptly and not reworn until cleaned.
- .4 Wear splash-proof safety goggles where liquid chlorobiphenyl (54% chlorine) may contact eyes.

3.7 EMERGENCY RESPONSES

- .1 General:
 - .1 Immediately report to Departmental Representative PCB spills on ground or in water, PCB spills in drip pans, or PCB leaks.
 - .2 Rope off area around edges of PCB leak or spill and post "PCB Spill Authorized Personnel Only" caution sign. Immediately transfer leaking items to drip pan or other container.
 - .3 Initiate cleanup of spills as soon as possible, but no later than 48 hours of its discovery. If misting, elevated temperatures or open flames are present, or if spill is situated in confined space, notify Departmental Representative. Mop up liquid with rags or other conventional absorbent. Properly contained and dispose of spent

- absorbent as solid PCB waste.
- .4 Workers to evacuate site. When leaving, shut down water in use. Only personnel trained in use of, and wearing SCUBA apparatus, will be allowed to re-enter site.
- .5 Do not return to site until Owner's representative and Ministry of the Environment representatives have declared the area safe for re-entry.
- .2 Spill, leak, and disposal procedures:
 - .1 Permit access to only those wearing protective equipment and clothing.
 - .2 Issue poison warnings.
 - .3 Call local fire department or PCB Emergency Response Team.
 - .4 Avoid contact and inhalation.
 - .5 Remove ignition sources.
 - .6 Ventilate areas of spill or leak.
 - .7 Stop or reduce discharge if possible without risk.
 - .8 Collect spilled material for reclamation.
 - .9 Do not flush to sewer.
 - .10 Use only inert sawdust, vermiculite, dry sand and earth absorbents as approved by Departmental Representative.
 - .11 Wipe contaminated area with rags and kerosene, fuel oil and 1,1,1-trichloroethane chloroethene VG solvent). Do not use acetone or toluene.
 - .12 Notify environmental authorities to determine disposal and clean-up procedures.
- .3 Fire protection and emergency procedures plan for storage sites.
 - .1 Ensure most recent revision of plan is in effect.
 - .2 Develop plan in consultation with local fire department.
 - .3 Ensure employees authorized to enter PCB storage site are familiar with contents of fire protection and emergency procedures plan.
 - .4 Send one copy to local fire department.
 - .5 Display one copy at storage site in area accessible in fire or spill situation.
 - .6 Display one copy at storage site owner's place of business.
- .4 Respirators:
 - .1 Use when chlorobiphenyl concentrations are above permissible exposure levels.
 - .2 Use when entering tanks or closed vessels.
 - .3 Use in emergency situations.
- .5 Permissible exposure limit.
 - .1 0.5 milligram of chlorobiphenyl (54% chlorine) per cubic metre of air, averaged over 8 hours, 1.0 microgram of chlorobiphenyl (54% chlorine) per cubic metre of air up to 10 hours/day.
- .6 Fire protection:
 - .1 Wear totally encapsulated suit and self-contained breathing apparatus with full face piece operated in positive pressure mode

3.8 SANITATION

- .1 Promptly wash liquid-contaminated skin with soap or mild detergent and water.
- .2 Prohibit eating and smoking in areas where liquid chlorobiphenyl (54% chlorine) is handled, processed or stored.
- .3 Wash hands thoroughly with soap or mild detergent and water after handling liquid chlorobiphenyl (54% chlorine).

3.10 FIELD QUALITY CONTROL

- .1 Owners or Operators of Storage Sites:
 - .1 At request of inspector, measure concentration of PCBs in accordance with CEPA SOR/92-507 - Storage of PCB Material Regulations.
 - .2 Inspect storage site monthly and repair or replace, if necessary, PCB equipment, floors, drains, drainage systems, waterproof roofs or barriers, fire prevention apparatus, personnel protection equipment, security fences and materials used for clean-up at site.
 - .3 Immediately repair or replace drum, container or equipment found to be leaking PCBs.
 - .4 Immediately clean up contaminated area.
 - .5 Ensure controlled access to storage site to prevent entry by unauthorized persons.

PART 1 - GENERAL

1.1 REFERENCES

- .1 Health Canada/Workplace Hazardous Materials Information System (WHMIS)
 - .1 Material Safety Data Sheets (MSDS).
- .2 Underwriter's Laboratories of Canada (ULC)
 - .1 CAN/ULC-S101-14, Standard Methods of for Fire Endurance Tests of Building Construction and Materials.
 - .2 CAN/ULC-S102-10, Standard Method of Test for Surface Burning Characteristics of Building Materials and Assemblies.
 - .3 CAN/ULC-S115-11, Standard Method of Fire Tests of Firestop Systems.

1.2 DEFINITIONS

- .1 Fire Stop Material: device intended to close off opening or penetration during fire or materials that fill openings in wall or floor assembly where penetration is by cables, cable trays, conduits, ducts and pipes and poke-through termination devices, including electrical outlet boxes along with their means of support through wall or floor openings.
- .2 Single Component Fire Stop System: fire stop material that has Listed Systems Design and is used individually without use of high temperature insulation or other materials to create fire stop system.
- .3 Multiple Component Fire Stop System: exact group of fire stop materials that are identified within Listed Systems Design to create on site fire stop system.
- .4 Continuity of Fire Separations: NBC 2015, Division B, Parts 3.1.8 and 3.1.9.1, 9.10.9):
 - .1 Wall, partition or floor assemblies required to be a fire separation shall be: constructed as a continuous element; have a fire resistance rating; have openings protected by a closure; and have penetrations sealed by a firestop.

1.3 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Submit manufacturer's printed product literature, specifications and datasheet and include product characteristics, performance criteria, physical size, finish and limitations.
 - .2 Submit two copies of WHMIS MSDS - Material Safety Data Sheets in accordance with Section 02 62 00.01.
- .3 Shop Drawings:
 - .1 Submit shop drawings to show location, proposed material, reinforcement, anchorage, fastenings and method of installation.
 - .2 Construction details should accurately reflect actual job conditions.

- .4 Quality assurance submittals: submit following in accordance with Section 01 45 00.
 - .1 Test reports: in accordance with CAN/ULC-S101 for fire endurance and CAN/ULC-S102 for surface burning characteristics.
 - .1 Submit certified test reports from approved independent testing laboratories, indicating compliance of applied fire stopping with specifications for specified performance characteristics and physical properties.
 - .2 Certificates: submit certificates signed by manufacturer certifying that materials comply with specified performance characteristics and physical properties.
 - .3 Manufacturer's Instructions: submit manufacturer's installation instructions and special handling criteria, installation sequence, cleaning procedures.
 - .4 Manufacturer's Field Reports: submit to manufacturer's written reports within 3 days of review, verifying compliance of Work, as described in PART 3 - FIELD QUALITY CONTROL.

1.4 QUALITY ASSURANCE

- .1 Qualifications:
 - .1 Installer: company specializing in fire stopping installations with 5 years documented and approved by manufacturer.
 - .2 All fire stopping material shall be from one manufacturer.
 - .3 All fire stopping installation work for entire project shall be by a single contractor experienced in firestopping. Individual disciplines shall NOT fire stop their own work.
- .2 Pre-Installation Meetings: convene pre-installation meeting one week prior to beginning work of this Section, with contractor's representative and Departmental Representative in accordance with Section 01 32 16.06 and 01 32 16.07 to:
 - .1 Verify project requirements.
 - .2 Review installation and substrate conditions.
 - .3 Co-ordination with other building subtrades.
 - .4 Review manufacturer's installation instructions and warranty requirements.
- .3 Site Meetings: as part of Manufacturer's Services described in PART 3 - FIELD QUALITY CONTROL, schedule site visits, to review Work, at stages listed.
 - .1 After delivery and storage of products, and when preparatory Work is complete, but before installation begins.
 - .2 Twice during progress of Work at 25% and 60% complete.
 - .3 Upon completion of Work, after cleaning is carried out.

1.5 DELIVERY, STORAGE AND HANDLING

- .1 Packing, shipping, handling and unloading:
 - .1 Deliver, store and handle materials in accordance with Section 01 61 00.
 - .2 Deliver, store and handle materials in accordance with manufacturer's written instructions.
 - .3 Deliver materials to the site in undamaged condition and in original unopened containers, marked to indicate brand name, manufacturer, and ULC markings.
- .2 Storage and Protection:
 - .1 Store materials indoors, in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Replace defective or damaged materials with new.
- .3 Waste Management and Disposal:
 - .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 20.

PART 2 - PRODUCTS

2.1 SUSTAINABLE REQUIREMENTS

- .1 Materials and products in accordance with Section 01 47 15.
- .2 Do verification requirements in accordance with Section 01 47 17.

2.2 MATERIALS

- .1 Fire stopping and smoke seal systems: in accordance with CAN/ULC-S115.
 - .1 Asbestos-free materials and systems capable of maintaining effective barrier against flame, smoke and gases in compliance with requirements of CAN/ULC-S115 and not to exceed opening sizes for which they are intended and conforming to specified special requirements described in PART 3.
 - .2 Fire stop system rating: F.
- .2 Service penetration assemblies: systems tested to CAN/ULC-S115.
- .3 Service penetration fire stop components: certified by test laboratory to CAN/ULC-S115.
- .4 Fire-resistance rating of installed fire stopping assembly in accordance with NBC.
- .5 Fire stopping and smoke seals at openings intended for ease of re-entry such as cables: elastomeric seal.
- .6 Fire stopping and smoke seals at openings around penetrations for pipes, ductwork and other mechanical items requiring sound and vibration control: elastomeric seal.

- .7 Primers: to manufacturer's recommendation for specific material, substrate, and end use.
- .8 Water (if applicable): potable, clean and free from injurious amounts of deleterious substances.
- .9 Damming and backup materials, supports and anchoring devices: to manufacturer's recommendations, and in accordance with tested assembly being installed as acceptable to authorities having jurisdiction.
- .10 Sealants for vertical joints: non-sagging.

PART 3 - EXECUTION

3.1 MANUFACTURER'S INSTRUCTIONS

- .1 Compliance: comply with manufacturer's written recommendations or specifications, including product technical bulletins, handling, storage and installation instructions, and datasheets.

3.2 PREPARATION

- .1 Examine sizes and conditions of voids to be filled to establish correct thicknesses and installation of materials.
 - .1 Ensure that substrates and surfaces are clean, dry and frost free.
- .2 Prepare surfaces in contact with fire stopping materials and smoke seals to manufacturer's instructions.
- .3 Maintain insulation around pipes and ducts penetrating fire separation without interruption to vapour barrier.
- .4 Mask where necessary to avoid spillage and over coating onto adjoining surfaces; remove stains on adjacent surfaces.

3.3 INSTALLATION

- .1 Install fire stopping and smoke seal material and components in accordance with manufacturer's certified tested system listing.
- .2 Seal holes or voids made by through penetrations, poke-through termination devices, and unpenetrated openings or joints to ensure continuity and integrity of fire separation are maintained.
- .3 Provide temporary forming as required and remove forming only after materials have gained sufficient strength and after initial curing.
- .4 Tool or trowel exposed surfaces to neat finish.
- .5 Remove excess compound promptly as work progresses and upon completion.

3.4 SEQUENCES OF OPERATION

- .1 Proceed with installation only when submittals have been reviewed by Departmental Representative.

3.5 FIELD QUALITY CONTROL

- .1 Inspections: notify Departmental Representative when ready for inspection and prior to concealing or enclosing fire stopping materials and service penetration assemblies.
- .2 Manufacturer's Field Services:
 - .1 Obtain written report from manufacturer verifying compliance of Work, in handling, installing, applying, protecting and cleaning of product and submit Manufacturer's Field Reports as described in PART 1 - SUBMITTALS.
 - .2 Provide manufacturer's field services consisting of product use recommendations and periodic site visits for inspection of product installation in accordance with manufacturer's instructions.
 - .3 Schedule site visits, to review Work, as directed in PART 1 - QUALITY ASSURANCE.

3.6 CLEANING

- .1 Proceed in accordance with Section 01 74 11.
- .2 On completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.
- .3 Remove temporary dams after initial set of fire stopping and smoke seal materials.

3.7 SCHEDULE

- .1 Fire stop and smoke seal at:
 - .1 Penetrations through fire-resistance rated masonry, concrete, and gypsum board partitions and walls.
 - .2 Edge of floor slabs at curtain wall and precast concrete panels.
 - .3 Top of fire-resistance rated masonry and gypsum board partitions.
 - .4 Intersection of fire-resistance rated masonry and gypsum board partitions.
 - .5 Control and sway joints in fire-resistance rated masonry and gypsum board partitions and walls.
 - .6 Penetrations through fire-resistance rated floor slabs, ceilings and roofs.
 - .7 Openings and sleeves installed for future use through fire separations.
 - .8 Around mechanical and electrical assemblies penetrating fire separations.
 - .9 Rigid ducts: greater than 129 cm²: fire stopping to consist of bead of fire stopping material between retaining angle and fire separation and between retaining angle and duct, on each side of fire separation.

PART 1 - GENERAL

1.1 General Requirements:

- .1 Provide field devices, expansion modules as required, control wiring, power wiring, conduit, hardware, and electrical work associated with three new transformers monitoring work.
- .2 Confirm exact location of building automation system (BAS) and new transformers which are to be monitored by BAS during bid stage.

1.2 DESCRIPTION OF SYSTEM

- .1 The building currently has a ESC Auto building automation system with front-end and abilities to access the database, programming, and system monitoring.

1.3 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Control Schematics
 - .2 BAS points list indicating the panel ID, panel location, hardware address, point acronym, point description, field device type, point type (i.e. AO/DO/AI/DI), end device fail position, end device manufacture and model number, and wire tag ID).
 - .3 Submit manufacturer's instructions, printed product literature and data sheets for electric and electronic control system for HVAC and include product characteristics, performance criteria, physical size, finish and limitations.

PART 2 - PRODUCTS

2.1 Additional Monitor Points

- .1 Add the following monitor points for the new transformers:
 - .1 T1 Transformer:
 - .1 Oil High Temperature Alarm, DI
 - .2 Oil Level Alarm, DI
 - .3 Rapid Rise Pressure Alarm, DI
 - .4 Gas Detection Alarm, DI
 - .5 Ground Fault Alarm, DI
 - .2 T2 Transformer:
 - .1 Oil High Temperature Alarm, DI
 - .2 Oil Level Alarm, DI
 - .3 Rapid Rise Pressure Alarm, DI
 - .4 Gas Detection Alarm, DI
 - .5 Ground Fault Alarm, DI
 - .3 T3 Transformer:
 - .1 Oil High Temperature Alarm, DI
 - .2 Oil Level Alarm, DI
 - .3 Rapid Rise Pressure Alarm, DI

.4 Gas Detection Alarm, DI

2.2 EXISTING BAS UPDATE

- .1 The BAS graphic interface software is existing. The graphic interface shall be updated to indicate each of the new transformer additional monitor points as described above.

2.3 APPROVED SYSTEM INTEGRATOR

- .1 ESC Automation
Contact: Albert Galit
e-Mail: agalit@escautomation.com
Address: 5525 Eglinton Ave W #100, Etobicoke, ON M9C 5K5

PART 3 - EXECUTION

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for electric and electronic control systems installation in accordance with manufacturer's written instructions.
- .2 Visually inspect substrate in presence of Departmental Representative.
- .3 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
- .4 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 POWER SOURCES AND WIRING METHODS

- .1 All wiring line and low voltage shall be installed in EMT conduit unless specifically specified otherwise.
- .2 Install EMT and cable at right angles to building lines, securely fastened, and in accordance with the standards set out in Division 26.
- .3 All exterior wiring line and low voltage from new transformers to the building will be through conduits as shown on Electrical Drawing E-02 SITE PLAN - NEW.

3.3 COMMISSIONING

- .1 The contractor shall be responsible for the "end to end" commissioning, testing, verification and start-up of the complete control system hardware and software.
- .2 Confirm and demonstrate to the Departmental Representative and Consultant that all systems are programmed and operating correctly.
- .3 At the completion of commissioning, provide the Commissioning Report

documenting all tests and include all documents, signed and dated by the Contractor's technician performing the tests. Submit one (1) electronic copy of Commissioning Report to the Departmental Representative.

3.4 AS-BUILT DOCUMENTATION MANUAL

- .1 The As-built documentation shall include the following An Information sheet that contains:
 - .1 Building Name and address.
 - .2 A brief description of the control details. i.e. total # of points, list of equipment controls and which panels they a connected to.
 - .3 Panel's information i.e. part numbers for panels used and there serial numbers and revision # (if applicable).
 - .4 Software version.
 - .6 Warrantly start date and duration.
 - .7 BAS Contractor Name, address, and Phone number.
- .2 BAS points list indicating the panel ID, panel location, hardware address, point acronym, point description, field device type, point type (i.e. AO/DO/AI/DI), end device fail position, end device manufacture and model number and wire tag ID.
- .3 Wiring diagrams including complete power system, interlocks, control and data communications.
- .4 Manufacturers' data/specification sheets and catalogue cuts for all material and equipment supplied including the workstation PC and any equipment (e.g. valves, starters, VFDs, etc.) supplied under the mechanical scope of work. This section shall include a summary sheet that indicates all BAS Device, Manufacturers', model number, and quantity of each used on this job.
- .5 Provide a CD with each manual to include all of the As Built Documentation contained within the manual (fixture cuts, operating/maintenance procedures, warranties, letters, graphics, points lists, programming, sequences etc.). This shall include As Built drawings in Autocad format.

PART 1 - GENERAL

1.1 REFERENCES

- .1 Definitions:
 - .1 Electrical and electronic terms: unless otherwise specified or indicated, terms used in these specifications, and on drawings, are those defined by IEEE SP1122.
- .2 Reference Standards:
 - .1 CSA Group
 - .1 CSA C22.1-18, Canadian Electrical Code, Part 1 (24th Edition), Safety Standard for Electrical Installations.
 - .2 CAN3-C235-83(R2015), Preferred Voltage Levels for AC Systems, 0 to 50,000 V.
 - .2 Institute of Electrical and Electronics (IEEE)/National Electrical Safety Code Product Line (NESC)

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for review and include product characteristics, performance criteria, physical size, finish and limitations.
- .3 Submit for review single line electrical diagrams under plexiglass in glazed frames and locate as indicated.
 - .1 Electrical distribution system in main electrical room.
 - .2 Electrical power generation and distribution systems in power plant rooms.
- .4 Shop drawings:
 - .1 Submit drawings stamped and signed by professional engineer registered or licensed in Province of Ontario, Canada.
 - .2 Submit wiring diagrams and installation details of equipment indicating proposed location, layout and arrangement, control panels, accessories, piping, ductwork, and other items that must be shown to ensure co-ordinated installation.
 - .3 Identify on wiring diagrams circuit terminals and indicate internal wiring for each item of equipment and interconnection between each item of equipment.
 - .4 Indicate of drawings clearances for operation, maintenance, and replacement of operating equipment devices.
 - .5 Submit three number of copies of 600 x 600 mm minimum size drawings and product data to authority having jurisdiction.
 - .6 If changes are required, notify Departmental Representative of these changes before they are made.

- .5 Certificates:
 - .1 Provide CSA certified equipment and material.
 - .2 Where CSA certified equipment and material is not available, submit such equipment and material to authority having jurisdiction for special approval before delivery to site.
 - .3 Submit test results of installed electrical systems and instrumentation.
 - .4 Permits and fees: in accordance with General Conditions of contract.
 - .5 Submit, upon completion of Work, load balance report as described in PART 3 - LOAD BALANCE.
 - .6 Submit certificate of acceptance from authority having jurisdiction upon completion of Work to Departmental Representative.

- .6 Manufacturer's Field Reports: submit to Departmental Representative manufacturer's written report, within 3 days of review, verifying compliance of Work and electrical system and instrumentation testing, as described in PART 3 - FIELD QUALITY CONTROL.

1.3 CLOSEOUT SUBMITTALS

- .1 Submit in accordance with Section 01 78 00.

- .2 Operation and Maintenance Data: submit operation and maintenance data for review.
 - .1 Provide for each system and principal item of equipment as specified in technical sections for use by operation and maintenance personnel.
 - .2 Operating instructions to include following:
 - .1 Wiring diagrams, control diagrams, and control sequence for each principal system and item of equipment.
 - .2 Start up, proper adjustment, operating, lubrication, and shutdown procedures.
 - .3 Safety precautions.
 - .4 Procedures to be followed in event of equipment failure.
 - .5 Other items of instruction as recommended by manufacturer of each system or item of equipment.
 - .3 Print or engrave operating instructions and frame under glass or in approved laminated plastic.
 - .4 Post instructions where directed.
 - .5 For operating instructions exposed to weather, provide weather-resistant materials or weatherproof enclosures.
 - .6 Ensure operating instructions will not fade when exposed to sunlight and are secured to prevent easy removal or peeling.

1.4 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 and with manufacturer's written instructions.

- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.

- .3 Storage and Handling Requirements:
 - .1 Store materials off ground, indoors, in dry location and in accordance

- with manufacturer's recommendations in clean, dry, well-ventilated area.
- .2 Store and protect equipment and materials from nicks, scratches, and blemishes.
- .3 Replace defective or damaged materials with new.
- .4 Packaging Waste Management: remove for reuse and return by manufacturer of pallets, crates, padding and packaging materials as specified in accordance with Section 01 74 20.

PART 2 - PRODUCTS

2.1 DESIGN REQUIREMENTS

- .1 Operating voltages: to CAN3-C235.
- .2 Motors, electric heating, control and distribution devices and equipment to operate satisfactorily at 60 Hz within normal operating limits established by above standard.
 - .1 Equipment to operate in extreme operating conditions established in above standard without damage to equipment.
- .3 Language operating requirements: provide identification nameplates and labels for control items in English.

2.2 MATERIALS AND EQUIPMENT

- .1 Provide material and equipment in accordance with Section 01 61 00.
- .2 Material and equipment to be CSA certified. Where CSA certified material and equipment are not available, obtain special approval from authority having jurisdiction before delivery to site and submit such approval as described in PART 1 - ACTION AND INFORMATIONAL SUBMITTALS.
- .3 Factory assemble control panels and component assemblies.

2.3 ELECTRIC MOTORS, EQUIPMENT AND CONTROLS

- .1 Verify installation and co-ordination responsibilities related to motors, equipment and controls, as indicated.
- .2 Control wiring and conduit: in accordance with Section 26 29 03 except for conduit, wiring and connections below 50 V which are related to control systems specified in mechanical sections and as indicated on mechanical drawings.

2.4 WARNING SIGNS

- .1 Warning Signs: in accordance with requirements of authority having jurisdiction and Departmental Representative.
- .2 Porcelain enamel decal signs, minimum size 175 x 250 mm.

2.5 WIRING TERMINATIONS

- .1 Ensure lugs, terminals, screws used for termination of wiring are suitable for either copper or aluminum conductors.

2.6 EQUIPMENT IDENTIFICATION

- .1 Identify electrical equipment with nameplates and labels as follows:
 - .1 Nameplates: lamicoid 3 mm matt white finish face, black core, lettering accurately aligned and engraved into core mechanically attached with self tapping screws.
 - .2 Sizes as follows:

NAMEPLATE SIZES

Size 1	10 x 50 mm	1 line	3 mm high letters
Size 2	12 x 70 mm	1 line	5 mm high letters
Size 3	12 x 70 mm	2 lines	3 mm high letters
Size 4	20 x 90 mm	1 line	8 mm high letters
Size 5	20 x 90 mm	2 lines	5 mm high letters
Size 6	25 x 100 mm	1 line	12 mm high letters
Size 7	25 x 100 mm	2 lines	6 mm high letters

- .2 Labels: embossed plastic labels with 6 mm high letters unless specified otherwise.
- .3 Wording on nameplates and labels to be approved by Departmental Representative prior to manufacture.
- .4 Allow for minimum of twenty-five (25) letters per nameplate and label.
- .5 Nameplates for terminal cabinets and junction boxes to indicate system and/or voltage characteristics.
- .6 Identify equipment with Size 3 labels engraved "ASSET INVENTORY NO. [_____] " as directed by Departmental Representative.
- .7 Disconnects, starters and contactors: indicate equipment being controlled and voltage.
- .8 Terminal cabinets and pull boxes: indicate system and voltage.
- .9 Transformers: indicate capacity, primary and secondary voltages.

2.7 WIRING IDENTIFICATION

- .1 Identify wiring with permanent indelible identifying markings, numbered

and coloured plastic tapes, on both ends of phase conductors of feeders and branch circuit wiring.

- .2 Maintain phase sequence and colour coding throughout.
- .3 Colour coding: to CSA C22.1.
- .4 Use colour coded wires in communication cables, matched throughout system.

2.8 CONDUIT AND CABLE IDENTIFICATION

- .1 Colour code conduits, boxes and metallic sheathed cables.
- .2 Code with plastic tape or paint at points where conduit or cable enters wall, ceiling, or floor, and at 15 m intervals.
- .3 Colours: 25 mm wide prime colour and 20 mm wide auxiliary colour.

	<u>Prime</u>	<u>Auxiliary</u>
up to 250 V	Yellow	
up to 600 V	Yellow	Green
up to 5 kV	Yellow	Blue
up to 15 kV	Yellow	Red
Telephone	Green	
Other Communication Systems	Green	Blue
Fire Alarm	Red	
Emergency Voice	Red	Blue
Other Security Systems	Red	Yellow

2.9 FINISHES

- .1 Shop finish metal enclosure surfaces by application of rust resistant primer inside and outside, and at least two coats of finish enamel.
 - .1 Finalize electrical equipment painting with Departmental representative prior to painting.

PART 3 - EXECUTION

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 INSTALLATION

- .1 Do complete installation in accordance with CSA C22.1 except where specified otherwise.
- .2 Do overhead and underground systems in accordance with CAN/CSA-C22.3 No.1 except where specified otherwise.

3.3 NAMEPLATES AND LABELS

- .1 Ensure manufacturer's nameplates, CSA labels and identification nameplates are visible and legible after equipment is installed.

3.4 CONDUIT AND CABLE INSTALLATION

- .1 Install conduit and sleeves prior to pouring of concrete.
 - .1 Sleeves through concrete: schedule 40 steel pipe, sized for free passage of conduit, and protruding 50 mm.
- .2 If plastic sleeves are used in fire rated walls or floors, remove before conduit installation.
- .3 Install cables, conduits and fittings embedded or plastered over, close to building structure so furring can be kept to minimum.

3.5 LOCATION OF OUTLETS

- .1 Locate outlets in accordance with Section 26 05 32.
- .2 Do not install outlets back-to-back in wall; allow minimum 150 mm horizontal clearance between boxes.
- .3 Change location of outlets at no extra cost or credit, providing distance does not exceed 3000 mm, and information is given before installation.
- .4 Locate light switches on latch side of doors.
 - .1 Locate disconnect devices in mechanical and elevator machine rooms

on latch side of floor.

3.6 MOUNTING HEIGHTS

- .1 Mounting height of equipment is from finished floor to centreline of equipment unless specified or indicated otherwise.
- .2 If mounting height of equipment is not specified or indicated, verify before proceeding with installation.
- .3 Install electrical equipment at following heights unless indicated otherwise.
 - .1 Local switches: 1400 mm.
 - .2 Wall receptacles:
 - .1 Outdoor: 1000 mm.
 - .2 Panelboards: as required by Code or as indicated.

3.7 CO-ORDINATION OF PROTECTIVE DEVICES

- .1 Ensure circuit protective devices such as overcurrent trips, relays and fuses are installed to required values and settings.

3.8 FIELD QUALITY CONTROL

- .1 Load Balance:
 - .1 Measure phase current to panelboards with normal loads (lighting) operating at time of acceptance; adjust branch circuit connections as required to obtain best balance of current between phases and record changes.
 - .2 Measure phase voltages at loads and adjust transformer taps to within 2% of rated voltage of equipment.
 - .3 Provide upon completion of work, load balance report as directed in PART 1 - ACTION AND INFORMATIONAL SUBMITTALS, phase and neutral currents on panelboards, dry-core transformers and motor control centres, operating under normal load, as well as hour and date on which each load was measured, and voltage at time of test.
- .2 Conduct following tests in accordance with Section 01 45 00.
 - .1 Power distribution system including phasing, voltage, grounding and load balancing.
 - .2 Circuits originating from branch distribution panels.
 - .3 Lighting and its control.
 - .4 Motors, heaters and associated control equipment including sequenced operation of systems where applicable.
 - .5 Insulation resistance testing:
 - .1 Megger circuits, feeders and equipment up to 350 V with a 500 V instrument.
 - .2 Megger 350-600 V circuits, feeders and equipment with a 1000 V instrument.
 - .3 Check resistance to ground before energizing.
- .3 Carry out tests in presence of Departmental Representative.

- .4 Provide instruments, meters, equipment and personnel required to conduct tests during and at conclusion of project.
- .5 Manufacturer's Field Services:
 - .1 Obtain written report from manufacturer verifying compliance of Work, in handling, installing, applying, protecting and cleaning of product and submit Manufacturer's Field Reports as described in PART 1 - ACTION AND INFORMATIONAL SUBMITTALS.
 - .2 Provide manufacturer's field services consisting of product use recommendations and periodic site visits for inspection of product installation in accordance with manufacturer's instructions.

3.9 SYSTEM STARTUP

- .1 Instruct Departmental Representative and operating personnel in operation, care and maintenance of systems, system equipment and components.
- .2 Arrange and pay for services of manufacturer's factory service engineer to supervise start-up of installation, check, adjust, balance and calibrate components and instruct operating personnel.
- .3 Provide these services for such period, and for as many visits as necessary to put equipment in operation, and ensure that operating personnel are conversant with aspects of its care and operation.

3.10 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

PART 1 - GENERAL

1.1 DESCRIPTION

- .1 Provide a short-circuit and protective device coordination study for the electrical distribution system. The intent of these studies are to verify that the specified and supplied equipment are properly rated, correctly applied, and within industry and manufacturer's tolerances.
- .2 Short circuit study shall:
 - .1 Include all portions of the electrical distribution system from the normal and alternate sources of power throughout the distribution system down to the smallest protective device.
 - .2 Consider operation during normal conditions, alternate operations, emergency power conditions, and any other operations which could result in maximum fault conditions.
- .3 Coordination study shall:
 - .1 Determine the correct settings for the protective devices which will minimize the damage caused by an electrical fault and allow for selective coordination between the devices.
 - .2 Include the closest upstream utility protective device down to the panelboard main, branch, or feeder circuit breakers.
 - .3 Consider operation during normal conditions, alternate operation, and during emergency power conditions.

1.2 QUALIFICATIONS

- .1 Contractor shall have the coordination study prepared by qualified engineers of an independent consultant. Consultant shall be a Registered Professional Electrical Engineer, licensed in the province where the project is completed, who has at least ten (10) years of experience and specializes in performing power system studies.
- .2 Perform short circuit and coordination study using the industry recognized program for Windows computer software package.

1.3 SUBMITTALS

- .1 Submit power system studies within 30 days after the electrical equipment submittals have been received for review by the Departmental Representative.
- .2 Submit three (3) copies of the power systems study.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 IMPEDANCE ONE-LINE DIAGRAM

- .1 Create an impedance one-line diagram. Protect all electrical equipment wiring by overcurrent devices installed under this project and indicate each location where the fault current will be calculated. Clearly indicate, on the single-line, the schematic wiring of the electrical distribution system.
- .2 Show reference nodes on the single-line diagram referring to a formal report and include the following specific information:
 - .1 X/R ratios, utility contribution, and short circuit values (asymmetrical and symmetrical) at the bus of the main service, and all downstream equipment containing overcurrent devices.
 - .2 Transformer kVA and voltage ratings, percent impedance, X/R ratios and wiring connections.
 - .3 Voltage at each bus.
 - .4 Identifications of each bus.
 - .5 Conduit material, feeder sizes and length.

3.2 SHORT CIRCUIT STUDY

- .1 Calculate by means of the industry recognized program for Windows computer software package. Incorporate pertinent data, rationale employed, and assumptions in developing the calculations in the introductory remarks of the study.
- .2 Do study in accordance with applicable ANSI and IEEE Standards.
- .3 Determine available 3 phase short circuit and ground fault currents at each bus. Incorporate motor contribution in determining momentary and interrupting ratings of the protective devices.
- .4 Present data determined by short circuit study in table format. Include:
 - .1 Node & Device identification.
 - .2 Operating voltage.
 - .3 Type of Protective device. (i.e. fuse, molded case circuit breaker, etc.)
 - .4 Device short circuit rating.
 - .5 Calculated maximum short circuit current, 3 phase or ground fault, asymmetrical and symmetrical, and X/R ratio.
 - .6 De-rate the devices where the tested X/R ratio is less than the calculated X/R ratio. (maximum fault current multiplied by MF.)
 - .7 Comments section indicating that device is underrated.

3.3 PROTECTIVE DEVICE COORDINATION STUDY

- .1 Calculate by means of the industry recognized program for Windows computer software package.
- .2 Meet or exceed CSA C22.1-18 Canadian Electrical Code (CEC).

- .3 Include the closest upstream utility protective device down to the panelboard main, branch, or feeder circuit breakers. Prepare coordination curves to determine the required settings of protective devices to assure selective coordination.
- .4 Include phase and ground overcurrent protection, as well as settings for all other adjustable protective devices.
- .5 Graphically illustrate on log-log paper that adequate time separation exists between devices. Use sufficient curves to clearly indicate the coordination achieved between devices. Maintain reasonable coordination intervals and separation of characteristic curves. Plot the specific time-current characteristics of each protective device in such a manner that the upstream devices will be clearly depicted on the sheet.
- .6 Plots shall include complete titles, representative one-line diagram and legends, associated power company's relays or fuse characteristics, and complete parameters of transformers. Maximum of eight protective devices per sheet.
- .7 Indicate the following specific information on the coordination curves:
 - .1 Device identifications.
 - .2 Time and current ratio for curves.
 - .3 Fuse circuit breaker, and relay curves, showing complete operating bands of low-voltage circuit breaker trip curves.
 - .4 Significant maximum symmetrical or asymmetrical short circuit cutoff point.
 - .5 Electric utility's relays and/or fuses including manufacturer's minimum melt, total clearing, tolerance.
 - .6 Medium voltage equipment relays.
 - .7 Medium and low voltage fuses including manufacturer's minimum melt, total clearing, tolerance, and damage bands.
 - .8 Low voltage equipment circuit breaker trip devices, including manufacturers tolerance bands.
 - .9 Pertinent transformer full-load currents at 100% and 600%.
 - .10 Ground fault protective device settings.
 - .11 Other system load protective devices for largest branch circuit and feeder circuit breaker in each motor control center and panelboard.
- .8 Develop a table to summarize the settings selected for the protective devices. Include the following:
 - .1 Device identification.
 - .2 Current transformer ratio, relay tap, time delay, and instantaneous pickup.
 - .3 Circuit breaker sensor rating, long-time, short-time, and instantaneous settings, and time bands.
 - .4 Fuse rating and type.
 - .5 Ground fault pickup and time delay.

3.4 ANALYSIS

- .1 Analyze short circuit calculations and highlight any equipment that is determined to be underrated as specified or not coordinated. Propose

approaches to effectively protect the underrated equipment. Proposed major corrective modifications will be taken under advisement by the Departmental Representative, and the Contractor will be given further instructions.

- .2 After developing the coordination curves, highlight areas lacking coordination. For each sheet, present a technical evaluation with a discussion of the logical compromises for best coordination.

3.5 REPORT

- .1 Summarize the results of the power system study in a final report.
- .2 Report shall include the following sections:
 - .1 Introduction, executive summary and recommendations, assumptions, impedance one line drawing, and copies of the project single-line drawings.
 - .2 Tabulations of equipment ratings versus calculated short circuit values and X/R ratios, and commentary regarding same.
 - .3 Protective device time versus current coordination curves, tabulations of relay and circuit breaker trip settings, fuse selection, and commentary regarding same.
 - .4 Copies of manufacturer's time current curves for the devices studied and plotted.

PART 1 - GENERAL

1.1 REFERENCES

- .1 Canadian Standards Association (CSA International)
 - .1 CSA C22.1-18, Canadian Electrical Code, Part 1 (24th Edition).
 - .2 CSA C22.2 No. 131-14, Type TECK 90 Cable.
 - .3 CAN/CSA-C61089-11(R2015), Round Wire Concentric Lay Overhead Electrical Stranded Conductors.
- .2 National Electrical Manufacturers' Association (NEMA)/Insulated Cable Engineers Association (ICEA)
 - .1 ICEA S-93-639/NEMA WC74-2012, 5-46 KV Shielded Power Cable for Use in the Transmission and Distribution of Electrical Energy.

1.2 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.
- .2 Provide product data in accordance with Section 01 33 00.
 - .1 Provide manufacturer's printed product literature, specifications, data sheet and include product characteristics, performance criteria, physical size, finish and limitations.
- .3 Quality assurance submittals: submit following in accordance with Section 01 45 00.
 - .1 Manufacturer's Instructions: submit manufacturer's installation instructions and special handling criteria, installation sequence, cleaning procedures.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with manufacturer's written instructions.
- .2 Waste Management and Disposal:
 - .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 20.

PART 2 - PRODUCTS

2.1 TECK POWER CABLE (1001 - 15000 V)

- .1 Cable: to CSA C22.2 No. 131 and in accordance with Section 26 05 00.
- .2 Bare copper grounding conductor, size as indicated.
- .3 Copper circuit conductors, size and number as indicated.
- .4 Strand shielding.

- .5 Insulation: chemically cross-linked thermosetting polyethylene rated RW90, 5 kV to ICEA S-93-639/NEMA WC74.
- .6 Insulation shielding: semi-conducting non-metallic tape over insulation and served wire shield over tape to ICEA S-93-639/NEMA WC74.
- .7 Separator tape over conductor assembly.
- .8 Inner jacket of PVC.
- .9 Interlocked aluminum armour.
- .10 Overall PVC jacket rated minus 40°C.

PART 3 - EXECUTION

3.1 INSTALLATION

- .1 Install power cable on cable ladder as indicated and in accordance with manufacturer's instructions.
- .2 Install power cable in trenches as indicated.
- .3 Provide supports and accessories for installation of high voltage power cable.
- .4 Install stress cones, terminations and splices in accordance with manufacturer's instructions
- .5 Install grounding in accordance with local inspection authority having jurisdiction.
- .6 Provide cable identification tags and identify each phase conductor of power cable.

3.2 FIELD QUALITY CONTROL

- .1 Perform tests in accordance with Section 26 05 00.
- .2 Use of qualified tradespersons for installation, splicing, termination and testing of high voltage power cables.
- .3 Engage an independent testing agent to test high voltage power cable. Submit test result and inspection certificate.

PART 1 - GENERAL

1.1 REFERENCES

- .1 CSA International
 - .1 CSA C22.1-18, Canadian Electrical Code, Part 1 (24th Edition).
 - .2 CSA C22.2 No.18.1-13, Metallic outlet boxes (Tri-national standard, with UL 514A and ANCE NMX- J-023/1).
 - .3 CSA C22.2 No.18.2-06(R2016), Nonmetallic Outlet Boxes.
 - .4 CSA C22.2 No.18.3-12, Conduit, tubing, and cable fittings (Tri-national standard, with ANCE NMX-J-017 and UL 514B).
 - .5 CSA C22.2 No.18.4-15, Hardware for the Support of Conduit, Tubing, and Cable (Bi-National standard, with UL 2239).
 - .6 CSA C22.2 No. 18.5-13, Positioning devices (Bi-national standard, with UL 1565).
 - .7 CSA C22.2 NO. 65-13, Wire connectors (Tri- national standard, with UL 486A-486B and NMX-J-543-ANCE).
- .2 Electrical and Electronic Manufacturers' Association of Canada (EEMAC)
 - .1 EEMAC 1Y-2-1961, Bushing Stud Connectors and Aluminum Adapters (1200 Ampere Maximum Rating).
- .3 National Electrical Manufacturers Association (NEMA)

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for wire and box connectors and include product characteristics, performance criteria, physical size, finish and limitations.

1.3 CLOSEOUT SUBMITTALS

- .1 Submit in accordance with Section 01 78 00.
- .2 Operation and Maintenance Data: submit operation and maintenance data for wire and box connectors for incorporation into manual.

1.4 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials off ground, indoors, in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated

- area.
- .2 Store and protect wire and box connectors from nicks, scratches, and blemishes.
- .3 Replace defective or damaged materials with new.
- .4 Packaging Waste Management: remove for reuse and return by manufacturer of pallets, crates, padding and packaging materials as specified in accordance with Section 01 74 20.

PART 2 - PRODUCTS

2.1 MATERIALS

- .1 Pressure type wire connectors to: CSA C22.2 No.65, with current carrying parts of copper sized to fit copper conductors as required.
- .2 Fixture type splicing connectors to: CSA C22.2 No.65, with current carrying parts of copper sized to fit copper conductors 10 AWG or less.
- .3 Bushing stud connectors: to EEMAC 1Y-2 and NEMA to consist of:
 - .1 Connector body and stud clamp for copper conductors and bar.
 - .2 Clamp for stranded round copper conductors and bar.
 - .3 Stud clamp bolts.
 - .4 Bolts for copper conductors and bar.
 - .5 Sized for conductors and bars as indicated.
- .4 Clamps or connectors for TECK cable, as required to: CSA C22.2 No.18.

PART 3 - EXECUTION

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for wire and box connectors installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 INSTALLATION

- .1 Remove insulation carefully from ends of conductors and cables and:
 - .1 Apply coat of zinc joint compound on aluminum conductors prior to installation of connectors.
 - .2 Install mechanical pressure type connectors and tighten screws with appropriate compression tool recommended by manufacturer. Installation shall meet secureness tests in accordance with CSA C22.2

- No.65.
- .3 Install fixture type connectors and tighten to CSA C22.2 No.65.
Replace insulating cap.
- .4 Install bushing stud connectors in accordance with EEMAC 1Y-2 and NEMA.

3.3 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

PART 1 - GENERAL

1.1 PRODUCT DATA

- .1 Provide product data in accordance with Section 01 33 00.

1.2 DELIVERY, STORAGE AND HANDLING

- .1 Packaging Waste Management: remove for reuse and return by manufacturer of pallets, crates, padding and packaging materials in accordance with Section 01 74 20.

PART 2 - PRODUCTS

2.1 BUILDING WIRES

- .1 Conductors: stranded for 10 AWG and larger. Minimum size: 12 AWG.
- .2 Copper conductors: size as indicated, with 1000 V insulation of cross-linked thermosetting polyethylene material rated RW90 XLPE, Non-Jacketed.

2.2 TECK 90 CABLE

- .1 Cable: in accordance with Section 26 05 00.
- .2 Conductors:
 - .1 Grounding conductor: copper.
 - .2 Circuit conductors: size as indicated.
- .3 Insulation:
 - .1 Cross-linked polyethylene XLPE.
 - .2 Rating: 1000 V.
- .4 Inner jacket: polyvinyl chloride material.
- .5 Armour: interlocking galvanized steel.
- .6 Overall covering: thermoplastic polyvinyl chloride, compliant to applicable Building Code classification for this project.
- .7 Fastenings:
 - .1 One-hole steel straps to secure surface cables 50 mm and smaller. Two-hole steel straps for cables larger than 50 mm.
 - .2 Channel type supports for two or more cables.
 - .3 Threaded rods: 6 mm diameter to support suspended channels.
- .8 Connectors:
 - .1 Watertight approved for TECK cable.

2.3 CONTROL CABLES

- .1 Type: LVT: 2 soft annealed copper conductors, sized as indicated:
 - .1 Insulation: thermoplastic.
 - .2 Sheath: cotton braid, thermoplastic jacket, and armour of closely wound aluminum wire.

- .2 Type: low energy 300 V control cable: stranded annealed copper conductors sized as indicated LVT: 2 soft annealed copper conductors, sized as indicated:
 - .1 Insulation: PVC.
 - .2 Shielding: copper braid over each pair and group of conductors.
 - .3 Overall covering: PVC jackets and interlocked armour of flat galvanized steel.

- .3 Type: 600 V stranded annealed copper conductors, sizes as indicated:
 - .1 Insulation: RW90 (x-link).
 - .2 Shielding: copper braid over each pair and group of conductors.
 - .3 Overall covering: interlocked armour with PVC over sheath.

PART 3 - EXECUTION

3.1 FIELD QUALITY CONTROL

- .1 Perform tests in accordance with Section 26 05 00.
- .2 Perform tests using method appropriate to site conditions and to approval of Departmental Representative and local authority having jurisdiction over installation.
- .3 Perform tests before energizing electrical system.

3.2 GENERAL CABLE INSTALLATION

- .1 Install cable in trenches in accordance with Section 33 71 73.02.
- .2 Lay cable in cable trays in accordance with Section 26 05 36.
- .3 Terminate cables in accordance with Section 26 05 20.
- .4 Cable Colour Coding: to Section 26 05 00.
- .5 Conductor length for parallel feeders to be identical.
- .6 Lace or clip groups of feeder cables at distribution centres, pull boxes, and termination points.
- .7 Wiring in walls: typically drop or loop vertically from above to better facilitate future renovations. Generally wiring from below and horizontal wiring in walls to be avoided unless indicated.
- .8 Branch circuit wiring for surge suppression receptacles and permanently wired computer and electronic equipment to be 2-wire circuits only, i.e.

common neutrals not permitted.

- .9 Provide numbered wire collars for control wiring. Numbers to correspond to control shop drawing legend. Obtain wiring diagram for control wiring.

3.3 INSTALLATION OF BUILDING WIRES

- .1 Install wiring as follows:
 - .1 In conduit systems in accordance with Section 26 05 34.

3.4 INSTALLATION OF TECK90 CABLE (0 -1000 V)

- .1 Group cables wherever possible on channels.
- .2 Install cable exposed, securely supported by straps or hangers.

3.5 INSTALLATION OF CONTROL CABLES

- .1 Install control cables in conduit.
- .2 Ground control cable shield.

PART 1 - GENERAL

1.1 SECTION INCLUDES

- .1 Materials and installation for connectors and terminations.

1.2 RELATED SECTIONS

- .1 Section 26 05 33 - Raceway and Boxes for Electrical Systems.

1.3 REFERENCES

- .1 CSA C22.1-18, Canadian Electrical Code, Part 1 (24th Edition).
- .2 CSA C22.2 No.41-13, Grounding and Bonding Equipment (Tri-National Standard, with NMX-J-590ANCE and UL 467).
- .3 CSA C22.2 No.65-13, Wire connectors (Tri-National Standard, with UL 486A-486B NMX-J-543-ANCE).

1.4 PRODUCT DATA

- .1 Submit product data in accordance with Section 01 33 00.

1.5 CERTIFICATES

- .1 Obtain inspection certificate of compliance covering high voltage stress coning from inspection authority Engineer and include it with as-built drawings and maintenance manuals.

1.6 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate and recycle waste materials in accordance with Section 01 74 20.
- .2 Divert unused metal and wiring materials from landfill to metal recycling facility as approved by Departmental Representative.

PART 2 - PRODUCTS

2.1 CONNECTORS AND TERMINATIONS

- .1 Copper long barrel compression connectors to CSA C22.2 No. 65 as required sized for conductors.
- .2 Contact aid for aluminum cables where applicable.
- .3 4-way joint boxes NEMA 4X stainless steel type in accordance with Section 26 05 33.
- .4 4-way junction boxes with respective pothead for 4 conductor cables with allowance for stress - cone beyond for X - linked polyethylene cable with

aluminum sheath, and overall jacket in accordance with Section 26 05 33.

PART 3 - EXECUTION

3.1 INSTALLATION

- .1 Install stress cones, terminations, and splices in accordance with manufacturer's instructions.
- .2 Bond and ground as required to CSA C22.2 No.41.

PART 1 - GENERAL

1.1 REFERENCES

- .1 CSA standards
 - .1 CSA C22.1-18, Canadian Electrical Code, Part 1 (24th Edition), Safety Standard for Electrical Installations.
- .2 Institute of Electrical and Electronics Engineers (IEEE)
 - .1 IEEE 837-2014, Standard for Qualifying Permanent Connections Used in Substation Grounding.

1.2 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Provide manufacturer's printed product literature, specifications and datasheet and include product characteristics, performance criteria, physical size, finish and limitations.
- .3 Quality assurance submittals: provide in accordance with Section 01 45 00.
 - .1 Manufacturer's Instructions: provide manufacturer's written installation instructions and special handling criteria, installation sequence, cleaning procedures.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with manufacturer's written instructions.
- .2 Waste Management and Disposal:
 - .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 20.

PART 2 - PRODUCTS

2.1 MATERIALS

- .1 Rod electrodes: copper clad steel, 19 mm diameter by 3 m long.
- .2 Conductors: bare, stranded, tinnedsoft annealed copper wire, size No. 4/0 AWG and 4/0 AWG for ground bus, electrode interconnections, metal structures, gradient control mats, transformers, switchgear, motors, ground connections.
- .3 Conductors: bare, stranded tinnedsoft annealed copper wire, size No. 2/0 AWG for grounding cable sheaths, raceways, pipe work, screen guards, switchboards, potential transformers.
- .4 Conductors: PVC insulated coloured green, stranded tinned soft annealed

- copper wire No. 10 AWG for grounding meter and relay cases.
- .5 Conductors: No. 3/0 AWG extra flexible (425 strands) copper conductor for connection of switch mechanism operating rod to gradient control mat, fence gates, vault doors.
 - .6 Bolted removable test links.
 - .7 Accessories: non-corroding, necessary for complete grounding system, type, size material as indicated, including:
 - .1 Grounding and bonding bushings.
 - .2 Protective type clamps.
 - .3 Bolted type conductor connectors.
 - .4 Thermit welded type conductor connectors.
 - .5 Bonding jumpers, straps.
 - .6 Pressure wire connectors.
 - .8 Wire connectors and terminations: as indicated.
 - .9 Grounding resistance bank: outdoor, NEMA 4X stainless steel enclosure, single phase, high resistance grounding for 600V system, 347V Lin to Neutral, 5A continuous rating, 71.9 ohm complete with dual resistor paths for a redundant system, ground fault relay, resistor path monitors and controls with audio and visual alarm and ground fault alarm signal for facility BAS system.
 - .10 Cable sheath isolating sleeves.

PART 3 - EXECUTION

3.1 INSTALLATION

- .1 Install continuous grounding system including, electrodes, conductors, connectors and accessories as indicated and to requirements of local authority having jurisdiction.
- .2 Ground fences to grounding system independent of station ground.
- .3 Install connectors and cadweld in accordance with manufacturer's instructions.
- .4 Protect exposed grounding conductors during and after construction.
- .5 Make buried connections, and connections to electrodes, structural steel work, using copper welding by thermit process.
- .6 Use mechanical connectors for grounding connections to equipment provided with lugs.
- .7 Use No. 4/0 AWG bare copper cable for main ground bus of substation and No. 4/0 AWG mhd bare copper cable for taps on risers from main ground bus to equipment.

- .8 Use tinned copper conductors for aluminum structures.
- .9 Do not use bare copper conductors near un-jacketed lead sheath cables.
- .10 Install grounding resistor bank and connect to T1 and T2 neutral point.

3.2 ELECTRODE INSTALLATION

- .1 Install ground rod electrodes. Make grounding connections to station equipment.
- .2 Install ground rod electrodes at transformer and switchgear locations.
- .3 Install gradient control mats. Connect mats to station ground electrode and switch mechanism operating rods.
- .4 Make special provision for installing electrodes that will give acceptable resistance to ground value, where rock or sand terrain prevails.

3.3 EQUIPMENT GROUNDING

- .1 Install grounding connections as indicated to typical station equipment including: neutral, gradient control mats. Non-current carrying parts of: transformers, circuit breakers, frames of gang-operated switches and fuse cutout bases. Cable sheaths, raceways, pipe work, screen guards, switchboards, potential transformers. Meter and relay cases. Any exposed building metal, within or forming part of station enclosure. Sub-station fences.
- .2 Ground hinged doors to main frame of electrical equipment enclosure with flexible jumper.
- .3 Connect metallic piping (water, oil, air, etc.) inside station to main ground bus at several locations, including each service location within station. Make connections to metallic water pipes outside station to assist in reduction of station ground resistance value.

3.4 NEUTRAL GROUNDING

- .1 Connect transformer neutral and distribution neutral together using 1000 V insulated conductor to one side of ground test link, the other side of the test link being connected directly to main station ground. Ensure distribution neutral and neutrals of potential transformers and service banks are bonded directly to transformer neutral and not to main station ground.
- .2 Interconnect electrodes and neutrals at each grounding installation.
- .3 Connect neutral of station service transformer to main neutral bus with tap of same size as secondary neutral.
- .4 Ground transformer tank with continuous conductor from tank ground lug through connector on ground bus to primary neutral. Connect neutral bushing

at transformer to primary neutral in same manner.

3.5 FIELD QUALITY CONTROL

- .1 Perform tests in accordance with Section 26 05 00.
- .2 Engage an independent testing agent to inspect grounding and perform ground resistance test before backfilling.
- .3 Perform earth loop test and resistance tests using method appropriate to site conditions and to approval of Departmental Representative and local authority having jurisdiction.
- .4 Perform test before energizing electrical system.
- .5 Provide step-and-touch potential calculations using measured station ground resistance measurements. Submit test result and inspection certificate before energizing electrical system.

PART 1 - GENERAL

1.1 REFERENCES

- .1 American National Standards Institute/Institute of Electrical and Electronics Engineers (ANSI/IEEE)
 - .1 ANSI/IEEE 837-2014, IEEE Standard for Qualifying Permanent Connections Used in Substation Grounding.
- .2 CSA International
 - .1 CSA C22.1-18, Canadian Electrical Code, Part 1 (24th Edition).

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for grounding equipment and include product characteristics, performance criteria, physical size, finish and limitations.

1.3 CLOSEOUT SUBMITTALS

- .1 Submit in accordance with Section 01 78 00.
- .2 Operation and Maintenance Data: submit operation and maintenance data for grounding equipment for incorporation into manual.

1.4 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials off ground, indoors, in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect grounding equipment from nicks, scratches, and blemishes.
 - .3 Replace defective or damaged materials with new.
- .4 Packaging Waste Management: remove for reuse and return by manufacturer of pallets, crates, padding and packaging materials as specified in accordance with Section 01 74 20.

PART 2 - PRODUCTS

2.1 EQUIPMENT

- .1 Clamps for grounding of conductor: size as required to electrically conductive underground water pipe.
- .2 Copper conductor: minimum 6 m long for each concrete encased electrode, bare, stranded, tinned, soft annealed, size as indicated.
- .3 Rod electrodes: copper clad steel 19 mm diameter by minimum 3 m long.
- .4 Grounding conductors: bare stranded copper, tinned, soft annealed, size as indicated.
- .5 Insulated grounding conductors: green, copper conductors, size as indicated.
- .6 Ground bus: copper, size as indicated, complete with insulated supports, fastenings, connectors.
- .7 Non-corroding accessories necessary for grounding system, type, size, material as indicated, including but not necessarily limited to:
 - .1 Grounding and bonding bushings.
 - .2 Protective type clamps.
 - .3 Bolted type conductor connectors.
 - .4 Thermit welded type conductor connectors.
 - .5 Bonding jumpers, straps.
 - .6 Pressure wire connectors.
- .8 Grounding resistance bank: outdoor, NEMA 4X stainless steel enclosure, single phase, 71.9 ohms, 347V, 5A. complete with:
 - .1 Automatic pulsing system.
 - .2 Ground fault and resistor integrity monitoring relay.
 - .3 Redundant resistor system.
 - .4 Fault current percentage dial type indicator
 - .5 Test/reset push buttons.
 - .6 indication lamps for system healthy, Trip, Ground fault and Resistor fault.

PART 3 - EXECUTION

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for grounding equipment installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions

- immediately upon discovery.
- .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 INSTALLATION GENERAL

- .1 Install complete permanent, continuous grounding system including, electrodes, conductors, connectors, accessories. Where EMT is used, run ground wire in conduit.
- .2 Install connectors in accordance with manufacturer's instructions.
- .3 Protect exposed grounding conductors from mechanical injury.
- .4 Make buried connections, and connections to conductive water main, electrodes, using copper welding by thermit process.
- .5 Use mechanical connectors for grounding connections to equipment provided with lugs.
- .6 Soldered joints not permitted.
- .7 Install bonding wire for flexible conduit, connected at both ends to grounding bushing, solderless lug, clamp or cup washer and screw. Neatly cleat bonding wire to exterior of flexible conduit.
- .8 Install flexible ground straps for bus duct enclosure joints, where such bonding is not inherently provided with equipment.
- .9 Install grounding resistance bank as indicated.
- .10 Make grounding connections in radial configuration only, with connections terminating at single grounding point. Avoid loop connections.
- .11 Bond single conductor, metallic armoured cables to cabinet at supply end, and provide non-metallic entry plate at load end.
- .12 Ground secondary service pedestals.

3.3 MAINTENANCE HOLES

- .1 Install conveniently located grounding stud, electrode, size as indicated stranded copper conductor in each maintenance hole.
- .2 Install ground rod in each maintenance hole so that top projects through bottom of maintenance hole. Provide with lug to which grounding connection can be made. Confirm ground resistance meets or exceeds Canadian Electrical Code minimum requirements.

3.4 ELECTRODES

- .1 Make ground connections to continuously conductive underground water pipe on street side of water meter.
- .2 Install rod electrodes and make grounding connections as indicated.
- .3 Bond separate, multiple electrodes together.
- .4 Use size 4/0 AWG copper conductors for connections to electrodes.
- .5 Make special provision for installing electrodes that will give acceptable resistance to ground value where rock or sand terrain prevails. Ground as indicated.

3.5 SYSTEM AND CIRCUIT GROUNDING

- .1 Install system and circuit grounding connections to neutral secondary 600 V (T1 and T2 transformers) and 4160 V (T3 transformer) system.

3.6 EQUIPMENT GROUNDING

- .1 Install grounding connections to typical equipment included in, but not necessarily limited to following list. Service equipment, transformers, switchgear, duct systems, frames of motors, motor control centres, starters, control panels, building steel work, generators, elevators and escalators, distribution panels, outdoor lighting, cable trays.

3.7 GROUNDING BUS

- .1 Install copper grounding bus mounted on insulated supports on wall of electrical room or adjacent to main equipment.

3.8 FIELD QUALITY CONTROL

- .1 Perform tests in accordance with Section 26 05 00.
- .2 Perform ground continuity and resistance tests using method appropriate to site conditions and to approval of Departmental Representative and local authority having jurisdiction over installation.
- .3 Perform tests before energizing electrical system.
- .4 Disconnect ground fault indicator during tests.

3.9 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.

- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

PART 1 - GENERAL

1.1 REFERENCES

- .1 CSA Group
 - .1 CSA C22.1-18, Canadian Electrical Code, Part 1 (24th Edition), Safety Standard for Electrical Installations.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for hangers and supports and include product characteristics, performance criteria, physical size, finish and limitations.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials off ground, indoors, in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect hangers and supports from nicks, scratches, and blemishes.
 - .3 Replace defective or damaged materials with new.
- .4 Packaging Waste Management: remove for reuse and return by manufacturer of pallets, crates, padding and packaging materials as specified in accordance with Section 01 74 20.

PART 2 - PRODUCTS

2.1 SUPPORT CHANNELS

- .1 U shape, size 41 x 41 mm, 2.5 mm thick, surface mounted.

PART 3 - EXECUTION

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for hangers and supports installation in accordance with manufacturer's written

instructions.

- .1 Visually inspect substrate in presence of Departmental Representative.
- .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
- .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 INSTALLATION

- .1 Secure equipment to hollow and solid masonry, tile and plaster surfaces with lead anchors or nylon shields.
- .2 Secure equipment to poured concrete with expandable inserts.
- .3 Secure equipment to hollow masonry walls or suspended ceilings with toggle bolts.
- .4 Support equipment, conduit or cables using clips, spring loaded bolts, cable clamps designed as accessories to basic channel members.
- .5 Fasten exposed conduit or cables to building construction or support system using straps.
 - .1 One-hole steelstraps to secure surface conduits and cables 53 mm and smaller.
 - .2 Two-hole steel straps for conduits and cables larger than 53 mm.
 - .3 Beam clamps to secure conduit to exposed steel work.
- .6 Suspended support systems.
 - .1 Support individual cable or conduit runs with 6 mm diameter threaded rods and spring clips.
 - .2 Support 2 or more cables or conduits on channels supported by 6 mm diameter threaded rod hangers where direct fastening to building construction is impractical.
- .7 For surface mounting of two or more conduits use channels.
- .8 Provide metal brackets, frames, hangers, clamps and related types of support structures where indicated or as required to support conduit and cable runs.
- .9 Ensure adequate support for raceways and cables dropped vertically to equipment where there is no wall support.
- .10 Do not use wire lashing or perforated strap to support or secure raceways or cables.
- .11 Do not use supports or equipment installed for other trades for conduit or cable support except with permission of other trade and approval of Departmental Representative.
- .12 Install fastenings and supports as required for each type of equipment cables and conduits, and in accordance with manufacturer's installation

recommendations.

3.3 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

PART 1 - GENERAL

1.1 REFERENCES

- .1 Canadian Standards Association (CSA International)
 - .1 CSA C22.1-18, Canadian Electrical Code, Part 1, 24th Edition.

1.2 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Provide manufacturer's printed product literature, specifications and datasheet and include product characteristics, performance criteria, physical size, finish and limitations.
- .3 Provide shop drawings: in accordance with Section 01 33 00.
 - .1 Provide drawings stamped and signed by professional engineer registered or licensed in Province of Ontario, Canada.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Waste Management and Disposal:
 - .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 20.

PART 2 - PRODUCTS

2.1 JUNCTION AND PULL BOXES

- .1 Construction: welded NEMA-4X Stainless steel enclosure.
- .2 Covers Flush Mounted: 25 mm minimum extension all around.
- .3 Covers Surface Mounted: screw-on flat and turned edge covers.

PART 3 - EXECUTION

3.1 JUNCTION, PULL BOXES INSTALLATION

- .1 Install pull boxes in inconspicuous but accessible locations.
- .2 Mount cabinets with top not higher than 2 m above finished floor except where indicated otherwise.
- .3 Install terminal block as indicated in Type T cabinets.
- .4 Only main junction and pull boxes are indicated. Install additional pull boxes as required by CSA C22.1.

3.2 IDENTIFICATION

- .1 Equipment Identification: to Section 26 05 00.
- .2 Identification Labels: size 2 indicating system name, voltage and phase or as indicated.

PART 1 - GENERAL 2021-02-19

1.1 REFERENCES

- .1 Canadian Standards Association (CSA International)
 - .1 CSA C22.1-18, Canadian Electrical Code, Part 1, 24th Edition.

1.2 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00.
- .2 Waste Management and Disposal:
 - .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 20.

PART 2 - PRODUCTS

2.1 OUTLET AND CONDUIT BOXES GENERAL

- .1 Size boxes in accordance with CSA C22.1.
- .2 102 mm square or larger outlet boxes as required.
- .3 Gang boxes where wiring devices are grouped.
- .4 Blank cover plates for boxes without wiring devices.
- .5 347 V outlet boxes for 347 V switching devices.
- .6 Combination boxes with barriers where outlets for more than one system are grouped.

2.2 GALVANIZED STEEL OUTLET BOXES

- .1 One-piece electro-galvanized construction.
- .2 Single and multi-gang flush device boxes for flush installation, minimum size 76 x 50 x 38 mm or as indicated. 102 mm square outlet boxes when more than one conduit enters one side with extension and plaster rings as required.
- .3 Utility boxes for outlets connected to surface-mounted EMT conduit, minimum size 102 x 54 x 48 mm.
- .4 102 mm square or octagonal outlet boxes for lighting fixture outlets.

- .5 Extension and plaster rings for flush mounting devices in finished plaster and tile walls.

2.3 MASONRY BOXES

- .1 Electro-galvanized steel masonry single and multi-gang boxes for devices flush mounted in exposed block walls.

2.4 CONDUIT BOXES

- .1 Cast FS or FD boxes with factory-threaded hubs and mounting feet for surface wiring of devices.

2.5 OUTLET BOXES FOR NON-METALLIC SHEATHED CABLE

- .1 Electro-galvanized, sectional, screw ganging steel boxes, minimum size 76 x 50 x 63 mm with two double clamps to take non-metallic sheathed cables.

2.6 FITTINGS - GENERAL

- .1 Bushing and connectors with nylon insulated throats.
- .2 Knock-out fillers to prevent entry of debris.
- .3 Conduit outlet bodies for conduit up to 35 mm and pull boxes for larger conduits.
- .4 Double locknuts and insulated bushings on sheet metal boxes.

PART 3 - EXECUTION

3.1 INSTALLATION

- .1 Support boxes independently of connecting conduits.
- .2 Fill boxes with paper, sponges or foam or similar approved material to prevent entry of debris during construction. Remove upon completion of work.
- .3 For flush installations mount outlets flush with finished wall using plaster rings to permit wall finish to come within 6 mm of opening.
- .4 Provide correct size of openings in boxes for conduit. Do not install reducing washers.
- .5 Vacuum clean interior of outlet boxes before installation of wiring devices.
- .6 Identify systems for outlet boxes as required.

PART 1 - GENERAL

1.1 REFERENCES

- .1 CSA International
 - .1 CSA C22.2 No.40-M1989(R2014), Cutout, Junction and Pull Boxes.
 - .2 CSA C22.1-18, Canadian Electrical Code, Part 1 (24th Edition).

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for raceway and boxes and include product characteristics, performance criteria, physical size, finish and limitations.

1.3 CLOSEOUT SUBMITTALS

- .1 Submit in accordance with Section 01 78 00.
- .2 Operation and Maintenance Data: submit operation and maintenance data for raceway and boxes for incorporation into manual.

1.4 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials off ground, indoors, in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect raceway and boxes from nicks, scratches, and blemishes.
 - .3 Replace defective or damaged materials with new.
- .4 Packaging Waste Management: remove for reuse and return by manufacturer of pallets, crates, padding and packaging materials as specified in accordance with Section 01 74 20.

PART 2 - PRODUCTS

2.1 JUNCTION BOXES DISTRIBUTION LEVEL

- .1 Welded NEMA-4X stainless steel rectangular boxes 6 mm thick minimum painted with chromate primer and gray enamel with removable plate on front side,

designed for through run of main cable and porcelain enclosed disconnecting branches of 2 or 3 single conductor cables, using pothead plug and socket disconnectors enclosed in porcelain tubes and caps, standard designed for no voltage disconnecting, and for wall mounting in maintenance holes, branch cables rated 250 A, 5 kV, filled with medium hard asphalt base compound.

2.2 JUNCTION BOXES POWER LEVEL

- .1 Welded NEMA-4X stainless steel rectangular boxes, with joints ground smooth and fitted with gasket, contacts mounted on porcelain supports to which conductors are fastened by soldered-on lugs, medium hard asphalt compound filled, suitable for 3-phase, 15 kV cable, 250 MCM maximum cable size, with wiping sleeve and stuffing box entrance.
- .2 Welded NEMA-4X stainless steel rectangular boxes, oil resistant gasketed steel plate lids fastened with silicon-bronze bolts, shot blasted and painted with chromate primer and gray enamel, cable heads medium hard asphalt compound filled cap nut sealed potheads with wiping sleeve and stuffing box entrances, air filled, disconnecting links insulated switch stick operated at no voltage rated 500 A at 7500 V, 3 or 4-way for wall mounting in maintenance holes.

PART 3 - EXECUTION

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for raceway and boxes installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 INSTALLATION

- .1 Install distribution level NEMA-4X stainless steel boxes on walls of maintenance holes. Splice main cable in box and connect branch feeder. Fasten cover and fill with compound.
 - .1 Ground stainless steel boxes as required.
- .2 Install power level boxes as follows:
 - .1 Cast iron type: on trench floor, connect cable terminals to box contacts, fasten lid and fill with compound before trench is backfilled.
 - .2 stainless steel type: mount on wall of maintenance hole; connect cables to box terminals; install disconnect links, fasten lid securely check for air leaks.
 - .3 Ground power level boxes as required.

3.3 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

PART 1 - GENERAL

1.1 REFERENCES

- .1 Canadian Standards Association (CSA International)
 - .1 CSA C22.1-18, Canadian Electrical Code, Part 1 (24th Edition), Safety Standard for Electrical Installations.
 - .2 CSA C22.2 NO. 18.1-13, Metallic Outlet Boxes.
 - .3 CSA C22.2 NO. 18.2-06(R2016), Nonmetallic Outlet Boxes.
 - .4 CSA C22.2 No. 18.3-12, Conduit, Tubing, and Cable Fittings (Tri-National standard, with ANCE NMX-J-017 and UL 514B).
 - .5 CSA C22.2 No. 18.4-15, Hardware for the Support of Conduit, Tubing, and Cable.
 - .6 CSA C22.2 No. 45.1-07(R2012), Electrical Rigid Metal Conduit - Steel (Tri-National standard, with UL 6 and NMX-J-534-ANCE-2007).
 - .7 CSA C22.2 No. 56-13, Flexible Metal Conduit and Liquid-Tight Flexible Metal Conduit
 - .8 CSA C22.2 No. 83-M1985(R2013), Electrical Metallic Tubing.
 - .9 CSA C22.2 No. 211.2-06(R2016), Rigid PVC (Unplasticized) Conduit.
 - .10 CSA C22.2 No. 227.3-15, Mechanical protection tubing (MPT) and fittings (Bi-national standard, with UL 1696)

1.2 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.
- .2 Product data: submit manufacturer's printed product literature, specifications and datasheets.
 - .1 Submit cable manufacturing data.
- .3 Quality assurance submittals:
 - .1 Test reports: submit certified test reports.
 - .2 Certificates: submit certificates signed by manufacturer certifying that materials comply with specified performance characteristics and physical properties.
 - .3 Instructions: submit manufacturer's installation instructions.

1.3 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 20.
- .2 Place materials defined as hazardous or toxic waste in designated containers.
- .3 Ensure emptied containers are sealed and stored safely for disposal away from children.

PART 2 - PRODUCTS

2.1 CABLES AND REELS

- .1 Provide cables on reels or coils.
 - .1 Mark or tag each cable and outside of each reel or coil, to indicate cable length, voltage rating, conductor size, and manufacturer's lot number and reel number.
- .2 Each coil or reel of cable to contain only one continuous cable without splices.
- .3 Identify cables for exclusively dc applications.
- .4 Reel and mark shielded cables rated 2,001 volts and above.

2.2 CONDUITS

- .1 Rigid metal conduit: to CSA C22.2 No. 45, hot dipped galvanized steel threaded.
- .2 Epoxy coated conduit: to CSA C22.2 No. 45, with zinc coating and corrosion resistant epoxy finish inside and outside.
- .3 Electrical metallic tubing (EMT): to CSA C22.2 No. 83, with couplings and with expanded ends.
- .4 Rigid PVC conduit: to CSA C22.2 No. 211.2.
- .5 Flexible metal conduit: to CSA C22.2 No. 56, liquid-tight flexible galvanized steel.
- .6 Flexible PVC conduit: to CSA C22.2 No. 227.3.

2.3 CONDUIT FASTENINGS

- .1 One-hole steel straps to secure surface conduits 50 mm and smaller.
 - .1 Two-hole steel straps for conduits larger than 50 mm.
- .2 Beam clamps to secure conduits to exposed steel work.
- .3 Channel type supports for two or more conduits.
- .4 Threaded rods, 6 mm diameter, to support suspended channels.

2.4 CONDUIT FITTINGS

- .1 Fittings: to CSA C22.2 No. 18.3 and CSA C22.2 No. 18.4, manufactured for use with conduit specified. Coating: same as conduit.
- .2 Ensure factory "ells" where 90 degrees bends for 25 mm and larger conduits.

- .3 Watertight connectors and couplings for EMT.
 - .1 Set-screws are not acceptable.

2.5 EXPANSION FITTINGS FOR RIGID CONDUIT

- .1 Weatherproof expansion fittings with internal bonding assembly suitable for 100 mm linear expansion.
- .2 Watertight expansion fittings with integral bonding jumper suitable for linear expansion and 19 mm deflection.
- .3 Weatherproof expansion fittings for linear expansion at entry to panel.

2.6 FISH CORD

- .1 Polypropylene.

PART 3 - EXECUTION

3.1 MANUFACTURER'S INSTRUCTIONS

- .1 Compliance: comply with manufacturer's written recommendations or specifications, including product technical bulletins, handling, storage and installation instructions, and datasheets.

3.2 INSTALLATION

- .1 Install conduits to conserve headroom in exposed locations and cause minimum interference in spaces through which they pass.
- .2 Conceal conduits except in mechanical and electrical service rooms and in unfinished areas.
- .3 Surface mount conduits.
- .4 Use rigid galvanized steelhot dipped galvanized steel threaded conduit except where specified otherwise.
- .5 Use epoxy coated conduit underground.
- .6 Use electrical metallic tubing (EMT) only above 3 m not subject to mechanical injury.
- .7 Use rigid pvc conduit underground.
- .8 Use flexible galvanized steel conduit for work in movable metal partitions.
- .9 Use liquid tight flexible galvanized steel conduit for connection to vibrating equipment.
- .10 Use explosion proof flexible connection for connection to explosion proof motors.

- .11 Install conduit sealing fittings in hazardous areas.
 - .1 Fill with compound.
- .12 Minimum conduit size for lighting and power circuits: 19 mm.
- .13 Bend conduit cold:
 - .1 Replace conduit if kinked or flattened more than 1/10th of its original diameter.
- .14 Mechanically bend steel conduit over 19 mm diameter.
- .15 Field threads on rigid conduit must be of sufficient length to draw conduits up tight.
- .16 Install fish cord in empty conduits.
- .17 Remove and replace blocked conduit sections.
 - .1 Do not use liquids to clean out conduits.
- .18 Dry conduits out before installing wire.

3.3 SURFACE CONDUITS

- .1 Run parallel or perpendicular to building lines.
- .2 Locate conduits behind infrared or gas fired heaters with 1.5 m clearance.
- .3 Run conduits in flanged portion of structural steel.
- .4 Group conduits wherever possible on surface channels.
- .5 Do not pass conduits through structural members except as indicated.
- .6 Do not locate conduits less than 75 mm parallel to steam or hot water lines with minimum of 25 mm at crossovers.

3.4 CLEANING

- .1 Proceed in accordance with Section 01 74 11.
- .2 On completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.

PART 1 - GENERAL

1.1 REFERENCES

- .1 Canadian Standards Association (CSA International)
 - .1 CSA C22.1-18, Canadian Electrical Code, (24th Edition)
 - .2 CSA C22.2 No.126.1-17, Metal Cable Tray Systems (Bi-National Standard, with NEMA VE 1-2017).
- .2 National Electrical Manufacturers Association (NEMA) standards
 - .1 NEMA VE 1-2017, Metal Cable Tray Systems.
 - .2 NEMA VE 2-2001, Cable Tray Installation Guidelines.

1.2 SHOP DRAWINGS AND PRODUCT DATA

- .1 Submit shop drawings and product data in accordance with section 01 33 00.
- .2 Identify types of cable troughs used.
- .3 Show actual cable trough installation details and suspension system.

1.3 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate and recycle waste materials in accordance with Section 01 74 20.
- .2 Remove from site and dispose of all packaging materials at appropriate recycling facilities.
- .3 Collect and separate for disposal paper, plastic, polystyrene, corrugated cardboard, packaging material in appropriate on-site bins for recycling in accordance with Waste Management Plan.
- .4 Divert unused metal and wiring materials from landfill to metal recycling facility as approved by Departmental Representative.
- .5 Fold up metal banding, flatten and place in designated area for recycling.

PART 2 - PRODUCTS

2.1 CABLE TROUGH

- .1 Cable troughs and fittings: to NEMA VE 1.
- .2 Ladder Ventilated type, Class A, C1, D1, E to CSA C22.2 No.126.1.
- .3 Trays: Hot dip galvanized steel, Width and depth as indicated.
- .4 Fittings: horizontal elbows, end plates, drop outs, vertical risers and drops, tees, wyes, expansion joints and reducers where required, manufactured accessories for cable trough supplied.
 - .1 Radii on fittings: 900 mm minimum.

- .5 Solid covers for complete cable trough system including fittings.
- .6 Barriers where different voltage systems are in same cable trough.
- .7 Ground cable trays with #4/0 AWG bare copper conductor attached to each tray section in accordance with CEC requirements.
- .8 Provide fire stop material at firewall penetrations.

2.2 SUPPORTS

- .1 Provide supports as required.

PART 3 - EXECUTION

3.1 INSTALLATION

- .1 in accordance with NEMA VE 2.
- .2 Support cable trough on both sides.
- .3 Remove sharp burrs or projections to prevent damage to cables or injury to personnel.

3.2 CABLES IN CABLE TROUGH

- .1 Install cables individually.
- .2 Lay cables into cable trough. Use rollers when necessary to pull cables.
- .3 Secure cables in cable trough at 6 m centers, with nylon ties.
- .4 Identify cables every 30 m with size 2 nameplates.

PART 1 - GENERAL

1.1 REFERENCES

- .1 Canadian Standards Association (CSA International)
 - .1 CAN/CSA-802.3-15, Minimum Efficiency Values for Power Transformers.
 - .2 CAN/CSA C88-16, Power Transformers and Reactors
 - .3 CAN/CSA-C2.1-06(R2017), Single-Phase and Three-Phase Liquid-Filled Distribution Transformers.
- .2 IEEE standards
 - .1 IEEE C57.10.12-2017, IEEE Standard Requirements for Oil Immersed Power Transformers

1.2 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Submit manufacturer's printed product literature, specifications and datasheet and include product characteristics, performance criteria, and limitations.
- .3 Submit shop drawings and indicate:
 - .1 Dimensioned positions of mounting devices.
 - .2 Dimensioned positions of terminations.
 - .3 Identified internal and external component layout on assembly drawing.
 - .4 Insulating liquid capacity.
- .4 Quality Assurance Submittals: submit following in accordance with Section 01 45 00.
 - .1 Certificates: submit type and production certificates signed by manufacturer certifying that materials comply with specified performance characteristics and physical properties.
 - .2 Instructions: submit manufacturer's installation instructions.
 - .1 make available 1 copy of systems supplier's installation instructions.
- .5 Closeout Submittals
 - .1 Provide maintenance data for liquid filled transformers for incorporation into manual specified in Section 01 78 00.
 - .2 Include insulating liquid maintenance data.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Ship transformers complete with first fill of liquid.
- .2 Waste Management and Disposal:
 - .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 20.

1.4 MAINTENANCE

- .1 Provide maintenance materials in accordance with Section 01 78 00.
- .2 Spare parts:
 - .1 As per manufacturer's recommendation for maintenance and 10-years operation

PART 2 - PRODUCTS

2.1 TRANSFORMER CHARACTERISTICS

- .1 Transformers: to CAN/CSA-C2.1-06 (R2017) and CAN/CSA C88-16.
- .2 Liquid cooled, outdoor, distribution transformers type ONAN.
- .3 Primary voltage: 27600 V, 60 Hz, delta connected (Dyn1), three-phase, three wires, ungrounded.
- .4 Secondary voltage:
 - .1 T1 and T2 transformers: 600/347 V, wye connected, three-phase, four wires, neutral resistor grounded suitable for delta-wye connection.
 - .2 T3 transformer: 4160/2400 V, wye connected, three-phase, four-wire, solidly grounded.
- .5 Capacity: 3000 kVA.
- .6 Basic impulse level:
 - .1 HV: 200 kV
 - .2 LV (T1 and T2): 45 kV
 - .3 LV (T3): 75 kV
- .7 Polarity: additive.
- .8 Impedance:
 - .1 T1 and T2 transformers: not less than 5.86% and not more than 5.90%.
 - .2 T3 transformer: 6.09%
- .9 No load losses as per CSA C802.3-1.
- .10 Full load losses as per CSA C802.3-1.
- .11 Vector Group: Dyn1.
- .12 HV and LV windings: Copper.
- .13 Temperature Rise: 55 °C.

2.2 MOUNTING

- .1 Transformers suitable for unit substation, floor mounting coupled with switchgears.

2.3 VIBRATION DAMPERS

- .1 Anti-vibration mountings to isolate not less than 90% of disturbing vibrations.

2.4 VOLTAGE TAPS

- .1 Four-2.5% taps, 2-FCAN, 2-FCBN.

2.5 TAP CHANGER

- .1 Externally operated off-load with provision for padlocking on 3 phase units.

2.6 HIGH VOLTAGE BUSHINGS

- .1 Bushings: to EEMAC L9-3.
- .2 Three high voltage bushings on three phase transformers.

2.7 INSULATING LIQUID

- .1 Insulating liquid: Biodegradable insulating oil.

2.8 THROAT CONNECTIONS

- .1 Extend primary terminals through a throat connection indicated.

2.9 ACCESSORIES

- .1 Hanger irons and adapter plates.
- .2 Top filter press connection.
- .3 Liquid Celsius temperature measuring device, maximum indicating type, dial type, with two sets contacts.
- .4 Liquid level gauge with two sets contacts.
- .5 Gas detector relay with two sets contacts (for conservator type transformers).
- .6 Winding Celsius temperature detector relay and sensing elements with two sets contacts.
- .7 Wiring and terminal box for protective devices.
- .8 Top non-flammable insulating liquid sampling device.
- .9 Anchor devices, setting templates means for bolting down.
- .10 Bi-directional skid base.

- .11 Wildlife proof shroud for each high voltage bushing.
- .12 Vacuum pressure gauge : dial type.
- .13 Factory install accessories.
- .14 Drain valve with plug: 25 mm.
- .15 Sudden pressure relay.

2.10 FINISH

- .1 Finish tank exterior in accordance with Section 26 05 00.

2.11 EQUIPMENT IDENTIFICATION

- .1 Provide equipment identification in accordance with Section 26 05 00.
- .2 Owner's equipment reference label: size 7.

2.12 SOURCE QUALITY CONTROL

- .1 Provide production type test certificates to Departmental Representative.

PART 3 - EXECUTION

3.1 MANUFACTURER'S INSTRUCTIONS

- .1 Compliance: comply with manufacturer's written recommendations or specifications, including product technical bulletins, handling, storage and installation instructions, and datasheets.

3.2 INSTALLATION

- .1 Install transformers only after other work in area is completed and in accordance with manufacturer's instructions.
- .2 Install transformers on the existing concrete pad.
- .3 Use spreader bars on slings when lifting transformers into place.
- .4 Set and secure transformers in place rigid, plumb, square.
- .5 Ensure internal connections are mechanically tight.
- .6 Make connections.
- .7 Connect transformer ground terminal to system ground.
- .8 Fill transformers when required with metal hose and ensure care is taken to prevent contamination of liquid and components.
- .9 Set taps to produce rated secondary voltage at no-load.

- .10 Wire one set contacts on liquid temperature measuring device, liquid level gauge, gas detector relay, winding temperature detector relay, to Building Automation System.

3.3 FIELD QUALITY CONTROL

- .1 Perform tests in accordance with Section 26 05 00.
- .2 Carry out following insulation tests using megger with 20,000 megaohm scale and resulting insulation resistance corrected to base of 20°C.
 - .1 High voltage to ground with secondary grounded for duration of test.
 - .2 Low voltage to ground with primary grounded for duration of test.
 - .3 High to low voltage.
- .3 Inspect primary and secondary connections for tightness and for signs of overheating.
- .4 Inspect and clean bushings and insulators.
- .5 Check liquid level and temperature indicators.
- .6 Set transformer taps to rated voltage as specified.
- .7 Inspect for liquid leaks and excessive rusting.
- .8 Inspect liquid level.
- .9 Check fuses for correctness of type and size.
- .10 Check for grounding and neutral continuity between primary and secondary circuits of transformer.

3.4 CLEANING

- .1 Proceed in accordance with Section 01 74 11.
- .2 On completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.