


SMALL CRAFT HARBOURS




NOTES


1. ALL ELEVATIONS ARE IN METRES UNLESS OTHERWISE NOTED.
2. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE NOTED.



DETAIL - DOCK TO DOCK CONNECTION PLATES NOTE: (ALL COMPONENTS OF CONNECTION PLATES SHALL BE GALVANIZED.)



4
10/10



PLAN - DOCK TO DOCK END CONNECTIONS



1
10/10

GENERAL NOTES

1. DO NOT SCALE FROM DRAWING.
2. ALL DIMENSIONS IN MILLIMETRES.
3. ALL ELEVATIONS IN METRES.
4. CONTRACTOR MUST VERIFY ALL DIMENSIONS AND CONDITIONS ON SITE PRIOR TO PROCEEDING WITH ANY PORTION OF THIS WORK.
5. ALL REFERENCES TO CODES AND STANDARDS SHALL BE INTERPRETED TO MEAN LATEST EDITION UNLESS NOTED OTHERWISE.

CONCRETE

1. CONCRETE COMPRESSIVE STRENGTH TO BE 35 MPa AT 28 DAYS, UNLESS NOTED OTHERWISE.
2. CONCRETE WORK TO CONFORM TO REQUIREMENTS OF CSA-STANDARD CAN3-A23.1 LATEST EDITION.
3. CONCRETE FORMWORK AND FALSEWORK MATERIALS SHALL CONFORM TO CSA A23.1.

REINFORCEMENT


1. PERFORM REINFORCING WORK IN ACCORDANCE WITH CSA 23.1.
2. REINFORCING STEEL SHALL CONFORM TO CAN/CSA G30.18, GRADE 400R OR 400W.
3. MINIMUM CONCRETE COVER TO REINFORCING STEEL TO BE IN ACCORDANCE WITH CAN3-A23.1.
4. REINFORCING STEEL TO BE 400 MPa.
5. ALL REINFORCING STEEL DETAILING AND PLACING CONFORM TO ACI MANUAL FOR DETAILING OF REINFORCED CONCRETE STRUCTURE U/N.

STRUCTURAL STEEL

1. PERFORM STRUCTURAL STEEL WORK IN ACCORDANCE WITH CAN/CSA-S16.
2. ALL FABRICATION AND WELDING SHALL CONFORM TO CSA W59 AND BE PERFORMED BY A COMPANY CERTIFIED BY AND WELDERS QUALIFIED IN ACCORDANCE WITH CSA W47.1 FOR DIVISION 1 OR DIVISION 2.1.
3. FILLET WELDS SHALL NOT BE LESS THAN 5 mm. WELDING ELECTRODES TO BE "BASIC" LOW HYDROGEN TYPE, TO CSA W48 SERIES, COMPATIBLE WITH STEEL TO BE WELDED.
4. STRUCTURAL SHAPES TO CSA G40.21, GRADE 350W.
5. STRUCTURAL PLATES TO CSA G40.21, GRADE 300W (MINIMUM).
6. HIGH TENSILE BOLTS, NUTS AND WASHERS TO ASTM A325, UNLESS NOTED OTHERWISE.
7. ANCHOR BOLTS TO ASTM F1554, GRADE 55, UNLESS NOTED OTHERWISE.

WOOD


1. ALL TIMBER TO BE TREATED TO CSA 080.



TYPICAL END ELEVATION @ CONNECTION PLATES




5
9/10



SECTION @ VERTICAL POST CONNECTION (TYP)




6
9/10




SECTION - CHAIN CONNECTION



2
5/10




TOP VIEW - FLIP PLATE



TOP VIEW - FIXED PLATE

- NOTES:
1. HINGE PIN SHALL BE 10mm galv. steel rod, length as required c/w heavy duty cotter pin.
 2. GAP PLATE TO BE SECURED TO DOCK DECK TO COVER GAP BETWEEN DOCKS WHERE DOCKS ARE JOINED TOGETHER. TWO (2) COMPLETE ASSEMBLY REQUIRED.
 3. 8-12.7mm LAG SCREWS.

DETAIL - FLOATING DOCK GAP PLATE



3
10/10



PROVINCE OF NEWFOUNDLAND AND LABRADOR
PEGA PERMIT HOLDER
 This Permit Allows
DILLON CONSULTING LIMITED
 To Practice Professional Engineering
 in Newfoundland and Labrador.
 Permit No. as issued by PEGNL D0161
 which is valid for the year 2020

0	ISSUED FOR TENDER	JUL.17 2020
B	ISSUED FOR FINAL REVIEW	APR.17 2020
A	ISSUED FOR 66% REVIEW	MAR.05 2020
revisions		date
project		project

SMALL BOAT BASIN DEVELOPMENT
 CARTWRIGHT, NL

FLOATING DOCK PLAN, ELEVATION, SECTION & DETAILS

designed C. WILLETTE concu
 date FEBRUARY 2020
 drawn P. BAILEY dessine
 date FEBRUARY 2020
 approved approve

Tender Paul Curran Submission
 DFO Project Manager
 project number no. du projet
723335
 drawing no. no. du dessin
C10 OF 11