

SPAN BALANCE ANALYSIS REPORT

Test Conducted: May 10, 2017

BURLINGTON CANAL VERTICAL LIFT BRIDGE
HAMILTON, ONTARIO
CANADA
PWGSC Project No. R.012641.001

Submitted to:

Mr. Mark Thomas
The State Group, Inc.

Submitted by:

Mr. John R. Williams
Ontario PE 100175197



Stafford Bandlow
Engineering, Inc.



Submitted: May 26, 2017

TABLE OF CONTENTS

| | Page |
|--|------|
| INTRODUCTION | 1 |
| TEST PROCEDURE AND EQUIPMENT | 1 |
| METHOD OF ANALYZING RECORDED DATA..... | 2 |
| WEATHER CONDITIONS | 3 |
| PRESENTATION OF BALANCE RESULTS..... | 4 |
| DISCUSSION OF RESULTS..... | 5 |

APPENDICES

| | |
|------------|---|
| APPENDIX A | Figures |
| APPENDIX B | Strip Chart Recordings |
| APPENDIX C | Sample Balance Calculations |
| APPENDIX D | Graphical Results |
| | Best Fit of Theoretical Imbalance Curve to Imbalance Data |

INTRODUCTION

This report details balance tests performed at the Burlington Canal Vertical Lift Bridge in Hamilton, Ontario, Canada. The tests were conducted by Stafford Bandlow Engineering, Inc. (SBE) for The State Group, Inc. to obtain the post construction balance condition of the lift span at the end of a rehabilitation project.

SBE was on site at the Burlington Canal Vertical Lift Bridge on May 10, 2017 for the purpose of performing balance tests. The tests were conducted on the span drive machinery in the North and South towers simultaneously during testing. Figure 1, Appendix A depicts a general plan of the lift span with identification of directions.

TEST PROCEDURE AND EQUIPMENT

The current tests were performed utilizing gages that were installed by SBE as part of prior balance tests at the bridge. The gages were installed as follows: Two 2-element (gage) 90 degree foil type strain gage rosettes were spot welded to each of the eight main pinion shafts that engage the sheave's ring gear. Figure 2, Appendix A depicts the layout of the span drive machinery and shows the location of the strain gage installation. A total of eight rosettes (sixteen gages) were used for each tower. Measurements Group LWK-06-W250D-350 gages were used. Surface preparation of the shaft and mounting of the gages were performed in accordance with the strain gage manufacturer's requirements. Each pair of rosettes was mounted on a circumferential line 180 degrees apart from one another. The gages from each pair of rosettes were wired in a full Wheatstone bridge; the Wheatstone bridge effectively cancels out strain on the shaft surface produced by bending and temperature changes and ensures that the indicated strain is due to torsion only. Once mounted the gages were protected for future use. The gages were checked for proper resistance and grounding prior to the current test. All gage values were found to be within an acceptable range.

Each Wheatstone bridge was hard wired via Belden twisted pair shielded cable to one channel of a four channel Somat e-DAQ-lite bridge expansion board. Figure 3, Appendix A depicts the strain gage wiring schematic. The gain for each channel was set such that the relation between the output from the system in millivolts and the shear strain at the surface of the shaft in microstrain was established. nCode's Test Control Environment software was used to capture the requisite data.

Prior to recording actual test data, the brakes were released to relieve any torsional strain in the shafts due to residual or seating torque from the span drive machinery. The motor shaft was rotated to obtain clearance on each side of the engaged main pinion teeth. Clearance was verified with a feeler gage. Once

clearance was obtained, the instruments were zeroed with the shaft torque set to zero.

Lift height was monitored through event marks indicating revolutions of the main pinion shaft. The event marks were provided by a Hall Effect sensor which monitored two diametrically opposite magnets affixed to the pinion shaft and provided a voltage output each time a magnet passed the sensor. Calculations were performed to convert revolutions of the main pinion shaft into the change in lift height in feet. Two magnets were affixed to the pinion shaft so that each event mark corresponded to 1.6 feet of lift height, and 68 events were provided for a normal full lift (109 ft.). The Hall Effect sensor readings were taken at the same tower where strain readings were recorded.

Each strain channel was sampled at a rate of 50 Hz for the duration of each bridge lift. The data was reviewed in the field at the conclusion of each bridge operation to check the integrity of the data and then saved to disk.

METHOD OF ANALYZING RECORDED DATA

Strip charts for each run from each tower of the testing are presented in Appendix B. Each strip chart contains the strain data for the four instrumented shafts in each tower versus the lift height for a complete opening cycle. The data from each test run was analyzed at incremental lift heights which corresponded to the system event marks. 100 data points centered on each event mark are summed and then averaged. In this way, any periodic fluctuations in the test data (sliding friction on the gear teeth, gear tooth impacts, etc.) are effectively filtered out. Averaged data points were then selected from the constant velocity region of each test run; the data in the accelerating and decelerating regions were discarded. The averaged data points and their corresponding lift heights were entered into a proprietary balance program and used to determine the balance condition of the lift span according to the governing balance equation. These calculations are described below.

The strain recorded in the shaft relates to the torque in the shaft according to the mechanics of the shaft geometry and material. This allows the shaft torque to be calculated from the recorded strain data. Then the ratio between the main pinion and the sheave trunnion is used to convert main pinion shaft torque to sheave trunnion torque. An efficiency factor is used to account for the frictional losses between the rack pinion shaft and the sheave trunnion. This factor is calculated using the machinery losses and efficiency coefficients provided in the Canadian Highway Bridge Design Code, CAN/CSA-S6-06 (hereafter referred to as CHBDC) Table 13.8. The sheave trunnion torque was then converted to an equivalent force at the main counterweight ropes using the pitch radius of the ropes.

The imbalance force was determined in the following manner: For a given span position the imbalance assists the machinery in one direction (raise or lower) and resists the machinery in the opposite direction. Friction always opposes the machinery. Therefore, the summation of the raising and lowering force at a given lift height divided by two is equal to the span imbalance force at that lift height. This assumes that the friction is equal in both directions. Since there is no reasonable way to determine the true system friction this assumption must be made.

The span balance changes with lift height as a result of the main counterweight ropes passing over the counterweight sheaves and due to the effect of the auxiliary counterweight system. A mathematical equation for the theoretical change in span balance versus lift height due to both factors was derived based on the geometry and weights provided on the original design drawings, with two noteworthy exceptions.

1. The weight of each auxiliary counterweight has been modified from 18,000 lbs. as indicated on the design drawings to 18,500 lbs. in accordance with changes during a 2002-2003 main counterweight rope replacement project.
2. The weight of the main counterweight ropes has been taken as 8.51 lbs. per linear foot in accordance with standard rope manufacturer's information.

The mathematical equation is used in a curve-fitting program to determine the best fit of the theoretical imbalance curve to the imbalance data. The fitted imbalance curve is then used to determine the imbalance at the fully lowered position. Actual imbalance data cannot be obtained in the lowered position due to the acceleration torque. Sample calculations utilizing the balance equation are presented in Appendix C. Figure 4, Appendix A, identifies the auxiliary counterweight system variables used in the balance equation.

WEATHER CONDITIONS

The weather on May 10, 2017 was clear and dry with a mean temperature of 46°F. The average wind speed reported at the Hamilton, ON weather station was 3 MPH with gusts up to 6 MPH at the time of the testing.

PRESENTATION OF BALANCE RESULTS

The following table documents the balance condition for each corner of the lift span. The table presents the seated imbalance (i.e. imbalance with span fully seated) as well as the friction force, which is also determined as part of the analysis. The individual results from each of three test runs are provided with the averages of the three test runs.

| Burlington Canal Lift Bridge | | | | | | |
|-------------------------------------|-------------------------------|------------------|------------------|-------------------------------|------------------|------------------|
| North Tower | | | | | | |
| Test Date: May 10, 2017 | | | | | | |
| Run | Seated Imbalance (lb.) | | | Average Friction (lb.) | | |
| | NW Corner | NE Corner | North End | NW Corner | NE Corner | North End |
| 1 | +4,539 | +2,868 | +7,407 | +2,857 | +2,873 | +5,731 |
| 2 | +6,285 | +1,226 | +7,512 | +3,319 | +2,485 | +5,804 |
| 3 | +6,559 | +871 | +7,430 | +3,442 | +2,314 | +5,756 |
| Average | +5,794 | +1,655 | +7,450 | +3,206 | +2,557 | +5,764 |

| Burlington Canal Lift Bridge | | | | | | |
|-------------------------------------|-------------------------------|------------------|------------------|-------------------------------|------------------|------------------|
| South Tower | | | | | | |
| Test Date: May 10, 2017 | | | | | | |
| Run | Seated Imbalance (lb.) | | | Average Friction (lb.) | | |
| | SW Corner | SE Corner | South End | SW Corner | SE Corner | South End |
| 1 | +5,050 | +1,241 | +6,291 | +3,768 | +1,908 | +5,676 |
| 2 | +2,428 | +3,971 | +6,399 | +3,119 | +2,677 | +5,796 |
| 3 | +225 | +5,974 | +6,199 | +2,628 | +3,064 | +5,692 |
| Average | +2,568 | +3,729 | +6,296 | +3,172 | +2,550 | +5,721 |

Note: Positive (+) imbalance indicates span heavy.
 Negative (-) imbalance indicates counterweight heavy.

The fitted imbalance curves which yield the above results are presented in Appendix D. Each graph contains the best fit of the theoretical imbalance curve to the imbalance data, the opening force, the closing force and the friction force relative to the main counterweight ropes.

DISCUSSION OF RESULTS

The Specifications establish requirements for final balance as follows:

“Make any necessary adjustment to the counterweights required to achieve a balance condition equal to that measured prior to construction (plus or minus 5%).”

The following table summarizes the average seated imbalance per tower at the time of the initial test on April 22, 2015 and at the time of the post construction test on May 10, 2017:

| Burlington Canal Lift Bridge Results Comparison | | |
|--|---------------------------------------|--------------------|
| Test Date | Average Seated Imbalance (lb.) | |
| | North Tower | South Tower |
| April 22, 2015 | +7,452 | +6,265 |
| May 10, 2017 | +7,450 | +6,296 |
| % Difference | -0.03% | 0.49% |


The post construction balance condition of each end of the lift span is within 0.5% of the balance condition prior to construction, which is well within the acceptance criteria in the Specifications.

APPENDIX A

Figures



NORTH
TOWER



LIFT
SPAN

NE
Corner



SE
Corner

NW
Corner

SW
Corner



SOUTH
TOWER



OPERATOR'S
HOUSE


Figure 1. Plan View of Movable Span

Project:

Burlington Canal Lift Bridge
Hamilton, Ontario
Strain Gage Imbalance Tests

Prepared by:


Stafford Bandlow Engineering, Inc.



- NOTES:
1. ROPE PITCH DIA. ON SHEAVE = 15'
 2. RATIO RACK PINION/RING GEAR = 14.74
 3. RATIO SECONDARY REDUCER = 4.21

**NORTH TOWER SHOWN
(SOUTH TOWER SIMILAR)**

| | |
|---|---|
| <p>Figure 2. Location of Strain Gage Installation and Event Mark Recording</p> | |
| <p>Project:</p> | <p>Burlington Canal Lift Bridge Hamilton, Ontario Strain Gage Imbalance Tests</p> |
| <p>Prepared by:</p> | <p>Stafford Bandlow Engineering, Inc.</p> |




Project:

**Burlington Canal Lift Bridge
Hamilton, Ontario
Strain Gage Imbalance Tests**

Prepared by:

Stafford Bandlow Engineering, Inc.

Figure 3. Strain Gage Wiring Schematic



$X_{AUX} = 23.167 \text{ ft.}$
 $Y_{AUX} = 48.286 \text{ ft.}$
 $R_{AUX} = 2.5 \text{ ft.}$

Figure 4. Auxiliary Counterweight Machinery

Project:

Burlington Canal Lift Bridge
 Hamilton, Ontario, Canada
 Strain Gage Imbalance Tests


Prepared by:

Stafford Bandlow Engineering, Inc.


APPENDIX B

Strip Chart Recordings


Burlington Canal Lift Bridge North Tower Test Run 1




Burlington Canal Lift Bridge North Tower Test Run 2




Burlington Canal Lift Bridge North Tower Test Run 3




Burlington Canal Lift Bridge South Tower Test Run 1



Burlington Canal Lift Bridge South Tower Test Run 2



Burlington Canal Lift Bridge South Tower Test Run 3



APPENDIX C

Sample Balance Calculations

Burlington Lift Bridge Sample Calculations

Prepared By: JRW

Checked By: RST

Governing Equation
(for each corner)

$$IMB_i = \left[\begin{aligned} & \text{Imbalance}_{set} + \left[-2 \cdot (\text{corner} \cdot \text{Ropes} \cdot \text{Mass}_{unit}) \cdot \text{height}_i \right] \dots \\ & + \text{corner} \cdot (-1) \cdot F_{cwt} \cdot \sin \left[\text{atan} \left(\frac{y_{aux} - \text{height}_i}{x_{aux}} \right) \right] + \text{asin} \left[\frac{R_{aux}}{x_{aux} \cdot \cos \left(\text{atan} \left(\frac{y_{aux} - \text{height}_i}{x_{aux}} \right) \right)} \right] \end{aligned} \right]$$



Known:

$F_{cwt} := 18500$ $\text{Ropes} := 20$ $\text{corner} = 2$ $x_{aux} := 23.167$
 $\text{Mass}_{unit} := 8.51$ $R_{aux} := 2.5$ $y_{aux} := 48.286$

Reference Figure 4 for identification of X_{AUX} , Y_{AUX} , R_{AUX} .



Input Data from strip charts:

Note: For presentation, a limited portion of the data used in the calculation is shown below. A total of 69 data points are used in the analysis.

| | | | | | | | | | | | |
|---------|----|----|---------------------|--------|-------|---------------------|----|-------|---------------------|-------|-------|
| | 0 | | 0 | | 0 | | 0 | | 0 | | |
| | 0 | 0 | 0 | 35.5 | 0 | 34.97 | 0 | 9.36 | 0 | 1.48 | |
| | 1 | 1 | 1 | 40.99 | 1 | 39.07 | 1 | 12.5 | 1 | 5.31 | |
| | 2 | 2 | 2 | 102.51 | 2 | 100.99 | 2 | 74.63 | 2 | 65.37 | |
| | 3 | 3 | 3 | 31.75 | 3 | 30.35 | 3 | 12.21 | 3 | 4.7 | |
| | 4 | 4 | 4 | 29.8 | 4 | 29.31 | 4 | 12.2 | 4 | 4.7 | |
| | 5 | 5 | 5 | 31 | 5 | 29.47 | 5 | 10.39 | 5 | 3.23 | |
| | 6 | 6 | 6 | 27.59 | 6 | 27.18 | 6 | 11.21 | 6 | 3.78 | |
| event = | 7 | 7 | CH1 _{op} = | 7 | 27.42 | CH2 _{op} = | 7 | 9.05 | CH3 _{op} = | 7 | 1.63 |
| | 8 | 8 | | 8 | 24.95 | | 8 | 7.72 | | 8 | -0.36 |
| | 9 | 9 | | 9 | 21.73 | | 9 | 8.53 | | 9 | 0.97 |
| | 10 | 10 | | 10 | 19.68 | | 10 | 7.73 | | 10 | -0.23 |
| | 11 | 11 | | 11 | 16.94 | | 11 | 7.49 | | 11 | -0.18 |
| | 12 | 12 | | 12 | 13.84 | | 12 | 7.26 | | 12 | -0.76 |
| | 13 | 13 | | 13 | 12.37 | | 13 | 7.17 | | 13 | -0.44 |
| | 14 | 14 | | 14 | 9.8 | | 14 | 7.43 | | 14 | -0.79 |
| | 15 | 15 | | 15 | 7.94 | | 15 | 7.14 | | 15 | -0.09 |

Burlington Lift Bridge Sample Calculations

Prepared By: JRW

Checked By: RST

| | |
|-----------------------|-------|
| | 0 |
| 0 | 6.85 |
| 1 | 36.67 |
| 2 | 5.37 |
| 3 | 3.49 |
| 4 | 1.8 |
| 5 | 1.48 |
| 6 | 49.43 |
| CH1 _{cl} = 7 | -1.13 |
| 8 | -1.43 |
| 9 | -1.5 |
| 10 | -2.03 |
| 11 | -2.1 |
| 12 | -3.68 |
| 13 | -2.88 |
| 14 | -5.42 |
| 15 | -4.32 |

| | |
|-----------------------|-------|
| | 0 |
| 0 | 6.21 |
| 1 | 35.04 |
| 2 | 4.78 |
| 3 | 2.54 |
| 4 | 1.18 |
| 5 | 0.58 |
| 6 | 49.27 |
| CH2 _{cl} = 7 | -1.74 |
| 8 | -1.91 |
| 9 | -2.02 |
| 10 | -2.53 |
| 11 | -2.6 |
| 12 | -4.26 |
| 13 | -3.31 |
| 14 | -6.01 |
| 15 | -5.01 |

| | |
|-----------------------|--------|
| | 0 |
| 0 | -6.42 |
| 1 | 15.91 |
| 2 | 4.61 |
| 3 | 2.56 |
| 4 | 0.65 |
| 5 | -3.72 |
| 6 | 39.4 |
| CH3 _{cl} = 7 | -7.15 |
| 8 | -9.52 |
| 9 | -13.08 |
| 10 | -15.9 |
| 11 | -18.31 |
| 12 | -19.56 |
| 13 | -22.63 |
| 14 | -21.07 |
| 15 | -25.87 |

| | |
|-----------------------|--------|
| | 0 |
| 0 | -11.91 |
| 1 | 10.24 |
| 2 | -1.84 |
| 3 | -2.68 |
| 4 | -5 |
| 5 | -9.49 |
| 6 | 32.38 |
| CH4 _{cl} = 7 | -12.34 |
| 8 | -15.35 |
| 9 | -18.83 |
| 10 | -22.03 |
| 11 | -24.12 |
| 12 | -25.86 |
| 13 | -28.52 |
| 14 | -27.73 |
| 15 | -31.18 |

$$\text{height} := \text{event} \cdot \left[\frac{\pi \cdot 15}{\left(\frac{280}{19}\right)} \cdot \frac{1}{2} \right]$$

This operation converts the event marks to lift height in feet (2 event marks per revolution of the rack pinion shaft).

The following variables will be used:

- G = shear modulus of shaft material (11,500,000 psi for steel)
- J = polar moment of inertia
- R = total ratio from gages to trunnion including rack and pinion
- Ro = radius to outside of shaft on which gages are mounted
- Ri = radius of hole through shaft (if applicable)
- Ratio = Ratio from pinion to rack
- Radius to ropes = Rope pitch radius on sheave
- n = efficiency from gages to trunnion

$$G := 11.5$$

$$R_o := \frac{6.5}{2}$$

$$R_i := \frac{0}{2}$$

$$J := \frac{\pi}{2} \cdot (R_o^4 - R_i^4)$$

These calculations are the proprietary information of Stafford Bandlow Engineering, Inc. As such these calculations are not for general circulation and shall not be used without the express written consent of Stafford Bandlow Engineering, Inc.

Burlington Lift Bridge Sample Calculations

Prepared By: JRW

Checked By: RST

Solve for Torque in shaft on which gages are located:

TOS = opening torque in the shaft on which the gages are mounted

TCS = closing torque in the shaft on which the gages are mounted

$$TOS_{ch1} := G \cdot \frac{J}{R_o} \cdot CH1_{op} \cdot \frac{1}{12}$$

$$TCS_{ch1} := G \cdot \frac{J}{R_o} \cdot CH1_{cl} \cdot \frac{1}{12}$$

$$TOS_{ch2} := G \cdot \frac{J}{R_o} \cdot CH2_{op} \cdot \frac{1}{12}$$

$$TCS_{ch2} := G \cdot \frac{J}{R_o} \cdot CH2_{cl} \cdot \frac{1}{12}$$

$$TOS_{ch3} := G \cdot \frac{J}{R_o} \cdot CH3_{op} \cdot \frac{1}{12}$$

$$TCS_{ch3} := G \cdot \frac{J}{R_o} \cdot CH3_{cl} \cdot \frac{1}{12}$$

$$TOS_{ch4} := G \cdot \frac{J}{R_o} \cdot CH4_{op} \cdot \frac{1}{12}$$

$$TCS_{ch4} := G \cdot \frac{J}{R_o} \cdot CH4_{cl} \cdot \frac{1}{12}$$

Solve for Force at Ropes to produce recorded torques

FOS = opening force at ropes

FCS = closing force at ropes

Ratio = Ratio from pinion to rack

Radius to ropes = Rope pitch radius on sheave

n = efficiency from gages to trunnion

$$\text{Ratio} := \frac{280}{19}$$

$$\text{Radius}_{\text{toropes}} := \frac{15}{2}$$

$$n := .98$$

$$FOS_{ch1} := TOS_{ch1} \cdot \left(\frac{\text{Ratio} \cdot n}{\text{Radius}_{\text{toropes}}} \right)$$

$$FOS_{ch2} := TOS_{ch2} \cdot \left(\frac{\text{Ratio} \cdot n}{\text{Radius}_{\text{toropes}}} \right)$$

$$FCS_{ch1} := TCS_{ch1} \cdot \left(\frac{\text{Ratio} \cdot n}{\text{Radius}_{\text{toropes}}} \right)$$

$$FCS_{ch2} := TCS_{ch2} \cdot \left(\frac{\text{Ratio} \cdot n}{\text{Radius}_{\text{toropes}}} \right)$$

$$FOS_{ch3} := TOS_{ch3} \cdot \left(\frac{\text{Ratio} \cdot n}{\text{Radius}_{\text{toropes}}} \right)$$

$$FOS_{ch4} := TOS_{ch4} \cdot \left(\frac{\text{Ratio} \cdot n}{\text{Radius}_{\text{toropes}}} \right)$$

$$FCS_{ch3} := TCS_{ch3} \cdot \left(\frac{\text{Ratio} \cdot n}{\text{Radius}_{\text{toropes}}} \right)$$

$$FCS_{ch4} := TCS_{ch4} \cdot \left(\frac{\text{Ratio} \cdot n}{\text{Radius}_{\text{toropes}}} \right)$$

$$FO := FOS_{ch1} + FOS_{ch2} + FOS_{ch3} + FOS_{ch4}$$

$$FC := FCS_{ch1} + FCS_{ch2} + FCS_{ch3} + FCS_{ch4}$$

$$\text{Imb}_{\text{total}} := \frac{FO + FC}{2}$$

$$\text{Friction} := \frac{FO - FC}{2}$$

These calculations are the proprietary information of Stafford Bandlow Engineering, Inc. As such these calculations are not for general circulation and shall not be used without the express written consent of Stafford Bandlow Engineering, Inc.

Burlington Lift Bridge Sample Calculations

Prepared By: RW

Checked By: RST

Equation for the fitting curve:

$$F(\text{Imbalance}_{\text{set}}, \text{height}) := \left[\begin{array}{l} \text{Imbalance}_{\text{set}} + [-2 \cdot \text{corner} \cdot (\text{Ropes} \cdot \text{Mass}_{\text{unit}}) \cdot \text{height}] \dots \\ + \text{corner} \cdot (-1) \cdot F_{\text{cwt}} \cdot \sin \left[\text{atan} \left(\frac{y_{\text{aux}} - \text{height}}{x_{\text{aux}}} \right) \right] + \text{asin} \left[\frac{R_{\text{aux}}}{x_{\text{aux}}} \right] \cdot \cos \left(\text{atan} \left(\frac{y_{\text{aux}} - \text{height}}{x_{\text{aux}}} \right) \right) \end{array} \right]_{i=12 \dots \text{length}(\text{height}) - 11}$$

$i := 12 \dots \text{length}(\text{height}) - 11$ i is a range variable for the number of rows in the above matrices. The points

$$\text{SSE}(\text{Imbalance}_{\text{set}}) := \sum_i (\text{Imb}_{\text{total}_i} - F(\text{Imbalance}_{\text{set}}, \text{height}_i))^2$$

$\text{Imbalance}_{\text{set}} := 50000$, initial guess

Given

$\text{SSE}(\text{Imbalance}_{\text{set}}) = 0$

$\text{Imbalance}_{\text{set}} := \text{MinErr}(\text{Imbalance}_{\text{set}})$

$\text{Imbalance}_{\text{set}} = 41698.145$, Solution

$\text{height} := 0$

$$\text{Imbalance}_{\text{ini}} := \left[\begin{array}{l} \text{Imbalance}_{\text{set}} + [-2 \cdot (\text{corner} \cdot \text{Ropes} \cdot \text{Mass}_{\text{unit}}) \cdot \text{height}] \dots \\ + \text{corner} \cdot (-1) \cdot F_{\text{cwt}} \cdot \sin \left[\text{atan} \left(\frac{y_{\text{aux}} - \text{height}}{x_{\text{aux}}} \right) \right] + \text{asin} \left[\frac{R_{\text{aux}}}{x_{\text{aux}}} \right] \cdot \cos \left(\text{atan} \left(\frac{y_{\text{aux}} - \text{height}}{x_{\text{aux}}} \right) \right) \end{array} \right]_{i=12 \dots \text{length}(\text{height}) - 11}$$

$\text{Imbalance}_{\text{ini}} = 7628$

$\text{mean}(\text{Friction}) = 4518$

Positive imbalance indicates bridge is span heavy.

Negative imbalance indicates bridge is counterweight heavy.

APPENDIX D

Graphical Results

Best Fit of Theoretical Imbalance Curve to Imbalance Data

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

TOWER = "North Tower"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 1"



Average
100 Points

Analyze
height_{min} = 17.6
height_{max} = 94.3

- xxx Imbalance Force - Data Points
- ddd Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{ini} := \left[\text{Imbalance}_{set} + \left[-2 \cdot (\text{corners} \cdot \text{Ropes} \cdot \text{Mass}_{unit}) \cdot \text{height}_{ini} \right] \dots \right. \\
 \left. + \left[\text{corners} \cdot \left[-F_{cwt} \cdot \left[\sin \left[\text{atan} \left(\frac{y_{aux} - \text{height}_{ini}}{x_{aux}} \right) \right] + \text{asin} \left[\frac{R_{aux}}{\left(\frac{x_{aux}}{\cos \left(\text{atan} \left(\frac{y_{aux} - \text{height}_{ini}}{x_{aux}} \right) \right)} \right)} \right]} \right] \right] \right] \right]$$

Imbalance_{ini} = 7407 Friction_{ave} = 5731

Positive imbalance indicates bridge is span heavy.
 Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

Corner1 = "NW Corner"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 1"



Average
100 Points

Analyze
height_{min} = 17.6
height_{max} = 94.3

- ××× Imbalance Force - Data Points
- ◇◇◇ Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{\text{iniC1}} := \left[\text{Imbalance}_{\text{setC1}} + \left[-2 \cdot (\text{Ropes} \cdot \text{Mass}_{\text{unit}}) \cdot \text{height}_{\text{ini}} \right] \dots \right. \\ \left. + \text{corner} \cdot \left[(-1) \cdot F_{\text{cwt}} \cdot \sin \left[\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right] + \text{asin} \left[\frac{R_{\text{aux}}}{\left(\frac{x_{\text{aux}}}{\cos \left(\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right) \right)} \right]} \right] \right]$$

Imbalance_{iniC1} = 4539

Friction_{aveC1} = 2857

Positive imbalance indicates bridge is span heavy.

Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

Corner2 = "NE Corner"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 1"



Average
100 Points

Analyze
height_{min} = 17.6
height_{max} = 94.3

- xxx Imbalance Force - Data Points
- ddd Opening Force - Data Points
- +++ Closing Force - Data Points
- Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{\text{iniC2}} := \left[\text{Imbalance}_{\text{setC2}} + \left[-2 \cdot (\text{Ropes} \cdot \text{Mass}_{\text{unit}}) \cdot \text{height}_{\text{ini}} \right] \dots \right. \\ \left. + \text{corner} \cdot \left[(-1) \cdot F_{\text{cwt}} \cdot \left[\sin \left[\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right] + \text{asin} \left[\frac{R_{\text{aux}}}{\left(\frac{x_{\text{aux}}}{\cos \left(\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right) \right)} \right]} \right] \right] \right]$$

Imbalance_{iniC2} = 2868

Friction_{aveC2} = 2873

Positive imbalance indicates bridge is span heavy.

Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

TOWER = "North Tower"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 2"



Average
100 Points

Analyze
height_{min} = 17.6
height_{max} = 94.3

- xxx Imbalance Force - Data Points
- ddd Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{ini} := \left[\text{Imbalance}_{set} + \left[-2 \cdot (\text{corners} \cdot \text{Ropes} \cdot \text{Mass}_{unit}) \cdot \text{height}_{ini} \right] \dots \right. \\
 \left. + \left[\text{corners} \cdot \left[-F_{cwt} \cdot \left[\sin \left[\text{atan} \left(\frac{y_{aux} - \text{height}_{ini}}{x_{aux}} \right) \right] + \text{asin} \left[\frac{R_{aux}}{\left(\frac{x_{aux}}{\cos \left(\text{atan} \left(\frac{y_{aux} - \text{height}_{ini}}{x_{aux}} \right) \right)} \right)} \right]} \right] \right] \right] \right]$$

Imbalance_{ini} = 7512 Friction_{ave} = 5804

Positive imbalance indicates bridge is span heavy.
 Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

Corner1 = "NW Corner"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 2"



Average
100 Points

Analyze
height_{min} = 17.6
height_{max} = 94.3

- ××× Imbalance Force - Data Points
- ◇◇◇ Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{\text{iniC1}} := \left[\text{Imbalance}_{\text{setC1}} + \left[-2 \cdot (\text{Ropes} \cdot \text{Mass}_{\text{unit}}) \cdot \text{height}_{\text{ini}} \right] \dots \right. \\ \left. + \text{corner} \cdot \left[(-1) \cdot F_{\text{cwt}} \cdot \sin \left[\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right] + \text{asin} \left[\frac{R_{\text{aux}}}{\left(\frac{x_{\text{aux}}}{\cos \left(\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right) \right)} \right]} \right] \right]$$

Imbalance_{iniC1} = 6285

Friction_{aveC1} = 3319

Positive imbalance indicates bridge is span heavy.

Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

Corner2 = "NE Corner"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 2"



Average
100 Points

Analyze
height_{min} = 17.6
height_{max} = 94.3

- ××× Imbalance Force - Data Points
- ◇◇◇ Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{\text{iniC2}} := \left[\text{Imbalance}_{\text{setC2}} + \left[-2 \cdot (\text{Ropes} \cdot \text{Mass}_{\text{unit}}) \cdot \text{height}_{\text{ini}} \right] \dots \right. \\ \left. + \text{corner} \cdot \left[(-1) \cdot F_{\text{cwt}} \cdot \left[\sin \left[\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right] + \text{asin} \left[\frac{R_{\text{aux}}}{\left(\frac{x_{\text{aux}}}{\cos \left(\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right) \right)} \right]} \right] \right] \right]$$

Imbalance_{iniC2} = 1226

Friction_{aveC2} = 2485

Positive imbalance indicates bridge is span heavy.

Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

TOWER = "North Tower"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 3"



Average
100 Points

Analyze
height_{min} = 11.2
height_{max} = 97.5

- ××× Imbalance Force - Data Points
- ◇◇◇ Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{ini} := \left[\text{Imbalance}_{set} + \left[-2 \cdot (\text{corners} \cdot \text{Ropes} \cdot \text{Mass}_{unit}) \cdot \text{height}_{ini} \right] \dots \right. \\
 \left. + \left[\text{corners} \cdot \left[-F_{cwt} \cdot \left[\sin \left[\text{atan} \left(\frac{y_{aux} - \text{height}_{ini}}{x_{aux}} \right) \right] + \text{asin} \left[\frac{R_{aux}}{\left(\frac{x_{aux}}{\cos \left(\text{atan} \left(\frac{y_{aux} - \text{height}_{ini}}{x_{aux}} \right) \right)} \right)} \right]} \right] \right] \right] \right]$$

Imbalance_{ini} = 7430 Friction_{ave} = 5756

Positive imbalance indicates bridge is span heavy.
 Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

Corner1 = "NW Corner"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 3"



Average
100 Points

Analyze
height_{min} = 11.2
height_{max} = 97.5

- ××× Imbalance Force - Data Points
- ◇◇◇ Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{\text{iniC1}} := \left[\text{Imbalance}_{\text{setC1}} + \left[-2 \cdot (\text{Ropes} \cdot \text{Mass}_{\text{unit}}) \cdot \text{height}_{\text{ini}} \right] \dots \right. \\ \left. + \text{corner} \cdot \left[(-1) \cdot F_{\text{cwt}} \cdot \left[\sin \left[\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right] + \text{asin} \left[\frac{R_{\text{aux}}}{\left(\frac{x_{\text{aux}}}{\cos \left(\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right) \right)} \right]} \right] \right] \right]$$

Imbalance_{iniC1} = 6559

Friction_{aveC1} = 3442

Positive imbalance indicates bridge is span heavy.

Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

Corner2 = "NE Corner"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 3"



Average
100 Points

Analyze
height_{min} = 11.2
height_{max} = 97.5

- ××× Imbalance Force - Data Points
- ◇◇◇ Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{\text{iniC2}} := \left[\text{Imbalance}_{\text{setC2}} + \left[-2 \cdot (\text{Ropes} \cdot \text{Mass}_{\text{unit}}) \cdot \text{height}_{\text{ini}} \right] \dots \right. \\ \left. + \text{corner} \cdot \left[(-1) \cdot F_{\text{cwt}} \cdot \sin \left[\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right] + \text{asin} \left[\frac{R_{\text{aux}}}{\left(\frac{x_{\text{aux}}}{\cos \left(\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right) \right)} \right] \right] \right]$$

Imbalance_{iniC2} = 871

Friction_{aveC2} = 2314

Positive imbalance indicates bridge is span heavy.

Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

TOWER = "South Tower"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 1"



- ××× Imbalance Force - Data Points
- ◇◇◇ Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

$height_{ini} := 0$

$$Imbalance_{ini} := \left[\begin{array}{l} Imbalance_{set} + \left[-2 \cdot (corners \cdot Ropes \cdot Mass_{unit}) \cdot height_{ini} \right] \dots \\ + \left[\begin{array}{l} corners \cdot \left[-F_{cwt} \cdot \left[\sin \left[\operatorname{atan} \left(\frac{y_{aux} - height_{ini}}{x_{aux}} \right) \right] + \operatorname{asin} \left[\frac{R_{aux}}{\left(\frac{x_{aux}}{\cos \left(\operatorname{atan} \left(\frac{y_{aux} - height_{ini}}{x_{aux}} \right) \right)} \right)} \right] \right] \right] \end{array} \right] \end{array} \right]$$

$Imbalance_{ini} = 6291$ $Friction_{ave} = 5676$

Positive imbalance indicates bridge is span heavy.
 Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

Corner1 = "SW Corner"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 1"



Average
100 Points

Analyze
height_{min} = 9.6
height_{max} = 97.5

- ××× Imbalance Force - Data Points
- ◇◇◇ Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{\text{iniC1}} := \left[\text{Imbalance}_{\text{setC1}} + \left[-2 \cdot (\text{Ropes} \cdot \text{Mass}_{\text{unit}}) \cdot \text{height}_{\text{ini}} \right] \dots \right. \\ \left. + \text{corner} \cdot \left[(-1) \cdot F_{\text{cwt}} \cdot \sin \left[\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right] + \text{asin} \left[\frac{R_{\text{aux}}}{\left(\frac{x_{\text{aux}}}{\cos \left(\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right) \right)} \right]} \right] \right]$$

Imbalance_{iniC1} = 5050

Friction_{aveC1} = 3768

Positive imbalance indicates bridge is span heavy.

Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

Corner2 = "SE Corner"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 1"



Average
100 Points

Analyze
height_{min} = 9.6
height_{max} = 97.5

- ××× Imbalance Force - Data Points
- ◇◇◇ Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{\text{iniC2}} := \left[\text{Imbalance}_{\text{setC2}} + \left[-2 \cdot (\text{Ropes} \cdot \text{Mass}_{\text{unit}}) \cdot \text{height}_{\text{ini}} \right] \dots \right. \\ \left. + \text{corner} \cdot \left[(-1) \cdot F_{\text{cwt}} \cdot \left[\sin \left[\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right] + \text{asin} \left[\frac{R_{\text{aux}}}{\left(\frac{x_{\text{aux}}}{\cos \left(\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right) \right)} \right]} \right] \right] \right]$$

Imbalance_{iniC2} = 1241

Friction_{aveC2} = 1908

Positive imbalance indicates bridge is span heavy.

Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

TOWER = "South Tower"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 2"



Average
100 Points

Analyze
height_{min} = 9.6
height_{max} = 97.5

- xxx Imbalance Force - Data Points
- ddd Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{ini} := \left[\text{Imbalance}_{set} + \left[-2 \cdot (\text{corners} \cdot \text{Ropes} \cdot \text{Mass}_{unit}) \cdot \text{height}_{ini} \right] \dots \right.$$

$$\left. + \left[\text{corners} \cdot \left[-F_{cwt} \cdot \left[\sin \left[\text{atan} \left(\frac{y_{aux} - \text{height}_{ini}}{x_{aux}} \right) \right] + \text{asin} \left[\frac{R_{aux}}{\left(\frac{x_{aux}}{\cos \left(\text{atan} \left(\frac{y_{aux} - \text{height}_{ini}}{x_{aux}} \right) \right)} \right)} \right]} \right] \right] \right] \right]$$

Imbalance_{ini} = 6399
Friction_{ave} = 5796

Positive imbalance indicates bridge is span heavy.
 Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

Corner1 = "SW Corner"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 2"



Average
100 Points

Analyze
height_{min} = 9.6
height_{max} = 97.5

- ××× Imbalance Force - Data Points
- ◇◇◇ Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{\text{iniC1}} := \left[\text{Imbalance}_{\text{setC1}} + \left[-2 \cdot (\text{Ropes} \cdot \text{Mass}_{\text{unit}}) \cdot \text{height}_{\text{ini}} \right] \dots \right. \\ \left. + \text{corner} \cdot \left[(-1) \cdot F_{\text{cwt}} \cdot \sin \left[\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right] + \text{asin} \left[\frac{R_{\text{aux}}}{\left(\frac{x_{\text{aux}}}{\cos \left(\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right) \right)} \right]} \right] \right]$$

Imbalance_{iniC1} = 2428

Friction_{aveC1} = 3119

Positive imbalance indicates bridge is span heavy.

Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

Corner2 = "SE Corner"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 2"



Average
100 Points

Analyze
height_{min} = 9.6
height_{max} = 97.5

- ××× Imbalance Force - Data Points
- ◇◇◇ Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{\text{iniC2}} := \left[\text{Imbalance}_{\text{setC2}} + \left[-2 \cdot (\text{Ropes} \cdot \text{Mass}_{\text{unit}}) \cdot \text{height}_{\text{ini}} \right] \dots \right. \\
 \left. + \text{corner} \cdot \left[(-1) \cdot F_{\text{cwt}} \cdot \sin \left[\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right] + \text{asin} \left[\frac{R_{\text{aux}}}{\left(\frac{x_{\text{aux}}}{\cos \left(\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right) \right)} \right]} \right] \right]$$

Imbalance_{iniC2} = 3971

Friction_{aveC2} = 2677

Positive imbalance indicates bridge is span heavy.

Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

TOWER = "South Tower"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 3"



Average
100 Points

Analyze
height_{min} = 9.6
height_{max} = 97.5

- xxx Imbalance Force - Data Points
- ddd Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{ini} := \left[\text{Imbalance}_{set} + \left[-2 \cdot (\text{corners} \cdot \text{Ropes} \cdot \text{Mass}_{unit}) \cdot \text{height}_{ini} \right] \dots \right. \\
 \left. + \left[\text{corners} \cdot \left[-F_{cwt} \cdot \left[\sin \left[\text{atan} \left(\frac{y_{aux} - \text{height}_{ini}}{x_{aux}} \right) \right] + \text{asin} \left[\frac{R_{aux}}{\left(\frac{x_{aux}}{\cos \left(\text{atan} \left(\frac{y_{aux} - \text{height}_{ini}}{x_{aux}} \right) \right)} \right)} \right]} \right] \right] \right] \right]$$

Imbalance_{ini} = 6199 Friction_{ave} = 5692

Positive imbalance indicates bridge is span heavy.
Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

Corner1 = "SW Corner"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 3"



Average
100 Points

Analyze
height_{min} = 9.6
height_{max} = 97.5

- ××× Imbalance Force - Data Points
- ◇◇◇ Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{\text{iniC1}} := \left[\text{Imbalance}_{\text{setC1}} + \left[-2 \cdot (\text{Ropes} \cdot \text{Mass}_{\text{unit}}) \cdot \text{height}_{\text{ini}} \right] \dots \right. \\ \left. + \text{corner} \cdot \left[(-1) \cdot F_{\text{cwt}} \cdot \sin \left[\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right] + \text{asin} \left[\frac{R_{\text{aux}}}{\left(\frac{x_{\text{aux}}}{\cos \left(\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right) \right)} \right]} \right] \right]$$

Imbalance_{iniC1} = 225

Friction_{aveC1} = 2628

Positive imbalance indicates bridge is span heavy.

Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height


BRIDGE = "Burlington Canal Lift Bridge"

BRIDGE_TYPE = "Tower Drive Vertical Lift"

Corner2 = "SE Corner"

TEST_DATE = "May 10, 2017"

TEST_ID = "Run 3"



Average
100 Points

Analyze
height_{min} = 9.6
height_{max} = 97.5

- ××× Imbalance Force - Data Points
- ◇◇◇ Opening Force - Data Points
- +++ Closing Force - Data Points
- - - Imbalance Force - Fitted Curve
- Friction

height_{ini} := 0

$$\text{Imbalance}_{\text{iniC2}} := \left[\text{Imbalance}_{\text{setC2}} + \left[-2 \cdot (\text{Ropes} \cdot \text{Mass}_{\text{unit}}) \cdot \text{height}_{\text{ini}} \right] \dots \right. \\
 \left. + \text{corner} \cdot \left[(-1) \cdot F_{\text{cwt}} \cdot \sin \left[\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right] + \text{asin} \left[\frac{R_{\text{aux}}}{\left(\frac{x_{\text{aux}}}{\cos \left(\text{atan} \left(\frac{y_{\text{aux}} - \text{height}_{\text{ini}}}{x_{\text{aux}}} \right) \right) \right)} \right] \right] \right]$$

Imbalance_{iniC2} = 5974

Friction_{aveC2} = 3064

Positive imbalance indicates bridge is span heavy.


Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height

BRIDGE= "Burlington Canal Lift Bridge"
 TOWER = "North Tower"
 TEST_DATE = "May 10, 2017"

BRIDGE_TYPE= "Tower Drive Vertical Lift"
 TEST_ID = "Average Imbalance"



Average
100 Points
 Analyze
 height_{min} = 9.6
 height_{max} = 97.5

- xxx Imbalance Force - Averaged Data Points of Final Test
- - - Imbalance Force - Fitted Curve of Final Test for Avg. Data
- +5% Imbalance Force - Initial Test Fitted Curve - Avg. Data
- -5% Imbalance Force - Initial Test Fitted Curve - Avg. Data

height_{ini} := 0

$$\text{Imbalance}_{ini} := \left[\text{Imbalance}_{set} + \left[-2 \cdot (\text{corners} \cdot \text{Ropes} \cdot \text{Mass}_{unit}) \cdot \text{height}_{ini} \right] \dots \right. \\
 \left. + \left[\text{corners} \cdot \left[-F_{cwt} \cdot \left[\sin \left[\text{atan} \left(\frac{y_{aux} - \text{height}_{ini}}{x_{aux}} \right) \right] + \text{asin} \left[\frac{R_{aux}}{\left(\frac{x_{aux}}{\cos \left(\text{atan} \left(\frac{y_{aux} - \text{height}_{ini}}{x_{aux}} \right) \right) \right)} \right]} \right] \right] \right] \right]$$

May 10, 2017 North End Results
 Imbalance_{ini} = 7431 lb. Friction_{ave} = 5773 lb.

April 22, 2015 North End Results
 Initial Imbalance = 7,452 lb. Friction = 5,755 lb.


Positive imbalance indicates bridge is span heavy.
 Negative imbalance indicates bridge is counterweight heavy.

Span Balance Curves

Imbalance Versus Lift Height

BRIDGE= "Burlington Canal Lift Bridge"
 TOWER = "South Tower"
 TEST_DATE = "May 10, 2017"

BRIDGE_TYPE= "Tower Drive Vertical Lift"
 TEST_ID = "Average Imbalance"



Average
100 Points

Analyze
 height_{min} = 9.6
 height_{max} = 97.5

- ××× Imbalance Force - Averaged Data Points of Final Test
- Imbalance Force - Fitted Curve of Final Test for Avg. Data
- +5% Imbalance Force - Initial Test Fitted Curve - Avg. Data
- -5% Imbalance Force - Initial Test Fitted Curve - Avg. Data

height_{ini} := 0

$$\text{Imbalance}_{ini} := \left[\text{Imbalance}_{set} + \left[-2 \cdot (\text{corners} \cdot \text{Ropes} \cdot \text{Mass}_{unit}) \cdot \text{height}_{ini} \right] \dots \right. \\
 \left. + \left[\text{corners} \cdot \left[-F_{cwt} \cdot \left[\sin \left[\text{atan} \left(\frac{y_{aux} - \text{height}_{ini}}{x_{aux}} \right) \right] + \text{asin} \left[\frac{R_{aux}}{\left(\frac{x_{aux}}{\cos \left(\text{atan} \left(\frac{y_{aux} - \text{height}_{ini}}{x_{aux}} \right) \right)} \right)} \right] \right] \right] \right] \right]$$

May 10, 2017 South End Results
 Imbalance_{ini} = 6296 lb. Friction_{ave} = 5721 lb.

April 22, 2015 South End Results
 Initial Imbalance = 6,274 lb. Friction = 5,215 lb.

Positive imbalance indicates bridge is span heavy.
 Negative imbalance indicates bridge is counterweight heavy.