

PART 1 - GENERAL

1.1 ACTION AND  
INFORMATIONAL  
SUBMITTALS

- .1 Submittals: in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Submit written request in advance of cutting or alteration which affects:
  - .1 Structural integrity of elements of project.
  - .2 Integrity of weather-exposed or moisture-resistant elements.
  - .3 Efficiency, maintenance, or safety of operational elements.
  - .4 Visual qualities of sight-exposed elements.
  - .5 Work of Departmental Representative or separate contractor.
- .3 Include in request:
  - .1 Identification of project.
  - .2 Location and description of affected Work.
  - .3 Statement on necessity for cutting or alteration.
  - .4 Description of proposed Work, and products to be used.
  - .5 Alternatives to cutting and patching.
  - .6 Effect on Work of Departmental Representative or separate contractor.
  - .7 Written permission of affected separate contractor.
  - .8 Date and time work will be executed.

1.2 MATERIALS

- .1 Required for original installation.
- .2 Change in Materials: Submit request for substitution in accordance with Section 01 33 00 - Submittal Procedures.

1.3 PREPARATION

- .1 Inspect existing conditions, including elements subject to damage or movement during cutting and patching.
  - .2 After uncovering, inspect conditions affecting performance of Work.
-

- 1.3 PREPARATION  
(Cont'd)
- .3 Beginning of cutting or patching means acceptance of existing conditions.
  - .4 Provide supports to assure structural integrity of surroundings; provide devices and methods to protect other portions of project from damage.
  - .5 Provide protection from elements for areas which are to be exposed by uncovering work; maintain excavations free of water.
- 1.4 EXECUTION
- .1 Execute cutting, fitting, and patching to complete Work.
  - .2 Fit several parts together, to integrate with other Work.
  - .3 Uncover Work to install ill-timed Work.
  - .4 Remove and replace defective and non-conforming Work.
  - .5 Provide openings in non-structural elements of Work for penetrations of mechanical and electrical Work.
  - .6 Execute Work by methods to avoid damage to other Work, and which will provide proper surfaces to receive patching and finishing.
  - .7 Employ original installer to perform cutting and patching for weather-exposed and moisture-resistant elements, and sight-exposed surfaces.
  - .8 Cut rigid materials using masonry saw or core drill. Pneumatic or impact tools not allowed on masonry work without prior approval.
  - .9 Restore work with new products in accordance with requirements of Contract Documents.
  - .10 Fit Work airtight to pipes, sleeves, ducts, conduit, and other penetrations through surfaces.
-

- |   |     |  |
|---|-----|--|
| <u>1.4 EXECUTION</u><br><u>(Cont'd)</u> | .11 | Refinish surfaces to match adjacent finishes:<br>Refinish continuous surfaces to nearest<br>intersection. Refinish assemblies by<br>refinishing entire unit. |
|   | .12 | Conceal pipes, ducts and wiring in floor, wall<br>and ceiling construction of finished areas<br>except where indicated otherwise.                            |

PART 2 - PRODUCTS

- |                     |    |           |
|---------------------|----|-----------|
| <u>2.1 NOT USED</u> | .1 | Not Used. |
|---------------------|----|-----------|

PART 3 - EXECUTION

- |                     |    |           |
|---------------------|----|-----------|
| <u>3.1 NOT USED</u> | .1 | Not Used. |
|---------------------|----|-----------|