

Wharf Repairs

Bay St. Lawrence, Victoria County, NS

Project No. R.117914.001

Miscellaneous Items

Page 1

Part 1 - GENERAL

- | | |
|------------------------------------|---|
| 1.1 <u>Description of Work</u> | .1 This section specifies requirements for the following items:
.1 Ladders
.2 Fenders and sheathing
.3 Fender Piles |
| 1.2 <u>Related Work</u> | .1 Refer to other Specification Sections or related information.

.2 Section 01 33 00 - Submittal Procedures

.3 Section 05 50 00 - Metals and Metal Fabrication

.4 Section 06 05 73 - Dimension Timber |
| 1.3 <u>Measurement for Payment</u> | .1 Ladders, including all timber, rungs, vertical uprights and fasteners shall be measured in accordance with Section 01 29 00 - Project Particulars and Measurement.

.2 Fenders and sheathing (dimension timber), including fasteners, shall be measured in accordance with Section 01 29 00 - Project Particulars and Measurement. |

PART 2 - PRODUCTS

- | | |
|-----------------------------|--|
| 2.1 <u>Dimension Timber</u> | .1 All timber supplied by Contractor shall conform to Section 06 05 73 - Dimension Timber

.2 Prior to pressure treatment at plant, have tops of fenders and sheathing bevelled at 4 horizontal to 1 vertical as indicated on the plans. |
| 2.2 Hardware | .1 All hardware supplied by Contractor shall conform to Section 05 50 00 - Metals and Metal Fabrication |

PART 3 - EXECUTION

- | | |
|--------------------|---|
| 3.1 <u>Ladders</u> | .1 Fabricate and assemble ladder units as indicated and install completed units |
|--------------------|---|

Wharf Repairs

Bay St. Lawrence, Victoria County, NS

Project No. R.117914.001

Miscellaneous Items

Page 2

including vertical uprights in locations shown on plan or as indicated by *Departmental Representative*.

- .2 Install bolts in counterbore on exterior face of ladders, as shown.
- .3 Apply preservative treatment to areas of unprotected wood exposed during course of work in accordance with Section 06 05 73 - Dimension Timber

3.2 Fenders and Sheathing

- .1 Fasten fenders and sheathing to timber wales with machine bolts where indicated.
- .3 Install bolts in counterbore on exterior face of fenders, as shown. Use round-head sheathing bolts for sheathing, as shown.
- .3 Apply preservative treatment to areas of unprotected wood exposed during course of work in accordance with Section 06 05 73 - Dimension Timber

3.2 Fenders Piles

- .1 Fasten fenders piles to existing structure where indicated.
- .3 Install bolts in counterbore on exterior face of fender piles, as shown.
- .3 Apply preservative treatment to areas of unprotected wood exposed during course of work in accordance with Section 06 05 73 - Dimension Timber

-----END of SECTION-----