

Construction & Refurbishment of Bay Class  
SAR Lifeboat Marine Infrastructures  
Burin, NL  
R.116548.001

2022-01-17

PART 1 - GENERAL1.1 RELATED  
SECTIONS

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 03 30 00 - Cast-in-Place Concrete.
- .3 Section 31 09 16.01 - Pile Driving Template.
- .4 Section 31 61 13 - Pile Foundation, General Requirement.
- .5 Section 31 62 16.13 - Sheet Steel Piles.
- .6 Section 31 63 19.13 - Rock Sockets for Piles.

1.2 REFERENCES

- .1 American Society for Testing and Materials International, (ASTM)
  - .1 ASTM A 53/A53M-10, Standard Specification for Pipe, Steel, Black and Hot-Dipped, Zinc-Coated Welded and Seamless.
  - .2 ASTM A 269-10, Standard Specification for Seamless and Welded Austenitic Stainless Steel Tubing for General Service.
  - .3 ASTM A307-10, Standard Specification for Carbon Steel Bolts and Studs, 60,000 PSI Tensile Strength.
  - .4 ASTM A123/A123M-09, Standard Specification for Zinc (Hot Dip Galvanized) Coatings on Iron and Steel Products.
- .2 Canadian General Standards Board (CGSB)
  - .1 CAN/CGSB-1.40-97, Anti-corrosive Structural Steel Alkyd Primer.
  - .2 CAN/CGSB-1.181-99, Ready-Mixed, Organic Zinc-Rich Coating.

Construction & Refurbishment of Bay Class  
SAR Lifeboat Marine Infrastructures  
Burin, NL  
R.116548.001

2022-01-17

- .3 Canadian Standards Association (CSA International)
  - .1 CSA-G40.20/G40.21-04 (R2009), General Requirements for Rolled or Welded Structural Quality Steel/Structural Quality Steel.
  - .2 CAN/CSA-S16.1-09, Design of Steel Structures.
  - .3 CSA W48-06, Filler Metals and Allied Materials for Metal Arc Welding (Developed in co-operation with the Canadian Welding Bureau).
  - .4 CSA W59-03 (R2008), Welded Steel Construction (Metal Arc Welding).
- .4 The Environmental Choice Program
  - .1 CCD-047a-98, Paints, Surface Coatings.
  - .2 CCD-048-98, Surface Coatings - Recycled Water-borne.

### 1.3 SUBMITTALS

- .1 Product Data:
  - .1 Submit manufacturer's printed product literature, specifications and data sheet in accordance with Section 01 33 00 - Submittal Procedures.
  - .2 Submit two copies of WHMIS MSDS - Material Safety Data Sheets in accordance with Section 01 33 00 - Submittal Procedures. Indicate VOC's:
    - .1 For finishes, coatings, primers and paints.
- .2 Shop Drawings
  - .1 Submit shop drawings in accordance with Section 01 33 00 - Submittal Procedures.
  - .2 Indicate materials, core thicknesses, finishes, connections, joints, method of anchorage, number of anchors, supports,

Construction & Refurbishment of Bay Class  
SAR Lifeboat Marine Infrastructures  
Burin, NL  
R.116548.001

2022-01-17

reinforcement, details, and accessories.

1.4 QUALITY  
ASSURANCE

- .1 Test Reports: Certified test reports showing compliance with specified performance characteristics and physical properties.
- .2 Certificates: Product certificates signed by manufacturer certifying materials comply with specified performance characteristics and criteria and physical requirements.

1.5 DELIVERY,  
STORAGE, AND  
HANDLING

- .1 Packing, Shipping, Handling and Unloading:
- .2 Deliver, store, handle and protect materials in accordance with Section 01 61 00 - Common Product Requirements.
- .3 Storage and Protection:
  - .1 Cover exposed stainless steel surfaces with pressure sensitive heavy protection paper or apply strippable plastic coating, before shipping to job site.
  - .2 Leave protective covering in place until final cleaning of building. Provide instructions for removal of protective covering.

1.6 MEASUREMENT FOR  
PAYMENT

- .1 Tie-back anchors: The tie back anchors will be measured by the unit. Include all labour, plant and equipment in the unit price, including drilling, anchors, grouting, tensioning, knuckles, sleeves, etc. Any damage caused to the existing decking or other infrastructure during anchor installation is to be repaired at the Contractor's expense.

Construction & Refurbishment of Bay Class  
SAR Lifeboat Marine Infrastructures  
Burin, NL  
R.116548.001

2022-01-17

- .2 Steel supports (galvanized) to support timber wales will not be measured separately for payment and is to be included in the lump sum arrangement. C-channel on back of steel sheet piling (galvanized) will not be measured separately for payment.

## PART 2 - PRODUCTS

### 2.1 MATERIALS

- .1 Steel sections and plates: to CAN/CSA-G40.20/G40.21, Type 400W for sections and Type 300W for plates.
- .2 Welding materials: to CSA W59.
- .3 Welding electrodes: to CSA W48 Series.
- .4 Bolts and anchor bolts: to ASTM A 307.

### 2.2 FABRICATION

- .1 Fabricate work square, true, straight and accurate to required size, with joints closely fitted and properly secured.
- .2 Use self-tapping shake-proof flat headed screws on items requiring assembly by screws or as indicated.
- .3 Where possible, fit and shop assemble work, ready for erection.
- .4 Ensure exposed welds are continuous for length of each joint. File or grind exposed welds smooth and flush.

### 2.3 FINISHES

- .1 Galvanizing: hot dipped galvanizing with zinc coating to ASTM-A123/A123M.

Construction & Refurbishment of Bay Class  
SAR Lifeboat Marine Infrastructures  
Burin, NL  
R.116548.001

2022-01-17

- .2 Shop coat primer: to CAN/CGSB-1.40.
- .3 Zinc primer: zinc rich, ready mix to CAN/CGSB-1.181.

#### 2.4 SHOP PAINTING

- .1 Apply one shop coat of primer to metal items, with exception of galvanized or concrete encased items.
- .2 Use primer unadulterated, as prepared by manufacturer. Paint on dry surfaces, free from rust, scale, grease. Do not paint when temperature is lower than 7 degrees C.
- .3 Clean surfaces to be field welded; do not paint.

### PART 3 - EXECUTION

#### 3.1 ERECTION

- .1 Do welding work in accordance with CSA W59 unless specified otherwise.
- .2 Erect metalwork square, plumb, straight, and true, accurately fitted, with tight joints and intersections.
- .3 Provide suitable means of anchorage acceptable to Departmental Representative such as dowels, anchor clips, bar anchors, expansion bolts and shields, and toggles.
- .4 Exposed fastening devices to match finish and be compatible with material through which they pass.
- .5 Make field connections with bolts to CAN/CSA-S16.1, or weld.

Construction & Refurbishment of Bay Class

SAR Lifeboat Marine Infrastructures

Burin, NL

R.116548.001

2022-01-17

- .6 Touch-up rivets, field welds, bolts and burnt or scratched surfaces after completion of erection with primer.
- .7 Touch-up galvanized surfaces with zinc rich primer where burned by field welding.

### 3.2 CLEANING

- .1 Perform cleaning after installation to remove construction and accumulated environmental dirt.
- .2 Upon completion of installation, remove surplus materials, rubbish, tools and equipment barriers.