



RETURN BIDS TO:

RETOURNER LES SOUMISSIONS À:

Bid Receiving Public Works and Government
Services Canada/Réception des soumissions Travaux
publics et Services gouvernementaux Canada
See herein for bid submission
instructions/

Voir la présente pour les
instructions sur la présentation
d'une soumission

NA
Alberta

**SOLICITATION AMENDMENT
MODIFICATION DE L'INVITATION**

The referenced document is hereby revised; unless otherwise
indicated, all other terms and conditions of the Solicitation
remain the same.

Ce document est par la présente révisé; sauf indication contraire,
les modalités de l'invitation demeurent les mêmes.

Comments - Commentaires

**Vendor/Firm Name and Address
Raison sociale et adresse du
fournisseur/de l'entrepreneur**

Issuing Office - Bureau de distribution
Public Works and Government Services Canada/Travaux
publics et Services gouvernementaux Canada
Harry Hays Building (HHB)
Room 759, 220-4th Avenue SE
Calgary
Alberta
T2G 4X3

| | |
|---|--|
| Title - Sujet Monitor Arms Monitor Arms | |
| Solicitation No. - N° de l'invitation ET025-221794/A | Amendment No. - N° modif. 001 |
| Client Reference No. - N° de référence du client ECCC-ET025-221794 | Date 2022-03-28 |
| GETS Reference No. - N° de référence de SEAG PW-\$CAL-143-7259 | |
| File No. - N° de dossier CAL-1-44036 (143) | CCC No./N° CCC - FMS No./N° VME |
| Solicitation Closes - L'invitation prend fin at - à 02:00 PM Mountain Daylight Saving Time MDT on - le 2022-04-12 Heure Avancée des Rocheuses HAR | |
| F.O.B. - F.A.B. Plant-Usine: <input type="checkbox"/> Destination: <input checked="" type="checkbox"/> Other-Autre: <input type="checkbox"/> | |
| Address Enquiries to: - Adresser toutes questions à: Kunz, Roxanne | Buyer Id - Id de l'acheteur cal143 |
| Telephone No. - N° de téléphone (403) 463-0037 () | FAX No. - N° de FAX (418) 566-6167 |
| Destination - of Goods, Services, and Construction: Destination - des biens, services et construction: ENVIRONMENT AND CLIMATE CHANGE CANADA (ECCC) 234 Donald Street WINNIPEG, MB R3C 1M8 | |

Instructions: See Herein

Instructions: Voir aux présentes

| | |
|--|--|
| Delivery Required - Livraison exigée | Delivery Offered - Livraison proposée |
| Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur | |
| Telephone No. - N° de téléphone Facsimile No. - N° de télécopieur | |
| Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie) | |
| Signature | Date |

Solicitation No. – N° de l’invitation
ET025-221794/A

Amd. No – N° de la modif.
001

Buyer ID – Id de l’acheteur
CAL143

Client Ref. No. – N° de réf. De client
ET025-221794/

File No. – N° du dossier

CCC No./ N° CCC – FMS No/ N° VME

This amendment is being raised to extend the closing date of the solicitation, and address questions and provide revisions with regards to solicitation No. ET025-221794/A:

1. **DELETE:** Closing date April 5, 2022
INSERT: Closing date April 12, 2022

Section A: Questions and Answers

Section B: Revisions to the Request for Proposal

Section A: Questions and Answers

- Q1.** Regarding line item 7.2 and 19.2 in the Compliance Matrix, would a plastic cover for the wire manager on the arms and on the pole ends be acceptable?
- A1.** **Yes, providing that there are no plastic components in the *mechanism* of the monitor arm (ie. No plastic parts in the articulating arms that affect movement or operation).**
- Q2.** Will monitor arms that have plastic wire management clips along the post be acceptable?
- A2.** **Yes, this is acceptable providing that there are no plastic components in the *mechanism* of the monitor arm.**
- Q3.** Regarding line item 17.1 in the Compliance Matrix, the average 34" monitor weight is approximately 12 lbs, 25 lbs seems excessive. As the single-arm monitor is one less arm than the double and the double only requires 40lbs, would the single-arm weight capacity of 20 lbs also be accepted?
- A3.** **The single arm monitor must have a weight capacity of 25 lbs. Each arm of the dual unit should be rated for 25 lbs each, with a total of 40 lbs as a unit (ie if one arm carries a weight of 25lbs, the second arm would only accommodate 15 lbs and vice versa). (See Section B: Revision).**

Section B: Revisions to the Request for Proposal

1. At Annex A, **DELETE COMPLIANCE MATRIX – MINIMUM MANDATORY PERFORMANCE SPECIFICATIONS** in its entirety.

INSERT:

COMPLIANCE MATRIX – MINIMUM MANDATORY PERFORMANCE SPECIFICATIONS:

| Requirement: | Manufacturer(s) Offered: | Model Number(s) Offered: |
|-------------------------------|---------------------------------|---------------------------------|
| Monitor Arms: Single and Dual | | |

| Item # | Performance Specification | Status (M) Mandatory | Performance Specification Offered: Bidder <u>should</u> indicate how they meet the performance specification by recording this information in this column | Cross Reference: In this column, Bidders <u>should</u> cross-reference where this performance specification is indicated in their supporting documents |
|-------------------------------|---|-------------------------|--|---|
| MA-1: Dual Monitor Arm | | | | |
| 1 | Description | | | |
| 1.1 | Must be work surface mounted | M | | |
| 1.2 | Monitor capacity must be: 2 monitors, side by side (preferably also stacking) | M | | |
| 1.3 | Must include central post, two (2) arms, base, post collar, desk clamp, grommet mount | M | | |
| 2 | Construction Material | | | |
| 2.1 | Must be aluminum, recycled aluminum or extruded metal | M | | |
| 3 | Lift | | | |
| 3.1 | Must be a minimum 13" (330mm) | M | | |
| 4 | Monitor Size | | | |
| 4.1 | Must provide adjustability for minimum monitor size of 34" (40" diagonally) | M | | |
| 5 | Weight Capacity | | | |
| 5.1 | Must have a minimum weight capacity of 40 lbs total, but rated for 25 lbs per arm | M | | |
| 6 | Movement | | | |
| 6.1 | Must have a minimum 75 degree tilt | M | | |
| 6.2 | Must have 180 degree rotation, portrait and landscape | M | | |
| 6.3 | Must have a Slider bar | M | | |
| 7 | Mechanism: | | | |
| 7.1 | Must have pneumatic or spring tension, manual adjustment (weight compensating adjustable technology) | M | | |
| 7.2 | Must not have any plastic parts | M | | |
| 8 | Mounting Standard | | | |
| 8.1 | The mounting interface must provide mounting brackets for standard VESA 4 holes patterns: 75mm (2.9in) x 75mm (2.9) or 100mm (3.9 in) x 100mm (3.9 in). The Monitor arm must be able to provide vertical and horizontal depth adjustment by the user without the use of tools | M | | |

| | | | | |
|---------------------------------|---|---|--|--|
| 9 | Desk Clamp | | | |
| 9.1 | Must include a 2-piece clamp, or bolt-through attached to worksurface edge | M | | |
| 10 | Cable Management | | | |
| 10.1 | Must be grommet mount, in post, or flexible rubber channels | M | | |
| 11 | Warranty | | | |
| 11.1 | Must include a minimum 10 year, 24/7 use | M | | |
| 12 | Sustainability | | | |
| 12.1 | Product must be third-party certified by one of the following standards: BIFMA, Living Product Challenge, or Greenguard Certification | M | | |
| MA-2: Single Monitor Arm | | | | |
| 13 | Description | | | |
| 13.1 | Must be Worksurface mounted. | M | | |
| 13.2 | Monitor capacity must be: 1 monitor | M | | |
| 13.3 | Must include central post, one (1) arm, extension, base, post collar, desk clamp | M | | |
| 14 | Construction Material | | | |
| 14.1 | Must be Aluminum, Recycled Aluminum, or Extruded Metal | M | | |
| 15 | Lift | | | |
| 15.1 | Must be a minimum of 10.4" (264mm) | M | | |
| 16 | Monitor Size | | | |
| 16.1 | Must provide adjustability for minimum monitor size of 34" (40" diagonally) | M | | |
| 17 | Weight Capacity | | | |
| 17.1 | Must have a minimum weight capacity of 25 lbs | M | | |
| 18 | Movement | | | |
| 18.1 | Must have a minimum 75 degree tilt | M | | |
| 18.2 | Must have 180 degree rotation, portrait and landscape | M | | |
| 19 | Mechanism: | | | |
| 19.1 | Must have pneumatic or spring tension, manual adjustment (weight compensating adjustable technology) | M | | |
| 19.2 | Must not have any plastic parts | M | | |
| 20 | Mounting Standard | | | |
| 20.1 | The mounting interface must provide mounting brackets for standard VESA 4 holes patterns: 75mm (2.9in) x 75mm (2.9) or 100mm (3.9 in) x 100mm (3.9 in). The Monitor arm must be able to provide vertical and horizontal depth adjustment by the user without the use of tools | M | | |

Solicitation No. – N° de l'invitation
ET025-221794/A

Amd. No – N° de la modif.
001

Buyer ID – Id de l'acheteur
CAL143

Client Ref. No. – N° de réf. De client
ET025-221794/

File No. – N° du dossier

CCC No./ N° CCC – FMS No/ N° VME

| | | | | |
|------|---|---|--|--|
| 21 | Desk Clamp | | | |
| 21.1 | Must include a 2-piece clamp, or bolt-through, attached to worksurface edge | M | | |
| 22 | Cable Management | | | |
| 22.1 | Must be grommet mount, in post, or flexible rubber channels | M | | |
| 23 | Warranty | | | |
| 23.1 | Must include a minimum 10 year, 24/7 use | M | | |
| 24 | Sustainability | | | |
| 24.1 | Product must be third-party certified by one of the following standards: BIFMA, or Living Product Challenge | M | | |

ALL OTHER TERMS AND CONDITIONS REMAIN THE SAME