

PART 1 - GENERAL

1.1 RELATED
SECTIONS

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 61 00 - Common Product Requirements.
- .3 Section 01 78 00 - Closeout Submittals.
- .4 Section 08 11 00 - Metal Doors and Frames.

1.2 REFERENCES

- .1 Canadian Steel Door and Frame Manufacturers' Association (CSDFMA).
 - .1 CSDFMA Canadian Metric Guide for Steel Doors and Frames (Modular Construction): standard hardware location dimensions.
- .2 Canadian General Standards Board (CGSB).
 - .1 CAN/CGSB-69.17-M86(R1993), Bored and Preassembled Locks and Latches.
 - .2 CAN/CGSB-69.18-M90/ANSI/BHMA A156.1-1981, Butts and Hinges.
 - .3 CAN/CGSB-69.22-M90/ANSI/BHMA A156.6-1986, Architectural Door Trim.
 - .4 CAN/CGSB-69.28-M90/ANSI/BHMA A156.12-1986, Interconnected Locks and Latches.
 - .5 CAN/CGSB-69.29-93/ANSI/BHMA A156.13-1987, Mortise Locks and Latches.
 - .6 CAN/CGSB-69.31-M89/ANSI/BHMA A156.15-1981, Closer/Holder Release Device.

1.3 SUBMITTALS

- .1 Product Data:
 - .1 Submit manufacturer's printed product literature, specifications and data sheet in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Samples:
 - .1 Submit samples in accordance with Section 01 33 00 - Submittal Procedures.
 - .2 Identify each sample by label indicating applicable specification paragraph number, brand name and number, finish and hardware package number.
 - .3 After approval samples will be returned for incorporation in the Work.
- .3 Hardware List:

1.3 SUBMITTALS
(Cont'd)

- .3 (Cont'd)
 - .1 Submit contract hardware list in accordance with Section 01 33 00 - Submittal Procedures.
 - .2 Indicate specified hardware, including make, model, material, function, size, finish and other pertinent information.
- .4 Manufacturer's Instructions:
 - .1 Submit manufacturer's installation instructions.
- .5 Closeout Submittals
 - .1 Provide operation and maintenance data for door closers, locksets, door holders for incorporation into manual specified in Section 01 78 00 - Closeout Submittals.

1.4 QUALITY
ASSURANCE

- .1 Regulatory Requirements:
- .2 Certificates: product certificates signed by manufacturer certifying materials comply with specified performance characteristics and criteria and physical requirements.

1.5 DELIVERY,
STORAGE, AND
HANDLING

- .1 Packing, Shipping, Handling and Unloading:
 - .1 Deliver, store, handle and protect materials in accordance with Section 01 61 00 - Common Product Requirements.
 - .2 Package each item of hardware including fastenings, separately or in like groups of hardware, label each package as to item definition and location.
- .2 Storage and Protection:
 - .1 Store finishing hardware in locked, clean and dry area.

1.6 WASTE DISPOSAL
AND MANAGEMENT

- .1 Separate and recycle waste materials in accordance with Section 01 74 21 - Construction/Demolition Waste Management And Disposal.
- .2 Remove from site and dispose of packaging materials at appropriate recycling facilities.

- 2.1 HARDWARE ITEMS .1 Use one manufacturer's products only for similar items.
- 2.2 DOOR HARDWARE .1 Locks and latches:
 .1 Bored and preassembled locks and latches: to CAN/CGSB-69.17, preassembled lock, grade 1, designed for function and keyed as stated in Hardware Schedule.
 .2 Lever handle: plain design.
 .3 Escutcheons: round.
 .4 Normal strikes: box type, lip projection not beyond jamb.
 .5 Cylinders: key into keying system.
 .6 Finished to satin.
- .2 Butts and hinges:
 .1 Butts and hinges: to CAN/CGSB-69.18, designated by letter A and numeral identifiers, followed by size and finish, listed in Hardware Schedule.
- .3 Door Closers and Accessories:
 .1 Door controls (closers): to CAN/CGSB-69.20, designated by letter C and numeral identifiers listed in Hardware Schedule, size in accordance with CAN/CGSB-69.20, table A1, finished to satin.
- .4 Thresholds: 150 mm wide x full width of door opening, stainless steel mill finish, plain surface,, with lip.
- .5 Weatherstripping:
 .1 Head and jamb seal:

2.2 DOOR HARDWARE
(Cont'd)

- .5 (Cont'd)
 - .1 (Cont'd)
 - .1 Extruded aluminum frame and closed cell neoprene vinyl insert.
 - .2 Adhesive backed neoprene vinyl covered foam material.
 - .2 Door bottom seal:
 - .1 Extruded aluminum frame and closed cell neoprene vinyl sweep, stainless steel finish.

2.3 FASTENINGS

- .1 Use only fasteners provided by manufacturer. Failure to comply may void warranties and applicable licensed labels.
- .2 Supply screws, bolts, expansion shields and other fastening devices required for satisfactory installation and operation of hardware.
- .3 Exposed fastening devices to match finish of hardware.
- .4 Use fasteners compatible with material through which they pass.

2.4 KEYING

- .1 Doors, to be keyed alike great grand master keyed. Prepare detailed keying schedule in conjunction with Departmental Representative.
- .2 Provide keys in duplicate for every lock in this Contract.

PART 3 - EXECUTION

3.1 MANUFACTURER'S
INSTRUCTIONS

- .1 Compliance: comply with manufacturer's written data, including product technical bulletins, product catalogue installation instructions, product carton installation instructions, and data sheets.
- .2 Furnish metal door and frame manufacturers with complete instructions and templates for preparation of their work to receive hardware.
- .3 Furnish manufacturers' instructions for proper installation of each hardware component.

3.2 INSTALLATION

- .1 Install hardware to standard hardware location dimensions in accordance with Canadian Metric Guide for Steel Doors and Frames (Modular Construction) prepared by Canadian Steel Door and Frame Manufacturers' Association.
- .2 Where door stop contacts door pulls, mount stop to strike bottom of pull.
- .3 Use only manufacturer's supplied fasteners. Failure to comply may void manufacturer's warranties and applicable licensed labels. Use of "quick" type fasteners, unless specifically supplied by manufacturer, is unacceptable.

3.3 ADJUSTING

- .1 Adjust door hardware, operators, closures and controls for optimum, smooth operating condition, safety and for weather tight closure.
- .2 Lubricate hardware, operating equipment and other moving parts.
- .3 Adjust door hardware to provide tight fit at contact points with frames.

3.4 CLEANING

- .1 Perform cleaning after installation to remove construction and accumulated environmental dirt.
- .2 Clean hardware with damp rag and approved non-abrasive cleaner, and polish hardware in accordance with manufacture's instructions.
- .3 Remove protective material from hardware items where present.
- .4 Upon completion of installation, remove surplus materials, rubbish, tools and equipment barriers.