



**RETURN BIDS TO:  
RETOURNER LES SOUMISSIONS À:**

Omar Kraya  
omar.kraya@tpsgc-pwgsc.gc.ca

**SOLICITATION AMENDMENT  
MODIFICATION DE L'INVITATION**

The referenced document is hereby revised; unless otherwise indicated, all other terms and conditions of the Solicitation remain the same.

Ce document est par la présente révisé; sauf indication contraire, les modalités de l'invitation demeurent les mêmes.

**Comments - Commentaires**

**Vendor/Firm Name and Address**  
**Raison sociale et adresse du**  
**fournisseur/de l'entrepreneur**

**Issuing Office - Bureau de distribution**  
Weapons Systems Division/Division des systèmes  
d'arme  
11 Laurier St. / 11, rue Laurier  
8C2, Place du Portage  
Gatineau  
Québec  
K1A 0S5

|  |   |
|--|---|
| <b>Title - Sujet</b> RFI for Service Pistols Replacement   |   |
| <b>Solicitation No. - N° de l'invitation</b><br>M7594-224467/B   | <b>Amendment No. - N° modif.</b><br>004     |
| <b>Client Reference No. - N° de référence du client</b><br>M7594-224467  | <b>Date</b><br>2022-04-25                   |
| <b>GETS Reference No. - N° de référence de SEAG</b><br>PW-\$\$BM-030-28618   |   |
| <b>File No. - N° de dossier</b><br>030bm.M7594-224467  | <b>CCC No./N° CCC - FMS No./N° VME</b>      |
| <b>Solicitation Closes - L'invitation prend fin</b><br><b>at - à 02:00 PM</b> Eastern Daylight Saving Time EDT<br><b>on - le 2022-05-04</b> Heure Avancée de l'Est HAE |   |
| <b>F.O.B. - F.A.B.</b><br><b>Plant-Usine:</b> <input type="checkbox"/> <b>Destination:</b> <input type="checkbox"/> <b>Other-Autre:</b> <input type="checkbox"/>       |   |
| <b>Address Enquiries to: - Adresser toutes questions à:</b><br>Kraya, Omar   | <b>Buyer Id - Id de l'acheteur</b><br>030bm |
| <b>Telephone No. - N° de téléphone</b><br>(343) 552-5009 ( )   | <b>FAX No. - N° de FAX</b><br>( ) -         |
| <b>Destination - of Goods, Services, and Construction:</b><br><b>Destination - des biens, services et construction:</b>  |   |

**Instructions: See Herein**

**Instructions: Voir aux présentes**

|  |  |
|--|--|
| <b>Delivery Required - Livraison exigée</b>  | <b>Delivery Offered - Livraison proposée</b> |
| <b>Vendor/Firm Name and Address</b><br><b>Raison sociale et adresse du fournisseur/de l'entrepreneur</b>   |  |
| <b>Telephone No. - N° de téléphone</b><br><b>Facsimile No. - N° de télécopieur</b>   |  |
| <b>Name and title of person authorized to sign on behalf of Vendor/Firm</b><br><b>(type or print)</b><br><b>Nom et titre de la personne autorisée à signer au nom du fournisseur/</b><br><b>de l'entrepreneur (taper ou écrire en caractères d'imprimerie)</b> |  |
| <b>Signature</b>   | <b>Date</b>                                  |

**The following changes are effective immediately.**

Amendment 004 is issued for the following reason:

- (1) Publish Bidders' Questions and Answers;
  - (2) Amend section 9. **"ENQUIRIES AND SUBMISSION OF RFI RESPONSES"**
  - (3) Amend section 11.1. **Technical/Performance Specifications for the RCMP Service Pistol may include, but are not limited to: at "11.1.11"**
- 

**1. Bidders' Questions and Answers**

**Question # 1.**

In regard to the below requested trigger pull, we would like to know the specific device that the RCMP use to test trigger pull. In that way we could procure the same device to ensure our findings would match those of the RCMP.

11.1.11 The pistol's trigger must be of a striker fired. The trigger pull tension must be within a tolerance of 2.49 Kg  $\pm$  .227 Kg (5.5 lbs  $\pm$  .5 lbs).

**Answer**

The trigger pull testing method, not device, will be: Static Weights made by Custom Gunsmithing Inc.

**Question # 2.**

Can you please confirm that submissions for the subject solicitation should be sent directly to [omar.kraya@tpsgc-pwgsc.gc.ca](mailto:omar.kraya@tpsgc-pwgsc.gc.ca) ; we do not need to initiate a "Connect service" request, correct?

**Answer.**

This is correct for the RFI

---

**Amendment**

**2.**

**Delete:**

**Sec 9. ENQUIRIES AND SUBMISSION OF RFI RESPONSES in its entirety.**

**Insert:**

#### **Sec 9. ENQUIRIES AND SUBMISSION OF RFI RESPONSES**

All enquiries on this RFI must be directed to the PWGSC Contracting Authority.

Interested suppliers must note that all communication pertaining to the subject matter of this RFI shall exclusively be directed to the PWGSC Contracting Authority. Interested suppliers must not communicate directly with RCMP stakeholders or with other Government of Canada representatives other than the PWGSC Contracting Authority, regarding any aspect of this procurement process, including the subject matter described herein.

Any questions directed to the PWGSC Contract Authority while the RFI is open, will be posted to buyandsell.ca minus the respondents identity, along with the appropriate responses from Canada.

#### **PWGSC Contracting Authority:**

PSPC will not necessarily respond to enquiries in writing or by circulating answers to all potential suppliers as this is not a solicitation process. However, respondents with questions regarding this RFI may direct their enquiries to the Contracting Authority named below:

Name: Omar Kraya  
Title: Supply Team Leader  
Division Munitions and Weapons Systems Division – BK/BM

Address:  
Public Services and Procurement Canada  
11 Laurier Street  
Gatineau, Quebec  
K1A 0S5  
Canada

Email: [omar.kraya@tpsgc-pwgsc.gc.ca](mailto:omar.kraya@tpsgc-pwgsc.gc.ca)

**Time and Place for Submission of Responses:** Suppliers interested in providing a response must deliver to the contracting authority by the time and date indicated on the information cover page of this RFI.

**RFI Submission:** You must email [omar.kraya@tpsgc-pwgsc.gc.ca](mailto:omar.kraya@tpsgc-pwgsc.gc.ca)

**3.**

**Delete:**

**Sec 11.1. Technical/Performance Specifications for the RCMP Service Pistol may include, but are not limited to: in its entirety.**

**Insert:**

**Sec 11.1. Technical/Performance Specifications for the RCMP Service Pistol may include, but are not limited to:**

**11.1.1** The pistol must have a maximum length of 190.5 mm (7.50 inches).

- 11.1.2** The pistol must have a maximum overall height of 140 mm (5.51 inches) with the magazine and any RDS removed.
- 11.1.3** The pistol must be capable of reliably firing 9x19mm Luger calibre ammunition in current service with the RCMP .
- 11.1.4** The pistol must be a mechanically-locked, recoil-operated, semi-automatic pistol.
- 11.1.5** The pistol must feature a non-reflective, black matte finish on all exposed surfaces.
- 11.1.6** The pistol's slide must be manufactured from corrosion resistant steel such as stainless steel. It must have a finish that is resistant to rust and salt water corrosion.
- 11.1.7** The pistol's frame must be manufactured of polymer.
- 11.1.8** The grip or grip module must provide for various hand sizing options. The front portion of the grip must not feature any prominent finger grooves.
- 11.1.9** The pistol must feature an ambidextrous slide catch lever(s) that can be activated using either hand.
- 11.1.10** The pistol's magazine release must be configurable for only right handed or only left handed.
- 11.1.11** The pistol must be striker fired. The trigger pull tension must be within a tolerance of 2.49 Kg  $\pm$  .227 Kg (5.5 lbs  $\pm$  .5 lbs).
- 11.1.12** The pistol must be supplied with three (3) magazines, with a minimum capacity of 15 rounds per magazine.
- 11.1.13** The pistol's recoil spring guide must be manufactured of corrosion resistant steel such as stainless steel.
- 11.1.14** The pistol must have no external manual safety levers.
- 11.1.15** The pistol must be capable of discharging a cartridge with the magazine removed.
- 11.1.16** The pistol must have an internal firing pin safety preventing the forward movement of the firing pin unless the trigger is physically pulled to the rear.
- 11.1.17** The pistol must have a mechanical safety to prevent the pistol from firing when not in battery.

- 11.1.18** The pistol must feature a safety incorporated into the trigger shoe to prevent the trigger's rearward movement without physical pressure on the trigger.
- 11.1.19** The internal firing pin block safety must only be deactivated once the trigger is depressed beyond the trigger safety de-activation point.
- 11.1.20** The pistol must have a visual or tactile loaded chamber indicator feature.
- 11.1.21** The pistol must feature high definition night sights that will shoot 9x19mm Luger 147 grain ammunition to point of aim at 25m.
- 11.1.22** The front sight must be black in colour and have either a yellow or orange coloured glow-in-the-dark photoluminescent outline surrounding a green coloured tritium phosphor-filled glass lamp in the center (round dot).
- 11.1.23** The pistol must have a minimum operating temperature range of -40°C to +48°C.
- 11.1.24** The pistol slide must be configured to accept a RDS.
- 11.1.25** The rear iron sight dovetail must be integral to the slide.