

This Amendment No. 001 to Solicitation #5000064577 is raised to answer the following questions and amend Annex A – Specifications of the solicitation.

Questions (Q) and Answers (A):

Q1: 5.3 a, b and c. Work plan reference to concrete design and placement. Where is the concrete? Is this meant to be in the specs?

A1: At Annex A - Specifications, at section 5.3: a, b, and c are removed. See amendment below.

Q2: What is the anticipated soil type?

A2: Only surface soil characteristics are known. As these may be misleading or non-indicative of excavations soil properties, they are not stated.

The solicitation is amended in Annex A – Specifications as follows:

1. At **3.0 Existing Infrastructure**, under the diagram:

DELETE: Figure 3:

INSERT: Figure 3: Taseko River Drawing (1982)

2. At 4.2:

DELETE: Remove the existing steel plate anchors and install [two, three] (2) new steel plate anchors...

INSERT: Remove the existing steel plate anchors and install two (2) new steel plate anchors...

3. At 4.6:

DELETE: c) Hardware includes (see Drawings for full list):
i. Fist Grips;
ii. Thimbles; to be twisted, placed around the object required, then twisted back to their original state unless otherwise specified by the Technical Authority; cutting of timbles not allowed;
iii. Turnbuckles; and
Shackle for HD A frames

INSERT: c) Hardware includes (see Drawings for full list):
i. Fist Grips;
ii. Thimbles; to be twisted, placed around the object required, then twisted back to their original state unless otherwise specified by the Technical Authority; cutting of timbles not allowed;
iii. Turnbuckles.

4. At 5.3 Work Plan:

- DELETE:** The contractor must provide a Work Plan, clearly stating their methodology for the relevant points as listed below:
- a) Installation of the new steel plate anchors;
 - b) Method of formwork;
 - c) Concrete design mixture;
 - d) Method of concrete placement to ensure performance is achieved;
 - e) Lowering and replacing the main cable and marker cable. Cable must not enter the river;
 - f) Safety considerations for traffic on river;
 - g) ECCC supplied materials must be covered fully with a tarp when not being used, the security of all materials provided to the contractor is the responsibility of the contractor after receiving from ECCC;
 - h) Stabilizing or lowering A-frame; the A-frame cannot impact the river bank or be placed in the stream;
 - i) The steel A-frames have a pin base connection, meaning they are unstable under reduced tension in the existing cables.
 - j) A-frame structures on both banks are required to be stabilized in all directions during the entire construction activity;
 - k) List of contractor's tools and equipment; See Section 5.17 for ECCC recommendations.

- INSERT:** The contractor must provide a Work Plan, clearly stating their methodology for the relevant points as listed below:
- a) Installation of the new steel plate anchors;
 - b) Lowering and replacing the main cable and marker cable. Cable must not enter the river;
 - c) Safety considerations for traffic on river;
 - d) ECCC supplied materials must be covered fully with a tarp when not being used, the security of all materials provided to the contractor is the responsibility of the contractor after receiving from ECCC;
 - e) Stabilizing or lowering A-frame; the A-frame cannot impact the river bank or be placed in the stream;
 - f) The steel A-frames have a pin base connection, meaning they are unstable under reduced tension in the existing cables.
 - g) A-frame structures on both banks are required to be stabilized in all directions during the entire construction activity;
 - h) List of contractor's tools and equipment; See Section 5.17 for ECCC recommendations.

All other terms and conditions remain the same.