



1
M20-06
PLUMBING & DRAINAGE FIFTH FLOOR
SCALE: 1:100
0m 1m 2m 3m 4m 5m 6m 7m 8m 9m 10m

- GENERAL NOTES:**
- DRAWINGS SHALL BE READ IN CONJUNCTION WITH ALL FLOOR PLANS AND SPECIFICATIONS.
 - ALL EXISTING SERVICES SHOWN ARE APPROXIMATE AND BASED ON EXISTING DRAWINGS. CONTRACTOR SHALL VERIFY ALL LOCATIONS ON SITE.
 - CONTRACTOR TO COORDINATE INSTALLATION WITH ALL OTHER TRADES INVOLVED ON SITE.
 - ENSURE NOT TO DISTURB SERVICES COVERING AREAS NOT INCLUDED IN THE SCOPE. ALL WORK MUST BE COORDINATED WITH DEPARTMENTAL REPRESENTATIVE.
 - CONTRACTOR SHALL VISIT SITE TO EXAMINE EXISTING CONDITIONS.
 - CONTRACTOR TO PROPOSE SOLUTIONS FOR REVIEW TO THE CONSULTANT IF ANY INTERFERENCES OCCUR DUE TO SITE CONDITIONS.
 - PROVIDE PLUMBING VENT SYSTEM IN ACCORDANCE WITH CODE REQUIREMENTS. VENT SYSTEM NOT SHOWN. COORDINATE WITH ALL OTHER SERVICES.
 - ALL DRAINAGE PIPING SHOWN ON THE DRAWINGS IS SUGGESTED ONLY AND SHOULD BE CONSIDERED GRAPHICAL IN NATURE AND THE CONTRACTOR MUST INSTALL TO MEET THE CODE.
 - INSTALL ALL PIPING AS HIGH AS POSSIBLE. COORDINATE ROUTING WITH EXISTING LIGHTING FIXTURES.
 - MECHANICAL CONTRACTOR TO X-RAY SCAN SLAB PRIOR TO CORING.

- DRAWING NOTES:**
- PROVIDE FLOOR CORING AS REQUIRED.
 - 50e DCW FROM BELOW.
 - 25e DHW FROM BELOW.
 - 15e DHWR DOWN.
 - 25e DCW AND 15e DHW PIPING FROM BELOW. BRANCH OFF 15e DCW C/W ISOLATION VALVE AND CONNECT TO BOTTLE FILLER BFL-1.

