



**RETURN BIDS TO:**

**RETOURNER LES SOUMISSIONS À:**

**Bid Receiving - PWGSC / Réception des soumissions -  
TPSGC**

**11 Laurier St. / 11, rue Laurier**

**Place du Portage, Phase III**

**Core 0B2 / Noyau 0B2**

**Gatineau, Québec K1A 0S5**

**Bid Fax: (819) 997-9776**

**SOLICITATION AMENDMENT  
MODIFICATION DE L'INVITATION**

The referenced document is hereby revised; unless otherwise indicated, all other terms and conditions of the Solicitation remain the same.

Ce document est par la présente révisé; sauf indication contraire, les modalités de l'invitation demeurent les mêmes.

**Comments - Commentaires**

**Vendor/Firm Name and Address**

**Raison sociale et adresse du  
fournisseur/de l'entrepreneur**

**Issuing Office - Bureau de distribution**

Defence Communications Division. (QD)

11 Laurier St./11, rue Laurier

Place du Portage, Phase III, 8C2

Gatineau, Québec K1A 0S5

<b>Title - Sujet</b> TIC3 Air - Ground/Air/Ground (G/A/G) TIC3 Air - Ground/Air/Ground (G/A/G) System Upgrade	
<b>Solicitation No. - N° de l'invitation</b> W8475-235517/A	<b>Amendment No. - N° modif.</b> 009
<b>Client Reference No. - N° de référence du client</b> W8475-235517	<b>Date</b> 2023-09-15
<b>GETS Reference No. - N° de référence de SEAG</b> PW-\$\$QD-028-29137	
<b>File No. - N° de dossier</b> 028qd.W8475-235517	<b>CCC No./N° CCC - FMS No./N° VME</b>
<b>Solicitation Closes - L'invitation prend fin</b> <b>at - à 02:00 PM</b> Eastern Daylight Saving Time EDT <b>on - le 2023-10-16</b> Heure Avancée de l'Est HAE	
<b>F.O.B. - F.A.B.</b> <b>Plant-Usine:</b> <input type="checkbox"/> <b>Destination:</b> <input type="checkbox"/> <b>Other-Autre:</b> <input type="checkbox"/>	
<b>Address Enquiries to: - Adresser toutes questions à:</b> Garate, Oscar	<b>Buyer Id - Id de l'acheteur</b> 028qd
<b>Telephone No. - N° de téléphone</b> (873) 355-3354 ( )	<b>FAX No. - N° de FAX</b> ( ) -
<b>Destination - of Goods, Services, and Construction:</b> <b>Destination - des biens, services et construction:</b>	

**Instructions: See Herein**

**Instructions: Voir aux présentes**

<b>Delivery Required - Livraison exigée</b>	<b>Delivery Offered - Livraison proposée</b>
<b>Vendor/Firm Name and Address</b> <b>Raison sociale et adresse du fournisseur/de l'entrepreneur</b>	
<b>Telephone No. - N° de téléphone</b> <b>Facsimile No. - N° de télécopieur</b>	
<b>Name and title of person authorized to sign on behalf of Vendor/Firm</b> <b>(type or print)</b> <b>Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)</b>	
<b>Signature</b>	<b>Date</b>



## REQUEST FOR PROPOSAL

**W8475-235517**

**Air Traffic Management (ATM) Ground/Air/Ground (G/A/G) radios**

### AMENDMENT # 9

This Administrative Amendment # is raised to modify the following:

#### I. Annex A

##### a. Section 4.1 Table A1-1

<b>Delete</b>	Transceivers Delivery 12 MACA 24 MACA Antennas Delivery 12 MACA 24 MACA Ancillaries Delivery 12 MACA 24 MACA
<b>Insert</b>	Transceivers Delivery 15 MACA 30 MACA Antennas Delivery 15 MACA 30 MACA Ancillaries Delivery 15 MACA 30 MACA

#### II. Appendix A1 – Requirements Specifications

##### a. 5.1.2 Technical, Table A1-35 SATS.4 AC Power Supply Input

<b>Delete</b>	1. Single Phase 2. 120/240 VAC, +/-10%; 3. 60 Hz +/-10%
<b>Insert</b>	1. Single Phase 2. 120 VAC, +/-10%; 3. 60 Hz +/-10%

##### a) 5.1.2 Technical, Table A1-35 SATS.5 AC Power Supply Output

<b>Delete</b>	1. Single Phase 2. 120/240 VAC, +/-10%; 3. 60 Hz +/-10%
<b>Insert</b>	1. Single Phase 2. 120 VAC, +/-10%; 3. 60 Hz +/-10%

##### b) 5.3.2, Table A1-39 SATS.11

<b>Delete</b>	The features and functionality of the Handset must include: 1. Analog line connection using 4-wire (E&M). 2. VoIP audio connection. 3. Configurability via a web browser.
<b>Insert</b>	The features and functionality of the Handset must include:



	1. Analog line connection using 4-wire (E&M). 2. Configurability via a web browser.
--	--

c) 2.1.1 Table A1-1, ADGS.10 Part c

<b>Delete</b>	If there is a conflict between a particular G/A/G AD Transceiver mandatory technical specification listed in this document and the corresponding ETSI specification (or equivalent North American specification standards, if determined by the Supplier to be currently in existence), the Supplier must use that specification identified in the standards as the mandatory requirement (and provide a note or clarification).
<b>Insert</b>	If there is a conflict between the measurement method used to validate a particular G/A/G AD Transceiver mandatory technical specification listed in this document and the corresponding ETSI measurement method specification (or equivalent North American specification standards, if determined by the Supplier to be currently in existence), the Supplier must use that specification identified in the standards as the mandatory requirement (and provide a note or clarification).

d) 2.1.1 Table A1-1, ADGS.10 Part d

<b>Delete</b>	If there is a conflict between the mandatory technical specifications listed in this document and Accepted Industry Standards (or their recommendations) the Supplier must provide written technical justifications for the Accepted Industry Standards approach.
<b>Insert</b>	If there is a conflict between the measurement method used to validate the mandatory technical specifications listed in this document and Accepted Industry Standards (or their recommendations) the Supplier must provide written technical justifications for the Accepted Industry Standards measurement method approach.

e) 2.2.10.1 Table A1-11, Mil-STD-810G w/Change 1 methods, or equivalent

<b>Delete</b>	<b>Operational:</b> 507.6 Procedure 1b and 520.4 Procedure III <b>Survival:</b> 507.6 Procedure II and 520.4 Procedure III <b>Storage and Transportation:</b> 507.6 Procedure 1a and 520.4 Procedure III
<b>Insert</b>	<b>Operational:</b> 507.6 Procedure 1b <b>Survival:</b> 507.6 Procedure II <b>Storage and Transportation:</b> 507.6 Procedure 1a

III. Appendix A3 DID

a. DID-ACE-SE-001: ATM Rack, Cabling and Wiring Design, Part 3.1

<b>Delete</b>	The ATM Radio System must be configured, optimally laid-out, and supplied within a standard equipment rack of 42 U height and capability to support standard 19-inch (482.6 mm) rack unit pieces of equipment and devices.
---------------	--



---

<b>Insert</b>	The ATM Radio System must be configured, optimally laid-out, and supplied within a standard equipment rack of 45 U height and capability to support standard 19-inch (482.6 mm) rack unit pieces of equipment and devices.
---------------	--

#### **IV. Appendix A4 Installation and Deployment Sites**

a. 1.1.i.(iv)

<b>Delete</b>	Military-off-the-shelf (MOTS) Uninterrupted Power Supply (UPS)
<b>Insert</b>	Uninterrupted Power Supply (UPS)

b. 2.1.k.(iii)

<b>Delete</b>	Military-off-the-shelf (MOTS) Uninterrupted Power Supply (UPS)
<b>Insert</b>	Uninterrupted Power Supply (UPS)

**All other Terms and Conditions remain unchanged.**

---