



RETURN BIDS TO:

RETOURNER LES SOUMISSIONS À:

Bid Receiving - PWGSC / Réception des soumissions -
TPSGC

11 Laurier St. / 11, rue Laurier
Place du Portage , Phase III
Core 0B2 / Noyau 0B2

Gatineau
Québec
K1A 0S5
Bid Fax: (819) 997-9776

SOLICITATION AMENDMENT MODIFICATION DE L'INVITATION

The referenced document is hereby revised; unless otherwise indicated, all other terms and conditions of the Solicitation remain the same.

Ce document est par la présente révisé; sauf indication contraire, les modalités de l'invitation demeurent les mêmes.

Title - Sujet Pistolet Systeme Pistolet Systeme		
Solicitation No. - N° de l'invitation M7594-224467/F		Amendment No. - N° modif. 009
Client Reference No. - N° de référence du client M7594-224467		Date 2024-02-27
GETS Reference No. - N° de référence de SEAG PW-\$\$BM-039-29244		
File No. - N° de dossier 039bm.M7594-224467	CCC No./N° CCC - FMS No./N° VME	
Solicitation Closes - L'invitation prend fin at - à 02:00 PM Eastern Daylight Saving Time EDT on - le 2024-03-22 Heure Avancée de l'Est HAE		
F.O.B. - F.A.B. Specified Herein - Précisé dans les présentes		
Plant-Usine: <input type="checkbox"/> Destination: <input type="checkbox"/> Other-Autre: <input checked="" type="checkbox"/>		
Address Enquiries to: - Adresser toutes questions à: Grosser, Keith		Buyer Id - Id de l'acheteur 039bm
Telephone No. - N° de téléphone (873) 355-2334 ()		FAX No. - N° de FAX () -
Destination - of Goods, Services, and Construction: Destination - des biens, services et construction:		

Comments - Commentaires

Vendor/Firm Name and Address

Raison sociale et adresse du
fournisseur/de l'entrepreneur

Instructions: See Herein

Instructions: Voir aux présentes

Delivery Required - Livraison exigée	Delivery Offered - Livraison proposée
Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur	
Telephone No. - N° de téléphone Faximile No. - N° de télécopieur	
Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)	
Signature	Date

Issuing Office - Bureau de distribution

Weapons Systems Division/Division des systèmes
d'arme
11 Laurier St. / 11, rue Laurier
8C2, Place du Portage
Gatineau
Québec
K1A 0S5

RFP Amendment 009 is raised for the following:

- 1. To answer questions from Potential Bidders during the RFP stage.**
-

A discrepancy has been identified by Canada in the French Copy of Annex E. Please see the attached UPDATED Annex E in French to correct the discrepancy.

Question 63.

MT 7.13 states that the holster must mount to a belt that ranges from 3.66 cm (1.44 inches) to 5.7 cm (2.24 inches). Plain clothes holsters normally come equipped to fit typical plain clothes belt sizes, 1-5 to 1.75". Would the RCMP accept a plain clothes holster equipped with a belt slide to accommodate belts from 1.5 to 1.75" if there were additional belt slides available for the holster to accommodate belts up to 2.25" available as an accessory if needed. If so, would this additional larger belt slide need to be included with each holster.

Answer 63.

Yes, the RCMP would accept a plain clothes holster equipped with a belt slide to accommodate belts from 1.5" to 1.75" should there be an adapter that accommodates the belt range of 3.66 cm (1.44 inches) to 5.7 cm (2.24 inches).

The use of adaptors to mount to a belt that ranges from 3.66 cm (1.44 inches) to 5.7 cm (2.24 inches) is acceptable and the RCMP has amended MT 7.13. If adaptors are required they must be included with each plain clothes holder.

Question 64.

Annex C, §2.5.8. requires that "each pistol must be provided with one additional magazine base plate that has an attachment point for a ceremonial lanyard loop."

If a lanyard attachment point is located on the grip portion of the pistol as a standard feature, would this be allowed as an alternative to an additional magazine baseplate? This design approach avoids the extra baseplate, which is both a cost and logistical advantage to the Canadian government?

Answer 64

Canada has amended MT2.5.8 and updated Annex C and D. Canada will accept one of the following three (3) methods/options to meet this current requirement:

1. Meet the current requirement
2. Deliver their pistol with standard attachment point subject to it being able to accept the current RCMP issued lanyard clip.
3. Provide a lanyard clip that fits the pistol's current attachment point, subject that the clip will accommodate the current RCMP issued lanyard.

Question 65

Annex E, §2.12.2 & 2.12.3. requires that "The training pistol with the submitted weapon light and submitted RDS attached must be capable of firing RCMP marking cartridges."

This contradicts Annex C, 2.12.3 that does not mention the RDS.

Can the RCMP clarify whether or not an RDS is required or not on the training pistol.

*If it does, can we please be allowed the use of an adapter plate for the RDS on the training gun since the manufacturer is most likely a third party such as General Dynamic or UTM and we might not be able to guarantee a direct milling?

Answer 65.

Annex C is Statement of Requirements, where you will only find the mandatory requirements. Annex D has the Mandatory and Rated requirements, RT2.12.2 and RT2.12.3 are both rated requirements that reference the RDS. The RDS is not a mandatory for the training pistol, it is a rated requirement. If an RDS is provided with the training pistol then it will be evaluated accordingly with Annex E (Performance Evaluation Criteria, Rated).

Yes an adaptor plate for the RDS is acceptable for the training pistol.

Annex D and E, RT 2.12.2 has been updated to reflect this.

Question 66

Annex E, §2.12.2 & 2.12.3. requires that "The training pistol with the submitted weapon light and submitted RDS attached must be capable of firing RCMP marking cartridges."

There seems to be confusion whether or not the RDS is required on the blue training pistol.

If the RDS is not required, what is the reason for this decision?

Answer 66.

Annex C is Statement of Requirements, where you will only find the mandatory requirements. Annex D has the Mandatory and Rated requirements, RT2.12.2 and RT2.12.3 are both rated requirements that reference the RDS. The RDS is not a mandatory for the training pistol, it is a rated requirement. If an RDS is provided with the training pistol then it will be evaluated accordingly with Annex E (Performance Evaluation Criteria, Rated).

Yes an adaptor plate for the RDS is acceptable for the training pistol.

Annex D and E, RT 2.12.2 has been updated to reflect this.

Question 67

§2.5.9. "The full circumference edge at the entrance of the magazine well must be beveled or flared and be integrated into the pistol's frame (grip module) in order to aid in the insertion of a magazine."

The word 'FULL' should be removed as many manufacturers have 3 out of 4 sides of the magwell beveled or flared. This could limit the RCMP's choice and could be interpreted as way to direct the process towards a pre-determined product.

Answer 67.

Canada will accept a pistol submission with three (3) of the four (4) sides of the magazine well beveled or flared to aid in the insertion of the magazine. Canada has amended Annex C, D, E

Question 68

Annex D

MT 2.5.8

Each pistol must be provided with one additional magazine base plate that has an attachment point for a ceremonial lanyard loop. The Bidder must provide written documentation that demonstrates how this requirement is met. Documentation must include a manufacturer's specification sheet or test results from an accredited independent, third-party testing facility.

The industry standard regarding a lanyard loop is generally an attachment point to the pistol grip module (as per the illustrations below). Designing & engineering a magazine baseplate for that purpose would be a time consuming and cost prohibitive for the purpose. This could be easily mitigated if the RCMP was willing to accept both methods (i.e magazine baseplate and pistol grip attachment method). At a minimum, would the RCMP be willing to wait after the contract award to address this requirement and pay for the development of the device if required?

If the RCMP is not willing to be flexible in that regard and considering the timeline of the RFP, we would like to ask for a 30 day extension to design and engineer a baseplate that meets the requirement.

Answer 68.

Canada has amended MT 2.5.8 and updated Annex's C, D. Canada will accept one of the following three (3) methods/options to meet this current requirement:

1. Meet the current requirement
2. Deliver their pistol with an attachment point subject to it being able to accept the current RCMP issued lanyard clip.
3. Provide a lanyard clip that fits the pistol's current attachment point, subject that the clip will accommodate the current RCMP issued lanyard.

Canada will amend the closing date from March 8, 2024 to March 22, 2024.

Question 69

MT 2.8.5

The pistol's magazine must have a baseplate that protrudes a minimum of 2.54 mm (0.10 inch) up to a maximum of 6.35 mm (0.25 inch) from the front of the pistol's grip. The Bidder must provide written documentation that demonstrates how this requirement is met. Documentation must include a manufacturer's specification sheet or test results from an accredited independent, third-party testing facility.

We understand the above requirements' purpose is to give users the ability to rip the magazine out with their support hand in the event of a malfunction. Our magwell / magazine design is different than the above mentioned but achieves the same by giving the user a positive grip on either side of the magazine instead of the front end.

We have no issue designing & engineering a magazine baseplate/ magwell as per the above but will need an extension of 30 days to design and test the design.

Ref. Annex D

RT 2.12.3 The training pistol with the submitted weapon light and submitted RDS attached should be capable of firing RCMP marking cartridges Demonstrated: 20 points Not Demonstrated: 0 points

Answer 69.

Canada will not accept any deviations from this requirement in regards to the baseplate protruding from the front of the pistol's grip. Canada has updated Annex C,D and E MT 2.8.5 to read "The pistol's magazine must have a baseplate that protrudes a minimum of 2.54 mm (0.10 inch) up to a maximum of 8.35 mm (0.329 inch) from the front of the pistol's grip.

Canada will amend the closing date from March 8, 2024 to March 22, 2024.

Question 70

Since a custom training pistol slide that direct mounts the RDS is required we will be forced to request a 45 day extension in order to complete design and engineering to meet this requirement.

Answer 70.

Direct milling of the training pistol slide is not mandatory. Canada will accept the use of an adapter plate to attach the RDS to the training pistol.

Annex D and E RT2.12.2 have been updated to reflect this.

Question 71.

Ref. the RFP page 17 para 5.2.2 Security Requirement

When will you require the AFR Form? Can we submit to you right away?

Answer 71.

Bidders are to submit the AFR 471 form with their bid at the time of bid closing.

Question 72.

Annex C §2.5.8 - Each pistol must be provided with one additional magazine base plate that has an attachment point for a ceremonial lanyard loop.

Q: Is our assumption correct, that in case of a drop, the Lanyard loop fixed at the bottom plate must only withstand the weight of full loaded Magazine. Not the complete weight of the pistol incl. Magazine.? What will be the specified drop height?

Answer 72.

Please note MT 2.5.8 is not part of Annex E, Performance Evaluation. Your assumption is incorrect, there will be no drop for this criteria MT2.5.8.

Question 73.

Annex C §2.11.7 - The pistol's rear sight tritium vials must be green surrounded with a black outline.

Q: Tritium vials usually have a green centre dot surrounded with a very small metal tube around. Can this very small metal tube ring around the tritium dot (visible abutting face) stay in metallic colour or must it also be black?

Answer 73.

Canada will accept a metallic colour on the small metal tube ring that secures the tritium dot. Annex C, D, E MT2.11.7 have been updated.

Question 74.

MT 2.8.5 states "The pistol's magazine must have a baseplate that protrudes a minimum of 2.54mm (0.100") up to a maximum of 6.35 mm (0.250") from the front of the pistol's grip". Will Canada accept a revision to a maximum value of 8.35mm vertically from front of the pistol grip? Our pistol magazine plate and grip was designed to allow for maximum ergonomics and positive control. The shape of the magazine plate with the vertical extension allows the operator to grasp and extract it with the supportive hand and is designed to guarantee more grip space beyond the frame grip. This doesn't negatively impact and in fact improves operational control.

Answer 74.

Canada has update MT 2.8.5 to read "The pistol's magazine must have a baseplate that protrudes a minimum of 2.54mm (0.100") up to a maximum of 8.35 mm (0.329") from the front of the pistol's grip". Annex C, D, E MT2.8.5 have been updated to reflect this.

Question 75.

MT 2.8.4 states "The pistol's magazine must have witness holes that aligns with each cartridge in the magazine starting at cartridge number four (4)". Will Canada accept a magazine with witness holes that start at cartridge number four (4) and aligns with cartridge 6, 8, 10, 12, 14 and 17? As the operator should still load the magazine to its full capacity and this can be positively witnessed, the witness holes as described still achieves the goal to the operator despite not showing each cartridge in the magazine and will not affect operational effectiveness.

Answer 75.

Canada will accept a magazine with witness holes that start at cartridge number four (4) and aligns with cartridge 6, 8, 10, 12, 14 and 17. Annex C, D, E MT2.8.4 have been updated to reflect this.

Question 76.

MT 2.11.1 states "The pistol's front sight must be black and must have a yellow or orange coloured glow-in-the-dark photoluminescent outline surrounding a green tritium phosphor-filled glass lamp in the center (round dot)". Does Canada require the photoluminescent outline to be seen at all times (Day/Night) or just during low light conditions?

Answer 76.

The requirement is that the photo luminescent outline must be visible at all times ie during daylight and in the dark. Annex C, D, and E MT 2.11.1 have been updated to reflect this.

Question 77.

MT 2.12.3 states "The training pistol with the submitted weapon light attached must be capable of firing RCMP marking cartridge". Can Canada confirm the RCMP marking cartridge is a standard SIMUNITION cartridge or is it a specific round designed for the RCMP? If specific can the rounds be provided to industry to confirm functionality?

Answer 77.

Currently the RCMP uses Simunition FX Marking and Non-Marking Cartridges for 9mm. The RCMP will not be providing rounds to industry.

Question 78.

Will the Government considering extending this RFP again. The original RFP permitted 40 days to respond to a medium level complexity RFP for four (4) separate items, which included the Christmas holidays, which greatly reduced the time manufactures had to respond. The two-week extension (amendment 001, answer 1) is insufficient as it was based on a trade show and did not consider other factors. Bidders must compile technical and administrative documents from four (4) separate manufactures. Essentially four solicitation compiled into one. The government itself permits a standard 60-day bid validity (2.1 – subsection 5.4 of the Standard acquisition clauses and Conditions Manual) window to review bid submission. The Government exercised its right to extended bid validity to 180 days (an additional 120 days). We would respectfully request that the government extended the closing date by another 60 days. This would be half the time that the government extended its bid validity.

Answer 78.

Canada has amended the closing date to March 22, 2024.

Question 79.

2.2.1 Limitations of Bids – states, "Canada will only accept up to two bids per bidding entity". The way this RFP is written, (technical specification) most bidders may try to include specific ancillary items; more specifically the Aim point RDS, Streamlight weapon light and the Safariland holster, what will the

Government do if they received more than two submission with the same ancillary items from these entities?

Answer 79.

Each bidding entity (bidder) may submit up to two bids. If more than two bids are received, the first two received will be the two retained unless directed otherwise by the bidder. Each bid will be evaluated separately.

Question 80.

Annex E: Performance Evaluation – Can the government confirm what will happen is an ancillary item fails in one bid submission but passes in another. IE the Streamlight TLR-7 is part of three bid submissions, but fails MT 4.5 for one bidder's submission but not the other two. Does this deem the Streamlight TLR-7 non-compliant? Conversely, if it passes for two bidders, but not for the third, will it be deemed compliant for the third?

Answer 80.

Each bid submission must stand on its own merit.

Question 81.

We recommend the Government add the industry standard of round count to the training pistol minimum warranty requirement per 2.2.4.G (warranty period of ten (10) years or 10,000 rounds, whichever comes first).

Answer 81.

As the training pistols will be utilized in a controlled environment, Canada does not see a need to expand the warranty requirement.

Question 82.

We understand per 2.5.8 the pistol must come with a ceremonial lanyard loop that can be attached to the pistol magazines base plate. Would a lanyard loop incorporated into the grip (as per industry standard) so as to not interfere with the magazine form/fit/function be acceptable to the Government? If not, can the Government provide a diagram of this requirement?

Answer 82.

Canada has amended MT2.5.8 and updated Annex C and D. Canada will accept one of the following three (3) methods/options to meet this current requirement:

1. Meet the current requirement
2. Deliver their pistol with standard attachment point subject to it being able to accept the current RCMP issued lanyard clip.
3. Provide a lanyard clip that fits the pistol's current attachment point, subject that the clip will accommodate the current RCMP issued lanyard.

Question 83.

We understand per 2.8.5 the pistols magazine must have a baseplate that protrudes a minimum of 2.54mm up to a maximum of 6.35mm from the front of the pistols grip. This requirement precludes the ability to utilize pistol and magazine accessories such as extended base plates and magazine funnels. Would the Government consider having the baseplate protrude from the sides instead of the front in order to allow for use of wider array of end user accessories?

Answer 83.

No, Canada will not accept any deviations to this requirement. This is an operational requirement that supports the extraction of a magazine that fails to drop/release from the magazine well.

Question 84.

Traditionally U.S. and Canadian Law Enforcement use a standard high visibility 3-dot sighting system with standard tritium dots that appear white in the daylight and glow green at night. Tritium dots are normally green or orange in color and when used in a 3-dot sighting system the dots appear white in the daylight and glow green or orange at night. Would this hi-visibility set-up as illustrated below meet the requirements of 2.11.1?

Answer 84.

Canada cannot validate your offering at this stage of the process. As per criteria of MT 2.11.1 requires that the front sight must be black and must have a yellow or orange coloured glow-in-the-dark photoluminescent outline surround a green tritium phosphor-filled glass lamp in the center (round dot).

Question 85.

We understand per MT 2.12.2 and MT 2.12.3 the training pistol must come with the submitted weapon light attached to it in the same manner as the submitted service pistol. Can the Government confirm the training pistol configuration as being the same as the submitted service pistol would mean the RDS also be mounted and zeroed as stated in RT212.2 and RT 2.12.3

Answer 85.

The training pistol's RDS can be mounted directly to the pistol slide, or can be mounted with an adapter plate interface. There is no evaluated accuracy requirement for the training pistol.

Question 86.

We understand per RT2.11.3 and MT 2.11.3 that the pistols front sights must have a square front post with a width measuring between 3.05mm and 3.68mm, would the Government consider expanding the maximum width to 3.9mm to allow for increased competition?

Answer 86.

No, Canada will not consider deviations to this requirement. Canada has established this specification to meet their operational needs to balance out the width of the front sight with the width and tolerance of the rear sight to allow the shooter to acquire the proper sight alignment rapidly if necessary.

Question 87.

We understand per RT 2.13.1 the slide should be manufactured of stainless steel, can the Government confirm this requirement applies only to the service pistol.

Answer 87.

MT 2.13.1 states that "The slide must be manufactured of steel"; this applies only to the service pistol. The training pistol slide must be manufactured of either steel or aluminum.

Question 88.

We understand per MT 4.3 that the light cannot protrude beyond the muzzle; if the holster contains the pistol with a light, the length of the light should not impact the overall concealability. Could the Government consider increasing the length of this requirement to 1.5cm past the muzzle to increase competition and availability of light options?

Answer 88.

No, Canada will not consider deviations to this requirement. Canada's experience with tactical lights that extend beyond the muzzle of the pistol causes gases to quickly layer onto the lens of the tactical light thus necessitating additional cleaning which accelerates the erosion of the lens surface reducing the clarity and output capacity of the light. The flashlight extending beyond the muzzle of the firearm also extends the overall length of the pistol which will have a negative impact on GBA+ considerations.

Question 89.

Per MT 5.4 we understand the case needs to have a foam insert. Would the Government consider removing the foam insert requirement and allow for a simple foam insert? Doing so would reduce costs to the Government.

Answer 89.

No, Canada will not consider deviations to this requirement. The foam segregation cuts are necessary to better secure the configured pistol, magazines, and components during shipment.

Question 90.

We understand per MT 2.11.10 the rear iron sights must be dovetailed into the slide behind the RDS and be adjustable for windage and elevation. Would the government consider amending this to allow an alternative to the dovetail for to increase RDS options and increase competition?

Answer 90.

No, Canada will not consider deviations to this requirement.

Question 91.

We understand per 3.16, a RDS dot size of 3.5 (MOA) +- .5 MOA is preferred. Would the Government consider a 2 MOA dot is acceptable to allow for finer, more accurate aiming?

Answer 91.

No, Canada will not consider deviation to this requirement. Canada has determined the red dot size based on operational requirements which included our shooting statistics which included distances shot with our current service pistol.

Question 92.

We understand per MT 3.12 the RDS dimensions must be less than or equal to 55.88 mm length. Would the government consider extending this length requirement to 61mm in order to increase competition?

Answer 92.

No, Canada will not consider deviation to this requirement.

Question 93.

We understand per the requirements a level of quality management certification is expected; could the Government confirm that ISO 9001:2015 is an acceptable standard.

Answer 93.

Yes, ISO 9001:2015 is an acceptable standard.

Question 94.

We understand per 3.10, the RDS must be adjustable for elevation and windage at no coarser than 1 Minute of Angle (MOA) per click. Would the Government consider a slight increase to 1.5 MOA per click? The operational difference is minimal - 0.375" of adjustment per click at 1.5 MOA as compared to 0.25" per click at 1 MOA adjustments at 24 meters, or roughly 1/3 the diameter of a 9mm bullet – and would promote greater competition.

Answer 94.

Canada would accept a RDS with 1.5 MOA per click adjustment.
Annex C, D, MT3.10 has been updated to reflect this.

Question 95.

Can the government clarify their response in Amendment 001, answer 2? The clause to have all pistols and maintenance kits supplied under resulting contract must be manufactured in Canada or a NATO country including Australia or New Zealand is used for a reason. We would assume that whatever the reasoning is for the clause that it should apply to all ancillaries' items such as the RDS, Pistol Light and Holster. Why would not all mandatory items requested be subject to the same clause? Can the

government consider amending their response to include all items are subject to this clause or none of them?

Answer 95.

Canada has identified certain origin of goods requirements (Pistols and Preventive Maintenance Kits) as measures that are required to allow Canada to protect national security, public safety, public order, human life and the health, safety based in part in helping to ensure there are no critical capability gaps by helping to create a continuous source of supply of a critical and necessary tool used by Canada's national Police Force and Conservation and Protection Officers in fulfilling its mandate

ALL OTHER TERMS AND CONDITIONS REMAIN UNCHANGED.

ANNEX C RCMP SERVICE PISTOL STATEMENT OF REQUIREMENT

Overview

The Royal Canadian Mounted Police (RCMP) requires a new service pistol to support operations. This document comprises the Statement of Requirement (SOR), detailing the characteristics and technical specifications in accordance with the operational requirements. The pistol must meet all Technical and Performance specifications as specified in the sections that follow. Accessories such as pistol mounted lights as well as slide mounted optics will also be specified. The accessories must be designed to function with the specific firearm as specified herein.


Capability #	Description
1.0 Bundle Specifications	
1.1	The pistol, RDS, LED weapon light, and general duty holster must operate as a system within a minimum temperature range of -40°C to +48°C.
1.2	The pistol with fixed ancillaries (RDS and LED weapon light), must fit in the general duty holster.
1.3	All components of the bundle must be capable of functioning at the same time without affecting performance.
1.4	The pistol with fixed ancillaries (RDS and LED weapon light), must fit in the plain clothes holster.
2.0 Service Pistol Specifications	
2.1.1	The pistol must be capable of firing 20,000 rounds without:
	a. Needing to change the barrel, frame and slide;
	b. Incurring a class 4 event;
	c. Incurring more than 100 pts based on class 1, 2, and 3 events as per evaluation outlined in [RT 2.1.1]; and
2.1.2	d. Needing to change any part due to failure outside the manufacturer's part replacement schedule.
	The pistol's parts, components, magazines, and magazine parts (excluding barrel, frame, and slide) must not require replacement for a minimum of 5000 rounds.
2.1.3	The pistol must have a maximum length of 191 mm (7.52 inches) when measured from the barrel muzzle to the rear of the beavertail.

Capability #	Description
2.1.4	The pistol must have a maximum overall height of a maximum of 148 mm (5.83 inches) measured from the top of the slide to the bottom of the pistol grip with the magazine and RDS removed.
2.1.5	The pistol must have a maximum overall width of 36.1 mm (1.42 inches) measured from slide catch lever to slide catch lever.
2.1.6	The pistol barrel must have a minimum length of 99 mm (3.9 inches) and a maximum length of 108 mm (4.25 inches).
2.1.7	The pistol must not weigh more than a maximum of 822.14 grams (29 oz) when the magazine is empty, and no accessories are attached.
2.2 Ammunition Requirements	
2.2.1	The pistol must be capable of firing 9mm Luger +P ammunition.
2.2.2	The pistol must be capable of shooting a 15.25 cm (6 inches) grouping from 25 m (27.34 yards) away.
2.3 Pistol Lock Mechanism	
2.3.1	The pistol must be a mechanically locked, recoil-operated, striker-fired semi-automatic pistol.
2.3.2	The recoil spring guide must be manufactured of solid metal or polymer.
2.4 Pistol Finish	
2.4.1	The pistol must have a matte black finish on all visibly exposed surfaces when the pistol is fully assembled. Visibly exposed surface parts include grip frame housing, back straps, frame, slide and magazines.

Capability #	Description
2.4.2	The pistol's metal or metal-alloy parts must be made of either a corrosion-resistant material (i.e. stainless steel) or must have a corrosion-resistant surface finish (i.e. DLC).
2.4.3	The parts of the pistol that are normally handled by a user (grip, slide, trigger, and trigger guard) must not have any sharp edges.
2.4.4	The pistol's frame (grip module) must be manufactured of polymer.
2.4.5	The pistol's frame (grip module) must be manufactured to ensure that its shape cannot be distorted when gripped or when accessories are mounted.
2.5 Ergonomic Requirements	
2.5.1	The pistol's grip must accommodate a minimum of three distinct grip sizes (small, medium, and large).
2.5.2	When affixed, the grip options must not come loose or fall off.
2.5.3	The pistol's grip must not have finger grooves.
2.5.4	The pistol's grip frame housing and back strap must be textured.
2.5.5	The underside of the trigger guard and the underside of the beavertail must not be textured.

Capability #	Description
2.5.6	The pistol's front and rear sides (left and right) of the slide must have non-slip grasping grooves.
2.5.7	The pistol must have (an) ambidextrous slide catch lever(s) that enables a user to activate it using either hand.
2.5.8	<p>Each pistol must be provided with one additional base plate that has an attachment point for a ceremonial lanyard loop or meet the following specification:</p> <ol style="list-style-type: none"> 1. Meet the current requirement 2. Deliver their pistol with standard attachment point subject to it being able to accept the current RCMP issued lanyard clip. 3. Provide a lanyard clip that fits the pistol's current attachment point, subject that the clip will accommodate the current RCMP issued lanyard.
2.5.9	A minimum of three (3) of the four (4) sides/edges at the entrance of the magazine well must be beveled or flared and be integrated into the pistol's frame (grip module) in order to aid in the insertion of a magazine.
2.6 Magazine Release	
2.6.1	The pistol's magazine release must be configurable for either a right- or left-handed user.
2.6.2	The pistol must have a push button that will release the magazine when a user presses it by making a lateral movement (from side to side) with their thumb.
2.6.3	The pistol's magazine release must prevent the magazine from being released while firing or handling the pistol.
2.7 Trigger	

Capability #	Description
2.7.1	The pistol's trigger pull weight must be a minimum of 2.27 kg (5.0 lbs.) up to a maximum of 3.18 kg (7.0 lbs.).
2.7.2	The pistol's trigger pull must positively reset when a user releases the trigger following a firing cycle.
2.7.3	The pistol's striker fired mechanism must have a minimum firing pin indent of 0.28 mm (0.011 inch).
2.8 Magazines	
2.8.1	Each pistol must be supplied with three (3) magazines.
2.8.2	The pistol's magazine must have a minimum capacity of seventeen (17) rounds.
2.8.3	The pistol magazine must be manufactured out of stainless steel, plastic, or steel with a durable corrosion resistant finish such as diamond-like carbon coating (DLC). Any alternate finishes not specified must be approved by the technical authority prior to bid closing
2.8.4	The pistol's magazine must have witness holes starting at maximum cartridge number four (4) that either align with each cartridge or align with cartridges 6, 8, 10, 12, 14 and 17.
2.8.5	The pistol's magazine must have a baseplate that protrudes a minimum of 2.54 mm (0.10 inch) up to a maximum of 8.35 mm (0.329 inch) from the front of the pistol's grip.

Capability #	Description
 <p>Figure 1</p>	<p>When the pistol's magazine release button is pressed, the pistol's magazine must drop free from the pistol with the following criteria:</p> <ul style="list-style-type: none"> a) without user intervention; b) when the magazine is loaded and when it is empty; and c) when the slide is in either a forward or rear-locked position.
2.8.6	2.9 Rail System
2.9	The pistol must have a Picatinny MIL-STD-1913 compatible rail system that is integrated into the pistol's frame dust cover.
	2.10 Safety Features
2.10.1	The pistol must have no external manual safety levers, grip safeties, and push-button safeties.
2.10.2	The pistol must enable a user to discharge a cartridge with the pistol's magazine removed.

Capability #	Description
2.10.3	The pistol must have an internal firing pin safety.
2.10.4	The pistol must have a mechanical safety to prevent a user from firing the pistol when not in battery (slide not fully forward and unlocked).
2.10.5	The pistol must have either a visual or tactile indicator that alerts a user that the pistol's chamber is loaded.
2.10.6	The pistol must have a safety feature that prevents the pistol from firing and firing pin from moving forward when dropped.
2.11 Iron Sights	
2.11.1	The pistol's front sight must be black and must have a yellow or orange coloured glow-in-the-dark photoluminescent outline surrounding a green tritium phosphor-filled glass lamp in the center (round dot). The photo luminescent outline must be visible at all times ie. during daylight and in the dark.
2.11.2	The pistol with iron sights and the pistol with RDS must shoot to point of aim within a 5.08 cm (2 inches) radius at 25 m (27.34 yards).
2.11.3	The pistol's front sights must have a square front post with a width measuring between 3.05 mm (0.120 inch) and 3.68 mm (0.145 inch).
2.11.4	<p>The pistol's rear sight must have each of the following:</p> <ul style="list-style-type: none"> a) a square or u-shaped notch; b) a surface that will reduce glare to assist a user with front sight focus; and c) a notch width between 4.57 mm (0.180 inch) and 5.46 mm (0.215 inch).

Capability #	Description
2.11.5	The pistol's front sight tritium glass lamp must be protected with a mechanism that will prevent the removal of the coloured portion of the front sight when using cleaning or chemical products on the pistol.
2.11.6	The pistol's rear sight must be black.
2.11.7	The pistol's rear sight tritium vials must be green surrounded with a black outline. The small metal tube ring that secures the tritium dot can be of a metallic color.
2.11.8	The pistol's front and rear sights must be replaceable.
2.11.9	The pistol's rear sight must enable a user to adjust it for windage.
2.11.10	The pistol's rear iron sight dovetail must be milled to the pistol's slide.
2.11.11	The pistol's sights must have a fixed elevation.
2.12	Training Pistol Specifications
2.12.1	The training pistol must be blue, inclusive of the magazine baseplate.
2.12.2	The training pistol must come with the submitted weapon light attached to it in the same manner as the submitted service pistol.
2.12.3	The training pistol with the submitted weapon light attached must be capable of firing RCMP marking cartridges. Canada's requirement is for the training pistol to be a replica of the offered duty pistol and to work with the duty holster that will come with the duty pistol.

Capability #	Description
	Canada requires the training pistol to use the same holster as the duty pistol.
2.13 Pistol Slide Specifications	
2.13.1	The duty pistol slide must be manufactured of steel.
2.13.2	The slide must have a durable finish that is resistant to rust and salt water corrosion.
3.0 Red Dot Sight (RDS) Specifications	
3.1	The red dot sight (RDS) must be configured to directly mount to the pistol slide.
3.2	The RDS mounting surface must be machined to enable a user to view the pistol's front and rear iron sights when using the pistol.
3.3	The RDS must enable a user to view the pistol's iron sights through the RDS at a lower 1/3 co-witness.
3.4	The RDS mounting screw(s) must be made of steel.
3.5	The RDS must function and maintain zero (0) within a temperature range of -40°C to +48°C for a minimum of 4 hours.
3.6	The RDS housing must be made of hard anodized aluminum alloy with a non-reflective, matte black finish. Any alternate material not specified must be approved by the technical authority prior to bid closing.
3.7	Including the battery, the RDS must weigh no more than 62 g (2.19 oz.).

Capability #	Description
3.8	The RDS magnification must be 1X.
3.9	The RDS must be parallax free within 25m (27.3 yds).
3.10	The RDS must have flush mounted elevation and windage click adjustments that will enable a user to adjust for elevation and windage at no coarser than 1.5 Minute of Angle (MOA) per click.
3.11	The RDS must have a minimum clear aperture of 15 mm (.59 inch) in both width and height.
3.12	The RDS exterior dimensions must be less than or equal to 55.88 mm (2.2 inch) long x 34.3 mm (1.35 inch) wide x 34.3 mm (1.35 inch) in height.
3.13	The RDS dot intensity switch must be positioned to adjust by the support hand.
3.14	The RDS dot intensity switch must be flush mounted and use a pliable or soft material that must function under operational temperature requirements as specified in MT 1.1.
3.15	The RDS must have a minimum of 8 dot intensity settings.
3.16	The RDS dot must be red and must be $3.5 \text{ (MOA)} \pm .5 \text{ MOA}$ in size.
3.17	The RDS optic lenses must have a coating that does not create a glare or reflection for the user.

Capability #	Description
3.18	When viewed from the rear of the optic, the RDS field of view must be clear and true to colour.
3.19	The RDS must use a coin cell Lithium battery with a minimum battery life of two (2) years when operating at the middle dot intensity setting (room temperature, constant on).
3.20	When set to high, the RDS dot intensity setting must enable a user to view the red dot in bright lighting conditions (i.e. outdoors in sunlight) at a distance of 6.4m (7 yards).
3.21	The user must be able to change the RDS battery without having to remove the RDS from the pistol slide.
3.22	The RDS must be waterproof to a rating of IPX7 as defined in ANSI/ NEMA FL 1-2009.
3.23	When affixed to the pistol with a loaded magazine and after being dropped from 1.3 meters, the RDS must: a) remain affixed to the pistol; b) maintain the ability to see the red dot; and c) maintain its 0.
3.24	The RDS must have one or more dot intensity settings for night vision.
	4.0 LED Weapon Light Specification

Capability #	Description
4.1	The LED weapon light must mount on a Picatinny MIL-STD-1913 pistol rail.
4.2	LED Weapon Light Dimensions
4.2.1	The LED weapon light must have a maximum height of 32.2 mm (1.27 inches).
4.2.2	The LED weapon light must have a maximum width of 29.8 mm (1.18 inches).
4.2.3	The LED weapon light must have a maximum length of 65.5 mm (2.58 inches).
4.2.4	Including the battery, the LED weapon light must have a maximum weight of 68.1 g (2.4 oz.).
4.3	The LED weapon light must not protrude beyond the muzzle of the pistol.
4.4	The LED weapon light must have ambidextrous, rear activated operating and switching controls.
4.5	The LED weapon light's operating and switching controls must include each of the following settings: a) momentary on; and b) constant on.
4.6	The LED weapon light must have ambidextrous high and low switch configurations.

Capability #	Description
4.7	The LED weapon light must include a lockout feature that will prevent the LED weapon light from being accidentally activated.
4.8	The LED weapon light must be a light emitting diode (LED) light with a minimum output of 500 lumens and a minimum run time of 1.5 hours.
4.9	When affixed to the pistol with a loaded magazine and after being dropped from 121.9 cm the LED weapon light, whether still affixed or detached from the pistol after the drop, must maintain function of: a) momentary on; and b) constant on.
4.10	When affixed to the pistol with a loaded magazine and after being dropped from 121.9 cm, the LED weapon light glass must not break, become dislodged, or fall out.
4.11	The LED weapon light lens must be made of heat resistant glass.
4.12	The LED weapon light lens must be scratch resistant.
4.13	The LED weapon light must use a lithium 3 Volt CR123A battery.
4.14	The LED weapon light must have a hard anodized aluminum body.
4.15	The LED weapon light must have a minimum waterproof rating of IPX7 as defined in ANSI/ NEMA FL 1-2009.

Capability #	Description
4.16	The user must be able to replace the LED weapon light battery without having to remove the LED weapon light from the pistol.
5.0 Carrying Case	
5.1	The carrying case must have maximum external dimensions of 38.1 cm (15 inches) in width, 30.5 cm (12 inches) in height, and 15.24 cm (6 inches) in depth to hold the configured pistol with RDS and LED weapon light, and three magazines, along with pistol accessories such as grip components.
5.2	The carrying case must be equipped with a minimum of two (2) latching devices.
5.3	The carrying case must include two (2) separated securing eyelets with a minimum diameter of 7 mm (0.276 inch) and a maximum diameter of 9 mm (0.354 inch) that when locked with two (2) RCMP approved locks will secure the case from being pried open by hand.
5.4	The carrying case must include a foam insert that does not absorb water and is cut to secure and segregate the configured pistol with RDS and weapon light installed, grip components and three magazines by a minimum of 1.91 cm (0.75 inch) on all sides. The ASTM D3575 (L: Water Absorption) test standard is acceptable and will meet the RCMP requirement.
5.5	The carrying case must have a carrying handle.
5.6	The carrying case must have a hinged lid that will hold open when empty or lay flat when opened.
5.7	The carrying case must be stackable.

Capability #	Description
5.8	The carrying case must be opaque so that the contents within the case are not visible when the case is closed.
5.9	<p>The carrying case must not be embossed with any name, logo* nor any markings which could indicate the content as a firearm.</p> <p>*Canada will accept the logo of the carrying case manufacturer on the carrying case but no markings that would indicate the contents of the carrying case being a firearm in any way</p>
5.10	The carrying case must be coloured black or in grey tones.
6.0 Pistol Holster - General Duty	
6.1	The holster must be available in a left- and right-handed configuration.
6.2	The holster must be able to secure the configured pistol with RDS and LED weapon light.
6.3	The pistol must remain in the holster and the holster must not sustain any damage when evaluated in accordance with RCMP-UEP SP 2-2022 Standard Practice for Evaluation of Pistol Holster Retention Mechanism(s).
6.4	The holster must have two (2) mechanical locking devices to keep the pistol in the holster, including:
	a) an automatic locking system, and b) a self-locking system.

Capability #	Description
6.5	The holster's mechanical locking devices must release the pistol from the holster when a user performs two (2) opposing, sequential motions.
6.6	The holster's automatic locking system must offer retention in all directions for both left and right-handed holsters.
6.7	The holster must enable the user to have full access to the grip of the pistol before drawing the pistol out.
6.8	The holster's retention and locking mechanisms must be positioned on the top forward portion of the holster to enable a user to draw the pistol with their dominant or nondominant hand.
6.9	The holster must have a locking mechanism that can be serviced by a user (i.e. cleaning and adjustments).
6.10	When the holster's retention features are deactivated, the holster must enable a user to draw the pistol parallel to the body.
6.11	The holster must be made of a durable, polymer material with a non-reflective, matte black surface finish.
6.12	The holster must protect the magazine release from inadvertently releasing the magazine while in the holster.
6.13	The holster must shroud the RDS and rear sight from view when in a locked and holstered position.

Capability #	Description
6.14	The holster's locking mechanism must feature a shroud to prevent an inadvertent release of the locking mechanism.
6.15	The holster must mount to an in-service duty belt that ranges from 5.0 cm (1.97 inch) to 5.7 cm (2.24 inches) in width and 3 mm (0.12 inch) to 5 mm (0.2 inch) thickness limiting unnecessary movement. It is acceptable if the holster is capable of being mounted to a MOLLE duty belt with a different back plate. The back plate must be included in each Pistol Package
6.16	The holster must remain attached to the in-service nylon duty belt when force is applied in accordance with RCMP-UEP SP 3-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).
6.17	The pistol must remain in the holster when force is applied in accordance with RCMP-UEP SP 2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).
6.18	The holster must not migrate while in use on the in-service duty belt.
6.19	The holster's exterior and interior metal parts and springs must feature corrosion-resistant material (i.e. stainless steel) or corrosion-resistant surface finish (i.e. electropolating).
6.20	The bottom of the holster must have (a) drain hole(s) or be open.
6.21	The holster must not scratch the surface finish of the pistol.
6.22	The RDS holster shroud must not impede holstering of the configured pistol.
6.23	The holster must mount to an MOLLE duty belt. It is acceptable if the holster is capable of being mounted to a MOLLE duty belt with

Capability #	Description
	a different back plate. The back plate must be included in each Pistol Package
7.0	Pistol Holster - Plain Clothes
7.1	The holster must be available in a left- and right-handed configuration.
7.2	The holster must be able to secure the configured pistol with RDS and LED weapon light installed.
7.3	The pistol must remain in the holster and the holster must not sustain any damage when evaluated in accordance with RCMP-UEP SP 2-2022 Standard Practice for Evaluation of Pistol Holster Retention Mechanism(s).
7.4	The holster must have one (1) mechanical automatic locking device to keep the pistol in the holster.
7.5	The holster's automatic locking device must offer retention in all directions for both left- and right-handed holsters.
7.6	The holster must enable the user to have full access to the grip of the pistol before drawing the pistol out.
7.7	The holster's retention/locking release mechanism must be positioned on the top forward portion of the holster to enable a user to draw the pistol with their dominant or non-dominant hand.
7.8	The holster must have a locking mechanism that can be serviced by a user (i.e. cleaning and adjustments).
7.9	When the holster's retention features are deactivated, the holster must enable a user to draw the pistol parallel to the body.

Capability #	Description
7.10	The holster must be made of a durable polymer material with a non-reflective, matte black surface finish.
7.11	The holster must protect the magazine release from inadvertently releasing the magazine while in the holster.
7.12	The holster must prevent unnecessary movement in accordance with RCMP-UEP SP 3-2022 (Standard Practice for Evaluation of Pistol Holster Belt Slide Attachments).
7.13	The holster must mount to a belt that ranges from 3.66 cm (1.44 inches) to 5.7 cm (2.24 inches) in width and 3 mm (0.12 inch) to 5 mm (0.2 inch) thickness, limiting unnecessary movement.
7.14	The holster must remain attached to the wearers belt (G.S. 1045-122 Belt, Waist, Leather, Black dated 2018-08-29) when force is applied in accordance with RCMP-UEP SP2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).
7.15	The holster must not migrate while in use on the user's belt.
7.16	The holster's exterior and interior metal parts and springs must feature corrosion-resistant material (i.e. stainless steel) or corrosion-resistant surface finish (i.e. electropolating).
7.17	The bottom of the holster must have (a) drain hole(s) or be open.
7.18	The holster must not scratch the surface finish of the pistol.

ANNEX D: MANDATORY TECHNICAL & RATED CRITERIA

A. PART 1 - MANDATORY TECHNICAL CRITERIA

The bidder is requested to provide technical documentation such as user manuals, screenshots, design or technical documents, as well as other accredited independent third-party information to support the Bidder's response to each requirement. Links to websites are not acceptable and any reference material listed by the Bidder to demonstrate compliance on a criterion is requested to be part of the bid (soft copy). If it is not included in the bid, it will not be taken into consideration by Canada. The Bidder should direct Canada to the appropriate location in the bid documentation.

Only bids that meet the mandatory technical criteria will be subject to point rating technical criteria. Bidders must meet the mandatory technical evaluation criteria in order to be found technically compliant otherwise they will be considered non-compliant and their bid will not be given further consideration. Bidders who do not meet one or more rated technical criteria will not achieve the corresponding points, but will not be eliminated from the process as a result.

Technical Evaluation Criteria (Mandatory)				
Pistol Bundle		Description	Method of Evaluation	Compliance (Y/N)
Number				Reference (Bid Page No.)
MT 1.1	The pistol, RDS, LED weapon light, and general duty holster must operate as a system within a minimum temperature range of -40°C to +48°C.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility		
MT 1.2	The pistol with fixed ancillaries (RDS and LED weapon light), must fit in the general duty holster.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents		

		<p>Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>		
MT 1.3	All components of the bundle must be capable of functioning at the same time without affecting performance.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>		
MT 1.4	The pistol with fixed ancillaries (RDS and LED weapon light) must fit in the plain clothes holster.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>		
Service Pistol Specifications				
MT 2.1.1	<p>The pistol must be capable of firing 20,000 rounds without:</p> <ul style="list-style-type: none"> a. Needing to change the barrel; b. Incurring a class 4 event; c. Incurring more than 100 pts based on class 1, 2, and 3 events 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets</p>		

	as per evaluation outlined in [RT 2.1.1]; and d. Needing to change any part due to failure outside the manufacturer's part replacement schedule.	Photos User manuals Test results from an accredited independent third-party testing facility
MT 2.1.2	The pistol's parts, components, magazines, and magazine parts (excluding barrel, frame, and slide) must not require replacement for a minimum of 5000 rounds.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 2.1.3	The pistol must have a maximum length of 191 mm (7.52 inches) when measured from the barrel muzzle to the rear of the beavertail.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 2.1.4	The pistol must have a maximum overall height of 148 mm (5.83 inches) measured from the top of the slide to the bottom of the pistol grip with the magazine and RDS removed.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility

MT 2.1.5	The pistol must have a maximum overall width of 36.1 mm (1.42 inches) measured from slide catch lever to slide catch lever.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 2.1.6	The pistol barrel must have a minimum length of 99 mm (3.9 inches) and a maximum length of 108 mm (4.25 inches).	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 2.2.1	The pistol must be capable of firing 9mm Luger +P ammunition.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p>	

		<p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
	MT 2.2.2	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p> <p>The pistol must be capable of shooting a 15.25 cm (6 inch) grouping from 25 m (27.34 yards) away.</p>	
	MT 2.3.1	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p> <p>The pistol must be a mechanically-locked, recoil-operated, striker-fired semi-automatic pistol.</p>	
	MT 2.3.2	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos</p> <p>The recoil spring guide must be manufactured of solid metal or polymer.</p>	

		User manuals Test results from an accredited independent third-party testing facility	
	MT 2.4.1	<p>The pistol must have a matte black finish on all visibly exposed surfaces when the pistol is fully assembled. Visibly exposed surface parts include grip frame housing, back straps, frame, slide and magazines.</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p>
	MT 2.4.2	<p>The pistol's metal or metal-alloy parts must be made of either a corrosion-resistant material (i.e. stainless steel) or must have a corrosion-resistant surface finish (i.e. DLC).</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>
	MT 2.4.3	<p>The parts of the pistol that are normally handled by a user (grip, slide, trigger, and trigger guard) must not have any sharp edges.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>

		The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 2.4.4	The pistol's frame (grip module) must be manufactured of polymer.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 2.4.5	The pistol's frame (grip module) must be manufactured to ensure that its shape cannot be distorted when gripped or when accessories are mounted.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 2.5.1	The pistol's grip must accommodate a minimum of three distinct grip sizes (small, medium, and large).	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 2.5.2	When affixed, the grip options must not come loose or fall off.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents	

		<p>Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
	MT 2.5.3	<p>The pistol's grip must not have finger grooves.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>
	MT 2.5.4	<p>The pistol's grip frame housing and back strap must be textured.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>
	MT 2.5.5	<p>The underside of the trigger guard and the underside of the beavertail must not be textured.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals</p>

		Test results from an accredited independent third-party testing facility	
MT 2.5.6	The pistol's front and rear sides (left and right) of the slide must have non-slip grasping grooves.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	
MT 2.5.7	The pistol must have (an) ambidextrous slide catch lever(s) that enables a user to activate it using either hand.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	
MT 2.5.8	<p>Each pistol must be provided with one additional base plate that has an attachment point for a ceremonial lanyard loop or meet the following specification:</p> <ol style="list-style-type: none"> 1. Meet the current requirement 2. Deliver their pistol with standard attachment point subject to it being able to accept the current RCMP issued lanyard clip. 3. Provide a lanyard clip that fits the pistol's current attachment point, subject that the clip will accommodate the current RCMP issued lanyard. 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	

		The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 2.5.9	A minimum of three (3) of the four (4) sides/edges at the entrance of the magazine well must be beveled or flared and be integrated into the pistol's frame (grip module) in order to aid in the insertion of a magazine.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 2.6.1	The pistol's magazine release must be configurable for either a right or left handed user.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 2.6.2	The pistol must have a push button that will release the magazine when a user presses it by making a lateral movement (from side to side) with their thumb.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 2.6.3	The pistol's magazine release must prevent the magazine from being released while firing or handling the pistol.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents	

		<p>Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals</p>
	MT 2.7.1	<p>The pistol's trigger pull weight must be a minimum of 2.27kg (5.0 lbs) up to a maximum of 3.18kg (7.0 lbs).</p>		<p>The pistol's trigger pull must positively reset when a user releases the trigger following a firing cycle.</p>	
	MT 2.7.2				
	MT 2.7.3		<p>The pistol's striker fired mechanism must have a minimum firing pin indent of 0.28 mm (0.011 inches)</p>		

		Test results from an accredited independent third-party testing facility	
MT 2.8.1	Each pistol must be supplied with three (3) magazines.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	
MT 2.8.2	The pistol's magazine must have a minimum capacity of seventeen (17) rounds.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	
MT 2.8.3	<p>The pistol magazine must be manufactured out of stainless steel, plastic, or steel with a durable corrosion resistant finish such as diamond-like carbon coating (DLC). Any alternate finishes not specified must be approved by the technical authority prior to bid closing.</p>		<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility

		The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 2.8.4	The pistol's magazine must have witness holes starting at maximum cartridge number four (4) that either align with each cartridge or align with cartridges 6, 8, 10, 12, 14 and 17.	The pistol's magazine must have a baseplate that protrudes a minimum of 2.54 mm (0.10 inch) up to a maximum of 8.35 mm (0.329 inch) from the front of the pistol's grip.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 2.8.5			The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 2.8.6		When the pistol's magazine release button is pressed, the pistol's magazine must drop free from the pistol with the following criteria: a) without user intervention, b) when the magazine is loaded and when it is empty, and c) when the slide is in either a forward or rear-locked position.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 2.9	The pistol must have a Picatinny MIL-STD-1913 compatible rail system that is integrated into the pistol's frame dust cover.		The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents

		<p>Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals</p>
	MT 2.10.1	<p>The pistol must have no external manual safety levers, grip safeties, and push-button safeties.</p>			
	MT 2.10.2	<p>The pistol must enable a user to discharge a cartridge with the pistol's magazine removed.</p>			
	MT 2.10.3	<p>The pistol must have an internal firing pin safety.</p>			

		Test results from an accredited independent third-party testing facility	
MT 2.10.4	The pistol must have a mechanical safety to prevent a user from firing the pistol when not in battery (slide not fully forward and unlocked).	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 2.10.5	The pistol must have either a visual or tactile indicator that alerts a user that the pistol's chamber is loaded.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 2.10.6	The pistol must have a safety feature that prevents the pistol from firing and the firing pin from moving forward when dropped.		

	c) A notch width between 4.57 mm (0.180 inch) and 5.46 mm (0.215 inch).	Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
	MT 2.11.5 The pistol's front sight tritium glass lamp must be protected with a mechanism that will prevent the removal of the coloured portion of the front sight when using cleaning or chemical products on the pistol.	Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
	MT 2.11.6 The pistol's rear sight must be black.		The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals
	MT 2.11.7 The pistol's rear sight tritium vials must be green surrounded with a black outline. The small metal tube ring that secures the tritium dot can be of a metallic color.		

		Test results from an accredited independent third-party testing facility	
MT 2.11.8	The pistol's front and rear sights must be replaceable.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 2.11.9	The pistol's rear sight must enable a user to adjust it for windage.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 2.11.10	The pistol's rear iron sight dovetail must be milled to the pistol's slide.		

		The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 2.11.11	The pistol's sights must have a fixed elevation.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 2.12.1	The training pistol must be blue, inclusive of the magazine baseplate.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 2.12.2	The training pistol must come with the submitted weapon light attached to it in the same manner as the submitted service pistol.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 2.12.3	The training pistol with the submitted weapon light attached must be capable of firing RCMP marking cartridges. Canada's requirement is for the training	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents	

	<p>pistol to be a replica of the offered duty pistol and to work with the duty holster that will come with the duty pistol.</p> <p>Canada requires the training pistol to use the same holster as the duty pistol.</p>	<p>Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
	<p>The duty pistol slide must be manufactured of steel.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
MT 2.13.1			
MT 2.13.2	<p>The slide must have a durable finish that is resistant to rust and salt water corrosion.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
	<p>Red Dot Sight (RDS)</p>		
MT 3.1	<p>The red dot sight (RDS) must be configured to direct mount to the pistol slide.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos</p>	

	User manuals Test results from an accredited independent third-party testing facility	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 3.2	The RDS mounting surface must be machined to enable a user to view the pistol's front and rear iron sights when using the pistol.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 3.3	The RDS must enable a user to view the pistol's iron sights through the RDS at a lower 1/3 co-witness.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 3.4	The RDS mounting screw(s) must be made of steel.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	

		The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 3.5	The RDS must function and maintain 0 within a temperature range of -40°C to +48°C for a minimum of 4 hours.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 3.6	The RDS housing must be made of hard anodized aluminum alloy with a non-reflective, matte black finish. Any alternate material not specified must be approved by the technical authority prior to bid closing.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 3.7	Including the battery, the RDS must weigh no more than 62 g (2.19 oz.)	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 3.8	The RDS magnification must be 1X.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents	

		<p>Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
		<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
MT 3.9	The RDS must be parallax free within 25 m (27.3 yds).	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
MT 3.10	<p>The RDS must have flush mounted elevation and windage click adjustments that will enable a user to adjust for elevation and windage at no coarser than 1.5 Minute of Angle (MOA) per click.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
MT 3.11	The RDS must have a minimum clear aperture of 15 mm (0.59 inch) in both width and height.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals</p>	

		Test results from an accredited independent third-party testing facility	
MT 3.12	The RDS exterior dimensions must be less than or equal to 55.88 mm (2.2 inch) long x 34.3 mm (1.35 inch) wide x 34.3 mm (1.35 inch) in height.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	
MT 3.13	The RDS dot intensity switch must be positioned to adjust by the support hand.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	
MT 3.14	The RDS dot intensity switch must be flush mounted and use a pliable or soft material that must function under operational temperature requirements as specified in MT 1.1.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	

		The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 3.15	The RDS must have a minimum of 8 dot intensity settings.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 3.16	The RDS dot must be red and must be 3.5 ± .5 MOA in size.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 3.17	The RDS optic lenses must have a coating that does not create a glare or reflection for the user.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 3.18	When viewed from the rear of the optic, the RDS field of view must be clear and true to colour.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents	

		<p>Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	<p>The RDS must use a coin cell Lithium battery with a minimum battery life of two (2) years when operating at the middle dot intensity setting (room temperature, constant on).</p>	<p>When set to high, the RDS dot intensity setting must enable a user to view the red dot in bright lighting conditions (i.e. outdoors in sunlight) at a distance of 6.4m (7 yards).</p>	<p>The user must be able to change the RDS battery without having to remove the RDS from the pistol slide.</p>
	MT 3.19					
	MT 3.20					
	MT 3.21					

		Test results from an accredited independent third-party testing facility	
MT 3.22	The RDS must be waterproof to a rating of IPX7 as defined in ANSI/NEMA FL 1-2009.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	
MT 3.23	<p>When affixed to the pistol with a loaded magazine and after being dropped from 121.9cm, the RDS must:</p> <ol style="list-style-type: none"> a) remain affixed to the pistol; b) maintain the ability to see the red dot; and c) maintain its 0. 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	
MT 3.24	The RDS must have one or more dot intensity settings for night vision.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	LED Weapon Light

		The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 4.1	The LED weapon light must mount on a Picatinny MIL-STD-1913 pistol rail.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 4.2.1	The LED weapon light must have a maximum height of 32.2 mm (1.27 inches).	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 4.2.2	The LED weapon light must have a maximum width of 29.8 mm (1.18 inches).	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 4.2.3	The LED weapon light must have a maximum length of 65.5 mm (2.58 inches).	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents

		<p>Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
	<p>Including the battery, the weapon light must have a maximum weight of 68.1 g (2.4 oz.)</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
MT 4.3	<p>The LED weapon light must not protrude beyond the muzzle of the pistol.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
MT 4.4	<p>The LED weapon light must have ambidextrous, rear activated operating and switching controls.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals</p>	

		Test results from an accredited independent third-party testing facility	
	MT 4.5	<p>The LED weapon light's operating and switching controls must include each of the following settings:</p> <ul style="list-style-type: none"> a) momentary on; and b) constant on. 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
	MT 4.6	The LED weapon light must have ambidextrous high and low switch configurations.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
	MT 4.7	The LED weapon light must include a lockout feature that will prevent the LED weapon light from being accidentally activated.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility

		The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 4.8	The LED weapon light must be a light emitting diode (LED) light with a minimum output of 500 lumens and a minimum run time of 1.5 hours.	When affixed to the pistol with a loaded magazine and after being dropped from 121.9 cm the LED weapon light, whether still affixed or detached from the pistol after the drop, must maintain function of: a) momentary on; and b) constant on.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 4.9	MT 4.10	When affixed to the pistol with a loaded magazine and after being dropped from 121.9 cm, the LED weapon light glass must not break, become dislodged, or fall out.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 4.11	The LED weapon light lens must be made of heat resistant glass.		The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents

		<p>Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
	MT 4.12	<p>The LED weapon light lens must be scratch resistant.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>
	MT 4.13	<p>The LED weapon light must use a lithium 3 Volt CR123A battery.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>
	MT 4.14	<p>The LED weapon light must have a hard anodized aluminum body.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals</p>

		Test results from an accredited independent third-party testing facility	
MT 4.15	The LED weapon light must have a minimum waterproof rating of IPX7 as defined in ANSI/ NEMA FL 1-2009.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	
MT 4.16	The user must be able to replace the LED weapon light battery without having to remove the LED weapon light from the pistol.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	
Carrying Case		<p>The carrying case must have maximum external dimensions of 38.1 cm (15 inches) in width, 30.5 cm (12 inches) in height, and 15.24 cm (6 inches) in depth to hold the configured pistol with RDS and LED weapon light, and three magazines, along with pistol accessories such as grip components.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility

		The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility	
MT 5.2	The carrying case must be equipped with a minimum of two (2) latching devices.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
MT 5.3	<p>The carrying case must include two (2) separated securing eyelets with a minimum diameter of 7 mm (0.276 inch) and a maximum diameter of 9 mm (0.354 inch) that when locked with two (2) RCMP approved locks will secure the case from being pried open by hand.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
MT 5.4	<p>The carrying case must include a foam insert that does not absorb water and is cut to secure and segregate the configured pistol with RDS and weapon light installed, grip components and three magazines by a minimum of 1.91 cm (0.75 inch) on all sides.</p> <p>The ASTM D3575 (L: Water Absorption) test standard is acceptable and will meet the RCMP requirement</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
MT 5.5	<p>The carrying case must have a carrying handle.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents</p>	

		<p>Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
	MT 5.6	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p> <p>The carrying case must have a hinged lid that will hold open when empty or lay flat when opened.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>
	MT 5.7	<p>The carrying case must be stackable.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>
	MT 5.8	<p>The carrying case must be opaque so that the contents within the case are not visible when the case is closed.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals</p>

		Test results from an accredited independent third-party testing facility	
	The carrying case must not be embossed with any name, logo*, nor any markings which could indicate the content as a firearm. *Canada will accept the logo of the carrying case manufacturer on the carrying case but no markings that would indicate the contents of the carrying case being a firearm in any way	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	
MT 5.9		<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	
General Duty Holster			
MT 6.1	The holster must be available in a left- and right-handed configuration.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals 	

		Test results from an accredited independent third-party testing facility	
MT 6.2	The holster must be able to secure the configured pistol with RDS and weapon light.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 6.3	The pistol must remain in the holster and the holster must not sustain any damage when evaluated in accordance with RCMP-UEP SP 2-2022 Standard Practice for Evaluation of Pistol Holster Retention Mechanism(s).	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 6.4	The holster must have two (2) mechanical locking devices to keep the pistol in the holster, including: a) an automatic locking system; and b) a self-locking system.		

		The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 6.5	The holster's mechanical locking devices must release the pistol from the holster when a user performs two (2) opposing, sequential motions.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 6.6	The holster's automatic locking system must offer retention in all directions for both left and right-handed holsters.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 6.7	The holster must enable the user to have full access to the grip of the pistol before drawing the pistol out.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 6.8	The holster's retention and locking mechanisms must be positioned on the top forward portion of the holster to enable a user to draw the pistol with their dominant or nondominant hand.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents

		<p>Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
	MT 6.9	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p> <p>The holster must have a locking mechanism that can be serviced by a user (i.e. cleaning and adjustments).</p>	
	MT 6.10	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p> <p>When the holster's retention features are deactivated, the holster must enable a user to draw the pistol parallel to the body.</p>	
	MT 6.11	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals</p> <p>The holster must be made of a durable, polymer material with a non-reflective, matte black surface finish.</p>	

		Test results from an accredited independent third-party testing facility	
MT 6.12	The holster must protect the magazine release from inadvertently releasing the magazine while in the holster.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 6.13	The holster must shroud the RDS and rear sight from view when in a locked and holstered position.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 6.14	The holster's locking mechanism must feature a shroud to prevent an inadvertent release of the locking mechanism.		

		<p>Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
	MT 6.19	<p>The holster's exterior and interior metal parts and springs must feature corrosion-resistant material (i.e. stainless steel) or corrosion-resistant surface finish (i.e. electroplating).</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
	MT 6.20	<p>The bottom of the holster must have (a) drain hole(s) or be open.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
	MT 6.21	<p>The holster must not scratch the surface finish of the pistol.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals</p>	

		Test results from an accredited independent third-party testing facility	
MT 6.22	The RDS holster shroud must not impede holstering of the configured pistol.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals <p>Test results from an accredited independent third-party testing facility</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals <p>Test results from an accredited independent third-party testing facility</p>
	MT 6.23	<p>The holster must mount to a MOLLE duty belt.</p> <p>It is acceptable if the holster is capable of being mounted to a MOLLE duty belt with a different back plate. The back plate must be included in each Pistol Package</p>	<p>The holster must mount to a MOLLE duty belt.</p> <p>It is acceptable if the holster is capable of being mounted to a MOLLE duty belt with a different back plate. The back plate must be included in each Pistol Package</p>

Plain Clothes Holster	The holster must be available in a left- and right-handed configuration.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 7.1	The holster must be able to secure the configured pistol with RDS and LED weapon light installed.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 7.2	The pistol must remain in the holster and the holster must not sustain any damage when evaluated in accordance with RCMP-JEP SP 2-2022 Standard Practice for Evaluation of Pistol Holster Retention Mechanism(s).	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to: Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 7.3	The holster must have one (1) mechanical automatic locking device to keep the pistol in the holster.	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:
MT 7.4		

	Test results from an accredited independent third-party testing facility	
MT 7.8	The holster must have a locking mechanism that can be serviced by a user (i.e. cleaning and adjustments).	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 7.9	When the holster's retention features are deactivated, the holster must enable a user to draw the pistol parallel to the body.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
MT 7.10	The holster must be made of a durable polymer material with a non-reflective, matte black surface finish.	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility

The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:	<ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:	<ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
The holster must protect the magazine release from inadvertently releasing the magazine while in the holster.	<p>The holster must prevent unnecessary movement in accordance with RCMP-UEP SP 3-2022 (Standard Practice for Evaluation of Pistol Holster Belt Slide Attachments).</p> <p>MT 7.12</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility 	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility
The holster must mount to a belt that ranges from 3.66 cm (1.44 inches) to 5.7 cm (2.24 inches) in width and 3 mm (0.12 inch) to 5 mm (0.2 inch) thickness, limiting unnecessary movement.	<p>MT 7.13</p>	<p>The bidder must remain attached to the wearers belt (G.S. 1045-122 Belt, Waist, Leather, Black dated 2018-08-29) when force is applied in accordance with RCMP-UEP SP2-2022 (Standard Practice</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents

		<p>Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>	
	MT 7.15	<p>The holster must not migrate while in use on the user's belt.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>
	MT 7.16	<p>The holster's exterior and interior metal parts and springs must feature corrosion-resistant material (i.e. stainless steel) or corrosion-resistant surface finish (i.e. electroplating).</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals Test results from an accredited independent third-party testing facility</p>
	MT 7.17	<p>The bottom of the holster must have (a) drain hole(s) or be open.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <p>Design documents Technical Documents Manufacturer Specification sheets Photos User manuals</p>

	<p>The holster must not scratch the surface finish of the pistol.</p>	<p>The bidder must provide written documentation that demonstrates how this requirement is met. Such as but not limited to:</p> <ul style="list-style-type: none"> Design documents Technical Documents Manufacturer Specification sheets Photos User manuals <p>Test results from an accredited independent third-party testing facility</p>
	MT 7.18	

PART 2 - RATED TECHNICAL CRITERIA

The bidder is required to provide technical documentation such as user manuals, screenshots, design or technical documents, as well as other accredited independent third-party information to support the Bidder's response to each requirement. Links to websites are not acceptable and any reference material listed by the Bidder to demonstrate compliance on a criterion is requested to be part of the bid (soft copy). If it is not included in the bid, it will not be taken into consideration by Canada. The Bidder should direct Canada to the appropriate location in the bid documentation.

Technical Evaluation Criteria (Rated)			
Number	Description	Points Allocation (Maximum Allocation = 180)	Score
Service Pistol			
RT 2.1.1	The pistol should be capable of firing 20,000 rounds without incurring class 1, class 2, and class 3 events.	Demonstrated: 100 points Not Demonstrated: 0 points	
RT 2.12.2	The training pistol should come with the submitted RDS attached to it either by being directly mounted to the training pistol or with the use of an adapter plate interface.	Demonstrated: 40 points Not Demonstrated: 0 points	
RT 2.12.3	The training pistol with the submitted weapon light and submitted RDS attached should be capable of firing RCMP marking cartridges	Demonstrated: 20 points Not Demonstrated: 0 points	
LED Weapon Light			
RT 4.9	When affixed to the pistol with a loaded magazine and after being dropped from 121.9 cm, the LED weapon light should remain affixed.	Demonstrated: 20 points Not Demonstrated: 0 points	

ANNEX E: PERFORMANCE EVALUATION

Introduction

The performance evaluation is to validate the Bidder's written responses to select mandatory and point-rated technical evaluation criteria found in Annex A. Unless otherwise specified, all evaluations will be conducted in English.

Performance Evaluation

Evaluators will follow the procedures documented within each performance evaluation in order to validate the specific mandatory and point-rated evaluation criteria as identified. Evaluators will record whether the Bidder has met the requirements listed for the mandatory or point-rated criteria identified for each performance evaluation.

Performance evaluations will be conducted at an RCMP or Government of Canada facility and may be scheduled concurrently. Should there be technical or logistical issues outside of the Bidder's control, the Bidder will not be penalized and the evaluation will continue once Canada has resolved the issue(s).

Evaluators

Performance evaluations will be conducted by RCMP employees and observed by the PSPC Contracting Authority and the Fairness Monitor. Personnel in training at depot and emergency response team personnel will not be part of the performance evaluation. Different evaluators may be scheduled for each individual performance evaluation however the same RCMP evaluators will conduct the evaluation for all Bidders. If an evaluator is unable to complete the evaluation once a specific performance evaluation has begun, a replacement evaluator will be found and the specific performance evaluation will be re-started for that criteria.

Performance Evaluation Outcome

Performance will be validated against the Bidder's responses to the mandatory and rated criteria as identified.

Failure to achieve a mandatory criterion being evaluated for a Performance Evaluation will render the Bidder non-compliant. If there is a critical failure in the Bidder's pistol at any time during the Performance Evaluation, the Bidder will fail, their bid will not be given further consideration and the bidder will be deemed non-compliant.

If the Bidder does not meet a mandatory requirement, the Bidder will fail the performance evaluation and their bid will not be given further consideration.

If the Bidder does not meet a rated score as high for a rated criteria as described in the Bidder's written bid, the scoring for that portion of their bid will be re-assessed downward. Bidder's scores will not be increased as a result of the performance evaluation.

Bidders that pass all mandatory evaluation criteria in the Performance Evaluation will proceed to the Usability Evaluation in Annex D

Bidder Set-up Responsibilities

Each bidder must provide Canada with the following new items that are the same models proposed as part of the bid response and must be delivered to Canada no later than sixty (60) days after bid submission to support both the Performance Evaluation (Annex C) and the Usability Evaluation (Annex D). These items will be used as follows:

Item	Quantity	Item	Quantity
Pistol (Pre-Sighted and zeroed) (9 right handed and 1 left handed)	10	RDS	10
LED Weapon Light	10	General Duty Holster (6 right handed and 2 left handed)	8
Magazines	30	Plain Clothes Holster (1 right handed and 1 left Handed)	2
Training Pistol (Pre-Sighted and zeroed)	1	Magazines (Training)	3
Grip Sizing Components	Quantity based on bid submission. Minimum of 3 per pistol.	Carrying Case	10
Tools and Test Equipment	As per manufacturer's recommended service requirements	Maintenance Kits	As per manufacturer's service requirements

The Bidder must supply user manual(s) for all provided products that provide sufficient detail for evaluators to use as a reference to carry out the performance evaluation. The Bidder must also supply user manual(s) or instructions to provide Canada with any additional information they may require to complete the set-up of the performance evaluation. Bidders may include pre-recorded training videos or pre-recorded demonstrations in addition to the technical documentation and instructions. PSPC and the fairness monitor will be in attendance throughout. Bidders will not be permitted to witness the evaluations.

Canada Set-up Responsibilities

Canada will carry out the evaluations at one or more RCMP or Government of Canada facilities. Evaluation facilities will be equipped to support live fire shooting, requisite temperature control equipment as well as precision measuring devices. Prior to the conduct

of the performance evaluation, Canada will clean, lubricate (using RCMP approved lubricant), and assemble pistols with the RDS and LED weapon light as per each manufacturer's specifications. Canada will inspect, gauge and confirm the zero to verify that pistols are safe to fire prior to live fire evaluations. For live fire components of the performance evaluation, Canada will service the pistol and ancillary equipment as per the manufacturer's recommended parts replacement and cleaning protocols. For any weapon that is deemed unsafe to fire, the reasons will be recorded and the bid will be deemed noncompliant and given no further consideration.

The Bidders must be in full compliance of all technical evaluation criteria (mandatory) that are validated during the performance evaluation and will not progress to the Usability Evaluation (Annex F) if deemed non-compliant.

Performance Evaluation Criteria (Mandatory)

Number	Description	Evaluation Method(s)
Service Pistol		
MT 2.1.3	The pistol must have a maximum length of 191 mm (7.52 inches) when measured from the barrel muzzle to the rear of the beavertail.	The evaluator will measure the pistol using a precision measuring instrument. The measurement will be taken from the furthest forward point of the pistol (muzzle end), to the furthest rearward point of the pistol (the beavertail portion of the grip).
MT 2.1.4	The pistol must have a maximum overall height of 148 mm (5.83 inches) measured from the top of the slide to the bottom of the pistol grip with the magazine and RDS removed.	The evaluator will measure the pistol using a precision measuring instrument. The measurement will be taken from the top of the slide (not including the sights and RDS) to the bottom of the pistol grip with the magazine and RDS removed.
MT 2.1.5	The pistol must have a maximum overall width of 36.1 mm (1.42 inches) measured from slide catch lever to slide catch lever.	The evaluator will measure the pistol using a precision measuring instrument. The measurement will be taken from slide catch lever to slide catch lever.
MT 2.1.6	The pistol barrel must have a minimum length of 99 mm (3.89 inches) and a maximum length of 108 mm (4.25 inches).	The evaluator will measure the pistol's barrel length using a precision measuring instrument. The measurement will be taken from the foremost (muzzle end) and rearmost portion (back of the chamber) of the barrel not including the feeding ramp.
MT 2.1.7	The pistol must not weigh more than a maximum of 822.14 grams (29 oz) when the magazine is empty, and no accessories are attached.	The evaluator will place the pistol with an empty magazine and no accessories attached on a calibrated scale to ensure it weighs no more than 822.14 grams (29 oz)
MT 2.2.2	The pistol must be capable of shooting a 15.25 cm (6 inch) grouping from 25 m (27.34 yards) away.	This requirement will be evaluated as follow: <ol style="list-style-type: none"> 1. The evaluator will shoot the pistol for accuracy in a standing position from 25 m (27.34 yards) away shooting Winchester SXT 147 gr. duty ammunition supported on a sandbag; 2. The evaluator will shoot five (5) groups of five (5) rounds; and

		3. The evaluator will calculate the average of the five (5) groupings to confirm compliance.
MT 2.4.3	The parts of the pistol that are normally handled by a user (grip, slide, trigger, and trigger guard) must not have any sharp edges.	The evaluator will visually and physically inspect the pistol frame and/ or grip module to ensure it is manufactured of polymer.
MT 2.4.4	The pistol's frame (grip module) must be manufactured of polymer.	The evaluator will visually and physically inspect the pistol frame and/ or grip module to ensure it is manufactured of polymer.
MT 2.5.3	The pistol's grip must not have finger grooves.	The evaluator will visually and physically inspect the front portion of the grip.
MT 2.5.4	The pistol's grip frame housing and back strap must be textured.	The evaluator will visually and physically inspect the surface of the pistol grip frame housing and back strap for texture.
MT 2.5.5	The underside of the trigger guard and the underside of the beavertail must not be textured.	The evaluator will visually and physically inspect the trigger guard and the underside of the beavertail are not textured.
MT 2.5.6	The pistol's front and rear sides (left and right) of the slide must have non-slip grasping grooves.	The evaluator will visually and physically inspect the pistol for non-slip grasping grooves on the slide.
MT 2.5.7	The pistol must have (an) ambidextrous slide catch lever(s) that enables a user to activate it using either hand.	<p>This requirement will be evaluated as follows:</p> <ol style="list-style-type: none"> 1. The evaluator will manually cycle the slide to the rear and engage the slide stop with their right thumb; 2. The evaluator will insert a loaded magazine; 3. The evaluator will depress the slide catch lever with their right thumb to release the slide; and 4. This test will be repeated with the evaluator's left thumb. <p>A minimum of three (3) of the four (4) sides/edges at the entrance of the magazine well must be beveled or flared and be integrated into the pistol's frame (grip module) in order to aid in the insertion of a magazine.</p>
MT 2.6.1	The pistol's magazine release must be configurable for either a right- or left- handed user.	The evaluator will visually and physically inspect the pistol's magazine release for either right-hand or left-hand only configurations.
MT 2.6.2	The pistol must have a push button that will release the magazine when a user presses it by making a lateral movement (from side to side) with their thumb.	<p>The requirement will be evaluated as follows:</p> <ol style="list-style-type: none"> 1. The evaluator while holding a pistol in a shooting position will push the magazine release by making a lateral movement with their thumb; and 2. The evaluator will visually and physically inspect the pistol's magazine catch.
MT 2.7.1	The pistol's trigger pull weight must be a minimum of 2.27kg (5.0 lbs) up to a maximum of 3.18kg (7.0 lbs).	<p>The requirement will be measured as follows:</p> <ol style="list-style-type: none"> 1. The evaluator will choose one (1) pistol at random to perform the trigger weight evaluation. 2. The evaluator will use NRA Official Universal Weights to conduct this test; using a hook

	<p>system to attach the weights to the trigger;</p> <p>3. The pistol will be orientated vertically with the barrel facing upwards;</p> <p>4. The evaluator will load a weight jig with a 2.15 kg (4.75 lbs) static weight placed on it;</p> <p>5. The evaluator will lift the pistol vertically with the jig contacting the trigger. The pistol must not fire or it will be deemed non compliant;</p> <p>6. The evaluator will continue to repeat the test by adding 0.11 kg (0.25 lbs) of static weights to the weight jig until the trigger weight is determined by the pistol firing; and</p> <p>7. The evaluator will verify that the assessed trigger weight falls within the 2.27kg (5.0 lbs) to 3.18kg (7.0 lbs) range.</p> <p>8. The evaluator will perform a total of five (5) trigger pulls on the chosen pistol.</p> <p>9. The evaluator will calculate the average of the five (5) trigger pulls to determine the average trigger pull weight of the pistol.</p>	
MT 2.7.3	<p>The pistol's striker fired mechanism must have a minimum firing pin indent of 0.28 mm (0.011 inch)</p>	<p>This requirement will be evaluated as follow:</p> <ol style="list-style-type: none"> 1. The evaluator will insert a copper crusher into an adapter cartridge which will be inserted into the chamber of the pistol; 2. An adjustment screw will ensure that the crusher is against the breech face when the pistol is in battery; 3. The trigger will be pulled, then the adapter cartridge ejected from the pistol; 4. The copper crusher will be removed from the adapter cartridge and the firing pin indent will be measured on a dial indicator to ensure a minimum firing pin indent of 0.28 mm (0.011 inch); and 5. This test will be conducted three (3) times ensuring minimum indent each time.
MT 2.8.2	<p>The pistol's magazine must have a minimum capacity of seventeen (17) rounds.</p>	<p>The evaluator will load each magazine with seventeen (17) rounds of Winchester 9mm SXT duty ammunition to ensure a minimum capacity of seventeen (17) rounds.</p>
MT 2.8.4	<p>The pistol's magazine must have witness holes starting at maximum cartridge number four (4) that either align with each cartridge or align with cartridges 6, 8, 10, 12, 14 and 17.</p>	<p>The evaluator will load the magazine one cartridge at a time to maximum capacity. From the fourth cartridge onwards each witness hole will be visually inspected to ensure a cartridge aligns with the witness hole.</p>
MT 2.8.5	<p>The pistol's magazine must have a baseplate that protrudes a minimum of 2.54 mm (0.10 inch) up to a maximum of 8.35 mm (0.329 inch) from the front of the pistol's grip.</p>	<p>This requirement will be evaluated as follows:</p> <ol style="list-style-type: none"> 1. The evaluator will insert a magazine into the pistol; 2. Each pistol will be measured with a precision measuring instrument; and 3. The distance which the magazine butt-plate extends past the front of the pistol grip will be measured to ensure a minimum protrusion of 2.54 mm (0.10 inch) up to a maximum of 6.35 mm (0.25 inch).
MT 2.8.6	<p>When the pistol's magazine release button is pressed, the pistol's magazine must drop free from the pistol with the following criteria:</p> <p>a) without user intervention;</p> <p>b) when the magazine is loaded and when it is empty; and</p> <p>c) when the slide is in either a forward or rear-locked position.</p>	<p>This requirement will be evaluated as follows:</p> <ol style="list-style-type: none"> 1. Pistol with one full magazine: <ul style="list-style-type: none"> a. The evaluator will insert one (1) loaded magazine; b. The evaluator will chamber one (1) round and fire one (1) round; and c. The magazine release will be depressed with the pistol floor plate oriented towards the ground. 2. Pistol with slide locked to the rear: <ul style="list-style-type: none"> a. The evaluator will insert one (1) loaded magazine; and b. The magazine release will be depressed with the pistol floor plate oriented

		<p>3. Pistol with the slide forward:</p> <ol style="list-style-type: none"> The evaluator will insert one (1) empty magazine; and The magazine release will be depressed with the pistol floor plate oriented towards the ground. <p>4. Pistol with slide locked to the rear:</p> <ol style="list-style-type: none"> The evaluator will insert one (1) empty magazine; and The magazine release will be depressed with the pistol floor plate oriented towards the ground.
MT 2.10.1	The pistol must have no external manual safety levers, grip safeties, and push-button safeties.	<p>The pistol will be visually inspected to ensure there are no external manual safety levers, grip safeties, and push-button safeties.</p>
MT 2.10.2	The pistol must enable a user to discharge a cartridge with the pistol's magazine removed.	<p>This requirement will be evaluated as follow:</p> <ol style="list-style-type: none"> The evaluator will insert a loaded magazine into the pistol; The evaluator will chamber the pistol with one (1) round; The evaluator will remove the magazine from the pistol; and The evaluator will pull the trigger.
MT 2.10.3	The pistol must have an internal firing pin safety.	<p>This requirement will be evaluated as follows:</p> <ol style="list-style-type: none"> Evaluation Method 1: <ol style="list-style-type: none"> The evaluator will remove the slide, the barrel, and recoil guide assembly from the pistol; Using a tool, the evaluator will push the firing pin forward to inspect if it protrudes from the breech face; and The evaluator will depress the firing pin safety, push the firing pin forward, and inspect if it protrudes from the breech face. Evaluation Method 2: <ol style="list-style-type: none"> The evaluator will insert a fully loaded magazine into the pistol; The evaluator will cycle the action to load a round into the chamber; The evaluator will extract and eject the casing to inspect the surface of each primer for any signs of contact with the firing pin; and The evaluator will repeat this test five (5) times.
MT 2.10.4	The pistol must have a mechanical safety to prevent a user from firing the pistol when not in battery (slide not fully forward and unlocked).	<p>This requirement will be evaluated as follows:</p> <ol style="list-style-type: none"> The evaluator will chamber a primed cartridge into the pistol; The evaluator will move the pistol's slide rearward 6.35 mm (0.25 inch); and The evaluator will pull the trigger and assess if the pistol fires.
MT 2.10.5	The pistol must have either a visual or tactile indicator that alerts a user that the pistol's chamber is loaded.	<p>This requirement will be evaluated as follows:</p> <ol style="list-style-type: none"> The evaluator will chamber one (1) Winchester 9mm SXT duty ammunition into the pistol; and The evaluator will inspect the pistol for a visual and/or tactile loaded chamber indicator.
MT 2.11.1	The pistol's front sight must be black and must have a yellow or orange coloured glow-in-the-dark photoluminescent outline	<p>The evaluator will visually inspect the pistol's front sight.</p>

	surrounding a green tritium phosphor-filled glass lamp in the center (round dot). The photo luminescent outline must be visible at all times ie. during daylight and in the dark.	This requirement will be evaluated as follows: 1. Iron Sights: a. The evaluator using the pistol shooting Winchester SXT 147 gr. duty ammunition supported on a sandbag will shoot one (1) group of five (5) rounds using the iron sights at 25 m (27.3 yds) b. An average of the grouping for the pistol with iron sight will be taken to assess whether the pistol meets the requirement. 2. Red Dot Sight: a. The evaluator using the pistol shooting Winchester SXT 147 gr. duty ammunition supported on a sandbag will shoot one (1) group of five (5) rounds using the RDS at 25 m (27.3 yds) b. An average of the grouping for the pistol with RDS will be taken to assess whether the pistol meets the requirement.
MT 2.11.2	The pistol with iron sights and the pistol with RDS must shoot to point of aim within a 5.08 cm (2 inches) radius at 25 m (27.34 yards).	
MT 2.11.3	The pistol's front sights must have a square front post with a width measuring between 3.05 mm (0.120 inch) and 3.68 mm (0.145 inch).	The evaluator will visually inspect and physically measure the front sight on each pistol using a precision measuring instrument.
MT 2.11.4	The pistol's rear sight must have each of the following: a) A square or u-shaped notch; b) A surface that will reduce glare to assist a user with front sight focus and; c) A notch width between 4.57 mm (0.180 inch) and 5.46 mm (0.215 inch).	The evaluator will visually inspect and physically measure the rear sight on each pistol using a precision measuring instrument.
MT 2.11.5	The pistol's front sight tritium glass lamp must be protected with a mechanism that will prevent the removal of the coloured portion of the front sight when using cleaning or chemical products on the pistol.	The evaluator will visually and physically inspect the pistol's front sight tritium glass lamp.
MT 2.11.6	The pistol's rear sight must be black.	The evaluator will visually inspect the pistol's rear sight.
MT 2.11.7	The pistol's rear sight tritium vials must be green surrounded with a black outline. The small metal tube ring that secures the tritium dot can be of a metallic color.	The evaluator will visually inspect the pistol's rear sight tritium vials.
MT 2.11.8	The pistol's front and rear sights must be replaceable.	The evaluator will visually inspect the pistol's front and rear sights.

MT 2.11.10	The pistol's rear iron sight dovetail must be milled to the pistol's slide.	The evaluator will visually inspect the pistol's rear iron sight dovetail.
MT 2.12.1	The training pistol must be blue, inclusive of the magazine baseplate.	The evaluator will visually inspect the training pistol.
MT 2.12.2	The training pistol must come with the submitted weapon light attached to it in the same manner as the submitted service pistol.	The evaluator will visually and physically inspect the training pistol with attached weapon light.
MT 2.12.3	<p>The training pistol with the submitted weapon light attached must be capable of firing RCMP marking cartridges.</p> <p>Canada's requirement is for the training pistol to be a replica of the offered duty pistol and to work with the duty holster that will come with the duty pistol.</p> <p>Canada requires the training pistol to use the same holster as the duty pistol.</p>	<p>This requirement will be evaluated as follows:</p> <ol style="list-style-type: none"> 1. The evaluator will assemble the training pistol, weapon light, and general duty holster as per manufacturer's specifications; 2. The evaluator will visually and physically inspect the assembled training pistol; 3. The evaluator will load the training pistol with three (3) magazines loaded to maximum capacity with RCMP marking cartridges; 4. The evaluator will fire the training pistol until all the rounds are fired. 5. The evaluator will record any weapon-related stoppages during the test (note: any stoppages determined to be ammunition-related defects will not be counted). 6. The evaluator will disassemble and visually and physically inspect the training pistol, weapon light, 3 magazines, and general duty holster.
Red Dot Sight (RDS)		
MT 3.1	The red dot sight (RDS) must be configured to direct mount to the pistol slide.	The evaluator will visually and physically inspect the red dot sight (RDS) mounted to the pistol slide.
MT 3.3	The RDS must enable a user to view the pistol's iron sights through the RDS at a lower 1/3 co-witness.	The evaluator will visually inspect the pistol with RDS mounted to ensure that it has the lower 1/3 co-witness of the iron sights through the RDS.
MT 3.7	Including the battery, the RDS must weigh no more than 62 g (2.19 oz.).	<p>This requirement will be evaluated as follows:</p> <ol style="list-style-type: none"> 1. The RDS (battery included) will be placed on a calibrated weighing scale without the mounting hardware; and 2. The weight will be recorded to ensure it weighs no more than 62 g (2.19 oz.)
MT 3.12	The RDS exterior dimensions must be less than or equal to 55.9 mm (2.2 inch) long x 34.3 mm (1.35 inch) wide x 34.3 mm (1.35 inch) in height.	The evaluator will physically measure the RDS using a precision measuring instrument to ensure exterior dimensions are less than or equal to 55.9 mm (2.2 inch) long x 34.3 mm (1.35 inch) wide x 34.3 mm (1.35 inch) in height.
MT 3.21	The user must be able to change the RDS battery without having to remove the RDS from the pistol slide.	The evaluator will perform a battery exchange on the installed RDS.
LED Weapon Light		
MT 4.2.1	The weapon light must have a maximum height of 32.2 mm (1.27 inches).	The evaluator will physically measure the weapon light using a precision measuring instrument.

MT 4.2.2	The weapon light must have a maximum width of 29.8 mm (1.18 inches).	The evaluator will physically measure the weapon light using a precision measuring instrument.
MT 4.2.3	The weapon light must have a maximum length of 65.5 mm (2.58 inches).	The evaluator will physically measure the weapon light using a precision measuring instrument.
MT 4.2.4	Including the battery, the weapon light must have a maximum weight of 68.1 g (2.4 oz.)	This requirement will be evaluated as follows: <ol style="list-style-type: none"> 1. The weapon light (battery included and installed) will be placed on a calibrated weighing scale; and 2. The weight will be recorded to ensure it is under the maximum weight of 68.1 g (2.4 oz.)
MT 4.3	The weapon light must not protrude beyond the muzzle of the pistol.	This requirement will be evaluated as follows: <ol style="list-style-type: none"> 1. The light will be attached to the pistol; and 2. A straight edge will be placed across the muzzle end of the pistol to ensure the weapon light does not protrude.
MT 4.5	The weapon light's operating and switching controls must include each of the following settings: <ol style="list-style-type: none"> a) momentary on; and b) constant on. 	This requirement will be evaluated as follows: <ol style="list-style-type: none"> 1. The weapon light will be tested for momentary on operation; and 2. The weapon light will be tested for a constant on function.
MT 4.6	The weapon light must have ambidextrous high and low switch configurations.	The evaluator will visually inspect the weapon light for an ambidextrous high and low switch configurations.
MT 4.7	The weapon light must include a lockout feature that will prevent the LED weapon light from being accidentally activated.	This requirement will be evaluated as follows: <ol style="list-style-type: none"> 1. The evaluator will activate the weapon light's lockout feature in accordance with manufacturer instructions and the momentary on and constant on functions will be activated; and 2. The evaluator will determine whether the light is capable of being activated while lockout is engaged.
MT 4.13	The weapon light must use a lithium 3 Volt CR123A battery.	The evaluator will visually inspect the weapon light for use of a lithium 3 Volt CR123A battery.
MT 4.16	The user must be able to replace the LED weapon light battery without having to remove the LED weapon light from the pistol.	The evaluator will perform a battery exchange on the installed weapon light.
Carrying Case		
MT 5.1	The carrying case must have maximum external dimensions of 38.1 cm (15 inches) in width, 30.5 cm (12 inches) in height, and 15.24 cm (6 inches) in depth to hold the configured pistol with RDS and LED weapon light installed, three magazines, and pistol accessories (such as grip components).	The evaluator will physically measure the external dimensions (height, width, and depth) of the carrying case using a precision measuring instrument.
MT 5.2	The carrying case must be equipped with a minimum of two (2) latching devices.	The evaluator will visually and physically inspect the carrying case latching devices.

<p>The carrying case must include two (2) separated securing eyelets with a minimum diameter of 7 mm (0.276 inch) and a maximum diameter of 9 mm (0.354 inch) that when locked with two (2) RCMP approved locks will secure the case from being pried open by hand.</p>	<p>The carrying case must include a foam insert that does not absorb water and is cut to secure and segregate the configured pistol components and three magazines by a minimum of 1.91 cm (0.75 inch) on all sides.</p> <p>The ASTM D3575 (L: Water Absorption) test standard is acceptable and will meet the RCMP requirement</p>	<p>This requirement will be evaluated as follows:</p> <ol style="list-style-type: none"> 1. The evaluator will physically measure each carrying case securing eyelets width with a precision measuring instrument; and 2. An unloaded configured pistol with RDS and weapon light, and three magazines will be placed into each carrying case. Each carrying case will then be secured with 2 RCMP approved locks and the evaluator, by hand, will attempt to pry open the carrying case and remove any of the contents.
<p>MT 5.3</p>	<p>MT 5.4</p>	<p>This requirement will be evaluated as follows:</p> <ol style="list-style-type: none"> 1. The evaluator will place the configured pistol with RDS and weapon light installed, grip components, and three magazines into the carrying case and measure all foam separation between contents and walls with a precision measuring instrument; 2. The evaluator will close and secure the lid on the carrying case and contents, pick up the carrying case and orient it: <ul style="list-style-type: none"> a. lid side up; b. lid side down; c. right side up; d. right side down; e. handle side up; and f. handle side down; 3. The evaluator will listen for any signs that the contents are not secure within the case (i.e., clunking sound); 4. The evaluator will place the case lid side up on a flat and level surface; and 5. The evaluator will open the case and inspect the contents for any dislodging from the foam. <p>The evaluator will visually and physically inspect the carrying case handle.</p>
<p>MT 5.5</p>	<p>MT 5.6</p>	<p>The carrying case must have a carrying handle.</p> <p>The carrying case must have a hinged lid that will hold open when empty or lay flat when opened.</p> <p>The carrying case must be stackable.</p> <p>The carrying case must be opaque so that the contents within the case are not visible when the case is closed.</p> <p>The carrying case must not be embossed with any name, logo*, nor any markings which could indicate the content as a firearm.</p>
<p>MT 5.8</p>	<p>MT 5.9</p>	<p>This requirement will be evaluated as follows:</p> <ol style="list-style-type: none"> 1. The evaluator will place the pistol with RDS and weapon light and three magazines into the carrying case, close and secure the carrying case as per manufacturer's instructions; and 2. The evaluator will visually inspect the carrying case on all 6 sides. <p>The evaluator will visually and physically inspect the carrying case.</p>
		<p>*Canada will accept the logo of the carrying case manufacturer on the carrying case but no markings that would indicate the contents</p>

	of the carrying case being a firearm in any way	
MT 5.10	The carrying case must be coloured black or in grey tones.	The evaluator will visually and physically inspect the carrying case.
Pistol Holster - General Duty		
MT 6.1	The holster must be available in a left- and right-handed configuration.	The evaluator will visually and physically inspect the holster.
MT 6.2	The holster must be able to secure the configured pistol with RDS and LED weapon light.	The evaluator will perform a physical evaluation in accordance with RCMP-UEP SP2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).
MT 6.3	The holster must have a minimum retention level rating of RCMP-UEP SP 2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).	The evaluator will perform a physical evaluation in accordance with RCMP-UEP SP2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).
MT 6.6	The holster's automatic locking system must offer retention in all directions for both left and right-handed holsters.	The evaluator will perform a physical evaluation in accordance with RCMP-UEP SP2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).
MT 6.7	The holster must enable the user to have full access to the grip of the pistol before drawing the pistol out.	This requirement will be evaluated as follows: <ol style="list-style-type: none"> 1. The evaluator will holster the configured pistol; and 2. The evaluator will visually and physically inspect the grip of the holstered pistol.
MT 6.13	The holster must shroud the RDS and rear sight from view when in a locked and holstered position.	This requirement will be evaluated as follows: <ol style="list-style-type: none"> 1. The evaluator will holster the configured pistol; and 2. The evaluator will visually inspect the RDS and rear sight of the holstered pistol.
MT 6.14	The holster's locking mechanism must feature a shroud to prevent an inadvertent release of the locking mechanism.	The evaluator will visually inspect and physically evaluate the holster's locking mechanism in accordance with RCMP-UEP SP2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).
MT 6.15	The holster must mount to an in-service duty belt that ranges from 5.0 cm (1.97 inch) to 5.7 cm (2.24 inches) in width and 3 mm (0.12 inch) to 5 mm (0.2 inch) thickness limiting unnecessary movement.	The evaluator will visually and physically inspect the holster for compatibility with in-service duty belt.
MT 6.16	It is acceptable if the holster is capable of being mounted to a MOLLE duty belt with a different back plate. The back plate must be included in each Pistol Package	The evaluator will perform a physical evaluation of the holster in accordance with RCMP-UEP SP2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).

	(Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).	
MT 6.17	The pistol must remain in the holster when force is applied in accordance with RCMP-UEP SP 2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).	The evaluator will perform a physical evaluation of the holster in accordance with RCMP-UEP SP2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).
MT 6.20	The bottom of the holster must have (a) drain hole(s) or be open.	The evaluator will visually and physically inspect the bottom of the holster.
Pistol Holster - Plain Clothes		
MT 7.1	The holster must be available in a left- and right-handed configuration.	The evaluator will visually and physically inspect the holster.
MT 7.2	The holster must be able to secure the configured pistol with RDS and LED weapon light installed.	The evaluator will perform a physical evaluation in accordance with RCMP-UEP SP2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).
MT 7.3	The pistol must remain in the holster and the holster must not sustain any damage when evaluated in accordance with RCMP-UEP SP 2-2022 Standard Practice for Evaluation of Pistol Holster Retention Mechanism(s).	The evaluator will perform a physical evaluation in accordance with RCMP-UEP SP2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).
MT 7.4	The holster must have one (1) mechanical automatic locking device to keep the pistol in the holster.	The evaluator will perform a physical evaluation in accordance with RCMP-UEP SP2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).
MT 7.5	The holster's automatic locking device must offer retention in all directions for both left and right-handed holsters.	The evaluator will perform a physical evaluation in accordance with RCMP-UEP SP2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).
MT 7.6	The holster must enable the user to have full access to the grip of the pistol before drawing the pistol out.	This requirement will be evaluated as follows: The evaluator will holster the configured pistol; and The evaluator will visually and physically inspect the grip of the holstered pistol.
MT 7.12	The holster must prevent unnecessary movement in accordance with RCMP-UEP SP 3-2022 (Standard Practice for Evaluation of Pistol Holster Belt Slide Attachments).	The evaluator will perform a physical evaluation of the holster in accordance with RCMP-UEP SP 3-2022 (Standard Practice for Evaluation of Pistol Holster Belt Slide Attachments)
MT 7.13	The holster must mount to a belt that ranges from 3.66 cm (1.44 inches) to 5.7 cm (2.24 inches) in width and 3 mm (0.12 inch) to 5 mm (0.2 inch) thickness, limiting unnecessary movement.	The evaluator will visually and physically inspect the holster for compatibility with in-service duty belt.

<p>MT 7.14</p> <p>The holster must remain attached to the wearers belt (G.S. 1045-122 Belt, Waist, Leather, Black dated 2018-08-29) when force is applied in accordance with RCMP-UEP SP2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).</p>	<p>The evaluator will perform a physical evaluation of the holster in accordance with RCMP-UEP SP2-2022 (Standard Practice for Evaluation of Pistol Holster Retention Mechanisms).</p>
<p>MT 7.17</p> <p>The bottom of the holster must have (a) drain hole(s) or be open.</p>	<p>The evaluator will visually and physically inspect the bottom of the holster.</p>

Performance Evaluation Criteria (Rated)		
Number	Description	Evaluation Method(s)
RT 2.12.2	The training pistol should come with the submitted RDS attached to it either by being directly mounted to the training pistol or with the use of an adapter plate interface.	<p>This requirement will be evaluated as follows:</p> <ol style="list-style-type: none"> 1. The evaluator will assemble the training pistol, RDS, weapon light, and general duty holster as per manufacturer's specifications; 2. The evaluator will visually and physically inspect the assembled training pistol; 3. The evaluator will load the training pistol with three (3) magazines loaded to maximum capacity with RCMP marking cartridges; 4. The evaluator will fire the training pistol until all the rounds are fired; 5. The evaluator will record any weapon-related stoppages during the test (note: any stoppages determined to be ammunition-related defects will not be counted); and 6. The evaluator will disassemble and visually and physically inspect the training pistol, RDS, weapon light, 3 magazines, and general duty holster.
RT 2.12.3	The training pistol with the submitted weapon light and submitted RDS attached must be capable of firing RCMP marking cartridges.	
RT 4.9	When affixed to the pistol with a loaded magazine and after being dropped from 1.3 meters (4.27 feet), the LED weapon light should remain affixed.	<p>The pistol will then be dropped from a height of 121.9 cm (48 inches) onto a concrete floor in the sequence of six (6) defined orientations. The evaluator will visually inspect the weapon light to ensure it remains affixed to the pistol.</p>

Performance Evaluation: Environmental Condition Testing

This requirement will be evaluated as follows:

1. For cold temperature test, each pistol, RDS, weapon light, and a loaded magazine will be:
 - a. cleaned, lubricated (using RCMP approved lubricant), and assembled as per manufacturer's specifications with vendor supplied batteries;
 - b. the loaded magazine will be inserted into the pistol, the RDS will be activated, and a round will be chambered;
 - c. the loaded configured pistol (mounted RDS and weapon light) will be placed in the general duty holster and exposed to a temperature of -40°C for 4 hours;
 - d. after exposure of 4 hours at -40°C condition, the loaded pistol will be removed from the freezer and the holster;
 - e. within five (5) minutes, the light will be activated, and the pistol will be fired five (5) times at 25m;
 - f. [MT 3.5] the point of impact (groupings) of the test will be compared to the grouping in MT 2.11.2;
 - g. the remaining rounds in the magazine will be fired; and
 - h. [MT 3.14] The RDS dot intensity switch will be adjusted to verify functionality.
2. For hot temperature test, each pistol, RDS, weapon light and a loaded magazine will be:
 - a. cleaned, lubricated (using RCMP approved lubricant), and assembled as per manufacturer's specifications;
 - b. the loaded magazine will be inserted into the pistol, the RDS will be activated, and a round will be chambered;
 - c. the loaded configured pistol (mounted RDS and weapon light) will be placed in the general duty holster and exposed to a temperature of 48°C for 4 hours;
 - d. after exposure of 4 hours at 48°C condition, the loaded pistol will be removed from the oven and the holster;
 - e. within five (5) minutes, the light will be activated, and the pistol will be fired ~~five~~ (5) times at 25m;
 - f. [MT 3.5] the point of impact (groupings) of the test will be compared to the grouping in MT 2.11.2;
 - g. the remaining rounds in the magazine will be fired; and
 - h. [MT 3.14] the RDS dot intensity switch will be adjusted to verify functionality.

Mandatories Evaluated

Number	Description	Method of Evaluation
MT 1.1	The pistol, red dot sight (RDS), weapon light, and general duty holster must operate as a system within a minimum temperature range of -40°C to +48°C.	The loaded configured pistol (mounted RDS and weapon light) will be placed in the general duty holster and exposed to a temperature of -40°C for 4 hours and 48°C for 4 hours during the first and second phase of the test. The pistol will then be visually and physically inspected.
MT 2.11.2	The pistol with iron sights and the pistol with RDS must shoot to point of aim within a 5.08 cm (2 inches) radius at 25 m (27.34 yards).	The loaded configured pistol (mounted RDS and weapon light) will be placed in the general duty holster and exposed to a temperature of -40°C for 4 hours and 48°C for 4 hours during the first and second phase of the test. The pistol will

<p>MT 3.5</p> <p>The RDS must function and maintain 0 within a temperature range of -40°C to +48°C for a minimum of 4 hours.</p>	<p>then be fired immediately five (5) times at 25m ensuring a point of aim within a 5.08 cm (2 inches) radius.</p>
<p>MT 3.14</p> <p>The RDS dot intensity switch must be flush mounted and use a pliable or soft material that must function under operational temperature requirements as specified in MT 1.1.</p>	<p>The loaded configured pistol (mounted RDS and weapon light) will be placed in the general duty holster and exposed to a temperature of -40°C for 4 hours and 48°C for 4 hours during the first and second phase of the test. The RDS dot intensity switch will then be adjusted to ensure functionality.</p>

Performance Evaluation: Endurance Testing

This requirement will be evaluated as follows:

1. The evaluator will clean, lubricate (using RCMP approved lubricant), and assemble three (3) pistols as per manufacturer's specifications;
2. **Safety Inspection:** The evaluator will inspect and gauge to verify that the pistols are safe to fire. For any weapon that is deemed unsafe to fire, the reasons will be recorded and the bid will be deemed noncompliant and given no further consideration;
3. [MT2.2.2] The evaluator will shoot the pistol for accuracy in a standing position from 25 m (27.34 yards) away shooting Winchester SXT 147 gr. duty ammunition supported on a sandbag. The evaluator will shoot one (1) group of five (5) rounds. The average of the grouping will be taken to ensure compliance with a six (6) inch grouping.
4. The evaluator will fire a 20,000 round endurance trial in a standing position using a combination of Winchester SXT 147 gr. duty (50% - 10 000 rounds) and RCMP approved training ammunition (50% - 10 000 rounds) in an RCMP approved firing range. The evaluator will clean and/or check the pistol as follows:

- a. [MT2.1.2] Every five hundred (500) rounds, the evaluator will:
 - i. Clean and lubricate (using RCMP approved lubricant) as per manufacturer's specifications; and
 - ii. Visually and physically inspect the pistol;
 - b. [MT2.2.2] Every five thousand (5000) rounds, the evaluator will shoot the pistol for accuracy in a standing position from 25 m (27.34 yards) away shooting Winchester SXT 147 gr. duty ammunition supported on a sandbag. The evaluator will shoot one (1) group of five (5) rounds. The average of the grouping will be taken to ensure compliance with a six (6) inch grouping;
 - c. [MT2.1.2] During the trial, parts will be changed as per manufacturer recommendations. The evaluator will not replace any parts (even if stated by manufacturer recommendations) before 5 000 rounds.
 - d. During the trial, the barrel, frame and slide will not be changed; and
 - e. [MT2.6.3] During the trial, the pistol magazine's release mechanism will be visually and physically inspected.
5. [RT2.1.1] The evaluator will record any weapon-related stoppages during the endurance trial (note: any stoppages determined to be ammunition-related defects and/or evaluator induced stoppages will not be counted). The stoppages will be weighted as follows:
- a. Class 1 Events will receive one (1) point
 - b. Class 2 Events will receive two (2) points
 - c. Class 3 Events will receive three (3) points
 - d. Note: Any pistol surpassing a score of 100 pts will be eliminated from contention.
6. The evaluator will record any part failure outside of the manufacturer's part replacement schedule during the endurance test.

Mandatories Evaluated

Number	Description	Method of Evaluation
MT 2.1.1	The pistol must be capable of firing 20,000 rounds without: <ol style="list-style-type: none"> a. Needing to change the barrel, frame and slide; b. Incurring a class 4 event; c. Incurring more than 100 pts based on class 1, 2, and 3 events; and 	The evaluator will fire a 20,000 round endurance trial in a standing position using a combination of Winchester SXT 147 gr. duty (50% - 10 000 rounds) and RCMP approved training ammunition (50% - 10 000 rounds) in an RCMP approved firing range. During the trial: <ol style="list-style-type: none"> 1. The barrel, frame and slide will not be changed. Every five hundred (500) rounds, the evaluator will clean, lubricate, visually inspect, and

	d. Needing to change any part due to failure outside the manufacturers part replacement schedule	<p>physically inspect the pistol;</p> <p>2. The evaluator will record any weapon-related stoppages during the endurance trial and categorize them by class (note: any stoppages determined to be ammunition-related defects will not be counted). Points will be tallied, ensuring compliance with the 136 pt threshold; and</p> <p>3. During the trial, parts will be changed as per manufacturer recommendations.</p>
MT 2.1.2	The pistol's parts, components, magazines, and magazine parts (excluding barrel, frame, and slide) must not require replacement for a minimum of 5000 rounds.	<p>The evaluator will fire a 20,000 round endurance trial in a standing position using a combination of Winchester SXT 147 gr. duty (50% - 10 000 rounds) and RCMP approved training ammunition (50% - 10 000 rounds) in an RCMP approved firing range. During the trial, the evaluator will not replace any parts (even if stated by manufacturer recommendations) before 5 000 rounds. Every five hundred (500) rounds, the evaluator will clean, lubricate, visually inspect, and physically inspect the pistol.</p>
MT 2.6.3	The pistol's magazine release must prevent the magazine from being released while firing or handling the pistol.	<p>The evaluator will fire a 20,000 round endurance trial in a standing position using a combination of Winchester SXT 147 gr. duty (50% - 10 000 rounds) and RCMP approved training ammunition (50% - 10 000 rounds) in an RCMP approved firing range. During the trial, the pistol magazine's release mechanism will be visually and physically inspected.</p>
Rated Evaluation		
Number	Description	Method of Evaluation
RT 2.1.1	The pistol should be capable of firing 20,000 rounds without incurring class 1, class 2, and class 3 events.	<p>The evaluator will fire a 20,000 round endurance trial in a standing position using a combination of Winchester SXT 147 gr. duty (50% - 10 000 rounds) and RCMP approved training ammunition (50% - 10 000 rounds) in an RCMP approved firing range. The evaluator will record any weapon-related stoppages during the endurance trial and categorize them by class (note: any stoppages determined to be ammunition-related defects will not be counted).</p>

Performance Evaluation: Drop Testing

This requirement will be evaluated as follows:

1. The evaluator will chamber the pistol with a primed cartridge case and insert a magazine loaded to one (1) less than maximum capacity;
2. The pistol will then be dropped six times from a height of 121.9 cm (48 inches) onto a concrete floor in the following sequence of orientations:
 - a. muzzle down;
 - b. muzzle up;
 - c. magazine down;
 - d. magazine up;
 - e. right side down; and
 - f. right side up.
3. [MT2.10.6] The evaluator will determine whether the gun discharges during the drop test;
4. Should the pistol fire when dropped, it will be deemed non-compliant;
5. Should the pistol not fire when dropped, the evaluator will fire the primed cartridge case. In the case that the primed cartridge case does not fire, the pistol will be deemed non-compliant;
6. [MT4.10] The evaluator will visually inspect the weapon light to ensure the LED weapon light glass does not break, become dislodged, or fall out;
7. Should the weapon light be compromised, the testing on the weapon light will be concluded;
8. [MT4.9] The evaluator will ensure the weapon light maintains function of:
 - a. momentary on,
 - b. and constant on.
9. In the event that the weapon light becomes detached from the firearm there will be no deduction provided that the light still maintains function of:
 - a. momentary on,
 - b. and constant on.
10. [MT3.23] The evaluator will visually and physically inspect the RDS to ensure:
 - a. The RDS continues to operate; and
 - b. Hardware retention remains secure;
11. [MT3.23] The evaluator will evaluate the point of impact change of the RDS as follows:
 - a. The evaluator will manually cycle the action.
 - b. The evaluator using the pistol shooting Winchester SXT 147 gr. duty ammunition supported on a sandbag will shoot a group of five (5) rounds using the RDS at 25 m (27.3 yards)
 - c. An average of the grouping for the pistol with RDS will be taken to assess whether the RDS' point of impact change is less than 5.08 cm (2 inches).

Mandatories Evaluated

Number	Description	Method of Evaluation
MT 2.10.6	The pistol must have a safety feature that prevents the pistol from firing and the firing pin from moving forward when dropped.	The pistol will then be dropped from a height of 121.9 cm (48 inches) onto a concrete floor in the sequence of six (6) defined orientations. The evaluator will determine whether the gun discharges during the drop test.

<p>MT 3.23</p> <p>When affixed to the pistol with a loaded magazine and after being dropped from 1.3 meters, the RDS must:</p> <ul style="list-style-type: none"> a) remain affixed to the pistol; b) maintain the ability to see the red dot, c) and maintain its 0. 	<p>The pistol will then be dropped from a height of 121.9 cm (48 inches) onto a concrete floor in the sequence of six (6) defined orientations. Following the last drop, the evaluator will visually and physically inspect the RDS to ensure:</p> <ol style="list-style-type: none"> 1. The RDS continues to operate; and 2. Hardware retention remains secure. <p>The pistol will then be dropped from a height of 121.9 cm (48 inches) onto a concrete floor in the sequence of six (6) defined orientations. The evaluator will ensure the weapon light maintains function of:</p> <ol style="list-style-type: none"> a. momentary on; and b. constant on. <p>In the event that the weapon light becomes detached from the firearm there will be no deduction provided that the light still maintains function of:</p> <ol style="list-style-type: none"> a. momentary on; and b. constant on. <p>The pistol will then be dropped from a height of 121.9 cm (48 inches) onto a concrete floor in the sequence of six (6) defined orientations. The evaluator will visually inspect the weapon light to ensure the LED weapon light glass does not break, become dislodged, or fall out.</p>
<p>MT 4.9</p> <p>When affixed to the pistol with a loaded magazine and after being dropped from 1.3 meters, the LED weapon light, whether still affixed or detached from the pistol after the drop, must maintain function of:</p> <ul style="list-style-type: none"> a) momentary on; and b) constant on. 	<p>The pistol will then be dropped from a height of 121.9 cm (48 inches) onto a concrete floor in the sequence of six (6) defined orientations. The evaluator will ensure the weapon light maintains function of:</p> <ol style="list-style-type: none"> a. momentary on; and b. constant on. <p>In the event that the weapon light becomes detached from the firearm there will be no deduction provided that the light still maintains function of:</p> <ol style="list-style-type: none"> a. momentary on; and b. constant on. <p>The pistol will then be dropped from a height of 121.9 cm (48 inches) onto a concrete floor in the sequence of six (6) defined orientations. The evaluator will visually inspect the weapon light to ensure the LED weapon light glass does not break, become dislodged, or fall out.</p>
<p>MT 4.10</p> <p>When affixed to the pistol with a loaded magazine and after being dropped from 1.3 meters (4.27 feet), the LED weapon light glass must not break, become dislodged, or fall out.</p>	<p>The pistol will then be dropped from a height of 121.9 cm (48 inches) onto a concrete floor in the sequence of six (6) defined orientations. The evaluator will visually inspect the weapon light to ensure the LED weapon light glass does not break, become dislodged, or fall out.</p>